Common Git Commands

Command	Description
git add .	Adds (stages) all files in the folder so Git can include them in the next commit. Use **git add FILE_NAME** to add a specific file.
Git branch	Checks what branch you are currently on. • To create a new branch, use **git branch <NEW_BRANCH_NAME>**, replacing <NEW_BRANCH_NAME> with the name of the branch you want to create
git checkout	Returns you to the latest version (the main branch). • To view a specific log, use **git checkout <COMMIT_ID>** and replace <COMMIT_ID> with the first 7 numbers/letters from the git log commands. • To leave your old commit and get back to your current files, use **git checkout master** • To switch between branches, use **git checkout <BRANCH_NAME),** where <BRANCH_NAME> is the name of the branch you want to switch to • To create a new branch and switch to it in one step, use **git checkout -b <BRANCH_NAME>** where <BRANCH_NAME> is the name you want for your new branch
git commit -m "<ADD A MESSAGE HERE>"	Saves a snapshot of your staged files with a short description of your changes.
git config	Enables you to tell git who you are (**git config--global user.name "<YOUR NAME>")** and your email address (**git config --global user.email "<YOUR EMAIL**>". You can verify your settings using **git config --list.**
git init	Starts (initializes) a new Git repository in the current folder.
git log	Shows a list of all commits, including the author, date, and message.
git log --oneline	Shows the same commit history but in a shorter, one-line format.
git stash	Temporarily saves your uncommitted changes and returns your files to the last saved version.
git stash pop	Restores your stashed change. It takes the last thing that was put in the stash and "pops" it back out so you can use it again.
git status	Shows which files are being tracked and whether any changes have been made.
git version	Tells you the version of Git that you have installed. If git is not installed, you will get an error.

Other Helpful Commands When Working With Git:

- Show hidden files
    - Command Line: **dir /a**
    - Mac Terminal: **ls -a**
    - Windows PowerShell**: ls -Force**
- Edit a file:
    - **Nano [filename.extension]**