



CS544 EA

# Applications

## Spring Security

# Spring Security

- Security, establishing who a user is (authentication), and allowing or disallowing actions (authorization) are vital to any serious application.
- In this Spring Security Module we will look at:
  - Authentication in a web environment
  - Requiring Authorization for certain web pages
  - Requiring Authorization for method calls
  - Defending against common attacks

# Basic Example

- We'll create a basic example to show the essentials of Spring Security
  - Configured with Java Config
  - Configured with XML
- Then we'll go into the details of the different parts

# WebAppInitializer

```
public class MyWebAppInitializer implements WebApplicationInitializer {  
  
    @Override  
    public void onStartUp(ServletContext container) throws ServletException {  
        // Create the 'root' Spring application context  
        AnnotationConfigWebApplicationContext rootContext  
            = new AnnotationConfigWebApplicationContext();  
        rootContext.register(WebConfig.class, SecurityConfig.class);  
        container.addListener(new ContextLoaderListener(rootContext));  
  
        // Create the dispatcher servlet  
        ServletRegistration.Dynamic appServlet = container.addServlet("mvc",  
            new DispatcherServlet(new GenericWebApplicationContext()));  
        appServlet.setLoadOnStartup(1);  
        appServlet.addMapping("/");  
  
        container.addFilter("springSecurityFilterChain",  
            new DelegatingFilterProxy("springSecurityFilterChain"))  
            .addMappingForUrlPatterns(null, false, "/*");  
    }  
}
```

Load both WebConfig and SecurityConfig

Apply Security Filter to all incoming requests

# WebConfig

Normal SpringMVC WebConfig

```
@Configuration
@EnableWebMvc
@ComponentScan("cs544")
public class WebConfig implements WebMvcConfigurer{
    @Bean
    public ViewResolver viewResolver() {
        InternalResourceViewResolver bean = new InternalResourceViewResolver();

        bean.setViewClass(JstlView.class);
        bean.setPrefix("/WEB-INF/view/");
        bean.setSuffix(".jsp");

        return bean;
    }
}
```

You can think of the `.and()` as the closing of an XML tag it takes you back to the root

# SecurityConfig

`@EnableWebSecurity` and  
Extends `WebSecurityConfigurerAdapter`

Showing  
2 of 3  
configure  
methods  
that can be  
overridden

```
@Configuration
@EnableWebSecurity
public class SecurityConfig extends WebSecurityConfigurerAdapter {
    @Override
    protected void configure(AuthenticationManagerBuilder auth) throws Exception {
        auth.inMemoryAuthentication()
            .withUser("admin").password("{noop}123").roles("USER", "ADMIN").and()
            .withUser("user").password("{noop}bla").roles("USER");
    }

    @Override
    protected void configure(HttpSecurity http) throws Exception {
        http
            .authorizeRequests().antMatchers("/important/**").hasRole("USER").and()
            .formLogin().and()
            .logout();
    }
}
```

Creates an inMemory use details  
without encoded passwords  
(just for demo, not good for production!)


People can login with a form  
and logout

Make sure anyone wanting to access  
anything under important  
has the USER role

# Generated login.jsp

You can also write your own

- Spring Security generates a form-login
  - When not logged in and try to access /important/\*\*



```

<?xml version="1.0" encoding="UTF-8"?>
<web-app xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns="http://java.sun.com/xml/ns/javaee"
  xmlns:web="http://java.sun.com/xml/ns/javaee/web-app_3_0.xsd"
  xsi:schemaLocation="http://java.sun.com/xml/ns/javaee http://java.sun.com/xml/ns/javaee/web-app_3_0.xsd"
  id="WebApp_ID" version="3.0">
  <display-name>security</display-name>
  <servlet>
    <servlet-name>SpringMVC</servlet-name>
    <servlet-class>org.springframework.web.servlet.DispatcherServlet</servlet-class>
    <load-on-startup>1</load-on-startup>
  </servlet>
  <servlet-mapping>
    <servlet-name>SpringMVC</servlet-name>
    <url-pattern>/</url-pattern>
  </servlet-mapping>

  <!-- Needed when using Spring with Filter -->
  <context-param>
    <param-name>contextConfigLocation</param-name>
    <param-value>/WEB-INF/springconfig.xml</param-value>
  </context-param>
  <listener>
    <listener-class>org.springframework.web.context.ContextLoaderListener</listener-class>
  </listener>
  <filter>
    <filter-name>springSecurityFilterChain</filter-name>
    <filter-class>org.springframework.web.filter.DelegatingFilterProxy</filter-class>
  </filter>
  <filter-mapping>
    <filter-name>springSecurityFilterChain</filter-name>
    <url-pattern>/*</url-pattern>
  </filter-mapping>
</web-app>

```

Or you can use a web.xml instead of the  
Initializer class

Automatically loads SpringMVC-servlet.xml

# Web.xml

Loads springconfig.xml as root config

Filter applies security



# SpringMVC-servlet.xml

Normal SpringMVC Config

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:context="http://www.springframework.org/schema/context"
xmlns:mvc="http://www.springframework.org/schema/mvc"
xsi:schemaLocation="http://www.springframework.org/schema/beans
    http://www.springframework.org/schema/beans/spring-beans.xsd
    http://www.springframework.org/schema/context
    http://www.springframework.org/schema/context/spring-context.xsd
    http://www.springframework.org/schema/mvc
    http://www.springframework.org/schema/mvc/spring-mvc.xsd">

    <!-- scan for @RequestMapping annotations-->
    <mvc:annotation-driven />

    <!-- scan for @Controller (and other component) annotations in the following package -->
    <context:component-scan base-package="springmvc.helloworld" />

    <!-- Resolves views to .jsp resources in the /WEB-INF/views directory -->
    <bean class="org.springframework.web.servlet.view.InternalResourceViewResolver">
        <property name="viewClass" value="org.springframework.web.servlet.view.JstlView" />
        <property name="prefix" value="/WEB-INF/views/" />
        <property name="suffix" value=".jsp" />
    </bean>

</beans>
```

# Springconfig.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
xmlns:sec="http://www.springframework.org/schema/security"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd
http://www.springframework.org/schema/security
http://www.springframework.org/schema/security/spring-security.xsd">
```

Security namespace

```
<sec:http>
  <sec:intercept-url pattern="/important/**" access="ROLE_USER"/>
  <sec:form-login />
  <sec:logout />
</sec:http>
```

http elements specify  
url patterns for security

```
<sec:authentication-manager>
  <sec:authentication-provider>
    <sec:user-service>
      <sec:user name="test" password="{noop}123" authorities="ROLE_USER, ROLE_ADMIN" />
      <sec:user name="bob" password="{noop}bobiscool" authorities="ROLE_USER" />
    </sec:user-service>
  </sec:authentication-provider>
</sec:authentication-manager>
</beans>
```

Authentication manager  
/ provider configuration