



Fuse-link, high speed, 200 A, AC 660 V, 100 kA, DIN 0, aR, DIN, IEC, type T indicator, live gripping lugs



Part no. **FUSE 200A 660V DIN 0 AR**  
Catalog No. **170M7919**

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	200
Rated voltage			AC 660 V
Construction size			DIN 0
Utilization category			aR
Status indicator			type T indicator
Description			live gripping lugs
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			DIN 43620 IEC 60269-4

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (eck@ss10.0.1-27-14-20-05 (AFZ800015))			
Construction size			Other
Rated current		A	200
Rated voltage		V	660
Voltage type			AC
Rated switching capacity		kA	100
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No