



Fuse-link, high speed, 200 A, AC 660 V, 100 kA, DIN 0, aR, DIN, IEC, type T indicator, live gripping lugs

Part no. **FUSE 200A 660V DIN 0 AR**
Catalog No. **170M7919**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	200
Rated voltage			AC 660 V
Construction size			DIN 0
Utilization category			aR
Status indicator			type T indicator
Description			live gripping lugs
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			DIN 43620 IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 (AFZ800015))			
Construction size			Other
Rated current		A	200
Rated voltage		V	660
Voltage type			AC
Rated switching capacity		kA	100
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

High-speed full-line catalogue (pdf)	https://www.eibt.com/product/Datasheet/170M7919.pdf
--------------------------------------	---