

Table of Contents

1. Speech	2
1.1. Repository	2
1.2. How to run?	3
1.3. Explanation	3
1.3.1. Settings	3
1.3.2. Python scripts	4
Say.py	4
Observer.py	4

Welcome

Project Willy

- [History of Willy](#)
- [Project Willy](#)
- [Publicity](#)
- [Sponsors](#)

Getting started

- [Introduction to ROS](#)
- [Development Guide](#)
- [Driving Willy](#)
- [Manual](#)
- [Wiki Manual](#)

Build of Willy

- [Design history](#)
- [Hardware](#)

Architecture

- [Software Architecture](#)
- [ROS topic design](#)

Raspberry Pi's

- [Sensor node](#)
- [Social Interaction node](#)
- [Power node](#)

Components

- [ROS master](#)
- [New ROS master on Ubuntu](#)

- [Sonar](#)
- [Lidar](#)
- [Kinect](#)
- [Localization and navigation](#)
- [Motor controller](#)
- [Joystick](#)

Lessons learned

- [Todo & Advice](#)
- [Lessons Learned](#)

Archive

- [Previous Groups](#)
- [Research Archive](#)
- [Skylab Architecture](#)
- [Skylab](#)
- [Multi master](#)
- [WillyWRT](#)
- [Realisation](#)
- [Hardware](#)
- [Brain](#)
- [Design Guild](#)
- [Social interaction](#)
- [Speech](#)
- [Speech recognition](#)
- [IMU](#)
- [Human Detection](#)
- [Radeffect App](#)

1. Speech

The Speech topic describes the ability of Willy to audibly communicate with human beings. It is part of the social interaction, but due to the necessity of the various components it seemed best to describe it as a separate topic in this Wiki.

1.1. Repository

1.2. How to run?

```
./START start
```

1.3. Explanation

Upon first run the installation script will install the necessary packages. After this, when the Raspberry pi is booting, it will automatically start the start script. This script will check if all prerequisites are met and will start the start_speech.sh script

The start_speech.sh script exists because it is the most convenient way to launch the python scripts. In total two python scripts will be launched, with settings read from the settings.xml file.

1.3.1. Settings

The settings.xml file contains the various settings to be used by the Say and Observer scripts.

```
<data>
  <settings>
    <setting name="volume">0.99</setting>
    <setting name="folder">/opt/willy/components/speech/drop/</setting>
    <setting name="filename">SpeakOut.mp3</setting>
    <setting name="sleep">2</setting>
  </settings>
</data>
```

- volume
 - This settings contains the value for the output volume and is stored as a float.
- folder
 - This settings contains the value for the folder location in which the .mp3 file is being stored and subsequently being read. Note the trailing slash!
- filename
 - This setting contains the value for the filename of the .mp3.
- sleep
 - This settings contains the value for the delay of the Say script after it has been launched.

1.3.2. Python scripts

- * Say.py
- * Observer.py

Say.py

This script is the ROS topic on which the text to be spoken is placed. The text is accepted as a string and forwarded to Google for processing. The returned mp3 file is saved in the drop folder for further processing.

Observer.py

This script is, as the name indicates, the observer of the drop folder. Upon start it will delete all files from the drop folder. After that it will pick up each .mp3 file as it is placed and play it accordingly. The volume can be set in the settings.xml file as mentioned earlier. After the file has been played it will be deleted from the folder.