

k-Anonymity Library Demo with k=3

```
In [130... import warnings
warnings.filterwarnings('ignore')
```

```
In [131... import kAnonymityLib as daio_dpt
import pandas as pd
dai_anonymization = daio_dpt.kAnonymity()
print(dai_anonymization)
```

k-Anonymity Class Library with k=3

```
In [132... names = ['age',
           'workclass',
           'fnlwgt',
           'education',
           'education-num',
           'marital-status',
           'occupation',
           'relationship',
           'race',
           'sex',
           'capital-gain',
           'capital-loss',
           'hours-per-week',
           'native-country',
           'income']
dai_anonymization.set_headers(names)
```

```
In [133... dai_anonymization.read_datafile("adult-all.txt")
```

```
In [134... df = dai_anonymization.dataframe
print(f"population size = {df.age.size}")
```

population size = 48842

```
In [135... age_range = lambda age: ("<= 20" if age <= 20
                             else ("21 - 30" if age <= 30
                                    else ("31 - 40" if age <= 40
                                           else ("41 - 50" if age <= 50
                                                else ("51 - 60" if age <= 60
                                                     else ("61 - 70" if age <= 70 else "> 70"))))))))
```

```
In [136... df["age"] = df.apply(lambda x: age_range(x.age), axis=1)
df["workclass"] = df.apply(lambda x: x.workclass.replace(" ", ""), axis=1)
df["workclass"] = df.apply(lambda x: "Others" if x.workclass=="?" else x.workclass, axis=1)
df["race"] = df.apply(lambda x: x.race.replace(" ", ""), axis=1)
df["education"] = df.apply(lambda x: x.education.replace(" ", ""), axis=1)
```

```
In [137... categorical = ['workclass',
                  'education',
                  'marital-status',
                  'occupation',
                  'relationship',
                  'race',
```

```
'sex',
'native-country',
'income',
'age']
```

```
In [138... feature_columns = ['race', 'sex', 'age']
```

```
In [139... dai_anonymization.set_categorical(categorical)
```

```
In [140... dai_anonymization.set_feature_columns(feature_columns)
```

```
In [141... dai_anonymization.set_sensitive_column("income")
```

```
In [142... dd = pd.Series({c: df[c].unique() for c in df})
print(dd)
```

```
age          ['31 - 40', '41 - 50', '51 - 60', '21 - 30', '...
workclass    ['State-gov', 'Self-emp-not-inc', 'Private', '...
fnlwtg      [77516, 83311, 215646, 234721, 338409, 284582,...
education    ['Bachelors', 'HS-grad', '11th', 'Masters', '9...
education-num [13, 9, 7, 14, 5, 10, 12, 11, 4, 16, 15, 3, 6,...
marital-status [' Never-married', ' Married-civ-spouse', ' Di...
occupation   [' Adm-clerical', ' Exec-managerial', ' Handle...
relationship  [' Not-in-family', ' Husband', ' Wife', ' Own-...
race          ['White', 'Black', 'Asian-Pac-Islander', 'Amer...
sex           [' Male', ' Female']
Categories (2, object): [...
capital-gain  [2174, 0, 14084, 5178, 5013, 2407, 14344, 1502...
capital-loss  [0, 2042, 1408, 1902, 1573, 1887, 1719, 1762, ...
hours-per-week [40, 13, 16, 45, 50, 80, 30, 35, 60, 20, 52, 4...
native-country [' United-States', ' Cuba', ' Jamaica', ' Indi...
income        [' <=50k', ' >50k']
Categories (2, object): ['...
dtype: object
```

```
In [143... dai_anonymization.partition_dataset()
print( len(dai_anonymization.finished_partitions) )
```

67

```
In [144... dai_anonymization.build_anonymized_dataset()
```


```
In [145... df1 = dai_anonymization.result_df
print(f"total records = {df1.age.size}")
```

total records = 48780

df1.to_csv("result.csv")

```
In [146... df1.groupby("age").size().plot.bar()
print(df1.groupby("age").size())
```

```
age
21 - 30    12170
31 - 40    12838
41 - 50    10363
51 - 60     6201
61 - 70     2726
<= 20       3619
> 70         863
dtype: int64
```



```
In [147...] df2 = dai_anonymization.removed_df
```

```
In [148...] df2.groupby(feature_columns).size()
```

```
Out[148]:
```

race	sex	age	
Amer-Indian-Eskimo	Female	51 - 60	1
		61 - 70	4
		> 70	1
	Male	61 - 70	2
Asian-Pac-Islander	Female	> 70	1
	Male	> 70	1
Black	Female	61 - 70	2
	Male	<= 20	1
Other	Female	41 - 50	2
		61 - 70	2
		> 70	1
	Male	41 - 50	38
		61 - 70	2
		> 70	1
White	Female	<= 20	2
	Male	<= 20	1

dtype: int64

```
In [155... df2_cols = ['age',
'workclass',
'education',
'marital-status',
'occupation',
'relationship',
'race',
'sex',
'native-country',
'income']

d3 = df2.groupby(feature_columns)
group_list = list(d3.groups.keys())
records = []
for x in [ x for x in group_list if d3.get_group(x).age.count() > 2]:
    y=d3.get_group(x)
    z=y.to_dict()
    dd = {}
    for w in list(z['workclass']):
        for v in df2_cols:
            dd[v]=z[v][w]
    records.append(dd)
df3 = pd.DataFrame(records)
df3.groupby(feature_columns).size()
```

```
Out[155]:
```

race	sex	age	
Amer-Indian-Eskimo	Female	61 - 70	4
Other	Male	41 - 50	38

dtype: int64

```
In [156... df3.head()
```

	age	workclass	education	marital-status	occupation	relationship	race	sex	native-country	income
0	61-70	State-gov	HS-grad	Widowed	Adm-clerical	Unmarried	Amer-Indian-Eskimo	Female	United-States	<=50k
1	61-70	State-gov	HS-grad	Widowed	Adm-clerical	Unmarried	Amer-Indian-Eskimo	Female	United-States	<=50k
2	61-70	State-gov	HS-grad	Widowed	Adm-clerical	Unmarried	Amer-Indian-Eskimo	Female	United-States	<=50k
3	61-70	State-gov	HS-grad	Widowed	Adm-clerical	Unmarried	Amer-Indian-Eskimo	Female	United-States	<=50k
4	41-50	Private	7th-8th	Never-married	Transport-moving	Not-in-family	Other	Male	Puerto-Rico	<=50k

Conclusion : Partitioning will lost some true data

```
In [157... dai_anonymization.finished_partitions = []
```

```
In [158... dai_anonymization.build_anonymized_dataset()
```

```
In [159... df1 = dai_anonymization.result_df
print(f"total records = {df1.age.size}")

total records = 48822
```

```
In [160... df2 = dai_anonymization.removed_df
print(f"removed records = {df2.age.size}")

removed records = 20
```

```
In [161... df2.groupby(feature_columns).size()
```

```
Out[161]:
```

race	sex	age	
Amer-Indian-Eskimo	Female	51 - 60	1
		> 70	1
	Male	61 - 70	2
	Female	> 70	1
Asian-Pac-Islander	Male	> 70	1
	Female	61 - 70	2
Black	Male	<= 20	1
	Female	41 - 50	2
Other		61 - 70	2
		> 70	1
	Male	61 - 70	2
		> 70	1
White	Female	<= 20	2
	Male	<= 20	1

dtype: int64

```
In [162... d3 = df2.groupby(feature_columns)
group_list = list(d3.groups.keys())
[ x for x in group_list if d3.get_group(x).age.count() > 2]
```

```
Out[162]: []
```

Conclusion : Anonymization works better without partitioning but runs slower

```
In [ ]:
```