# CS120: Computer Networks

Lecture 3. Physical Layer

Zhice Yang

Network Layers

Outline

➢ Communication Basics
- Communication Medium
  - Carrier
- Modulation

- Upper Bound of Throughput

- Transmission Method

How to Transmit a Bit in Physical World ?

- Bits in the physical world

```
a = 1 & 0;
```


Bits are conveyed in physical medium (e.g., electrical signals)

How to Transmit a Bit in Physical World ?

- Problems of directly conveying bits in cables
 - Distance, distortion, mobility, etc.

Cable

?

How to Transmit a Bit in Physical World ?

Electrical Signals

Light

Fiber:
Light

Free Space:
Radio, Acoustic
Wave, etc.

Sound

Physical Medium

6

Carrier Wave – the wave carrying information

1000Hz

Bits

Modulate

Carrier Wave
10^{14}Hz

Radio Spectrum:

f(Hz) 10^0	10^2	10^4	10^6	10^8	10^{10}	10^{12}	10^{14}	10^{16}	10^{18}	10^{20}	10^{22}	10^{24}
			Radio	Microwave		Infrared		UV	X-ray			Gamma ray

10^4 10^5 10^6 10^7 10^8 10^9 10^{10} 10^{11} 10^{12} 10^{13} 10^{14} 10^{15} 10^{16}

Satellite

Fiber optics

Coax

AM

FM

Terrestrial microwave

TV

8

Modulation

- Modulation: the process of varying one or more properties of the carrier wave to transmit the information
  - The signal containing information is called the modulated signal
- Example: On-Off Modulation

Modulated Light

| 1 | 0 | 0 | 1 | 1 | 0 | 1 | 0 |

Time

Demo: On-off Modulation

```
%%
clear all;
t=linspace(0,1,44100);
one=sin(2*pi*1000*t);
zero=zeros(1,length(one));
transmit=([one,zero,zero,one,one,zero,one,zero]);
figure;
plot(transmit);
sound(transmit,44100);
```

How Fast can We Achieve ?

1bps

2bps

Outline

- Communication Basics
  - Communication Medium
    - Carrier
  - Modulation
- ➤ Throughput Upper Bound
- Transmission Method

Shannon-Hartley Theorem

- The theoretical throughput upper bound:

Bandwidth

Signal Power

$$C = B\log_2(1 + \frac{S}{N})$$

Channel Capacity

Noise Power

"Bandwidth" v.s. Bandwidth

- The term "bandwidth" is often used with two different meanings.
  - Rate: throughput (bps)
  - Spectrum: the width of the occupied spectrum (Hz)

"Bandwidth" v.s. Bandwidth

Connection

IPv4 Connectivity:	Internet
IPv6 Connectivity:	No network access
Media State:	Enabled
SSID:	SHTULAN
Duration:	08:08:33
Speed:	54.0 Mbps
Signal Quality:	

This is the rate bandwidth
The spectrum bandwidth is 20MHz !

Details...   Wireless Properties

Activity

Sent ——   —— Received

Bytes:	93,569,624		357,957,602

Properties   Disable   Diagnose

How Fast can We Achieve ?

Limited by ADC DAC rate,
Available Spectrum

Limited by Power and
Safety Concerns

Bandwidth

Signal Power

$$C = B\log_2\left(1 + \frac{S}{N}\right)$$

Channel Capacity

Noise Power

Limited by Thermal Noise
and Manufacturing

16

Outline

- Communication Basics
  - Communication Medium
    - Carrier
  - Modulation

- Upper Bound of Throughput

➢ Transmission Methods
  - Baseband Transmission
 - Passband Modulation

Transmission Methods

- Baseband Transmission (Line Coding)
  - No carrier wave, transmit bits or coded stream directly to the medium, might not be long-distance, e.g., usb, Ethernet, HDMI, etc.

- Passband Modulation
  - Good transmission properties (suitable medium, distance, etc.)
  - Multiplexing

Baseband Transmission

- "1" -> High Voltage
- "0" -> Low Voltage

```
        1   0   0   1   1   0   1   0
                ___         _____     ___
Transmitted    |   |       |       |   |   |
Signal:     ___|   |_____|       |___|   |___
```

Baseband Transmission

- The communication signal is not necessarily changed in binary pattern, e.g.,:
  - "00" -> 2v
  - "01" -> 1v
  - NONE -> 0v
  - "10" -> -1v
  - "11" -> -2v

1   0   0   1   1   1   1   0

Symbol   -1   1   -2   -1

Signal:

- Symbol Rate := Baud Rate
  - The number of symbols per unit time

Symbol Rate

- Unit: baud (Bd), i.e., symbols per second
- Convert to bit rate
  - M: the number of different symbols
 - R_B: Baud Rate
  - R_b: Bit Rate

$$R_b = R_B \log_2 M$$

- Can we increase number of different symbols to increase Bandwidth ?
  - Signal/noise ratio is lower

Baseband Transmission

- How to Receive ?

Imperfect Square Wave
Reasons:
1. Hardware Imperfectness
2. EMR Filter

Baseband Transmission

- Problems at Receiver
  - Determine sampling time

× √

Avoid Long-duration Constant Signal

1 0 0 0 0 0 1 0

Transmitted Signal:

Baseband Transmission

- Clock Recovery
  - Synchronous Transmission
    - Transmit the clock directly through (additional line, frequency band, etc.)
    - low processing (decoding or encoding) overhead but low efficiency
  - Asynchronous Transmission

Baseband Transmission

- Clock Recovery
  - Option 1: Synchronous Transmission
    - e.g., Manchester Code (Ethernet 10BaseT)

Original signal: Low frequency

Coded signal: frequency is two 2 times of the original signal. Efficiency: 50%

26

Baseband Transmission

- Clock Recovery
  - Synchronous Transmission
    - Transmit the clock directly through (additional line, frequency band, etc.)
    - low processing (decoding or encoding) overhead but low efficiency
  - Asynchronous Transmission
    - Recover the clock from data signal
    - Use line encoder/decoder, high efficiency
    - Design
      - Goal: should avoid constant 0s or 1s
      - Reason: the hardware needs "changes" to track the clock

Baseband Transmission

- Clock Recovery
  - Option 2: Asynchronous Transmission
    - e.g., 4B5B Code (Ethernet 100BASE-TX)
    - Map 4-bit data to 5-bit code
      - To ensure there is no >=4 consecutive 0s in the coded data
        - No guarantee for 1s.
      - Efficiency: 80% (much higher than Manchester code)

Table 2.2 4B/5B Encoding

4-Bit Data Symbol	5-Bit Code
0000	11110
0001	01001
0010	10100
0011	10101
0100	01010
0101	01011
0110	01110
0111	01111
1000	10010
1001	10011
1010	10110
1011	10111
1100	11010
1101	11011
1110	11100
1111	11101

Baseband Transmission

- Clock Recovery
  - Option 2: Asynchronous Transmission
    - e.g., 4B5B Code (Ethernet 100BASE-TX)+NRZI
  - NRZI takes transitions at bit 1
   - Use to break consecutive 1s.

Table 2.2 4B/5B Encoding	
4-Bit Data Symbol	5-Bit Code
0000	11110
0001	01001
0010	10100
0011	10101
0100	01010
0101	01011
0110	01110
0111	01111
1000	10010
1001	10011
1010	10110
1011	10111
1100	11010
1101	11011
1110	11100
1111	11101

29

Transmission Method

- Baseband Transmission (Line Coding)
- Passband Modulation
  - Good transmission property
  - Multiplexing

Spectrum of Mechanical Wave, Sound Wave, etc.

Demo: Baseband and Passband Signal

```matlab
clear all;
fs=44100;
t=linspace(0,1,44100);
one=ones(1,length(t));% no carrier wave
zero=zeros(1,length(one));
transmit_05Hz_baseband=([one,zero,zero,one,one,zero,one,zero]); % 1bps 0.5Hz
fs_unit=fs*(0:length(transmit_05Hz_baseband)-1)/length(transmit_05Hz_baseband);
figure;
plot(fs_unit, abs(fft(transmit_05Hz_baseband))); % spectrum
figure;
plot(transmit_05Hz_baseband)
```

Baseband signal is used to modulate a carrier signal to get a passband signal

```matlab
clear all;
fs=44100;
t=linspace(0,1,44100);
one=sin(2*pi*1000*t);% carrier wave
zero=zeros(1,length(one));
transmit_05Hz_passband=([one,zero,zero,one,one,zero,one,zero]); % 1bps 0.5Hz
fs_unit=fs*(0:length(transmit_05Hz_passband)-1)/length(transmit_05Hz_passband);
figure;
plot(fs_unit, abs(fft(transmit_05Hz_passband))); % spectrum
```

31

How to Describe the Carrier ?

- Carrier is a Wave, has attributes:
  - Amplitude
  - Frequency
  - Phase

$$A \cdot \sin(2\pi f t + \phi)$$

Passband Modulation

- On-off Keying (OOK)
  - Switching the working state (on or off) of the carrier wave to express symbols
  - A special case of modifying the amplitude of the carrier.

- Demodulation
  - Averaging the received power (low pass filter)
  - Thresholding

Demo: OOK Modulation

```matlab
clear all;
t=linspace(0,1,44100);
one=sin(2*pi*10*t);
zero=zeros(1,length(one));
transmit=([one,zero,zero,one,one,zero,one,zero]);

receive=transmit;
receive_power=receive.^2;
receive_power_smooth=smooth(receive_power,44100);
sampling_point=(44100/2:44100:length(receive));
figure;
plot(receive_power_smooth);
hold on;
for i=1:length(sampling_point)
    plot([sampling_point(i),sampling_point(i)],[0.3,0.7], 'r');
end
hold off;

samples=receive_power_smooth(sampling_point);
bits=samples>mean(receive_power);
```

Passband Modulation

- Amplitude Shift Keying (ASK)
  - Switching in amplitude of the carrier wave to express symbols
  - Example:

"0"

"1"

- Demodulation
  - Non-coherent
    - Find the envelop (low pass filtering)
    - Thresholding
  - Coherent
    - Dot product with the carrier wave
    - $\text{Acos}(2\pi f t) \cdot \textcolor{red}{\cos(2\pi f t)} = \frac{1}{2}\text{A}(\cos(2\pi 2 f t) + 1)$
    - Low pass filtering
    - Thresholding

35

```
%% ASK demo
clear all;
t=linspace(0,1,44100);
one=sin(2*pi*10*t);
zero=0.5*sin(2*pi*10*t);
transmit=([one,zero,zero,one,one,zero,one,zero]);

receive=transmit;
receive_shift=receive.*[one,one,one,one,one,one,one,one];
figure;
plot(smooth(receive_shift,44100))
```

Passband Modulation

- Frequency Shift Keying (FSK)
  - Switching the frequency of the carrier wave to express symbols
  - Example:

"0"   "1"

- Demodulation
  - Similar as ASK

```
%% FSK demo
clear all;
t=linspace(0,1,44100);
one=sin(2*pi*10*t);
zero=cos(2*pi*20*t);
transmit=([one,zero,zero,one,one,zero,one,zero]);

receive=transmit;
receive_shift=receive.*[one,one,one,one,one,one,one,one];
figure;
plot(receive_shift)
figure;
plot(smooth(receive_shift,44100))
```

Passband Modulation

- Phase Shift Keying (PSK)
  - Switching the phase of the carrier wave to express symbols
 - Example:

"0"   "1"

- Demodulation
  - Coherent
    - Dot product with the carrier wave
      - $\cos{(2\pi ft)} \cdot \cos{(2\pi ft)} = \frac{1}{2}(\cos{(2\pi 2ft)} + 1)$
      - $\cos{(2\pi ft + \pi)} \cdot \cos{(2\pi ft)} = \frac{1}{2}(\cos{(2\pi 2ft)} - 1)$
    - Low pass filtering
    - Thresholding

```matlab
%% PSK demo
clear all;
t=linspace(0,1,44100);
one=sin(2*pi*10*t);
zero=cos(2*pi*10*t);
transmit=([one,zero,zero,one,one,zero,one,zero]);

receive=transmit;
receive_shift=receive.*[one,one,one,one,one,one,one,one];
figure;
plot(smooth(receive_shift,44100))
```

Passband Modulation

- Quadrature Amplitude Modulation (QAM)
  - ASK + PSK
  - Example:

"00"

"11"

"01"

"10"

Spectrum Shifting

- How to conveniently modulate the carrier ?
  - Generate the baseband digitally, and convert it to the passband through multiplying with the carrier wave.

Mathematically, passband signal is frequency-shifted from the baseband signal

By Now

- Bit stream can either be converted to analog signal via line coding or through modulating the carrier.

Bit Steam

$\cdot \cos{(2\pi f t)}$

Baseband

Modulation

Physical Medium

Reference

- Textbook 2.2

Other Implementation Issues

# Carrier Phase Misalignment

- The Problem

Received Signal:

Transmitter Carrier Wave:

Local Carrier Wave:

Carrier Phase does not Match
Big Problem for PSK !

Carrier Phase Misalignment

- Solution
  - Option1: find the accurate start of the received signal
    - to align the local carrier phase to the transmitter's carrier phase
  - Option2: use orthogonal carrier waves to find and align the phase shift
    - Transmitter Carrier Wave: $\cos{(2\pi ft + \phi)}$
    - Local Carrier Wave 1: $\cos{(2\pi ft)}$
    - Local Carrier Wave 2: $\cos{\left(2\pi ft + \frac{\pi}{2}\right)}$

$$\cos{(2\pi ft + \phi)} = A \cdot \cos{(2\pi ft)} + B \cdot \cos{\left(2\pi ft + \frac{\pi}{2}\right)}$$

Carrier Frequency Offset

- There is a frequency offset between two nodes

    - $\cos{(2\pi ft)} * \cos{(2\pi ft + 2\pi\Delta ft)} = \frac{1}{2}(\cos{(2\pi 2ft + 2\pi\Delta ft)} + \cos{(2\pi\Delta ft)})$

- Solution

    - Calibration
    - Do not use long frame in PSK