Load Safety Gate

One photo at the gate. GO or NO-GO before the truck leaves.

Mode: Startup · Track: Computer Vision · Team Destroyerrrrs

GO WARN NO-GO

Body roll · Overhang · Height · Plates and people blurred before anything is shown

A badly loaded truck is checked by eye, or not at all

Who uses it

The gate operator or dispatcher at a freight terminal, a fleet depot, or a dealer receiving yard. One photo, one answer, before the truck leaves.

What goes wrong today


Shifted or one-sided loads roll over. Overhanging cargo hits bridges, signs and other vehicles. Oversized loads draw fines and stop the truck at the first police post.

Who pays

The fleet owner or terminal, per gate. Partner angle: every Toyota and BYD arrives on a car carrier into a Royal Motors yard. Car carriers are the classic over-height and rear-overhang offenders.

Regulation already exists

Uzbekistan Decree 342, Annex 2: height 4.0 m, width 2.55 m, rear protrusion 2 m. Nobody measures it at the gate.



Live output of the deployed pipeline on a licensed test image (Wikimedia Commons, CC BY-SA 4.0).

Live demo

amir-kuldashev--load-safety-gate-web.modal.run

Open it on your phone. Take a photo of any truck, or give us one. No login, no app.

- Plates and people are pixelated first. The original is never stored.
- Green lines: body vertical edges and the ground line the roll is measured against.
- Red line: cargo beyond the body edge, in centimetres. Magenta: cargo top to ground, in metres.
- Verdict banner, per-check confidence, and the measured latency on CPU.
- When the photo does not allow a measurement the check says so. No guess, ever.



A pipeline, not a prompt

1

Photo

phone or gate camera

2

Detect

YOLO-World boxes: truck, trailer, cargo, car, plate, person. YOLOv8-seg truck mask. Pretrained, no training.

3

Blur

plates and people pixelated before storage or display

4

Measure

wheel finder, ground line, body verticals vs scene verticals, scale from 2.55 m body or 1.05 m wheel

5

Decide

Decree 342 thresholds; GO, WARN, NO-GO, or CANNOT ASSESS

6

Report

annotated image, checklist, confidence, latency

Ours

Privacy stage, wheel finder, geometry, decision rules, the 301-image licensed set, the 120-image labelled evaluation, the app and the deployment.

Borrowed, with attribution

Two pretrained Ultralytics models (AGPL-3.0). Open-vocabulary prompts, no fine-tuning needed for the demo. Runs on CPU in 0.19 s per image.

Measured relative to the truck itself, so a phone photo is honest

Body roll

Horizontal edges converge under perspective, so a level truck looks tilted if you compare top and bottom edges. We use the body's vertical edges instead: left and right halves converge in opposite directions and their mean cancels perspective. Reference: vertical lines in the scene (poles, walls), else the camera vertical at lower confidence.

Overhang

Cargo extent beyond the body edge at cargo height. Rear overhang in a side view, side overhang in a rear view. Converted to centimetres with a known object in the same image: body width 2.55 m or wheel diameter 1.05 m.

Height

Ground line through the tyre contact points to the top of cargo or body, same scale. Compared with the 4.0 m legal limit.

Product version

A fixed gate camera with known position and a reference marker removes the remaining ambiguity. The phone mode you see today is the degraded fallback, and it says CANNOT ASSESS when the view does not support a measurement.

Measured on a test set we built

Subset	Images	Truck found	Wheels	Scale	Roll reported
Car carriers	70	0.89	0.60	0.71	0.21
Flatbeds	55	0.87	0.71	0.76	0.27
Semi-trailers	30	0.97	0.70	0.83	0.37
Oversized loads	44	0.86	0.50	0.59	0.11
Night	38	0.97	0.66	0.74	0.45

Detector hit rate on 301 licensed Commons photos (no labels needed). Night holds up: the truck mask is the most robust stage.

Check	Precision	Recall	n
Tilted body	pending	pending	
Rear overhang	pending	pending	
Side overhang	pending	pending	
Over height	pending	pending	
Night / rain subset	pending	pending	25

Against 120 hand-labelled images (95 day, 25 night). Numbers come from eval/run_eval.py and are filled in once labelling is complete.

0.19 s

per image on 2 CPU cores, measured on the deployed server

< $0.001

compute per inspection; one warm server about $90 per month


0 faces

stored. Plates and people pixelated before anything is kept


Where it breaks, and what it does instead of guessing



Not a truck, or a tiny truck in the frame. Result: CANNOT ASSESS. The overloaded-vehicles category on Commons is mostly carts and motorbikes.



Front or three-quarter views foreshorten the body. Roll confidence drops below the floor and the check is skipped.



Night street with no truck in frame: CANNOT ASSESS. Dark trucks at night give a noisy mask edge and lower roll confidence; cargo the same colour as the body can merge into the mask.

Design rule

Every check reports a confidence and is skipped below a floor. A skipped check is shown as such, never as a pass.

The replication test

A weekend with the same tools gets you

- A detector that draws boxes around trucks and cargo
- A prompt to a vision model that says "looks overloaded"
- No measurement, no threshold, no number a gate operator can act on

What they do not get

- Perspective-safe roll from vertical edges, with a gravity reference in the same image
- Centimetres and metres from a known object in the frame, and a CANNOT ASSESS path
- A decision layer written from Decree 342, the regulation a police post actually applies
- A privacy stage that makes the product legal to pilot
- 301 licensed images with hit rates, 120 labelled, and a deployed gate product

Pilot budget and payback, every assumption on the slide

Pilot cost, 3 months	Amount	Assumption
Team: 2 engineers + 1 ops, part time	[confirm]	local salaries, 3 months
Cameras and mounts, 3 gates	$600	$200 per gate, one-off
Hosting	$270	one warm CPU server, $90 per month
Labelling and data	$500	about 40 hours of labelling
Legal and privacy review	[confirm]	blur at ingest, no personal data stored

Avoided loss per year, one fleet	Amount	Assumption
Rollovers prevented	[confirm]	cost of one rollover x events avoided
Oversize fines avoided	[confirm]	fine x stops per month
Cargo damage claims	[confirm]	claims per year x share caught at gate
Operator time	[confirm]	minutes per manual walkaround x trucks per day

Unit economics

Price per gate per month, software only. Compute per inspection is below $0.001, so margin is in the subscription, not the inference. One server serves dozens of gates.

Payback

Payback months = pilot cost / (avoided loss per month). Fill the [confirm] cells with the fleet's own figures and the formula gives the answer on the spot.

Next steps

Month 1

Fixed, calibrated camera at one gate. Reference marker removes scale ambiguity. Ten-second video mode.

Month 2

Fine-tune the detector on our labelled set. Add open door, loose strap and missing marking classes.

Month 3

Weighbridge and dispatch integration. Pilot at a Royal Motors receiving yard on incoming car carriers.

Repository: github.com/Winner-121/Destroyerrrrs_Final_Stage · Demo: amir-kuldashev--load-safety-gate-web.modal.run