A Practical Hybrid Robust VAE-CatBoost Framework for Efficient Multiclass Network Intrusion Detection

Vihaan Ovalekar(✉), Ojas Gore, Yash Pradhan, Ishan Tanawade, and Deepali Patil

Department of Artificial Intelligence and Data Science, SVKM's Dwarkadas J. Sanghvi College of Engineering, Mumbai, India
vihaan.ovalekar@gmail.com, ojasgore2005@gmail.com, yashpradhan0712@gmail.com, ishanst995@gmail.com

Abstract. Intrusion detectors often report near-perfect scores on random splits yet miss attack families absent from training. We propose a hybrid framework in which a robust variational autoencoder (VAE)—with a Student-t likelihood, missing-entry handling for undefined flow statistics, and a topological loss—feeds a CatBoost classifier and drives two streaming components. Using the VAE's reconstruction error and latent space, a correction relabels bursts of novel flows with the dominant recent attack class, while a detector flags unseen attack families. On CSE-CIC-IDS2018 with a time-ordered hold-out across three seeds, the framework reaches a mean F1 of 0.991 ± 0.004 over the four larger classes, versus 0.979 ± 0.001 for raw-feature CatBoost and 0.975 for the best of ten untuned re-run methods. This gain comes from the correction on the VAE signals, which also lifts raw-feature CatBoost to 0.990. With the detector, trained on attacks from other days, the framework reaches a Youden's J of 30.27 % on left-out days, versus 6.05 % for the best of five re-run methods trained on the same days, and the detector flags 30.86 % of an unseen family's flows, versus 4.81 % on raw features without monotone constraints. The full pipeline takes 0.05 ms per flow on one CPU thread.

Keywords: Intrusion detection · Variational autoencoder · Student-t likelihood · CatBoost · Novelty · Unseen attack families

1 Introduction

Intrusion detection systems (IDS) trained on network flows must handle class imbalance, heavy-tailed flow statistics, and attacks absent from training. Hybrid pipelines combining feature selection, autoencoders, and gradient-boosted trees report recalls near 99 % [1] and accuracies near 98 % [2] on public flow datasets, but these figures can be optimistic: random splits place flows from one attack session into both training and test data, ports let a model learn the attack machines, and accuracy masks small classes [3–6]. Moreover, because a classifier can output only seen classes, its detection can collapse on a new attack family [7, 8].

This paper retains the hybrid design but changes the autoencoder's role. In our framework (Fig. 1), CatBoost with SHAP importance selects the features (Stage 1), a robust variational autoencoder (VAE) encodes them (Stage 2), and a CatBoost classifier predicts the class from the VAE outputs (Stage 3). The VAE outputs also indicate how




Fig. 1. Architecture: Stage 2 encodes the defined features with a product of per-feature experts (PoE; an undefined statistic, dashed, is left out). In Stage 3, the correction relabels bursts of novel flows from the VAE NLL and latent mean z, and the detector checks the remaining Benign flows.

unusual a flow is, while its latent space groups similar flows; Stage 3 uses these signals in a streaming correction and an unseen-attack detector. We call Stages 1–3 without the detector *the framework*, and write *with the detector* when it is added. Our contributions are:

1. A robust VAE design for CICFlowMeter flow features that treats undefined statistics as missing entries rather than zeros, models heavy tails with a Student-t likelihood, and adds a topological loss for latent neighbourhoods; its NLL and latent space feed Stage 3 (Sect. 3).
2. A streaming correction that relabels bursts of novel flows and a monotone CatBoost detector for unseen families; both run online without host addresses (Sect. 3).
3. An evaluation on CSE-CIC-IDS2018 on a hold-out, left-out days, leave-one-attack-out folds, and a test day against ten re-run methods, with ablations and CPU timing (Sect. 4).

2 Related Work

Detection varies widely—and can collapse—when test attack classes are absent from training [7–10] (Table 3, bottom). Prior hybrids pass autoencoder errors [1] or VAE features [2] to tree classifiers, while streaming detectors track per-host statistics [11], score bursts of edges between hosts [12], or classify flow windows [13]. Instead, our streaming components count bursts in the VAE's latent space and thus require no host addresses.

3 Proposed Framework

3.1 Stage 1: CatBoost with SHAP Feature Selection

Stage 1 ranks the 64 candidate features by mean absolute SHAP value [14] across 20 CatBoost runs, each on a random 70 % of the features, and retains the smallest top set holding 95 % of the importance: 44 features on our data (Fig. 2, Table 1).

3.2 Stage 2: Robust Variational Autoencoder

Each part of our VAE [15] addresses a property of flow statistics.

Undefined Statistics. CICFlowMeter writes 0 when it cannot compute a statistic [16]; for instance, an inter-arrival time requires two packets and an idle time requires an idle period. Such a zero is not a measurement. In the training rows, 81.04 % of *Idle Max* values and 28.82 % of *Flow IAT Std* values are undefined. We mark these entries as missing ($b_j = 0$) using rules from the CICFlowMeter source code. Each feature j has its own small encoder, an expert, mapping x_j to a Gaussian $\mathcal{N}(\mu_j, \sigma_j^2)$ over the latent vector $z \in \mathbb{R}^5$. The posterior is the product of the defined-feature experts and a standard normal prior expert [17]: $\sigma^{-2} = 1 + \sum_j b_j \sigma_j^{-2}$ and $\mu = \sigma^2 \sum_j b_j \sigma_j^{-2} \mu_j$. Thus, a missing feature neither affects the posterior nor adds a likelihood term [18, 19].

Heavy Tails. In the training rows, flow durations span six orders of magnitude and forward packet counts span four, so a few extreme flows dominate a Gaussian likelihood. The decoder therefore assigns each feature a Student-t likelihood with learned location, scale, and degrees of freedom [20], with negative log-likelihood ℓ_j. A soft lower bound on the log scale prevents the scale from collapsing [21].

Neighbourhoods. Because the Stage 3 correction counts flows in latent-space cells, similar flows must remain close after encoding, which the VAE objective does not ensure. We therefore add the 0-dimensional topological loss $\mathcal{L}_t$ of Moor et al. [22], comparing the minimum spanning trees of the inputs and posterior means within each batch.

Objective. To train the experts on incomplete rows, each batch also includes a second view x_s per row that retains a random subset s of the defined features [18, 19]. The VAE minimizes

$$\mathcal{L} = \sum_{v \in \{x, x_s\}} \Big(\mathbb{E}_{q(z|v)} \big[\textstyle\sum_j m_j^v \ell_j \big] + \beta \, \mathrm{KL}\big(q(z \mid v) \,\|\, p(z)\big) \Big) + 0.1\beta \, \mathrm{KL}\big(q(z \mid x_s) \,\|\, q(z \mid x)\big) + \gamma \mathcal{L}_t, \quad (1)$$

where m_j^v is 1 for features present in view v, $p(z) = \mathcal{N}(0, I)$, and the third term aligns the two views [23]. The weight is $\gamma = 1$ (Sect. 3.4).

3.3 Stage 3: Classification, Correction and Detection

Classifier. For each flow, the VAE produces seven outputs: the five posterior means μ, the KL term, and the reconstruction NLL at $z = \mu$, summed over the 23 features defined for every flow so that the sum has the same terms across flows. A multiclass CatBoost classifier [24] with balanced class weights predicts the class from these outputs and is tuned with Optuna [25]. Because the classifier knows only the training classes, in tests on unseen families we count any non-Benign class as an attack, as in the binary view of [7].

Novel-Burst Correction. A learned attack can recur in a form the classifier misses: Slowloris teardown flows appear Benign to the classifier, yet look unusual to the VAE and arrive in bursts. The correction identifies such flows in three steps. First, a flow is *novel* if its reconstruction NLL exceeds the q_n quantile of Benign NLLs on a calibration day. Second, a flow belongs to a *burst* when many flows have recently arrived in its latent cell: after dividing each latent axis by its training SD, the cell is the grid cube of side w containing the flow's posterior mean. We measure this with the MIDAS-R score [12] thresholded at its q_b quantile on Benign training flows, using the latent cell in place of the host pair since the flow records carry no addresses. Third, a novel flow in a burst adopts the attack class predicted most often by the classifier among earlier flows from the last W seconds of the day, provided that class count passes a support threshold; otherwise, its prediction remains unchanged. Because the calibration day contains no training attack classes, any attack prediction on its Benign flows is a false alarm, and the q_s quantile of this count over its Benign flows sets the threshold. All quantities use only earlier flows, so the correction runs online. In the hold-out evaluation, same-day training flows remain in the stream and count as Benign predictions so that no training label adds attack support.

Unseen-Attack Detector. A flow from a new attack family that resembles no learned class remains Benign after the correction, so a second CatBoost model, the detector, checks every Benign flow. Its first input is the *relative NLL*: the reconstruction NLL minus the running median NLL of earlier same-day non-burst flows, since days differ in their normal NLL level. The other four inputs are the KL term, the latent cell's MIDAS-R score, the same score over novel flows only (relative NLL above its q_n quantile on calibration-day Benign flows), and the novel-flow share within the cell over the last W seconds. Each input is replaced by its percentile rank among Benign reference flows so that all days share a common scale. Monotone constraints [26] allow larger inputs only to raise the attack score, ensuring a more unusual flow never gets a lower score and making the detector less able to learn a narrow value range of one training family.

Its positives are labelled attacks from families absent from the VAE and classifier training labels: the training rows of the left-out class in each leave-one-attack-out fold, encoded by that fold's models, plus the attacks of day 02-28 and further capture days (Sect. 4.1). The negatives are half of the Benign flows from these days and the calibration day, with the cut-off set for 1 % false alarms on the other half. A left-out day excludes that day and its families on all days from detector training; a fold excludes its class. Any flagged flow becomes an *unknown attack*, a wrong class in the seen-class metrics.

3.4 Hyperparameter Selection

No model weight or threshold is fitted on the hold-out or test day, and the VAE stops on the 02-28 ELBO. The topological weight γ and the five correction settings are chosen with seed 3 on an inner split holding out the latest 20 % of training rows per day and class. The weight γ maximizes mean per-class F1 with the correction at its start values. The correction settings are then tuned one by one to maximize mean attack-versus-Benign F1 across three leave-one-attack-out folds of the inner split. For the detector, the NLL is taken relative to either the calibration-day median NLL or the day's running median,

Table 1. Settings of the framework; Stage 3 values are search ranges of Optuna's TPE sampler.

Part	Settings
Stage 1	20 CatBoost runs on random 70 % feature subsets and ≤50,000 training rows per class, SHAP on 1,000 rows per class; 300 iterations, depth 6, learning rate 0.1, balanced class weights
Stage 2	all training rows; signed log, standardization on defined entries; 44 experts of 20 ReLU units, latent size 5; decoder 128 ReLU units, Student-t, soft bound $\log \hat{\sigma} \geq -6$, $\nu = 1 + \text{softplus}$; $\beta = 0.5$, consistency 0.1β; second view: each defined feature kept with probability $1 - \rho$, $\rho \sim U(0, 0.7)$, and, in addition, the features removed that are undefined in a random other row of the batch; $\gamma \in \{0.1, 0.3, 1, 3\}$, chosen $\gamma = 1$, on 256 flows per batch, distances divided by their mean; Adam $8 \cdot 10^{-3}$, batch 32,768, ≤1,000 epochs, learning rate halved after 3 flat epochs, stop after 10 epochs without a relative gain of 10^{-4} in the 02-28 ELBO
Stage 3	CatBoost, plain boosting, balanced weights; Optuna TPE, 20 trials (10 random); iterations 200–1000, depth 4–8, learning rate 0.01–0.3, L2 1–30 (both log scale); mean per-class F1 over 3 time-blocked folds of a 10 % sample per day and class (classes under 2,000 rows whole); same search for raw CatBoost
Correction	grids, searched in this order from the start values in brackets: $w \in \{0.1, [0.2], 0.5\}$, $q_b \in \{0.975, [0.99], 0.995\}$, $W \in \{30, [60], 120\}$ s, $q_s \in \{0.975, [0.99], 0.995\}$, $q_n \in \{0.90, 0.95, [0.975], 0.99\}$; chosen $w = 0.1$, $q_b = 0.975$, $W = 120$ s, $q_s = 0.975$, $q_n = 0.9$; latent axes divided by their training SD; MIDAS-R edge score only, decay 0.5 [12], one-minute ticks; flows of the same second are not earlier than each other
Detector	CatBoost, depth 2, 500 iterations, learning rate 0.1, monotone; rank references: relative NLL and KL of calibration-day Benign flows, stream inputs of Benign training flows; median NLL of a reservoir sample of ≤20,000 earlier flows of the day with MIDAS-R below its 0.9 Benign training quantile, refreshed every 500 flows (calibration-day median for the first 1,000); ≤200,000 negatives per day; 1 % false alarms

and the inputs are chosen from five subsets; each configuration is validated by leaving out one further capture day or one fold at a time. The chosen configuration—the running median with all five inputs—achieves the highest mean detection rate among those with at most 2 % mean false alarms. Table 1 lists the grids and selected values.

4 Experiments and Results

4.1 Dataset and Protocol

We used the official CSE-CIC-IDS2018 CSV files [27, 28], corrected their 12-hour CICFlowMeter timestamps [16], and removed rows with non-finite values. To prevent shortcuts, we dropped the timestamp [4,6], the destination port [5], and three TCP header fields that identify the attacker machines on the training days (*Init Fwd Win Byts*, *Init Bwd Win Byts*, *Fwd Seg Size Min*; similar shortcuts are noted in [4, 6]), along with 10 constant columns, leaving 64 candidate features. We also removed duplicate rows, rows from other days matching training rows, and label conflicts (identical features with different labels). These conflicts include 184,551 FTP brute-force rows, consistent with the failed FTP attack in [29].

Table 2 summarizes the splits. Because the classes of test day 02-21 are absent from training, this day tests unseen families. Its HOIC window contains a burst of 358,621 Benign flows of one template; since Liu et al. [29] report no HOIC label issue beyond a time offset, we kept these flows as Benign. Outside this burst, the day has only 2,125 Benign flows. The detector also trains on further capture days where at least six hours each hold at least 1 % of the day's Benign flows, a rule that excludes the truncated file of day 02-16. On day 02-20, we removed 797 UDP flows labelled LOIC-HTTP within the LOIC-UDP window, since LOIC-UDP is a test-day class.

Table 2. Data splits after cleaning: the hold-out contains the latest 20 % of each day and class.

Split (use)	Day(s)	Rows (class counts)
Training (Stages 1–3)	02-14, 02-15	1,039,918 (Benign 923,868; SSH 75,224; GoldenEye 33,066; Slowloris 7,730; FTP 30)
Hold-out (seen classes)	02-14, 02-15	259,983 (Benign 230,968; SSH 18,807; GoldenEye 8,267; Slowloris 1,933; FTP 8)
Validation (VAE stop, detector)	02-28	222,123 (Benign 211,538; Infiltration 10,585)
Calibration	02-23	705,316 (Benign 704,897; web attacks 419)
Test (unseen classes)	02-21	555,189 (Benign 360,746; HOIC 192,713; LOIC-UDP 1,730)
Further days (detector)	02-20, 02-22, 03-01, 03-02	6,659,249 (Benign 5,896,584; LOIC-HTTP 573,708; Bot 143,315; Infiltration 45,408; web brute force 147; XSS 64; SQL injection 23)

Table 3. Re-run methods (top; deviations from the source in italics; not given: absent from the source) and reported results of related work (bottom; other splits and metrics). LOAO: leave-one-attack-out

Method	Settings
Random forest [8]	scikit-learn defaults, as the source; standardization; *signed log, balanced class weights*
MLP [7]	24 hidden units (WEKA rule of the source code); *scikit-learn with early stopping, not WEKA*
XGBoost [31], LightGBM [32]	library defaults, signed log + standardization (XGBoost has no random step)
IDAE-XG [1]	as the source; top 22 features by forest rank, 20 epochs (not given); *multiclass; no upsampling*
CNN-1D [33]	as the source ($\leq$20 epochs, patience 4); *our split, stratified random split in the source*
FlowTransformer [13]	8-flow windows (source code), 2 decoder blocks, learning rate of the source grid; *multiclass*
TabM [34]	package defaults, settings of the source (patience 16); *no tuning*
FT-Transformer [35]	default configuration and optimizer (patience 16); *no tuning, no ensemble*
TabNet [36]	Table 4 of the source, patience 20; learning rate 0.02 (library default; not given); *no SMOTE*
Work	**Data; split; reported result**
Ferreira [7]	CSE-CIC-IDS2018, train 02-16, test 02-21; MLP TPR 0.898 on test attacks, 0 on LOIC-UDP
Sakr [8]	CSE-CIC-IDS2018, 9 days; random forest F1 0.957 (random split), 0.239 (LOAO mean)
Verkerken [9]	CIC-IDS2017 random split: 41/47 unknown flows found; CSE-CIC-IDS2018 Infiltration recall 78.38 %
Soltani [10]	CSE-CIC-IDS2018 packet bytes, one unknown label per run: its accuracy 35.47–72.16 %

Metrics and Runs. For seen classes, the main metric is mean per-class F1 over classes with at least 30 hold-out rows, while FTP (8 rows) is reported separately. For unseen families, we report the detection rate (DR), Benign false-positive rate (FPR), and Youden's $J = \mathrm{DR} - \mathrm{FPR}$. Each seed (3, 4, 5) retrains every model after Stage 1 and recomputes every threshold, while Stage 1 runs once on the main split and once per fold. We report the mean and standard deviation (SD) over seeds and a paired bootstrap of the difference to raw CatBoost [30]. The VAEs and PyTorch re-run methods were trained on an RTX 5080 Laptop GPU and the other models on an Intel Core Ultra 9 275HX CPU; the code repository gives library versions, thread counts, and the command for every table: https://github.com/WinterBlossom0/IDS-VAE-and-Catboost.

Comparison Methods. We re-ran ten methods from related work—the *re-run methods*—on the same Stage 1 features, rows, and seeds (Table 3), with balanced class weights or class-balanced batches and no oversampling. Each method predicts the same hold-out, test day, and further days, and is retrained without the left-out class in each fold.




Fig. 2. Stage 1 SHAP ranking: (a) mean |SHAP| of the top 10 features over 20 runs; (b) cumulative share and importance of all 64 features (the 95 % rule keeps $k = 44$). The rankings of two disjoint halves of the runs have Spearman correlation 0.963 and top-44 Jaccard index 0.913.

4.2 Seen Classes: The Correction on VAE Signals Gives the Gain

We first test whether Stage 2 and the correction improve on CatBoost with the same 44 features (raw CatBoost) on the four classes with at least 30 hold-out rows (Table 4). The framework reaches a mean per-class F1 of 0.991 ± 0.004, versus 0.979 ± 0.001 for raw CatBoost and 0.975 for the best re-run method. It beats raw CatBoost in every seed by 0.008 to 0.017 (paired bootstrap, 95 % intervals for seeds 3, 4, and 5: [0.006, 0.010], [0.015, 0.020], [0.009, 0.013]). With the detector, F1 drops only to 0.990 ± 0.004, as the detector flags about 1 % of Benign hold-out flows as unknown attacks. Table 5 shows that the gain comes from Slowloris, while raw CatBoost is better on FTP (8 hold-out rows) and thus over all five classes (0.979 versus 0.940).

The ablations in Table 4 pinpoint the gain. Without the correction, the VAE classifier trails raw CatBoost (0.965 versus 0.979). The correction raises its Slowloris recall from 0.79 (not tabulated) to 0.98, and lifts raw CatBoost to a mean F1 of 0.990 too, tying the framework within the seed spread. Still, raw CatBoost with the correction must run the VAE for the NLL and latent cells, relabels more Benign flows, and is slower than the framework. The gain thus comes from the correction, which requires the VAE signals, rather than from the VAE as a feature compressor. Accordingly, a Gaussian likelihood, no topological loss, or the latent mean alone each changes the F1 by at most 0.003 with the correction present, within the seed spread, whereas without the correction the topological loss lowers the F1. For unseen families, a detector on the VAE without the topological loss reaches J 26.17 % on the left-out days, versus 26.37 % with it, when both train on the further days only, so the loss does not alter detection either. LightGBM and XGBoost in Stage 3 match the F1 with lower balanced accuracy. Giving Stage 3 both the 44 raw features and the seven VAE outputs fails to close the gap before the correction (0.973 versus 0.979) and matches the framework after it (0.991), while removing the FTP false alarms (FTP F1 0.98 versus 0.74).

Inference Time. With the detector, the framework needs 0.050 ms per flow on one CPU thread, against 0.018 ms for raw CatBoost; its merged VAE and CatBoost graph takes 0.044 ms (0.046 ms as two graphs), the correction 0.00015 ms and the detector

Table 4. Hold-out mean per-class F1 (classes ≥30 rows) per seed and mean ± SD, balanced accuracy (all classes), Benign hold-out flows relabelled (sum over seeds; with the detector: by the correction and the detector), and CPU ms per flow (batch 1, one thread, seed 3). With the correction, the framework has a higher mean F1 than raw CatBoost and each re-run method.

Configuration	Seed 3	Seed 4	Seed 5	Mean F1	Bal. acc.	Relab.	ms/flow
Ours (with the correction)	0.9883	0.9949	0.9895	0.9909 ± 0.0036	0.9947 ± 0.0018	487	0.044
Without the correction	0.9583	0.9700	0.9667	0.9650 ± 0.0060	0.9569 ± 0.0051	–	–
Without the topological loss	0.9880	0.9931	0.9906	0.9905 ± 0.0026	0.9865 ± 0.0153	405	–
No topological loss or corr.	0.9742	0.9655	0.9772	0.9723 ± 0.0060	0.9590 ± 0.0255	–	–
Gaussian likelihood	0.9876	0.9908	0.9864	0.9883 ± 0.0023	0.9940 ± 0.0008	583	–
Latent mean only (5 inputs)	0.9883	0.9913	0.9875	0.9890 ± 0.0020	0.9946 ± 0.0013	614	–
LightGBM in Stage 3	0.9905	0.9935	0.9900	0.9913 ± 0.0019	0.9767 ± 0.0284	671	0.16
XGBoost in Stage 3	0.9910	0.9954	0.9905	0.9923 ± 0.0027	0.9441 ± 0.0015	614	0.058
Raw + VAE inputs (51) + corr.	0.9902	0.9893	0.9934	0.9910 ± 0.0022	0.9950 ± 0.0007	1209	–
Raw + VAE inputs (51)	0.9781	0.9634	0.9788	0.9734 ± 0.0087	0.9673 ± 0.0085	–	–
Raw CatBoost + correction	0.9911	0.9896	0.9907	0.9904 ± 0.0008	0.9955 ± 0.0003	1377	0.057
Raw CatBoost (44 features)	0.9800	0.9776	0.9785	0.9787 ± 0.0012	0.9739 ± 0.0014	–	0.018
Ours + detector	0.9868	0.9937	0.9883	0.9896 ± 0.0036	–	7674	0.050
Re-run methods (Table 3)							
Random forest [8]	0.9642	0.9643	0.9643	0.9643 ± 0.00004	0.9042 ± 0.00004	–	0.0040
MLP [7]	0.9781	0.9555	0.9600	0.9645 ± 0.0120	0.9628 ± 0.0148	–	0.0031
XGBoost [31]	0.9640	0.9640	0.9640	0.9640 ± 0	0.9042 ± 0	–	0.0053
LightGBM [32]	0.9655	0.9677	0.9629	0.9654 ± 0.0024	0.9549 ± 0.0002	–	0.0059
IDAE-XG [1]	0.6959	0.6423	0.6425	0.6602 ± 0.0309	0.6621 ± 0.0215	–	0.016
CNN-1D [33]	0.9742	0.9780	0.9734	0.9752 ± 0.0024	0.9740 ± 0.0032	–	0.039
FlowTransformer [13]	0.8276	0.8279	0.8402	0.8319 ± 0.0072	0.8827 ± 0.0189	–	0.058
TabM [34]	0.9493	0.9510	0.9502	0.9502 ± 0.0008	0.9542 ± 0.0001	–	0.39
FT-Transformer [35]	0.9608	0.9606	0.9626	0.9613 ± 0.0011	0.9546 ± 0.0014	–	0.74
TabNet [36]	0.9546	0.9531	0.9632	0.9569 ± 0.0054	0.9594 ± 0.0058	–	0.098

0.0058 ms. We timed each pipeline with a time in Table 4 as ONNX Runtime 1.31 graphs and C++ code on one thread of an Intel Core Ultra 9 275HX, one flow per call from the extracted features to the final label, over the 100,000 consecutive flows in the middle of day 02-21 (98,562 Benign burst and 1,438 attack flows). Each time is the median of 4 passes; a full repeat gave the same order of the 16 pipelines and a framework time 1.3 % higher.

Table 6 measures F1 and cost with the k most important features of Stage 1 (seed 3; $k = 64$: all 79 columns minus the 15 dropped); for $k > 10$, our F1 stays within 0.9870–0.9908, and $k \in \{23, 40, 64\}$ score above the $k = 44$ of the 95 % rule.

4.3 Unseen Attack Families

Table 7 tests the detector alone on left-out days and the framework with the detector in the leave-one-attack-out folds. The detector mainly catches families whose flows arrive as bursts of novel flows. For LOIC-HTTP, it flags 99.01 % of request flows but only 0.28 % of unanswered attempts, while Infiltration stays mostly undetected. The VAE-based inputs are key: a CatBoost detector on the 44 raw features instead of its five inputs, trained on the same rows with the same cut-off but without monotone constraints, flags on average only 4.17 % (depth 6) and 4.81 % (depth 2) of each left-out family's flows, versus 30.86 % for ours (mean of Table 7a), showing that the labelled further days and tree depth alone do not explain the detection.

Table 5. Per-class hold-out results, mean over seeds 3–5, of the framework and raw CatBoost (top), and the confusion matrix of the framework, seed 3 (bottom; rows: true class)

		Ours (with correction)			Raw CatBoost (44 features)		
Class	Rows	Precision	Recall	F1	Precision	Recall	F1
Benign	230,968	0.9998	0.9978	0.9988	0.9989	0.9981	0.9985
DoS GoldenEye	8,267	0.9964	0.9992	0.9978	0.9983	0.9998	0.9990
DoS Slowloris	1,933	0.9801	0.9767	0.9784	0.9929	0.8724	0.9288
FTP-BruteForce	8	0.6218	1.0000	0.7360	0.9630	1.0000	0.9804
SSH-BruteForce	18,807	0.9775	1.0000	0.9886	0.9777	0.9995	0.9884
Balanced accuracy		0.9947 ± 0.0018			0.9739 ± 0.0014		
Macro ROC-AUC (one vs rest, classifier)		0.9993 ± 0.0005			0.9995 ± 0.0001		
Macro PR-AUC (one vs rest, classifier)		0.9689 ± 0.0219			0.9924 ± 0.0011		

True \ predicted	Benign	GoldenEye	Slowloris	FTP	SSH
Benign	230,374	34	56	0	504
DoS GoldenEye	8	8,259	0	0	0
DoS Slowloris	59	0	1,874	0	0
FTP-BruteForce	0	0	0	8	0
SSH-BruteForce	1	0	0	0	18,806

Table 6. Feature-count ablation (seed 3): hold-out mean per-class F1, VAE training time in s (one VAE at a time on the GPU) and inference time in ms per flow (batch 1, one thread, no detector, as Table 4)

	F1				ms per flow	
k	Ours	Raw	Raw + corr.	VAE (s)	Ours	Raw
10	0.9738	0.9815	0.9881	141	0.046	0.017
15	0.9877	0.9792	0.9886	158	0.072	0.019
23	0.9908	0.9782	0.9895	273	0.051	0.015
30	0.9870	0.9799	0.9908	357	0.054	0.024
40	0.9902	0.9813	0.9911	302	0.061	0.019
44	0.9883	0.9800	0.9911	317	0.044	0.018
64	0.9908	0.9805	0.9906	392	0.057	0.016

Table 8 compares all methods by Youden's J. Trained on days 02-14 and 02-15 only, our classifier scores like most re-run methods (J 0.57 % on left-out days); with the detector, also trained on the further days, the framework reaches 30.27 % and 78.29 % in the folds. Since the detector configuration was selected on these days and folds (Sect. 3.4), only the test day is unused by that choice. The test day shows the limit of the burst signal: 99.4 % of its Benign flows belong to one burst inside the HOIC window. The framework detects 81.35 % of LOIC-UDP flows, but also flags 66.77 % of this Benign burst, which receives higher detector scores than the HOIC flows. In the rows marked $^{+}$ in Table 8, the shallow re-run methods also train on the further days except the evaluated one, with each attack flow labelled by family, and flag flows by the detector's cut-off rule; Isolation Forest [37], an open-set detector, trains on their Benign flows only. Given the same days, the best reach J 6.05 % on left-out days (LightGBM) and 34.35 % in the folds (MLP), versus 30.27 % and 78.29 %.

Table 7. Attack families absent from all training labels, in %, mean ± SD over seeds 3–5: (a) left-out days, DR and Benign FPR of the detector alone; (b) leave-one-attack-out folds, DR on days 02-14 and 02-15 after each step, and hold-out Benign FPR; with raw CatBoost as classifier (same correction and detector), the mean final DR is 0.01 to 1.67 points higher per fold.

(a) Left-out days

Day	Family	DR	FPR
02-28	Infiltration	2.34±1.83	2.42±0.23
02-20	LOIC-HTTP	50.06±0.12	0.91±0.16
02-22	Web brute force	30.84±21.21	0.61±0.06
	SQL injection	13.04±7.53	
	XSS	48.44±17.61	
03-01	Infiltration	3.03±0.71	0.68±0.01
03-02	Bot	68.24±2.06	0.68±0.04

(b) Leave-one-attack-out folds

Removed class	Classifier	+ corr.	+ det.	FPR
SSH-BruteForce	0.0007±0.001	0.0007±0.001	95.16±5.02	2.19±1.21
DoS GoldenEye	0.11±0.01	11.96±1.40	58.19±19.27	1.68±0.92
DoS Slowloris	53.01±13.28	71.09±2.01	87.43±8.32	2.03±0.97

Table 8. Unseen attack families, in %, mean over seeds 3–5: Youden's J is the detection rate (DR) minus the Benign false-positive rate (FPR); a re-run method flags a flow whose argmax class is not Benign. $^{+}$: trained also on the further days and flagged at the detector's cut-off. Left-out days: mean over day and family; folds: mean over the three folds. Test day 02-21: DR, Benign FPR outside and inside the burst, and J against all Benign flows.

	J		Test day					
	Left-out days	Folds	DR UDP	DR HOIC	FPR out	FPR burst	J UDP	J HOIC
Ours + detector	30.27	78.29	81.35	0.01	15.42	66.77	14.88	−66.46
Random forest [8]	0.03	15.81	0	0	0.27	0.0003	−0.002	−0.002
MLP [7]	1.60	18.99	0	0	0.72	4.05	−4.03	−4.03
XGBoost [31]	−0.01	23.90	0	0	0.38	0	−0.002	−0.002
LightGBM [32]	−0.01	5.36	0.15	0	0.35	0.00009	0.15	−0.002
IDAE-XG [1]	24.57	36.52	99.81	32.17	68.17	67.64	32.16	−35.48
CNN-1D [33]	0.60	16.56	0.02	0	0.49	20.57	−20.43	−20.45
FlowTransformer [13]	8.33	8.02	93.29	17.32	38.35	68.57	24.90	−51.07
TabM [34]	0.02	16.84	63.91	0	1.36	0.57	63.34	−0.57
FT-Transformer [35]	0.31	20.85	6.61	0	0.64	0.94	5.67	−0.94
TabNet [36]	0.07	16.94	0	0.23	0.53	25.01	−24.87	−24.64
Random forest^{+}	0.16	−0.01	0	0.43	0.05	0	−0.0003	0.43
MLP^{+}	1.18	34.35	99.83	0.0002	1.38	27.43	72.55	−27.27
XGBoost^{+}	0.98	24.08	0	0.11	0.45	0	−0.003	0.11
LightGBM^{+}	6.05	22.96	0.50	0.33	0.28	0	0.50	0.33
IDAE-XG^{+}	−0.25	0.68	46.22	0.34	1.22	22.01	24.34	−21.54
Isolation Forest^{+} [37]	0.36	−0.65	66.69	0	33.44	0.01	66.48	−0.21

5 Limits

Unusual Benign bursts mimic attacks, non-burst attacks give no signal, and the correction assumes one attack at a time. Our evidence comes from one dataset with known errors and label faults [4, 29] and three seeds. CNN-1D, FlowTransformer, TabM, FT-Transformer, and TabNet were not given the further days, nor was Kitsune [11] run; re-run methods use defaults without the correction, and no ablation removes missing-entry handling.

6 Conclusion

We proposed a hybrid VAE-CatBoost framework in which a robust VAE serves both a classifier and two streaming components. On CSE-CIC-IDS2018, the correction lifts the mean per-class F1 of the four larger classes above raw CatBoost and ten untuned re-run methods, and the framework with the detector reaches a Youden's J of 30.27 % on left-out days, versus 6.05 % for the best untuned re-run method given the same days. A large Benign burst on the test day defeats the detector; separating such bursts from attacks remains future work.

Use of AI Tools. Claude Code was used for the implementation of the code and for finding bugs.

Disclosure of Interests. The authors have no competing interests to declare that are relevant to the content of this article.

References

1. Kang, Y., Tan, M., Lin, D., et al.: Intrusion detection model based on autoencoder and XGBoost. Journal of Physics: Conference Series **2171**(1), 012053 (2022)
2. Chen, Y., Zheng, X., Wang, N.: Construction of VAE-GRU-XGBoost intrusion detection model for network security. PLOS ONE **20**(6), e0326205 (2025)
3. Arp, D., Quiring, E., Pendlebury, F., et al.: Dos and don'ts of machine learning in computer security. In: USENIX Security. pp. 3971–3988 (2022)
4. Engelen, G., Rimmer, V., Joosen, W.: Troubleshooting an intrusion detection dataset: the CICIDS2017 case study. In: IEEE Security and Privacy Workshops (SPW). pp. 7–12 (2021)
5. D'hooge, L., Verkerken, M., Volckaert, B., et al.: Establishing the contaminating effect of metadata feature inclusion in machine-learned network intrusion detection models. In: DIMVA. LNCS, vol. 13358, pp. 23–41. Springer (2022)
6. Flood, R., Engelen, G., Aspinall, D., et al.: Bad design smells in benchmark NIDS datasets. In: IEEE EuroS&P. pp. 658–675 (2024)
7. Ferreira, P., Antunes, M.: Benchmarking bioinspired machine learning algorithms with CSE-CIC-IDS2018 network intrusions dataset. In: 26th Portuguese Conference on Pattern Recognition (RECPAD) (2020)
8. Sakr, H.A., El-Douh, A.A., Lapina, M., et al.: Explainable and deployment-aware zero-day intrusion detection for cloud-level backend and management ecosystems in EV/V2X cyber-physical systems. Computers **15**(9), 599 (2026)
9. Verkerken, M., D'hooge, L., Sudyana, D., et al.: A novel multi-stage approach for hierarchical intrusion detection. IEEE Transactions on Network and Service Management **20**(3), 3915–3929 (2023)
10. Soltani, M., Ousat, B., Jafari Siavoshani, M., et al.: An adaptable deep learning-based intrusion detection system to zero-day attacks. arXiv:2108.09199 (2021)
11. Mirsky, Y., Doitshman, T., Elovici, Y., et al.: Kitsune: An ensemble of autoencoders for online network intrusion detection. In: Network and Distributed System Security Symposium (NDSS) (2018)
12. Bhatia, S., Hooi, B., Yoon, M., et al.: MIDAS: Microcluster-based detector of anomalies in edge streams. In: AAAI. vol. 34, pp. 3242–3249 (2020)
13. Manocchio, L.D., Layeghy, S., Lo, W.W., et al.: FlowTransformer: A transformer framework for flow-based network intrusion detection systems. Expert Systems with Applications **241**, 122564 (2024)

14. Lundberg, S.M., Lee, S.I.: A unified approach to interpreting model predictions. In: NeurIPS. vol. 30, pp. 4765–4774 (2017)
15. Kingma, D.P., Welling, M.: Auto-encoding variational Bayes. In: ICLR (2014)
16. Habibi Lashkari, A.: CICFlowMeter: source code, BasicFlow.java. https://github.com/ahlashkari/CICFlowMeter, last accessed 2026/10/18
17. Wu, M., Goodman, N.: Multimodal generative models for scalable weakly-supervised learning. In: NeurIPS. vol. 31, pp. 5575–5585 (2018)
18. Ma, C., Tschiatschek, S., Palla, K., et al.: EDDI: Efficient dynamic discovery of high-value information with partial VAE. In: ICML. PMLR, vol. 97, pp. 4234–4243 (2019)
19. Ivanov, O., Figurnov, M., Vetrov, D.: Variational autoencoder with arbitrary conditioning. In: ICLR (2019)
20. Takahashi, H., Iwata, T., Yamanaka, Y., et al.: Student-t variational autoencoder for robust density estimation. In: IJCAI. pp. 2696–2702 (2018)
21. Rybkin, O., Daniilidis, K., Levine, S.: Simple and effective VAE training with calibrated decoders. In: ICML. PMLR, vol. 139, pp. 9179–9189 (2021)
22. Moor, M., Horn, M., Rieck, B., et al.: Topological autoencoders. In: ICML. PMLR, vol. 119, pp. 7045–7054 (2020)
23. Sinha, S., Dieng, A.B.: Consistency regularization for variational auto-encoders. In: NeurIPS. vol. 34, pp. 12943–12954 (2021)
24. Prokhorenkova, L., Gusev, G., Vorobev, A., et al.: CatBoost: Unbiased boosting with categorical features. In: NeurIPS. vol. 31, pp. 6638–6648 (2018)
25. Akiba, T., Sano, S., Yanase, T., et al.: Optuna: A next-generation hyperparameter optimization framework. In: ACM SIGKDD (KDD). pp. 2623–2631 (2019)
26. Íncer Romeo, Í., Theodorides, M., Afroz, S., et al.: Adversarially robust malware detection using monotonic classification. In: ACM IWSPA. pp. 54–63 (2018)
27. Canadian Institute for Cybersecurity: CSE-CIC-IDS2018 on AWS. https://www.unb.ca/cic/datasets/ids-2018.html, last accessed 2026/10/15
28. Sharafaldin, I., Habibi Lashkari, A., Ghorbani, A.A.: Toward generating a new intrusion detection dataset and intrusion traffic characterization. In: ICISSP. pp. 108–116. SCITEPRESS (2018)
29. Liu, L., Engelen, G., Lynar, T., et al.: Error prevalence in NIDS datasets: A case study on CIC-IDS-2017 and CSE-CIC-IDS-2018. In: IEEE Conference on Communications and Network Security (CNS). pp. 254–262 (2022)
30. Koehn, P.: Statistical significance tests for machine translation evaluation. In: EMNLP. pp. 388–395 (2004)
31. Chen, T., Guestrin, C.: XGBoost: A scalable tree boosting system. In: ACM SIGKDD (KDD). pp. 785–794 (2016)
32. Ke, G., Meng, Q., Finley, T., et al.: LightGBM: A highly efficient gradient boosting decision tree. In: NeurIPS. vol. 30, pp. 3146–3154 (2017)
33. Donoso, O.E., Pacheco, M.A., Vargas, J.P., et al.: Autoencoder versus CNN-1D for network traffic intrusion detection: A reproducible comparative evaluation with per-class analysis on CSE-CIC-IDS2018. Journal of Cybersecurity and Privacy **6**(5), 183 (2026)
34. Gorishniy, Y., Kotelnikov, A., Babenko, A.: TabM: Advancing tabular deep learning with parameter-efficient ensembling. In: ICLR (2025)
35. Gorishniy, Y., Rubachev, I., Khrulkov, V., et al.: Revisiting deep learning models for tabular data. In: NeurIPS. vol. 34, pp. 18932–18943 (2021)
36. Zegarra Rodríguez, D., Okey, O.D., Maidin, S.S., et al.: Attentive transformer deep learning algorithm for intrusion detection on IoT systems using automatic Xplainable feature selection. PLOS ONE **18**(10), e0286652 (2023)
37. Liu, F.T., Ting, K.M., Zhou, Z.H.: Isolation forest. In: IEEE ICDM. pp. 413–422 (2008)