

Three Phase Multi-Level Inverter Topologies and Modulation Techniques

Huan Nguyen-Duy Student ID: 2390703

Ho Chi Minh City University of Technology and Education



Table of Contents





Abstract

- To mention the vital role of power electronic converter in the power production domain
- The paper reveiews methodologies to control three-phase multi-level Inverter by PWD control techniques
- Proposal three-phase multi-level Inverter topologies and Modulation Techniques
- comparison among PWM control techniques phase disposition (PD), phase opposite disposition (POD), and alternate phase opposite disposition (APOD)
- Analysing THD and common mode between methodologies



Reference Papers

- Anup Kumar Panda and Yellasiri Suresh, "Research on cascaded multilevel inverter with single DC source by using three-phase transformers," Electrical Power and Energy Systems. no 40, pp. 9–20, 2012.
- Bendre A, Krstic S, Meer JV and Venkataramanan G., "Comparative evaluation of modulation algorithms for neutral point clamped converters," IEEE Trans Ind Appl 2005;41:634–43.
- Colak I, Kabalci E and Bayindir R., "Review of multilevel voltage source inverter topologies and control schemes," Energy Convers Manag 2011; 52:1114–28.
- Anup Kumar Panda.: Yellasiri Suresh.: Research on cascaded multilevel inverter with single DC source by using three-phase transformers. Electrical Power and Energy Systems. no 40, pp. 9–20, 2012.
- Suresh.Y., Panda A.K.: Research on a cascaded multilevel inverter by employing three-phase transformers. IET Power Electron., Vol. 5, no. 5, pp. 561–570, 2012
- R. Gonzalez, E. Gubia, J. Lopez, and L. Marroyo, "Transformer less single phase multilevel-based photovoltaic inverter," IEEE Trans. Ind. Electron., vol. 55, no. 7, pp. 2694–2702, Jul. 2008



Review Objective


- Three-Phase multi-level Inverter
 - Diode clamped Inverter
 - Flyting capacitor Inverter
 - Cascaded H-Bridge Inverter
- Single DC source with single phase transformer H-Bridge (topology 1)
- Single DC source with single phase transformer H-Bridge (topology 2)
- Modulation techniques
 - phase disposition (PD)
 - phase opposite disposition (POD)
 - alternate phase opposite disposition (APOD)



- The paper sets the target that can propose the topologies Inverter aim reduce cost, size, and weight
 - Reducing the number of active switches
 - Decreasing source components such as DC source
 - Esailer to control
- finding a solution to design three phase Inverter using signle DC source
 - Topology designs used to enhance the output voltage without increasing the number of levels
 - Having ablility to adapt for utility applications



Introduction about three-Phase Inverter





Introduction about three-Phase Inverter

- The three-phase converter include voltage source Inverter (VSI) and current source Inverter (CSI)
- voltage source Inverter (VSI)
 - fundamental three-phase Inverter with 2 level
 - multi-level three-phase Inverter (3, 5, or 7 level)



Three-Phase multi-level Inverter with Diode clamped Inverter




Fig. 2. Diode clamped inverter



- three phase multi-level 5 steps using diode clamped Inverter
- Using single source DC and containing DC bus voltage with 4 capacitor C1, C2, C3, and C4
- Each capacitor have one supply voltage and single capacitor voltage is limited by the voltage stress from switches
- using cascaded diodes to connect from switches S' to S



Three-Phase multi-level Inverter with Flyting capacitor Inverter




Fig. 3. Flying capacitor inverter



- three phase multi-level 5 steps using Flyting capacitor Inverter
- Using single source DC and containing DC bus voltage with 4 capacitor C1, C2, C3, and C4
- Each capacitor have one supply voltage and single capacitor voltage is limited by the voltage stress from switches
- using cascaded capacitor to connect from switches S' to S



Multiple DC sources with H-Bridge Inverter




Fig. 4. Cascaded H-Bridge Inverter



Multiple DC sources with H-Bridge Inverter

- Using Multiple DC source for each full-Bridge Inverters
- containing 6 full-Bridge Inverters that divide to three level
- The cascaded level 1, 2, and 3 corresponding with phase A, B, and C respectively
- The drawback of Multi-DC source H-Bridge Inverter is using a lot of DC source



Single DC source with single phase transformer H-Bridge (topology 1)




Fig. 5. Single DC source with single-phase transformers H-Bridge (Topology 1)

- Using only one DC source for a System
- transformers are imported between levels to gain amplification of output signal
- The cascaded level 1, 2, and 3 corresponding with phase A, B, and C respectively
- the benefit of this System is using only a single DC source



Single DC source with single phase transformer H-Bridge (topology 2)





Fig. 6. Single DC source with three-phase transformer H-Bridge (Topology



- Using only one DC source for a System
- transformers are imported between levels to gain amplification of output signal
- The cascaded level 1, 2, and 3 corresponding with phase A, B, and C respectively
- Three phase transformer 2 (below) is connected directly to LOAD
- in terms of increasing voltage level by connecting the second terminal of the transformer 2 to ouput LOAD that is the advantage of topology 2 comparing with topology 1


Modulation techniques



Modulation techniques

- We forcus on three methods using PWD control level shift
 - PD: this method reduces dramatically THD of the three-phase multi-level Inverter. However, the drawback of this method increases common mode.
 - POD and APOD: By the Contrast, both methodologies will increase THD and reduce the common mode

Simulation three phase 5 level with Diode clamped Inverter



Five level three phase Inverter output voltage using APOD




Fig. 10. Five level output voltage and current (Phase)




Fig. 11. Three phase output voltage and current (Phase)




Fig. 12. THD at a modulation index of 1.0

- figures depicts the outut voltage and current in 1 phase and 3 phases
- THD = 2.48% by APOD control algorithm



Five level three phase Inverter output voltage using PD





Fig. 13. Five level output voltage and current (Phase)






Fig. 15. THD at a modulation index of 1.0

- figures depicts the outut voltage and current in 1 phase and 3 phases
- THD = 2.43% by PD control algorithm

Five level three phase Inverter output voltage using POD





Fig. 16. Five level output voltage and current (Phase)



Fundamental (50Hz) = 2.806, THD= 2.44%

Fig. 18. THD at a modulation index of 1.0

- figures depicts the outut voltage and current in 1 phase and 3 phases
- THD = 2.44% by POD control algorithm □ ► ◆ □ ► ◆ ► ◆ ■

comparing THD

Table: Comparing THD among methodologies

PWM techniques	APOD	PD	POD
THD	2.48%	2.43%	2.44%





Content

Thanks for your attention

Presentation: Huan Nguyen-Duy