

Enhanced Spectrum Sensing Techniques for 5G New Radio (NR) and Long-Term Evolution (LTE) Utilizing Unet++ Deep Learning Network

¹ Huan Nguyen-Duy, ² Dr.Thien Huynh-The

^{1,2}Ho Chi Minh City University of Technology and Education (HCMUTE), Vietnam

^{1,2}The Intelligent Multimedia and Advanced Computing (IMAC) Laboratory

¹huan2931@gmail.com

²thienht@hcmute.edu.vn

Abstract—The 5G New Radio (NR) technology emerged as wireless communication revolution that opens opportunities to develop high-tech applications that includes wireless communication industry in specially and others in general. The 5G New Radio offers significantly higher the peak data range, high-frequency, and low-latency comparing to Long-Term Evolution (LTE). Both of them can be distinguished by the frequency range of spectrum extraction. In the recent year, the deep learning network domain introduced various cutting-edge technologies to tackle for semantic segmentation demand, it is essential for applications such as biomedical image segmentation, wireless communication spectrum sensing, and radar communication waveform recognition. In this paper, we propose the cutting-edge deep learning network base on Unet++ to enhance spectrum sensing for 5G New Radio (NR) and Long-Term Evolution (LTE) that incorporated by cutting edge deep learning techniques such as attention gate (AG), atrous spatial pyramid pooling (ASPP), group convolution, and skip connection. In detail, traditional convolution will be replaced by group convolution to reduce dramatically the complexity of deep network, others techniques will be applied to reach high accuracy, called WiComNet (wireless communication network) which are suitable for compact communication devices with limited resources. We utilize the spectrum generation of 5G New Radio and long-term evolution data by MatLab 5G toolbox to evaluate deep learning network. Our implementation and pre-trained model are available at: Spectrum sensing base on deep learning Github project

Index Terms—spectrum sensing, 5G New Radio (5G NR), Long-Term Evolution (LTE), Unet, unet++, deep learning network, attention gate, group convolution, semantic image segmentation, signal processing.

I. INTRODUCTION

The 5G New Radio (NR) is the next generation of cellular network technologies, it provides the high transmission data range and fast transmission in kinds of different frequencies that include low-bandwidth, middle-bandwidth, and high-bandwidth [?]. In particular, low-bandwidth and middle-bandwidth are popular in many countries, 3400 to 3800 MHz in Europe, 3300 to 4990 MHz in China, 3600 MHz to 4900 MHz in Japan, 3400 MHz to 3700 MHz in Korea, and 3700 MHz to 4200 MHz in United States. The 5G NR offers the long range of frequencies than fourth Long-Term Evolution (LTE), 5G NR offers a broader spectrum range, spanning from below 1GHz up to 52.6GHz, whereas LTE typically operates

within the 3.5GHz to 5GHz range.

In contemporary times, the demand for wireless communication network by utilizing the limited spectrum resource increased dramatically in the recent year, it requires a fast recognition for kinds of wireless radio to apply into minimal electronic devices. In the last decade, several solutions had been proposed to discriminate the type of spectrum in wireless communication network. The paper "Intelligent Spectrum Sensing with ConvNet for 5G and LTE Signals Identification" [?] introduced a innovative methodology that utilizing deep learning network which is ConvNet built by incorporating DeepLabv3+ (an efficient encode-decoder architecture for pixel-level classification) and ResNet18 (as a backbone network for feature extraction). As the result, it reached outstanding results with global accuracy 75% and 95% at signal-to-noise ratio 40db and 60db respectively [?], comparing to global accuracy 78% and 97% at signal-to-noise ratio 40db and 60db, respectively that using the enhance DeepLabV3+, which was showed by "Accurate Spectrum Sensing with Improved DeepLabV3+ for 5G-LTE Signals Identification" [?].

In the recent year, The deep learning network domain witnessed the development process of semantic segmentation, numerous robust encoder-decoder deep learning network was introduced for semantic segmentation domain that opened opportunities in image processing field, high precision together with light weight that have ability adapt to compact electronic devices, contributing to numerous applications related to Biomedical Image Segmentation [?], signal processing [?] [?], and medical Identification. To begin with a light weight semantic image segmentation deep learning network, Unet convolution network for Biomedical image segmentation was presented by Computer Science Department and BIOS Center for Biological Signaling Studies, University of Freiburg, Germany in 2015 [?]. Unet was built by multiple scale convolution networks including two path encoder and decoder from high-scale to small-scale image and small-scale image to high-scale image connected to encoder path and decoder path respectively. In 2020, Unet++ is a redesigning skip connection to exploit multiple scales features in image segmentation that was presented by Zongwei Zhou [?]. Unet++ offered a

higher accuracy than traditional Unet network by utilizing skip connection in each layer, the space between layers was replaced by deep convolution blocks that aim increase features extraction in the output of the network. However, these lead to increase the size of the network dramatically, the total parameters of Unet++ increased approximately fourth times comparing to traditional Unet network. [?].

In this paper, we presented innovative methodologies to enhance Unet++ deep learning network to tackle spectrum sensing 5G New Radio (NR) and Long-Term Evolution (LTE) base on received spectrum in frequency domain by the discrete Fourier transform. To begin with, we utilize group convolutions [?] to reduce dramatically the complexity of deep network, it not only has vital role in reducing the total of parameters but also retain a robust accuracy. On the other hand, attention mechanism was introduce in "Attention Is All You Need" [?], which created a renovation in the deep learning domain in general and semantic image segmentation in specific. In particular, Attention mechanism focus on the mainly regions in the image where need to discriminate segment of objects. Therefore, attention blocks have a light weight which plays a vital role for development deep learning network in compact power devices, especially in signal processing where numerous applications were deployed in smartphones, laptops, and others to discriminate the type of received signals that requires minimum computing performance. Thank to attention mechanism, the attention gate mechanism was introduced in "Attention U-Net: Learning Where to Look for the Pancreas" [?] by Biomedical Image Analysis Group, Imperial College London, London, UK in 2008, which enhances the discriminated ability of Unet network. In detail, attention gates adapted to skip connection in each layer of Unet network, it filter the features propagated through the skip connections [?]. The achievement of attention gates is focusing on extracted features in the same size at the corresponding layer, incorporating skip connections and lower layers by concatenation. On the other hand, atrous spatial pyramid pooling was introduce in "Modified UNet++ with atrous spatial pyramid pooling for blood cell image segmentation" [?], by using four parallel dilated convolution in majority scale sizes that improve general learning capacity of deep network. As the result, our innovative techniques showed effectively in waveform recognition tasks, WiComnet reach impressively spectrum recognition precision while reducing significantly the complexity. In Summary, we utilized incorporated attention gates, group convolution, and atrous spatial pyramid pooling [?] to reduce the size of the Unet++ network and rise the accuracy through attention gates that adapted to skip connection layers to tackle spectrum sensing for the 5G New Radio (NR) and the Long-term Evolution (LTE) base on received spectrum signals. Our objectives present a new innovative deep learning network base on Unet++ architecture that reduces dramatically complexity and reaches high accuracy

II. METHODOLOGY

A. Spectrum sensing system overview

In this work, we focus on how to present an efficient spectrum sensing to identify the 5G New Radio (NR) and

the long-term evolution (LTE) utilizing deep learning network. To begin with, received spectrum image for 5G NR, LTE, and noise are generated by MatLab 5G toolbox. We utilize the characteristic of semantic image segmentation that was introduced in numerous previous studies to discriminate the 5G NR and LTE signal using received spectrum in frequency domain. the discrimination in frequency and time of 5G NR and LTE signal takes place in the physical layer in the wireless communication network system. The figure 1 bellow depict the overall of our application that the received signal is corrected by compact devices, it is responsibility for transforming raw signal to spectrum in frequency domain using Fourier transform. these outputs are passed to deep learning network to classify the type of received signals. In the end, the objective of this application is to build a light weight network that is suitable for communication devices to respond in real-time.

B. Unet++ deep learning network

Unet++ deep learning network [?] is improved version that is inspired by traditional Unet network, it is a light weight encoder and decoder model that provide ability to predict in multiple scales. The main of Unet++ make it reaches higher accuracy than traditional Unet network that inserts more convolution blocks into blank space at layers [?], all of outputs are synthetic at each block by skip connection layers and lower layers that extract more features comparing to Unet network. Nevertheless, the drawback of this methodology increase the total parameters effectively, it was ten times comparing to Unet network and it is not suitable to adapt to compact communication devices. In our research, we decreased significantly the total parameters of Unet++ by replacing traditional convolutions with group convolutions. Furthermore, to increase the extraction feature ability of Unet++ network, we adapt attention gate [?] to before each convolution blocks and atrous spatial pyramid pooling [?] in the latest layer to enhance prediction ratio in image semantic segmentation.

C. Group convolution

Group convolution is primary technique that reduce dramatically the total parameters of the deep learning network [?]. The input and output are divided into multiple groups, each group has its own filters with the input data independently. the total parameters of group convolutions reduces significantly by decreasing the number of features in each group and extending the amount of groups in a group convolution block.



Fig. 1. Example for the group convolution.

The equation of a group convolution is showed by:

$$Y_{g,c} = \sum_{c'=0}^{C_{in}/G-1} \sum_{i=0}^{K-1} \sum_{j=0}^{K-1} (X_{g \cdot (C_{in}/G) + c', h+i, w+j} \cdot W_{g,c,i,j} + b_{g,c}) \quad (1)$$

Where:

- $Y_{g,c}$: is the output at position (g, c) in the g th group.
- $X_{g \cdot (C_{in}/G) + c', h+i, w+j}$: is the input activation at the corresponding position.
- $W_{g,c,i,j}$: is the weight of the convolution filter at position (g, c, i, j) .
- $b_{g,c}$: is the bias term associated with the output channel c in the g th group.
- H_{out}, W_{out} : are the height and width of the output feature map, respectively.

D. Attention gate

The attention gate is introduced by Ozan Oktay [?] that adapts to Unet network. The attention gate is inspired by attention mechanism [?] to enhance significantly image segmentation tasks. Our proposal design will insert attention gates into each skip connection layers of Unet++ network. Spatial region are selected by analysing both activation functions and contextual information which were provided by gating signal from lower layers, feature maps are extracted in multiple scales and merged through skip connections, all of them combine coarse and dense prediction in the output layer. Furthermore, the Unet++ network offers convolution blocks in each skip connection lines that combine with the input from lower layers by concatenation layers. As the result, we propose a method that adapt attention gates into each internal skip connection convolution blocks that enhance dramatically feature extraction abilities at each node. The attention gate architecture will be depicted in Figure 2.




Fig. 2. Attention gate architecture.

The output layer equation of a attention gate is illustrated by:

$$O = SC \cdot LL \cdot (SIG(C_{1 \times 1 \times 1} \cdot R(W_g + W_x))) \cdot C_{1 \times 1 \times F} \quad (2)$$

Where:

- O : the output layer.
- SC : the input layer from skip connection.
- LL : the the input of lower layer.
- $SIG()$: represent for the Sigmoid function.
- R : The represent for the Relu function.
- $C_{H \times W \times F}$: Convolution layer with H , W , and F is the height, weight, and features.

E. Atrous spatial pyramid pooling

In deep learning network, convolution often uses for filter extraction. However, in case of the number of convolution is too big, it leads to high complexity and weight. Atrous spatial pyramid pooling (ASSP) [?] was introduce by using parallel dilated convolutions in difference scales, it aims increasing general learning ability of deep network but retaining significantly the complexity of deep network. In general, the basic ASSP usually conducts with three 3x3 dilated convolution kernels which have dilated scale 1, 2, and 3 respectively. The ASSP module mainly combine four convolutions which include three multiple scale 3x3 dilated convolution kernels and a 1x1 convolution kernel, all of them will be concatenated at the output of ASSP module.

F. Training data

In this paper, we utilize generating 5G NR, LTE, 5G NR combined LTE and noise spectrum data images from Matlab 5G tool box, it provides generating data with variable signal to noise ratio (SNR) range, which defines as the ratio of the power of the signal to the power of the noise. First of all, we generate the training data which contains approximately 5k sub-frame in each class with the image size is 128x128 and SNR range is lower than 30db that aim optimizing calculation performance of our network. The 5G NR and LTE are distinguished by spectrum frequencies and bandwidth through Fourier transformer algorithm. The signal in high frequencies spectrum may be predicted 5G NR. By the contrast, it is predicted LTE or Noise if the spectrum frequency is unknown. There are several sample that depict for 5G NR, LTE, and noise respectively bellow.

III. PROPOSAL WIRELESS COMMUNICATION NETWORK BASE ON UNET++ ARCHITECTURE

In this paper, we introduce a new innovative deep learning network called Wireless Communication Network (WiCom-Net) base on Unet++ deep learning network [?], which is adapted by group convolution, attention gates, and atrous spatial pyramid pooling. Group convolution is applied to reduce significantly the complexity of Unet++ deep network, we divide 32 filter in a unit group convolution and double the number of group in each group convolution layer that corresponds to original Unet++ network respectively. Therefore, we not only obtain double filter in each convolution layer but also reduce complexity dramatically by applying group convolution. On the other hand, attention gates are adapted at multiple layers in decoder path that aim improving attention region in image semantic segmentation task, attention gates are combined by skip connection layers and lower layers, it retains more filter extraction and focuses on region border that help increase prediction ability of Wireless Communication Network. Furthermore, atrous spatial pyramid pooling is adapted in the latest layer with cascade hierarchical connection [?] that include four parallel convolution kernels (one 1x1 convolution and three dilated convolutions in multiple scale sizes) with 1, 2, and 3 dilated scale sizes in the first layer and 2, 6, and 5 in the second layer respectively, the concatenations are used to combine filter extractions in each layer. Additional, all layers in the encoder path are connected directly to ASSP module by skip connection that improve the number of input feature at the latest layer.

IV. SIMULATION RESULT AND EVALUATION

V. CONCLUSION

VI. PREPARE YOUR PAPER BEFORE STYLING

Before you begin to format your paper, first write and save the content as a separate text file. Complete all content and organizational editing before formatting. Please note sections ??–?? below for more information on proofreading, spelling and grammar.

Keep your text and graphic files separate until after the text has been formatted and styled. Do not number text heads— \LaTeX will do that for you.

A. Abbreviations and Acronyms

Define abbreviations and acronyms the first time they are used in the text, even after they have been defined in the abstract. Abbreviations such as IEEE, SI, MKS, CGS, ac, dc, and rms do not have to be defined. Do not use abbreviations in the title or heads unless they are unavoidable.

B. Units

- Use either SI (MKS) or CGS as primary units. (SI units are encouraged.) English units may be used as secondary units (in parentheses). An exception would be the use of English units as identifiers in trade, such as “3.5-inch disk drive”.

- Avoid combining SI and CGS units, such as current in amperes and magnetic field in oersteds. This often leads to confusion because equations do not balance dimensionally. If you must use mixed units, clearly state the units for each quantity that you use in an equation.
- Do not mix complete spellings and abbreviations of units: “Wb/m²” or “webers per square meter”, not “webers/m²”. Spell out units when they appear in text: “. . . a few henries”, not “. . . a few H”.
- Use a zero before decimal points: “0.25”, not “.25”. Use “cm³”, not “cc”.)

C. Equations

Number equations consecutively. To make your equations more compact, you may use the solidus (/), the exp function, or appropriate exponents. Italicize Roman symbols for quantities and variables, but not Greek symbols. Use a long dash rather than a hyphen for a minus sign. Punctuate equations with commas or periods when they are part of a sentence, as in:

$$a + b = \gamma \quad (1)$$

Be sure that the symbols in your equation have been defined before or immediately following the equation. Use “(??)”, not “Eq. (??)” or “equation (??)”, except at the beginning of a sentence: “Equation (??) is . . .”

D. \LaTeX -Specific Advice

Please use “soft” (e.g., `\eqref{Eq}`) cross references instead of “hard” references (e.g., (1)). That will make it possible to combine sections, add equations, or change the order of figures or citations without having to go through the file line by line.

Please don’t use the `{eqnarray}` equation environment. Use `{align}` or `{IEEEeqnarray}` instead. The `{eqnarray}` environment leaves unsightly spaces around relation symbols.

Please note that the `{subequations}` environment in \LaTeX will increment the main equation counter even when there are no equation numbers displayed. If you forget that, you might write an article in which the equation numbers skip from (17) to (20), causing the copy editors to wonder if you’ve discovered a new method of counting.

\BIBTeX does not work by magic. It doesn’t get the bibliographic data from thin air but from .bib files. If you use \BIBTeX to produce a bibliography you must send the .bib files.

\LaTeX can’t read your mind. If you assign the same label to a subsection and a table, you might find that Table I has been cross referenced as Table IV-B3.

\LaTeX does not have precognitive abilities. If you put a `\label` command before the command that updates the counter it’s supposed to be using, the label will pick up the last counter to be cross referenced instead. In particular, a `\label` command should not go before the caption of a figure or a table.

Do not use `\nonumber` inside the `{array}` environment. It will not stop equation numbers inside `{array}` (there

won't be any anyway) and it might stop a wanted equation number in the surrounding equation.

E. Some Common Mistakes

- The word “data” is plural, not singular.
- The subscript for the permeability of vacuum μ_0 , and other common scientific constants, is zero with subscript formatting, not a lowercase letter “o”.
- In American English, commas, semicolons, periods, question and exclamation marks are located within quotation marks only when a complete thought or name is cited, such as a title or full quotation. When quotation marks are used, instead of a bold or italic typeface, to highlight a word or phrase, punctuation should appear outside of the quotation marks. A parenthetical phrase or statement at the end of a sentence is punctuated outside of the closing parenthesis (like this). (A parenthetical sentence is punctuated within the parentheses.)
- A graph within a graph is an “inset”, not an “insert”. The word alternatively is preferred to the word “alternately” (unless you really mean something that alternates).
- Do not use the word “essentially” to mean “approximately” or “effectively”.
- In your paper title, if the words “that uses” can accurately replace the word “using”, capitalize the “u”; if not, keep using lower-cased.
- Be aware of the different meanings of the homophones “affect” and “effect”, “complement” and “compliment”, “discreet” and “discrete”, “principal” and “principle”.
- Do not confuse “imply” and “infer”.
- The prefix “non” is not a word; it should be joined to the word it modifies, usually without a hyphen.
- There is no period after the “et” in the Latin abbreviation “et al.”.
- The abbreviation “i.e.” means “that is”, and the abbreviation “e.g.” means “for example”.

An excellent style manual for science writers is [?].

F. Authors and Affiliations

The class file is designed for, but not limited to, six authors. A minimum of one author is required for all conference articles. Author names should be listed starting from left to right and then moving down to the next line. This is the author sequence that will be used in future citations and by indexing services. Names should not be listed in columns nor group by affiliation. Please keep your affiliations as succinct as possible (for example, do not differentiate among departments of the same organization).

G. Identify the Headings

Headings, or heads, are organizational devices that guide the reader through your paper. There are two types: component heads and text heads.

Component heads identify the different components of your paper and are not topically subordinate to each other. Examples include Acknowledgments and References and, for

these, the correct style to use is “Heading 5”. Use “figure caption” for your Figure captions, and “table head” for your table title. Run-in heads, such as “Abstract”, will require you to apply a style (in this case, italic) in addition to the style provided by the drop down menu to differentiate the head from the text.

Text heads organize the topics on a relational, hierarchical basis. For example, the paper title is the primary text head because all subsequent material relates and elaborates on this one topic. If there are two or more sub-topics, the next level head (uppercase Roman numerals) should be used and, conversely, if there are not at least two sub-topics, then no subheads should be introduced.

H. Figures and Tables

a) *Positioning Figures and Tables:* Place figures and tables at the top and bottom of columns. Avoid placing them in the middle of columns. Large figures and tables may span across both columns. Figure captions should be below the figures; table heads should appear above the tables. Insert figures and tables after they are cited in the text. Use the abbreviation “Fig. ??”, even at the beginning of a sentence.

TABLE I
TABLE TYPE STYLES

Table Head	Table Column Head		
	Table column subhead	Subhead	Subhead
copy	More table copy ^a		

^aSample of a Table footnote.



Fig. 3. Example of a figure caption.

Figure Labels: Use 8 point Times New Roman for Figure labels. Use words rather than symbols or abbreviations when writing Figure axis labels to avoid confusing the reader. As an example, write the quantity “Magnetization”, or “Magnetization, M”, not just “M”. If including units in the label, present them within parentheses. Do not label axes only with units. In the example, write “Magnetization (A/m)” or “Magnetization {A[m(1)]}”, not just “A/m”. Do not label axes with a ratio of quantities and units. For example, write “Temperature (K)”, not “Temperature/K”.

ACKNOWLEDGMENT

The preferred spelling of the word “acknowledgment” in America is without an “e” after the “g”. Avoid the stilted expression “one of us (R. B. G.) thanks ...”. Instead, try “R. B. G. thanks...”. Put sponsor acknowledgments in the unnumbered footnote on the first page.

REFERENCES

Please number citations consecutively within brackets [?]. The sentence punctuation follows the bracket [?]. Refer simply to the reference number, as in [?]¹—do not use “Ref. [?]” or “reference [?]” except at the beginning of a sentence: “Reference [?] was the first . . .”

Number footnotes separately in superscripts. Place the actual footnote at the bottom of the column in which it was cited. Do not put footnotes in the abstract or reference list. Use letters for table footnotes.

Unless there are six authors or more give all authors’ names; do not use “et al.”. Papers that have not been published, even if they have been submitted for publication, should be cited as “unpublished” [?]. Papers that have been accepted for publication should be cited as “in press” [?]. Capitalize only the first word in a paper title, except for proper nouns and element symbols.

For papers published in translation journals, please give the English citation first, followed by the original foreign-language citation [?].

REFERENCES

- [1] Huynh-The, Thien, et al. “Intelligent Spectrum Sensing with ConvNet for 5G and LTE Signals Identification.” 2023 IEEE Statistical Signal Processing Workshop (SSP). IEEE, 2023.
- [2] Nguyen, Gia-Vuong, Ca Van Phan, and Thien Huynh-The. “Accurate Spectrum Sensing with Improved DeepLabV3+ for 5G-LTE Signals Identification.” Proceedings of the 12th International Symposium on Information and Communication Technology. 2023.
- [3] Oktay, Ozan, et al. “Attention u-net: Learning where to look for the pancreas.” arXiv preprint arXiv:1804.03999 (2018).
- [4] Vaswani, Ashish, et al. “Attention is all you need.” Advances in neural information processing systems 30 (2017).
- [5] Ronneberger, Olaf, Philipp Fischer, and Thomas Brox. “U-net: Convolutional networks for biomedical image segmentation.” Medical image computing and computer-assisted intervention–MICCAI 2015: 18th international conference, Munich, Germany, October 5-9, 2015, proceedings, part III 18. Springer International Publishing, 2015.
- [6] Zhou, Zongwei, et al. “Unet++: Redesigning skip connections to exploit multiscale features in image segmentation.” IEEE transactions on medical imaging 39.6 (2019): 1856-1867.
- [7] Pirinen, Pekka. “A brief overview of 5G research activities.” 1st International Conference on 5G for Ubiquitous Connectivity. IEEE, 2014.
- [8] Lin, Xingqin, and Namyoon Lee. “5G and Beyond.” Cham, Switzerland: Springer Nature Switzerland AG (2021).
- [9] Krizhevsky, Alex, Ilya Sutskever, and Geoffrey E. Hinton. “Imagenet classification with deep convolutional neural networks.” Advances in neural information processing systems 25 (2012).
- [10] Lan, K., Cheng, J., Jiang, J., Jiang, X., Zhang, Q. (2023). Modified UNet++ with atrous spatial pyramid pooling for blood cell image segmentation. Mathematical biosciences and engineering: MBE, 20(1), 1420-1433.
- [11] Lian, X., Pang, Y., Han, J., Pan, J. (2021). Cascaded hierarchical atrous spatial pyramid pooling module for semantic segmentation. Pattern Recognition, 110, 107622.

IEEE conference templates contain guidance text for composing and formatting conference papers. Please ensure that all template text is removed from your conference paper prior to submission to the conference. Failure to remove the template text from your paper may result in your paper not being published.