Name :- Aaryan N. Raorane Roll no :- 5004 Div :- 5
branch :- AI & DS SAP ID :- 60018250070

accepted

Experiment No 4

1) Select :

```
select column1,column2
from table_name;
```

Retrieves selected columns from a table

2) where :

```
Select *
from tablename
where condition;
```

filters rows according to a condition

3) Comparison Operators :

```
select *
from tablename
where column_name operator values
```

operators => =, >, <, >=, <= and !=
filters using the above operators

4) AND :

```
select * from tablename
where condition1 AND condition2;
```

returns the row satisfying both conditions.

Sundaram
FOR EDUCATIONAL USE

5) OR :-

```
Select *
from tablename
where condition1 OR condition2;
```

returns rows satisfying at least one condition

6) NOT :-

```
select *
from tablename
where not condition;
```

returns rows that do not satisfy the condition.

7) Between :-

```
select *
from tablename
where columnname Between value1 and value2;
```

selects values within an inclusive range.

8) IN :-

```
select *
from tablename
where columnname IN (value1, value2, value3);
```

checks whether a column matches any value from a list

Sundaram
FOR EDUCATIONAL USE

9) Not In :-

```
select *
from tablename
where columnname Not In (value1, value2);
```

Selects rows whose column value is not in the specified list.

10) Like :-

```
select *
from tablename
where columnname Like pattern;
```

Searches text using pattern; % represents zero or more characters and _ represent one character

11) distinct :-

```
select distinct columnname
from tablename;
```

returns only unique values from a column.

12) Aggregate functions :-

```
select aggregate function(column name)
from tablename.
```

Sundaram
FOR EDUCATIONAL USE

calculates a summary using functions such as count(), sum(), avg(), Min(), or Max().

13) count :

```
select count(column name)
from tablename;
```

counts non-NULL values in a column

14) sum :

```
select sum(column name)
from tablename;
```

calculates the total of numeric values.

15) avg :

```
select avg(column name)
from tablename;
```

calculates the average of numeric values

16) Min :

```
select Min(column name)
from tablename;
```

returns the smallest value in a column

Sundaram
FOR EDUCATIONAL USE

17) Max:

```
select Max(column_name)
from table_name;
```

returns the largest value in a column.

18) Group by:

```
select column_name, count(*)
from table_name
Group by column_name;
```

Groups rows with same value and calculates a summary for each group.

19) Having:

```
select column_name, count(*)
from table_name
Group by column_name
having count(*) >= 2;
```

filters groups after Group by has been applied

20) AS alias:

```
Select column_name AS alias_name from table_name;
```

Give a temporary name to a column in the query result.

Sundaram
FOR EDUCATIONAL USE

21) Order By :

```
Select *
from tablename
order by column_name ;
```

sorts the result in ascending order by default

```
select *
from tablename
order by column_name DESC ;
```

sorts the result in descending order.

Sundaram FOR EDUCATIONAL USE