



Bonetrousle

by [robinyu](#)

Problem

Submissions

Leaderboard

Discussions

Editorial

Here's a *humerus* joke:

Why did Papyrus the skeleton go to the store by himself? Because he had *no body* to go with him!

Did you like it? Don't worry, I've got a ton more. A skele-*ton*.

Once upon a time, Papyrus the skeleton went to buy some pasta from the store. The store's inventory is *bare-bones* and they only sell one thing — boxes of uncooked spaghetti! The store always stocks exactly k boxes of pasta, and each box is numbered sequentially from 1 to k . This box number also corresponds to the number of sticks of spaghetti in the box, meaning the first box contains 1 stick, the second box contains 2 sticks, the third box contains 3 sticks, ..., and the k^{th} box contains k sticks. Because they only stock one box of each kind, the store has a *tendon*-cy to sell out of spaghetti.

During each trip to the store, Papyrus likes to buy exactly n sticks of spaghetti by purchasing exactly b boxes (no more, no less). Not sure *which* boxes to purchase, Papyrus calls *Sherlock Bones* for help but he's also stumped! Do you have the *guts* to solve this puzzle?

Given the values of n , k , and b for t trips to the store, determine which boxes Papyrus must purchase during each trip. For each trip, print a single line of b distinct space-separated integers denoting the box number for each box of spaghetti Papyrus purchases (recall that the store only has *one* box of each kind). If it's not possible to buy n sticks of spaghetti by purchasing b boxes, print -1 instead.

Input Format

The first line contains a single integer, t , denoting the number of trips to the store.

Each of the t subsequent lines describes a trip to the store in the form of three space-separated integers describing the respective values of n (the number of sticks to buy), k (the number of boxes the store has for sale), and b (the number of boxes to buy) for that trip to the store.

Constraints

- $1 \leq t \leq 20$
- $1 \leq b \leq 10^5$
- $1 \leq n \leq 10^{18}$
- $1 \leq k \leq 10^{18}$
- $b \leq k$

Output Format

For each trip to the store:

- If there is no solution, print -1 on a new line.
- Otherwise, print a single line of b distinct space-separated integers where each integer denotes the box number (i.e., the number of spaghetti sticks in the box) that Papyrus must purchase.

If there are multiple possible solutions, *you can print any one of them*. Do not print any leading or trailing spaces.

Sample Input

```

4
12 8 3
10 3 3
9 10 2
9 10 2

```

Sample Output

```

2 3 7
-1
5 4
1 8

```

Explanation

Papyrus makes the following trips to the store:

1. He wants to buy exactly $b = 3$ boxes of spaghetti and have a total number of $n = 12$ sticks. During this trip, the store has $k = 8$ boxes of spaghetti sticks where the first box has 1 stick, the second box has 2 sticks, the third box has 3 sticks, and so on. One possible solution would be the following:



Papyrus can buy the 2-stick, 3-stick, and 7-stick boxes for the total of $2 + 3 + 7 = 12$ sticks. *Note that this is not the only valid solution; other valid solutions are acceptable.*

2. He wants to buy exactly $b = 3$ boxes of spaghetti and have a total number of $n = 10$ sticks. Because the store only has three boxes in stock containing 1, 2, and 3 sticks of spaghetti, it's not possible for Papyrus to buy n sticks of spaghetti as buying all three boxes would only yield $1 + 2 + 3 = 6$ sticks (which is less than the $n = 10$ that he wanted to purchase). Thus, we print -1 on a new line.
3. The third and fourth trips to the store both contain the same values ($n = 9$, $k = 10$, $b = 2$); this is simply to illustrate that there may be multiple solutions for any given trip to the store and any valid solution is acceptable.

f t in

Solved score: 50.00pts

Submissions: 3394

Max Score: 50

Difficulty: Medium

Rate This Challenge:

☆☆☆☆☆

[More](#)

Current Buffer (saved locally, editable)

Java 7



```

1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8
9     public static void main(String[] args) {
10         /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class should be named Solution. */
11     }
12 }

```

Line: 1 Col: 1

 [Upload Code as File](#)☐ Test against custom input[Run Code](#)[Submit Code](#)

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)