



# Array Construction

by allllekssssa

Problem

Submissions

Leaderboard

Discussions

Editorial

Professor GukiZ has hobby — constructing different arrays. His best student, Nenad, gave him the following task that he just can't manage to solve:

Construct an  $n$ -element array,  $A$ , where the sum of all elements is equal to  $s$  and the sum of absolute differences between each pair of elements is equal to  $k$ . All elements in  $A$  must be non-negative integers.

$$A_0 + A_1 + \dots + A_{n-1} = s$$

$$\sum_{i=0}^{n-1} \sum_{j=i}^{n-1} |A_i - A_j| = k$$

If there is more than one such array, you need to find the lexicographically smallest one. In the case no such array  $A$  exists, print  $-1$ .

**Note:** An array,  $A$ , is considered to be lexicographically smaller than another array,  $B$ , if there is an index  $i$  such that  $A_i < B_i$  and, for any index  $j < i$ ,  $A_j = B_j$ .

## Input Format

The first line contains an integer,  $q$ , denoting the number of queries.

Each of the  $q$  subsequent lines contains three space-separated integers describing the respective values of  $n$  (the number of elements in array  $A$ ),  $s$  (the sum of elements in  $A$ ), and  $k$  (the sum of absolute differences between each pair of elements).

## Constraints

- $1 \leq q \leq 100$
- $1 \leq n \leq 50$
- $0 \leq s \leq 200$
- $0 \leq k \leq 2000$

## Subtasks

For 10% of the maximum score:

- $1 \leq q \leq 10$
- $1 \leq n \leq 5$
- $0 \leq s \leq 10$
- $0 \leq k \leq 20$

For 50% of the maximum score:

- $1 \leq q \leq 10$
- $1 \leq n \leq 50$
- $0 \leq s \leq 100$
- $0 \leq k \leq 500$

**Output Format**

For each query, print  $n$  space-separated integers describing the respective elements of the lexicographically smallest array  $A$  satisfying the conditions given above. If no such array exists, print  $-1$  instead.

**Sample Input**

```
1
3 3 4
```

**Sample Output**

```
0 1 2
```

**Explanation**

We have  $q = 1$  query in which  $n = 3$ ,  $s = 3$ , and  $k = 4$ . The lexicographically smallest array is  $A = [0, 1, 2]$ .

- The sum of array  $A$ 's elements is  $0 + 1 + 2 = 3 \equiv s$
- The absolute differences between each pair of elements are:  
 $|A_0 - A_1| = 1$   
 $|A_0 - A_2| = 2$   
 $|A_1 - A_2| = 1$

The sum of these absolute differences is  $1 + 1 + 2 = 4 \equiv k$

As array  $A$  is both lexicographically smallest and satisfies the given conditions, we print its contents on a new line as `0 1 2`.

[f](#) [t](#) [in](#)

Submissions: [400](#)

Max Score: 80

Difficulty: Advanced

Rate This Challenge:

☆☆☆☆☆

[More](#)

Current Buffer (saved locally, editable) [🔗](#) [🔄](#)

Java 7



```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8
9     public static void main(String[] args) {
10         /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class should be named Solution. */
11     }
12 }
```

Line: 1 Col: 1

[📁 Upload Code as File](#) ☐ Test against custom input

Run Code

Submit Code

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)