



Yet Another KMP Problem

by Stonefeang

Problem

Submissions

Leaderboard

Discussions

Editorial

This challenge uses the famous [KMP algorithm](#). It isn't really important to understand how KMP works, but you should understand what it calculates.

A KMP algorithm takes a string, S , of length N as input. Let's assume that the characters in S are indexed from 1 to N ; for every prefix of S , the algorithm calculates the length of its longest valid [border](#) in linear complexity. In other words, for every i (where $1 \leq i \leq N$) it calculates the largest l (where $0 \leq l \leq i - 1$) such that for every p (where $1 \leq p \leq l$) there is $S[p] = S[i - l + p]$.

Here is an implementation example of KMP:

```
kmp[1] = 0;
for (i = 2; i <= N; i = i + 1){
    l = kmp[i - 1];
    while (l > 0 && S[i] != S[l + 1]){
        l = kmp[l];
    }
    if (S[i] == S[l + 1]){
        kmp[i] = l + 1;
    }
    else{
        kmp[i] = 0;
    }
}
```

Given a sequence x_1, x_2, \dots, x_{26} , construct a string, S , that meets the following conditions:

1. The frequency of letter 'a' in S is exactly x_1 , the frequency of letter 'b' in S is exactly x_2 , and so on.
2. Let's assume characters of S are numbered from 1 to N , where $\sum_{i=1}^n x_i = N$. We apply the KMP algorithm to S and get a table, kmp , of size N . You must ensure that the sum of $kmp[i]$ for all i is minimal.

If there are multiple strings which fulfill the above conditions, print the [lexicographically](#) smallest one.

Input Format

A single line containing **26** space-separated integers describing sequence x .

Constraints

- The sum of all x_i will be a positive integer $\leq 10^6$.

Output Format

Print a single string denoting S .

Sample Input

```
2 2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
```

Sample Output

aabb

Explanation

The output string must have two 'a' and two 'b'. There are several such strings but we must ensure that sum of $kmp[i]$ for all $1 \leq i \leq 4$ is minimal. See the figure below:

kmp table for s="aabb"	kmp table for s="bbaa"	kmp table for s="abba"
1	1	1
2	1	0
3	0	0
4	0	1
sum = 1	sum = 1	sum = 1

kmp table for s="baba"	kmp table for s="abab"	kmp table for s="baab"
1	1	1
2	0	0
3	1	0
4	2	1
sum = 3	sum = 3	sum = 1

The minimum sum is 1. Among all the strings that satisfy both the condition, "aabb" is the lexicographically smallest.

[f](#) [t](#) [in](#)

Submissions: 983

Max Score: 60

Difficulty: Hard

Rate This Challenge:

☆☆☆☆☆

[More](#)Current Buffer (saved locally, editable)  

Java 7



```

1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8
9     public static void main(String[] args) {
10         /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class should be named Solution. */
11     }
12 }

```

Line: 1 Col: 1

 [Upload Code as File](#)
☐ Test against custom input
[Run Code](#)[Submit Code](#)

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)