



Bike Racers

by [amititkgp](#)

Problem

Submissions

Leaderboard

Discussions

Editorial

Topics

[Chinese Version](#)[Russian Version](#)

There are N bikers present in a city (shaped as a grid) having M bikes. All the bikers want to participate in the HackerRace competition, but unfortunately only K bikers can be accommodated in the race. Jack is organizing the HackerRace and wants to start the race as soon as possible. He can instruct any biker to move towards any bike in the city. In order to minimize the time to start the race, Jack instructs the bikers in such a way that the first K bikes are acquired in the minimum time.

Every biker moves with a unit speed and one bike can be acquired by only one biker. *A biker can proceed in any direction.* Consider distance between bikes and bikers as Euclidean distance.

Jack would like to know the *square of required time* to start the race as soon as possible.

Input Format

The first line contains three integers, N , M , and K , separated by a single space.

The following N lines will contain N pairs of integers denoting the co-ordinates of N bikers. Each pair of integers is separated by a single space. The next M lines will similarly denote the co-ordinates of the M bikes.

Constraints

$$1 \leq N \leq 250$$

$$1 \leq M \leq 250$$

$$1 \leq K \leq \min(N, M)$$

$$0 \leq x_i, y_i \leq 10^7$$

Output Format

A single line containing the square of required time.

Sample Input

```
3 3 2
0 1
0 2
0 3
100 1
200 2
300 3
```

Sample Output

```
40000
```

Explanation

There's need for two bikers for the race. The first biker (0,1) will be able to reach the first bike (100,1) in 100 time units. The second biker (0,2) will be able to reach the second bike (200,2) in 200 time units. This is the most optimal solution and will take 200 time units. So output will be $200^2 = 40000$.

Submissions: [1405](#)

Max Score: 65

Difficulty: Hard

Rate This Challenge:



Need Help?

[Binary Search](#)[More](#)

Current Buffer (saved locally, editable)  

Java 7  

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8
9     public static void main(String[] args) {
10         /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class should be named Solution. */
11     }
12 }
```

Line: 1 Col: 1

 [Upload Code as File](#)☐ Test against custom input[Run Code](#)[Submit Code](#)Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)