



Palindromic Border

by enesoncu

Problem

Submissions

Leaderboard

Discussions

Editorial

A **border** of a string is a [proper](#) prefix of it that is also a suffix. For example:

- a and abra are borders of abracadabra ,
- kan and kankan are borders of kankankan .
- de is a border of decode .

Note that decode is not a border of decode because it's not proper.

A **palindromic border** is a border that is palindromic. For example,

- a and ana are palindromic borders of anabanana ,
- 1, lol and lolol are palindromic borders of lololol .

Let's define $P(s)$ as the number of palindromic borders of string s . For example, if $s = lololol$, then $P(s) = 3$.

Now, a string of length N has exactly $N(N+1)/2$ non-empty substrings (we count substrings as distinct if they are of different lengths or are in different positions, even if they are the same string). Given a string s , consisting only of the first 8 lowercase letters of the English alphabet, your task is to find the sum of $P(s')$ for all the non-empty substrings s' of s . In other words, you need to find:

$$\sum_{1 \leq i \leq j \leq N} P(s_{i..j})$$

where $s_{i..j}$ is the substring of s starting at position i and ending at position j .

Since the answer can be very large, output the answer modulo $10^9 + 7$.

Input Format

The first line contains a string consisting of N characters.

Output Format

Print a single integer: the remainder of the division of the resulting number by $10^9 + 7$.

Constraints

$$1 \leq N \leq 10^5$$

All characters in the string can be any of the first 8 lowercase letters of the English alphabet (abcdefgh).

Sample Input 1

```
ababa
```

Sample Output 1

```
5
```

Sample Input 2

aaaa

Sample Output 2

10

Sample Input 3

abcacb

Sample Output 3

3

Explanation

$s = \text{ababa}$ has 15 substrings but only 4 substrings have palindromic borders.

$s_{1..3} = \text{aba} \rightarrow P(s_{1..3}) = 1$

$s_{1..5} = \text{ababa} \rightarrow P(s_{1..5}) = 2$

$s_{2..4} = \text{bab} \rightarrow P(s_{2..4}) = 1$

$s_{3..5} = \text{aba} \rightarrow P(s_{3..5}) = 1$

[f](#) [t](#) [in](#)



Submissions: 718

Max Score: 100

Difficulty: Expert

Rate This Challenge:

☆☆☆☆☆

[More](#)Current Buffer (saved locally, editable)  

Java 7



```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8
9     public static void main(String[] args) {
10         /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class should be named Solution. */
11     }
12 }
```

Line: 1 Col: 1

 Upload Code as File☐ Test against custom input

Run Code

Submit Code

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)