



Quicksort 1 - Partition



Problem

Submissions

Leaderboard

Discussions

The previous challenges covered [Insertion Sort](#), which is a simple and intuitive sorting algorithm with an average case performance of $O(n^2)$. In these next few challenges, we're covering a *divide-and-conquer* algorithm called [Quicksort](#) (also known as *Partition Sort*).

Step 1: Divide

Choose some pivot element, p , and partition your unsorted array, ar , into three smaller arrays: *left*, *right*, and *equal*, where each element in *left* $< p$, each element in *right* $> p$, and each element in *equal* $= p$.

Challenge

Given ar and $p = ar[0]$, partition ar into *left*, *right*, and *equal* using the *Divide* instructions above. Then print each element in *left* followed by each element in *equal*, followed by each element in *right* on a single line. Your output should be space-separated.

Note: There is no need to sort the elements *in-place*; you can create two lists and stitch them together at the end.

Input Format

The first line contains n (the size of ar).

The second line contains n space-separated integers describing ar (the unsorted array). The first integer (corresponding to $ar[0]$) is your pivot element, p .

Constraints

- $1 \leq n \leq 1000$
- $-1000 \leq x \leq 1000, x \in ar$
- All elements will be unique.
- Multiple answer can exists for the given test case. Print any one of them.

Output Format

On a single line, print the partitioned numbers (i.e.: the elements in *left*, then the elements in *equal*, and then the elements in *right*). Each integer should be separated by a single space.

Sample Input

```
5
4 5 3 7 2
```

Sample Output

```
3 2 4 5 7
```

Explanation

$ar = [4, 5, 3, 7, 2]$

Pivot: $p = ar[0] = 4$.

$left = \{ \}; equal = \{4\}; right = \{ \}$

$ar[1] = 5 \geq p$, so it's added to *right*.

$left = \{\}$; $equal = \{4\}$; $right = \{5\}$

$ar[2] = 3 < p$, so it's added to *left*.

$left = \{3\}$; $equal = \{4\}$; $right = \{5\}$

$ar[3] = 7 \geq p$, so it's added to *right*.

$left = \{3\}$; $equal = \{4\}$; $right = \{5, 7\}$

$ar[4] = 2 < p$, so it's added to *left*.

$left = \{3, 2\}$; $equal = \{4\}$; $right = \{5, 7\}$

We then print the elements of *left*, followed by *equal*, followed by *right*, we get: 3 2 4 5 7.

This example is only one correct answer based on the implementation shown, but it is not the only correct answer (e.g.: another valid solution would be 2 3 4 5 7).

f t in

Solved score: 10.00pts

Submissions: 47393

Max Score: 10

Difficulty: Easy

Rate This Challenge:

☆☆☆☆☆

[More](#)

Current Buffer (saved locally, editable)  

Java 7



```
1 import java.util.*;
2 public class Solution {
3
4     static void partition(int[] ar) {
5
6     }
7
8     static void printArray(int[] ar) {
9         for(int n: ar){
10             System.out.print(n+ " ");
11         }
12         System.out.println("");
13     }
14
15     public static void main(String[] args) {
16         Scanner in = new Scanner(System.in);
17         int n = in.nextInt();
18         int[] ar = new int[n];
19         for(int i=0;i<n;i++){
20             ar[i]=in.nextInt();
21         }
22         partition(ar);
23     }
24 }
25
```

Line: 1 Col: 1

 [Upload Code as File](#) ☐ Test against custom input

Run Code

Submit Code

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)