



Game of Two Stacks

by Shafaet

Problem

Submissions

Leaderboard

Discussions

Editorial

Alexa has two stacks of non-negative integers, stack $A = [a_0, a_1, \dots, a_{n-1}]$ and stack $B = [b_0, b_1, \dots, b_{m-1}]$ where index 0 denotes the top of the stack. Alexa challenges Nick to play the following game:

- In each move, Nick can remove one integer from the top of either stack A or stack B .
- Nick keeps a running sum of the integers he removes from the two stacks.
- Nick is disqualified from the game if, at any point, his running sum becomes greater than some integer x given at the beginning of the game.
- Nick's *final score* is the total number of integers he has removed from the two stacks.

Given A , B , and x for g games, find the maximum possible score Nick can achieve (i.e., the maximum number of integers he can remove without being disqualified) during each game and print it on a new line.

Input Format

The first line contains an integer, g (the number of games). The $3 \cdot g$ subsequent lines describe each game in the following format:

- The first line contains three space-separated integers describing the respective values of n (the number of integers in stack A), m (the number of integers in stack B), and x (the number that the sum of the integers removed from the two stacks cannot exceed).
- The second line contains n space-separated integers describing the respective values of a_0, a_1, \dots, a_{n-1} .
- The third line contains m space-separated integers describing the respective values of b_0, b_1, \dots, b_{m-1} .

Constraints

- $1 \leq g \leq 50$
- $1 \leq n, m \leq 10^5$
- $0 \leq a_i, b_j \leq 10^6$
- $1 \leq x \leq 10^9$

Subtasks

- $1 \leq n, m \leq 100$ for 50% of the maximum score.

Output Format

For each of the g games, print an integer on a new line denoting the maximum possible score Nick can achieve without being disqualified.

Sample Input 0


```
1
5 4 10
4 2 4 6 1
2 1 8 5
```

Sample Output 0


4

Explanation 0

The two stacks initially look like this:



The image below depicts the integers Nick should choose to remove from the stacks. We print 4 as our answer, because that is the maximum number of integers that can be removed from the two stacks without the sum exceeding $x = 10$.



(There can be multiple ways to remove the integers from the stack, the image shows just one of them.)

f t in

Submissions:5769

Max Score:30

Difficulty: Medium

Rate This Challenge:

☆☆☆☆☆

More

Current Buffer (saved locally, editable)

C++

```
1 #include <bits/stdc++.h>
2
3 using namespace std;
4
5 int main(){
6     int g;
7     cin >> g;
8     for(int a0 = 0; a0 < g; a0++){
9         int n;
10        int m;
11        int x;
12        cin >> n >> m >> x;
13        vector<int> a(n);
14        for(int a_i = 0; a_i < n; a_i++){
15            cin >> a[a_i];
16        }
17        vector<int> b(m);
18        for(int b_i = 0; b_i < m; b_i++){
19            cin >> b[b_i];
20        }
21        // your code goes here
22    }
23    return 0;
```

```
24 }  
25
```

Line: 1 Col: 1

 [Upload Code as File](#)☐ Test against custom input

Run Code

Submit Code

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)