



Kitty's Calculations on a Tree

by ma5termind

Problem

Submissions

Leaderboard

Discussions

Editorial

Kitty has a tree, T , consisting of n nodes where each node is uniquely labeled from 1 to n . Her friend Alex gave her q sets, where each set contains k distinct nodes. Kitty needs to calculate the following expression on each set:

$$\left(\sum_{\{u,v\}} u \cdot v \cdot \text{dist}(u,v) \right) \bmod (10^9 + 7)$$

where:

- $\{u,v\}$ denotes an unordered pair of nodes belonging to the set.
- $\text{dist}(u,v)$ denotes the number of edges on the unique path between nodes u and v .

Given T and q sets of k distinct nodes, can you help her calculate the expression for each set? For each set of nodes, print the value of the expression modulo $10^9 + 7$ on a new line.

Input Format

The first line contains two space-separated integers describing the respective values of n (the number of nodes in tree T) and q (the number of sets). Each of the $n - 1$ subsequent lines contains two space-separated integers, a and b , describing an *undirected* edge between nodes a and b . The $2 \cdot q$ subsequent lines define each set over two lines in the following format:

- The first line contains an integer, k , denoting the size of the set.
- The second line contains k space-separated integers describing the set's elements.

Constraints

- $1 \leq n \leq 2 \cdot 10^5$
- $1 \leq a, b \leq n$
- $1 \leq q \leq 10^5$
- $1 \leq k_i \leq 10^5$
- The sum of k_i over all q does not exceed $2 \cdot 10^5$.
- All elements in each set are *distinct*.

Subtasks

- $1 \leq n \leq 2000$ for 24% of the maximum score.
- $1 \leq n \leq 5 \cdot 10^4$ for 45% of the maximum score.
- $1 \leq n \leq 2 \cdot 10^5$ for 100% of the maximum score.

Output Format

Print q lines of output where each line i contains the expression for the i^{th} query, modulo $10^9 + 7$.

Sample Input 0

```

7 3
1 2
1 3
1 4
3 5
3 6
3 7
2
2 4
1
5
3
2 4 5

```

Sample Output 0


```

16
0
106

```

Explanation 0

Tree T looks like this:



We perform the following calculations for $q = 3$ sets:

- Set 0: Given set $\{2, 4\}$, the only pair we can form is $(u, v) = (2, 4)$, where $\text{dist}(2, 4) = 2$. We then calculate the following answer and print it on a new line:

$$\begin{aligned}
 & (2 \cdot 4 \cdot \text{dist}(2, 4)) \bmod (10^9 + 7) \\
 & \Rightarrow (2 \cdot 4 \cdot 2) \bmod (10^9 + 7) \\
 & \Rightarrow 16
 \end{aligned}$$

- Set 1: Given set $\{5\}$, we cannot form any pairs because we don't have at least two elements. Thus, we print 0 on a new line.
- Set 2: Given set $\{2, 4, 5\}$, we can form the pairs $(2, 4)$, $(2, 5)$, and $(4, 5)$. We then calculate the following answer and print it on a new line:

$$\begin{aligned}
 & (2 \cdot 4 \cdot \text{dist}(2, 4) + 2 \cdot 5 \cdot \text{dist}(2, 5) + 4 \cdot 5 \cdot \text{dist}(4, 5)) \bmod (10^9 + 7) \\
 & \Rightarrow (2 \cdot 4 \cdot 2 + 2 \cdot 5 \cdot 3 + 4 \cdot 5 \cdot 3) \bmod (10^9 + 7) \\
 & \Rightarrow 106
 \end{aligned}$$

f t in

Submissions: 616



Max Score: 80

Difficulty: Advanced

Rate This Challenge:

☆☆☆☆☆

[More](#)

Current Buffer (saved locally, editable)  

C++



```
1 #include <cmath>
```

```
2 #include <cstdio>
3 #include <vector>
4 #include <iostream>
5 #include <algorithm>
6 using namespace std;
7
8
9 int main() {
10     /* Enter your code here. Read input from STDIN. Print output to STDOUT */
11     return 0;
12 }
13
```

Line: 1 Col: 1

 [Upload Code as File](#)☐ Test against custom input

Run Code

Submit Code

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)