



Polynomial Division

by [zemen](#)

Problem

Submissions

Leaderboard

Discussions

Editorial

Consider a sequence, c_0, c_1, \dots, c_{n-1} , and a polynomial of degree 1 defined as $Q(x) = a \cdot x + b$. You must perform q queries on the sequence, where each query is one of the following two types:

- 1 i x: Replace c_i with x .
- 2 l r: Consider the polynomial $P(x) = c_l \cdot x^0 + c_{l+1} \cdot x^1 + \dots + c_r \cdot x^{r-l}$ and determine whether $P(x)$ is divisible by $Q(x) = a \cdot x + b$ over the field \mathbb{Z}_p , where $p = 10^9 + 7$. In other words, check if there exists a polynomial $R(x)$ with integer coefficients such that each coefficient of $P(x) - R(x) \cdot Q(x)$ is divisible by p . If a valid $R(x)$ exists, print **Yes** on a new line; otherwise, print **No**.

Given the values of n , a , b , and q queries, perform each query in order.

Input Format

The first line contains four space-separated integers describing the respective values of n (the length of the sequence), a (a coefficient in $Q(x)$), b (a coefficient in $Q(x)$), and q (the number of queries).

The second line contains n space-separated integers describing c_0, c_1, \dots, c_{n-1} .

Each of the q subsequent lines contains three space-separated integers describing a query of either type 1 or type 2.

Constraints

- $1 \leq n, q \leq 10^5$
- For query type 1: $0 \leq i \leq n - 1$ and $0 \leq x < 10^9 + 7$.
- For query type 2: $0 \leq l \leq r \leq n - 1$.
- $0 \leq a, b, c_i < 10^9 + 7$
- $a \neq 0$

Output Format

For each query of type 2, print **Yes** on a new line if $Q(x)$ is a divisor of $P(x)$; otherwise, print **No** instead.

Sample Input 0

```
3 2 2 3
1 2 3
2 0 2
1 2 1
2 0 2
```

Sample Output 0

```
No
Yes
```

Explanation 0

Given $Q(x) = 2 \cdot x + 2$ and the initial sequence $c = \{1, 2, 3\}$, we perform the following $q = 3$ queries:

1. $Q(x) = 2 \cdot x + 2$ is not a divisor of $P(x) = 1 + 2 \cdot x + 3 \cdot x^2$, so we print No on a new line.
2. Set c_2 to 1, so $c = \{1, 2, 1\}$.
3. After the second query, $P(x) = 1 + 2 \cdot x + 1 \cdot x^2$. Because $(2 \cdot x + 2) \cdot (500000004 \cdot x + 500000004) \bmod (10^9 + 7) = 1 + 2 \cdot x + 1 \cdot x^2 = P(x)$, we print Yes on a new line.

f t in

Submissions: [41](#)



Max Score: 60

Difficulty: Hard

Rate This Challenge:

☆☆☆☆☆

[More](#)

Current Buffer (saved locally, editable)  

Java 7



```

1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6
7 public class Solution {
8
9     public static void main(String[] args) {
10         Scanner in = new Scanner(System.in);
11         int n = in.nextInt();
12         int a = in.nextInt();
13         int b = in.nextInt();
14         int q = in.nextInt();
15         int[] c = new int[n];
16         for(int c_i=0; c_i < n; c_i++){
17             c[c_i] = in.nextInt();
18         }
19         for(int a0 = 0; a0 < q; a0++){
20             int queryType = in.nextInt();
21             int first = in.nextInt();
22             int second = in.nextInt();
23             // your code goes here
24         }
25     }
26 }
27

```

Line: 1 Col: 1

 [Upload Code as File](#) ☐ Test against custom input

Run Code

Submit Code

Join us on IRC at [#hackerrank](#) on freenode for hugs or bugs.

[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)