

Next.js API Routes · Supabase · HL7 FHIR R4
Satu Sehat Integration — Kementerian Kesehatan RI

Version 1.0 · April 2026

Overview

This document is the complete API specification for the SIMRS EHR backend. It covers all endpoints organized by module, including URL, HTTP method, request parameters, response shape, authentication requirements, and integration notes with the Satu Sehat FHIR API.

15 API Sections	60+ Endpoints	Next.js App Router	Supabase DB + Auth
-----------------	---------------	--------------------	--------------------

Contents

Architecture & File Structure	
Authentication & Security	
Standard Response Format	
Error Codes	
1. Authentication	/api/auth
2. CMS — Organization	/api/cms
3. Patients	/api/patients
4. Appointments & Online Booking	/api/appointments
5. Queue Management	/api/queue
6. Encounters	/api/encounters
7. Clinical Records	/api/clinical
8. Emergency (IGD)	/api/emergency
9. Inpatient (Rawat Inap)	/api/inpatient
10. Surgery (Operasi / OK)	/api/surgery
11. Laboratory	/api/lab
12. Nutrition (Gizi)	/api/nutrition
13. Pharmacy	/api/pharmacy
14. Purchase Orders	/api/purchase-orders
15. Billing & Invoicing	/api/billing

Architecture & File Structure

Next.js App Router

Technology Stack

Framework	Next.js 14+ (App Router) — API routes in app/api/*/route.ts
Database	Supabase (PostgreSQL 15) — with Row Level Security enabled
Authentication	Supabase Auth — email/password, session via httpOnly cookie
FHIR Client	Custom fetch wrapper in lib/satusehat/ — auto-refresh OAuth token
Validation	Zod — all request bodies validated before DB operations
Types	Auto-generated via: npx supabase gen types typescript --project-id ...

Project File Structure

SIMRS Backend uses Next.js API Routes (App Router) with Supabase as the database and auth provider.

Directory Structure:

```
/
├── app/
│   └── api/
│       ├── auth/
│       │   ├── login/route.ts
│       │   ├── logout/route.ts
│       │   └── me/route.ts
│       ├── cms/
│       │   └── organization/route.ts
│       ├── patients/
│       │   ├── route.ts           (GET list, POST create)
│       │   └── [id]/route.ts      (GET, PUT, DELETE)
│       ├── appointments/
│       │   ├── route.ts
│       │   ├── [id]/route.ts
│       │   └── slots/route.ts
│       ├── queue/
│       │   ├── route.ts
│       │   ├── [id]/route.ts
│       │   └── display/route.ts    (public - queue screen)
│       ├── encounters/
│       │   ├── route.ts
│       │   └── [id]/route.ts
│       ├── clinical/
│       │   ├── vital-signs/route.ts
│       │   ├── diagnoses/route.ts
│       │   ├── procedures/route.ts
│       │   ├── notes/route.ts     (CPPT)
│       │   ├── allergies/route.ts
│       │   └── resume/route.ts
│       ├── inpatient/
│       │   ├── admissions/route.ts
│       │   ├── admissions/[id]/route.ts
│       │   └── running-bill/route.ts
│       └── emergency/
```

```

■   ■   ■   route.ts
■   ■   ■   [id]/route.ts
■   ■   surgery/
■   ■   ■   route.ts
■   ■   ■   [id]/route.ts
■   ■   lab/
■   ■   ■   orders/route.ts
■   ■   ■   orders/[id]/route.ts
■   ■   ■   orders/[id]/results/route.ts
■   ■   nutrition/
■   ■   ■   orders/route.ts
■   ■   pharmacy/
■   ■   ■   medications/route.ts
■   ■   ■   stock/route.ts
■   ■   ■   prescriptions/route.ts
■   ■   ■   dispense/route.ts
■   ■   purchase-orders/
■   ■   ■   route.ts
■   ■   ■   [id]/route.ts
■   ■   billing/
■   ■   ■   invoices/route.ts
■   ■   ■   invoices/[id]/route.ts
■   ■   ■   running-bill/route.ts
■   lib/
■   ■   supabase/
■   ■   ■   server.ts           (createServerClient for API routes)
■   ■   ■   client.ts         (createBrowserClient for frontend)
■   ■   ■   middleware.ts     (session refresh middleware)
■   ■   satusihat/
■   ■   ■   auth.ts           (token management)
■   ■   ■   client.ts         (base fetch wrapper)
■   ■   ■   resources/        (one file per FHIR resource)
■   ■   ■   sync.ts           (sync queue processor)
■   ■   ■   utils/
■   ■   ■   ■   response.ts    (standard API response helpers)
■   ■   ■   ■   validate.ts    (zod schema validation)
■   ■   ■   ■   errors.ts      (error handler)
■   ■   middleware.ts         (Next.js middleware - auth guard)
■   ■   types/
■   ■   ■   database.ts        (Supabase generated types)
■   ■   ■   api.ts             (request/response types)

```

Key File Conventions

app/api/[resource]/route.ts	Handles collection: GET (list) + POST (create)
app/api/[resource]/[id]/route.ts	Handles single item: GET + PUT/PATCH + DELETE
lib/supabase/server.ts	createServerClient() — uses cookies for session. Used in all API routes
lib/supabase/client.ts	createBrowserClient() — used in React components for real-time subscriptions
middleware.ts	Refreshes session on every request. Protects routes requiring authentication
lib/satusihat/client.ts	Wrapper for all Satu Sehat FHIR API calls with token auto-refresh
lib/utils/response.ts	apiSuccess(), apiError() helpers for consistent JSON responses
types/database.ts	Auto-generated by: <code>npx supabase gen types typescript --project-id YOUR_ID</code>

Authentication & Security

Supabase Auth + RLS

All protected routes require a valid Supabase session token passed as a Bearer token in the Authorization header, or via the session cookie set during login. The server reads the user's role from the practitioners table using `auth.uid()` — roles are never trusted from the JWT payload alone.

Authorization header	Bearer — required on all protected routes
Token source	Obtained from <code>supabase.auth.signInWithPassword()</code> — stored in <code>httpOnly</code> cookie
Role detection	Server reads <code>practitioner.role</code> from DB using <code>auth.uid()</code> — not from JWT claims
Patient routes	Patients use same auth system — role = 'patient' in practitioners or patients.user_id
Public routes	GET <code>/api/queue/display</code> , GET <code>/api/appointments/slots</code> — no auth required
Satu Sehat token	Stored in environment variable + auto-refreshed in <code>lib/satusehat/auth.ts</code>

Standard Response Format

All endpoints return JSON with a consistent envelope:

```
// Success
{
  "success": true,
  "data": { ... } | [ ... ],
  "meta": { "total": 100, "page": 1, "limit": 20 } // for paginated lists
}

// Error
{
  "success": false,
  "error": "Human-readable error message",
  "code": "VALIDATION_ERROR" // optional machine-readable code
}
```

Standard Error Codes

HTTP Status	Name	When it occurs
400	Bad Request	Validation failed — missing or invalid fields
401	Unauthorized	No valid session / token expired
403	Forbidden	Authenticated but insufficient role/permission
404	Not Found	Resource does not exist or RLS blocked visibility
409	Conflict	Duplicate entry e.g. NIK already registered
422	Unprocessable Entity	Business logic error e.g. slot already full
500	Internal Server Error	Unexpected server/database error

1. Authentication

Base: `/api/auth` · Role: All Users

Handles login, logout, and session retrieval. Uses Supabase Auth under the hood. The session token is stored in an httpOnly cookie. After login, the caller receives the user's role and profile so the frontend can route them to the correct module.

POST `/api/auth/login`

Auth: None

Login — Sign in with email and password. Returns user profile + role.

Request Body / Params

Field	Type	Required	Description
email	string	Yes	User email address
password	string	Yes	User password

Response 200 OK

```
{ "success": true, "data": { "user": { "id": "uuid", "email": "dr.ahmad@rsk.id" }, "profile": { "id": "uuid", "full_name": "dr. Ahmad Sehat", "role": "doctor", "organization_id": "uuid" }, "access_token": "eyJ..." } }
```

Response 4xx Error

```
{ "success": false, "error": "Invalid login credentials" }
```

POST `/api/auth/logout`

Auth: Required

Logout — Invalidates the current session and clears the auth cookie.

Response 200 OK

```
{ "success": true, "message": "Logged out successfully" }
```

Response 4xx Error

```
{ "success": false, "error": "Not authenticated" }
```

GET `/api/auth/me`

Auth: Required

Get Current User — Returns the authenticated user's profile, role, and organization info.

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "full_name": "dr. Ahmad Sehat", "role": "doctor", "organization": { "id": "uuid", "name": "Puskesmas MKP" }, "specialization": "Dokter Umum" } }
```

Response 4xx Error

```
{ "success": false, "error": "Unauthorized" }
```

2. CMS — Organization

Base: /api/cms · Role: Admin

Manages hospital/clinic profile data, poli services, and operational hours. This is the CMS (Content Management System) module used by the admin/owner to configure the system.

GET /api/cms/organization

Auth: Required

Get Organization Profile — Returns the organization profile including poli list and operational hours.

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "name": "Puskesmas MKP Kelompok 6", "type": "puskesmas",
"address": "Jl. Kesehatan No. 123", "phone": "(021) 1234-5678", "operational_hours": { "senin_jumat": {
"open": "08:00", "close": "15:00" }, "sabtu": { "open": "08:00", "close": "12:00" } }, "poli_services": [
... ] } }
```

Response 4xx Error

```
{ "success": false, "error": "Forbidden" }
```

PUT /api/cms/organization

Auth: Admin

Update Organization Profile — Updates clinic name, address, contact, operational hours. Role: admin only.

Request Body / Params

Field	Type	Required	Description
name	string	No	Organization name
address	string	No	Physical address
phone	string	No	Contact phone
email	string	No	Contact email
head_name	string	No	Head of facility name
operational_hours	object	No	JSON object of operating hours per day

Response 200 OK

```
{ "success": true, "data": { ...updated_organization } }
```

Response 4xx Error

```
{ "success": false, "error": "Forbidden — admin only" }
```

GET /api/cms/poli

Auth: None

List Poli Services — Returns all active poli services. Public — used on the hospital info page and booking.

Response 200 OK

```
{ "success": true, "data": [ { "id": "uuid", "name": "Poli Umum", "code": "PU", "quota_per_day": 30,
"is_active": true }, { "id": "uuid", "name": "Poli Gigi", "code": "PG", "quota_per_day": 20, "is_active":
true } ] }
```

Response 4xx Error

```
{ "success": false, "error": "Not found" }
```

POST /api/cms/poli

Auth: Admin

Create Poli Service — Creates a new poli service. Role: admin only.**Request Body / Params**

Field	Type	Required	Description
name	string	Yes	Poli name e.g. Poli Umum
code	string	Yes	Short code e.g. PU
location_id	uuid	Yes	Physical location of this poli
speciality_code	string	No	Satu Sehat speciality code
quota_per_day	number	No	Max patients per day (default 30)

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "name": "Poli Umum", ... } }
```

Response 4xx Error

```
{ "success": false, "error": "Code already exists" }
```


3. Patients

Base: /api/patients · Role:
Admin, Nurse, Doctor

Patient registration and management. On registration, the system calls the Satu Sehat MPI (Master Patient Index) to validate NIK and retrieve the Satu Sehat Patient ID. Medical record number is auto-generated.

GET /api/patients

Auth: Staff

List Patients — Returns paginated patient list. Supports search by name, NIK, medical record no, or BPJS no.

Request Body / Params

Field	Type	Required	Description
search	string	No	Search by name, NIK, MR number, or BPJS number
page	number	No	Page number (default: 1)
limit	number	No	Items per page (default: 20, max: 100)

Response 200 OK

```
{ "success": true, "data": [ { "id": "uuid", "full_name": "Budi Santoso", "nik": "3171...",  
  "medical_record_no": "MR/2024/000001" } ], "meta": { "total": 150, "page": 1, "limit": 20 } }
```

Response 4xx Error

```
{ "success": false, "error": "Unauthorized" }
```

POST /api/patients

Auth: Staff

Register New Patient — Registers a new patient. Automatically calls Satu Sehat MPI to validate NIK and stores the ss_patient_id. Auto-generates medical_record_no.

Request Body / Params

Field	Type	Required	Description
nik	string	No	National ID — triggers MPI lookup if provided
bpjs_no	string	No	BPJS membership number
full_name	string	Yes	Patient full name
date_of_birth	string	Yes	Date of birth in YYYY-MM-DD format
gender	enum	Yes	male female other
phone	string	No	Contact phone number
address	string	No	Full address
blood_type	string	No	A, B, AB, O
emergency_contact_name	string	No	Emergency contact name
emergency_contact_phone	string	No	Emergency contact phone

Response 200 OK
<pre>{ "success": true, "data": { "id": "uuid", "medical_record_no": "MR/2024/000152", "full_name": "Budi Santoso", "ss_patient_id": "100000030009", "nik": "3171xxxxxxxxxxxxx" } }</pre>
Response 4xx Error
<pre>{ "success": false, "error": "NIK already registered" }</pre>

GET	/api/patients/[id]	Auth: Staff / Self
Get Patient Detail — Returns full patient profile including allergy list and latest encounter summary.		
Response 200 OK		
<pre>{ "success": true, "data": { "id": "uuid", "full_name": "Budi Santoso", "medical_record_no": "MR/2024/000001", "allergies": [{ "substance_display": "Amoxicillin", "criticality": "high" }], "last_visit": "2024-11-15" } }</pre>		
Response 4xx Error		
<pre>{ "success": false, "error": "Patient not found" }</pre>		

PUT

/api/patients/[id]

Auth: Staff

Update Patient

— Updates patient demographic data. NIK and medical_record_no cannot be changed after creation.

Request Body / Params

Field	Type	Required	Description
full_name	string	No	Updated full name
phone	string	No	Updated phone number
address	string	No	Updated address
bpjs_no	string	No	Updated BPJS number
blood_type	string	No	Updated blood type

Response 200 OK

{ "success": true, "data": { ...updated_patient } }

Response 4xx Error

{ "success": false, "error": "Patient not found" }

4. Appointments & Online Booking

Base: /api/appointments ·
Role: Patient (User Module),
Nurse

Handles the online booking flow. Patients browse available slots, book an appointment, and receive a booking_code. The nurse uses check-in endpoints to convert the appointment into an active encounter. Synced to Satu Sehat as FHIR Appointment.

GET /api/appointments/slots

Auth: None

Get Available Slots — Returns available time slots for a poli on a given date. Public endpoint — used on booking page.

Request Body / Params

Field	Type	Required	Description
poli_service_id	uuid	Yes	Target poli ID
date	string	Yes	Date in YYYY-MM-DD format

Response 200 OK

```
{ "success": true, "data": [ { "id": "uuid", "start_time": "08:00", "end_time": "08:30", "quota": 5, "booked_count": 3, "is_available": true, "practitioner": { "full_name": "dr. Ahmad" } } ] }
```

Response 4xx Error

```
{ "success": false, "error": "Poli not found" }
```

POST /api/appointments

Auth: Patient / Staff

Create Booking — Books an appointment. Decrements slot booked_count. Generates booking_code. Sends FHIR Appointment to Satu Sehat asynchronously.

Request Body / Params

Field	Type	Required	Description
patient_id	uuid	Yes	Patient ID
poli_service_id	uuid	Yes	Target poli ID
slot_id	uuid	Yes	Selected time slot
payment_type	enum	Yes	umum bpjs
bpjs_referral_no	string	No	BPJS referral number (required if bpjs)
chief_complaint	string	No	Patient's main complaint

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "booking_code": "PU-2024-001523", "appointment_date": "2024-12-01", "appointment_time": "08:00", "poli": { "name": "Poli Umum" }, "doctor": { "full_name": "dr. Ahmad Sehat" }, "status": "booked" } }
```

Response 4xx Error

```
{ "success": false, "error": "Slot is no longer available" }
```

GET /api/appointments

Auth: Staff / Patient

List Appointments — Staff sees all appointments for their org. Patient sees only their own. Filterable by date, poli, and status.

Request Body / Params

Field	Type	Required	Description
date	string	No	Filter by date YYYY-MM-DD
poli_service_id	uuid	No	Filter by poli
status	string	No	pending booked arrived cancelled
page	number	No	Page number

Response 200 OK

```
{ "success": true, "data": [ { "id": "uuid", "booking_code": "PU-001", "patient": {...}, "status": "booked" } ], "meta": {...} }
```

Response 4xx Error

```
{ "success": false, "error": "Unauthorized" }
```

PATCH /api/appointments/[id]

Auth: Staff / Patient

Update Appointment Status — Nurse uses this to check-in a patient (status: arrived → checked_in). Patient can cancel (status: cancelled). Triggers queue number generation on check-in.

Request Body / Params

Field	Type	Required	Description
status	enum	Yes	arrived checked_in cancelled no_show
cancel_reason	string	No	Required when status=cancelled

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "status": "checked_in", "queue": { "queue_number": "A023", "sequence_number": 23 } } }
```

Response 4xx Error

```
{ "success": false, "error": "Appointment cannot be cancelled at this stage" }
```

5. Queue Management

Base: /api/queue · Role:
Nurse (manage), Public
(display screen)

Controls the physical queue system. The queue display screen polls the public endpoint. Nurses call patients and advance the queue. When a patient is called, a Satu Sehat encounter status update is triggered.

GET /api/queue/display

Auth: None

Queue Display (Public) — Public endpoint for the queue display screen. Returns current and next numbers per poli.

Request Body / Params

Field	Type	Required	Description
poli_service_id	uuid	No	Filter by specific poli (omit for all poli)
date	string	No	Date (default: today)

Response 200 OK

```
{ "success": true, "data": [ { "poli": { "name": "Poli Umum", "code": "PU" }, "current": { "queue_number": "A023", "patient_name": "B***o" }, "next": [ "A024", "A025", "A026" ] } ] }
```

Response 4xx Error

```
{ "success": false, "error": "Bad request" }
```

GET /api/queue

Auth: Staff

List Queue (Staff) — Returns today's full queue list for a poli including patient info and status.

Request Body / Params

Field	Type	Required	Description
poli_service_id	uuid	Yes	Target poli ID
date	string	No	Date (default: today)
status	string	No	waiting called in_service done skipped

Response 200 OK

```
{ "success": true, "data": [ { "queue_number": "A023", "patient": { "full_name": "Budi" }, "status": "waiting", "called_at": null } ] }
```

Response 4xx Error

```
{ "success": false, "error": "Unauthorized" }
```

POST /api/queue

Auth: Nurse

Create Queue Entry — Creates a queue entry — called on patient walk-in (no appointment) or auto-called on check-in.

Request Body / Params

Field	Type	Required	Description
patient_id	uuid	Yes	Patient ID
poli_service_id	uuid	Yes	Target poli
appointment_id	uuid	No	Linked appointment if pre-booked
queue_prefix	string	No	Letter prefix (default: A)

Response 200 OK
<pre>{ "success": true, "data": { "queue_number": "A024", "sequence_number": 24, "status": "waiting" } }</pre>
Response 4xx Error
<pre>{ "success": false, "error": "Patient already in queue today" }</pre>

PATC H	/api/queue/[id]	Auth: Nurse
-----------	-----------------	-------------

Call / Advance Queue — Advances a queue entry status. Calling a patient (called) triggers nurse notification. Marking done (in_service → done) moves to the next patient.

Request Body / Params

Field	Type	Required	Description
status	enum	Yes	called in_service done skipped

Response 200 OK

```
{ "success": true, "data": { "queue_number": "A023", "status": "called", "called_at": "2024-12-01T09:15:00Z" } }
```

Response 4xx Error

```
{ "success": false, "error": "Invalid status transition" }
```

6. Encounters

Base: /api/encounters · Role:
Nurse, Doctor, Admin

The central clinical transaction. An encounter is created when a patient's queue number is called. It links the patient, doctor, nurse, poli, and all subsequent clinical data. Synced to Satu Sehat as FHIR Encounter.

POST /api/encounters Auth: Nurse

Create Encounter — Creates a new encounter — triggered when nurse calls a patient. Sets status to in_progress. Also sends FHIR Encounter to Satu Sehat.

Request Body / Params

Field	Type	Required	Description
patient_id	uuid	Yes	Patient ID
poli_service_id	uuid	No	Poli (outpatient/IGD)
encounter_class	enum	Yes	outpatient inpatient emergency
appointment_id	uuid	No	Linked appointment (if pre-booked)
queue_id	uuid	No	Linked queue entry
doctor_id	uuid	No	Assigned doctor
nurse_id	uuid	No	Assigned nurse
payment_type	enum	Yes	umum bpjs
is_referred_in	bool	No	True if patient has referral letter
referral_from	string	No	Origin facility name

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "status": "in_progress", "encounter_class": "outpatient", "ss_encounter_id": "4f735a03-...", "started_at": "2024-12-01T09:15:00Z" } }
```

Response 4xx Error

```
{ "success": false, "error": "Patient already has an active encounter" }
```

GET /api/encounters/[id] Auth: Staff

Get Encounter Detail — Returns a full encounter with all linked clinical data: vital signs, diagnoses, procedures, notes, prescriptions, lab orders.

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "patient": { "id": "uuid", "full_name": "Budi", "medical_record_no": "MR/2024/001" }, "vital_signs": { ... }, "diagnoses": [ ... ], "procedures": [ ... ], "prescriptions": [ ... ], "lab_orders": [ ... ], "clinical_notes": [ ... ] } }
```

Response 4xx Error

```
{ "success": false, "error": "Encounter not found" }
```

PATCH

/api/encounters/[id]

Auth: Doctor / Nurse

Update Encounter Status — Updates encounter status (e.g. finished when doctor completes examination). Also updates Satu Sehat Encounter via PUT.

Request Body / Params

Field	Type	Required	Description
status	enum	Yes	in_progress finished cancelled
finished_at	string	No	ISO timestamp when encounter ended
doctor_id	uuid	No	Assign doctor if not set at creation

Response 200 OK

{ "success": true, "data": { "id": "uuid", "status": "finished", "finished_at": "2024-12-01T10:30:00Z" } }

Response 4xx Error

{ "success": false, "error": "Cannot finish encounter without a diagnosis" }

7. Clinical Records

Base: /api/clinical · Role:
Nurse, Doctor, Lab Nurse,
Nutritionist

All clinical sub-records within an encounter: vital signs, diagnoses, procedures, CPPT notes, and allergies. Each endpoint syncs to the corresponding Satu Sehat FHIR resource asynchronously after saving locally.

POST /api/clinical/vital-signs

Auth: Nurse

Record Vital Signs — Nurse records patient vital signs after queue number is called. BMI auto-calculated. Synced to Satu Sehat Observation.

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	Yes	Parent encounter
systolic_bp	number	No	Systolic blood pressure (mmHg)
diastolic_bp	number	No	Diastolic blood pressure (mmHg)
heart_rate	number	No	Heart rate (bpm)
temperature	number	No	Temperature (Celsius)
oxygen_saturation	number	No	SpO2 (%)
weight_kg	number	No	Weight (kg)
height_cm	number	No	Height (cm)
pain_scale	number	No	Pain scale 0-10

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "bmi": 22.5, "ss_observation_id": "obs-uuid" } }
```

Response 4xx Error

```
{ "success": false, "error": "Encounter not found or not in progress" }
```

POST /api/clinical/diagnoses

Auth: Doctor

Add Diagnosis — Doctor adds ICD-10 diagnosis to an encounter. One encounter can have multiple diagnoses (primary + secondary).

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	Yes	Parent encounter
icd10_code	string	Yes	ICD-10 code e.g. J06.9
icd10_display	string	Yes	Human-readable diagnosis name
diagnosis_type	enum	No	primary secondary comorbidity
onset_date	string	No	Onset date YYYY-MM-DD

Field	Type	Required	Description
notes	string	No	Additional notes

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "icd10_code": "J06.9", "ss_condition_id": "cond-uuid" } }
```

Response 4xx Error

```
{ "success": false, "error": "Forbidden – doctor role required" }
```

POST /api/clinical/procedures

Auth: Doctor

Record Procedure / Tindakan — Doctor records a medical procedure using ICD-9-CM or KPTL code. Synced to Satu Sehat as FHIR Procedure.

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	Yes	Parent encounter
procedure_code	string	Yes	ICD-9-CM or KPTL code
procedure_display	string	Yes	Procedure name
is_surgery	bool	No	True for surgical procedures (default false)
notes	string	No	Notes

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "procedure_code": "87.44", "ss_procedure_id": "proc-uuid" } }
```

Response 4xx Error

```
{ "success": false, "error": "Invalid procedure code" }
```

POST /api/clinical/notesAuth: Doctor,
Nurse, Nutritionist,
Lab Nurse

Write CPPT Note — Any clinical staff writes a SOAP-format progress note (CPPT). The writer_role is determined from the authenticated user's practitioner role.

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	Yes	Parent encounter
subjective	string	No	S: Patient's complaints
objective	string	No	O: Examination findings
assessment	string	No	A: Clinical assessment
plan	string	No	P: Plan and follow-up

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "writer_role": "doctor", "note_date": "2024-12-01T10:00:00Z" } }
```

Response 4xx Error

```
{ "success": false, "error": "Unauthorized role" }
```

GET /api/clinical/notes

Auth: Staff

Get CPPT Notes — Returns all CPPT notes for an encounter, ordered by date. Includes writer name and role.**Request Body / Params**

Field	Type	Required	Description
encounter_id	uuid	Yes	Filter by encounter

Response 200 OK

```
{ "success": true, "data": [ { "id": "uuid", "writer": { "full_name": "dr. Ahmad", "role": "doctor" }, "subjective": "...", "note_date": "..." } ] }
```

Response 4xx Error

```
{ "success": false, "error": "Forbidden" }
```

POST /api/clinical/allergies

Auth: Doctor, Nurse

Record Allergy — Adds an allergy record to the patient's permanent medical history.**Request Body / Params**

Field	Type	Required	Description
patient_id	uuid	Yes	Patient ID
encounter_id	uuid	No	Encounter where allergy was identified
substance_display	string	Yes	Allergen name
category	enum	No	medication food environment
criticality	enum	No	low high unable-to-assess
reaction_description	string	No	Description of reaction

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "substance_display": "Amoxicillin", "criticality": "high" } }
```

Response 4xx Error

```
{ "success": false, "error": "Allergy already recorded" }
```

POST /api/clinical/resume

Auth: Doctor

Create Medical Resume — Doctor creates the final medical resume (Resume Medis) at the end of encounter. This is the key document sent to Satu Sehat as FHIR Composition.

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	Yes	Parent encounter
chief_complaint	string	Yes	Main complaint
history_of_illness	string	No	History of present illness
physical_examination	string	No	Physical exam findings
summary	string	Yes	Clinical summary
follow_up_plan	string	No	Post-visit plan

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "ss_composition_id": "comp-uuid", "ss_sync_status": "synced" } }
```

Response 4xx Error

```
{ "success": false, "error": "Encounter must be finished before creating resume" }
```

POST /api/clinical/consents

Auth: Nurse

Record Informed Consent — Records patient or guardian consent for invasive procedures. A document URL from Supabase Storage can be attached.

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	Yes	Parent encounter
consent_type	string	Yes	surgery invasive_procedure general
consented_by	string	Yes	Name of the consenting person
relation_to_patient	string	No	self parent spouse etc.
document_url	string	No	URL to signed document in storage

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "consented_at": "2024-12-01T08:00:00Z" } }
```

Response 4xx Error

```
{ "success": false, "error": "Encounter not found" }
```

8. Emergency (IGD)

Base: /api/emergency · Role:
Nurse, Doctor

IGD-specific workflow. Fast registration with minimal data, triage by nurse, then doctor examination. Final outcome can be discharge, referral out, or admission to inpatient. Builds on the base Encounter.

POST /api/emergency

Auth: Nurse

Create IGD Admission — Fast registration for IGD patient. Creates an encounter + emergency_encounter record. NIK is optional — patient can be registered with minimal data.

Request Body / Params

Field	Type	Required	Description
patient_id	uuid	No	Existing patient ID (if known)
nik	string	No	NIK for quick lookup or new patient creation
full_name	string	No	Patient name (if new patient without NIK)
payment_type	enum	Yes	umum bpjs

Response 200 OK

```
{ "success": true, "data": { "encounter_id": "uuid", "emergency_id": "uuid", "patient": { "id": "uuid", "full_name": "..."}, "status": "emergency_admitted" } }
```

Response 4xx Error

```
{ "success": false, "error": "Failed to create IGD admission" }
```

PATCH /api/emergency/[id]/triage

Auth: Nurse

Submit Triage — IGD nurse submits triage data: chief complaint, vital signs, triage category (P1-P4). If critical, marks is_critical=true for immediate resuscitation.

Request Body / Params

Field	Type	Required	Description
triage_category	string	Yes	P1 P2 P3 P4
triage_complaint	string	Yes	Chief complaint at triage
is_critical	bool	No	True if immediate action needed
systolic_bp	number	No	Via vital signs
heart_rate	number	No	Via vital signs
temperature	number	No	Via vital signs
oxygen_saturation	number	No	Via vital signs

Response 200 OK

```
{ "success": true, "data": { "status": "in_triage", "triage_category": "P2", "triaged_at": "..."} }
```

Response 4xx Error

```
{ "success": false, "error": "IGD encounter not found" }
```

**PATC
H****/api/emergency/[id]/outcome**

Auth: Doctor

Set IGD Outcome — Doctor sets the final outcome. If rawat_inap, creates inpatient_admissions record. If rujukan, creates referral letter details.

Request Body / Params

Field	Type	Required	Description
outcome	enum	Yes	discharged referred admitted_inpatient
referred_to	string	No	Destination facility (if referred)
referral_letter_no	string	No	Referral letter number
needs_ambulance	bool	No	Request ambulance
admission_data	object	No	Required if outcome=admitted_inpatient: { room_location_id, bed_number, room_class, dpjp_id }

Response 200 OK

```
{ "success": true, "data": { "status": "completed", "outcome": "admitted_inpatient", "admission_id": "uuid" } }
```

Response 4xx Error

```
{ "success": false, "error": "Doctor role required" }
```

9. Inpatient (Rawat Inap)

Base: /api/inpatient · Role:
Nurse, Doctor

Full inpatient lifecycle from admission to discharge. Each day creates a new encounter linked to the episode of care. Running bill accumulates automatically when medications are dispensed, lab tests ordered, or procedures recorded.

POST /api/inpatient/admissions

Auth: Nurse, Doctor

Create Admission — Creates an inpatient admission and episode of care. Can originate from outpatient, IGD, or referral.

Request Body / Params

Field	Type	Required	Description
patient_id	uuid	Yes	Patient being admitted
admitted_from	enum	Yes	outpatient igd rujukan
dpjp_id	uuid	Yes	Dokter Penanggung Jawab Pasien
room_location_id	uuid	Yes	Assigned room/ward location ID
bed_number	string	Yes	Bed identifier
room_class	enum	Yes	kelas_1 kelas_2 kelas_3 vip
payment_type	enum	Yes	umum bpjs
sep_number	string	No	BPJS SEP number
source_encounter_id	uuid	No	Originating encounter (IGD/outpatient)

Response 200 OK

```
{ "success": true, "data": { "admission_id": "uuid", "episode_of_care_id": "uuid", "bed_number": "101-A", "status": "admitted" } }
```

Response 4xx Error

```
{ "success": false, "error": "Bed already occupied" }
```

GET /api/inpatient/admissions/[id]

Auth: Staff

Get Admission Detail — Returns full admission details including episode summary, daily encounters, running bill total, assigned DPJP, and room info.

Response 200 OK

```
{ "success": true, "data": { "admission_id": "uuid", "patient": {...}, "dpjp": {...}, "room": {...}, "running_bill_total": 1250000, "status": "in_care" } }
```

Response 4xx Error

```
{ "success": false, "error": "Admission not found" }
```

POST /api/inpatient/admissions/[id]/daily-encounter

Auth: Nurse

Create Daily Encounter — Creates a new daily encounter linked to the admission. Called each morning (or per shift). This is the encounter that links to daily vitals, CPPT, and medical orders.

Request Body / Params

Field	Type	Required	Description
shift	enum	No	pagi sore malam (default: pagi)
nurse_id	uuid	No	Assigned nurse for this shift
doctor_id	uuid	No	Attending doctor for today

Response 200 OK

```
{ "success": true, "data": { "encounter_id": "uuid", "record_date": "2024-12-02", "shift": "pagi" } }
```

Response 4xx Error

```
{ "success": false, "error": "Daily encounter already exists for this shift" }
```

PATCH /api/inpatient/admissions/[id]/discharge

Auth: Doctor

Process Discharge — Doctor approves discharge. Sets status to discharge_approved. Nurse then finalizes. On complete discharge, final invoice is generated from running_bill.

Request Body / Params

Field	Type	Required	Description
discharge_summary	string	Yes	Discharge summary notes
follow_up_plan	string	No	Post-discharge plan
action	enum	Yes	approve finalize

Response 200 OK

```
{ "success": true, "data": { "status": "discharge_approved", "invoice_id": "uuid" } }
```

Response 4xx Error

```
{ "success": false, "error": "Discharge requires a medical resume" }
```

GET /api/inpatient/running-bill

Auth: Staff

Get Running Bill — Returns accumulated charges for an active inpatient stay grouped by category.

Request Body / Params

Field	Type	Required	Description
episode_of_care_id	uuid	Yes	Episode of care ID

Response 200 OK


```
{ "success": true, "data": { "items": [ { "item_type": "room", "item_name": "Kelas 3 - 2 hari", "subtotal": 300000 } ], "total": 1250000 } }
```

Response 4xx Error

```
{ "success": false, "error": "Episode not found" }
```

10. Surgery (Operasi / OK)

Base: /api/surgery · Role:
Doctor, Nurse

Surgery workflow from request to post-operative care. A surgeon requests surgery, admin schedules an OK room, pre-op assessment is done, and on surgery day the system tracks start/end time and intra-operative notes.

POST /api/surgery

Auth: Doctor

Create Surgery Request — Doctor creates a surgery request from any encounter type (outpatient, inpatient, IGD).

Request Body / Params

Field	Type	Required	Description
patient_id	uuid	Yes	Patient
encounter_id	uuid	Yes	Source encounter
surgery_type	string	Yes	Type/name of surgery
indication	string	Yes	Clinical indication
anesthesia_type	string	No	umum lokal regional spinal
episode_of_care_id	uuid	No	Link to inpatient episode if applicable

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "status": "surgery_requested" } }
```

Response 4xx Error

```
{ "success": false, "error": "Encounter not found" }
```

PATCH /api/surgery/[id]/schedule

Auth: Admin, Nurse

Schedule Surgery — Schedules the surgery: assigns OK room, surgeon, anesthesiologist, date and time.

Request Body / Params

Field	Type	Required	Description
scheduled_date	string	Yes	ISO datetime for surgery
ok_location_id	uuid	Yes	Operating room location ID
surgeon_id	uuid	Yes	Primary surgeon
anesthesiologist_id	uuid	No	Anesthesiologist

Response 200 OK

```
{ "success": true, "data": { "status": "surgery_scheduled", "scheduled_date": "2024-12-05T08:00:00Z" } }
```

Response 4xx Error

```
{ "success": false, "error": "OK room not available at this time" }
```

**PATC
H****/api/surgery/[id]/intraop**

Auth: Doctor

Record Intra-Operative — Records start time, end time, and intra-operative notes during surgery.**Request Body / Params**

Field	Type	Required	Description
surgery_start_at	string	Yes	Actual surgery start datetime
surgery_end_at	string	No	Actual surgery end datetime
intra_op_notes	string	No	Intra-operative notes

Response 200 OK

```
{ "success": true, "data": { "status": "intra_operative", "surgery_start_at": "..." } }
```

Response 4xx Error

```
{ "success": false, "error": "Surgery not in ready status" }
```

**PATC
H****/api/surgery/[id]/postop**

Auth: Doctor, Nurse

Record Post-Operative — Records post-op notes and PACU (recovery room) monitoring. Sets outcome for further inpatient care.**Request Body / Params**

Field	Type	Required	Description
post_op_notes	string	No	Post-operative notes
pacu_notes	string	No	Recovery room notes
pacu_discharge_at	string	No	When patient left PACU
needs_inpatient_after	bool	No	Requires inpatient post-surgery

Response 200 OK

```
{ "success": true, "data": { "status": "surgery_completed" } }
```

Response 4xx Error

```
{ "success": false, "error": "Surgery not yet completed" }
```

11. Laboratory

Base: /api/lab · Role: Doctor
(order), Lab Nurse (process
+ results)

Two-step flow: doctor creates lab order → lab nurse processes and uploads results. LOINC codes are used for test identification. Synced to Satu Sehat as ServiceRequest + Specimen + DiagnosticReport.

POST /api/lab/orders

Auth: Doctor

Create Lab Order — Doctor creates a lab order with one or more test items. Each item has a LOINC code.

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	Yes	Parent encounter
priority	enum	No	routine urgent stat (default: routine)
clinical_notes	string	No	Clinical context for the lab
items	array	Yes	Array of test items: [{ loinc_code, test_name, specimen_type }]

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "status": "lab_ordered", "items": [ { "id": "uuid", "test_name": "CBC", "loinc_code": "58410-2" } ] } }
```

Response 4xx Error

```
{ "success": false, "error": "Doctor role required" }
```

GET /api/lab/orders

Auth: Staff

List Lab Orders — Returns lab orders. Lab nurse sees all pending orders. Doctor sees orders they placed.

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	No	Filter by encounter
status	string	No	lab_ordered sample_taken processing result_uploaded
date	string	No	Filter by date

Response 200 OK

```
{ "success": true, "data": [ { "id": "uuid", "patient": {...}, "status": "lab_ordered", "priority": "urgent", "items": [...] } ] }
```

Response 4xx Error

```
{ "success": false, "error": "Unauthorized" }
```

**PATC
H****/api/lab/orders/[id]**

Auth: Lab Nurse

Update Lab Order Status — Lab nurse updates workflow status: sample_taken → processing.**Request Body / Params**

Field	Type	Required	Description
status	enum	Yes	sample_taken processing
lab_nurse_id	uuid	No	Assigning lab nurse
specimen_collected_at	string	No	Specimen collection timestamp

Response 200 OK

```
{ "success": true, "data": { "status": "sample_taken", "specimen_collected_at": "..." } }
```

Response 4xx Error

```
{ "success": false, "error": "Lab nurse role required" }
```

POST /api/lab/orders/[id]/results

Auth: Lab Nurse

Upload Lab Results — Lab nurse enters results for each test item. Triggers Satu Sehat sync of DiagnosticReport. Status changes to result_uploaded.**Request Body / Params**

Field	Type	Required	Description
results	array	Yes	Array: [{ item_id, result_value, result_unit, reference_range, result_status: normal abnormal critical }]

Response 200 OK

```
{ "success": true, "data": { "status": "result_uploaded", "ss_diagnostic_report_id": "diag-uuid",  
  "results": [ { "test_name": "Hemoglobin", "result_value": "12.5", "result_unit": "g/dL", "result_status":  
    "normal" } ] } }
```

Response 4xx Error

```
{ "success": false, "error": "All items must have results before uploading" }
```

12. Nutrition (Gizi)

Base: /api/nutrition · Role:
Nutritionist

Nutritionist module — active only for inpatient patients. Creates and manages daily meal plans based on patient diagnosis and nutritional assessment.

POST /api/nutrition/orders

Auth: Nutritionist

Create Nutrition Order — Nutritionist creates a nutrition order for an inpatient episode. Includes nutritional assessment and daily meal plan.

Request Body / Params

Field	Type	Required	Description
episode_of_care_id	uuid	Yes	Inpatient episode
encounter_id	uuid	No	Current encounter
nutritional_status	string	No	baik kurang lebih buruk
dietary_restrictions	string	No	e.g. diet diabetes, rendah garam
energy_needs_kcal	number	No	Daily caloric needs
protein_needs_g	number	No	Daily protein needs in grams
meal_plan	object	Yes	JSON: { pagi: '...', siang: '...', malam: '...' }

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "order_date": "2024-12-01", "nutritional_status": "kurang", "meal_plan": {...} } }
```

Response 4xx Error

```
{ "success": false, "error": "Nutritionist role required" }
```

PUT /api/nutrition/orders/[id]

Auth: Nutritionist

Update Meal Plan — Updates the meal plan for the current day based on changes in patient condition.

Request Body / Params

Field	Type	Required	Description
meal_plan	object	Yes	Updated meal plan JSON
nutritional_status	string	No	Updated nutritional assessment
dietary_restrictions	string	No	Updated dietary restrictions

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "meal_plan": { "pagi": "bubur + sup", "siang": "nasi + lauk", "malam": "bubur" } } }
```

Response 4xx Error

{ "success": false, "error": "Nutrition order not found" }

GET /api/nutrition/orders

Auth: Nutritionist,
Doctor, Nurse

List Nutrition Orders — Returns nutrition orders for an inpatient episode.

Request Body / Params

Field	Type	Required	Description
episode_of_care_id	uuid	Yes	Filter by episode

Response 200 OK

{ "success": true, "data": [{ "id": "uuid", "order_date": "2024-12-01", "meal_plan": {...} }] }

Response 4xx Error

{ "success": false, "error": "Unauthorized" }

13. Pharmacy

Base: /api/pharmacy · Role:
Doctor (prescribe),
Pharmacist (dispense +
stock)

Full pharmacy module: medication master (synced with KFA), stock monitoring, prescription management, and dispensing. Stock is auto-deducted via DB trigger when a dispense record is inserted.

GET /api/pharmacy/medications

Auth: Staff

List Medications — Returns the medication catalog. Supports search by name, generic name, or KFA code.

Request Body / Params

Field	Type	Required	Description
search	string	No	Search by name or KFA code
category	string	No	Filter by category
page	number	No	Page number

Response 200 OK

```
{ "success": true, "data": [ { "id": "uuid", "name": "Amoxicillin 500mg", "form": "kapsul", "kfa_code": "93000456" } ] }
```

Response 4xx Error

```
{ "success": false, "error": "Unauthorized" }
```

GET /api/pharmacy/stock

Auth: Pharmacist,
Admin

Get Stock Status — Returns current stock levels. Can filter for items below minimum threshold.

Request Body / Params

Field	Type	Required	Description
below_minimum	bool	No	true = only show low-stock items
medication_id	uuid	No	Filter by specific medication

Response 200 OK

```
{ "success": true, "data": [ { "medication": { "name": "Amoxicillin 500mg" }, "quantity": 8, "minimum_stock": 10, "is_below_minimum": true, "expiry_date": "2025-06-01" } ] }
```

Response 4xx Error

```
{ "success": false, "error": "Pharmacist role required" }
```

POST /api/pharmacy/prescriptions

Auth: Doctor

Create Prescription — Doctor creates a prescription at the end of an encounter. Contains one or more drug items.

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	Yes	Parent encounter
items	array	Yes	Array: [{ medication_id, dosage, frequency, duration_days, quantity, instructions }]

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "items": [ { "id": "uuid", "medication": { "name": "Amoxicillin 500mg" }, "dosage": "3x1", "quantity": 15 } ] } }
```

Response 4xx Error

```
{ "success": false, "error": "Doctor role required" }
```

GET /api/pharmacy/prescriptions

Auth: Pharmacist

List Prescriptions (Queue) — Returns pending prescriptions for the pharmacist to process. Ordered by encounter finish time.

Request Body / Params

Field	Type	Required	Description
status	string	No	active completed (default: active)
date	string	No	Filter by date

Response 200 OK

```
{ "success": true, "data": [ { "id": "uuid", "patient": {...}, "encounter_id": "uuid", "items": [...] } ] }
```

Response 4xx Error

```
{ "success": false, "error": "Pharmacist role required" }
```

POST /api/pharmacy/dispense

Auth: Pharmacist

Dispense Medication — Pharmacist dispenses medication. Auto-deducts from stock via DB trigger. Marks prescription_item.is_dispensed = true. Synced to Satu Sehat as MedicationDispense.

Request Body / Params

Field	Type	Required	Description
prescription_id	uuid	Yes	Parent prescription
prescription_item_id	uuid	Yes	Specific item to dispense
stock_id	uuid	Yes	Stock batch to deduct from
quantity_dispensed	number	Yes	Quantity given to patient

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "quantity_dispensed": 15, "ss_medication_dispense_id": "disp-uuid" } }
```

Response 4xx Error

```
{ "success": false, "error": "Insufficient stock" }
```

14. Purchase Orders

Base: /api/purchase-orders ·
Role: Pharmacist (create),
Admin (approve)

Drug procurement workflow. Pharmacist monitors low-stock alerts, creates PO drafts, admin reviews and approves, then goods are received and stock is auto-updated via DB trigger.

POST /api/purchase-orders Auth: Pharmacist

Create Purchase Order — Pharmacist creates a PO draft with vendor and drug items.

Request Body / Params

Field	Type	Required	Description
vendor_id	uuid	Yes	Vendor/supplier ID
expected_delivery_date	string	No	Expected delivery date
notes	string	No	Notes to vendor
items	array	Yes	Array: [{ medication_id, quantity_ordered, unit_price }]

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "po_number": "PO/2024/12/00015", "status": "po_draft", "total_amount": 2500000 } }
```

Response 4xx Error

```
{ "success": false, "error": "Pharmacist role required" }
```

PATCH /api/purchase-orders/[id]/approve Auth: Admin

Approve / Reject PO — Admin approves or rejects the PO. On approval, status changes to po_sent.

Request Body / Params

Field	Type	Required	Description
action	enum	Yes	approve reject
rejection_reason	string	No	Required if action=reject

Response 200 OK

```
{ "success": true, "data": { "status": "po_sent", "approved_by": "uuid", "approved_at": "..." } }
```

Response 4xx Error

```
{ "success": false, "error": "Admin role required" }
```

PATC
H

/api/purchase-orders/[id]/receive

Auth: Pharmacist

Receive Goods — Pharmacist records received goods per item. Updating quantity_received triggers stock auto-addition via DB trigger.

Request Body / Params

Field	Type	Required	Description
items	array	Yes	Array: [{ po_item_id, quantity_received, batch_number, expiry_date, received_date }]

Response 200 OK

{ "success": true, "data": { "status": "po_completed", "items": [{ "is_fully_received": true }] } }

Response 4xx Error

{ "success": false, "error": "PO must be in po_sent status to receive goods" }

GET

/api/purchase-orders

Auth: Pharmacist,
Admin

List Purchase Orders — Returns POs filterable by status.

Request Body / Params

Field	Type	Required	Description
status	string	No	po_draft po_sent po_completed po_cancelled
page	number	No	Page number

Response 200 OK

{ "success": true, "data": [{ "id": "uuid", "po_number": "P0/2024/12/00015", "vendor": {...}, "status": "po_sent", "total_amount": 2500000 }] }

Response 4xx Error

{ "success": false, "error": "Unauthorized" }

15. Billing & Invoicing

Base: /api/billing · Role:
Cashier, Admin, Nurse

Handles payment processing for all encounter types. Outpatient/IGD: invoice created at cashier after encounter ends. Inpatient: running_bill converted to invoice at discharge. BPJS claims tracked with claim status.

POST /api/billing/invoices

Auth: Cashier,
Nurse

Create Invoice — Creates final invoice for a completed encounter. Auto-populates line items from procedures, lab, and prescriptions.

Request Body / Params

Field	Type	Required	Description
encounter_id	uuid	Yes	Source encounter
payment_type	enum	Yes	umum bpjs
bpjs_sep_number	string	No	BPJS SEP number (required for BPJS)

Response 200 OK

```
{ "success": true, "data": { "id": "uuid", "invoice_number": "INV/2024/12/00234", "total_amount": 75000, "status": "unpaid", "items": [ { "item_type": "consultation", "unit_price": 25000 }, ... ] } }
```

Response 4xx Error

```
{ "success": false, "error": "Encounter must be finished before invoicing" }
```

PATCH /api/billing/invoices/[id]/pay

Auth: Cashier

Process Payment — Marks invoice as paid and records payment timestamp.

Request Body / Params

Field	Type	Required	Description
paid_amount	number	Yes	Amount paid by patient
payment_method	string	No	cash transfer qris

Response 200 OK

```
{ "success": true, "data": { "status": "paid", "paid_amount": 75000, "paid_at": "2024-12-01T11:00:00Z" } }
```

Response 4xx Error

```
{ "success": false, "error": "Invoice not found or already paid" }
```

GET /api/billing/invoices

Auth: Cashier,
Admin

List Invoices — Returns invoices filterable by date, status, and payment type.

Request Body / Params

Field	Type	Required	Description
date	string	No	Filter by date
status	string	No	unpaid paid bpjs_claim_pending
payment_type	string	No	umum bpjs

Response 200 OK
<pre>{ "success": true, "data": [{ "invoice_number": "INV/2024/12/00234", "patient": {...}, "total_amount": 75000, "status": "paid" }] }</pre>
Response 4xx Error
<pre>{ "success": false, "error": "Unauthorized" }</pre>