	Spec	จำนวน	Recomend Brand and Model	
Frame				
Aluminum Profile	V-Slot 20x40 331mm	2		
	V-Slot 20x40 359mm	2	2	
	V-Slot 20x40 370mm	2		
	V-Slot 20x40 290mm	1		
	Angle corner	4	4 10 89 12 63	
	90 degree joining plate	10		
	Tee-nuts M5	89		
	M5x8mm low profile screw (or button head ISO 7380)	12		
	M5x10mm low profile screw (or button head ISO 7380)	63		
	M5x12mm low profile screw (or button head ISO 7380)	14	14	
	Self Tapping Screw M5	4	4	
	Set screw M5x4mm	8	3	
	M3x12mm socket head screw (hex)	100		
	M3 Steel washer (DIN 125), 0.5mm thick	8	3	
Linear Motion				
Linear Road for X axis	Shaft Dia. D(Ø) 8, Length 370	2	Chinese	
Linear Road for Y axis	Shaft Dia. D(Ø) 8, Length 330	2	2 Chinese	
Linear Road for Z axis	Shaft Dia. D(Ø) 8, Length 320	2	2 Chinese	
Linear Bearings	Inscribed Circle Dia. dr(Ø) 8, Overall Length 24	10	Chinese	
Pulley	2GT, 16T, Bore 5mm	2	Chinese	
Idler	2GT, 16T, Bore 5	2	Chinese	
Belt	2GT, Width 6mm, Pitch 2mm, Length: 1,000mm	1	Chinese	
Electronic				
Stepper for X, Y and E axis	Nema 17, 1A, ~0.48Nm, <= 42mm body	3	LDO NEMA 17 MOTOR COOL POWER QLINK LDO-42STH40-1004ASC	
Lead Screw (Normal)	Nema 17, 1A, Integrate Lead Screw 321mm, <= 35mm Body	2	LDO NEMA 17 MOTOR MK3 Z MOTOR QLINK LDO-42STH34-1004L321EC	
Board	BigTreeTech SKR 1.4 Turbo	1	BigTreeTech SKR 1.4 Turbo	
Driver	TMC 2209	5	BigTreeTech TMC 2209 V1.2	
Display	TFT35	1	BigTreeTech TFT35 V3	
Heated Bed	250x210mm MK52 24V	1	Chinese	
Spring Sheet	250x210 Sprint Sheet	1	Chinese	
Heated Bed Spacer	Outer diameter: 6mm, Inner diameter: 3.2mm, Overall length: 6mm	9	Standless stell spacer	
Carriage for heated bed	Carriage for heated bed MK52. 6mm Aluminium	1	Chinese	
Bed Sensor	PINDA 2	1	Chinese	
Power Supply	24V >= 300W	1	Chinese	
FILAMENT SENSOR	IR Filament Sensor	1	Chinese	

Other	อุปกรณ์อื่น ๆ เช่นสายไฟ ปลั๊ก น๊อต สกลู M3		Chinese หรือ บ้านหม้อ
Extruders			
Hotend	E3D V6	1	Clone E3D V6 24V
Drive Gear	BondTech Drivegear KIT 1.75 Inner 5.0	1	Clone BondTech Drivegear KIT 1.75 Inner 5.0
Extruder springs	d = 0.8mm, D = 5.0mm, L = 15.0mm, n = 10, Lm = 8.8mm, Fm = 41.08N	1	Original Prusa Extruder Springs
Extruder Fan	4010 24V	1	Chinese
Printed Fan	Radial Cooling Fan 5015 24V	1	Chinese