
Table of Contents

.....	1
Part A	1
Part B	1
Part C	2
Part D	4
Part E	5

```
% Section: 28944
% Group members: Connor Dupuis, Rachel Romaine, Corinne Meyers, Sara
% Kinzbruner
% Isabella Perlmutter

clear
close all
clc
```

Part A

```
Beta = 4;
```

Part B

```
N = 20;
n = 0:(N-1);


% we are creating a delta function

x = zeros(N,1);
x(1) = 1;

h1 = group_system(x, Beta);

figure
stem(n, h1);
ylabel('h1[n]');
xlabel('Samples(n)');

% the system is unstable because as n approaches infinity, the impulse
% response approaches infinity
```



Part C



```
%Y(z) = (1.5+Beta)*Y(z)*z^-1+1.5*Beta*Y(z)*z^-2+X(z)
%Y(z) - ((1.5+Beta)*Y(z)*z^-1+1.5*Beta*Y(z)*z^-2) = X(z)
%Y(z) (1 - ((1.5+Beta)*z^-1 + 1.5*Beta*z^-2) = X(z)
%Y(z)/X(z) = H(z) = 1/(1 - ((1.5+Beta)*z^-1 + 1.5*Beta*z^-2))
```


```
a1 = [1, -(1.5+Beta), -1.5*Beta];
b1 = 1;
```

```
figure
pzplot(b1,a1);
```

```
a2 = [0 1];
b2 = [1, -6.433];
```

```
figure
pzplot(b2,a2);
```





Part D

```
h2 = filter(b2,a2,h1);

figure
stem(1:length(h2), h2);
ylabel('h1[n]');
xlabel('Samples(n)');

% Unable to apply filter because of 0 in a(1) position.
% The transfer function of our system is:
% H(z) = Z - 6.433 (Non-causal)
% H(z) = (1-6.433z^-1)/z^-1 (Delayed to make causal)

% This system has zeros in the numerator that cancels out the unstable
% poles of the original system.

Error using filter
First denominator filter coefficient must be non-zero.

Error in eellab7finale (line 52)
h2 = filter(b2,a2,h1);
```

Part E

This approach requires to us to know the transfer function, therefore not applicable to arbitrary system in the real world where it is difficult to find the transfer function.

```
function pzplot(b,a)
% PZPLOT(B,A) plots the pole-zero plot for the filter described by
% vectors A and B. The filter is a "Direct Form II Transposed"
% implementation of the standard difference equation:
%
%      a(1)*y(n) = b(1)*x(n) + b(2)*x(n-1) + ... + b(nb+1)*x(n-nb)
%                  - a(2)*y(n-1) - ... - a(na+1)*y(n-na)
%
%
% MODIFY THE POLYNOMIALS TO FIND THE ROOTS
b1 = zeros(max(length(a),length(b)),1); % Need to add zeros to get
the right roots
a1 = zeros(max(length(a),length(b)),1); % Need to add zeros to get
the right roots
b1(1:length(b)) = b;      % New a with all values
a1(1:length(a)) = a;      % New a with all values
%
% FIND THE ROOTS OF EACH POLYNOMIAL AND PLOT THE LOCATIONS OF THE
ROOTS
h1 = plot(real(roots(a1)), imag(roots(a1)));
hold on;
h2 = plot(real(roots(b1)), imag(roots(b1)));
hold off;
%
% DRAW THE UNIT CIRCLE
circle(0,0,1)
%
% MAKE THE POLES AND ZEROS X's AND O's
set(h1, 'LineStyle', 'none', 'Marker', 'x', 'MarkerFaceColor','none', 'linewidth'
1.5, 'markersize', 8);
set(h2, 'LineStyle', 'none', 'Marker', 'o', 'MarkerFaceColor','none', 'linewidth'
1.5, 'markersize', 8);
axis equal;
%
% DRAW VERTICAL AND HORIZONTAL LINES
xminmax = xlim();
yminmax = ylim();
line([xminmax(1) xminmax(2)],[0 0], 'linestyle', ':', 'linewidth',
0.5, 'color', [1 1 1]*.1)
line([0 0],[yminmax(1) yminmax(2)], 'linestyle', ':', 'linewidth',
0.5, 'color', [1 1 1]*.1)
%
% ADD LABELS AND TITLE
xlabel('Real Part')
ylabel('Imaginary Part')
title('Pole-Zero Plot')
```

```
end

function circle(x,y,r)
% CIRCLE(X,Y,R)  draws a circle with horizontal center X, vertical
% center
% Y, and radius R.
%

    % ANGLES TO DRAW
    ang=0:0.01:2*pi;

    % DEFINE LOCATIONS OF CIRCLE
    xp=r*cos(ang);
    yp=r*sin(ang);

    % PLOT CIRCLE
    hold on;
    plot(x+xp,y+yp, ':', 'linewidth', 0.5, 'color', [1 1 1]*.1);
    hold off;

end
```

Published with MATLAB® R2020a