Server2 private readiness

Operator workflow. Source baseline c1ae9082 plus recorded E3c changes. Actual optimized owned notice-only process and signed S3 peer; no production or live sends.

1. Query the private listener

Use the configured private address (default 127.0.0.1:3001). GET /internal/ready with a four-second client timeout. HEAD performs the same probe without a body. POST returns 405. Keep the route outside the public proxy; public /internal/ready stays 404 and /health remains liveness.



Private readiness - actual owned observations

Real shared process, notice-only factory, signed loopback S3.

Peer	HTTP	ready	process	push	credentials	s3
clear	200	True	ready	not_required	ready	ready
bad-list	503	False	ready	not_required	ready	unavailable
clear	200	True	ready	not_required	ready	ready

All responses: `Cache-Control: no-store`

Public health 200 | Public readiness 404 | Private metrics 200

S3 LIST requests: 3 | S3 writes: 0 | Process exit: 0

Observed 2026-10-19T06:08:54.140757+00:00
Release test executable: f911e3964d340b44f2fefc08...
Recorded dirty-source build; not production, full-family or real-IAM qualification.
This is an evidence view, not a product dashboard.

Browser capture of retained actual process observations at 2026-10-19T06:08:54Z. It is an evidence view, not a product dashboard. Push is not_required only in this isolated notice-only factory.

Expected result: Healthy required components return 200 with ready=true and Cache-Control: no-store. Private /internal/metrics stays 200.

Server2 private readiness

Operator workflow. Source baseline c1ae9082 plus recorded E3c changes. Actual optimized owned notice-only process and signed S3 peer; no production or live sends.

2. Distinguish failure from recovery

Interpret process, push, credentials and s3 separately. Restoring/closed writer or process stop fails before dependencies. A configured S3 check has one three-second deadline for credential source, shared queue, one raw/v2/ LIST (max one key, 64 KiB), and strict XML decoding. Malformed, oversized or unavailable data returns 503. A later valid probe recovers; results are uncached.

Private readiness - actual owned observations

Real shared process, notice-only factory, signed loopback S3.

Peer	HTTP	ready	process	push	credentials	s3
clear	200	True	ready	not_required	ready	ready
bad-list	503	False	ready	not_required	ready	unavailable
clear	200	True	ready	not_required	ready	ready

All responses: `Cache-Control: no-store`

Public health 200 | Public readiness 404 | Private metrics 200

S3 LIST requests: 3 | S3 writes: 0 | Process exit: 0

Observed 2026-10-19T06:08:54.140757+00:00
Release test executable: f911e3964d340b44f2fefc08...
Recorded dirty-source build; not production, full-family or real-IAM qualification.
This is an evidence view, not a product dashboard.

The owned peer injects bad-list between two valid LIST replies: actual statuses 200 / 503 / 200. Exactly three LISTs and zero S3 writes were observed.

Expected result: The failed row reports s3=unavailable and ready=false. The next valid request returns s3=ready; concurrent stop/writer exit is rechecked before success.

Server2 private readiness

Operator workflow. Source baseline c1ae9082 plus recorded E3c changes. Actual optimized owned notice-only process and signed S3 peer; no production or live sends.

3. Respect the evidence boundary

Do not restart jobs, retry mutations, rewind journals or replay failed/unknown sends because readiness fails. This route performs no S3 write, weather, OAuth or FCM call. Avoid high-frequency polling: each configured S3 probe uses one LIST. The full five-field contract, build commands and selected evidence are in the editable server2-readiness.md manual.

Private readiness - actual owned observations

Real shared process, notice-only factory, signed loopback S3.

Peer	HTTP	ready	process	push	credentials	s3
clear	200	True	ready	not_required	ready	ready
bad-list	503	False	ready	not_required	ready	unavailable
clear	200	True	ready	not_required	ready	ready

All responses: `Cache-Control: no-store`

Public health 200 | Public readiness 404 | Private metrics 200

S3 LIST requests: 3 | S3 writes: 0 | Process exit: 0

Observed 2026-10-19T06:08:54.140757+00:00
Release test executable: f911e3964d340b44f2fefc08...
Recorded dirty-source build; not production, full-family or real-IAM qualification.
This is an evidence view, not a product dashboard.

Optimized executable was copied and hashed outside Cargo target. The actual process exited successfully and workflow listeners closed. No provider or device was contacted.

Expected result: A successful limited LIST does not establish GET/PUT permissions, every prefix, real-role missing-key behavior, host capacity, provider quotas, a full eligible recovery release, shadow or cutover. Those gates remain separate.