Common native verification

Run the existing verification layers through one fixed command. The default selection has 11 checks. A successful subset remains a subset, and no suite result qualifies whole-service earlier-release recovery, live traffic parity or production activation.

Prepare artifacts

Retain the Linux verification bundle

On a clean reviewed Linux checkout, run from `server2/`:

```
python3 tools/native_artifact.py --target-dir target --output ../reports/linux-native --archive
../reports/native.tar.gz
```

The producer reuses the selected Cargo target, builds sequentially, and requires 3 GiB expected build space plus a 3 GiB reserve. It selects compiler-emitted release executable paths for the eleven roles below and the logging/narrative probes. It exports `bin/`, `source/server2/`, `artifacts.json` and `bundle.json`. Only regular tracked server2 source and fixtures are copied; installed packages, ignored caches and account files are excluded. The optional archive contains a `native/` directory, including hidden tracked inputs and directory/executable modes. CI retains `native.tar.gz` inside the existing `server2-linux-musl-verified` artifact; the shared upload is unchanged. Compare the archive SHA-256 with the trusted producer/CI receipt before extracting it into a fresh owned directory. The original two-binary export remains unchanged. Seven-day CI retention is transport only; retain selected executable inputs and reports before expiry.

Check `python3 --version` (3.9 or later) and `git --version` on the receiving host. The paired replay records revision metadata using the Git executable even when the copied source has no Git checkout; an absent Git executable blocks that report. Run checks as an unprivileged account. After transfer to a fresh owned directory, restore executable permissions on the thirteen declared files if the transport stripped them, and preserve the exported source tree's read-only permissions. Run `chmod -R a-w BUNDLE/source` after transport and before verification; archives that omit directory entries and ZIP transports can lose directory modes. Python cache files must not become extra executable inputs. Run:

```
python3 BUNDLE/source/server2/tools/native_artifact.py --verify BUNDLE
```

Replace `BUNDLE` with the actual directory. Verify the trusted build receipt's revision, server2 tree and bundle metadata hash as well: these JSON hashes detect changes against that receipt, but are not signed attestations. Missing, changed, extra, symlinked, foreign-architecture or dynamically interpreted payloads block verification. Exit 2 is BLOCKED. No verification command installs files or starts a product process.

Rust integration tests retain `CARGO_MANIFEST_DIR` from compilation. Inspect `compiled_source_root` in `bundle.json`. On the empty owned host, map that exact location to `BUNDLE/source/server2` before execution; this is explicit operator setup, never a manifest-driven installation. Refuse an existing path or symlink and keep the frozen source unchanged. Do not overwrite a checkout or map it to a different revision. Then require:

```
python3 BUNDLE/source/server2/tools/native_artifact.py --verify BUNDLE --require-source-root
python3 BUNDLE/source/server2/tools/native_suite.py --artifacts BUNDLE/artifacts.json --out RUNS/native-1
python3 BUNDLE/source/server2/tools/widget_smoke.py --binary BUNDLE/bin/server2 --peer-binary
BUNDLE/bin/examples/loopback_server --output RUNS/widget-1
python3 BUNDLE/source/server2/tools/narrative_smoke.py --binary BUNDLE/bin/examples/narrative_smoke --out
RUNS/narrative-1
```

Use absolute bundle/run paths and fresh output directories outside the frozen source. The copied suite may observe no Git checkout; its declared artifact revision and the bundle's exact source tree remain the execution binding. Record the actual host, source-map verification and original failed runs separately. The bundle producer's PASS means export integrity only. Existing runtime checks must actually run; no full previous-release or production eligibility follows.

Build or declare individual artifacts

Use a reviewed checkout and the coordinator's Cargo target/build lease. Check free disk and keep the expected build plus a 3 GiB reserve. Build the server2 binary, examples `loopback_server`, `kma_s3_replay`, `warnings_smoke`, `notice_smoke`, `conditional_alert_smoke` and `warning_push_smoke` in release mode. Build release test executables with `cargo test --locked --release --test summary --test domestic --test state`

`--test runtime_services --no-run --message-format=json`. Use the emitted executable paths; do not guess a hash-suffixed test filename. The suite does not build or download artifacts.

Record JSON with exactly these top-level fields:

```
{
  "schema": 1,
  "revision": "0123456789abcdef0123456789abcdef01234567",
  "artifacts": {
    "notice_smoke": {
      "path": "/owned/release/examples/notice_smoke",
      "sha256": "0000000000000000000000000000000000000000000000000000000000000000",
      "profile": "release"
    }
  }
}
```

Replace the illustrative revision, path and hash with actual build provenance and file SHA-256. This example contains only the role needed for `--check notice`; a default full run requires all 11 roles listed by `--list`. Relative artifact paths resolve from the manifest directory. Revision/profile are caller declarations, not signed build attestations. Files must be executable and match the supplied hash. For KMA checks, the verified `kma_s3_replay` must reside at `examples/kma_s3_replay` beside the selected `server2` artifact, as the existing adapter requires. Keep manifests and executable copies in ignored task evidence.

Execute and inspect

Run from the repository root on a POSIX host with Python 3.9 or later, Git and dependencies already present:

```
python3 server2/tools/native_suite.py --list
python3 server2/tools/native_suite.py --artifacts reports/my-task/artifacts.json --out reports/my-task/run-1
python3 server2/tools/native_suite.py --artifacts reports/my-task/artifacts.json --out reports/my-
task/notice-1 --check notice
```

Each output directory must be new and outside `server2/`. Do not reuse a previous run directory. The suite validates all selected prerequisites before launching any child, then runs fixed commands sequentially with a narrow environment. No operator `.env`, provider credentials or proxy settings are inherited. Existing tools use owned loopback peers and synthetic fixtures. No manifest can supply a shell command.

Open `report.json`: inspect `selected`, `full_coverage`, each check's `status`, `layer`, `limitations`, artifact hashes and hashed evidence paths. `PASS` means only the selected checks passed. `full_coverage` is true only when all 11 passed. Unselected checks stay `NOT_RUN`. Exit 2 / `BLOCKED` means invalid prerequisites or output location; exit 1 / `FAIL` means an executed check, timeout or result validation failed. A failure retains logs and later checks still run. A zero exit without its expected structured result, a missing replay report or zero matching Rust tests is rejected. A timeout terminates the task-owned process group; it never changes runtime deadlines or retries a product failure.

Coverage and boundaries

ID	Existing verification	Boundary
kma-core	Frozen CORE/native S3 HTTP paired replay and perturbation control	Own denominator; no earlier-release rollback
kma-rich	Separate Rich/native S3 HTTP paired replay	Own denominator/provenance limits
world	Native VC/WAQI/S3 sharing and restart smoke	Includes frozen legacy coexistence/switch checks
warnings	Warning seed/raw/catalog/API with owned HTTP peer	Synthetic recorded provider
summary-model	Existing derive/record/lookup tests	Library/in-memory doubles

ID	Existing verification	Boundary
summary-http	Existing domestic summary_s3 tests	S3 HTTP/publication/backfill only
state	Existing registration journal/parity/restore/import tests	Library and owned HTTP layers
notice	Translation/S3/API/add/withdraw/delayed commit example	Owned synthetic translation service
conditional-alert	Weather/OAuth/FCM/claim/restart example	No real device send
warning-push	Warning catalog/geocode/OAuth/FCM/feed/restart example	No real device send
workers	Current production factory, 9 phases x 3 termination triggers	Current release only; no prior-release qualification

CI runs the suite's Python controls and retains all existing product gates. The full operator suite is explicitly invoked with its required artifacts; a unit-control pass is not an integrated suite run. The workflow design describes the intended tool flow, not a deployed or source-pinned runtime diagram. Selected execution evidence records what was actually run.

Actual usage capture

```
S19b | actual invocation and retained stdout

python3 server2/tools/native_suite.py
  --artifacts reports/issue-2704-s19b/artifacts-build2.json
  --out reports/issue-2704-s19b/functional-3

PASS kma-core [paired-http-replay]
PASS kma-rich [paired-http-replay]
PASS world [http-coexistence-smoke]
PASS warnings [loopback-http-smoke]
PASS summary-model [library-tests]
PASS summary-http [http-integration-tests]
PASS state [library-and-http-tests]
PASS notice [loopback-http-smoke]
PASS conditional-alert [loopback-http-smoke]
PASS warning-push [loopback-http-smoke]
PASS workers [process-matrix]
PASS native verification: all checks selected;
  reports/issue-2704-s19b/functional-3/report.json

Report summary (composed from the JSON):
  11/11 PASS | full_coverage=true | process exit=0
  CORE 220 / Rich 92 responses per side | workers 27 cases
  Summary model 27 / HTTP 10 tests | state 18 tests
  No whole-service prior-release or production qualification
Report SHA-256: 907258334acf3f7d56244df6152bd6b1
               10ed822b655abf6cd5ef74cf5c7249c6
```

Actual common-suite invocation and result

The capture and selected evidence belong to the recorded execution identity. Neither a static stdout banner nor repeated log bytes establish a second execution. Keep family-specific reports and the original failed outcomes when investigating a run.

Linux host execution record

Selected 2026-10-17 Linux bundle/EC2 evidence records the source identities and original failures. Nine native checks passed in the original run; two missing-Git report failures were renewed separately and passed. Neither native report claims full coverage. All eleven checks have passing evidence across the retained runs; the packaging-only source change has unchanged runtime/fixture/harness bytes and all thirteen executable hashes. WW HTTP, narrative and logging also passed. The separate nginx host setup failure is tracked in #2814.



Typeset actual retained CLI results

This labelled image is rendered from actual CLI records; browser/window capture was unavailable. It is not an application UI screenshot or another execution. Real S3, live shadow, quota, production listener and eligible previous full-release gates remain open.