

Graft setup • TodayWeather

Quick manual | Verified 2026-10-03 | Graft 0.21.1 | Codex CLI 0.159.2

Install and build

Install Node 20+ and explicitly run `npm install --global @nanonets/graft@0.21.1`. From the checkout, run `./scripts/build-graft.sh`, then `graft check`. The wrapper reapplies focused scopes after cache deletion. Generated `graft/` stays ignored.

Find code

```
graft skeleton server/controllers/controllerManager.js
graft grep WeatherUtil --fixed --in client/www/js
```

Read the architecture index first. Use graph edges to navigate and verify relevant source before changing behavior. Native bundles and docs need direct inspection.

Verify offline adapters

```
python3 scripts/verification/graft/test_adapters.py
```

```
$ python3 scripts/verification/graft/test_adapters.py
Ran 8 tests in 2.265s

OK
```

Rendered capture of actual CLI output; eight tests passed.

Real Graft smoke

```
python3 scripts/verification/graft/smoke.py \
--output reports/verification/graft-smoke
```

Passed: fresh focused build, freshness, server/client queries, ignored cache, session-start/prompt hook outputs and six MCP tools. No weather runtime or live provider calls were made.

Host setup and hook trust

Both hosts link to one canonical skill in `.agents/skills/graft/`. Claude project settings provide hooks/statusline and MCP. Codex project config enables hooks and Graft MCP. Restart the intended host.

Codex /hooks

Enter `/hooks`. Select each project Graft hook: `SessionStart`, `UserPromptSubmit`, `PostToolUse` and `Stop`. Inspect its command and press `t` to trust it. Avoid approving unrelated hooks. Account trust is never committed.

Linked worktrees

Codex reads hooks from the original checkout. Keep matching `.codex/config.toml` and `.codex/hooks.json` there. The command resolves the active worktree; a missing Graft shim safely skips execution. The isolated discovery check below found four untrusted hooks, as expected for a fresh account.

```
{
  "codex_version": "codex-cli 0.159.2",
  "hooks": [
    {
      "event": "postToolUse",
      "source": "original-repository/.codex/hooks.json",
      "trust": "untrusted"
    },
    {
      "event": "sessionStart",
      "source": "original-repository/.codex/hooks.json",
      "trust": "untrusted"
    },
    {
      "event": "userPromptSubmit",
      "source": "original-repository/.codex/hooks.json",
      "trust": "untrusted"
    },
    {
      "event": "stop",
      "source": "original-repository/.codex/hooks.json",
      "trust": "untrusted"
    }
  ],
  "user_configuration_isolated": true,
  "model_task_submitted": false
}
```

Rendered capture of actual isolated Codex discovery output. No model task was submitted.

Troubleshooting and limits

Missing CLI: install explicitly and check PATH. Build exits 127 with guidance; hooks no-op. Package lookup is bounded at 1.5 seconds. Stale cache: rerun the build wrapper. Hook discovery: check original checkout and restart. Direct adapter execution does not prove a full Claude conversation used it. See editable `graft-manual.md` and `graft.md` for commands, provenance and selected evidence.