Bounded paired reads: CLI quick start

S1-S3: Python 3.10+, two owned local HTTP peers and a matching candidate file. This fixture capture does not establish live product parity. See the adjacent operations guide for the manifest schema, production prerequisites and conditional reads (S4).

1. Preview, capture, then inspect before resuming

Run paired_read.py with --manifest and --candidate for a dry preview. Add --execute --state and --candidate-binary only after the parent run is qualified. For two local peers, add --loopback-test --production with the second loopback origin. The excerpt below is actual output from that CLI sequence.

Actual CLI capture and terminal resume

Local fixture peers; excerpt from the 2026-11-13 smoke.

```
{
  "terminal": "duration-complete",
  "attempts": {
    "candidate": 1,
    "production": 1
  },
  "pending": 0,
  "skipped_conditionals": 0,
  "qualification": "not assessed"
}
exit=0
Refuse terminal resume
refused: run is terminal; automatic resume refused
exit=2
candidate retained body: {"temperature":17}
production retained body: {"temperature":18}
Actual CLI smoke: 2 distinct bodies, 2 attempts, no repeated
request; product parity not assessed.
```

Two different raw responses were retained. The subsequent --resume was refused because this run had already reached its duration. No production requests were sent.

Expected result: Inspect terminal, attempts and pending. Duration completion is not a product PASS. Ordinary interruption may resume the unchanged run; terminal errors/duration cannot. Preserve evidence and complete the separate cloud cleanup.