Server2 private readiness

Operator workflow. Base c1ae9082 plus recorded E3c changes. Actual optimized notice-only process factory; no production main, live providers or device sends.

1. Query the private listener

Use the configured private address (default 127.0.0.1:3001). GET /internal/ready with a four-second client timeout. HEAD probes without a body. POST returns 405. Keep this route outside the public proxy. The public route is unmounted; its existing fallback is unchanged.

Private readiness - actual owned observations

Notice-only process factory; production main was not run.

Peer	HTTP	ready	process	push	credentials	s3
clear	200	true	ready	not_required	ready	ready
bad-list	503	false	ready	not_required	ready	unavailable
clear	200	true	ready	not_required	ready	ready

All responses: `Cache-Control: no-store`

Fixture: health200 | public readiness404 | private metrics200

S3 LIST:3 | S3 writes:0 | Process exit:0

Observed 2026-10-19T06:40:09.390515+00:00
Client signs requests; peer does not validate signatures, IAM or TLS.
Requires original compile-time checkout, Python and peer fixture assets.
Bypasses main dotenv, Config::from_vars and production coverage validation.
Release test SHA-256: b20a9b59d053d40ea5ab6682...
Recorded dirty-source build; no full-family, host or production qualification.
Evidence view, not a product dashboard.

Actual retained observations at 2026-10-19T06:40:09Z. Public 404 belongs to this notice-only fixture; it is not a universal coexistence response.

Expected result: Healthy required components return 200, ready=true and Cache-Control: no-store. Private metrics stays 200; /health remains liveness.

Server2 private readiness

Operator workflow. Base c1ae9082 plus recorded E3c changes. Actual optimized notice-only process factory; no production main, live providers or device sends.

2. Distinguish failure from recovery

Read process, push, credentials and s3 separately. Stop or unavailable writer fails before dependencies. One three-second deadline includes credential source, shared S3 queue, one raw/v2/ LIST (max one key, 64 KiB), and strict XML decode through shared CPU admission.

Private readiness - actual owned observations

Notice-only process factory; production main was not run.

Peer	HTTP	ready	process	push	credentials	s3
clear	200	true	ready	not_required	ready	ready
bad-list	503	false	ready	not_required	ready	unavailable
clear	200	true	ready	not_required	ready	ready

All responses: `Cache-Control: no-store`

Fixture: health200 | public readiness404 | private metrics200

S3 LIST:3 | S3 writes:0 | Process exit:0

Observed 2026-10-19T06:40:09.390515+00:00
Client signs requests; peer does not validate signatures, IAM or TLS.
Requires original compile-time checkout, Python and peer fixture assets.
Bypasses main dotenv, Config::from_vars and production coverage validation.
Release test SHA-256: b20a9b59d053d40ea5ab6682...
Recorded dirty-source build; no full-family, host or production qualification.
Evidence view, not a product dashboard.

The owned peer injects malformed XML between valid replies: 200 / 503 / 200. Three LIST requests and zero S3 writes were observed.

Expected result: Malformed, oversized or unavailable data returns 503. A later valid request recovers. Local stop/writer state is rechecked after the await. Results are uncached.

Server2 private readiness

Operator workflow. Base c1ae9082 plus recorded E3c changes. Actual optimized notice-only process factory; no production main, live providers or device sends.

3. Preserve matching executable inputs

This release test child invokes process::run and RuntimeServices::from_vars_at. It bypasses main dotenv, Config::from_vars and production coverage validation. The main binary was built and hashed, not run. Retain the original compile-time checkout and python3: tests/storage/catalog_peer.py, deploy/local/peer.py and config/local-stack.json.



Private readiness - actual owned observations

Notice-only process factory; production main was not run.

Peer	HTTP	ready	process	push	credentials	s3
clear	200	true	ready	not_required	ready	ready
bad-list	503	false	ready	not_required	ready	unavailable
clear	200	true	ready	not_required	ready	ready

All responses: `Cache-Control: no-store`

Fixture: health200 | public readiness404 | private metrics200

S3 LIST:3 | S3 writes:0 | Process exit:0

Observed 2026-10-19T06:40:09.390515+00:00
Client signs requests; peer does not validate signatures, IAM or TLS.
Requires original compile-time checkout, Python and peer fixture assets.
Bypasses main dotenv, Config::from_vars and production coverage validation.
Release test SHA-256: b20a9b59d053d40ea5ab6682...
Recorded dirty-source build; no full-family, host or production qualification.
Evidence view, not a product dashboard.

Copied optimized test SHA-256 b20a9b59... is bound to recorded dirty source. Copying the executable alone does not make it portable. Unused provider and metadata builtins point to dead loopback.

Expected result: Use only matching retained inputs or a separately verified source-root bundle. This partial factory does not establish complete production startup or full recovery eligibility.

Server2 private readiness

Operator workflow. Base c1ae9082 plus recorded E3c changes. Actual optimized notice-only process factory; no production main, live providers or device sends.

4. Interpret limits and polling cost

The client signs SigV4 requests; the peer does not validate signatures, IAM or TLS. Do not rewind claims, retry mutations or replay failed/unknown sends because readiness fails. Readiness 503 uses generic cause=capacity in the shared HTTP logger; interpret the fixed component fields first.

Private readiness - actual owned observations

Notice-only process factory; production main was not run.

Peer	HTTP	ready	process	push	credentials	s3
clear	200	true	ready	not_required	ready	ready
bad-list	503	false	ready	not_required	ready	unavailable
clear	200	true	ready	not_required	ready	ready

All responses: `Cache-Control: no-store`

Fixture: health200 | public readiness404 | private metrics200

S3 LIST:3 | S3 writes:0 | Process exit:0

Observed 2026-10-19T06:40:09.390515+00:00
Client signs requests; peer does not validate signatures, IAM or TLS.
Requires original compile-time checkout, Python and peer fixture assets.
Bypasses main dotenv, Config::from_vars and production coverage validation.
Release test SHA-256: b20a9b59d053d40ea5ab6682...
Recorded dirty-source build; no full-family, host or production qualification.
Evidence view, not a product dashboard.

The evidence view shows an actual response-handling workflow, not authentication proof or a product dashboard. Process exited successfully and listeners closed.

Expected result: Each configured probe consumes one shared-admission LIST. Avoid frequent polling. GET/PUT permissions, all prefixes, real-role missing keys, host capacity, provider quotas, full recovery, shadow and cutover remain separate gates.