

Keycloak Usage

We use a normal Keycloak IdP server (just as a demo). We refer to its documentation here: https://www.keycloak.org/docs/latest/server_admin/index.html

Below we document some important steps for you

General remarks

- Be sure that you work on the swiss-hds Realm (change via Manage realms)
- Be sure to use the swiss-hds Client (go into the Clients menu)

Creating a new User

1. Go to the "Users" menu on the left menu.
2. Click on "Add user"
3. Add a Username. The other fields are optional

Remark: you can also reuse existing users under [Environment-Details for Labs#ExistingUsersandCredentials](#).

Adding a redirect URI

1. Go to the swiss-hds Client
2. On the Tab "Settings", add a new "Valid redirect URIs"
3. Click on Save

Parameters

Example URL for the login in our case:

https://swisshds.u.c.bag.admin.ch/keycloak/realms/swiss-hds/protocol/openid-connect/auth?client_id=swiss-hds&redirect_uri=https%3A%2F%2Fswisshds.u.c.bag.admin.ch%2Fclient%2F&state=9fdf35fa-ed56-42a8-88d4-03882629a78b&response_mode=fragment&response_type=code&scope=openid&nonce=1dc09342-3f62-4b3b-8987-95603a6e5ab0&code_challenge=954l0qzAWFWxA9LgiQfiz7pEfAuTK6IMvpaNzMv3yrU&code_challenge_method=S256

```
KEYCLOAK_URL = {
  value = "https://swisshds.u.c.bag.admin.ch/keycloak"
}
KEYCLOAK_REALM = {
  value = "swiss-hds"
}
KEYCLOAK_CLIENT_ID = {
  value = "swiss-hds"
}
OAUTH2_JWK_URI = {
  value = "https://swisshds.u.c.bag.admin.ch/keycloak/realms/swiss-hds/protocol/openid-connect/certs"
}
```