

Policy Service Usage

- [Introduction](#)
- [UI Usage](#)
 - [Configuration in the Tab "System"](#)
 - [Add new Data Stores \(or more precisely, its gateway\) in the Policy Service](#)
 - [Configuration in the Tab "Patient"](#)
 - [Create/ Edit active relationships](#)
 - [Set blocked documents](#)
 - [Test the service=Invoke manual access checks](#)

Introduction

This service manages who can see what documents in the SwissHDS.

There are 2 base concepts (simplified):

- "Aktive Beziehung" (active relationship between a patient and 1-N doctors). You are in such a relationship while a doctor is treating you (from the first to the last consultation).
- Blocked documents

The basic model is: during an active relationship, the doctors involved in the relationship can access all your documents. Unless a document is blocked.

UI Usage

<https://swisshds.u.c.bag.admin.ch/policy/>

In the UI, there are 2 top-level tabs: Patient and System.

Configuration in the Tab "System"

Add new Data Stores (or more precisely, its gateway) in the Policy Service

You need to add the gateway URL that protects your data store in the policy server system list. This URL is the provider identity that also needs to be configured in the gateway.

For this, you add a new entry, you just set the provider identity field and keep the other fields empty, or "provider identity,,,".

Rationale for this configuration: In this view you can constrain, which principals can do what on your store. So you could say that others can only read FHIR resources of type Bundle.

Or also allow writing FHIR Tasks (e.g. for COW workflows). We currently do not use this feature in the lab (but you need to make one such entry with "provider identity,,,," to indicate that your gateway is open).

Configuration in the Tab "Patient"

Create/ Edit active relationships

To create a new relationship, click on the New button under Patient Relationship. The important fields to enter are patientId and the principals (comma-separated list of entries).

Both values are just strings. They need to be linked to the entries in HAOD.

To edit a relationship, click on the little pencil on the right of a relationship.

Set blocked documents

You can optionally define blocked documents under the Patient Deny Rules. This is not in the core of the labs. This mechanism will likely change in the future.

The important fields are PatientId, ResourceId, Allowed Principals and Allowed Relationship Ids.

Test the service=Invoke manual access checks

You can check whether a given actor would have access to a document. You do this, via the Try Patient Access Evaluation section.

The important 3 fields are the patientId (the one the document belongs to), the principalId (the one requesting access) and the resourceId (id of the document). The latest field is optional.

