
REPRESENTATION

****time** — relative elapsed time (in seconds)

DESCRIPTION

The ****time** representation is used to represent elapsed time (from some arbitrary moment deemed “time zero”) to the onset of the current moment. A typical use for ****time** is to represent the elapsed time from the beginning of a work (in seconds). Data tokens in ****time** consist simply of numbers of seconds, with an optional decimal value. The ****time** representation has no provision for representing “hours” or “minutes”.

Barlines are represented using the “common system” for barlines — see **barlines** (2).

FILE TYPE

It is recommended that files containing predominantly ****time** data should be given names with the distinguishing ‘.tim’ extension.

SIGNIFIERS

The following table summarizes the ****time** mappings of signifiers and signifieds.

0-9	decimal values
.	fractional second delimiter; null token
=	barlines
==	double barline

*Summary of ****time** Signifiers*

EXAMPLES

A sample document is given below:

**kern	**metpos	**takt	**time
*M4/4	*M4/4	*M4/4	*M4/4
*MM60	*MM60	*MM60	*MM60
*c:	*	*	*
=1	=1	=1	=1
8r	1	1	0
16cc	4	1.5	0.5
16bn	5	1.75	0.75
8cc	3	2	1
8g	4	2.5	1.5
8a-	2	3	2
16cc	4	3.5	2.5
16b	5	3.75	2.75
8cc	3	4	3
8dd	4	4.5	3.5
=2	=2	=2	=2
8g	1	1	4
16cc	4	1.5	4.5
16bn	5	1.75	4.75
8cc	3	2	5
8dd	4	2.5	5.5
16f	2	3	6
16g	5	3.25	6.25
4a-	4	3.5	6.5
*-	*-	*-	*-

PERTINENT COMMANDS

Currently, no special-purpose Humdrum commands produce ****time** as output, or process ****time** encoded data as input.

TANDEM INTERPRETATIONS

The following tandem interpretations can be used in conjunction with ****time**:

MIDI channel	*Ch1
meter signatures	*M6/8
tempo	*MM96.3

*Tandem interpretations for ****time***

SEE ALSO

barlines (2), ****date** (2), ****dur** (2), ****metpos** (2), ****ordo** (2), ****recip** (2), ****takt** (2), ****Zeit** (2)