

VIM-PLUG-IN  
**latex-support.vim**  
 VERSION 1.3ALPHA  
**HOT KEYS**

Key mappings for Vim and gVim

<http://www.vim.org> — Wolfgang Mehner, wolfgang-mehner@web.de

(i) insert mode, (n) normal mode, (v) visual mode,  
 (T) tab-completion

<i>Help</i>		
'he	English dictionary	(n,i)
'ht	start <b>texdoc</b>	(n,i)
'hp	help (plug-in)	(n,i)
<i>Comments</i>		
[n]'cl	end-of-line comment	(n, i, v)
[n]'cj	adjust end-of-line comments	(n, i, v)
'cs	set end-of-line comment col.	(n)
[n]'cc	toggle code comment	(n, i, v)
'cfr1	frame comment, type 1	(n, i)
'cfr2	frame comment, type 2	(n, i)
'cfr3	frame comment, type 3	(n, i)
'ch	file prolog	(n, i)
'cm	plug-in macros	(n, i, T)
'cd	date	(n, i)
'ct	date & time	(n, i)
<i>Document</i>		
'dc	documentclass	(n, i, T)
'di	indices	(n, i, T)
'dti	title	(n, i)
'dbi	bibliography	(n, i)
'dac	addcontentsline	(n, i)
'dln	newlength	(n, i)
'dls	setlength	(n, i)
'dla	addtolength	(n, i)
'dlp	print length	(n, i)
'dlt	set length to	(n, i)

<i>Text</i>		
'e	environment	(n, i, v, T)
'to	organization	(n, i, T)
'ts	section	(n, i, T)
'tld	list environment, description	(n, i)
'tle	list environment, enumerate	(n, i)
'tli	list environment, itemize	(n, i)
'tll	list environment, list	(n, i)
'tlit	list environment, item	(n, i)
'tlil	list environment, item+labels	(n, i)
'tf	font style	(n, i, v, T)
'tfs	font size	(n, i, v, T)
'tq	quotes	(n, i, v, T)
'tsp	spacing	(n, i, T)
'tal	line alignment + spacing	(n, i, v, T)
'tac	accents	(n, i, T)
'ttc	textcomp characters	(n, i, T)
'tbi	bibitem	(n, i)
'tci	cite	(n, i)
'tfo	footnote	(n, i)
'tin	index	(n, i)
'tla	label	(n, i)
'tma	marginpar	(n, i)
'tco	newcommand	(n, i)
'tnc	nocite	(n, i)
'tpa	pageref	(n, i)
'tre	ref	(n, i)
'tur	url	(n, i, v)

<i>Math</i>		
'msp	spaces	(n, i, T)
'mac	accents	(n, i, T)
'mfs	font styles	(n, i, T)
'md	delimiter	(n, i, T)
'mf	functions	(n, i, T)
'mgl	lowercase greek	(n, i, T)
'mgu	uppercase greek	(n, i, T)
'mo	operators	(n, i, T)
'mr	relations	(n, i, T)
'mar	arrows	(n, i, T)
'me	equation+label	(n, i, v)
'mea	eqnarray+label	(n, i, v)
'mca	cases	(n, i, v)
'mch	choose	(n, i, v)
'mfr	frac	(n, i, v)
'mma	matrix	(n, i)
'mnr	nth root	(n, i, v)
'mpr	prod	(n, i, v)
'msq	sqrt	(n, i, v)
'msu	sum	(n, i, v)
'mon	operatorname	(n, i, v)

<i>Beamer</i>		
<b>`bf</b>	frame	(n, i, v)
<b>`bc</b>	columns	(n, i, v, T)
<b>`bi</b>	itemize	(n, i, v)
<b>`bo</b>	overprint	(n, i, b)
<b>`bg</b>	includegraphics	(n, i)
<b>`bbl</b>	block	(n, i, v)
<i>Wizard</i>		
<b>`wll</b>	lstlisting	(n, i, v)
<b>`wlii</b>	lstinputlisting	(n, i)
<b>`wlin</b>	lstinline	(n, i, v)
<b>`wls</b>	lstset	(n, i, T)
<b>`wtt</b>	table	(n, i, v)
<b>`wtf</b>	table, floating	(n, i, v)
<b>`wtg</b>	tabbing	(n, i)
<b>`wtr</b>	tabular	(n, i)
<b>`wf</b>	figure	(n, i)
<b>`wff</b>	floatingfigure	(n, i)
<b>`wwf</b>	wrapfigure	(n, i)
<b>`wbf</b>	fbox	(n, i, v)
<b>`wbfr</b>	framebox	(n, i, v)
<b>`wbm</b>	mbox	(n, i, v)
<b>`wbmb</b>	makebox	(n, i, v)
<b>`wmp</b>	minipage	(n, i, v)
<b>`wbp</b>	parbox	(n, i, v)
<i>Snippets</i>		
<b>`nr</b>	read code snippet	(n, i)
<b>`nv</b>	view code snippet	(n, i)
<b>`nw</b>	write code snippet	(n, i, v)
<b>`ne</b>	edit code snippet	(n, i)
<b>`ntl</b>	edit local templates	(n, i)
<b>`ntc</b>	edit custom templates	(n, i)
<b>`ntp</b>	edit personal templates	(n, i)
<b>`ntr</b>	reread the templates	(n, i)
<b>`ntw</b>	template setup wizard	(n, i)
<b>`nts</b>	choose template style	(n, i, T)

<i>Run</i>		
<b>`rr</b>	save + run typesetter	(n, i)
<b>`rla</b>	save + run <b>lacheck</b>	(n, i)
<b>`re</b>	errors from last bg. process	(n, i)
<b>`rdvi</b>	view DVI	(n, i)
<b>`rpdf</b>	view PDF	(n, i)
<b>`rps</b>	view PS	(n, i)
<b>`rc</b>	run a converter	(n, i)
<b>`rmg</b>	run <b>makeglossaries</b>	(n, i)
<b>`rmi</b>	run <b>makeindex</b>	(n, i)
<b>`rbi</b>	run <b>bibtex</b>	(n, i)
<b>`rt</b>	choose the typesetter	(n, i, T)
<b>`rp</b>	method for external processing	(n, i, T)
<b>`rh</b>	hardcopy buffer to postscript	(n, i, v)
<b>`rse</b>	show plug-in settings	(n, i)
<i>Tool Box</i>		
<b>`rm</b>	run <b>make</b>	(n, i)
<b>`rcm</b>	choose makefile	(n, i)
<b>`rmc</b>	<b>make clean</b>	(n, i)
<b>`rma</b>	command line arguments for <b>make</b>	(n, i)

## Run

Run the typesetter or **lacheck** :

**:Latex** [<tex-file>]

**:LatexCheck** [<tex-file>]

Run tools like **makeindex** or **bibtex** :

**:LatexMakeglossaries** [<base>]

**:LatexMakeindex** [<idx-file>]

**:LatexBibtex** [<aux-file>]

(the default arguments are derived from the name of the current buffer)

Get the errors from the last background process:

**:LatexErrors**

## View

View a document of the specified format (supports **dvi**, **pdf**, and **ps**):

**:LatexView** [<format>]

**:LatexView** [<format>] <file>

**:LatexView** <file> [<format>]

(the default filename is derived from the name of the current buffer.)

## Options

Print or set the typesetter:

**:LatexTypesetter** [<typesetter>]

Print or set the processing method:

**:LatexProcessing** [<method>]

(both commands support tab-compl.)

## Make

Run **make** :

**:Make** [<args>]

Set the current makefile:

**:MakeFile** <file>

(both commands support tab-compl.)

Help for the Make Tool:

**:MakeHelp**