

# SelVPC provider

The SelVPC provider is used to interact with the Selectel VPC resources. The provider needs the Selectel API key token to authorize its requests.

Use the navigation to the left to read about the available resources.

## Example Usage

---

```
# Configure the SelVPC Provider
provider "selvpc" {
  token = "SELECTEL_API_TOKEN_KEY"
}

# Create a project
resource "selvpc_resell_project_v2" "project_1" {
  # ...
}
```

## Configuration Reference

---

The following arguments are supported:

- token - (Required) The Selectel API key token. If omitted, the SEL\_TOKEN environment variable is used.
- endpoint - (Optional) The Selectel VPC endpoint. Needed only if this provider is used for tests environment. If omitted, the provider will use the official Selectel VPC endpoint automatically.

## Additional Logging

---

To enable debug logging, set the TF\_LOG environment variable to DEBUG:

```
$ env TF_LOG=DEBUG terraform apply
```

## Testing and Development

---

In order to run the Acceptance Tests for development you need to set the SEL\_TOKEN environment variable:

```
$ env SEL_TOKEN=SELECTEL_API_TOKEN TF_ACC=1 go test -v ./selvpc/...
```

Please create an issue describing a new feature or bug prior creating a pull request.

# selvpc\_resell\_floatingip\_v2

Manages a V2 floatingip resource within Resell Selectel VPC.

## Example Usage

---

```
resource "selvpc_resell_floatingip_v2" "floatingip_1" {  
  project_id = "887e5e35458d4ee38a6ae0543555dec5"  
  region     = "ru-1"  
}
```

## Argument Reference

---

The following arguments are supported:

- `project_id` - (Required) An associated Selectel VPC project. Changing this creates a new floating IP.
- `region` - (Required) A region of where the floating IP resides. Changing this creates a new floating IP.

## Attributes Reference

---

The following attributes are exported:

- `port_id` - Contains id of the Networking service port.
- `floating_ip_address` - Contains floating IP address.
- `fixed_ip_address` - Contains internal IP address of the Networking service port.
- `status` - Shows if the license is used or not.
- `servers` - Shows information about servers that use this floating IP. Contains `id`, `name` and `status` fields.

## Import

---

Floating IPs can be imported using the `id`, e.g.

```
$ env SEL_TOKEN=SELECTEL_API_TOKEN terraform import selvpc_resell_floatingip_v2.floatingip_1 aa402146-d83e-4c8c-8b74-1f415d4b8253
```

# selvpc\_resell\_license\_v2

Manages a V2 license resource within Resell Selectel VPC.

## Example Usage

---

```
resource "selvpc_resell_license_v2" "license_windows_2016_standard" {  
  project_id = "887e5e35458d4ee38a6ae0543555dec5"  
  region     = "ru-2"  
  type       = "license_windows_2012_standard"  
}
```

## Argument Reference

---

The following arguments are supported:

- `project_id` - (Required) An associated Selectel VPC project. Changing this creates a new license.
- `region` - (Required) A region of where the license resides. Changing this creates a new license.
- `type` - (Required) The type of license. Changing this creates a new license.

## Attributes Reference

---

The following attributes are exported:

- `status` - Shows if the license is used or not.
- `servers` - Shows information about servers that use this license. Contains `id`, `name` and `status` fields.

## Import

---

Licenses can be imported using the `id`, e.g.

```
$ env SEL_TOKEN=SELECTEL_API_TOKEN terraform import selvpc_resell_license_v2.license_1 4123
```

# selvpc\_resell\_project\_v2

Manages a V2 project resource within Resell Selectel VPC.

## Example Usage

---

```
resource "selvpc_resell_project_v2" "kubernetes_cluster" {
  name          = "kubernetes_cluster"
  custom_url    = "kubernetes-cluster-123.selvpc.ru"
  theme {
    color = "2753E9"
  }
  quotas = [
    {
      resource_name = "compute_cores"
      resource_quotas = [
        {
          region = "ru-3"
          zone   = "ru-3a"
          value  = 12
        }
      ]
    },
    {
      resource_name = "compute_ram"
      resource_quotas = [
        {
          region = "ru-3"
          zone   = "ru-3a"
          value  = 20480
        }
      ]
    },
    {
      resource_name = "volume_gigabytes_fast"
      resource_quotas = [
        {
          region = "ru-3"
          zone   = "ru-3a"
          value  = 100
        }
      ]
    }
  ]
}
```

## Argument Reference

---

The following arguments are supported:

- `name` - (Required) The name of the project.
- `custom_url` - (Optional) The custom url for the project. Needs to be the 3rd-level domain for the `selvpc.ru`. Example: `terraform-project-001.selvpc.ru`.

- `theme` - (Optional) An additional theme settings for this project. The structure is described below.
- `auto_quotas` - (Optional) A boolean parameter that specifies if project should get automatically calculated quotas.
- `quotas` - (Optional) An array of desired quotas for this project. The structure is described below.

The theme block supports:

- `color` - (Optional) A background color in hex format.
- `logo` - (Optional) An url of the project header logo.

The quotas block supports:

- `resource_name` - (Required) A name of the billing resource to set quotas for.
- `resource_quotas` - (Required) An array of desired billing quotas for this particular resource. The structure is described below.

The resource\_quotas block supports:

- `region` - (Optional) A Selectel VPC region for the resource quota.
- `zone` - (Optional) A Selectel VPC zone for the resource quota.
- `value` - (Required) A value of the resource quota.

## Attributes Reference

---

The following attributes are exported:

- `url` - An url of the Selectel VP project. It is set by the Selectel and can't be changed by the user.
- `enabled` - Shows if project is active or it was disabled by the Selectel.
- `all_quotas` - Contains all quotas. They can differ from the configurable quota argument since the project will have all available resource quotas automatically applied.

## Import

---

Projects can be imported using the `id`, e.g.

```
$ env SEL_TOKEN=SELECTEL_API_TOKEN terraform import selvpc_resell_project_v2.project_1 0a343062504b4d06a0fac375e466db25
```

# selvpc\_resell\_role\_v2

Manages a V2 role resource within Resell Selectel VPC.

## Example Usage

---

```
resource "selvpc_resell_project_v2" "project_1" {
  auto_quotas = true
}

resource "selvpc_resell_user_v2" "user_1" {
  password = "secret"
}

resource "selvpc_resell_role_v2" "role_tf_acc_test_1" {
  project_id = "${selvpc_resell_project_v2.project_1.id}"
  user_id    = "${selvpc_resell_user_v2.user_1.id}"
}
```

## Argument Reference

---

The following arguments are supported:

- `project_id` - (Required) An associated Selectel VPC project. Changing this creates a new role.
- `user_id` - (Required) An associated Selectel VPC user. Changing this creates a new role.

## Attributes Reference

---

There are no additional attributes for this resource.

## Import

---

Roles can be imported by specifying `project_id` and `user_id` arguments, separated by a forward slash:

```
$ env SEL_TOKEN=SELECTEL_API_TOKEN terraform import selvpc_resell_role_v2.role_1 <project_id>/<user_id>
```

# selvpc\_resell\_subnet\_v2

Manages a V2 subnet resource within Resell Selectel VPC.

## Example Usage

---

```
resource "selvpc_resell_project_v2" "project_1" {
  auto_quotas = true
}

resource "selvpc_resell_subnet_v2" "subnet_1" {
  project_id   = "${selvpc_resell_project_v2.project_1.id}"
  region      = "ru-3"
  ip_version   = "ipv4"
  prefix_length = 29
}
```

## Argument Reference

---

The following arguments are supported:

- `project_id` - (Required) An associated Selectel VPC project. Changing this creates a new subnet.
- `region` - (Required) A region of where the subnet resides. Changing this creates a new subnet.
- `prefix_length` - (Optional) A prefix length of the subnet. Defaults to 29. Changing this creates a new subnet.
- `ip_version` - (Optional) A version of the IP protocol of the subnet. Defaults to "ipv4". Changing this creates a new subnet.
- `type` - (Required) The type of the subnet. Changing this creates a new subnet.

## Attributes Reference

---

The following attributes are exported:

- `cidr` - Shows subnet CIDR representation.
- `network_id` - Shows associated OpenStack Networking service network ID.
- `subnet_id` - Shows associated OpenStack Networking service subnet ID.
- `status` - Shows if the subnet is used or not.
- `servers` - Shows information about servers that use this subnet. Contains `id`, `name` and `status` fields.

## Import

---

Subnets can be imported using the `id`, e.g.

```
$ env SEL_TOKEN=SELECTEL_API_TOKEN terraform import selvpc_resell_subnet_v2.subnet_1 2060
```



# selvpc\_resell\_token\_v2

Manages a V2 token resource within Resell Selectel VPC.

ID of this resource can be used within the OpenStack API Identity service as the X-Auth-Token value.

## Example Usage

---

```
resource "selvpc_resell_project_v2" "project_1" {  
  auto_quotas = true  
}  
  
resource "selvpc_resell_token_v2" "token_tf_acc_test_1" {  
  project_id = "${selvpc_resell_project_v2.project_1.id}"  
}
```

## Argument Reference

---

The following arguments are supported:

- `project_id` - (Optional) An associated Selectel VPC project. Changing this creates a new token.
- `account_name` - (Optional) An associated Selectel VPC account. Changing this creates a new token.

## Attributes Reference

---

There are no additional attributes for this resource.

## Import

---

Tokens can't be imported at this time.

# selvpc\_resell\_user\_v2

Manages a V2 user resource within Resell Selectel VPC.

## Example Usage

---

```
resource "selvpc_resell_user_v2" "user_1" {  
  password = "verysecret"  
  enabled  = true  
}
```

## Argument Reference

---

The following arguments are supported:

- `name` - (Required) Name of the user. Changing this updates the name of the existing user.
- `password` - (Required) Password of the user. Changing this updates the password of the existing user.
- `enabled` - (Optional) Enabled state of the user. Changing this updates the enabled state of the existing user.

## Attributes Reference

---

There are no additional attributes for this resource.

## Import

---

Users can't be imported at this time.