

1. GENERAL

1.1. ATIS

D-ATIS Arrival 118.030
D-ATIS Departure 118.730

1.2. NOISE ABATEMENT PROCEDURES

1.2.1. RWY USAGE

1.2.1.1. ARRIVALS/DEPARTURES

RWY 25 will preferably be assigned to landing ACFT, provided the tailwind component does not exceed 5 KT. However, the take-off and landing direction will be changed from RWY 25 to RWY 07 if the braking action on the RWYs is impaired by water, snow, slush, ice, or frost, etc., even if the tailwind component is less than 5 KT. The take-off and landing direction also depends on the availability of navigation aids or significant weather in the approach and departure area.

1.2.1.2. DEPARTURES

Preferred take-off direction for landing direction 25/18:

For departures to the Northwest (OBOKA), North (MARUN) and Northeast (TOBAK), RWY 25C is preferred.

For departures to the Southwest (SOBRA, ULKIG), South (ANEKI), Southeast (CINDY) and East (SULUS), RWY 18 is preferred, provided the tailwind component for RWY 18 is not greater than 15 KT.

Preferred take-off direction for landing direction 07/18:

For departures to the Northwest (OBOKA), North (MARUN), Northeast (TOBAK) and East (KOMIB, SULUS), RWY 07C is preferred.

For departures to the Southwest (SOBRA, ULKIG), South (ANEKI) and Southeast (CINDY), RWY 18 is preferred, provided the tailwind component for RWY 18 is not greater than 15 KT.

Exceptions are possible if required due to traffic safety, the availability of navigation aids, significant weather in the approach and departure area or noise abatement measures or if Aerodrome Control deems that the traffic situation permits.

Tailwind component RWY 18:

If the tailwind component for RWY 18 exceeds 10 KT, this will be broadcast by ATIS.

Pilots unable to accept the greater tailwind component are requested to advise ATC as early as possible - at the latest when they request start-up approval.

Warning: In cases of strong winds, wind shear and increased turbulence must be expected on RWY 18.

1.2.2. NIGHT FLYING RESTRICTIONS AND OPERATIONAL RESTRICTIONS
OUTSIDE NIGHTTIME HOURS FOR CIVIL AVIATION

- a) Landing RWY Northwest (07L/25R) may only be used by ACFT up to and including code letter E in compliance with ICAO categorization. Airplanes with code letter F in compliance with categorization according to ICAO Attachment 14, jet airplanes, which cannot be classified into the airplane groups up to and including S 6.3 in compliance with the instructions for calculating noise protection zones as well as airplanes of the type MD11 may not use landing RWY Northwest (07L/25R). Take-offs of ACFT are not permitted from landing RWY Northwest (07L/25R).
- b) ACFT without a noise certification in accordance with ICAO Annex 16 are not permitted to take-off from or land on the whole RWY system of Frankfurt/Main APT during the entire hours of operation of Frankfurt/Main APT.

EDDF/FRA

JEPPESEN

FRANKFURT/MAIN, GERMANY

FRANKFURT/MAIN

26 JUL 24

10-1P1

AIRPORT BRIEFING

1. GENERAL

- c) ACFT that merely comply with the noise certification values in accordance with ICAO Annex 16, Volume I, Part II, Chapter 2 are not permitted to take off from or land on the whole RWY system of Frankfurt/Main APT during the entire hours of operation of Frankfurt/Main APT unless - documented by a certificate according to Article 11c, paragraph 7 of the German Aviation Regulation (LuftVO) in the version published on 27 March 1999 (Federal Law Gazette (BGBl.) I, p. 580), last amended by the second ordinance amending aviation regulations on requirements for the operation of ACFT dated 17 November 2006 (BGBl. I, p. 2644) - the German Federal Aviation Office (LBA) has granted an exemption for the ACFT concerned according to Article 11c, paragraphs 4 - 6 of the LuftVO or a Member State of the European Union has granted an exemption in accordance with Article 11c, paragraph 8 of the LuftVO.

- d) The following operational provisions apply to ACFT that are marginally compliant with ICAO Annex 16, Volume I, Part II, Chapter 3 within the meaning of Article 48a no. 4 of the Regulation on the Certification and Licensing in Aviation (LuftVZO), last amended by the second ordinance amending aviation regulations on requirements for flight crews dated 13 June 2007 (BGBl. I, p. 1048), the following operational regulations apply:

Take-offs and landings are not permitted on all days of the week between 2000-0800LT, unless an exemption in accordance with Article 48f, paragraph 1 of the LuftVZO or an individual exemption in accordance with paragraph 2 of the regulation has been granted.

From the beginning of the winter 2011/2012 scheduling period, take-offs and landings are not permitted between Friday, 2000LT and Monday, 0800LT, unless they have been granted an exemption in accordance with Article 48f, paragraph 1 of the LuftVZO or an individual exemption in accordance with paragraph 2 of the regulation.

ACFT arriving late or early whose landing is planned by the APT coordinator for a slot outside the operational restrictions up to 2000LT or from 0800LT may land until 2200LT and from 0600LT, provided that the late or early arrival was not envisaged as such in the flight plan (Article 25 LuftVO).

- e) Following the opening of the landing RWY Northwest, from the first day of the new scheduling period, which - because of the added capacity of the landing RWY Northwest - provides an increase in the coordinated hourly RWY capacity, take-offs and landings are not permitted on the whole RWY system of Frankfurt/Main APT between 2200-0600LT on all days of the week, unless otherwise provided.

Between 2200-2300LT as well as between 0500-0600LT, only such ACFT are permitted to take off and land that - have a noise certification value in accordance with ICAO Annex 16, Volume I, Part II, Chapter 4 and whose take-off or landing has been coordinated by the APT coordinator of the Federal Republic of Germany at least one day in advance.

Between 2300-0500LT scheduled ACFT movements are not permitted.

The following regulations apply to ACFT arriving late or early:

- ACFT that are not only marginally compliant with ICAO Annex 16, Volume I, Part III, Chapter 3 within the meaning of Article 48a of the LuftVZO, and ACFT fulfilling the provisions of ICAO Annex 16, Volume I, Part II, Chapter 4 and whose landing is planned by the APT coordinator for a slot up to 2200LT or from 0600LT, are permitted to land until 2400LT and/or from 0500LT without being counted against the quota as well as the maximum limit, provided that the late or early arrival was not envisaged as such in the flight plan (Article 25 of the LuftVO).
- ACFT fulfilling the provisions of ICAO Annex 16, Volume I, Part II, Chapter 4 and whose landing is planned by the APT coordinator for a slot between 2200-2300LT and between 0500-0600LT under the conditions set out, are permitted to land until 2400LT without being counted against the maximum limit provided that the late arrival was not envisaged as such in the flight plan (Article 25 of the LuftVO).

EDDF/FRA

JEPPESEN

FRANKFURT/MAIN, GERMANY

FRANKFURT/MAIN

26 JUL 24

10-1P2

AIRPORT BRIEFING

1. GENERAL

Early arrivals before 0500LT are not permitted.

ACFT are not permitted to use the landing RWY Northwest between 2300-0500LT. At Frankfurt/Main APT, take-offs and landings of ACFT conducting flight checks of radio, radar or APT facilities are permitted between 2200-0600LT only if the ACFT meet the provisions of ICAO Annex 16, Volume I, Part II, Chapter 4 and if it is absolutely necessary to conduct these checks during this period of time.

Propeller ACFT with a maximum take-off mass of less than 9,000kg may take-off and land between 2200-0600LT only under the restrictions outlined in sections above; instead of the mentioned noise certification values they must at least fulfill the higher sound-proofing requirements defined in Article 4 of the Airfield Noise Abatement Ordinance (Landeplatz-LaermschutzV) of 5 January 1999 (Federal Law Gazette I, page 35; German-language publication Nfl I 134/99).

- f) Delayed take-offs to be conducted in a period of restricted operations by an ACFT subject to the restrictions require individual permission by the local aviation supervision office. Permission may only be granted if the delay is due to reasons beyond the control of the air carrier concerned. Delayed take-offs are not permitted between 2400-0500LT.

EXCEPTIONS

Excluded from the restrictions mentioned above are:

- Landings of ACFT approaching Frankfurt/Main APT as an alternate aerodrome for meteorological, technical or other safety reasons as well as take-offs and landings of ACFT rendering medical assistance or on missions in disasters, as well as evacuation flights;
- Flights conducted particularly in the public interest.

Apart from this, the approving authority may grant exemptions from the operational restrictions only upon application in cases of particular hardship. It is not a case of particular hardship if the operational restriction makes the air carrier's ACFT turn-around planning more difficult or requires arrangements for passenger transfer or accommodation. Processing of applications is subject to charges.

As a rule, the application shall be submitted in writing - in urgent cases also via telephone - to:

Hessisches Ministerium fuer Wirtschaft, Energie,
Verkehr und Wohnen
Oertliche Luftaufsichtsstelle/local Aviation Supervision Office
Gebaeude (building) 514
60547 Frankfurt am Main/Germany
Tel.: 069/690-71717
Fax: 069/690-66150

The application shall contain:

- Applicant's name and, if necessary, name of the handling partner;
- Applicant's telephone and fax numbers;
- Name and address of the air carrier;
- E-mail address of the applicant for the invoice;
- Flight number;
- Registration and type of ACFT;
- Classification of the ACFT according to noise certification level (noise certificate of the ACFT according to Section 11c LuftVO);
- Planned time of departure for which the exemption is requested;
- Number of passengers;
- Weight of cargo in tonnes.

EDDF/FRA

JEPPESEN

FRANKFURT/MAIN, GERMANY

FRANKFURT/MAIN

26 JUL 24

10-1P3

AIRPORT BRIEFING

1. GENERAL

The reasons for the application shall be specified; the applicant shall state, in particular, to what extent the take-off delay is due to reasons beyond the control of the airline and/or where the hardship lies.

Take-off or landing clearances granted by ATC as well as other clearances do not automatically include the necessary exemption by the approval authority.

ATC will not grant exemptions via radiotelephony.

The pilot-in-command (PIC) shall report any landing conducted during a period of restricted operations by an ACFT subject to the restriction which does not meet any of the grounds for exemption according to the provisions to the local aviation supervision office immediately after landing and specify the reasons (declaration of PIC).

1.2.3. REVERSE THRUST

On the entire RWY system of Frankfurt Main APT, reverse thrust may only be used in the idle reverse thrust mode. Exceptions are unavoidable cases for safety reasons, e.g. because of the comparatively shorter LDA on RWY 25R/07L.

1.2.4. RUN-UP TESTS

Engine run-ups with thrust settings above an idle power setting may only be conducted at the following positions:

- On the apron of hangar 5 and in the run-up enclosure in the time between 0600-2200LT;
- In the time between 2200-0600LT, engine run-ups with the thrust setting on part-load on the apron of hangar 5, whereby on the position hangar 5 west the maximum power setting may only be taken to part-load low (up to 50% N1), as well as in the run-up enclosure; engine run-ups with the thrust setting on full-load may only be conducted in the run-up enclosure.

Engine run-ups shall be conducted in such a way that their duration of exposure on the next built-up area shall not, on average, result in a continuous sound level higher than 57 dB(A) during the day and 50 dB(A) during the night.

Engine run-ups in the time between 2200-0600LT with a thrust setting above an idle power setting shall be notified to the local aviation supervision office.

Engine test runs and run-ups as well as extensive maintenance work on ACFT at the positions are not permitted. Apron control may grant exceptions in justified cases.

1.3. SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM

1.3.1. OPERATION OF MODE S TRANSPONDERS

1.3.1.1. GENERAL

An Advanced Surface Movement Guidance and Control System, using Mode S multilateration and Automatic Dependent Surveillance-Broadcast (ADS-B), is in operation.

1.3.1.2. OPERATION OF MODE S TRANSPONDERS WHEN ACFT IS ON GROUND

Pilots shall ensure that Mode S transponders are able to operate when ACFT is on the ground.

Pilots shall select the assigned Mode A code as well as the Mode S call sign and set the transponder to AUTO Mode or ON (eg. XPDR):

- From request for push-back or taxi, whichever is earlier;
- After landing, continuously until ACFT is fully parked on stand;
- When fully parked on stand, select STBY.

For Mode S call sign, flight crew shall use ICAO defined format for entering the ACFT identification (e.g. DLH5MC, AFR6380, SAS589, BAW68PG).

To ensure that performance of systems based on SSR frequencies is not compromised, TCAS shall not be activated before reaching the RWY holding position. After landing, it shall be deselected after vacating RWY.

ACFT taxiing without flight plan shall select Mode A code 2000.

1. GENERAL

1.4. ACFT GUIDANCE BY MEANS OF TWY CENTERLINE LIGHTS, CLEARANCE BARS AND STOP BARS

1.4.1. GENERAL

Whenever the operation of CAT III low visibility procedures is announced, taxiing is restricted for all ACFT to TWYs with operating centerline lights, unless otherwise instructed.

The TWY centerline lights within the ILS-critical/sensitive area are color-coded (yellow/green) from RWY 07C/25C to TWYs L and M, from RWY 07R/25L to TWYs M and R, from RWY 07L/25R to TWY P, from RWY 18 from the North to TWY Y5 and from RWY 18 from the South to TWYs L and N. Landing ACFT are requested to report when they are clear of the color-coded TWY centerline lights to indicate that they have vacated the ILS-critical/sensitive area.

In order to facilitate ground movement, centerline lights, several clearance bars and stop bars are installed.

1.4.2. CLEARANCE BARS

Clearance bars are operated together with the centerline lighting and consist of three unidirectional surface lights showing YELLOW in the direction of approach to the intersection, arranged at 90° to the TWY centerline and partly displaced laterally to centerline.

If the traffic situation requires, ACFT may be instructed to hold at a specific clearance bar. If no such instruction is given, ACFT may taxi across the clearance bar without a specific clearance.

1.4.3. STOP BARS

Stop bars are operated independently of the centerline lighting and consist of unidirectional surface lights showing red in the direction of approach to a taxi-holding position/an intersection, spaced at intervals of 10?3m across the overall width of a TWY at 90° to the TWY centerline.

Taxiing across an operating stop bar is strictly prohibited.

1.5. REDUCED RWY SEPARATION

The aerodrome control unit may apply the following reduced RWY separation minima during the day and at night:

RWY	ACFT CAT 1 or 2 succeeding/departing ACFT		ACFT CAT 1 thru 3 succeeding/departing ACFT
	CAT 1	CAT 2	CAT 3
07L/25R	1969?600m	4921?1500m	7874?2400m
07C/25C			
07R/25L			
18	-	-	

Refer also to ATC pages Germany.

1.6. TAXI PROCEDURES

1.6.1. GENERAL

ACFT are permitted to taxi on the maneuvering area between RWY 07C/25C and TWY L only with the minimum engine revolutions absolutely required.

TWY Y7 (section East of ACFT stand V718) MAX wingspan 79'/24m.

TWYs N blue, N orange, N7 blue, N7 orange, N8 blue, N8 orange, western link between TWYs S33 and S and TWY Y7 (section between TWY Y5 and ACFT stand V718) MAX wingspan 118'/36m.

TWY N South MAX wingspan 171?52m.

TWY N7 (section North of TWY N) MAX wingspan 213'/65m.

Taxi connection between TWY S33 and TWY S (direction West) MAX wingspan 118?36m.

EDDF/FRA

JEPPesen

FRANKFURT/MAIN, GERMANY

FRANKFURT/MAIN

28 MAR 25

10-1P5

AIRPORT BRIEFING

1. GENERAL

On the entire operating area including ACFT hangars and their aprons, taxi maneuvers which do not take place prior to take-off or after landing of an ACFT must be carried out by means of ACFT tractors and not by means of engine power.

1.6.2. TAXIING ON APRON

ACFT stand taxilanes on aprons have been classified as follows:

- L (East of U);
- N (between N3 and N-East);
- N-Blue;
- N-Orange;
- N3 (North of N);
- N5 (North of N);
- N7 (North of N);
- N8 (North of N);
- N8-Blue;
- N8-Orange;
- N13;
- N14 (North of N);
- S4 (South of S);
- S5 (South of S);
- S6;
- S7 (South of S);
- S8 (South of S);
- S9 (South of S);
- S11 (South of S);
- S13;
- S15;
- S23;
- Y7

Reduced wing-tip clearance for ACFT of EASA code A, B and C on ACFT stand taxilanes is minimum 15'/4.5m from obstacles.

Reduced wing-tip clearance for ACFT of EASA code D, E and F on ACFT stand taxilanes is minimum 25'/7.5m from obstacles and is minimum 8'/2.5m from parallel apron roadways or height restricted objects.

ACFT type A380-800 will be towed with reduced obstacle clearance of 16?5m on TWY N11.

ACFT are permitted to taxi on the apron only at the indispensable minimum engine speed. As a rule, when taxiing (especially in turns), it shall be ensured that the engine power of all engines in operation is as synchronous as possible.

ACFT are not allowed to increase engine power significantly beyond idle speed, especially when taxiing within the apron cul-de-sacs or close to buildings. This particularly applies to the area of turn positions A1, B10 and C2.

When taxiing into parking stands, ACFT shall not stop in turns. If an ACFT comes to a stop, notify Apron Control prior to increasing engine power.

In the General Aviation area the wing-tip clearance is minimum 15'/4.5m.

Adhere strictly to the yellow, blue and orange taxi guidance lines. Adjust taxi speed accordingly.

1.6.3. TAXIING IN CASES OF LOW VISIBILITY

When leaving stand V173B at night and in other low visibility situations, nose gear lights shall generally be switched on. This shall not apply if ACFT is guided by Follow-me car and if the lights dazzle the pilot. In these situations, it is permitted to keep nose gear lights switched off even in cases of low visibility.

1.6.4. FAILURE OF AN ACFT's ANTI-COLLISION LIGHT (BEACON)

Before push-back or entering the apron, the red anti-collision lights (beacon) of an ACFT shall be switched on. If one anti-collision light (beacon) on the ACFT is inoperative, the pilot shall inform apron control and, additionally, switch on the white wing-tip strobe lights.

EDDF/FRA

JEPPESEN

FRANKFURT/MAIN, GERMANY

FRANKFURT/MAIN

23 MAY 25

10-1P6

AIRPORT BRIEFING

1. GENERAL

1.6.5. SEPARATE CENTERLINES FOR ACFT TYPE A380

Stands C14, C15 and C16 have separate centerlines only available for ACFT type A380 designated with C14S, C15S and C16S. To park other ACFT types, the centerlines C14, C15 and C16 shall be used. The separate centerlines C14S, C15S and C16S are parallel to centerlines C14, C15 and C16. Due to the short distance between the centerlines C14 and C14S, C15 and C15S as well as between C16 and C16S, the pilot shall pay special attention when taxiing onto the stand.

1.6.6. DEVIATIONS TO EASA REGULATIONS

1.6.6.1. TWYS

Fillets

At numerous TWYs, the distances from the taxi guideline to the TWY side strip marking are up to 1.6'/0.5m less than required in curves. Therefore, taxiing in TWY curves always has to be performed with great accuracy at Frankfurt APT.

Rapid exit TWYs: TWY L7, L8, L10, L15

The radius of the turn-off curve is significantly less than the required minimum of 550m on rapid exit TWYs.

RWY holding positions: TWY L, L1, L21, M, M29, T, U, W, W9, Y, Y1, Y3, S33

At the following holding positions, approach surface 07C and/or take-off climb surface 25C are penetrated by holding ACFT:

- TWY L: CAT I RWY holding position before RWY 18;
- TWY M: CAT I RWY holding position before RWY 18 and RWY holding position M2;
- TWY L21: CAT I RWY holding position before RWY 07C/25C;
- TWY W: RWY holding positions W4, W6 and W8;
- TWY Y: RWY holding position Y2;
- TWY Y1: RWY holding position Y10.

At the following holding positions, approach surface 25C and/or take-off climb surface 07C are penetrated by holding ACFT:

- TWY L1: CAT I RWY holding position before RWY 07C/25C;
- TWY T: RWY holding positions T2 and T4;
- TWY U: RWY holding positions U2 and U4.

At the following holding positions, approach surface 07R is penetrated by holding ACFT:

- TWY M29: CAT I RWY holding position before RWY 07R/25L;
- TWY S33: RWY holding position S40;
- TWY W: RWY holding positions W6, W8 and W10;
- TWY W9: RWY holding position W9;
- TWY Y: RWY holding position Y6;
- TWY Y3: RWY holding position Y12.

At the following holding positions, approach surface 25L and/or take-off climb surface 07R are penetrated by holding ACFT:

- TWY T: RWY holding position T6 and T8;
- TWY U: RWY holding positions U6 and U8.

TWY width: TWY Y5

The TWY width is slightly less than the required 75'/23m for ACFT with an outer main gear wheel span 30'/9m to 49'/15m.

1.6.6.2. CLEARANCE DISTANCES

At a majority of the ACFT stands, the clearance distances to neighbouring objects are less than required.

Especially for ACFT stands A26-A40, safe horizontal distances of at least 3.6'/0.8m to height-restricted objects are to be expected in the area of the wings.

1. GENERAL

1.7. PARKING INFORMATION

1.7.1. GENERAL

On stands A11 thru A40, A50 thru A69, B20 thru B48, C4 thru C16, D1 thru D4A, D5 thru D8A, E2, E2A, E5, E5A, E6 thru E9A, F211 thru F232, F233, F234thruF238, G1 thru G16, H2 thru H14, J2 thru J13, J17, K2 thru K10, V93thruV130, V143, V144, V266 thru V270, V322 thru V328 and V702 thru V721 push-back required.

In order to protect ground handling personnel from jet blast and to avoid damage, pilots are not allowed to increase engine power significantly above idle speed during taxi procedures into and out of stands, in particular for stands A1, B10 and C2.

On stands A11, A13 thru A26, A28, A30, A34, A36, A38, A40, A50, A52, A54 thru A54B, A58 thru A58B, A62 thru A62B, A66 thru A66B, A69, B20, B22thruB28, B41 thru B48, C4, C5, C6, C8, C11, C13, C14, C14S, C15, C15A, C15S, C16, C16A, C16S, D1, D1A, D4, D4A, D5, D5A, D8, D8A, E2, E2A, E5, E5A, E6, E6A, E9, E9A, F211, F213, F214, F215, F231, F232, F233, F237, F238, G1thruG9, H2, H4, H6, H8, H10, H12, H14, J5, J7, J9, J11, J13, J17, K2, K4, K6 , K8, K10, V106 thru V130 and V266 thru V270 Visual Docking Guidance System (A-VDGS) available.

1.7.2. USE OF AUXILLIARY POWER UNIT (APU)

The use of the APU shall be reduced to the absolute minimum required. The APU should be switched off at the end of deboarding at the latest and switched on again 5 minutes before the start of boarding at the earliest, provided this is possible in line with technical/operational requirements for the respective flight operation.

1.8. OTHER INFORMATION

Glider areas in vicinity of APT.

Bird strike warning system for RWY 07L APCH available.

For APT Collaborative Decision Making (A-CDM) see ATC pages Germany.

2. ARRIVAL

2.1. NOISE ABATEMENT PROCEDURES

Frankfurt ATC will apply the following "NIGHT Procedures":

Between 2200-0500LT all inbound ACFT shall expect a RNP X approach.

In addition, pilots should be prepared not to expect a descent clearance below FL070 until 6NM prior to reaching KUGUK and/or ORVIV (RWYs 25C/25L) and 6NM prior to reaching ULNOK and/or IBLUS (RWYs 07C/07R). Pilots shall adjust their speed accordingly and are urgently requested to conduct the descent from FL070 as continuous descent, whenever possible.

In the case that RNP X approach procedures cannot be applied due to the absence of RNP equipment or restricting weather minima, pilots will be issued a clearance for an ILS approach in compliance with the "NIGHT approach procedures" described below.

During "NIGHT approach procedures" inbound ACFT should expect clearances whereby the final track will be reached not closer to the APT than:

- approximately 18NM (RWYs 25 C/L); and
- approximately 19NM (RWYs 07 C/R) from THR.

This corresponds with the waypoints DF622 (25L), DF522 (25C), DF652 (07R) and DF552 (07C). The fly-by function of these waypoints is not affected.

Pilots should subsequently expect a clearance for an ILS approach with GP interception at 5000?

EDDF/FRA
FRANKFURT/MAIN

JEPPESEN
13 DEC 24 (10-1P8)

FRANKFURT/MAIN, GERMANY
AIRPORT BRIEFING

2. ARRIVAL

In addition, pilots should expect a clearance to descend below FL070 only 6NM prior to reaching the above-mentioned points. Pilots should adjust their speed accordingly and are urgently requested to perform their descent from FL070 as a continuous descent whenever possible.

These procedures may not be applied:

- to flights with STS/HOSP;
- in meteorological conditions such as CB,TS;
- in emergencies.

In the event of a technical failure of the ILS equipment, i.e. the need to fly non-precision approaches, descent clearances to 4000' will be issued.

2.2. CAT II/III OPERATIONS

RWYs 07L, 07C, 07R, 25L, 25C and 25R approved for CAT II/III operations, special aircrew and ACFT certification required.

2.3. RWY OPERATIONS

2.3.1. HIGH INTENSITY RWY OPERATIONS (HIRO)

ACFT of CAT SUPER will not be included in high intensity RWY operations, but should also vacate the RWY as quickly as possible.

At NIGHT, the use of HIRO is restricted to RWY 07L/25R and RWY 07R/25L.

2.3.1.1. APPROACH

ACFT on A- and D-STARs will be guided onto RWY 07L/25R, while ACFT on B- and C-STARs will be guided onto RWY 07R/25L. Irrespective of this, approaching ACFT which are planned to be parked at an ACFT stand in Cargo City South or at the GAT will preferably be guided to RWY 07R/25L. If operationally possible, ACFT which are parked in the Eastern section of the Northern apron and at T3 will also be guided to RWY 07R/25L.

When changing frequencies from LANGEN Radar to FRANKFURT Arrival initial call shall be restricted to

FRANKFURT ARRIVAL + CALLSIGN + WAKE TURBULENCE CATEGORY

if other than "M" to avoid frequency congestion. When being transferred from approach control to aerodrome control the initial call shall consist of

FRANKFURT TOWER, CALL SIGN, TYPE OF APPROACH + RWY

2.3.1.2. APPROACHES AT A GLIDE ANGLE OF 3.2°

RWY 07L/25R is equipped with two ILS systems for each landing direction.

One ILS per landing direction radiates signals for a glide angle of 3.2°, the other one for a glide angle of 3.0°.

The PAPI systems indicate the correct path down to a height of 200' for 3.0° and 3.2°.

Regular operations will be conducted under CAT I conditions only. The approach procedure will only be assigned if no long-lasting tail wind (more than 30 minutes) is expected. If tail wind prevails or is to be expected, the provisions of Item 1.2.1.1. will be applied and an ILS approach procedure at 3.0° will be assigned for RWY 07L/25R.

If it is not possible to conduct an approach at 3.2° for safety reasons, the pilot shall mention this in the initial call to LANGEN Radar. Such ACFT will be assigned another RWY.

2.3.1.3. ARRIVALS

Pilots are reminded:

- to plan and to name the expected rapid exit TWY during the APCH briefing;
- to vacate the RWY as quickly as possible;
- to adjust taxi speed after touchdown when it is evident that the ACFT will miss the planned rapid exit TWY. Low taxi speeds shall be avoided on the RWY.

EDDF/FRA

JEPPESEN

FRANKFURT/MAIN, GERMANY

FRANKFURT/MAIN

13 DEC 24

10-1P9

AIRPORT BRIEFING

2. ARRIVAL

Whenever RWY conditions permit, the following rapid exit TWYs shall be considered for planning:

RWY	ACFT	Preferred Turnoffs	Dist from THR ft (m)
07L	HEAVY (except SUPER)	P6	7382' (2250m)
	MEDIUM (JET)	P8	5741' (1750m)
	MEDIUM (PROP)/LIGHT	P10	4429? (1350m)
07C DAY only	HEAVY (except SUPER)	L9	8202' (2500m)
	MEDIUM/LIGHT	L11	5906' (1800m)
07R	HEAVY (except SUPER)	M13	7054' (2150m)
	MEDIUM/LIGHT	M15	5659' (1725m)
25L	HEAVY (except SUPER)	M21	7464' (2275m)
	MEDIUM (JET)	M17	6135' (1870m)
	MEDIUM (PROP)/LIGHT	M11	3560? (1085m)
25C DAY only	HEAVY (except SUPER)	L13	6742' (2055m)
	MEDIUM (JET)	L10	5577' (1700m)
	MEDIUM (PROP)/LIGHT	L8	3691' (1125m)
25R	HEAVY (except SUPER)	P20	7382? (2250m)
	MEDIUM (JET)	P16	5741? (1750m)
	MEDIUM (PROP)/LIGHT	P14	4429? (1350m)

Aerodrome Control may apply reduced separation on RWYs. Any changes in separation by Aerodrome Control shall be observed.

Pilots may only change the frequency after landing if instructed to do so by Aerodrome Control.

If pilots do not receive further taxi clearance, they shall stop in front of a RWY and the corresponding landing and take-off climb surfaces and TWYs L and N11.

2.4. TAXI PROCEDURES

To maintain smooth taxiing traffic, ACFT having landed on RWY 07R/25L will be guided, if possible, to defined change-over points, depending on the assigned parking position, to cross RWY 07C/25C.

This procedure will be withdrawn during adverse weather conditions, at the latest when CAT III operation is in force.

Exiting RWY 25C out of exit TWY L8 up to code C only.

2.5. OTHER INFORMATION

Parallel independent operation may be in force.

2.5.1. FLIGHT AND DESCENT PLANNING

For flight and descent planning purposes expect the following levels at the transfer points from LANGEN ACC to FRANKFURT APP:

- KERAX between FL130 and FL110;
- SPESA between FL120 and FL100;
- ROLIS at FL150;
- UNOKO between FL130 and FL110 (at RAMOB).

These levels shall only be used for planning purposes. The actual transfer level will be cleared by ATC individually.

EDDF/FRA

JEPPESEN

FRANKFURT/MAIN, GERMANY

FRANKFURT/MAIN

28 JUL 23

10-1P10

AIRPORT BRIEFING

3. DEPARTURE

3.1. DATALINK DEPARTURE CLEARANCE (DCL)

In addition to clearances via radio, DFS Deutsche Flugsicherung GmbH offers to issue start-up approval and en-route clearance by means of data link (Eurocae Standard ED85A).

The following time parameters apply to data link departure clearances (DCL):

- t_i 30 minutes prior to TOBT (earliest point in time for cockpit RCD message).
- t_f TSAT (latest point in time for cockpit RCD message).
- t_0 1 minute (defined standard).
- t_1 5 minutes (defined standard).
- t_2 1 minute (defined standard).

The clearance (CLD - departure clearance uplink message) issued by the tower is based on TSAT - "Start-up approved according TSAT". The TSAT issued at this point in time by means of the TSAT reporting channels applies. In addition, the pilot shall monitor TSAT updates. After completion of the data link process, the pilots shall maintain continuous air-ground voice communication watch on the frequency given in the CLD and shall refrain from asking questions about the start-up approval.

Depending on the traffic and weather situation, the process can be altered and the enroute clearance can be transmitted separately via data link (CLD) after receiving an RCD, while start-up approval will be issued at a later point in time.

Pilots are obliged to state during their initial call (RCD) whether only an enroute clearance (Request ENROUTE CLEARANCE) or a combined enroute and start-up approval (Request START-UP and ENROUTE CLEARANCE) is requested.

Pilots shall maintain continuous air-ground voice communication watch on frequency FRANKFURT Delivery throughout the complete process.

3.2. DE-ICING

3.2.1. GENERAL

Notification of ACFT de-icing may be sent on frequency 121.985 or via phone 069/690-30560 by the ACFT operator or his representative. In the period of 1 May up to and including 14 October, requests for ACFT de-icing can only be made by phone: 069/690-30560.

3.2.2. ACFT STANDS

The de-icing of ACFT at the respective ACFT stands will take place with engines switched off, passenger bridges cast off, and the ACFT clear of handling equipment.

3.2.3. REMOTE DE-ICING PADS (DPS)

The remote De-icing Pad West (DPW) falls within the responsibility of Aerodrome Control and includes de-icing pads DP1 and DP2. When carrying out de-icing procedure, responsibility will temporarily be transferred to FRANKFURT Apron.

If necessary for operations, the ADC will assign ACFT to be de-iced at additional locations (TWY N7, positions V159, V161 and G16A). Instructions for taxiing to and onto these positions will be issued by FRANKFURT Apron. ACFT will be guided by a marshaller to the de-icing position. The marshaller's instructions must be followed. When requested by FRANKFURT Apron, radiotelephony communication shall be established with the de-icing crew on the frequency assigned. ACFT parked on positions East of TWY N3 which intend to depart from RWY 18 can be de-iced at position G16A with running engines.

De-icing on DP1 and DP2 Center MAX wingspan less than 262'/80m.

De-icing on DP2 East and DP2 West MAX wingspan less than 118'/36m.

ACFT which were de-iced on DP1 will be guided to TWY W1 by Apron Control before handed over to ATC.

3. DEPARTURE

After de-icing on DP2 intersection take-off out of TWY W3 from RWY 18 required.

On the remote de-icing pads, only jet ACFT with running engines will be de-iced. Propeller ACFT will not be de-iced for safety reasons.

Underwing de-icing or with hot air, de-icing of undercarriage or de-icing with special viscosities, the control of the central engines (e.g. DC10, MD11), as well as special examinations of individual ACFT parts (e.g. hands on checks) cannot be carried out on the remote de-icing pads.

ACFT will be positioned on de-icing pad DP1 by an eyeline to the LEFT of centerline, which depicts the exact holding position to the pilot optically. This taxiing-aid is made up of 5 amber surface lights with single-sided beams. If the surface lighting or the eyeline is out of order, ACFT will be guided by a marshaller.

ACFT will be positioned on de-icing pad DP2 by an eyeline to the LEFT of the respective centerline, which enables the pilot to visualize the exact holding position. This eyeline is made up to 5 yellow surface lights which shine on one side. If centerline lighting or eyeline is out of operation, ACFT will be guided by a marshaller.

During the de-icing proceedings, the pilot-in-command shall ensure continuous listening watch on the respective frequency of FRANKFURT Apron. After de-icing proceedings have been concluded, the pilot-in-command shall report to FRANKFURT Apron that he is ready to taxi.

3.3. START-UP AND TAXI PROCEDURES

3.3.1. GENERAL

At TOBT, the ACFT must be ready for start-up or on-stand de-icing, and the pilot shall maintain continuous air-ground voice communication watch on the frequency of FRANKFURT Delivery.

Start-up may be requested and approved either via radio or data link (DCL).

Starting engines on push-back stands may only take place prior to push-back operation and after prior approval by apron control.

ACFT parking on stand B10 have to contact FRANKFURT Apron, prior to actual engine start-up.

3.3.2. FROM 0600-2200LT

All ACFT parked at positions East of TWY N3 and planned for departure from RWY 18 have to expect to taxi via TWYs U, T, R and S. Departure will take place basically from position S. Pilots unable to comply with these conditions shall advise FRANKFURT Apron upon initial contact.

3.3.3. STANDARD TAXI ROUTE (STR)

Name	Handover from Apron to DFS	Taxi Instructions	Holding Point
TRANSITION 1	STOP U2	U-S-S11-R-S28-S	S-RWY18

If the flight crew is unable to follow the standard taxi route TRANSITION 1, they shall inform during the initial call.

If the flight crew becomes unsure about TRANSITION 1, they shall request an individual clearance.

3.3.3.1. VOICE COMMUNICATION

Standard taxi route TRANSITION 1.

ACFT CALL SIGN.

Taxi to holding point RWY 18, intersection Sierra, via TRANSITION 1.

3. DEPARTURE

3.4. NOISE ABATEMENT PROCEDURES

3.4.1. OPERATIONAL RWY USE AND SID CONCEPT - STANDARD OPS

In general, pilots have to expect en-route clearance according to this concept. OPR are requested to file SID in flight plan according to this guideline. Deviating SID in flight plan will be changed automatically. Route details and further non-standard SIDs see 10-3 pages. Non-standards on pilot request only. Non-standard operation temporarily possible, if considered necessary by ATC. If unable to comply with restrictions, advise EDDF Delivery prior to start-up.

RWY-in-use	RWY (C)enter (L)eft (R)ight	SID Route Designator	Direction/ACFT CAT	NAV Spec
25/18			RWY 25C for DEP to the NW (OBOKA), N (MARUN), NE (TOBAK). <i>RWY 25L</i> with special authorization by <i>TWR only</i> . RWY 18 for DEP to the SW (SOBRA, ULKIG), S (ANEKI), SE (CINDY), E (SULUS).	
07/18			RWY 07C for DEP to the NW (OBOKA), N (MARUN), NE (TOBAK), E (SULUS) and EDDN Area (KOMIB). <i>RWY 07R</i> with special authorization by <i>TWR only</i> . RWY 18 for DEP to the SW (SOBRA, ULKIG), S (ANEKI), SE (CINDY).	

3. DEPARTURE

In general, pilots have to expect en-route clearance according to this concept. OPR are requested to file SID in flight plan according to this guideline. Deviating SID in flight plan will be changed automatically. Route details and further non-standard SIDs see 10-3 pages. Non-standards on pilot request only. Non-standard operation temporarily possible, if considered necessary by ATC. If unable to comply with restrictions, advise EDDF Delivery prior to start-up.				
RWY-in-use	RWY (C)enter (L)eft (R)ight	SID Route Designator	Direction/ACFT CAT	NAV Spec
25	C + L	FOXTROT	2-engined HEAVY ACFT to the N, NE.	RNAV-1
	C + L	GOLF	2-engined HEAVY ACFT to the NW, N, NE.	RNAV-1
			All ACFT to the NW, N, NE unable to comply with restrictions on SIDs northbound.	
	C	MIKE	All ACFT, except 2-engined HEAVY ACFT, to the NW, N, NE unable WHISKEY.	BRNAV
	C	WHISKEY	Shall be used by all ACFT, except 2-engined HEAVY ACFT, to the NW, N, NE complying with RNP-1 and RF-leg requirements instead of MIKE.	RNP-1*
	L	HOTEL	All ACFT RWY 25L (with special authorization by TWR only), except 2-engined HEAVY ACFT, to the NW, N, NE unable KILO. Shall be used by all ACFT RWY 25L (with special authorization by TWR only), except 2-engined HEAVY ACFT, to the NW, N, NE complying with RNP-1 and RF-leg requirements instead of HOTEL.	BRNAV
	L	KILO		RNP-1*
	C + L	NOVEMBER	Between 2200-0700LT: All 3- and 4-engined HEAVY and SUPER ACFT due to noise abatement.	RNAV-1
	C + L	PAPA	Single- and Twin-Props may use PAPA to the SW instead of RWY 18.	RNAV-1
	C + L	QUEBEC	In case of RNAV-failure and by ATC only.	NON RNAV
* Check SID description for required NAV-specification/sensor restriction.				

3. DEPARTURE

In general, pilots have to expect en-route clearance according to this concept. OPR are requested to file SID in flight plan according to this guideline. Deviating SID in flight plan will be changed automatically. Route details and further non-standard SIDs see 10-3 pages. Non-standards on pilot request only. Non-standard operation temporarily possible, if considered necessary by ATC. If unable to comply with restrictions, advise EDDF Delivery prior to start-up.				
RWY-in-use	RWY (C)enter (L)eft (R)ight	SID Route Designator	Direction/ACFT CAT	NAV Spec
07	C + R	CHARLIE	In case of RNAV-failure and by ATC only.	NON RNAV
	C + R	DELTA	All HEAVY and SUPER ACFT to the NW, N, NE, E.	BRNAV
			All MEDIUM and LIGHT ACFT to the NE, E or if considered necessary by ATC.	
			All MEDIUM and LIGHT ACFT to the NW, N if considered necessary by ATC.	
			Between 2200-0700LT: All ACFT to the NW, N, NE, E due to noise abatement.	
18	C + R	ECHO	Between 0700-2200LT: All MEDIUM and LIGHT ACFT to the NW, N.	BRNAV
		BRAVO	In case of RNAV-failure and by ATC only.	NON RNAV
		LIMA	All ACFT to the SW, S, SE. All ACFT to the NW (by ATC only).	RNAV-1*
		UNIFORM	Shall be used by all ACFT to the SW complying with the restrictions and RNP-1 and RF-leg requirements.	RNP-1
		SIERRA	All ACFT to the SE. All ACFT to the SW, NW, N, NE (by ATC only).	RNAV-1*
		ROMEO	Between 2300-0600LT: All ACFT to the NW, N, NE (by ATC only).	RNAV-1*
* Check SID description for required NAV-specification/sensor restriction.				

EDDF/FRA

JEPPESEN

FRANKFURT/MAIN, GERMANY

FRANKFURT/MAIN

4 AUG 23

10-1P15

Eff 10 Aug

AIRPORT BRIEFING

3. DEPARTURE

3.4.2. ADDITIONAL NOISE ABATEMENT MEASURES

3.4.2.1. OPERATIONAL CONCEPT "NOISE RESPITE PERIODS"

At APT, noise respite periods for operating direction 25 will be implemented in accordance with the following plan.

As a rule, the following RWY shall always be used during the times shown:

Between 0500-0600LT

- RWYs 25C/R shall be used for landing;
- RWY 25L shall be used for departing.

Between 2200-2300LT

- RWY 25L shall be used for landing;
- RWYs 18 and 25C shall be used for departing.

GENERAL

As a rule, noise respite periods will always be implemented in the time periods between 0500-0600LT and between 2200-2300LT, provided the conditions required by air traffic control are met.

In the provision of air traffic control, the following flights, among others, will be exempt from the regulations of the noise respite periods:

- Flights for which the pilot has declared an emergency or which are apparently in an emergency situation, including flights affected or threatened by unlawful interference;
- Security flights of air defense;
- Flights on search and rescue missions;
- Flights transporting sick or injured persons requiring immediate medical assistance (including flights designated as LHO (Live Human Organ));
- Government flights, including flights with Head of State status in accordance with the regulations laid down by the Federal Ministry of Transport and Digital Infrastructure (BMVI);
- Flights where a pilot requests the use of a certain RWY for safety reasons;
- Particularly endangered flights;
- Calibration flights.

In addition, noise respite periods will not be implemented when restricted by infrastructure or poor weather conditions (e.g. construction work, snow clearing).

Further information can be found in the "alliance paper" which is the basis for the respite periods (www.wirtschaft.hessen.de).

PROCEDURES

The provisions concerning delayed take-offs and landings of ACFT described in Para 1.2.2. remain unchanged.

If the APT operator Fraport or an airline using the APT thinks that the implementation of the noise respite period in the morning or evening is very likely to lead to operational disruptions, they shall inform the aviation supervision office (Luftaufsicht) about this. The aviation supervision office will then suspend the noise respite period without further formalities or verification processes.

The aviation supervision office (Luftaufsicht) will inform Fraport about the suspension of the noise respite period. Fraport will in turn inform the air navigation services and airlines using its communication channels.

EDDF/FRA

JEPPesen

FRANKFURT/MAIN, GERMANY

FRANKFURT/MAIN

7 JUL 23

10-1P16

Eff 13 Jul

AIRPORT BRIEFING

3. DEPARTURE

3.4.3. DEDICATED RWY OPERATIONS (DROPS)

When RWY 07 is in use, between 0500-0600LT RWY utilization will be arranged on **odd** calendar days:

All take-offs will be handled via RWY 18, thus avoiding the utilisation of the RWYs 07C/07R for take-offs.

When using the DROps procedures and operating direction 07 for departures to the North, only SIDs with the designation "R" will be allocated by the AD control tower. ACFT unable to adhere to "Cross FFM R-200 at or above 2500?" on the SIDs with the designation "R" will only be granted start-up approval and enroute clearance after coordination has taken place with the approach control unit.

Special Features

If meteorological conditions and/or other operational conditions do not allow the use of RWY 18, another RWY will be allocated after coordination has taken place with the approach control unit. This also applies to ambulance flights and/or flights with corresponding priority of service.

On **even** weekdays, the current procedures employed and published shall apply.

3.5. RWY OPERATIONS

3.5.1. CALCULATED TAKE-OFF TIME (CTOT) AND SLOT PROCEDURES

Departing ACFT shall be ready for take-off at the RWY 5 minutes prior to CTOT at the earliest, and at CTOT at the latest.

3.5.2. HIGH INTENSITY RWY OPERATIONS (HIRO)

ACFT that are not ready for departure will not receive clearance to line up.

Pilots are requested to report to Aerodrome Control if they are not ready to depart without being asked.

Pilots shall advise Aerodrome Control on initial call of the earliest possible intersection take-off.

When using RWYs 07 and 18, pilots of ACFT of wake turbulence categories light and medium which are taxiing to RWY 18 via TWY N or L due to their ACFT stand shall calculate the take-off run from the intersection to TWY M in order to avoid a departure delay due to required separation from arriving ACFT on RWY 07R.

Pilots who cannot accept a take-off run from the intersection of TWY M are requested to advise ATC at the same time they request start-up approval.

The entire RWY system is characterized by interdependencies. Pilots are thus expected to begin their take-off runs immediately after receiving their take-off clearance.

After take-off, ACFT should rapidly accelerate to the published maximum speed for the initial segment of the cleared SID. Afterwards, or if there is no published MAX speed, ACFT below FL100 should rapidly accelerate to 250 KT.

3.6. OTHER INFORMATION

3.6.1. GENERAL

When glider areas in vicinity of APT activated, expect higher crossing altitude by ATC for SIDs which require higher climb gradient than standard.

Winds between 200° and 160° in a clockwise direction and speeds of 15 KT and more shall be expected on RWY 18. Gusts and strong windshifts up to tail wind components may occur.