



OASIS Security Report

Hardcoded Secrets Security Analysis

Date: 2026-06-11 10:39:21 — **Model:** mistral:latest

Vulnerability: Hardcoded Secrets

Project: clean_contracts

Analysis root: ../clean

Table of contents

▢ Summary

▢ Statistics

▢ Files

▢ Detailed analysis

▢ Assistant

△ Errors & notes

Summary

Analyzed **2** file(s) for Hardcoded Secrets.

[Return to table of contents](#)

Statistics

Files analyzed: 2 **Total findings:** 2

Critical		0
High		0

Medium**2****Low****0**[Return to table of contents](#)

Files

File	Similarity
/work/project/dataset/clean/modifier_reentrancy_fixed.sol	0.640
/work/project/dataset/clean/simple_dao_fixed.sol	0.626

[Return to table of contents](#)

Detailed analysis

File 1: /work/project/dataset/clean/modifier_reentrancy_fixed.sol

Similarity score: 0.640

Source lines: 1-42

► Finding 1.1: Vulnerability found (Medium)

Vulnerable code

```
keccak256(abi.encodePacked("Nu Token")) == bank.supportsToken(),
```

Explanation

Hardcoded API key in the function.

Impact

Unauthorized access or account compromise

Entry point

supportsToken() modifier

Execution path

```

'''
+-----+
| Modifier |
+--->| supportsToken() |
+-----+
| Bank     |
+----->| supportsToken() |
+-----+'''

```

Parameters

Nu Token

Exploitation steps

- Find the API key in the code.
- Replace the API key with an attacker's key.

Example payloads

- Attacker's API key

Remediation

Use environment variables or secure vaults to store sensitive data such as API keys, instead of hardcoding them.

Secure example

```
'''  
keccak256(abi.encodePacked(_apiKey)) == bank.supportsToken(), // Replace  
_apiKey with a variable containing the API key securely.  
'''
```

File 2: /work/project/dataset/clean/simple_dao_fixed.sol

Similarity score: 0.626

Source lines: 1-34

► Finding 2.1: Vulnerability found (Medium)

Vulnerable code

```
donate(address to) payable public{...}
```

Explanation

Hardcoded contract address in the donate function.

Impact

Unauthorized access or account compromise due to exposure of sensitive data.

Entry point

donate function

Execution path

```
***
- Call donate(address)
  -> Function implementation
    <- Execute with hardcoded contract address
***
```

Exploitation steps

- Obtain source code
- Identify donate function
- Locate the contract address in donate function

Conditions

Attacker has access to the source code.

Remediation

Use environment variables or secure vaults to store the contract address.

Secure example

```
donate(address payable _to) public {...}
```


Assistant (triage / codebase)

In the OASIS dashboard (JSON report preview), use the chat below to triage findings, exploitation paths, and remediation. Select file, chunk, and finding to narrow context when needed.

[Return to table of contents](#)

Errors & Notes

No file-level errors were recorded.

[Return to table of contents](#)