## Thesis or Article

JeffGWood@mavs.uta.edu

July 6, 2016

# Contents

1	Introduction		
2	Background		
	2.1 Change of Reference		
	2.2 Points and Lines in the Image Plane	5	
	2.3 Epipolar constraint	5	
	2.4 Fundamental Matrix		
	2.5 Intrinsic Calibration Matrix	6	
	2.6 Essential Matrix	6	
3	Point Interpolation	7	
4	Image segmentation	9	
5	Process 10		

## Introduction

Through the development of applications such as augmented and virtual reality, object / scene reconstruction and visual effects, the process of generating images from an arbitrary vantage point can be found in a variety of applications. In this Thesis (or Article) I will discuss various methods for Image Creation from an arbitrary vantage point, which can be accomplished by two main methodologies of Geometric Construction and Image Synthesis. While both methods use stereo correspondance of multiple images, they differ in the way information is stored and used.

Geometric Construction (GC) contains information about the real-world spatial properties (Coordinates in space, Color), thus viewing results are non-constrained in vantage point. Image Synthesis (IS) relies on image properties (pixel displacement) and is thus viewing results are imited in the possible vantage points.

## Symbols and Notation

Symbol	Description
v	Vectors in lowercase bold
$\mathbf{v}_a$	$a$ -component of vector $\mathbf{v}$
${f M}$	Matrices in uppercase bold
$\mathbf{M}_{r,c}$	Entry in row $r$ and column $c$ of matrix $\mathbf{M}$
$\mathbf{x}$	Generic 3-dimensional spatial coordinate
$ ilde{\mathbf{x}}$	Generic 3-dimensional spatial coordinate (expressed homogeneously)
$\mathbf{y}$	Generic 2-dimensionals image coordinate
$ ilde{ extbf{y}}$	Generic 2-dimensional image coordinate (expressed homogeneously)
$\mathbf{u}$	Pixelized 2-dimensional image coordinate
$ ilde{ ext{u}}$	Pixelized 2-dimensional image coordinate (expressed homogeneously)
$^A\mathbf{x}$	Generic 3-dimensional spatial coordinate in reference frame $A$
${}^A{ ilde{ ilde{{f x}}}}$	Generic 3-dimensional spatial coordinate (expressed $homogeneously$ ) in reference frame A
$_{B}^{C}\mathbf{ ilde{M}}$	Change from of reference frame $B$ to reference frame $C$
s	Normalizing factor applied to homogeneous vector $\tilde{\mathbf{v}}$ such that original $\mathbf{v} = s \cdot \tilde{\mathbf{v}}$ is recovered
$^D\mathbb{S}$	Spatial reference frame $D$
$\left[\mathbf{x} ight]_{ imes}$	Skew-symmetric matrix version of vector ${\bf x}$ used as <i>left</i> -operand in the <i>cross</i> -
7	product such that $[\mathbf{x}]_{\times} \cdot \mathbf{y} = \mathbf{x} \times \mathbf{y}$
	Epipolar line
$\mathbb{P}$	Ray (or <i>pencil</i> ) of all possible vectors $\mathbf{x}$ where $\mathbf{x} = s \cdot \tilde{\mathbf{x}}$ for some value of $s$

# Background

Oridinarily, real-world data contains 3-dimensions. Because standard images only include 2-dimensional data, information regarding depth is lost (i.e. it is often difficult to judge distance from a single image without visual cues). Stereovision attempts to resolved this by finding the same point in both stereoscopic images (known as a corresponding point), and recovering the depth information. An elementry example of this occurs in stereoscopic images with relatively low distance between cameras (i.e they are right next to each other). Objects that are farther away from the observer occur closer together in the stereo images, whereas objects closer to the camera appear appear farther appart in the stereo-images.

### 2.1 Change of Reference

Each view from a pair of stereo-images encompasses its own frame of reference (i.e. the directions of forward or backward are unique to image and may differe considerably depending on camera displacement). This requires expressing points from different frames of reference (traditionally referred to left and right) in a single reference frame. As such it is necessary to be able to express coordinates in a given reference frame in any other reference frame.

Coordinates given in  ${}^{A}\mathbf{x}$  can be expressed in  ${}^{B}\mathbf{x}$  by the geometric transformation:

$${}^{B}\mathbf{x} = {}^{B}_{A}\mathbf{R} \cdot {}^{A}\mathbf{x} + {}^{B}_{A}\mathbf{t}$$

or

$${}^{B}\tilde{\mathbf{x}} = \begin{bmatrix} {}^{B}\mathbf{R} & {}^{B}\mathbf{t} \\ \hline 0 & 1 \end{bmatrix} \cdot {}^{A}\tilde{\mathbf{x}}$$

$$= {}_A^B \mathbf{M} \cdot {}^A \tilde{\mathbf{x}}$$

where  ${}^B_A\mathbf{M}$  is also the geometric transformation necessary to transform  ${}^B\mathbb{S}$  into  ${}^A\mathbb{S}$ .

Withough calculating any new quantities, rearranging allows us to express coordinates in  ${}^{B}\mathbf{x}$  in the  ${}^{A}\mathbf{x}$  reference frame as:

$${}_{A}^{B}\mathbf{R}^{\intercal}\cdot\left({}^{B}\mathbf{x}-{}_{A}^{B}\mathbf{t}\right)={}^{A}\mathbf{x}$$

and similarly transforms  ${}^{A}\mathbb{S}$  into  ${}^{B}\mathbb{S}.$ 

### 2.2 Points and Lines in the Image Plane

The image plane exists in  $\mathbb{R}^2$ . Points can be represented as vectors in the *standard*-form  $\mathbf{x} = [x, y]^\intercal$  or in *homogeneous*-form of  $\tilde{\mathbf{x}} = [x, y, 1]^\intercal$ . Points of the form  $\tilde{\mathbf{x}} = [x, y, 0]^\intercal$  are a special case that are referred to as *point at infinity*.

Lines in  $\mathbb{R}^2$  can also be represented in different contexts. The *vector offset* method calculates a line  $\mathbf{s}(t)$  between points  $\mathbf{x_1}$  and  $\mathbf{x_2}$  as

$$\mathbf{s}(t) = (1 - t) \cdot \mathbf{x_1} + \mathbf{x_2}$$
$$= \mathbf{x_1} + t \cdot (\mathbf{x_2} - \mathbf{x_1})$$

in which the line is parallel to the vector  $\mathbf{x_2} - \mathbf{x_1}$  and offset from the origin by the vector  $\mathbf{x_1}$ . Lines are also represented by their coefficients as  $\mathbf{l} = [a, b, c]^{\mathsf{T}}$  where

$$\mathbf{l}^{\mathsf{T}} \cdot \tilde{\mathbf{x}} = \begin{bmatrix} a & b & c \end{bmatrix} \cdot \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$
$$= a \cdot x + b \cdot y + c \cdot 1$$
$$= 0$$

This definition allows us to say point  $\tilde{\mathbf{x}}$  lies on line  $\mathbf{l}$  if  $\mathbf{l}^{\intercal} \cdot \tilde{\mathbf{x}} = 0$ . The line  $\mathbf{l}$  joining two points  $\tilde{\mathbf{x}}_1$  and  $\tilde{\mathbf{x}}_2$  is then calculated as the cross product of  $\mathbf{l} = \mathbf{x}_1 \times \mathbf{x}_2$ 

### 2.3 Epipolar constraint

Each point of of interest (also referred to as a *feature*) in a single image occurs in a 2-dimensional space at location  $\tilde{\mathbf{y}} = [x, y, 1]^{\mathsf{T}}$ . The same point in space when viewed from an image at a similar (though different) angle is referred to as a *corresponding point* with location of  $\tilde{\mathbf{y}}' = [x', y', 1]^{\mathsf{T}}$ . This set of infinitley many points form a 1-dimensional subspace (also known as a *pencil*) of the 3-dimensional world space.

The pencil, when viewed from an image at a different angled-position, appears as a line  $\mathbf{l}' = [A', B', C']^{\mathsf{T}}$ , known as the *epipolar line*. The fact that the corresponding point (in the *angled image*) of  $\tilde{\mathbf{y}}' = [x', y', 1]^{\mathsf{T}}$  occurs on this epipolar line is referred to as the *epipolar constraint*. It is formalized, using the previously given *line-point equality* of  $\mathbf{l}'^{\mathsf{T}} \cdot \tilde{\mathbf{y}}' = 0$  for the *angled* image. Similarly, the corresponding point of  $\tilde{\mathbf{y}}' = [x', y', 1]^{\mathsf{T}}$  produces an epipolar line in the *original image* of  $\mathbf{l} = [A, B, C]$ . The original point of  $\tilde{\mathbf{y}} = [x, y, 1]^{\mathsf{T}}$  must lie located on this epipolar line as required by the epipolar constraint, resulting in the *line-point equality* of  $\mathbf{l}^{\mathsf{T}} \cdot \tilde{\mathbf{y}} = 0$  for the *original image*.

When viewed in ther respective images, each point ( $\tilde{\mathbf{y}}$  and  $\tilde{\mathbf{y}}'$ ) has a pencil that coincides with that point. Since the pencils act as directional-vectors in 3-dimensional space, there is a unique 2-dimensional plane which contain both of these vectors, known as the epipolar plane. It is the intersection of the epipolar plane with the original image-plane and the angled image-plane that results in the epipolar lines of  $\mathbf{l}$  and  $\mathbf{l}'$ . In fact, the epipolar plane (in each image's reference frame)<sup>2</sup> has the same vector form of  $\mathbf{l} = \mathbf{P} = [A, B, C]^{\mathsf{T}}$  and  $\mathbf{l}' = \mathbf{P}' = [A', B', C']^{\mathsf{T}}$ . When testing whether points lie on the planes, we use spatial coordinates instead of the homogeneous image coordinates in the point-line-plane equality of  $\mathbf{P}^{\mathsf{T}} \cdot \mathbf{x} = 0$  and  $\mathbf{P}'^{\mathsf{T}} \cdot \mathbf{x}' = 0$ .

<sup>&</sup>lt;sup>1</sup>A change of reference is implied between coordinates  $\tilde{\mathbf{y}} = [x', y', 1]^\mathsf{T}$  and  $\tilde{\mathbf{y}}' = [x', y', 1]^\mathsf{T}$ . The majority of corresponding points do not occur at the same image coordinates between images (i.e  $\tilde{\mathbf{y}} \neq \tilde{\mathbf{y}}'$ ). The only way a single world coordinate can yield different image coordinates, is if a change of reference occurs in world space each time the image coordinates are obtained by dividing by  $z_{world}$ .

<sup>&</sup>lt;sup>2</sup>There is a single *epipolar plane* for pair of corresponding points  $\tilde{\mathbf{y}}$  and  $\tilde{\mathbf{y}}'$ , though it can be parameterized infinitley many ways, depending on the *frame of reference* 

### 2.4 Fundamental Matrix

In stereo vision, points  $(\tilde{\mathbf{x}})$  in one image I are related to the epipolar line (l') that contain the corresponding point  $(\tilde{\mathbf{x}}')$  by the Fundamental Matrix  $(\mathbf{F})$ .

$$l' = \mathbf{F} \cdot \tilde{\mathbf{x}}$$

### 2.5 Intrinsic Calibration Matrix

#### 2.6 Essential Matrix

When coordinates from a reference frame are expressed as *normalized image coordinates* the range of possible NIC values in the corresponding image are given by the

# Point Interpolation

Pixels from image a and image b can be used to create a new images. This is done by interpolating the pixel positions ( $\mathbf{p}_{uv}^a$  and  $\mathbf{p}_{uv}^b$ ) of corresponding points between frames. Because not all pixels are established as corresponding points, pixel correspondences between corresponding points ( $\mathbf{p}_{uv}$ ) are calculated through bi-linear interpolation of 4 established corresponding points:

$$\mathbf{P}_{uv} = \mathbf{P}_{00} \cdot (1 - u) \cdot (1 - v) + \mathbf{P}_{10} \cdot u \cdot (1 - v) + \mathbf{P}_{01} \cdot (1 - u) \cdot v + \mathbf{P}_{11} \cdot u \cdot v$$

This is done through the following series of linear equations

$$x_{uv} = \begin{bmatrix} u & 1 \end{bmatrix} \begin{bmatrix} -1 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} x_{00} & x_{01} \\ x_{10} & x_{11} \end{bmatrix} \begin{bmatrix} -1 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} v \\ 1 \end{bmatrix}$$
$$y_{uv} = \begin{bmatrix} u & 1 \end{bmatrix} \begin{bmatrix} -1 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} y_{00} & y_{01} \\ y_{10} & y_{11} \end{bmatrix} \begin{bmatrix} -1 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} v \\ 1 \end{bmatrix}$$

or as a single matrix equation of

$$\begin{bmatrix} x_{uv} & 0 \\ 0 & y_{uv} \end{bmatrix} = \begin{bmatrix} \mathbf{u} & \mathbf{0} \\ \mathbf{0} & \mathbf{u} \end{bmatrix}^T \begin{bmatrix} \mathbf{M} & \mathbf{0} \\ \mathbf{0} & \mathbf{M} \end{bmatrix}^T \begin{bmatrix} \mathbf{X} & \mathbf{0} \\ \mathbf{0} & \mathbf{Y} \end{bmatrix} \begin{bmatrix} \mathbf{M} & \mathbf{0} \\ \mathbf{0} & \mathbf{M} \end{bmatrix} \begin{bmatrix} \mathbf{v} & \mathbf{0} \\ \mathbf{0} & \mathbf{v} \end{bmatrix}$$

where

$$\mathbf{u} = \begin{bmatrix} u \\ 1 \end{bmatrix}, \mathbf{v} = \begin{bmatrix} v \\ 1 \end{bmatrix}, \mathbf{X} = \begin{bmatrix} x_{00} & x_{01} \\ x_{10} & x_{11} \end{bmatrix}, \mathbf{Y} = \begin{bmatrix} y_{00} & y_{01} \\ y_{10} & y_{11} \end{bmatrix}, \text{ and } \mathbf{M} = \begin{bmatrix} -1 & 1 \\ 1 & 0 \end{bmatrix}$$




Figure 3.1: Bi-Linear Point Correspondance

# Image segmentation

Central to our need to localize corresponding points in stereo images is the ability to partition images by similar texture or planar attributes compared to the image at hole. Such techniques are referred to as *image segmentation*.

Image segmentation of regions of similar color or textures region is often approached from a graph-theory standpoint, in which individual pixels form the nodes of the graph. Edges are formed by a number of methods, the simplest of which is for each pixel to have 4 equally weighted edges connecting with the 4 immediate adjoining pixels in *North*, *East*, *South* and *West* vicinities (referred to as the **4-neighborhood region**). A common variation of this is to *also* include the next 4 closest adjoining pixels in the *Northeast*, *Southeast*, *Southwest* and *Northwest* vicinities (referred to as the **8-neighborhood region**). More sophisticated methods assign edge weightings proportional to the difference in color values (*scalar gray values* or *euclidean distance of color vectors*) between each pixel-pair.

Binary segmentation (partitioning into two regions) can be accomplished through min-cut / max-flow algorithms

# **Process**

The system in question contains 3 main components

- 1. Image Acquisition System
  - Webcam / Kinect set-up
  - If Webcam should also contain Image-Processing module for:
    - Feature Identification
    - Point-correspondance
    - Sub-Pixel interpolation
- 2. Point Cloud Processing
  - Should take inputs
  - Should produce point-clouds as one of the output
  - (Possible) Options for Surface Reconstruction include:
    - Calculation of surface Normal through PCA
    - Mesh construction through Delaunay trianglulation
    - Parametrization of Bezier surface through linear-least squares.