
## **ADA Checklist for Existing Facilities**

## **Priority 2 – Access to Goods & Services**

Based on the 2010 ADA Standards for Accessible Design



The layout of the building should allow people with disabilities to obtain goods and services and to participate in activities without assistance.





This checklist was produced by the New England ADA Center, a project of the Institute for Human Centered Design and a member of the ADA National Network. This checklist was developed under a grant from the Department of Education, NIDRR grant number H133A060092-09A. However the contents do not necessarily represent the policy of the Department of Education, and you should not assume endorsement by the Federal Government.

Questions or comments on the checklist contact the New England ADA Center at 617-695-0085 voice/tty or ADAinfo@NewEnglandADA.org

For the full set of checklists, including the checklists for recreation facilities visit www.ADAchecklist.org.

Prio	rity 2 – Access to Goods 8	& Services		Comments	Possible Solutions
2.1	Does the accessible entrance provide direct access to the main floor, lobby and elevator? [See 2010 ADA Standards for Accessible Design – 206.4]	□Yes □No		Photo #:	<ul> <li>Create accessible route</li> <li>•</li> </ul>
Inter	ior Accessible Route			1	
2.2	Are all public spaces on at least one accessible route? [206.2.4]	□ <sub>Yes</sub> □ <sub>No</sub>			<ul><li>Create accessible route</li><li></li></ul>
				Photo #:	
2.3	Is the route stable, firm and slip-resistant? [40.2, 302.1]	□Yes □No			<ul><li>Repair uneven surfaces</li><li>•</li></ul>
				Photo #:	
2.4	Is the route at least 36 inches wide? [403.5.1]  Note: The accessible route can narrow to 32 inches min. for a max. of 24 inches. These narrower portions of the route must be at least 48 inches from each other.	Yes No Measurement:	36"min 48"min 24"max+ 32"min 32"min		• Widen route •
				Photo #:	

2.5	If the route is greater than 200 feet in length and less than 60 inches wide, is there a passing space no less than 60 x 60 inches? [403.5.3]	Yes No Measurement:	36"min 60"min	Photo #:	<ul><li>Widen route for passing space</li><li></li></ul>
2.6	Is the running slope no steeper than 1:20, i.e. for every inch of height change there are at least 20 inches of route run? [403.3]  Note: If the running slope is steeper than 1:20, treat as a ramp and add features such as edge protection and handrails.	Yes No		Photo #:	• Regrade •
2.7	Is the cross slope no steeper than 1:48? [403.3]	Yes No Measurement:		Photo #:	• Regrade •
2.8	Do all objects on circulation paths through public areas, e.g. fire extinguishers, drinking fountains, signs, etc., protrude no more than 4 inches into the path?  Or	Yes No	4"max Or		Remove object     Add tactile warning such as permanent planter or partial walls

	If an object protrudes more than 4 inches, is the bottom leading edge at 27 inches or lower above the floor? [307.2]  Or  Is the bottom leading edge at 80 inches or higher above the floor? [307.4]	Yes No  Measurement:  Yes No  Measurement:	Or BATHROOM 80"min	Photo #:	
2.9	Are there elevators or platform lifts to all public stories?  Note: Vertical access is not required in new construction or alterations if a facility is less than three stories or has less than 3,000 square feet per story, unless the facility is a shopping center, shopping mall, professional office of a health care provider, transportation terminal, state facility or local government facility	□Yes □No		Photo #:	<ul> <li>Install if necessary</li> <li>Offer goods and services on an accessible story</li> </ul>

Ramp	os				
2.10	If there is a ramp, is it at least 36 inches wide? [405.5]  Note: If there are handrails, measure between the handrails.	Yes No Measurement:	36"min	Photo #:	<ul><li>Alter ramp</li><li>•</li></ul>
2.11	Is the surface stable, firm and slip resistant? [405.4]	□Yes □No		Photo #:	Resurface ramp
2.12	For each section of the ramp, is the running slope no greater than 1:12, i.e. for every inch of height change there are at least 12 inches of ramp run? [405.2]  Note: Rises no greater than 3 inches with a slope no steeper than 1:8 and rises no greater than 6 inches with a slope no steeper than 1:10 are permitted when due to space limitations.	Yes No Measurement:	1 12 min	Photo #:	Lengthen ramp to decrease slope     Relocate ramp

2.13	Is there a level landing that is at least 60 inches long and at least as wide as the ramp:				<ul><li> Alter ramp</li><li> Relocate ramp</li></ul>
	At the top of the ramp?  At the bottom of the ramp? [405.7.2, 405.7.3]	Yes No  Measurement:  Yes No	landing widths must be at least equal to ramp width		
		Measurement:		Photo #:	
2.14	Is there a level landing where the ramp changes direction that is at least 60 x 60 inches? [405.7.4]	Yes No Measurement:	60°min	Photo #:	<ul> <li>Increase landing size</li> <li>•</li> </ul>
2.15	If the ramp has a rise higher than 6 inches are there handrails on both sides? [405.8]	Yes No Measurement:	if greater than 6"	Photo #:	• Add handrails •

2.16	Is the top of the handrail gripping surface no less than 34 inches and no greater than 38 inches above the ramp surface? [505.4]	Yes No Measurement:	34"-38"	Photo #:	Adjust handrail height
2.17	Is the handrail gripping surface continuous and not obstructed along the top or sides? [505.3]  If there are obstructions, is the bottom of the gripping surface obstructed no more than 20%? [505.6]	☐Yes ☐No ☐Yes ☐No Measurement:		Photo #:	Reconfigure or replace handrails
2.18	If the handrail gripping surface is circular, is it no less than 1 ¼ inches and no greater than 2 inches in diameter? [505.7.1]	Yes No Measurement:	11/4-2*	Photo #:	<ul> <li>Replace handrails</li> <li>•</li> </ul>
2.19	If the handrail gripping surface is non-circular:  Is the perimeter no less than 4 inches and no greater than 6¼ inches?	Yes No Measurement:	4"-6 1/4" perimeter		Replace handrails

	Is the cross section no greater than 2¼ inches in diameter? [505.7.2]	Yes No Measurement:		Photo #:	
2.20	Does the handrail:  Extend at least 12 inches horizontally beyond the top and bottom of the ramp?  Return to a wall, guard, or landing surface? [505.10.1]	Yes No Measurement:  Yes No	12" min		Alter handrails
	Note: If a 12" extension would be hazardous (in circulation path), it is not required			Photo #:	
2.21	To prevent wheelchair casters and crutch tips from falling off:  Does the surface of the ramp extend at least 12 inches beyond the inside face of the handrail?  Or  Is there a curb or barrier that prevents the passage of a 4-inch diameter sphere?  [405.9.1, 405.9.2]	☐Yes ☐No  Measurement:  ☐Yes ☐No  Measurement:	12"min	Photo #:	<ul> <li>Add curb</li> <li>Add barrier</li> <li>Extend ramp width</li> <li>•</li> </ul>

Eleva	Elevators – Full Size & LULA (limited use, limited application) LULA elevators are often used in alterations.							
2.22	If there is a full size or LULA elevator, are the call buttons no higher than 54 inches above the floor? [407.2.1.1]	Yes No  Measurement:	54"max	Photo #:	<ul><li>Change call button height</li><li>•</li></ul>			
2.23	If there is a full size or LULA elevator, does the sliding door reopen automatically when obstructed by an object or person?* [407.3.3]	□Yes □No		Photo #:	* If constructed before 3/15/2012 and manually operated, the door is not required to reopen automatically  • Install opener •			
2.24	If there is a LULA elevator with a swinging door:  Is the door power- operated?  Does the door remain open for at least 20 seconds when activated? [403.3.2]	☐Yes ☐No ☐Yes ☐No Time:		Photo #:	<ul> <li>Add power operated door</li> <li>Adjust opening time</li> </ul>			

2.25	If there is a full size elevator:  Is the interior at least 54 inches deep by at least 36 inches wide with at least 16 sq. ft. of clear floor area?  Is the door opening width at least 32 inches?  [407.4.1 Exception]	Yes No  Measurement:  Yes No  Measurement:	-36"min → 54"min	Photo #:	• Replace elevator •
2.26	If there is a LULA elevator, is the interior:  At least 51 inches deep by 51 inches wide with a door opening width of at least 36 inches?  Or  At least 54 inches deep by at least 36 inches wide with at least 15 sq. ft. of clear floor area and a door opening width of at least 32 inches?  [408.4.1 Exceptions 1 and 2]	Yes No Measurement:  Yes No Measurement:	51"min ————————————————————————————————————	Photo #:	• Replace elevator •
2.27	If there is a full size or LULA elevator, are the in-car controls:  No less than 15 inches and no greater 48 inches above the floor?  Or	Yes No Measurement:	48"max 15"min		• Change control height •

	Up to 54 inches above the floor for a parallel approach? [408.4.6, 407.4.6.1]	Yes No Measurement:	54"max 15"min	Photo #:	
2.28	If there is a LULA elevator, are the in-car controls centered on a side wall? [408.4.6]	Yes No Measurement:		Photo #:	<ul> <li>Reconfigure controls</li> <li>•</li> </ul>
2.29	If there is a full size or LULA elevator:  Are the car control buttons designated with raised characters?  Are the car control buttons designated with Braille? [407.4.7.1, 703.2]	□Yes □No	5 6 0 3 0 4 0 *1 0 2 0	Photo #:	Add raised characters     Add Braille
2.30	If there is a full size or LULA elevator, are there audible signals which sound as the car passes or is about to stop at a floor? [407.4.8]	□Yes □No		Photo #:	<ul> <li>Install audible signals</li> <li>•</li> </ul>

2.31	If there is a full size or LULA elevator:  Is there a sign on both door jambs at every floor identifying the floor?	□Yes □No			<ul><li>Install signs</li><li>Change sign height</li><li></li></ul>
	Is there a tactile star on both jambs at the main entry level?	□Yes □No			
	Do text characters contrast with their backgrounds?	□Yes □No			
	Are text characters raised?	□Yes □No	48"min		
	Is there Braille?	□Yes □No			* If constructed before
	Is the sign mounted between 48 inches to the baseline of the lowest character and 60 inches to the baseline of the highest character above the	Yes No  Measurement:			3/15/2012 and mounted no higher than 60 inches to the centerline of the sign, relocation is not required
	floor?* [407.2.3, 408.2.3]			Photo #:	
Platfo	orm Lifts				
2.32	If a lift is provided, can it be used without assistance from others? [410.1]	□Yes □No		Photo #:	<ul> <li>Reconfigure so independently operable</li> <li>•</li> </ul>
				T 11010 #.	

2.33	Is there a clear floor space at least 30 inches wide by at least 48 inches long for a person using a wheelchair to approach and reach the controls to use the lift? [410.5]	Yes No Measurement:	48"min 30"min 48"min	Photo #:	<ul> <li>Remove obstructions</li> <li>•</li> </ul>
2.34	Are the lift controls no less than 15 inches and no greater than 48 inches above the floor? [410.5]	Yes No Measurement:	15"-48"	Photo #:	<ul> <li>Change control height</li> <li>•</li> </ul>
2.35	Is there a clear floor space at least 36 inches wide by at least 48 inches long inside the lift? [410.3]	Yes No Measurement:	36 " min 48" min	Photo #:	• Replace lift •
2.36	If there is an end door, is the clear opening width at least 32 inches? [410.6]	Yes No Measurement:	32"min	Photo #:	Alter door width

2.37	If there is a side door, is the clear opening width at least 42 inches? [410.6]	Yes No Measurement:	42"min	Photo #:	<ul><li>Alter door width</li><li></li></ul>
Signs	"Tactile characters" are read using to	ouch, i.e. raised chara	acters and Braille.		
2.38	If there are signs designating permanent rooms and spaces not likely to change over time, e.g. room numbers and letters, room names, and exit signs: [216.2]  Do text characters contrast with their backgrounds? [703.5]  Are text characters raised? [703.2]  Is there Braille? [703.3]  Is the sign mounted: On the wall on the latch side of the door? [703.4.2]	□Yes □No □Yes □No □Yes □No □Yes □No	354 LIBRARY		<ul> <li>Install tactile sign</li> <li>Relocate sign</li> <li>*</li> </ul>
	Note: Signs are permitted on the push side of doors with closers and without hold-open devices.				*If constructed before 3/15/2012 and a person may approach within 3 inches of the sign without

□<sub>Yes</sub> □<sub>No</sub> With clear floor space beyond encountering protruding the arc of the door swing objects or standing within centered on between the closed position the door swing, tactile characters Measurement: and 45-degree open position, relocation not required at least 18 x 18 inches \*If constructed before centered on the tactile characters?\* 3/15/2012 and mounted 18"min no higher than 60 inches [703.4.2] □Yes □No to the centerline of the So the baseline of the lowest sign, relocation not Measurement: character is at least 48 inches required above the floor and the baseline of the highest 60"max character is no more than 60 inches above the floor? \* 48"min [703.4.1] Note: If the sign is at double doors with one active leaf, the sign should be on the inactive leaf; if both leaves are active, the sign should be on the wall to the right of the right leaf. Photo #: • Install signs with 2.39 If there are signs that provide direction to or information contrasting characters • Change sign height about interior spaces: □yes □No Do text characters contrast with their backgrounds? LIBRARY. [703.5.1] **③** Is the sign mounted so that  $\square_{\mathsf{Yes}} \square_{\mathsf{No}}$ 40"min characters are at least 40 inches above the floor? Measurement: [703.5.6] Note: Raised characters and Photo #: Braille are not required.

**Institute for Human Centered Design** 2014

www.ADAchecklist.org

Priority 2 – Access to Goods & Services

Interi	ior Doors – to classrooms, me	edical exam roon	ns, conference rooms, etc.		
2.40	Is the door opening width at least 32 inches clear, between the face of the door and the stop, when the door is open 90 degrees? [404.2.3]	Yes No Measurement:	32" min————————————————————————————————————	Photo #:	<ul><li>Install offset hinges</li><li>Alter the doorway</li></ul>
2.41	If there is a front approach to the pull side of the door, is there at least 18 inches of maneuvering clearance beyond the latch side plus at least 60 inches clear depth?  Note: See 2010 Standards 404.2.4 for maneuvering clearance requirements on the push side of the door and side approaches to the pull side of the door.  On both sides of the door, is the floor surface of the maneuvering clearance level (no steeper than 1:48)? [404.2.4]	Yes No  Measurement:  Yes No  Measurement:	18"min	Photo #:	<ul> <li>Remove obstructions</li> <li>Reconfigure walls</li> <li>Add automatic door opener</li> </ul>

2.42	If the threshold is vertical is it no more than ¼ inch high?  Or	Yes No Measurement:			<ul><li>Remove or replace threshold</li></ul>
	No more than ½ inch high with the top ¼ inch beveled no steeper than 1:2, if the threshold was installed on or after the 1991 ADA Standards	Yes No Measurement:	1/4"max—		•
	went into effect (1/26/93)? Or	Yes No Measurement:			
	No more than ¾ inch high with the top ½ inch beveled no steeper than 1:2, if the threshold was installed before the 1991 ADA Standards went into effect (1/26/93)? [404.2.5, 303.2]		1/2"max-[		
	Note: The first ¼ inch of the ½ or ¾ inch threshold may be vertical; the rest must be beveled.		3/4"max -[	Photo #:	
2.43	Is the door equipped with hardware that is operable with one hand and does not require tight grasping, pinching or twisting of the wrist?	□Yes □No			<ul> <li>Replace inaccessible knob with lever, loop or push hardware</li> <li>Add automatic door opener</li> </ul>
	Door handle?	Yes No			•
	Lock (if provided)? [404.2.7]	□Yes □No		Photo #:	

2.44	Are the operable parts of the hardware no less than 34 inches and no greater than 48 inches above the floor? [404.2.7]	Yes No Measurement:	34"- 48"	Photo #:	<ul><li>Change hardware height</li><li></li></ul>
2.45	Can the door be opened easily (5 pounds maximum force)? [404.2.9]  Note: You can use a pressure gauge or fish scale to measure force. If you do not have one you will need to judge whether the door is easy to open.	Yes No Measurement:	5 lbf	Photo #:	<ul> <li>Adjust or replace closers</li> <li>Install lighter doors</li> <li>Install power-assisted or automatic door openers</li> </ul>
2.46	If the door has a closer, does it take at least 5 seconds to close from an open position of 90 degrees to a position of 12 degrees from the latch? [404.2.8.1]	Yes No Measurement:	1)2°	Photo #:	• Adjust closer •

2.47	Are aisles and pathways to goods and services, and to one of each type of sales and service counters, at least 36 inches wide? [403.5.1]	Yes No Measurement:	36" min	Photo #:	<ul> <li>Rearrange goods,</li> <li>equipment and furniture</li> <li>•</li> </ul>
2.48	Are floor surfaces stable, firm and slip resistant? [302.1]	□Yes □No			Change floor surface
				Photo #:	
2.49	If there is carpet:  Is it no higher than ½ inch?	Yes No Measurement:	½"max		• Replace carpet •
	Is it securely attached along the edges? [302.2]	□Yes □No		Photo #:	
Contr	ols – light switches, security	and intercom sys	stems, emergency/alarm boxes, et	C.	
2.50	Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward or parallel approach? [305.3]	Yes No  Measurement:	48"max		Change height of control      *If constructed before
	Are the operable parts no higher than 48 inches above the floor?* [309.3, 308]	Measurement:	30"min		3/15/2012 and a parallel approach is provided, controls can be 54 inches above the floor

			48″mi	48"max 30"min	Photo #:	
2.51	Can the control be operated with one hand and without tight grasping, pinching, or twisting of the wrist? [309.4]	□Yes □No			Dhata #	<ul><li>Replace control</li><li>•</li></ul>
Cooki	war Assaulte Augus thoute	ue enditeriores	-+	tou atulo algorius aus	Photo #:	
	ng: Assembly Areas – theate	ers, auditoriums, s	staulums, thea	ter style classrooms	s, etc.	
2.52	Are an adequate number of wheelchair spaces provided?	Yes No	# of Seats	Wheelchair Spaces		Reconfigure to add     wheelchair spaces
	[221.2.1]	Total #:	4 - 25	1	-	•
		Wheelchair #:	26 - 50	2	-	
		wheelchair #:	51 - 150	4	-	
			151 - 300	5		
			300+ see 2010	) Standards 221.2.1.	Photo #:	
2.53	Are wheelchair spaces dispersed to allow location choices and viewing angles equivalent to other seating, including specialty seating areas that provide distinct	□Yes □No	A			<ul> <li>Reconfigure to disperse wheelchair spaces</li> <li>•</li> </ul>

2.54	Where people are expected to remain seated, do people in wheelchair spaces have a clear line of sight over and between the heads of others in front of them? [802.2.1.1, 802.1.1.2]	□Yes □No		Photo #:	<ul> <li>Alter for line of sight</li> <li>•</li> </ul>
2.55	Where people are expected to stand, do people in wheelchair spaces have a clear line of sight over and between the heads of others in front of them? [802.2.2.1, 802.1.2.2]	□Yes □No		Photo #:	<ul> <li>Alter for line of sight</li> <li>•</li> </ul>
2.56	If there is a single wheelchair space, is it at least 36 inches wide? [802.1.2]	Yes No Measurement:		Photo #:	• Alter space •
2.57	If there are two adjacent wheelchair spaces, are they each at least 33 inches wide? [802.1.2]	Yes No Measurement:	→ 33"min → 33"min →	Photo #:	• Alter spaces •

2.58	If the wheelchair space can be entered from the front or rear, is it at least 48 inches deep? [802.1.3]	Yes No Measurement:	48"min	Photo #:	<ul><li>Alter space</li><li></li></ul>
2.59	If the wheelchair space can only be entered from the side, is it at least 60 inches deep? [802.1.3]	Yes No Measurement:	60"min -	Photo #:	• Alter space •
2.60	Do wheelchair spaces adjoin, but not overlap, accessible routes? [802.1.4]	□Yes □No	Accessibe Route	Photo #:	• Alter spaces •
2.61	Is there at least one companion seat for each wheelchair space? [221.3]	□Yes □No		Photo #:	<ul> <li>Add companion seats</li> <li>•</li> </ul>


2.62	Is the companion seat located so the companion is shoulder-to-shoulder with the person in a wheelchair? [802.3.1]	□Yes □No		Photo #:	<ul><li>Alter seating</li><li></li></ul>
2.63	Is the companion seat equivalent in size, quality, comfort and amenities to seating in the immediate area? [802.3.2]	□Yes □No		Photo #:	<ul><li>Add equivalent seating</li><li></li></ul>
Seati	ng: At dining surfaces (resta	urants, cafeterias	s, bars, etc.) and non-employee wo	rk surfaces (libraries, confe	rence rooms, etc.)
2.64	Are at least 5%, but no fewer than one, of seating and standing spaces accessible for people who use wheelchairs? [226.1]	Yes No  Total #:  Wheelchair #:		Photo #:	<ul><li>Alter to provide accessible spaces</li><li></li></ul>
2.65	Is there a route at least 36 inches wide to accessible seating? [403.5.1]	Yes No Measurement:	36"min	Photo #:	• Widen route •

At the accessible space(s), is the top of the accessible surface no less than 28 inches and no greater than 34 inches above the floor? [902.3]  Note: If for children, the top should be no less than 26 inches and no greater than 30	Yes No Measurement:	28"-34"		<ul> <li>Alter surface height</li> <li>•</li> </ul>
inches above the floor.			Photo #:	
Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward approach? [305.3]	Yes No Measurement:	30"		<ul> <li>Alter table or work surface</li> <li>Add accessible table or work surface</li> </ul>
Does it extend no less than 17 inches and no greater than 25 inches under the surface?	Yes No Measurement:			
Is there knee space at least 27 inches high and at least 30 inches wide? [306.2, 306.3]	Yes No Measurement:	27"min 30"min 17"- 25"		
Note: If for children, the knee space may be 24 inches high.			Photo #:	
	the top of the accessible surface no less than 28 inches and no greater than 34 inches above the floor? [902.3]  Note: If for children, the top should be no less than 26 inches and no greater than 30 inches above the floor.  Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward approach? [305.3]  Does it extend no less than 17 inches and no greater than 25 inches under the surface?  Is there knee space at least 27 inches high and at least 30 inches wide? [306.2, 306.3]  Note: If for children, the knee	the top of the accessible surface no less than 28 inches and no greater than 34 inches above the floor?  [902.3]  Note: If for children, the top should be no less than 26 inches and no greater than 30 inches above the floor.  Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward approach?  [305.3]  Does it extend no less than 17 inches and no greater than 25 inches under the surface?  Is there knee space at least 27 inches high and at least 30 inches wide?  [306.2, 306.3]  Note: If for children, the knee	the top of the accessible surface no less than 28 inches and no greater than 34 inches above the floor?  [902.3]  Note: If for children, the top should be no less than 26 inches and no greater than 30 inches above the floor.  Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward approach?  [305.3]  Does it extend no less than 17 inches and no greater than 25 inches under the surface?  Is there knee space at least 27 inches high and at least 30 inches wide?  [306.2, 306.3]  Note: If for children, the knee	the top of the accessible surface no less than 28 inches and no greater than 34 inches above the floor?  [902.3]  Note: If for children, the top should be no less than 26 inches and no greater than 30 inches above the floor.  Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward approach?  [305.3]  Does it extend no less than 17 inches and no greater than 25 inches under the surface?  Is there knee space at least 27 inches high and at least 30 inches wide?  [306.2, 306.3]  Note: If for children, the knee

2.68	Is there at least one space at least 36 inches wide by at least 48 inches long for a person in a wheelchair? [802.1.2, 802.1.3]	Yes No Measurement:	36"x48"	Photo #:	<ul> <li>Move furniture and equipment to provide space</li> <li>•</li> </ul>
Bench	nes – In locker rooms, dressir	ng rooms, fitting	rooms This section does not apply to	any other bences.	
2.69	In locker rooms, dressing rooms and fitting rooms, is there at least one room with a bench? [222.1, 803.4]	□Yes □No		Photo #:	• Add bench •
2.70		Yes No Measurement:  Yes No Measurement:  Yes No Measurement:  Yes No Measurement:	48" min 30" min 20"- 24"	Photo #:	Move bench     Replace bench     Affix bench to wall

			17"- 19"	Photo #:	
Chec	k-Out Aisles – supermarkets,	large retail store	es, etc.		
2.71	Is the aisle at least 36 inches wide? [904.3.1]	Yes No Measurement:	36"min	Photo #:	• Widen aisle •
2.72	Is the counter surface of at least one aisle no higher than 38 inches above the floor? [904.3.2]	Yes No Measurement:	38"max	Photo #:	• Lower counter •
2.73	Is the top of the counter edge protection no higher than 2 inches above the counter surface? [904.3.2]	Yes No	‡2"max	Photo #:	Lower edge protection

2.74	If there is a check writing surface, is the top no less than 28 inches and no greater than 34 inches above the floor? [904.3.3]	Yes No Measurement:	28"-34"		<ul><li>Alter check writing surface</li><li></li></ul>
			•	Photo #:	
2.75	If there is more than one check-out aisle is there a sign with the International Symbol of Accessibility at the accessible aisle? [216.11]	□Yes □No	F	Photo #:	• Add sign •



2.77	Does the accessible portion of the counter extend the same depth as the counter top? [904.4]	Yes No Measurement:		Photo #:	<ul> <li>Alter accessible portion</li> <li>•</li> </ul>
2.78	Is there a clear floor space at least 30 inches wide by at least 48 inches long for a forward or parallel approach? [904.4]	Parallel Measurement:  Forward Measurement:	30"min Or 48"min 48"min		<ul> <li>Reconfigure to provide a parallel or forward approach</li> <li>•</li> </ul>
				Photo #:	

2.79	For a parallel approach, is the clear floor space positioned with the 48 inches adjacent to the accessible length of counter? [904.4.1]	Yes No Measurement:	48"min	Photo#:	<ul> <li>If a parallel approach is not possible, a forward approach is required</li> <li>•</li> </ul>
2.80	For a forward approach:  Do no less than 17 and no greater than 25 inches of the clear floor space extend under the accessible length of the counter? [306.2.2, 306.2.3]	Yes No Measurement:	17-25" 48"min		<ul> <li>Reconfigure to provide knee clearance</li> <li>•</li> </ul>
	Is there at least 27 inches clearance from the floor to the bottom of the counter? [306.3.1]	Yes No  Measurement:	27"min	Photo #:	

Food Service Lines – in cafeterias, salad bars, eat-in fast food establishments, etc.

2.81	Does at least one of each type of self-service shelf or dispensing device for tableware, dishware, condiments, food and beverages have a forward or parallel approach? [904.5.1]	☐ Yes ☐ No☐ Forward☐ Parallel☐	Or	Photo #:	<ul> <li>Reconfigure to provide approach</li> <li>•</li> </ul>
2.82	If there is an unobstructed parallel approach, is the shelf or dispensing device no higher than 48 inches above the floor? [308.3.1]	Yes No Measurement:	48" max	Photo #:	Lower shelf and/or dispensing device
2.83	If there is a shallow obstruction no deeper than 10 inches with a parallel approach, is the shelf or dispensing device no higher than 48 inches above the floor? [308.3.1]	Yes No Measurement:	10" max	Photo #:	Lower shelf and/or dispensing device

2.84	If there is an obstruction no less than 10 inches and no greater than 24 inches deep with a parallel approach, is the shelf or dispensing device no higher than 46 inches above the floor? [308.3.2]	Yes No Measurement:	46" max	Photo #:	Lower shelf and/or dispensing device
2.85	If there is an unobstructed forward approach, is the shelf or dispensing device no higher than 48 inches above the floor? [308.2.1]	Yes No Measurement:	48"max	Photo #:	Lower shelf and/or dispensing device
2.86	If there is an obstruction no deeper than 20 inches with a forward approach:  Does clear floor space extend under the obstruction that is at least the same depth as the obstruction?  Is the shelf or dispensing device no higher than 48 inches above the floor? [904.5.1]	Yes No Measurement:  Yes No Measurement:	20"max 20"min	Photo #:	Reconfigure to provide knee space     Lower shelf and/or dispensing device

2.87	If the obstruction is no less than 20 inches and no greater than 25 inches deep with a forward approach:  Does clear floor space extend under the obstruction that is at least the same depth as the	Yes No Measurement:	20"-25" 44" max		Reconfigure to provide knee space     Lower shelf and/or dispensing device
	obstruction?  Is the shelf or dispensing device no higher than 44 inches above the floor? [904.5.1]	Yes No Measurement:		Photo #:	
2.88	If there is a tray slide, is the top no less than 28 inches and no greater than 34 inches above the floor? [904.5.2]	Yes No Measurement:	28"-34"	Photo #:	• Reconfigure •
		□Yes □No			•
				Photo #:	
		Yes No			•
				Photo #:	