

1. Which of the following is true about dynamic arrays in C++?

- A. They have a `length` member variable associated with them.
- B. **Correct Answer** They are stored contiguously in memory.
- C. Arrays can only be made on the stack.
- D. Values are always automatically initialized to a default value when you create an array regardless of its type.
- E. **Your Answer** More than one of the other options are true.

2. Consider this simple code, and assume the `puppy` class has default and copy constructors defined:

```
puppy * plantANew(puppy orig) {  
    puppy * seedling = new puppy(orig);  
    return seedling;  
}  
  
int main() {  
    puppy f1; puppy * f2;  
    f2 = plantANew(f1);  
    return 0;  
}
```

How many times is the `puppy` copy constructor called in the example above?

- A. **Correct Answer** **Your Answer** Twice.
- B. Three times.
- C. One time.
- D. Never, but the code executes with no errors.
- E. Never, because this code has a compiler error.

3. Consider the following code:

```
#include <iostream>  
using namespace std;  
  
void myfunc(int y, int *x) {  
    y = y+1;  
    cout << y << endl;  
    y = y+1;  
    *x = y;  
}  
  
int main() {  
  
    int z = 6;  
    int*x = &z;  
    myfunc(z, x);  
    myfunc(z+1, x);  
    return 1;  
}
```

What is the result of compiling and running this code?

- A. Nothing is printed to the screen.
- B. **Correct Answer** The numbers 7 and 10 are printed to the screen.
- C. **Your Answer** The numbers 7 and 11 are printed to the screen.
- D. This code has a compilation error.
- E. The numbers 7 and 8 are printed to the screen.

4. Consider this simple function definition.

```
PNG & ugly(PNG x) {  
    return x;  
}
```

Which of the following statements is true?

- A. **Correct Answer** This function is ugly for two of the other reasons.
- B. This function is ugly because there is a type mismatch between the return value and the return type.
- C. **Your Answer** This function is ugly because it returns a value parameter by reference.
- D. This function is ugly because the parameter is not `PNG const x`.
- E. This function is ugly because it could be slow.