

1

Objectives

- Critical-section problem and race condition.
- Hardware solutions to the critical-section problem using
 - ▶ memory barriers, compare-and-swap operations, and atomic variables.
- Mutex locks, semaphores, monitors, and condition variables: to solve the critical-section problem.
- Evaluate tools that solve the critical-section problem
 - ▶ in low-, moderate-, and high-contention scenarios.

Soongsil Univ.
Digital Systems Copyright 2023. (첫세대반도체 핵심공유대학 사업단) all rights reserved 2



3

```
6.1 Background
  Producer–consumer problem
     ▶Implementation of "count++" and "count--"
       register1 = count
                                          register2 = count
       register1 = register1 + 1
                                          register2 = register2 - 1
       count = register1
                                          count = register2
        • Register1, register2: CPU registers
                                                                   while (true) {
                                                                     /* produce an item in next produced */
     ► A result of interleaved concurrent execution
                                                                     while (count == BUFFER_SIZE)
                                                 \{register1 = 5\}
   T0: producer execute register1 = count
                                                                       ; /* do nothing */
   T1: producer execute register1 = register1 +1 {register1 = 6}
                                                                     buffer[in] = next produced;
   T2: consumer execute register2 = count
                                                  \{register2 = 5\}
                                                                     in = (in + 1) % BUFFER SIZE;
   T3: consumer execute register2 = register2 -1 {register2 = 4}
                                                                     count++;
   T4: producer execute
                            count = register1
                                                 \{count = 6\}
   T5: consumer execute
                            count = register2
                                                  \{count = 4\}
                                                                   while (true) {
        Incorrect state
                                                                     while (count == 0)
     ► Race condition
                                                                       ; /* do nothing */
                                                                     next consumed = buffer[out];

    manipulate the same data concurrently


                                                                     out = (out + 1) % BUFFER_SIZE;
        outcome depends on the order of the access
                                                                     count--;
     ► Process synchronization and coordination
                                                                   /st consume the item in next consumed st/
  Soongsil Univ.
Digital System Design Lab.
                                                 Operating Systems
                                                                       Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 4
```

6.2 The Critical-Section Problem

- Critical-section problem
 - ▶ Critical section: a segment of code in which process may update shared data
 - Only one process in the critical section
 - ▶ to design a protocol to synchronize activity so as to cooperatively share data
 - ▶general structure of a typical process

```
while (true) {
   entry section
     critical section
   exit section
     remainder section
}
```

- ▶Three requirements for solution to the critical-section problem
 - 1. Mutual exclusion: only one process in the critical section
 - 2. Progress: processes in entry section can participate in deciding to enter its critical section next, and this selection cannot be postponed indefinitely
 - 3. Bounded waiting: after a request and before a grant




Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 5

5

6.2 The Critical-Section Problem


- Ex. 1: a kernel data structure maintaining a list of all open files
 - ► Simultaneous opening files by two processes
 - ► Separate updates could result in a race condition
- Ex. 2: Simultaneous creating child processes



_

6.2 The Critical-Section Problem

- Ex. 3: kernel data structures for maintaining memory allocation, for maintaining process lists, and for interrupt handling
- Solution in a single-core environment
 - ►In order execution without preemption: to prevent interrupts while a shared variable was being modified
- Critical section handling in OS
 - ▶ Preemptive kernels: allows a process preempted while running in kernel mode
 - difficult to design for SMP architectures
 - more responsive
 - more suitable for real-time programming
 - ► Nonpreemptive kernel: a kernel-mode process will run until
 - it exits kernel mode, blocks, or voluntarily yields control of the CPU
 - free from race conditions



Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 7

7

6.3 Peterson's Solution

- a classic software-based solution
 - ▶ May not work for the modern processor; provides a good algorithmic description
 - restricted to two processes that alternate execution between critical and remainder sections
- Structure of process Pi

```
int turn;
boolean flag[2];
while (true) {
  flag[j] = true;
  turn = i;
  while (flag[i] && turn == i)
  ;
   /* critical section */
  flag[j] = false;
   /*remainder section */
}
```

Soongsil Univ.

Digital System Design Lab.

Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 8

6.3 Peterson's Solution Structure of process Pi int turn; //Who enters critical section int turn; boolean flag[2]; boolean flag[2]; while (true) { while (true) { flag[i] = true; //Pi is ready to enter its critical section flag[j] = true; turn = j; //Pj is allowed to execute in its critical section turn = i;while (flag[j] && turn == zj) //True if arriving later while (flag[i] && turn == i) // stay in the while /* critical section */ /* critical section */ flag[i] = false; flag[j] = false; /*remainder section */ /*remainder section */ **►** Requirements Mutual exclusion: turn can be either 0 or 1 but cannot be both → satisfied • Progress: single entry – simple. – Both – Pi arrives first and stays in the while → turn is set by Pj → Pi entry ■ Bounded-waiting: single entry – simple -Both - Pi waiting \rightarrow flag[j] = false when Pj exits \rightarrow Pi entry (waiting for at most one entry) Digital System Design Lab. Operating Systems Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 9

6.3 Peterson's Solution Reordering of instructions by processors and/or compilers ► Single-threaded: working correctly ► Multithreaded application with shared data Ex. //Data //Thread 1 //Thread 2 boolean flag = false; while (!flag) x = 100;flag = true; int x = 0; print x; // no data dependency - Correct answer: 100 - Reordering in thread 2: 0 or 100 - Reordering in thread 1: 0 or 100 ■ Peterson's solution flag[0] = trueprocess₀ \longrightarrow turn = 1 \rightarrow turn = 0, flag[1] = true time Soongsil Univ. Digital System Design Lab. Operating Systems Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 10

6.4 Hardware Support for Synchronization

- Software-based solutions are not guaranteed to work on modern computer architectures
- Memory Barriers
 - ► memory model
 - Strongly ordered: a memory modification on one processor is immediately visible to all other processors.
 - Weakly ordered: modifications to memory on one processor may not be immediately visible to other
 - ▶ Memory barriers (or memory fences): instructions that can force any changes in memory to be propagated
 - ensures that all loads and stores are completed before any subsequent load or store operations
 - Ex.

```
//Data
boolean flag = false;
int x = 0;
```

```
//Thread 1
while (!flag)
 memory barrier();
print x;
```

```
//Thread 2
x = 100;
memory barrier();
flag = true;
```

the value of flag is loaded before the value of x

the assignment to x occurs before the assignment to flag

to avoid the reordering of operations

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 11

11

Digital System Design Lab.

6.4 Hardware Support for Synchronization

- Hardware Instructions
 - ▶ to test and modify the content of a word or to swap the contents of two words atomically that is, as one uninterruptible unit
 - ► Conceptual instruction: test and set() and compare and swap()
 - Simultaneous execution on different core: sequential execution in arbitrary order

```
boolean test_and_set(boolean *target) {
  boolean rv = *target;
  *target = true;
  return rv;
}
do {
  while (test_and_set(&lock))
    ; /* do nothing */
    /* critical section */
  lock = false;
    /* remainder section */
} while (true);
```

Soongsil Univ. Diçital System Design Lab.

Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 12

6.4 Hardware Support for Synchronization

Hardware Instructions (cont.)

►CAS ex.

 2nd process cannot access to critical section int compare_and_swap(int *value, int expected, int new_value) { int temp = *value; if (*value == expected) *value = new_value; return temp; while (true) { while (compare_and_swap(&lock, 0, 1) != 0) ; /* do nothing */ /* critical section */ lock = 0;/* remainder section */ //Satisfying mutual-exclusion

```
boolean waiting[n]; // initialized to false
int lock; // initialized to 0
```

```
while (true) {
  waiting[i] = true;
  key = 1;
  while (waiting[i] && key == 1)
    // key=lock
    key = compare_and_swap(&lock,0,1);// lock=1
  waiting[i] = false;
    /* critical section */
  j = (i + 1) \% n; // next to i
  while ((j != i) && !waiting[j])
    j = (j + 1) \% n;
  if (j == i)
    lock = 0;
    waiting[j] = false;
  /* remainder section */
// Satisfying mutual-exclusion and bounded-waiting
```

Soongsil Univ.

Digital System Design Lab.

//Not satisfying bounded-waiting

Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 13

13

6.4 Hardware Support for Synchronization

Atomic Variables

provides atomic operations on basic data types such as integers and booleans

```
► Ex. increment(&sequence); atomic integer void increment(atomic_int *v)
       int temp;
       do {
       temp = *v;
       while (temp != compare and swap(v, temp, temp+1));
```

▶atomic variables do not entirely solve race conditions in all circumstances

- Ex. bounded-buffer problem (producer-consumer)
 - Empty buffer, two consumers waiting
 - Producer provides one item → both consumers could exit their while loops

Soongsil Univ. Digital System Design Lab.

Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 14

6.5 Mutex Locks

- Hardware-based solutions
 - ▶ complicated as well as generally inaccessible to application programmers
- Mutex(mutual exclusion) lock
 - ► Simplest higher-level software tools
 - ▶ protects critical sections and prevents race conditions

```
while (true) {
  acquire lock
    critical section
  release lock
    remainder section
}
```

```
acquire() {
  while (!available)
   ; /* busy wait */
  available = false;
}
```

```
release() {
   available = true;
}
```

- ▶ Calls to either acquire() or release() must be performed atomically
 - implemented using the CAS operation
- ▶ busy waiting: waiting processes loop continuously in the call to acquire()
- ► Spinlock: the processes "spins" while waiting.
 - No context switch → preferable for multicore systems (widely used)



Digital System Design Lab.

Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 15

15

6.6 Semaphores

- A more robust tool for synchronization in more sophisticated ways (Dijkstra)
- Semaphore S
 - ▶integer variable: accessed only through two atomic operations: wait() and signal()
 - ►wait(): termed P (from proberen, "to test")
 - ► signal(): called V (from verhogen, "to increment")

```
wait(S) {
  while (S <= 0)
    ; // busy wait
  S--;
}</pre>
signal(S) {
  S++;
}
```

- ► Atomic execution on all modifications of the semaphore
 - wait(): S<=0 and S-- without interruption



Soongsil Univ. Digital System Design Lab.

Operating Systems


Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 16

6.6 Semaphores

- Semaphore Usage
 - ► Counting semaphore: over an unrestricted domain
 - Ex. to control access to a given resource consisting of a finite number (→initialized) of instances
 - -wait(): decrementing the count until $0 \rightarrow$ resource blocked
 - -signal(): incrementing the count
 - Ex. two concurrently running processes: P1 with a statement S1 and P2 with S2: S2 after S1
 - semaphore synch=0

```
//P1 //P2 wait(synch); signal(synch); S2;
```

- ▶ Binary semaphore: 0 and 1
 - Similar to mutex lock



Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 17

17

6.6 Semaphores

- Semaphore Implementation
 - ► Modified wait() and signal(): preventing busy waiting
 - ► Waiting process is suspended in the waiting queue associated with the semaphore: waiting state
 - Processes are added to and removed from S->list
 - ► Restarted by signal() operation of another process
 - waiting → ready

Soongsil Univ. Diçital System Design Lab.

- ►S->value may be negative
 - number of processes waiting on that semaphore
- ► Atomic execution of wait() and signal()
 - Disable interrupts on every core or
 - Provide compare_and_swap() or spinlocks

```
typedef struct {
   int value;
   struct process *list;
} semaphore;

wait(semaphore *S) {
   S->value--;
   if (S->value < 0) {
      add this process to S->list;
      sleep(); //Semaphore waiting queue
   }
}

signal(semaphore *S) {
   S->value++;
   if (S->value <= 0) {
      remove a process P from S->list;
      wakeup(P);
   }
}
```

Operating Systems

ns Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 18

6.7 Monitors

- Synchronization problem due to programming errors
 - ► Simultaneous entry to critical section
 - ► Permanent blocking

```
signal(mutex);
...
critical section
...
wait(mutex);
```

```
wait(mutex);
...
critical section
...
wait(mutex);
```

```
wait(mutex);
...
critical section
...
```

```
critical section
...
signal(mutex);
```

▶ A solution: to incorporate simple synchronization tools as high-level language constructs

Monitor Usage

- ►monitor type: an abstract data type (ADT)
 - includes a set of programmer-defined operations
 - provided with mutual exclusion within the monitor
 - declares the variables: define the state of an instance of that type
 - + bodies of functions: operate on those variables
 - cannot be used directly by the various processes
 - Variables and functions are local

Soongsil Univ. Digital System Design Lab.


Operating Systems


Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 19

19

6.7 Monitors

- Monitor usage (cont.)
 - ▶Only one process at a time is active within a monitor
 - ▶not sufficiently powerful for modeling some synchronization schemes





Soongsil Univ. Digital System Design Lab.

Operating Systems


Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 20

6.7 Monitors

- Monitor usage (cont.)
 - ▶ condition construct for tailor-made synchronization

```
condition x, y;
x.wait(); //process is suspended
x.signal(); //release a suspended process. No effect without any waiting process
```

- cf. signal() in semaphore: always affects the state of the semaphore
- \triangleright Q: suspended, P: x.signal(): Q is resumed \rightarrow 2 possibilities
 - 1. Signal and wait. P either waits until Q leaves the monitor or waits for another condition
 - 2. Signal and continue. Q either waits until P leaves the monitor or waits for another condition



Digital System Design Lab.

Operating Systems

21

6.7 Monitors

else

- Implementing a Monitor Using Semaphores
 - ► Implementation of function F (signal-and-wait scheme)

```
wait(mutex); //binary semaphore mutex (initialized to 1) for mutual exclusion
  body of F
if (next_count > 0) //integer next_count: to count the number of processes suspended on next
  signal(next); //binary semaphore next (initialized to 0)
```

signal(mutex);

```
//x.wait()
                      //x.signal
x_count++;
                     if (x_count > 0) {
if (next_count > 0)
                       next_count++;
  signal(next);
                       signal(x_sem);
                       wait(next); //signal and wait
  signal(mutex);
                       next count--;
wait(x_sem);
X count--;
```

Binary semaphore


Soongsil Univ. Digital System Design Lab.

Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 22

6.7 Monitors

- Resuming Processes within a Monitor
 - ► Simple resuming scheduling: FCFS, or



Summary

- Race condition
 - ▶ Race conditions can result in corrupted values of shared data.
- Critical section: shared data and a possible race condition
- A solution to the critical-section problem:
 - ▶(1) mutual exclusion, (2) progress, and (3) bounded waiting.
- Software solutions: Peterson's solution,
- Hardware support for the critical-section problem
 - ▶ memory barriers, hardware instructions(CAS and atomic variables)
- Mutex lock: mutual exclusion, acquire a lock
- Semaphores: mutual exclusion, integer value
- Monitor: high-level form of process synchronization. condition variables

Soongsil Univ. Digital System Design Lab.

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 24

Exercises, problems and projects

- Exercises
 - **►** 6.2, 6.3, 6.6
- Problems
 - **►** 6.7, 6.9, 6.12, 19

Digital System Design Lab.

6.7 The pseudocode below illustrates the basic push() and pop() operations of an array-based stack. Assuming that this algorithm could be used in a concurrent environment, answer the following questions:

Operating Systems

- a. What data have a race condition?
- b. How could the race condition be fixed?

```
push(item) {
                         pop() {
                                                   is empty() {
  if (top < SIZE) {</pre>
                           if (!is empty()) {
                                                     if (top == 0)
    stack[top] = item;
                             top--;
                                                       return true;
    top++;
                             return stack[top];
                                                     else
                                                       return false;
                           else
  else
                                                  }
    ERROR
                             ERROR
```

y


25

Exercises, problems and projects

6.9 The following program example can be used to sum the array values of size N elements in parallel on a system containing N computing cores (there is a separate processor for each array element):

```
for j = 1 to log 2(N) {
  for k = 1 to N {
    if ((k + 1) % pow(2,j) == 0) {
      values[k] += values[k - pow(2,(j-1))]
    }
}
```

This has the effect of summing the elements in the array as a series of partial sums, as shown in the right side. After the code has executed, the sum of all elements in the array is stored in the last array location. Are there any race conditions in the above code example? If so, identify where they occur and illustrate with an example. If not, demonstrate why this algorithm is free from race conditions.



Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 25

Soongsil Univ.

Digital System Design Lab.

Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 26


Exercises, problems and projects

6.12 Some semaphore implementations provide a function getValue() that returns the current value of a semaphore. This function may, for instance, be invoked prior to calling wait() so that a process will only call wait() if the value of the semaphore is > 0, thereby preventing blocking while waiting for the semaphore. For example:

```
if (getValue(&sem) > 0)
 wait(&sem);
```

Many developers argue against such a function and discourage its use. Describe a potential problem that could occur when using the function getValue() in this scenario.

- **6.19** Assume that a system has multiple processing cores. For each of the following scenarios, describe which is a better locking mechanism—a spinlock or a mutex lock where waiting processes sleep while waiting for the lock to become available:
- The lock is to be held for a short duration.
- The lock is to be held for a long duration.
- A thread may be put to sleep while holding the lock.



Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 27

Converget 2023 (차세대반도체 혁신공유대학 사업단) all rights res

27

Exercises, problems and projects

Programming Problems

6.33 Assume that a finite number of resources of a single resource type must be managed. Processes may ask for a number of these resources and will return them once finished. As an example, many commercial software packages provide a given number of licenses, indicating the number of applications that may run concurrently. When the application is started, the license count is decremented. When the application is terminated, the license count is incremented. If all licenses are in use, requests to start the application are denied. Such a request will be granted only when an existing license holder terminates the application and a

The following program segment is used to manage a finite number of instances of an available resource. The maximum number of resources and the number of available resources are declared as follows:

```
#define MAX_RESOURCES 5
   int available_resources = MAX_RESOURCES;
When a process wishes to obtain a number of resources, it invokes the decrease count() function:
   /* decrease available resources by count resources return 0 */
   /* if sufficient resources available, otherwise return -1 */
   int decrease count(int count) {
     if (available_resources < count) return -1;</pre>
     else {
       available_resources -= count;
       return 0;
   Soongsil Univ.
Diçital System Design Lab.
```

Exercises, problems and projects

Programming Problems (cont.)

```
When a process wants to return a number of resources, it calls the increase_count() function:
   /* increase available resources by count */
   int increase_count(int count) {
     available_resources += count;
     return 0;
```

The preceding program segment produces a race condition. Do the following:

- a. Identify the data involved in the race condition.
- b. Identify the location (or locations) in the code where the race condition occurs.
- c. Using a semaphore or mutex lock, fix the race condition. It is permissible to modify the decrease count() function so that the calling process is blocked until sufficient resources are available.

Soongsil Univ. Digital System Design Lab.

Operating Systems

Copyright 2023. (차세대반도체 혁신공유대학 사업단) all rights reserved 29