

Pharmacy Reengineering (PRE)

Inbound ePrescribing (IEP) 3.1

Pentaho 8.2

**Deployment, Installation, Rollback, and Back-Out
Guide (DIRB)**



February 2020

Department of Veterans Affairs (VA)

Office of Information and Technology (OIT)

Revision History

Date	Version	Description	Author
02/26/2020	2.7	PSO*7.0*589 Maintenance Patch Release: <ul style="list-style-type: none"> • Updated WebLogic Installation section • Updated Pentaho Installation section • Updated VistA Back-Out and Rollback sections • Updated Title page, Revision History, and Footers • Updated formatting for consistency throughout 	Liberty C. Barthauer, PM J. Smith, TW
06/06/2019	2.6	Updates for changes with 3.1.0.005 reference: pg: 117, 127, and 132 Updated Title page to month of June	Technatomy
05/07/2019	2.5	Updates for changes with 3.1.0.004 reference: pg 127, 132, 145, 146, and 150 Updated Title page to month of March	Technatomy
03/11/2019	2.4	Updates for changes with 3.1.0.003 reference: pg 127, 132, 145, 146, and 150 Updated Title page to month of February	Technatomy
10/29/2018	2.3	Update Title page to month of November	Technatomy
10/24/2018	2.2	Updates for changes with 3.0.5.008 reference: pg 132	Technatomy
09/21/2018	2.1	Updated to address VIP RA Comments Sections: 5.6.1, 5.7.1, 6.5.2, 6.5.2.1	Technatomy
09/19/2018	2.0	Updates for changes with 3.0.5.005.	Technatomy
07/26/2017	0.93	Updates for changes with 2.0.4.057.	Technatomy
07/20/2017	0.92	Updates for changes with 2.0.4.057.	Technatomy
06/27/2017	0.91	Updates for changes with 2.0.4.054.	Technatomy
05/22/2017	0.8	Updates for changes with 2.0.4.048.	Technatomy
05/10/2017	0.7	Updates for changes with 2.0.3.047.	Technatomy
04/25/2017	0.6	Updates with corrected information for Staging, PreProd and Production.	Technatomy
04/12/2017	0.5	Updates with corrected information for Staging, PreProd and Production.	Technatomy
02/15/2017	0.4	Updates with corrected information for Staging, PreProd and Production. New sections for SSOi.	Technatomy
02/07/2017	0.3	Multiple updates with new steps introduced throughout Build 1, cleanup for Staging, PreProd and Production.	Technatomy
11/10/2016	0.2	Sprint Update – Added draft steps for rolling back Weblogic; added the VistA Patch #; added a placeholder for backing out the database.	Technatomy
10/27/2016	0.1	Initial Draft (Template Version 2.2 March 2016)	Technatomy

Artifact Rationale

This document describes the Deployment, Installation, Back-out, and Rollback Plan for new products going into the VA Enterprise. The plan includes information about system support, issue tracking, escalation processes, and roles and responsibilities involved in all those activities. Its purpose is to provide clients, stakeholders, and support personnel with a smooth transition to the new product or software, and should be structured appropriately, to reflect particulars of these procedures at a single or at multiple locations.

Per the Veteran-focused Integrated Process (VIP) Guide, the Deployment, Installation, Back-out, and Rollback Plan is required to be completed prior to Critical Decision Point #2 (CD #2), with the expectation that it will be updated throughout the lifecycle of the project for each build, as needed.

Table of Contents

1. Introduction	1
1.1 Purpose	1
1.2 Dependencies.....	1
1.3 Constraints	2
2. Roles and Responsibilities	3
3. Deployment	4
3.1 Timeline	4
3.2 Site Readiness Assessment	4
3.2.1 Application Architecture	5
3.2.2 Deployment Topology (Targeted Architecture).....	7
3.2.3 Site Information (Locations, Deployment Recipients)	7
3.2.4 Site Preparation	7
3.3 Resources	7
3.3.1 Facility Specifics.....	7
3.3.2 Hardware.....	7
3.3.3 Software	8
3.3.4 Communications.....	8
3.3.4.1 Deployment/Installation/Back-Out Checklist.....	8
4. Installation	9
4.1 Pre-installation and System Requirements.....	9
4.1.1 Pre-requisites	9
4.1.2 Environment Configurations	11
4.2 Platform Installation and Preparation	18
4.2.1 Modify /etc/hosts entry	18
4.2.2 X Windows	18
4.2.3 Setup Administration Accounts.....	18
4.2.4 Install Java.....	20
4.2.5 Apache Installation on VM1 and VM2.....	20
4.2.6 Apache Configuration on VM1 and VM2.....	21
4.2.7 Certificate Configuration	23
4.2.8 Create NSS certificate database on VM1.....	28

4.2.9	Create NSS certificate database on VM2.....	29
4.2.10	NSS Configuration on VM1	30
4.2.11	NSS Configuration on VM2	31
4.2.12	Install Apache Plug-in for WebLogic on VM1 and VM2	33
4.2.13	Configure Apache Plug-in for WebLogic on VM1	33
4.2.14	Configure Apache Plug-in for WebLogic on VM2	34
4.2.15	Create IEP CPanel on VM1 and VM2	34
4.2.16	Install Apache SSOi Web Agent on VM1	35
4.2.17	Configure Apache SSOi Web Agent on VM1	35
4.2.18	Post Configure Edits for Apache SSOi Web Agent on VM1	39
4.3	Download and Extract Files	41
4.4	Database Creation	41
4.5	Installation Scripts.....	41
4.6	Cron Scripts.....	41
4.7	Access Requirements and Skills Needed for the Installation.....	41
4.8	Installation Procedure.....	41
4.8.1	WebLogic Installation	42
4.8.1.1	Install WebLogic	42
4.8.1.2	Set Temporary Environment on VM1	62
4.8.1.3	Create a Domain Boot Identity File on VM1	62
4.8.1.4	Copy Identity/Trust Store Files on VM1.....	62
4.8.1.5	Configure nodemanager Identity/Trust Store on VM1	62
4.8.1.6	Configure TLS on VM1	62
4.8.1.7	Copy Identity/Trust Store Files on VM2.....	62
4.8.1.8	Configure nodemanager Identity/Trust Store on VM2.....	62
4.8.1.9	Disable basic authentication	63
4.8.1.10	Configure JPA for Domain on VM1	63
4.8.1.11	Create Inbound eRx Datasource.....	64
4.8.1.12	Configure Identity/Trust Store File on Managed Servers	72
4.8.1.13	Pack Domain on VM1	79
4.8.1.14	Unpack Domain on VM2.....	79
4.8.1.15	Copy Identity/Trust Store Files on VM2.....	79
4.8.1.16	Enroll VM2	79
4.8.1.17	Check Node Manager on Each WebLogic Machine	80
4.8.1.18	Create a Boot Identity File for Managed Servers	80
4.8.1.19	Deploy Test Application	81
4.8.1.20	Configure JPA for Domain on VM2	89
4.8.1.21	Install VistALink on VM1	89
4.8.1.22	Configure VistALink on VM1	90
4.8.1.23	Install VistALink on VM2	90
4.8.1.24	Configure VistALink on VM2	91
4.8.1.25	Stop and start Node Manager and Domain on VM1, VM2	91
4.8.1.26	Deploy VistALink Libraries	92
4.8.1.27	Deploy VistALink Adapters	116
4.8.2	Inbound eRx Application Installation.....	123

4.8.2.1	Install Inbound eRx Application.....	123
4.8.2.2	Create Startup/Shutdown Scripts	141
4.8.2.3	Shut Down Domain	141
4.8.2.4	Shut Down Nodemanagers.....	141
4.8.3	Pentaho Installation	142
4.8.3.1	Pentaho Software Installation	142
4.8.3.2	Pentaho Repository Definition Import.....	145
4.8.4	Nexus Repository Installation (DEV2 VM1 Only)	145
4.8.4.1	SonaType Nexus Software Installation	145
4.8.5	VistA Patch Installation	146
4.9	Installation Verification Procedure	146
4.10	System Configuration	146
4.11	Database Tuning.....	146
5.	Back-Out Procedure	147
5.1	Back-Out Strategy	147
5.2	Back-Out Considerations	147
5.2.1	Load Testing.....	147
5.2.2	User Acceptance Testing	147
5.3	Back-Out Criteria	147
5.4	Back-Out Risks	147
5.5	Authority for Back-Out.....	147
5.6	Back-Out Procedure.....	147
5.6.1	Back-Out of VistA Patch.....	147
5.6.2	Back-Out of Database	148
5.6.2.1	Restore backup files from tape	148
5.6.2.2	Mount the instance	148
5.6.2.3	Restore and recover the datafiles	148
5.6.2.4	Open the database and reset logs	148
5.6.3	Back-Out of WebLogic.....	148
5.6.3.1	Remove New Release	148
5.6.3.2	Deploy Back-out Release	149
5.7	Back-out Verification Procedure.....	150
6.	Rollback Procedure	151
6.1	Rollback Considerations	151
6.2	Rollback Criteria	151
6.3	Rollback Risks	151
6.4	Authority for Rollback.....	151

6.5 Rollback Procedure.....	151
6.5.1 Rollback of Database.....	151
6.5.1.1 Restore backup files from tape	151
6.5.1.2 Mount the instance	151
6.5.1.3 Restore and recover the datafiles	151
6.5.1.4 Open the database and reset logs	152
6.5.2 Rollback WebLogic	152
6.5.2.1 Remove New Release.....	152
6.5.2.2 Deploy Rolled-Back Release	152
6.5.3 Rollback VistA Patch	154
6.6 Rollback Verification Procedure	154
6.6.1 Validation of Roll Back Procedure.....	154
7. Operational Procedures	155
7.1 Startup Procedures	155
7.1.1 Start Weblogic Node Managers and Admin Console	155
7.1.2 Managed Servers.....	155
7.1.3 Pentaho Services Startup	155
7.2 Shut Down Procedures.....	157
7.2.1 Pentaho Services Shutdown	157
7.2.2 WebLogic Application Server Shutdown	157
8. Appendices.....	158
8.1 Certificate Contents	158
8.1.1 va_root_ca_cert.txt.....	158
8.1.2 va_internal_subordinate_ca_cert.txt.....	159
8.1.3 va_root_ca_s2_cert.pem	159
8.1.4 va_internal_ca1_s2_cert.pem.....	160
8.1.5 va_internal_ca2_s2_cert.pem.....	160
8.1.6 betrusted_production_ssp_ca_a1_cert.txt	161
8.1.7 federal_common_policy_ca_cert.txt	161
8.1.8 veterans_affairs_device_ca_b2_cert.txt	162
8.1.9 vaww.esrdev.aac.va.gov_cert.txt.....	163
8.1.10 vaww.esrstage1a.aac.va.gov.pem	164
8.1.11 vaww.esrstage1b.aac.va.gov.pem	164
8.1.12 vaww.esrpre-prod.aac.va.gov.pem	165
8.1.13 das-test.va.gov.pem	166
8.1.14 das-sqa.va.gov.pem	167

Table of Figures

Figure 1: Inbound eRx Application Context Diagram	1
Figure 2: High-Level eRx Architecture	6
Figure 3: Install WebLogic – Oracle Fusion Middleware Installation Inventory Setup	43
Figure 4: Install WebLogic – Oracle Universal Installer Dialog Box	43
Figure 5: Install WebLogic – Oracle Fusion Middleware WebLogic Server and Coherence Installer	44
Figure 6: Install WebLogic – Installation Location.....	45
Figure 7: Install WebLogic – Installation Type	46
Figure 8: Install WebLogic – Prerequisite Checks	47
Figure 9: Install WebLogic – Security Updates Screen.....	47
Figure 10: Install WebLogic – My Oracle Support Username/Email Address Not Specified Dialog Box ...	48
Figure 11: Install WebLogic – Installation Summary Screen.....	48
Figure 12: Install WebLogic – Installation Progress Screen	49
Figure 13: Install WebLogic – Installation Complete	49
Figure 14: Install WebLogic – Oracle Configuration Wizard Splash Screen.....	50
Figure 15: Install WebLogic – Create New Domain	50
Figure 16: Install WebLogic – Templates Screen	51
Figure 17: Install WebLogic – Administrator Account Screen	52
Figure 18: Install WebLogic - Domain Mode and JDK	52
Figure 19: Install WebLogic– Advanced Configuration	53
Figure 20: Install WebLogic – Administration Server Screen	54
Figure 21: Install WebLogic – Node Manager.....	55
Figure 22: Install WebLogic – Managed Servers	56
Figure 23: Install WebLogic – Clusters	57
Figure 24: Install WebLogic – Assign Servers to Clusters	58
Figure 25: Install WebLogic – Machines.....	58
Figure 26: Install WebLogic – Assign Servers to Machines	59
Figure 27: Install WebLogic – Configuration Summary Screen.....	60
Figure 28: Install WebLogic - Configuration Success.....	61
Figure 29: Create Inbound eRx Datasource – Datasources	64
Figure 30: Create Inbound eRx Datasource – Datasource Properties	65
Figure 31: Create Inbound eRx Datasource – Database Driver.....	65
Figure 32: Create Inbound eRx Datasource – Transaction Properties.....	66
Figure 33: Create Inbound eRx Datasource – Connection Properties	67
Figure 34: Create Inbound eRx Datasource – Test Connection.....	68
Figure 35: Create Inbound eRx Datasource – Select Targets/Finish	69
Figure 36: Create Inbound eRx Datasource – Modify New Datasource.....	69
Figure 37: Inbound eRx Datasource –Connection Pool Properties	70
Figure 38: Inbound eRx Datasource –Connection Pool Advanced Properties	70
Figure 39: Inbound eRx Datasource – Wrap Data Type Property	71
Figure 40: Inbound eRx Datasource – Save Properties.....	71
Figure 41: Configure Identity/Trust Store File – Access Server Configuration Page	72
Figure 42: Configure Identity/Trust Store File – Change Keystores	73
Figure 43: Configure Identity/Trust Store File – Keystores – Select Custom Identify and Custom Trust... <td>73</td>	73

Figure 44: Configure Identity/Trust Store File – Modify Keystore Settings	74
Figure 45: Configure Identity/Trust Store File – Modify SSL Settings	75
Figure 46: Configure Identity/Trust Store File – Managed Server 2 Configuration	76
Figure 47: Configure Identity/Trust Store File – Admin Server Configuration.....	76
Figure 48: Configure Identity/Trust Store File – Admin Server Configuration.....	77
Figure 49: Configure Identity/Trust Store File – Admin Server Configuration.....	78
Figure 50: Deploy Test Application: Deployments Page	81
Figure 51: Deploy Test Application – Install.....	81
Figure 52: Deploy Test Application – WAR File	82
Figure 53: Deploy Test Application – Accept Default Application Deployment.....	82
Figure 54: Deploy Test Application – Select Deployment Target	83
Figure 55: Deploy Test Application – Verify Deployment Settings	84
Figure 56: Deploy Test Application – Verify Deployment Settings (Finish)	85
Figure 57: Deploy Test Application – Verify “benefits” Settings	86
Figure 58: Deploy Test Application – Summary of Servers Table	87
Figure 59: Deploy Test Application – Servers Running.....	87
Figure 60: Deploy Test Application – Open Dizzyworld Benefits Application	88
Figure 61: Deploy Test Application – Shutdown Servers	88
Figure 62: Deploy VistA Link Connector – Deployments	92
Figure 63: Deploy VistA Link Connector – Select log4j Library to deploy.....	93
Figure 64: Deploy VistA Link Connector – Select Deployment Targets	94
Figure 65: Deploy VistA Link Connector – Summary of Deployments Verification 1	95
Figure 66: Deploy VistA Link Connector – Summary of Deployments Verification 2.....	96
Figure 67: Deploy VistA Link Connector – Deployment Configuration Screen.....	97
Figure 68: Deploy VistA Link Connector – Deployments	98
Figure 69: Deploy VistA Link Connector – Select vljConnector-1.6.0.028.jar Library to deploy	99
Figure 70: Deploy VistA Link Connector – Select Deployment Targets	100
Figure 71: Deploy VistA Link Connector – Summary of Deployments Verification 1	101
Figure 72: Deploy VistA Link Connector – Summary of Deployments Verification 2.....	102
Figure 73: Deploy VistA Link Connector – Deployment Configuration Screen	103
Figure 74: Deploy VistA Link Connector – Deployments	104
Figure 75: Deploy VistA Link Connector – Select vljFoundationsLib to deploy	105
Figure 76: Deploy VistA Link Connector – Select Deployment Targets	106
Figure 77: Deploy VistA Link Connector – Summary of Deployments Verification 1	107
Figure 78: Deploy VistA Link Connector – Summary of Deployments Verification 2.....	108
Figure 79: Deploy VistA Link Connector – Deployment Configuration Screen	109
Figure 80: Deploy VistA Link Connector – Deployments	110
Figure 81: Deploy VistA Link Connector – Select VistaLinkConsole to deploy.....	111
Figure 82: Deploy VistA Link Connector – Select Deployment Targets	112
Figure 83: Deploy VistA Link Connector – Select Deployment Targets	113
Figure 84: Deploy VistA Link Connector – Summary of Deployments Verification 1	114
Figure 85: Deploy VistA Link Connector – Summary of Deployments Verification 2	115
Figure 86: Deploy VistA Link Connector – Deployment Configuration Screen	116
Figure 87: Deploy VistA Link Connector – Deployments	117
Figure 88: Deploy VistA Link Connector – Select vljxxx_apapter to install.....	118
Figure 89: Deploy VistA Link Connector – Select Deployment Type.....	119
Figure 90: Deploy VistA Link Connector – Select Deployment Targets	119
Figure 91: Deploy VistA Link Connector – Adapter Optional Settings.....	120

Figure 92: Deploy VistA Link Connector – Finish Adapter Installation	121
Figure 93: Deploy VistA Link Connector – Start Resource Adapter	122
Figure 94: Install Inbound eRx Application – Configure Servers	123
Figure 95: Install Inbound eRx Application – Verify Server Settings	124
Figure 96: Install Inbound eRx Application – Verify General & Keystore Settings.....	125
Figure 97: Install Inbound eRx Application – Verify SSL Settings.....	126
Figure 98: Install Inbound eRx Application – Summary of Deployments.....	127
Figure 99: Install Inbound eRx Application – Install New Deployment of INB_ERX	128
Figure 100: Install Inbound eRx Application – Select INB_ERX Deployment Targets.....	129
Figure 101: Install Inbound eRx Application – Verify INB_ERX Deployment Settings.....	130
Figure 102: Install Inbound eRx Application – Verify INB_ERX Deployment Continued	131
Figure 103: Install Inbound eRx Application – Verify INB_ERX Deployment Settings (Finish)	132
Figure 104: Install Inbound eRx Application – Verify INB_ERX Deployment Configuration Settings.....	133
Figure 105: Install Inbound eRx Application – Install New Deployment of INB_ERX_UI.....	134
Figure 106: Install Inbound eRx Application – Select INB_ERX_UI Deployment Targets	135
Figure 107: Install Inbound eRx Application – Verify INB_ERX_UI Deployment Settings	136
Figure 108: Install Inbound eRx Application – Verify INB_ERX_UI Deployment Settings (Finish)	137
Figure 109: Install Inbound eRx Application – Verify INB_ERX_UI Deployment Configuration Settings	138
Figure 110: Install Inbound eRx Application – Start erx Servers	139
Figure 111: Install Inbound eRx Application – erx Servers Running	140

List of Tables

Table 1: Deployment, Installation, Back-out, and Rollback Roles and Responsibilities	3
Table 2: Deployment Timeline	4
Table 3: Site Preparation	7
Table 4: Software Specifications	8
Table 5: Deployment/Installation/Back-Out Checklist	9
Table 6: Development/SQA Detailed VM Requirements	9
Table 7: Staging Detailed VM Requirements	9
Table 8: Pre-Production Detailed VM Requirements	10
Table 9: Production Detailed VM Requirements	10
Table 10: Environment Variables	11
Table 11: Symbolic Names by Environment	12
Table 12: Symbolic Names by Environment (cont.)	12
Table 13: Symbolic Names by Environment (cont.)	13
Table 14: Symbolic Names by Environment (cont.)	14
Table 15: Symbolic Names by Environment (cont.)	15
Table 16: Symbolic Names by Environment (cont.)	16
Table 17: Symbolic Names for sensitive items	17

1. Introduction

This document describes how to deploy and install the various components of the software for the Pharmacy Reengineering (PRE) Inbound ePrescribing (eRx) project, as well as how to back-out the product and rollback to a previous version or data set. This document is a companion to the project charter and management plan for this effort. In cases where a non-developed Commercial Off-the-Shelf (COTS) product is being installed, the vendor provided User and Installation Guide may be used, but the Back-Out Recovery strategy still needs to be included in this document.

Veterans Health Administration (VHA), Patient Care Services (PCS) and Pharmacy Benefits Management (PBM) has requested a new capability as part of the PRE program to receive inbound electronic prescriptions (e-prescriptions or eRxs) from an external provider (e.g., a doctor not associated with the Department of Veterans Affairs [VA], medical staff at a Department of Defense [DoD] military treatment facility, etc.). They also seek the ability to transfer prescriptions electronically between pharmacies, both VA to VA, as well as VA to non-VA (ideally). Once received, these prescriptions will then be fed into the existing Veterans Health Information Systems and Technology Architecture (VistA) Outpatient Pharmacy (OP) for processing and dispensing.


1.1 Purpose

The purpose of this plan is to provide a single, common document that describes how, when, where, and to whom the PRE Inbound eRx application will be deployed and installed, as well as how it is to be backed out and rolled back, if necessary. The plan also identifies resources, communications plan, and rollout schedule. Specific instructions for installation, back-out, and rollback are included in this document.

1.2 Dependencies

Figure 1 depicts the Inbound eRx application and the external systems that it interacts with, including the following: Change Healthcare, Master Veteran Index (MVI), Eligibility & Enrollment (E&E), Health Data Repository (HDR), and VistA OP.

Figure 1: Inbound eRx Application Context Diagram



1.3 Constraints

Design constraints that pertain to the PRE Inbound eRx implementation include the following:

- Existing interfaces will be implemented with the least possible change in order to support existing client system implementations. However, it is recognized that in some circumstances, a change to the interface may be necessary in order to support PRE Inbound eRx requirements or to accommodate technology or frameworks used for PRE Inbound eRx development. One key change is the need for service consumers to maintain the session state and provide this to PRE Inbound eRx on each call. This change is necessary to provide stateless services, as required by the VA Service-Oriented Architecture (SOA).
- The Java language and Java Enterprise Edition (JEE) platform will be used to develop the PRE Inbound eRx.
- Security policies and mechanisms for SOA middleware are currently being developed and updated. The timeframes for the production ready versions may not coincide with the PRE Inbound eRx effort. This includes solutions to the VistA anonymous login and authorization/authentication for the middleware running on non-VistA platforms as part of the enterprise SOA architecture.
- The application user interfaces (UI) must follow enterprise common UI templates and style guidelines.
- Application user interfaces must comply with Section 508.
- The application must comply with VA Enterprise Architecture published data standards (HL7, National Council for Prescription Drug Programs [NCPDP]).
- Inbound eRx must identify and leverage authoritative information sources for data retrieval and manipulation.
- The application must operate optimally using information from the authoritative source or receive permission for caching data locally.
- The team must configure system/and server platforms used by the application using standard system images published in the current VA Release Architecture.
- The team must publish relational and object-oriented databases utilized by the solution in the current VA Release Architecture.
- The team must base application production capacity requirements on workload analysis, simulated workload benchmark tests, or application performance models.
- The team must base application storage capacity requirements on detailed capacity analysis and/or models.
- The team must design the solution to operate within the current VA Local Area Network (LAN) and Wide Area Network (WAN) network configurations.
- The deployment environment must meet the performance and downtime monitoring requirements of the solution.
- The team and data center must develop and provision a disaster recovery plan.
- All critical infrastructure components (including data) must be located at multiple physical locations.

- The application backup and restore solution must meet data recovery requirements [Recovery Point Objectives (RPO) and Recovery Time Objectives (RTO)].
- The application UIs must exist as browser-based UIs and roll and scroll in Vista.
- The application must establish secure access paths for accessing the application and application data.
- The solution must document specific reasons for all limited, external access to data, including the need to know along with security, privacy and other legal restrictions.
- The solution must implement appropriate controls that prevent unwarranted disclosure of sensitive, Personally Identifiable Information (PII), or Protected Health Information (PHI).
- The team must base all system interfaces (both external and internal) implemented by the solution on open standards such as SOAP, REST, JMS, MQ, HTTPS and standard message formats such as HL7 and NCPDP.
- The solution must access available enterprise information through services.
- The VA TRM must identify all products and standards used by this solution as permissible for usage.

2. Roles and Responsibilities

This section outlines the roles and responsibilities for managing the deployment of the PRE Inbound eRx system.

Table 1: Deployment, Installation, Back-out, and Rollback Roles and Responsibilities

ID	Team	Phase / Role	Tasks	Project Phase (See Schedule)
1	FO, EO, NDCP or Product Development (depending upon project ownership)	Deployment	Plan and schedule deployment (including orchestration with vendors).	Deployment
2	FO, EO, NDCP or Product Development (depending upon project ownership)	Deployment	Determine and document the roles and responsibilities of those involved in the deployment.	Design/Build
3	FO, EO, or NDCP	Deployment	Test for operational readiness.	Design/Build
4	FO, EO, or NDCP	Deployment	Execute deployment.	Design/Build
5	FO, EO, or NDCP	Installation	Plan and schedule installation.	Deployment
6	Regional PM/ Field Implementation Services (FIS)/ Office of Policy and Planning (OPP) PM	Installation	Ensure authority to operate and that certificate authority security documentation is in place.	Design/Build
7	Regional PM/FIS/OPP PM/ Nat'l Education & Training	Installations	Coordinate training.	Deployment
8	FO, EO, NDCP or Product Development (depending upon project ownership)	Back-out	Confirm availability of back-out instructions and back-out strategy	Deployment

ID	Team	Phase / Role	Tasks	Project Phase (See Schedule)
			(what are the criteria that trigger a back-out).	
9	FO, EO, NDCP or Product Development (depending upon project ownership)	Post Deployment	Hardware, Software and System Support.	Maintenance

3. Deployment

The deployment is planned as a phased rollout. This type of rollout is best suited for the rapid turnaround time and repeat nature of the installations required for this project.

3.1 Timeline

The deployment and installation is scheduled to run for 18 months as depicted in the master deployment schedule. The timelines are depicted in the Deployment Timeline table below.

Table 2: Deployment Timeline

VIP Build	Delivery Dates
VIP Build 1 Transaction Hub Version 1.0 Foundation	07/28/2016-10/31/2016
VIP Build 2 Transaction Hub Version 1.0 Complete eRx Transaction Hub	10/31/2016-01/27/2017
VIP Builds 3 & 4 Inbound Electronic Prescriptions Version 2.0 Complete Inbound eRx Transaction Processing, UAT, IOC, CD-2	01/28/2017-07/27/2017
VIP Build 5 National Deployment Version 2.0 (includes 1.0 and 2.0)	07/28/2017-11/27/2017
VIP Build 1 & 2 (New CD1) Transfer to/from VA Pharmacy Development Increment for Version 3 eRx Transfers plus other features development, UAT, IOC, CD-2	07/28/2017-01/27/2018
VIP Build 3 National Deployment Version 3 National Deployment of Version 3.0 (4 months total)	03/04/2018-06/01/2018

3.2 Site Readiness Assessment


This section discusses the locations that will receive the PRE Inbound eRx application deployment. Topology determinations are made by Enterprise Systems Engineering (ESE) and vetted by Field Operations (FO), National Data Center Program (NDCP), and AITC during the design phase as appropriate. Field site coordination is done by FO unless otherwise stipulated by FO.

The product will be released by the PRE Inbound eRx Configuration Manager to the AITC Build Manager via a Change Order. The AITC Build Manager will follow the installation steps in Section 4 to complete the product's activation at AITC and for the Disaster Recovery server. The Implementation Manager has assured site readiness by assessing the readiness of the receiving site to deploy the product. AITC, under contract, will provide the product dependencies, power, equipment, space, manpower, etc., to ensure the successful activation of this product.

3.2.1 Application Architecture

The following diagram represents the high-level architecture for the eRx application.

Figure 2: High-Level eRx Architecture



3.2.2 Deployment Topology (Targeted Architecture)

This product will be released to AITC. The AITC, under contract, will house and secure this product on its Pre-Production and then Production servers. A few field located super users will be given access upon National Release. The PRE Inbound eRx system will be available to VA users on a continuous basis (excluding scheduled maintenance activities). Clustering at the application and web services servers will provide high availability and failover capabilities at the application tier and presentation tier. The servers will be load-balanced to distribute uniform processing across all servers.

Additionally, a VistA patch will be released to all VistA sites.

3.2.3 Site Information (Locations, Deployment Recipients)

AITC will host the web and application servers for the PRE Inbound eRx system.

Initial Operating Capability (IOC) will occur in September of 2018. IOC sites are:

- Brooklyn, NY VA Medical Center (VAMC)
- Fayetteville VAMC Veterans Health Care System of the Ozarks
- Health Administration Center (Meds by Mail)
- Indianapolis, IN VA Medical Center

3.2.4 Site Preparation

No preparation is required for the individual VistA sites installing the VistA patch or using the Inbound eRx application.

The following table describes preparation required by AITC prior to deployment.

Table 3: Site Preparation

Site/Other	Problem/Change Needed	Features to Adapt/Modify to New Product	Actions/Steps	Owner
AITC	Creation of VMs for application hosting	N/A	<ul style="list-style-type: none">• Software Installation• Network configuration	ESE

3.3 Resources

This section describes the hardware, software, and communications for the deployment of Inbound eRx, where applicable.

3.3.1 Facility Specifics

No facility-specific features are required for this deployment.

3.3.2 Hardware

As middleware, PRE Inbound eRx requires no hardware to install.

3.3.3 Software

The following table describes the software specifications required prior to deployment.

Table 4: Software Specifications

Required Software	Make	Version	Configuration	Manufacturer	Other
WebLogic Application Server	Application Server	12.1.3c	Clustered	Oracle	
Oracle Database	Database	11.2.0g	Standalone (not synchronized across data centers)	Oracle	
Pentaho Data Integration	Data Integration Tool	8.2	Standalone	Pentaho (a Hitachi Group Company)	

Please see the Roles and Responsibilities table in Section 2 above for details about who is responsible for preparing the site to meet these software specifications.

The software components will be staged at the following location:

\vaauspecdbs801.aac.dva.va.gov\AITC\IEP-eRx\downloads

Application deployment packages will be staged at the following location:

\vaauspecdbs801.aac.dva.va.gov\AITC\IEP-eRx\v.30\deployments

3.3.4 Communications

This section outlines the communications to be distributed to the business user community:

- Communication between the development team and AITC will occur via email and conference calls scheduled through Microsoft Lync.
- Notification of scheduled maintenance periods that require the service to be offline or that may degrade system performance will be disseminated to the business user community a minimum of 48 hours prior to the scheduled event.
- Notification to VA users for unscheduled system outages or other events that impact the response time will be distributed within 30 minutes of the occurrence.
- Notification will be distributed to VA users regarding technical help desk support for obtaining assistance with receiving and processing inbound eRxs and sending and receiving eRx transfers.

3.3.4.1 Deployment/Installation/Back-Out Checklist

The table below is an example of the coordination effort and can be used to document the day/time/individual when each activity (deploy, install, back-out) is completed for Inbound eRx.

Table 5: Deployment/Installation/Back-Out Checklist

Activity	Day	Time	Individual who completed task
Deploy			
Install			
Back-Out			

4. Installation

This section outlines the installation steps for the various Inbound eRx components.

NOTE: The highlighted sections throughout this document indicate that the text will be modified in future versions of this document.

4.1 Pre-installation and System Requirements

This section outlines the minimum requirements for the product to be installed, as well as the recommended hardware and software system requirements.

4.1.1 Pre-requisites

The following table outlines the specifications for VM.

Table 6: Development/SQA Detailed VM Requirements

VM	RAM (GB)	Space (GB)	CPUs	OS	VM Description/Use/DNS Required
1	16	300	4	RHEL 6	DEV 1 DB Server running Oracle
2	16	300	4	RHEL 6	DEV 2 DB Server running Oracle
3	16	300	4	RHEL 6	SQA 1 DB Server running Oracle
4	16	300	4	RHEL 6	SQA 2 DB Server running Oracle
5	16	300	4	RHEL 6	DEV1 AP Server running Apache/WebLogic
6	16	300	4	RHEL 6	DEV 2 AP Server running Apache/WebLogic
7	16	300	4	RHEL 6	SQA 1 AP Server running Apache/WebLogic
8	16	300	4	RHEL 6	SQA 2 AP Server running Apache/WebLogic
Total	128	2400	32	8	

Table 7: Staging Detailed VM Requirements

VM	RAM (GB)	Space (GB)	CPUs	OS	VM Description/Use/DNS Required
1	16	800	4	RHEL 7	STAGING DB Server running Oracle
2	16	300	4	RHEL 7	STAGING Application Server running Apache/WebLogic

VM	RAM (GB)	Space (GB)	CPUs	OS	VM Description/Use/DNS Required
3	16	300	4	RHEL 7	STAGING Application Server running Apache/WebLogic
Total	48	1400	16	3	

Table 8: Pre-Production Detailed VM Requirements

VM	RAM (GB)	Space (GB)	CPUs	OS	VM Description/Use/DNS Required
1	16	1300	4	RHEL 6	PRE-PRODUCTION DB Server running Oracle
2	16	300	4	RHEL 6	PRE-PRODUCTION Application Server running Apache/WebLogic
3	16	300	4	RHEL 6	PRE-PRODUCTION Application Server running Apache/WebLogic
Total	48	1900	12	3	

Table 9: Production Detailed VM Requirements

VM	RAM (GB)	Space (GB)	CPUs	OS	VM Description/Use/DNS Required
1	16	1300	4	RHEL 6	PRODUCTION DB Server running Oracle
2	16	300	4	RHEL 6	PRODUCTION Application Server running Apache/WebLogic
3	16	300	4	RHEL 6	PRODUCTION Application Server running Apache/WebLogic
Total	48	1900	12	3	

4.1.2 Environment Configurations

Table 10 lists Environment Variables values that should be substituted throughout this document as system administrators are completing the installation steps.

Table 10: Environment Variables

ENV	ORACLE_BASE	WLS_HOME	DOMAIN_HOME
DEV1	/u01/app/Oracle_Home	\$ORACLE_BASE/wlserver	\$ORACLE_BASE/user_projects/domains/erxdomain1
DEV2	/u01/app/Oracle_Home	\$ORACLE_BASE/wlserver	\$ORACLE_BASE/user_projects/domains/erxdomain2
SQA1	/u01/app/Oracle_Home	\$ORACLE_BASE/wlserver	\$ORACLE_BASE/user_projects/domains/erxdomain1
STAG	/u01/oracle	\$ORACLE_BASE/wlserver	\$ORACLE_BASE/user_projects/domains/iep-stage
STAG2	/u01/oracle	\$ORACLE_BASE/wlserver	\$ORACLE_BASE/user_projects/domains/iep-stage2
PREP	/u01/oracle	\$ORACLE_BASE/wlserver	\$ORACLE_BASE/user_projects/domains/iep-preprod
PREP2	/u01/oracle	\$ORACLE_BASE/wlserver	\$ORACLE_BASE/user_projects/domains/iep-preprod2
PROD	/u01/oracle	\$ORACLE_BASE/wlserver	\$ORACLE_BASE/user_projects/domains/iep-prod
PROD2	/u01/oracle	\$ORACLE_BASE/wlserver	\$ORACLE_BASE/user_projects/domains/iep-prod2

Table 11 lists the symbolic names that should be substituted throughout this document as system administrators are completing the installation steps.

Table 11: Symbolic Names by Environment

ENV	vm1_fqdn	vm1_name	vm2_fqdn	vm2_name	domain
DEV1	vaauserxappdev1.aac.va.gov	vaauserxappdev1	vaauserxappdev2.aac.va.gov	vaauserxappdev2	erxdomain1
DEV2	vaauserxappdev2.aac.va.gov	vaauserxappdev2	vaauserxappdev1.aac.va.gov	vaauserxappdev1	erxdomain2
SQA1	vaauserxappsqa1.aac.va.gov	vaauserxappdev1	vaauserxappdev2.aac.va.gov	vaauserxappdev2	erxdomain1
STAG	vaausappiep402.aac.va.gov	vaausappiep402	vaausappiep403.aac.va.gov	vaausappiep403	iep-stage
STAG2	vaausappiep621.aac.va.gov	vaausappiep621	vaausappiep622.aac.va.gov	Vaausappiep622	iep-stage2
PREP	vaausappiep404.aac.va.gov	vaausappiep404	vaausappiep405.aac.va.gov	vaausappiep405	iep-preprod
PREP2	vaausappiep421.aac.va.gov	vaausappiep421	vaausappiep422.aac.va.gov	vaausappiep422	iep-preprod2
PROD	vaausappiep201.aac.va.gov	vaausappiep201	vaausappiep202.aac.va.gov	vaausappiep202	iep-prod
PROD2	vaausappiep221.aac.va.gov	vaausappiep221	vaausappiep222.aac.va.gov	vaausappiep222	iep-prod2

Table 12: Symbolic Names by Environment (cont.)

ENV	env	Env	erx_port	proxy_fqdn	proxy_name	db_fqdn	db_name	db_port
DEV1	dev1	Dev1	8001	vaauserxappdev1.aac.va.gov	vaauserxappdev1	vaauserx dbs dev1.aac.va.gov	ERXD1	1549
DEV2	dev2	Dev2	8003	vaauserxappdev2.aac.va.gov	vaauserxappdev2	vaauserx dbs dev2.aac.va.gov	ERXD2	1550
SQA1	sqa1	Sqa1	8001	Vaauserxappsqa2.aac.va.gov	vaauserxappsqa2	vaauserx db sqa1.aac.va.gov	ERXS1	1549
STAG	stag	Stag	8001	vaausappiep402.aac.va.gov	vaausappiep403	vaausdb siep400.aac.va.gov	IEPQA	1647
STAG2	stag2	Stag2	8001	vaausappiep622.aac.va.gov	vaausappiep622	vaausdb siep400.aac.va.gov	IEPQA2	1648
PREP	prep	Prep	8001	vaausappiep404.aac.va.gov	vaausappiep404	vaausdb siep401.aac.va.gov	IEPY	1647
PREP2	prep2	Prep2	8001	vaausappiep422.aac.va.gov	vaausappiep422	vaausdb siep420.aac.va.gov	IEPY2	1647
PROD	prod	Prod2	8001	vaausappiep201.aac.va.gov	vaausappiep201	vaausdb siep200.aac.va.gov	IEPP	1647
PROD2	prod2	Prod2	8001	vaausappiep221.aac.va.gov	vaausappiep221	vaausdb siep220.aac.va.gov	IEPP2	1647

Table 13: Symbolic Names by Environment (cont.)

ENV	mserver1	mserver2	cluster
DEV1	erx1	erx2	dev1
DEV2	erx1	erx2	dev1
SQA1	erx1	erx2	dev1
STAG2	ManagedServer001	ManagedServer002	Cluster001
STAG	ManagedServer001	ManagedServer002	Cluster001
PREP2	ManagedServer001	ManagedServer002	Cluster001
PREP	ManagedServer001	ManagedServer002	Cluster001
PROD2	ManagedServer001	ManagedServer002	Cluster001
PROD	ManagedServer001	ManagedServer002	Cluster001

Table 14: Symbolic Names by Environment (cont.)

ENV	iam_hco	iam_policy_entries
DEV1	INTHCO	policyserver="smp1.int.iam.va.gov,44441,44442,44443" policyserver="smp2.int.iam.va.gov,44441,44442,44443" policyserver="smp3.int.iam.va.gov,44441,44442,44443" policyserver="smp4.int.iam.va.gov,44441,44442,44443"
DEV2	INTHCO	policyserver="smp1.int.iam.va.gov,44441,44442,44443" policyserver="smp2.int.iam.va.gov,44441,44442,44443" policyserver="smp3.int.iam.va.gov,44441,44442,44443" policyserver="smp4.int.iam.va.gov,44441,44442,44443"
SQA1	SQAHCO	policyserver="smp1.sqa.iam.va.gov,44441,44442,44443" policyserver="smp2.sqa.iam.va.gov,44441,44442,44443" policyserver="smp3.sqa.iam.va.gov,44441,44442,44443" policyserver="smp4.sqa.iam.va.gov,44441,44442,44443"
STAG	PREPRODHCO	policyserver="smp1.preprod.iam.va.gov,44441,44442,44443" policyserver="smp2.preprod.iam.va.gov,44441,44442,44443" policyserver="smp3.preprod.iam.va.gov,44441,44442,44443" policyserver="smp4.preprod.iam.va.gov,44441,44442,44443" policyserver="smp5.preprod.iam.va.gov,44441,44442,44443" policyserver="smp6.preprod.iam.va.gov,44441,44442,44443" policyserver="smp7.preprod.iam.va.gov,44441,44442,44443" policyserver="smp8.preprod.iam.va.gov,44441,44442,44443"
STAG2	PREPRODHCO	policyserver="smp1.preprod.iam.va.gov,44441,44442,44443" policyserver="smp2.preprod.iam.va.gov,44441,44442,44443" policyserver="smp3.preprod.iam.va.gov,44441,44442,44443" policyserver="smp4.preprod.iam.va.gov,44441,44442,44443" policyserver="smp5.preprod.iam.va.gov,44441,44442,44443" policyserver="smp6.preprod.iam.va.gov,44441,44442,44443" policyserver="smp7.preprod.iam.va.gov,44441,44442,44443" policyserver="smp8.preprod.iam.va.gov,44441,44442,44443"

Table 15: Symbolic Names by Environment (cont.)

ENV	iam_hco	iam_policy_entries
PREP	PREPRODHCO	policyserver="smp1.preprod.iam.va.gov,44441,44442,44443" policyserver="smp2.preprod.iam.va.gov,44441,44442,44443" policyserver="smp3.preprod.iam.va.gov,44441,44442,44443" policyserver="smp4.preprod.iam.va.gov,44441,44442,44443" policyserver="smp5.preprod.iam.va.gov,44441,44442,44443" policyserver="smp6.preprod.iam.va.gov,44441,44442,44443" policyserver="smp7.preprod.iam.va.gov,44441,44442,44443" policyserver="smp8.preprod.iam.va.gov,44441,44442,44443"
PREP2	PREPRODHCO	policyserver="smp1.preprod.iam.va.gov,44441,44442,44443" policyserver="smp2.preprod.iam.va.gov,44441,44442,44443" policyserver="smp3.preprod.iam.va.gov,44441,44442,44443" policyserver="smp4.preprod.iam.va.gov,44441,44442,44443" policyserver="smp5.preprod.iam.va.gov,44441,44442,44443" policyserver="smp6.preprod.iam.va.gov,44441,44442,44443" policyserver="smp7.preprod.iam.va.gov,44441,44442,44443" policyserver="smp8.preprod.iam.va.gov,44441,44442,44443"

Table 16: Symbolic Names by Environment (cont.)

ENV	iam_hco	iam_policy_entries
PROD	PRODHCO	policyserver="smp1.prod.iam.va.gov,44441,44442,44443" policyserver="smp2.prod.iam.va.gov,44441,44442,44443" policyserver="smp3.prod.iam.va.gov,44441,44442,44443" policyserver="smp4.prod.iam.va.gov,44441,44442,44443" policyserver="smp5.prod.iam.va.gov,44441,44442,44443" policyserver="smp6.prod.iam.va.gov,44441,44442,44443" policyserver="smp7.prod.iam.va.gov,44441,44442,44443" policyserver="smp8.prod.iam.va.gov,44441,44442,44443"
PROD2	PRODHCO	policyserver="smp1.prod.iam.va.gov,44441,44442,44443" policyserver="smp2.prod.iam.va.gov,44441,44442,44443" policyserver="smp3.prod.iam.va.gov,44441,44442,44443" policyserver="smp4.prod.iam.va.gov,44441,44442,44443" policyserver="smp5.prod.iam.va.gov,44441,44442,44443" policyserver="smp6.prod.iam.va.gov,44441,44442,44443" policyserver="smp7.prod.iam.va.gov,44441,44442,44443" policyserver="smp8.prod.iam.va.gov,44441,44442,44443"

In addition to the above Environment Variables and Symbolic Names, there are several passwords or secret phrases which are required throughout the installation. The table below identifies Symbolic Names that will be used in this document and provide a brief description of each. The values of these sensitive items will be defined by the appropriate administrator during the installation process and should be properly recorded and shared with others on a need to know basis.

Table 17: Symbolic Names for sensitive items

Symbolic Name			
keystore_passphrase			
privatekey_passphrase			
weblogic_password			

The following are the properties that define the SSL security settings for WebLogic. These properties must be set respective to each environment.

```
KeyStores=CustomIdentityAndCustomTrust
CustomIdentityAlias=[proxy_fqdn]
CustomIdentityKeyStoreFileName=[DOMAIN_HOME]/security/[proxy_fqdn]
CustomIdentityKeyStorePassPhrase=[keystore_passphrase]
CustomIdentityKeyStoreType=JKS
CustomIdentityPrivateKeyPassPhrase=[privatekey_passphrase]
```

Ensure the environment variables are set as follows:

```
$ export ORACLE_BASE=/u01/app/Oracle_Home
$ export WLS_HOME=$ORACLE_BASE/wlserver
$ export DOMAIN_HOME=$ORACLE_BASE/user_projects/domains/erxdomain1
```

4.2 Platform Installation and Preparation

The following sections describe the steps to prepare the operating system for the installation of the application. Most activities are to be performed by the RHEL System Administrator.

4.2.1 Modify /etc/hosts entry

1. Modify /etc/hosts to add fully qualified domain name for the local server (the following must be performed by a system administrator):

```
$ sudo vi /etc/hosts
```

2. Add entries similar to the following:

```
????.???.???.???    [vm1_fqdn] [vm1_name].domain.local [vm1_name]
????.???.???.???    [vm2_fqdn] [vm2_name].domain.local [vm2_name]
????.???.???.???    [db_fqdn] [db_name].domain.local [db_name]
```

3. Save the file and exit. Note the following explanations of the hosts entry fields:

```
????.???.???.???      <- IP address of the server
```

4.2.2 X Windows

1. Install the Linux X Window libraries (the following must be performed by a system administrator):

```
$ sudo yum install xorg-x11-xauth.x86_64
```

2. Start Attachmate Reflection X (Click *Start > All Programs > Attachmate Reflection > Reflection X*).

3. Modify the SSH session:

- a. Connection > SSH > X11 > Enable X11 forwarding
- b. Connection > SSH > X11 > X display location > :0.0

4. Connect to the Linux server with the new SSH session settings. The DISPLAY environment variable should be automatically set.

5. In order to run X applications after doing a sudo su to another account, first modify the .Xauthority file

6. As your normal Linux login account:

```
$ cp ~/.Xauthority /tmp
```

7. After you sudo su to another user, copy the .Xauthority file:

```
$ cp /tmp/.Xauthority ~
```

4.2.3 Setup Administration Accounts

1. Create the Linux WebLogic user and group (the following must be performed by a system administrator):

```
$ sudo groupadd -g 7400 weblogic (this group already exists in LDAP)
$ sudo useradd -g weblogic weblogic
```

2. Create the Linux weblogic sudoer file (the following must be performed by a system administrator):

```
$ cat > /etc/sudoers.d/weblogic
weblogic ALL=NOPASSWD:/sbin/service wls start,/sbin/service wls stop,/sbin/service wls
stop_all,/sbin/service wls status,/sbin/service wlsm start,/sbin/service wlsm
stop,/sbin/service wlsm status
Cmnd_Alias WLS_SU=/bin/su - weblogic, /bin/su - weblogic2, /bin/su - weblogic3, /bin/su -
aacesrpprod, /bin/su - aacxpologger, /bin/su - introsvr
```

```

Cmnd_Alias WLS_CMD=/bin/ls, /bin/du, /bin/grep, /bin/cat, /sbin/chkconfig --list,
/sbin/service wls stop, /sbin/service wls start
Cmnd_Alias LSOF_CMD=/usr/sbin/lsof
WLS      ALL=(ALL)    WLS_CMD
WLS      ALL=(ALL)    WLS_SU
WLS      ALL=(ALL)    LSOF_CMD
%weblogic   ALL=(ALL)    WLS_CMD
%weblogic   ALL=(ALL)    WLS_SU
%weblogic   ALL=(ALL)    LSOF_CMD
<ctrl>d

```

3. Modify the Linux weblogic account to add umask command near the beginning of the file `~weblogic/.bash_profile`:

```
umask 0022
```

4. Create the app software directory if it doesn't exist (the following must be performed by a system administrator):

```

$ sudo chmod 777 /u01
$ sudo mkdir -p /u01/app
$ sudo chown weblogic:weblogic /u01/app
$ sudo chmod 777 /u01/app

```

5. Create the Linux kettle user and group (the following must be performed by a system administrator):

```

$ sudo groupadd -g 7600 kettle
$ sudo useradd -g kettle kettle
$ sudo usermod -a -G weblogic kettle (weblogic group already exists in LDAP)

```

6. Create the Linux kettle sudoer file (the following must be performed by a system administrator):

```

$ sudo cat > /etc/sudoers.d/kettle
kettle ALL=NOPASSWD:/sbin/service kettle start,/sbin/service kettle stop,/sbin/service
kettle stop_all,/sbin/service kettle status
Cmnd_Alias KETTLE_SU=/bin/su - kettle
Cmnd_Alias KETTLE_CMD=/bin/ls, /bin/du, /bin/grep, /bin/cat, /sbin/chkconfig --list,
/usr/sbin/ls
%kettle      ALL=(ALL)    KETTLE_CMD
%kettle      ALL=(ALL)    KETTLE_SU
<ctrl>d

```

7. Create the pentaho software directory if it doesn't exist (the following must be performed by a system administrator):

```

$ sudo mkdir -p /u01/app/pentaho
$ sudo chown kettle:kettle /u01/app/pentaho
$ sudo chmod 755 /u01/app/pentaho

```

8. Modify the Linux kettle account to add umask command near the beginning of the file `~kettle/.bash_profile`:

```
umask 0022
```

9. Modify the Linux kettle account to replace the PATH= and export PATH near the end of the file `~kettle/.bash_profile`:

```

export JAVA_HOME=/u01/app/java/latest/bin/java
export PATH=${JAVA_HOME}/bin:${PATH}: ${HOME}/bin

```

10. Create the Linux apache sudoer file (the following must be performed by a system administrator):

```

$ sudo vi /etc/sudoers.d/apache
apache ALL=(kettle:kettle) NOPASSWD:/u01/app/cpanel/bin/carte_slave_util.sh
<ctrl>d

```

4.2.4 Install Java

1. Log into Linux and sudo su to the weblogic account:
\$ sudo su - weblogic
2. Create downloads directory if it doesn't exist:
\$ mkdir -p /u01/downloads
3. Download Oracle JDK 1.8 for Linux x86-64 to the downloads directory:
Download from ATIC IEP eRx Downloads directory
4. Create Java directory if it doesn't exist:
\$ mkdir -p /u01/app/java
5. Unpack the Oracle JDK 1.8 archive to in the downloads directory:
\$ cd /u01/app/java
\$ gzip -cd < /u01/downloads/jdk-8uxxxx-linux-x64.tar.gz | tar xvf -
6. Create symbolic link for latest Java installation:
\$ ln -s cd /u01/app/java/jdk1.8.0_xxx /u01/app/java/latest
7. Add instructions to open permissions to permit access to all users, and to create link for /u01/app/java if located in a different location.
\$ exit
8. Return to your Linux account.
\$ exit

4.2.5 Apache Installation on VM1 and VM2

Perform the following steps on VM1 and VM2:

1. EO SA installs standard Apache 2.2 RHEL6 RPM, login to Linux and verify the following:
\$ sudo rpm -q -a | grep httpd
httpd-2.2.15-39.el6.x86_64
httpd-tools-2.2.15-39.el6.x86_64
2. Install the Linux NSS package (the following must be performed by a system administrator):
\$ sudo yum install mod_nss.x86_64
3. Modify the httpd startup configuration (the following must be performed by a system administrator):
\$ sudo chkconfig --level 2345 httpd on
\$ sudo systemctl enable httpd # for RHEL 7 systems

4.2.6 Apache Configuration on VM1 and VM2

servers are RHEL 7 and they have Apache version 2.4, Want to confirm if these instructions are for Apache 2.2 or 2.4?
Here are the differences between document and Apache conf file on server.
6. No <IfModule prefork.c>
9. No <Directory "/var/www/icons"> section
Instead <Directory "/var/www/html"> section exist and it has the Option parameter Options Indexes FollowSymLinks

The following step need to be performed on VM1 and VM2:

1. Modify HTTPD configuration:

```
$ sudo vi /etc/httpd/conf/httpd.conf
```

2. Modify Timeout parameter:

```
Timeout 120
```

3. Modify <IfModule prefork.c>parameters:

```
StartServers      8
ServerLimit     300
MaxClients     300
```

4. Modify Listen parameter:

```
Listen 80
```

5. Modify <Directory /> section:

```
<Directory '/'>
    Options FollowSymLinks
    AllowOverride None
    <Limit PUT>
        Order deny,allow
        Deny from all
    </Limit>
</Directory>
```

6. Modify <Directory "/var/www/icons"> Options parameter:

```
#Options Indexes MultiViews FollowSymLinks
Options Indexes
```

7. Modify <Directory "/var/www/html"> section:

```
<Directory "/var/www/html">
    Options Indexes FollowSymLinks
    AllowOverride None
    Order allow,deny
    Allow from all
</Directory>
```

8. Add <Directory "/var/www/html/cpanel"> section:

```
<Directory "/var/www/html">
    Options Indexes FollowSymLinks
    AllowOverride None
    Order allow,deny
    Allow from all
</Directory>
```

9. Enable ScriptAlias:

```
ScriptAlias /cgi-bin/ "/var/www/cgi-bin/"
```

10. Modify <Directory "/var/www/cgi-bin"> section:

```
<Directory "/var/www/cgi-bin">
    AllowOverride None
    Options None
    Order allow,deny
    Allow from all
</Directory>
```

11. Modify HTTPD configuration:

```
$ sudo vi /etc/httpd/conf/httpd.conf
```

12. Add Header Edit entries to bottom of /etc/httpd/conf/httpd.conf

```
Header edit Set-Cookie "(?i)^((?:(!;\s?HttpOnly).)+)$" "$1; HttpOnly"
Header edit Set-Cookie "(?i)^((?:(!;\s?secure).)+)$" "$1; Secure"
Header always append X-Frame-Options DENY
```

13. Reverse Proxy to Pentaho Slaves in /etc/httpd/conf.d/pentaho.conf:

```
$ sudo vi /etc/httpd/conf.d/pentaho.conf
#
#           Reverse proxy to Pentaho slaves
#
<Location /master1>
    ProxyPass http://[vm1_fqdn]:8080/
    ProxyPassReverse http://[vm1_fqdn]:8080/
    AddOutputFilterByType SUBSTITUTE text/html
    Substitute "s|/kettle//master1/kettle/|i"
</Location>
<Location /slave1>
    ProxyPass http://[vm1_fqdn]:8081/
    ProxyPassReverse http://[vm1_fqdn]:8081/
    AddOutputFilterByType SUBSTITUTE text/html
    Substitute "s|/kettle//slave1/kettle/|i"
</Location>
<Location /slave2>
    ProxyPass http://[vm1_fqdn]:8082/
    ProxyPassReverse http://[vm1_fqdn]:8082/
    AddOutputFilterByType SUBSTITUTE text/html
    Substitute "s|/kettle//slave2/kettle/|i"
</Location>
<Location /slave3>
    ProxyPass http://[vm2_fqdn]:8083/
    ProxyPassReverse http://[vm2_fqdn]:8083/
    AddOutputFilterByType SUBSTITUTE text/html
    Substitute "s|/kettle//slave3/kettle/|i"
</Location>
<Location /slave4>
    ProxyPass http://[vm2_fqdn]:8084/
    ProxyPassReverse http://[vm2_fqdn]:8084/
    AddOutputFilterByType SUBSTITUTE text/html
    Substitute "s|/kettle//slave4/kettle/|i"
</Location>
<Location /slave5>
    ProxyPass http://[vm2_fqdn]:8085/
    ProxyPassReverse http://[vm2_fqdn]:8085/
    AddOutputFilterByType SUBSTITUTE text/html
    Substitute "s|/kettle//slave4/kettle/|i"
</Location>
```

14. Restart Apache:

```
$ sudo service httpd stop
$ sudo service httpd start
```

4.2.7 Certificate Configuration

```
3 thru 14. saving these certificates with .pem file extension instead of .txt, this does
not make any difference in functionality, it's only a better representation of the file
format, since they are actually PEM format.
15, 16. Replacing these steps with the AITC standards that we follow to generate and
request certificates. Steps are as follows:
1) Create a configuration file with name: [proxy_fqdn].cnf, content:
distinguished_name = req_distinguished_name
[req]
req_extensions = v3_req
prompt = no
[ v3_req ]
# Extensions to add to a certificate request
basicConstraints = CA:FALSE
keyUsage = nonRepudiation, digitalSignature, keyEncipherment
# Some CAs do not yet support subjectAltName in CSRs.
# Instead the additional names are form entries on web
# pages where one requests the certificate...
subjectAltName      = @alt_names
[alt_names]
DNS.1 = [proxy_fqdn1]
DNS.2 = [proxy_fqdn2]
[ req_distinguished_name ]
C           = US
ST          = Texas
L           = Austin
O           = US Department of Veterans Affairs
OU          = AITC
CN          = [proxy_fqdn]
emailAddress = cdcoweblogicadministrators@va.gov
[ req_attributes ]
challengePassword = xxxxxxxxxxxx
Command to generate csr and private key:
openssl req -new -newkey rsa:2048 -keyout [proxy_fqdn].key -out [proxy_fqdn].csr -config
[proxy_fqdn].cnf
```

1. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Create a “certificates” directory to store all certificate artifacts:

```
$ mkdir /u01/certificates
$ cd /u01/certificates
```

3. Create the va_root_ca_cert.pem certificate in the “certificates” directory:

```
$ cat > va_root_ca_cert.pem
```

4. Paste the va_root_ca_cert.pem content from Appendix 8.1.1.

```
<ctrl>d
```

5. Create the va_internal_subordinate_ca_cert.pem content in the “certificates” directory:

```
$ cat > va_internal_subordinate_ca_cert.pem
```

6. Paste the va_internal_subordinate_ca_cert.pem content from Appendix 8.1.2.

```
<ctrl>d
```

7. Create the va_root_ca_s2_cert.pem certificate in the “certificates” directory:

```
$ cat > va_root_ca_s2_cert.pem
```

8. Paste the va_root_ca_s2_cert.pem content from Appendix 8.1.3.

```
<ctrl>d
```

9. Create the va_intermediate_ca1_s2_cert.pem certificate in the “certificates” directory:

```
$ cat > va_intermediate_ca1_s2_cert.pem
```

10. Paste the va_intermediate_ca1_s2_cert.pem content from Appendix 8.1.4.

```
<ctrl>d
```

11. Create the va_intermediate_ca2_s2_cert.pem certificate in the “certificates” directory:

```
$ cat > va_intermediate_ca2_s2_cert.pem
```

12. Paste the va_intermediate_ca2_s2_cert.pem content from Appendix 8.1.5.

```
<ctrl>d
```

13. Create the betrusted_production_ssp_ca_a1_cert.pem certificate in the “certificates” directory:

```
$ cat > betrusted_production_ssp_ca_a1_cert.pem
```

14. Paste the betrusted_production_ssp_ca_a1_cert.pem content from Appendix 8.1.6.

```
<ctrl>d
```

15. Create the federal_common_policy_ca_cert.pem certificate in the “certificates” directory:

```
$ cat > federal_common_policy_ca_cert.pem
```

16. Paste federal_common_policy_ca_cert.txt content from Appendix 8.1.7.

```
<ctrl>d
```

17. Create the veterans_affairs_device_ca_b2_cert.pem certificate in the “certificates” directory:

```
$ cat > veterans_affairs_device_ca_b2_cert.pem
```

18. Paste the veterans_affairs_device_ca_b2_cert.pem content from Appendix 8.1.8.

```
<ctrl>d
```

19. Create the vaww.ersdev.aac.va.cert.pem certificate in the “certificates” directory:

```
$ cat > vaww.ersdev.aac.va.cert.pem
```

20. Paste the vaww.ersdev.aac.va.cert.pem content from Appendix 8.1.9.

```
<ctrl>d
```

21. Create the vaww.esrstage1a.aac.va.gov.pem certificate in the “certificates” directory:

```
$ cat > vaww.esrstage1a.aac.va.gov.pem
```

22. Paste the vaww.esrstage1a.aac.va.gov.pem content from Appendix 8.1.10.

```
<ctrl>d
```

23. Create the vaww.esrstage1b.aac.va.gov.pem certificate in the “certificates” directory:

```
$ cat > vaww.esrstage1b.aac.va.gov.pem
```

24. Paste the vaww.esrstage1b.aac.va.gov.pem content from Appendix 8.1.11.

```
<ctrl>d
```

25. Create the vaww.esrpre-prod.aac.va.gov.pem certificate in the “certificates” directory:

```
$ cat > vaww.esrpre-prod.aac.va.gov.pem
```

26. Paste the vaww.esrpre-prod.aac.va.gov.pem content from Appendix 8.1.12

```
<ctrl>d
```

27. Create the das-test.va.gov.pem certificate in the “certificates” directory:

```
$ cat > vaww.esrstage1a.aac.va.gov.pem
```

28. Paste the das-test.va.gov.pem content from Appendix 0.

```
<ctrl>d
```

29. Create the das-sqa.va.gov.pem certificate in the “certificates” directory:

```
$ cat > das-sqa.va.gov.pem
```

30. Paste the das-sqa.va.gov.pem content from Appendix 8.1.14.

```
<ctrl>d
```

31. Create the das.va.gov.pem certificate in the “certificates” directory:

```
$ cat > das.va.gov.pem
```

32. Paste the das.va.gov.pem content from Appendix 8.1.15.

```
<ctrl>d
```

33. Create a certificate request configuration file:

```
$ cat > [proxy_fqdn]_csr_cfg.txt
[req]
default_bits=2048
prompt=no
default_md=sha256
req_extensions=req_ext
distinguished_name=dn

[ dn ]
C=US
ST=Texas
L=Austin
O=US Department of Veterans Affairs
OU=AITC
CN=[proxy_fqdn]
emailAddress=admin@va.gov

[ req_ext ]
subjectAltName=@alt_names

[ alt_names ]
DNS.1=[proxy_fqdn]
DNS.2=[vm2_fqdn]
<ctrl>d
```

34. Generate a permanent certificate signing request:

```
$ openssl req -out [proxy_fqdn]_csr_[yyyymmdd].txt -newkey rsa:2048 -keyout
[proxy_fqdn]_key.txt -new -sha256 -nodes -config [proxy_fqdn]_csr_cfg.txt
Generating a 2048 bit RSA private key
+++++
.....+++
.....+++
writing new private key to ' [proxy_fqdn]_key.txt '
-----
```

35. Submit the certificate signing request to VA PKI to obtain a permanent certificate.

36. Save the permanent certificate in the “certificates” directory:

```
$ cat > /u01/certificates/[proxy_fqdn]_cert.pem
```

37. Paste permanent certificate content.

```
<ctrl>d
```

38. Generate a *[proxy_fqdn]* pkcs12 certificate store:

```
$ openssl pkcs12 -export -name [proxy_fqdn] -in [proxy_fqdn]_cert.pem -inkey
[proxy_fqdn]_key.txt -out [proxy_fqdn].p12
Enter Export Password: #####
Verifying - Enter Export Password: #####
```

39. Generate *[proxy_fqdn]* java keystore:

```
$ keytool -importkeystore -deststorepass ##### -destkeypass ##### -destkeystore
[proxy_fqdn].jks -srckeystore [proxy_fqdn].p12 -srcstoretype PKCS12 -srcstorepass #### -
alias [proxy_fqdn]
```

40. Import va_root_ca_cert.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias va_root_ca -file va_root_ca_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

41. Import va_internal_subordinate_ca_cert.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias va_internal_subordinate_ca -file
va_internal_subordinate_ca_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

42. Import va_root_ca_s2_cert.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias va_root_ca_s2 -file va_root_ca_s2_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

43. Import va_intermediate_ca1_s2_cert.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias va_intermediate_ca1_s2 -file va_intermediate_ca1_s2_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

44. Import va_intermediate_ca2_s2_cert.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias va_intermediate_ca2_s2 -file va_intermediate_ca2_s2_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

45. Import veterans_affairs_device_ca_b2_cert.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias veterans_affairs_device_ca_b2 -file veterans_affairs_device_ca_b2_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

46. Import betrusted_production_ssp_ca_a1_crt.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias betrusted_production_ssp_ca -file betrusted_production_ssp_ca_a1_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

47. Import federal_common_policy_ca_cert.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias federal_common_policy_ca -file federal_common_policy_ca_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

48. Import sqa.services.eauth.va.gov_cert.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias sqa.services.eauth.va.gov -file sqa.services.eauth.va.gov_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

49. Import vaww.esrdev.aac.va.gov_cert.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias vaww.esrdev.aac.va.gov -file vaww.esrdev.aac.va.gov_cert.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

50. Import vaww.esrstage1a.aac.va.gov.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias vaww.esrstage1a.aac.va.gov -file vaww.esrstage1a.aac.va.gov.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

51. Import vaww.esrstage1b.aac.va.gov.pem Certificate into *[proxy_fqdn]* java keystore:

```
$ keytool -import -alias vaww.esrstage1b.aac.va.gov -file vaww.esrstage1b.aac.va.gov.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
```

```
Trust this certificate? [no]: yes
Certificate was added to keystore
```

52. Import vaww.esrspre-prod.aac.va.gov.pem Certificate into **[proxy_fqdn]** java keystore:

```
$ keytool -import -alias vaww.esrspre-prod.aac.va.gov -file vaww.esrspre-
prod.aac.va.gov.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

53. Import das-test.va.gov.pem Certificate into **[proxy_fqdn]** java keystore:

```
$ keytool -import -alias das-test.va.gov -file das-test.va.gov.pem -keystore
[proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

54. Import das-sqa.va.gov.pem Certificate into **[proxy_fqdn]** java keystore:

```
$ keytool -import -alias das-sqa.va.gov -file das-sqa.va.gov.pem -keystore
[proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

55. Import das.va.gov.pem Certificate into **[proxy_fqdn]** java keystore:

```
$ keytool -import -alias das.va.gov -file das
.va.gov.pem -keystore [proxy_fqdn].jks
Enter keystore password: #####
Trust this certificate? [no]: yes
Certificate was added to keystore
```

56. Copy certificate artifacts to VM2:

```
$ scp [proxy_fqdn].jks [vm2_fqdn]:/u01/certificates
$ scp [vm2_fqdn].p12 [vm2_fqdn]:/u01/certificates
$ scp cacerts [vm2_fqdn]:/u01/certificates
```

4.2.8 Create NSS certificate database on VM1

1. Create a new NSS certificate database:

```
$ sudo mv /etc/httpd/alias /etc/httpd/alias_orig  
$ sudo mkdir /etc/httpd/alias  
$ sudo certutil -N -d /etc/httpd/alias  
Enter new password: ####  
Re-enter password: ####
```

2. Add server permanent certificate:

```
$ sudo pk12util -i [proxy_fqdn].p12 -d /etc/httpd/alias -n [proxy_fqdn]  
Enter Password or Pin for "NSS Certificate DB": ####  
Enter password for PKCS12 file: ####  
pk12util: PKCS12 IMPORT SUCCESSFUL
```

3. Add certificate chain:

```
$ sudo certutil -A -d /etc/httpd/alias -i va_root_ca_s2_cert.pem -t CT,, -n va_root_ca_s2  
$ sudo certutil -A -d /etc/httpd/alias -i va_intermediate_ca1_s2_cert.pem -t CT,, -n  
va_intermediate_ca1_s2  
$ sudo certutil -A -d /etc/httpd/alias -i va_intermediate_ca2_s2_cert.pem -t CT,, -n  
va_intermediate_ca2_s2
```

4. Modify certificate database permissions:

```
$ sudo chmod g+r, o+rx /etc/httpd/alias  
$ sudo chmod -R g+r, o+r /etc/httpd/alias/*
```

5. Verify installed certificates:

```
$ certutil -L -d /etc/httpd/alias
```

6. Create certificate database password file:

```
$ cat > /etc/httpd/conf/password.conf  
internal:####  
NSS FIPS 140-2 Certificate DB:####  
<ctrl>d
```

7. Modify certificate database password file permissions:

```
$ sudo chmod g+r, o+r /etc/httpd/conf/password.conf
```

8. Start HTTPD server

```
$ sudo service httpd start
```

9. Review access_log, error_log, nss_access_log and nss_error_log to ensure TLS is functioning correctly.

4.2.9 Create NSS certificate database on VM2

1. Create a new NSS certificate database:

```
$ sudo mv /etc/httpd/alias /etc/httpd/alias_orig  
$ sudo mkdir /etc/httpd/alias  
$ sudo certutil -N -d /etc/httpd/alias  
Enter new password: ####  
Re-enter password: ####
```

2. Add server permanent certificate:

```
$ sudo pk12util -i [vm2_fqdn].p12 -d /etc/httpd/alias -n [vm2_fqdn]  
Enter Password or Pin for "NSS Certificate DB": ####  
Enter password for PKCS12 file: ####  
pk12util: PKCS12 IMPORT SUCCESSFUL
```

3. Add certificate chain:

```
$ sudo certutil -A -d /etc/httpd/alias -i va_root_ca_s2_cert.pem -t CT,, -n va_root_ca_s2  
$ sudo certutil -A -d /etc/httpd/alias -i va_intermediate_ca1_s2_cert.pem -t CT,, -n  
va_intermediate_ca1_s2  
$ sudo certutil -A -d /etc/httpd/alias -i va_intermediate_ca2_s2_cert.pem -t CT,, -n  
va_intermediate_ca2_s2
```

4. Modify certificate database permissions:

```
$ sudo chmod g+r, o+rx /etc/httpd/alias  
$ sudo chmod -R g+r, o+r /etc/httpd/alias/*
```

5. Verify installed certificates:

```
$ certutil -L -d /etc/httpd/alias
```

6. Create certificate database password file:

```
$ cat > /etc/httpd/conf/password.conf  
internal:####  
NSS FIPS 140-2 Certificate DB:####  
<ctrl>d
```

7. Modify certificate database password file permissions:

```
$ sudo chmod g+r, o+r /etc/httpd/conf/password.conf
```

8. Start HTTPD server

```
$ sudo service httpd start
```

9. Review access_log, error_log, nss_access_log and nss_error_log to ensure TLS is functioning correctly.

4.2.10 NSS Configuration on VM1

```
6. cp /tmp/INB_ERX1.0/downloads/WLSPlugin12.1.3-Apache2.2-Apache2.4-
Linux_x86_64/lib/mod_wl_24.so /etc/httpd/modules/ - Need Linux SA assistance.
Note: we are using mod_wl_24.so instead of mod_wl.so since Apache on this server is
Apache v2.4
7.
- Changed From LoadModule weblogic_module modules/mod_wl.so To LoadModule
weblogic_module modules/mod_wl_24.so
- remove "#exit"
8. Remove this step as we will run Apache commands as WebLogic.
9. Replace with
- sudo systemctl status httpd.service
- sudo systemctl stop httpd.service
- sudo systemctl start httpd.service
```

The following steps need to be performed on VM1 and VM2:

1. Rename the RPM default ssl.conf file to ssl.conf_orig to prevent Apache from loading during startup.

```
$ sudo mv ssl.conf ssl.conf_orig
```

2. Modify NSS configuration:

```
$ sudo vi /etc/httpd/conf.d/nss.conf
```

- a. Modify Listen parameter:

```
#Listen 8443
Listen 443
```

- b. Modify NSSPassPhraseDialog parameter:

```
#NSSPassPhraseDialog builtin
NSSPassPhraseDialog file:/etc/httpd/conf/password.conf
NSSFIPS on
```

- c. Modify VirtualHost tag:

```
#<VirtualHost _default_:8443>
<VirtualHost _default_:443>
```

- d. Modify ServerName parameter:

```
#ServerName www.example.com:8443
ServerName [proxy_fqdn]:443
```

- e. Modify NSS logging parameters:

```
#ErrorLog /etc/httpd/logs/error_log
#TransferLog /etc/httpd/logs/access_log
ErrorLog /etc/httpd/logs/nss_error_log
TransferLog /etc/httpd/logs/nss_access_log
```

- f. Modify NSSCipherSuite parameters:

```
#NSSCipherSuite
+aes_128_sha_256,+aes_256_sha_256,+ecdhe_ecdsa_aes_128_gcm_sha_256,+ecdhe_ecdsa_ae
s_128_sha,+ecdhe_ecdsa_aes_256_sha,+ecdhe_rsa_aes_128_gcm_sha_256,+ecdhe_rsa_aes_1
28_sha,+ecdhe_rsa_aes_256_sha,+rsa_aes_128_gcm_sha_256,+rsa_aes_128_sha,+rsa_aes_2
56_sha
NSSCipherSuite +rsa_aes_128_sha,+rsa_aes_256_sha
```

- g. Modify NSSProtocol parameters:

```
#NSSProtocol SSLv3,TLSv1.0,TLSv1.1
NSSProtocol TLSv1.1,TLSv1.2
```

- h. Modify NSSNickname parameter:

```
#NSSNickname Server-Cert
NSSNickname [proxy_fqdn]
NSSEnforceValidCerts off
```

- i. Save the nss.conf file.

3. Start HTTPD server

```
$ sudo service httpd start
```

4. Review access_log, error_log, nss_access_log and nss_error_log to ensure TLS is functioning correctly.

4.2.11 NSS Configuration on VM2

```
6. cp /tmp/INB_ERX1.0/downloads/WLSPlugin12.1.3-Apache2.2-Apache2.4-Linux_x86_64/lib/mod_wl_24.so /etc/httpd/modules/ - Need Linux SA assistance.  
Note: we are using mod_wl_24.so instead of mod_wl.so since Apache on this server is Apache v2.4  
7.  
- Changed From LoadModule weblogic_module modules/mod_wl.so To LoadModule weblogic_module modules/mod_wl_24.so  
- remove "#exit"  
8. Remove this step as we will run Apache commands as WebLogic.  
9. Replace with  
- sudo systemctl status httpd.service  
- sudo systemctl stop httpd.service  
- sudo systemctl start httpd.service
```

The following steps need to be performed on VM1 and VM2:

1. Rename the RPM default ssl.conf file to ssl.conf_orig to prevent Apache from loading during startup.

```
$ sudo mv ssl.conf ssl.conf_orig
```

2. Modify NSS configuration:

```
$ sudo vi /etc/httpd/conf.d/nss.conf
```

- a. Modify Listen parameter:

```
#Listen 8443  
Listen 443
```

- b. Modify NSSPassPhraseDialog parameter:

```
#NSSPassPhraseDialog builtin  
NSSPassPhraseDialog file:/etc/httpd/conf/password.conf  
NSSFIPS on
```

- c. Modify VirtualHost tag:

```
#<VirtualHost _default_:8443>  
<VirtualHost _default_:443>
```

- d. Modify ServerName parameter:

```
#ServerName www.example.com:8443  
ServerName [vm2_fqdn]:443
```

- e. Modify NSS logging parameters:

```
#ErrorLog /etc/httpd/logs/error_log  
#TransferLog /etc/httpd/logs/access_log  
ErrorLog /etc/httpd/logs/nss_error_log  
TransferLog /etc/httpd/logs/nss_access_log
```

- f. Modify NSSProtocol parameters:

```
#NSSProtocol SSLv3,TLSv1.0,TLSv1.1  
NSSProtocol TLSv1.1,TLSv1.2
```

- g. Modify NSSNickname parameter:

```
#NSSNickname Server-Cert  
NSSNickname [proxy_fqdn]  
NSSEnforceValidCerts off
```

- h. Save the nss.conf file.

3. Start HTTPD server

```
$ sudo service httpd start
```

4. Review access_log, error_log, nss_access_log and nss_error_log to ensure TLS is functioning correctly.

4.2.12 Install Apache Plug-in for WebLogic on VM1 and VM2

The following steps need to be performed on VM1 and VM2:

1. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Create downloads directory if it doesn't exist:

```
$ mkdir -p /u01/downloads
```

3. Download Oracle WLS Plugin 12.1.3 archive (v44415-01) to the downloads directory:

```
Download from AITC IEP eRx Downloads directory
```

4. Unzip the Oracle WLS Plugin 12.1.3 archive to in the downloads directory:

```
$ unzip fmw_12_1_3_0_wls_plugin_v44415-01.zip  
$ unzip WLSPlugins12c-12.1.3.zip WLSPlugin12.1.3-Apache2.2-Apache2.4-Linux_x86_64.zip  
$ mkdir WLSPlugin12.1.3-Apache2.2-Apache2.4-Linux_x86_64  
$ unzip WLSPlugin12.1.3-Apache2.2-Apache2.4-Linux_x86_64.zip \  
    -d WLSPlugin12.1.3-Apache2.2-Apache2.4-Linux_x86_64  
$ chmod -R o+rwx WLSPlugin12.1.3-Apache2.2-Apache2.4-Linux_x86_64  
$ exit
```

5. You should be back in your normal Linux login account.

6. Copy the Apache Plug-in for WebLogic libraries to the Linux system library directory (the following must be performed by a system administrator):

```
$ sudo cp /u01/downloads/WLSPlugin12.1.3-Apache2.2-Apache2.4-Linux_x86_64/lib/mod_* \  
    /usr/lib64/httpd/modules
```

4.2.13 Configure Apache Plug-in for WebLogic on VM1

The following steps need to be performed on VM1 and VM2:

1. Log into Linux and sudo su to the root account:

```
$ sudo su -  
# cat > /etc/httpd/conf.d/weblogic.conf  
LoadModule weblogic_module modules/mod_wl.so  
  
<IfModule weblogic_module>  
    WebLogicCluster [vm1_fqdn]:8001, [vm2_fqdn]:8001  
    MatchExpression /*  
    WLExcludePathOrMimeType /cpanel/*  
    WLIOTimeoutSecs 300  
    WLProxySSL OFF  
    WebLogicSSLVersion TLSv1_1 TLSv1_2  
    WLTimeoutSecs 2  
    DebugConfigInfo ON  
</IfModule>  
<CTRL><d>  
# exit
```

2. You should be back in your normal Linux login account.

3. Restart Apache

```
$ sudo service httpd stop  
$ sudo service httpd start
```

4. Review access_log, error_log, nss_access_log and nss_error_log to ensure Apache is functioning correctly.

4.2.14 Configure Apache Plug-in for WebLogic on VM2

The following steps need to be performed on VM1 and VM2:

1. Log into Linux and sudo su to the root account:

```
$ sudo su -
# cat > /etc/httpd/conf.d/weblogic.conf
LoadModule weblogic_module modules/mod_wl.so
LoadModule weblogic_module modules/mod_wl_24.so

<IfModule weblogic_module>
    WebLogicCluster [vm1_fqdn]:8001, [vm2_fqdn]:8001
    MatchExpression /*
    WLExcludePathOrMimeType /cpanel/*
    WLExcludePathOrMimeType /inbound/*
    WLIOTimeoutSecs 300
    WLProxySSL OFF
    WebLogicSSLSVersion TLSv1_1 TLSv1_2
    WLTimeoutSecs 2
    DebugConfigInfo ON
</IfModule>
<CTRL><d>
# exit
```

2. You should be back in your normal Linux login account.
3. Restart Apache

```
$ sudo service httpd stop
$ sudo service httpd start
```

4. Review access_log, error_log, nss_access_log and nss_error_log to ensure Apache is functioning correctly.

4.2.15 Create IEP CPanel on VM1 and VM2

1. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Create downloads directory if it doesn't exist:

```
$ mkdir -p /u01/deployments
```

3. Download the CPanel Archive (cpanel_yyyymmdd.tgz) to the deployments directory:

```
Download from AITC IEP eRx Deploymentss directory
$ exit
```

4. You should be back in your normal Linux login account.

5. Unpack the CPanel Archive from the root (/) directory:

```
$ cd /
$ sudo tar xvf /u01/deployments/cpanel_yyyymmdd.tgz
```

4.2.16 Install Apache SSOi Web Agent on VM1

1. Start Xming or other X Server on your Windows Desktop/Laptop. Connect to the server using Putty. The DISPLAY environment variable should be set.

2. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

3. Create downloads directory if it doesn't exist:

```
$ mkdir -p /u01/downloads
```

4. Download CA SiteMinder Apache Web Agent (smwa-12.51-cr07-linux-x86-64.zip) to the downloads directory:

```
Download from AITC IEP eRx Downloads directory
```

5. Unzip the CA SiteMinder Apache Web Agent archive to in the downloads directory:

```
$ cd /u01/downloads  
$ unzip smwa-12.51-cr07-linux-x86-64.zip -d smwa-12.51-cr07-linux-x86-64  
$ chmod o+rwx smwa-12.51-cr07-linux-x86-64  
$ chmod o+r smwa-12.51-cr07-linux-x86-64/layout.properties  
$ chmod ugo+rwx smwa-12.51-cr07-linux-x86-64/ca-wa-12.51-cr07-linux-x86-64.bin  
$ exit
```

6. You should be back in your normal Linux login account.

7. Execute the CA SiteMinder Apache Web Agent installer (the following must be performed by a system administrator):

```
$ sudo /u01/downloads/smwa-12.51-cr07-linux-x86-64/ca-wa-12.51-cr07-linux-x86-64.bin -i  
console
```

8. Press <Enter> to continue installing in Console mode:

```
PRESS <ENTER> TO CONTINUE: <ENTER>
```

9. Press <Enter> many times to scroll through license agreement:

```
PRESS <ENTER> TO CONTINUE: <ENTER>
```

10. Enter “Y” to accept license agreement:

```
DO YOU ACCEPT THE TERMS OF THIS LICENSE AGREEMENT? (Y/N) : Y
```

11. Enter installation path:

```
ENTER AN ABSOLUTE PATH, OR PRESS <ENTER> TO ACCEPT THE DEFAULT  
: /u01/app/CA/webagent
```

12. Confirm installation path:

```
INSTALL FOLDER IS: /u01/app/webagent  
IS THIS CORRECT? (Y/N) : Y
```

13. Confirm installation details:

```
Please Review the Following Before Continuing:  
Product Name:  
    CA SiteMinder Web Agent  
Install Folder:  
    /u01/app/webagent  
Disk Space Information (for Installation Target):  
    Required: 300,510,677 Bytes  
    Available: 60,435,013,632 Bytes  
PRESS <ENTER> TO CONTINUE: <ENTER>
```

14. Confirm exit from installer:

```
PRESS <ENTER> TO EXIT THE INSTALLER: <ENTER>
```

4.2.17 Configure Apache SSOi Web Agent on VM1

1. Log into Linux and sudo su to the root account (the following must be performed by a system administrator):

```
$ sudo su -
```

2. Change directory to the agent home and "source" the Siteminder environment:

```
# cd /u01/app/CA/webagent  
# ./ca_wa_env.sh
```

3. Change to install config info directory and launch the configuration wizard:

```
# cd install_config_info  
# ./ca-wa-config.sh -i console
```

4. Type 1 to register the trusted host, then Press Enter

```
->1- Yes, I would like to do Host Registration now.  
2- No, I would like to do Host Registration later.
```

```
ENTER A COMMA-SEPARATED LIST OF NUMBERS REPRESENTING THE DESIRED CHOICES, OR  
PRESS <ENTER> TO ACCEPT THE DEFAULT: 1
```

5. In the Admin User Name prompt, type threg then press Enter

```
Enter the name of an administrator who has the right to register trusted hosts  
with the Policy Server.
```

```
This entry must match the name of an administrator defined in the Policy  
Server.
```

```
Admin User Name (Default: ): threg
```

6. For Shared Secret Rollover, type n then press Enter

```
Enable Shared Secret Rollover (y/n) (Default: n): n
```

7. Type the threg password then press Enter

```
Enter the password of an administrator who has the right to register trusted  
hosts with the Policy Server. This entry must match the name of an  
administrator defined in the Policy Server.:
```

```
Confirm Admin Password: <- va1234!
```

8. Type the Trusted Host Name then press Enter

```
Specify the name of the host you want to register with the Policy Server.
```

```
Enter the name of the host configuration object. The name must match a host  
configuration object name already defined on the Policy Server.
```

```
Trusted Host Name (Default: ): [proxy_fqdn]
```

9. Type the Host Configuration Object then press Enter

```
Host Configuration Object (Default: ): [iam_hco]
```

10. Type the Policy Server IP Address then press Enter

```
Policy Server IP Address
```

```
-----
```

```
Enter the IP Address of the Policy Server where you are registering this host.
```

```
Policy Server IP Address (Default: ): [iam_policy]
```

11. In the FIPS Mode Settings, select 3 then press Enter

```
FIPS Mode Setting
```

```
-----
```

```
->1- FIPS Compatibility Mode  
2- FIPS Migration Mode  
3- FIPS Only Mode
```

```
ENTER THE NUMBER FOR YOUR CHOICE, OR PRESS <ENTER> TO ACCEPT THE DEFAULT:: 3
```

12. Press Enter twice to accept the default file name and location of Host configuration

```
Host Configuration file location
```

```
-----
```

```
Enter file name (Default: SmHost.conf):
```

```
Enter location (Default: /u01/app/CA/webagent/config):
```

13. Select 1 for Apache Web Server, then press Enter

```
Select Web Server(s)
```

```
-----
```

- 1- Apache Web Server
- 2- Domino Web Server
- >3- iPlanet or Sun ONE Web Server

```
ENTER A COMMA-SEPARATED LIST OF NUMBERS REPRESENTING THE DESIRED CHOICES, OR  
PRESS <ENTER> TO ACCEPT THE DEFAULT: 1
```

14. Specify the path to apache instance /home/apache/httpd

```
Apache Web Server path
```

```
-----
```

```
Enter the root path of where Apache Web server installed.
```

```
Please enter path (Default: ): /etc/httpd
```

15. Select the Apache version, type 3 then press Enter

```
Apache Version
```

```
-----
```

```
Please select a choice for the Apache version.
```

- 1- Apache version 1.x
- 2- Apache version 2.x
- 3- Apache version 2.2.x
- 4- Apache version 2.4.x

```
ENTER THE NUMBER OF THE DESIRED CHOICE: 4
```

16. Select the Apache Type, type 6 then press Enter

```
Apache Server Type
```

```
-----
```

```
Please select one of the following appropriately match your previous selection
```

- 1- Oracle HTTP Server
- 2- IBM HTTP Server
- 3- HP Apache
- 4- ASF/RedHat Apache
- 5- RedHat JWS HTTP Server

```
ENTER THE NUMBER OF THE DESIRED CHOICE: 4
```

17. Type 1 to confirm the Apache version

```
Select Web Server(s)
```

```
-----
```

- 1- [] Apache 2.2.15

```
Select the web server(s) you wish to preserve or configure/reconfigure as  
Web Agent(s). Enter a comma-separated list of numbers representing the
```

desired choices. Already configured web servers are marked as [x] in the above list, you can un-configure or skip these web servers in next steps by not listing them in comma-separated list here.: 1

18. Type the Agent Configuration Object, then press Enter

Agent Configuration Object

Enter the name of an Agent Configuration Object that defines the configuration parameters which the Web Agent will use for Apache 2.2.15.

Agent Configuration Object (Default: AgentObj): PREAgentConfig

19. To select Basic over SSL Authentication, Type 1 then press Enter

SSL Authentication

The following SSL configurations are available for this web server. If the Web Agent will be providing advanced authentication, select which configuration it will use to configure Apache 2.2.15.

- >1- HTTP Basic over SSL
- 2- X509 Client Certificate
- 3- X509 Client Certificate and HTTP Basic
- 4- X509 Client Certificate or HTTP Basic
- 5- X509 Client Certificate or Form
- 6- X509 Client Certificate and Form
- 7- No advanced authentication

ENTER THE NUMBER FOR YOUR CHOICE, OR PRESS <ENTER> TO ACCEPT THE DEFAULT:: 1

20. Type 1 on the Webagent Enable prompt then press Enter

Webagent Enable option

Please select Yes to Enable the WebAgent

- 1- Yes
- >2- No

ENTER THE NUMBER FOR YOUR CHOICE, OR PRESS <ENTER> TO ACCEPT THE DEFAULT:: 1

21. On the Summary Screen, Type 1 then press Enter

Web Server Configuration Summary

Please confirm the configuration selection. Accept the configuration and press 'Enter' to continue. To change one or more settings, select 'Previous'. Select 'Cancel' will exit the configuration.

Configure the following webserver(s):
Apache Server:
Apache 2.2.15
Agent Configuration Object: PREAgentConfig
SSL Authentication type: HTTP Basic over SSL

IS WebAgent Enabled: YES

Please enter a choice.

- >1- Continue
- 2- Previous
- 3- Cancel

ENTER THE NUMBER OF THE DESIRED CHOICE, OR PRESS <ENTER> TO ACCEPT THE DEFAULT: 1

22. Continue installation if ssl.conf file doesn't exist:

```
1- Continue  
2- Exit
```

```
Unable to process configuration. File /etc/httpd/conf.d/ssl.conf doesnt  
exist. Please make sure the configuration path is valid.
```

```
Please select a choice..: 1
```

23. Confirm exit from installer:

```
PRESS <ENTER> TO EXIT THE INSTALLER: <ENTER>
```

24. Enter "exit" to log out of root account:

```
# exit
```

25. You should be back in your normal Linux login account.

4.2.18 Post Configure Edits for Apache SSOi Web Agent on VM1

1. Log into Linux and sudo su to the root account:

```
$ sudo su -
```

2. Edit /u01/app/CA/webagent/config/SmHost.conf:

```
vi /u01/app/CA/webagent/config/SmHost.conf
```

3. Verify policyserver entries:

```
# Add additional bootstrap policy servers here for fault tolerance.  
[iam_policy_servers]
```

4. Edit /etc/httpd/conf/WebAgent.conf:

```
vi /etc/httpd/conf/WebAgent.conf
```

5. Enable the agent:

```
EnableWebAgent="YES"
```

6. For an embedded Apache web server (included by default) on a RedHat Linux system, modify certain configuration files to accommodate the product first. Follow these steps::

```
cp /etc/sysconfig/httpd /etc/sysconfig/httpd.orig  
vi /etc/sysconfig/httpd
```

Add the following line to the end of the file:

```
PATH=$PATH:web_agent_home/bin
```

Save the changes and close the text editor.

7. Source ca_wa_env.sh script in the following file (instead of starting it manually each time):

```
cp /etc/init.d/httpd /etc/init.d/httpd.orig  
vi /etc/init.d/httpd
```

Add the following code snippet after the similar snippet for /etc/sysconfig/httpd

```
# Source CA Webagent environment  
if [ -f /u01/app/CA/webagent/ca_wa_env.sh ]; then  
    . /u01/app/CA/webagent/ca_wa_env.sh  
fi
```

8. Modify the apachectl script to set the webagent environment variables:

```
cp /usr/sbin/apachectl /usr/sbin/apachectl.orig  
vi /usr/sbin/apachectl
```

Locate a line resembling the following example:

```
# Source /etc/sysconfig/httpd for $HTTPD setting, etc
```

Add the following code snippet after the similar snippet for /etc/sysconfig/httpd/:

```
# Source CA Webagent environment
```

```
if [ -r /u01/app/CA/webagent/ca_wa_env.sh ]; then
    . /u01/app/CA/webagent/ca_wa_env.sh
fi
```

9. Modify permission of CA SmHost.conf file

```
# chmod 666 /u01/app/CA/webagent/config/SmConf.conf
```

10. Create /opt/ca/webagent symbolic link

```
# mkdir /opt/ca
# chmod 755 /opt/ca
# ln -s /u01/app/CA/webagent/ /opt/ca/webagent
```

11. Modify ownership and permission of CA Webagent log files

```
# chown apache:apache /u01/app/CA/webagent/log
# chmod 777 /u01/app/CA/webagent/log
```

12. Modify trace file verbocity

Modify SSOi WebAgent trace.conf file:

```
# cd /opt/ca/webagent/config
# vi trace.conf
```

Modify lines near the bottom per the following:

```
nete.enableConsoleLog=0
nete.enableFileLog=0
nete.logFile=0

nete.conapi.logLevel=0
nete.conapi.ipc.logLevel=0
nete.conapi.tcpip.logLevel=0

nete.mon.monitoringApiLogLevel=0
```

Modify SSOi WebAgent WebAgentTrace.conf file:

```
# vi WebAgentTrace.conf
```

Modify lines neer the bottom to be:

```
components: WebAgent
data: Date, Time, Pid, Function, TransactionID, User, Message
```

13. Modify sysctl for Apache on RHEL 7.

Open a text file for sysctl properties:

```
dzdo systemctl edit httpd.service
```

Insert the following:

```
[Service]
ExecStart=
ExecReload=
```

```
ExecStart=/bin/bash -a -c 'source /u01/CA/webagent/ca_wa_env.sh && exec /usr/sbin/httpd
$OPTIONS -DFOREGROUND'
ExecReload=/bin/bash -a -c 'source /u01/CA/webagent/ca_wa_env.sh && exec /usr/sbin/httpd
$OPTIONS -k graceful'
```

Close and save.

This will create /etc/systemd/system/httpd.service.d/override.conf.

Reload the deamon:

```
dzdo systemctl daemon-reload
```

httpd should come up with a normal start command.

If a “file not found” error occurs, file “ca_wa_env.sh” may be in a different location.

These files can get installed in different locations across different systems.

If this is the case, execute a find command:

```
dzdo find / -name 'ca_wa_env.sh'
```

If ‘ca_wa_env.sh’ is not found, search for “set-apache-env.sh”.

```
dzdo find / -name 'set-apache-env.sh'
```

Update override.conf with the correct path.

Reload the deamon:

```
dzdo systemctl daemon-reload
```

Verify system is functioning correctly.

14. Restart Apache and check the logs for connection or errors.

```
# exit  
$ sudo service httpd stop  
$ sudo service httpd start
```

4.3 Download and Extract Files

This section is not applicable to this guide.

4.4 Database Creation

This section is not applicable to this guide.

4.5 Installation Scripts

This section is not applicable to this guide.

4.6 Cron Scripts

This section is not applicable to this guide.

4.7 Access Requirements and Skills Needed for the Installation

This section is not applicable to this guide.

4.8 Installation Procedure

This section provides step-by-step instructions for installing all components of the Inbound eRx software on all platforms.

4.8.1 WebLogic Installation

The following subsections describe the steps to install the WebLogic application server. Most activities are to be performed by the WebLogic Administrator.

4.8.1.1 Install WebLogic

1. Log into Linux and sudo to the weblogic account as follows:

```
$ sudo su - weblogic
```

2. Modify the weblogic Linux account .bash_profile, replace the PATH= and export PATH with the following near the end of the file:

```
export JAVA_HOME=/u01/app/java/latest
export PATH=${JAVA_HOME}/bin:${PATH}: ${HOME}/bin
```

3. Exit weblogic account:

```
$ exit
```

4. Start Xming or other X Server on your Windows Desktop/Laptop. Connect to the server using Putty. The DISPLAY environment variable should be set.

5. Log into Linux and modify your .Xauthority permissions:

```
$ chmod 755 ~
$ chmod 644 ~/.Xauthority
```

6. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

7. Copy the .Xauthority file from your normal Linux account to the current account:

```
$ cp ~yourusername/.Xauthority .
```

8. Create downloads directory if it doesn't exist:

```
$ mkdir -p /u01/downloads
```

9. Download Oracle WLS 12.1.3 installer (v44413-01) to the downloads directory:

Download from AITC IEP eRx Downloads directory

10. Unzip the Oracle WLS 12.1.3 installer to the downloads directory:

```
$ unzip fmw_12.1.3.0.0_wls_v44413-01.zip
```

11. Run the Oracle WLS 12.1.3 installer:


```
$ java -jar fmw_12.1.3.0.0_wls.jar
```

12. Enter "y" to accept prerequisite checks.

13. Enter "/u01/app/oraInventory".


14. Select **OK**.

Figure 3: Install WebLogic – Oracle Fusion Middleware Installation Inventory Setup



15. The Oracle Universal Installer will appear for a few moments.

Figure 4: Install WebLogic – Oracle Universal Installer Dialog Box



16. Once the installer is complete, select **Next**.


Figure 5: Install WebLogic – Oracle Fusion Middleware WebLogic Server and Coherence Installer



17. Enter *Oracle Home*: “[**ORACLE_BASE**]”.

18. Select **Next**.


Figure 6: Install WebLogic – Installation Location



19. For *Installation Type*, select the *WebLogic Server* radio button.


20. Select **Next**.

Figure 7: Install WebLogic – Installation Type



21. Select **Next** again on the **Prerequisite Checks** screen.

Figure 8: Install WebLogic – Prerequisite Checks




22. On the Security Updates screen, leave the *Email* field blank.

23. Uncheck “I wish to receive security updates via My Oracle Support”.


24. Select **Next**.

Figure 9: Install WebLogic – Security Updates Screen




25. Select **Yes** to acknowledge not receiving critical security issues notifications.

Figure 10: Install WebLogic – My Oracle Support Username/Email Address Not Specified Dialog Box



26. On the *Installation Summary* screen, select **Install**.

Figure 11: Install WebLogic – Installation Summary Screen




27. Wait while the installation progresses.

28. Once the installation is complete, the following screen will display.

29. Select **Next**.


Figure 12: Install WebLogic – Installation Progress Screen



30. On the **Installation Complete** screen, leave *Automatically Launch the Configuration Wizard* checked.

31. Select **Finish**.

Figure 13: Install WebLogic – Installation Complete



32. The Oracle **Configuration Wizard** splash screen will appear for a few moments.

Figure 14: Install WebLogic – Oracle Configuration Wizard Splash Screen




33. On the **Configuration Type** screen, select *Create a new domain*.

34. Enter the following in the *Domain Location*:

`[ORACLE_BASE]/user_projects/domains/[domain]`


35. Select **Next**.

Figure 15: Install WebLogic – Create New Domain




36. On the **Templates** screen, select the *Create Domain using Product Templates* radio button.
37. Under *Available Templates*, select “Basic WebLogic Server Domain”.
38. Select **Next**.

Figure 16: Install WebLogic – Templates Screen




39. On the **Administrator Account** screen, enter *Name*: “weblogic”
40. Enter *Password*: “xxxxxxxx”
41. Enter *Confirm Password*: “xxxxxxxx”
42. Select **Next**.

Figure 17: Install WebLogic – Administrator Account Screen




43. On the **Domain Mode and JDK** screen, select the *Development* radio button for the *Domain Mode*.
44. For *JDK*, select the *Oracle HotSpot 1.8.0_xxx* radio button.
45. Select **Next**.

Figure 18: Install WebLogic - Domain Mode and JDK




46. On the **Advanced Configuration** screen, check *Administration Server*, *Node Manager*, and *Managed Servers, Clusters and Coherence*.
47. Select **Next**.

Figure 19: Install WebLogic– Advanced Configuration




48. On the **Administration Server** screen, enter *Server Name*: “AdminServer”
49. Enter *Listen Address*: “All Local Addresses”
50. Enter *Listen Port*: “7001”
51. Uncheck the check box for *Enable SSL*.
52. Leave the *SSL Listen Port* field blank.
53. Select **Next**.

Figure 20: Install WebLogic – Administration Server Screen




54. On the **Node Manager** screen, select the *Per Domain Default Location* radio button.
55. Enter *Username*: "weblogic"
56. Enter *Password*: "xxxxxxxx"
57. Enter *Confirm Password*: "xxxxxxxx"
58. Select **Next**.

Figure 21: Install WebLogic – Node Manager




59. On the **Managed Servers** screen, select **Add**.
60. Enter the *Server Name*: “erx1”
61. Enter the *Listen Address*: **[vm1_fqdn]**
62. Enter *Listen Port*: “8001”
63. Leave *Enable SSL* unchecked.
64. Leave *SSL Listen Port* empty (Disabled).
65. Select **Add**.
66. Enter *Server Name*: “erx2”
67. Enter *Listen Address*: **[vm2_fqdn]**
68. Enter Listen Port: “8001”
69. Leave *Enable SSL* unchecked.
70. Leave *SSL Listen Port* empty (Disabled).
71. Select **Next**.

Figure 22: Install WebLogic – Managed Servers



72. On the **Clusters** screen, select **Add**.
73. Enter *Cluster Name*: “erx”
74. Enter *Cluster Address*: “[vm1_fqdn]:[erx_port], [vm2_fqdn]:[erx_port]”
75. Enter *Frontend Host*: “[proxy_fqdn]”
76. Enter *Frontend HTTP Port*: “80”
77. Enter *Frontend HTTPS*: “443”
78. Select **Next**.


Figure 23: Install WebLogic – Clusters



79. Assign “erx1” and “erx2” servers to the “erx” cluster.

80. Select **Next**.

Figure 24: Install WebLogic – Assign Servers to Clusters



81. Select **Add**.

82. Enter *Name*: “machine1”

83. Enter *Node Manager Listen Address*: “[*vm1_fqdn*]”

84. Enter *Node Manager Listen Port*: “5556”


85. Enter *Name*: “machine2”

86. Enter *Node Manager Listen Address*: “[*vm1_fqdn*]”

87. Enter *Node Manager Listen Port*: “5556”


88. Select **Next**.

Figure 25: Install WebLogic – Machines




89. On the **Assign Servers to Machines** screen, add “AdminServer” on *Servers* panel to “machine1” on *Machines* panel.
90. Add “erx1” on *Servers* panel to “machine1” on *Machines* panel.
91. Add “erx2” on *Servers* panel to “machine2” on *Machines* panel.
92. Select **Next**.

Figure 26: Install WebLogic – Assign Servers to Machines



93. On the **Configuration Summary** screen, select **Create** to accept the options and start creating and configuring the new domain.

Figure 27: Install WebLogic – Configuration Summary Screen




94. Once the configuration is complete, select **Next**.

95. If the configuration is successful, the **Configuration Success** screen will display as illustrated in the figure below.

96. Select **Finish**.

Figure 28: Install WebLogic - Configuration Success



97. The Oracle WebLogic Server 12.1.3 installation and configuration should be complete at this time. To modify the configuration, re-run the configuration wizard:

```
$ cd [ORACLE_BASE]/oracle_common/common/bin  
$ ./config.sh
```

98. Modify the configuration as needed.

4.8.1.2 Set Temporary Environment on VM1

On VM1, set temporary environment. Remember to amend the DOMAIN_HOME environment variable to match your domain:

```
$ export ORACLE_BASE=[ORACLE_BASE]
$ export WLS_HOME=$ORACLE_BASE/wlserver
$ export DOMAIN_HOME=$ORACLE_BASE/user_projects/domains/[domain]
```

4.8.1.3 Create a Domain Boot Identity File on VM1

On VM1, create a boot identity file for the domain if it doesn't exist:

```
$ mkdir -p $DOMAIN_HOME/servers/AdminServer/security
$ cat > $DOMAIN_HOME/servers/AdminServer/security/boot.properties
username=weblogic
password=#####
<ctrl>d
```

4.8.1.4 Copy Identity/Trust Store Files on VM1

Copy the server identity key store to the WebLogic domain "security" directory on VM1:

```
$ cp /u01/certificates/[proxy_fqdn].jks $DOMAIN_HOME/security/[proxy_fqdn].jks
```

4.8.1.5 Configure nodemanager Identity/Trust Store on VM1

On VM1, edit nodemanager.properties to add identity/trust store configuration:

```
$ cd $DOMAIN_HOME/nodemanager
$ cp nodemanager.properties nodemanager_orig.properties
$ vi nodemanager.properties
```

Add the following lines at the end of the file:

```
KeyStores=CustomIdentityAndCustomTrust
CustomIdentityAlias=[proxy_fqdn]
CustomIdentityKeyStoreFileName=[DOMAIN_HOME]/security/[proxy_fqdn].jks
CustomIdentityKeyStorePassPhrase=[keystore_passphrase]
CustomIdentityKeyStoreType=JKS
CustomIdentityPrivateKeyPassPhrase=[privatekey_passphrase]
```

Enter :wq to save the file and exit vi.

4.8.1.6 Configure TLS on VM1

On VM1, edit startManagedWeblogic.sh to modify TLS configuration:

```
$ cd $DOMAIN_HOME/bin
$ cp startWeblogic.sh startWeblogic_orig.sh
$ vi startWeblogic.sh
```

Modify the JAVA_OPTIONS as follows:

```
JAVA_OPTIONS="${SAVE_JAVA_OPTIONS} -Dweblogic.security.SSL.minimumProtocolVersion=TLSv1.1"
```

Enter :wq to save the file and exit vi.

4.8.1.7 Copy Identity/Trust Store Files on VM2

Copy the server identity key store to the WebLogic domain "security" directory on VM1:

```
$ cp /u01/certificates/[proxy_fqdn].jks $DOMAIN_HOME/security/[proxy_fqdn].jks
```

4.8.1.8 Configure nodemanager Identity/Trust Store on VM2

On VM1, edit nodemanager.properties to add identity/trust store configuration:

```
$ cd $DOMAIN_HOME/nodemanager
$ cp nodemanager.properties nodemanager_orig.properties
```

```
$ vi nodemanager.properties
```

Add the following lines at the end of the file:

```
KeyStores=CustomIdentityAndCustomTrust
CustomIdentityAlias=[proxy_fqdn]
CustomIdentityKeyStoreFileName=[DOMAIN_HOME]/security/[proxy_fqdn].jks
CustomIdentityKeyStorePassPhrase=[keystore_passphrase]
CustomIdentityKeyStoreType=JKS
CustomIdentityPrivateKeyPassPhrase=[privatekey_passphrase]
```

Enter :wq to save the file and exit vi.

4.8.1.9 Disable basic authentication

On VM1, edit config.xml to disable basic authentication:

```
$ cd $DOMAIN_HOME/config.xml
$ cp config.xml config_orig.xml
$ vi config.xml
```

Add the following line before the end tag </security-configuration>:

```
<enforce-valid-basic-auth-credentials>false</enforce-valid-basic-auth-credentials>
```

Enter :wq to save the file and exit vi.

4.8.1.10 Configure JPA for Domain on VM1

On VM1, edit setDomainEnv.sh script to add JPA modules via PRE_CLASSPATH:

```
$ cd $DOMAIN_HOME/bin
$ cp setDomainEnv.sh setDomainEnv_orig.sh
$ vi setDomainEnv.sh
```

Add the following two lines after the first line in the script:

```
PRE_CLASSPATH=[ORACLE_BASE]/oracle_common/modules/javax.persistence_2.1.jar:[WLS_HOME]/modules/com.oracle.weblogic.jpa21support_1.0.0.0_2-1.jar
export PRE_CLASSPATH
```

Enter :wq to save the file and exit vi.

4.8.1.11 Create Inbound eRx Datasource

This section provides step-by-step instructions for deploying VistA Link Connector.


1. Navigate to *Services*, then to *Data Sources*.
2. From the *Data Sources* page, select **New**.

Figure 29: Create Inbound eRx Datasource – Datasources

The screenshot shows the Oracle WebLogic Server Administration Console interface. The left sidebar displays the 'Domain Structure' for 'exdomain1' under the 'Services' category, specifically the 'Data Sources' node. The main content area is titled 'Summary of JDBC Data Sources' and contains a table with three columns: 'Name', 'Type', and 'JNDI Name'. Below the table, it says 'There are no items to display'. At the bottom of the table, there are 'New' and 'Delete' buttons. A context menu is open over the 'New' button, listing three options: 'Generic Data Source', 'GridLink Data Source', and 'Multi Data Source'. The 'Generic Data Source' option is highlighted. The top right corner of the screen shows the user 'Welcome, weblogic' and the domain 'Connected to: exdomain1'.


3. Enter *Name*: **InboundExrxDataSource**
4. Enter *JNDI Name*: **jdbc/InboundExrxDataSource**
5. Select *Database Type*: **Oracle**
6. Select **Next**.

Figure 30: Create Inbound eRx Datasource – Datasource Properties




7. Select *Database Driver*: **Oracle's Driver (Thin XA) for Instance connections; Versions: Any**
8. Select **Next**.

Figure 31: Create Inbound eRx Datasource – Database Driver



9. Select **Next**.

Figure 32: Create Inbound eRx Datasource – Transaction Properties



10. Enter *Database Name*: **[DB_NAME]**
11. Enter *Host Name*: **[DB_FQDN]**
12. Enter *JNDI Name*: **jdbc/InboundErxDataSource**
13. Enter *Port*: **[DB_PORT]**
14. Enter *Password*: **[DB_PASSWORD]**
15. Enter *Confirm Password*: **[DB_PASSWORD]**

Figure 33: Create Inbound eRx Datasource – Connection Properties

The screenshot shows the Oracle WebLogic Server Administration Console interface. On the left, there's a sidebar with 'Change Center' and 'View changes and restarts' sections, and a 'Domain Structure' tree under 'erxdomain1' which includes 'Environment', 'Deployments', 'Services' (with 'Messaging', 'Data Sources', 'Persistent Stores', etc.), 'Work Contexts', 'XML Registries', 'XML Entity Caches', 'JCOM', 'Mail Sessions', and 'File T3'. Below the sidebar are 'How do I...' and 'System Status' sections. The main right-hand panel is titled 'Create a New JDBC Data Source' and has a sub-section 'Connection Properties'. It asks 'What is the name of the database you would like to connect to?' with 'Database Name' set to 'ERXD1'. It then asks 'What is the name or IP address of the database server?' with 'Host Name' set to 'vaauserx dbsdev1.aac.va'. It asks 'What is the port on the database server used to connect to the database?' with 'Port' set to '1549'. It asks 'What database account user name do you want to use to create database connections?' with 'Database User Name' set to 'ERX_UPDATE_USER'. It asks 'What is the database account password to use to create database connections?' with 'Password' and 'Confirm Password' both containing masked text. At the bottom, it lists 'Additional Connection Properties' with 'oracle.jdbc.DRCPConnectionClass:' followed by an empty input field. Navigation buttons 'Back', 'Next', 'Finish', and 'Cancel' are at the very bottom.

16. Select **Test Configuration**.

17. If test is not successful, select **Back** and correct settings, otherwise select **Next**.


Figure 34: Create Inbound eRx Datasource – Test Connection

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. On the left, there's a navigation tree under 'Domain Structure' for 'erxdomain1' with 'Data Sources' selected. The main panel is titled 'Create a New JDBC Data Source' and is currently on the 'Test Configuration' step. It includes fields for 'Driver Class Name' (set to 'oracle.jdbc.xa.client.Oracle'), 'URL' (set to 'jdbc:oracle:thin:@vaause'), 'Database User Name' (set to 'ERX_UPDATE_USER'), 'Password' (redacted), 'Confirm Password' (redacted), 'Properties' (containing 'user=ERX_UPDATE_USER'), 'System Properties' (empty), and 'Test Table Name' (set to 'SQL ISVALID'). The top right shows a message 'Welcome, weblogic' and 'Connected to: erxdomain1'.

18. Select All servers in the cluster.


19. Select Finish.

Figure 35: Create Inbound eRx Datasource – Select Targets/Finish



20. Select InboundExDataSource hyperlink.

Figure 36: Create Inbound eRx Datasource – Modify New Datasource



21. Select the **Connection Pool** tab.

Figure 37: Inbound eRx Datasource –Connection Pool Properties

The screenshot shows the Oracle WebLogic Server Administration Console interface. The left sidebar displays the domain structure under 'exdomain1' with various services like Environment, Deployments, Messaging, Data Sources, and Work Contexts. The main panel is titled 'Settings for InboundExrxDataSource' and has tabs for Configuration, Targets, Monitoring, Control, Security, Notes, General, Connection Pool, Oracle, ONS, Transaction, Diagnostics, and Identity Options. The 'Connection Pool' tab is selected. A 'Save' button is at the bottom. The configuration details include:

- URL:** jdbc:oracle:thin:@vaauuserxdbdev1.aac.va.gov:1549
- Driver Class Name:** oracle.jdbc.xa.client.OracleXADatasource

Below these fields are descriptive notes and 'More Info...' links.

22. Scroll to the bottom of the **Connection Pool** page.

23. Select the **Advanced** hyperlink to expand the advanced properties.

Figure 38: Inbound eRx Datasource –Connection Pool Advanced Properties


This screenshot shows the 'Advanced' properties section of the connection pool configuration. It includes the following settings:

- Initial Capacity:** 1
- Maximum Capacity:** 15
- Minimum Capacity:** 1
- Statement Cache Type:** LRU
- Statement Cache Size:** 10

Each setting has a corresponding description and a 'More Info...' link. At the bottom is a 'Save' button.

24. Scroll down and uncheck the **Wrap Data Types** property.

Figure 39: Inbound eRx Datasource – Wrap Data Type Property



25. Scroll to the bottom of the of the **Advanced Connection Pool** page.

26. Select **Save**.

Figure 40: Inbound eRx Datasource – Save Properties

The screenshot shows the 'Save Properties' section of the Inbound eRx Datasource configuration. It includes the following fields:

- Connection Harvest Max Count:** Input field with value "1". Description: "The maximum number of connections that may be harvested when the connection harvesting occurs. Range of valid values is 1 to MaxCapacity." [More Info...](#)
- Connection Harvest Trigger Count:** Input field with value "-1". Description: "Specifies the number of available connections (triggers) used to determine when connection harvesting occurs." [More Info...](#)
- Connection Count of Refresh Failures Till Disable:** Input field with value "2". Description: "Specifies the number of reconnect failures allowed before WebLogic Server disables a connection to minimize the delay in handling the connection request caused by a database failure. Zero means it is disabled." [More Info...](#)
- Count of Test Failures Till Flush:** Input field with value "2". Description: "Specifies the number of test failures allowed before WebLogic Server closes all unused connections in the connection pool to minimize the delay caused by database testing. Zero means it is disabled." [More Info...](#)

A "Save" button is located at the bottom of the form.

4.8.1.12 Configure Identity/Trust Store File on Managed Servers

This section provides step-by-step instructions for configuring the identity/trust store file on the managed servers.

1. Under **Domain Structure**, navigate to **Servers**.
2. Select the **erx1** link to access the server configuration page in the **Administration Console**.

Figure 41: Configure Identity/Trust Store File – Access Server Configuration Page

The screenshot shows the Oracle WebLogic Server Administration Console interface. On the left, there's a navigation tree titled 'Domain Structure' under 'erxdomain1'. The 'Servers' node is selected and highlighted with a green box. The main right panel is titled 'Summary of Servers' and contains a table with the following data:

Name	Type	Cluster	Machine	State	Health	Listen Port
AdminServer(admin)	Configured		machine1	RUNNING	OK	7001
erx1	Configured	dev1	machine1	SHUTDOWN	Not reachable	8001
erx2	Configured	dev1	machine2	SHUTDOWN	Not reachable	8001

- Under Configuration > Keystores, select Change.

Figure 42: Configure Identity/Trust Store File – Change Keystores

The screenshot shows the Oracle WebLogic Server Administration Console interface. On the left, there's a navigation tree under 'Domain Structure' for 'exdomain1' with nodes like Environment, Services, Security Realms, etc. Below it is a 'How do I...' section with links for 'Configure identity and trust', 'Configure keystores', and 'Set up SSL'. To the right, the main panel is titled 'Settings for exr1' with tabs for Configuration, Protocols, Logging, Debug, Monitoring, Control, Deployments, Services, Security, Notes, Health Monitoring, Server Start, Web Services, and Coherence. The 'Keystores' tab is selected. A sub-section titled 'Keystores:' shows 'Demo Identity and Demo Trust' with a 'Change' button highlighted with a green box. Below this, there are sections for 'Identity' and 'Trust'. Under 'Identity', it shows 'Demo Identity Keystore' located at '/u01/app/Oracle_Home/user_projects/domains/exdomain1/security/DemoIdentity.jks', its type as 'jks', and its passphrase as a masked string. Under 'Trust', it shows 'Demo Trust' located at '/u01/app/Oracle_Home/wlsserver/server/lib/DemoTrust.jks'. At the bottom, there are 'Save' and 'Cancel' buttons.

- For **Keystores**, select **Custom Identity and Custom Trust**.

- Select **Save**.

Figure 43: Configure Identity/Trust Store File – Keystores – Select Custom Identify and Custom Trust

This screenshot is similar to Figure 42 but with a key difference: the 'Keystores:' dropdown menu now shows 'Custom Identity and Custom Trust' instead of 'Demo Identity and Demo Trust', with a green box highlighting the dropdown. The rest of the interface, including the tabs and sections, remains the same.

6. Modify the setting under the **Keystores** tab as illustrated in the figure below. The *Custom Identity Keystore* and *Custom Trust Keystore* use the same file path to the keystore file copied to the Domain “security” directory:
`(DOMAIN_HOME)/security/[proxy_fqdn].jks`.

Figure 44: Configure Identity/Trust Store File – Modify Keystore Settings

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar displays the 'Domain Structure' for 'encl' domain, including Environment, Servers, Clusters, Coherence Clusters, Machines, Virtual Hosts, Work Managers, Startup and Shutdown Classes, Deployments, Services, Security Realms, Interoperability, and Diagnostics. The right panel is titled 'Settings for encl' and has tabs for Configuration, Protocols, Logging, Debug, Monitoring, Control, Deployments, Services, Security, Notes, Health Monitoring, Server Start, Web Services, and Coherence. The 'Configuration' tab is selected. Under the 'Keystores' tab, there are sections for 'Identity' and 'Trust'. In the 'Identity' section, the 'Custom Identity Keystore' is set to '/u01/app/Oracle_Home/l/' and the 'Custom Identity Keystore Type' is 'JKS'. In the 'Trust' section, the 'Custom Trust Keystore' is set to 'xappdev1.aac.va.gov.jks' and the 'Custom Trust Keystore Type' is 'JKS'. A 'Save' button is located at the bottom of the form.

7. Modify the setting under the **SSL** tab as illustrated in the figure below. For the *Private Key Alias*, enter **[proxy_fqdn]**.
8. Enter and confirm the *Private Key Passphrase*.
9. Select **Save**.

Figure 45: Configure Identity/Trust Store File – Modify SSL Settings

The screenshot shows the Oracle WebLogic Server Administration Console interface. The title bar reads "ORACLE WebLogic Server Administration Console 12c". The top menu includes "Home", "Log Out", "Preferences", "Record", "Help", "Welcome, weblogic", and "Connected to: envdomain1". The left sidebar has sections like "Change Center", "Domain Structure" (listing "endomain1" with sub-nodes like "Environment", "Clusters", "Machines", etc.), "How do I...", and "System Status" (showing "Health of Running Servers" with counts for Failed (0), Critical (0), Overloaded (0), Warning (0), and OK (3)). The main content area is titled "Settings for env1" and has tabs for Configuration, Protocols, Logging, Debug, Monitoring, Control, Deployments, Services, Security, and Notes. The "SSL" tab is active. Below it are sub-tabs: General, Cluster, Services, Keystores, SSL (which is highlighted in blue), Federation Services, Deployment, Migration, Tuning, and Overload. A "Save" button is located at the bottom of the main content area. The central part of the screen displays configuration details for SSL settings, including fields for "Identity and Trust Locations", "Identity", "Private Key Location", "Private Key Alias" (set to "vaauuserxappdev1.aac.va"), "Private Key Passphrase", "Confirm Private Key Passphrase", "Certificate Location", and "Trusted Certificate Authorities". Each field has a corresponding "More Info..." link.

10. Navigate to *Servers*, and then select the **erx2** link to access the server configuration page in the **Administration Console**.
11. Repeat the Keystore configuration steps for **erx2** as described earlier in this section for **erx1**.

Figure 46: Configure Identity/Trust Store File – Managed Server 2 Configuration

Name	Type	Cluster	Machine	State	Health	Listen Port
AdminServer(admin)	Configured		machine1	RUNNING	OK	7001
erx1	Configured	dev1	machine1	SHUTDOWN	Not reachable	8001
erx2	Configured	dev1	machine2	SHUTDOWN	Not reachable	8001

12. Navigate to *Servers*, and then select the **AdminServer(admin)** hyperlink to access the server configuration page.
13. Repeat the Keystore configuration steps for **AdminServer(admin)** as described earlier in this section for **erx1**.

Figure 47: Configure Identity/Trust Store File – Admin Server Configuration

Name	Type	Cluster	Machine	State	Health	Listen Port
AdminServer(admin)	Configured		machine1	RUNNING	OK	7001
erx1	Configured	dev1	machine1	SHUTDOWN	Not reachable	8001
erx2	Configured	dev1	machine2	SHUTDOWN	Not reachable	8001

14. Navigate to *Servers*, and then select the **AdminServer(admin)** hyperlink to access the server configuration page.

Figure 48: Configure Identity/Trust Store File – Admin Server Configuration

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar has a tree view of the domain structure under 'erxdomain1'. The 'Servers' node is expanded, showing 'Clusters', 'Coherence Clusters', 'Machines', 'Virtual Hosts', 'Work Managers', 'Startup and Shutdown Classes', and 'Deployments'. Below this is a 'How do I...' section with links for creating managed servers, cloning servers, deleting managed servers, and deleting the administration server.

The main content area is titled 'Summary of Servers' and contains a table of servers. The table has columns: Name, Type, Cluster, Machine, State, Health, and Listen Port. There are three rows:

Name	Type	Cluster	Machine	State	Health	Listen Port
AdminServer(admin)	Configured		machine1	RUNNING	OK	7001
erx1	Configured	dev1	machine1	SHUTDOWN	Not reachable	8001
erx2	Configured	dev1	machine2	SHUTDOWN	Not reachable	8001

15. Under Configuration and General tabs:

- a. Check **Listen Port Enabled**
- b. Enter **Listen Port: 7001**
- c. Check **SSL Port Enabled**
- d. Enter **SSL Listen Port: 7002**
- e. Select **Save**.

Figure 49: Configure Identity/Trust Store File – Admin Server Configuration

The screenshot shows the Oracle WebLogic Server Administration Console interface. On the left, there's a navigation pane with sections like 'Domain Structure', 'How do I...', and 'System Status'. The main area is titled 'Settings for AdminServer' under the 'General' tab. It includes fields for 'Name' (AdminServer), 'Template' ((No value specified)), 'Machine' (machine1), 'Cluster' (Stand-Alone), 'Listen Address' (empty), 'Listen Port' (7001), 'SSL Listen Port' (7002), and checkboxes for 'Listen Port Enabled' and 'SSL Listen Port Enabled'. A 'Save' button is at the bottom.

4.8.1.13 Pack Domain on VM1

This section provides step-by-step instructions for packing the domain on VM1:

1. On VM1, stop the newly created domain.
2. In the session that is currently running “startWebLogic.sh”, enter <CTRL> C.
3. The log messages should indicate that the Admin Server “was shut down”.

NOTE: It may seem odd that we are immediately stopping the new domain, but some of the configuration is not written to the file system until the AdminServer is started for the first time.

4. Transfer the relevant configuration using the pack and unpack utilities.
5. On VM1, pack the domain configuration using the following commands. Remember to amend the DOMAIN_HOME environment variable and the -template_name parameter to match your domain.

```
$ mkdir /u01/templates  
$ chmod 777 /u01/templates  
$ $WLS_HOME/common/bin/pack.sh -managed=true -domain=$DOMAIN_HOME -  
template=/u01/templates/erxdomain1_template.jar -template_name=[domain] -  
log=/u01/templates/[domain]_template_pack.log
```

6. Copy the resulting jar file to VM2 under:
`/u01/templates`

4.8.1.14 Unpack Domain on VM2

On VM2, set temporary environment. Remember to amend the DOMAIN_HOME environment variable to match your domain:

```
$ export ORACLE_BASE=[ORACLE_BASE]  
$ export WLS_HOME=$ORACLE_BASE/wlserver  
$ export DOMAIN_HOME=$ORACLE_BASE/user_projects/domains/[domain]
```

Unpack the configuration on VM2. Remember to amend the DOMAIN_HOME environment variable to match your domain.

```
$ $WLS_HOME/common/bin/unpack.sh -domain=$DOMAIN_HOME -  
template=/u01/templates/[domain]_template.jar -  
log=/u01/templates/[domain]_template_unpack.log
```

4.8.1.15 Copy Identity/Trust Store Files on VM2

Copy the server identity key store to the WebLogic domain “security” directory on VM2:

```
$ cp /u01/certificates/[proxy_fqdn].jks $DOMAIN_HOME/security/[proxy_fqdn].jks
```

4.8.1.16 Enroll VM2

1. On VM1, restart the domain. Wait until it is fully started before continuing.

```
$ nohup $DOMAIN_HOME/bin/startWebLogic.sh 2>&1>  
$DOMAIN_HOME/servers/AdminServer/logs/AdminServer.out &
```

2. On VM2, start WLST.

```
$ $WLS_HOME/common/bin/wlst.sh
```

3. Connect to the administration server on VM1, enroll VM2, disconnect and exit WLST. Remember to amend the DOMAIN_HOME environment variable to match your domain.

```
> connect('weblogic', '#####', 't3s://[vm1_fqdn]:7002')
> nmEnroll('[DOMAIN_HOME]', '[DOMAIN_HOME]/nodemanager')
> disconnect()
> exit()
```

4. Check that the “\$ORACLE_BASE/domain-registry.xml” file contains an entry like the following. If it doesn't, add it manually.
`<domain location=" [DOMAIN_HOME] "/>`
5. Check that the “\$DOMAIN_HOME/nodemanager/nodemanager.domains” file contains an entry like the following. If it doesn't, add it manually.
`erxdomain1=[DOMAIN_HOME]`
6. If the node manager has not been started already on this server, start it now.
`$ nohup $DOMAIN_HOME/bin/startNodeManager.sh &`

4.8.1.17 Check Node Manager on Each WebLogic Machine

This section outlines the steps for checking that the node manager is reachable on each WebLogic machine.

1. Log in to the administration server (`http://[vm1_fqdn]:7001/console`).
2. In the *Domain Structure* tree, expand the *Environment* node and then select the *Machines* node.
3. In the right-hand pane, select on the first WebLogic machine (machine1).
4. Select the **Monitoring** tab. Be patient. This may take some time the first time it's done.
5. If the status is “Reachable”, everything is fine.
6. Repeat for the second WebLogic machine (machine2).

4.8.1.18 Create a Boot Identity File for Managed Servers

NOTE: This is a placeholder step that may be eliminated if the boot identity file is automatically copied over during the domain clone process.

On VM2, create a boot identity file for the domain if it doesn't exist:

```
$ mkdir -p $DOMAIN_HOME/servers/AdminServer/security
$ cat > $DOMAIN_HOME/servers/AdminServer/security/boot.properties
username=weblogic
password#####
<ctrl>d
```

NOTE: The above username and password will be encoded/encrypted after the first shutdown/startup cycle.

4.8.1.19 Deploy Test Application

This section outlines the steps for deploying the test application.

1. Start the node manager on all servers.
2. Create the deployments directory if it doesn't exist:
\$ mkdir -p /u01/deployments
3. Copy test application to the deployments directory:
\$ cp /u01/downloads/benefits.war /u01/deployments
4. Navigate to the *Deployments* page.

Figure 50: Deploy Test Application: Deployments Page

Name	Type	Cluster	Machine	State	Health	Listen Port
AdminServer(admin)	Configured		machine1	RUNNING	OK	7001
encl	Configured	dev1	machine1	SHUTDOWN	Not reachable	8001
encl2	Configured	dev1	machine2	SHUTDOWN	Not reachable	8001


5. From the *Deployments* page, select **Install**.

Figure 51: Deploy Test Application – Install

Name	State	Health	Type	Targets	Deployment Order
There are no items to display					


6. Install a new deployment of the test application using the WAR file as indicated in the figure below.
7. Select **Next**.

Figure 52: Deploy Test Application – WAR File




8. Accept the defaults for an application deployment. (The *Install this deployment as an application* radio button is marked.)
9. Select **Next**.

Figure 53: Deploy Test Application – Accept Default Application Deployment



10. Select the **All servers in the cluster** option under the “erx” cluster as the target for the deployment.
11. Select **Next**.


Figure 54: Deploy Test Application – Select Deployment Target



12. All of the values should appear as illustrated in the figure below.

13. Select **Next**.


Figure 55: Deploy Test Application – Verify Deployment Settings



14. Verify that all of the values appear as illustrated in the figure below.

15. Select **Finish**.

Figure 56: Deploy Test Application – Verify Deployment Settings (Finish)



16. The **Overview** tab should appear as illustrated in the figure below.

Figure 57: Deploy Test Application – Verify “benefits” Settings

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar displays the domain structure under 'erxdomain1' and various management links like 'Deploy Web applications', 'Configure Web applications', and 'Monitor Web applications and servlets'. The main content area is titled 'Settings for benefits' and contains the following configuration details:

Name:	benefits	The name of this application deployment. More Info...
Context Root:	benefits	The specific path at which this Web application is found by a servlet. More Info...
Path:	/u01/deployments/benefits.war	The path to the source of the deployable unit on the Administration Server. More Info...
Deployment Plan:	(no plan specified)	The path to the deployment plan document on the Administration Server. More Info...
Staging Mode:	(not specified)	Specifies whether an application's files are copied from a source on the Administration Server to the Managed Server's staging area during application preparation. More Info...
Plan Staging Mode:	(not specified)	Specifies whether a deployment plan's files are copied from a source on the Administration Server to the Managed Server's staging area during application preparation. More Info...
Security Model:	DDOnly	The security model specifies how this deployment should be secured. More Info...
Deployment Order:	100	An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup. More Info...
Deployment Principal Name:		A string value that indicates the principal that should be used when deploying the file or archive during startup and shutdown. This principal will be used to set the current subject when calling out into application code for interfaces such as ApplicationLifecycleListener. If no principal name is specified, then the anonymous principal will be used. More Info...

At the bottom, there is a 'Save' button and a 'Modules and Components' section showing one entry:

Name	Type
benefits	Web Application
Web Services	
None to display	

17. Navigate to the **Servers** page in the WebLogic console.

18. Select the **Control** tab.

19. Select **erx1** and **erx2** servers.

20. Select **Start**.

Figure 58: Deploy Test Application – Summary of Servers Table

Server	Machine	State	Status of Last Action
AdminServer(admin)	machine1	RUNNING	None
erx1	machine1	SHUTDOWN	None
erx2	machine2	SHUTDOWN	None

21. After a couple minutes, the state on the servers will change to **RUNNING**.


Figure 59: Deploy Test Application – Servers Running

Server	Machine	State	Status of Last Action
AdminServer(admin)	machine1	RUNNING	None
erx1	machine1	RUNNING	TASK COMPLETED
erx2	machine2	RUNNING	TASK COMPLETED

22. Open a web browser to [http://\[vm1_fqdn\]/benefits/](http://[vm1_fqdn]/benefits/).

23. The Dizzyworld Benefits application will display.

Figure 60: Deploy Test Application – Open Dizzyworld Benefits Application



24. Repeat Steps 22 and 23 with a Web browser pointed to [http://\[vm2_fqdn\]/benefits/](http://[vm2_fqdn]/benefits/).

25. Repeat Steps 22 and 23 with a Web browser pointed to [https://\[proxy_fqdn\]/benefits/](https://[proxy_fqdn]/benefits/).

26. Navigate to the **Servers** page in the WebLogic console.

27. Select the **Control** tab.

28. Select **erx1** and **erx2** servers.

29. Select **Shutdown**.

Figure 61: Deploy Test Application – Shutdown Servers

The screenshot shows the Oracle WebLogic Server Administration Console interface. The left sidebar is titled "Change Center" and includes sections for "View changes and restarts", "Domain Structure" (with "Servers" highlighted), and "How do I...". The main content area is titled "Summary of Servers" and has a "Control" tab selected. A message states: "Use this page to change the state of the servers in this WebLogic Server domain. Control operations on Managed Servers require starting the Node Manager. Starting Managed Servers in Standby mode requires the domain-wide administration port." Below this is a table titled "Servers (Filtered - More Columns Exist)". The table shows three servers: AdminServer(admin) in RUNNING state, and erx1 and erx2 in SHUTDOWN state. Buttons for "Start", "Resume", "Suspend", "Shutdown", and "Restart SSL" are available for each server. The "erx1" and "erx2" rows have checkboxes checked, indicating they are selected for shutdown.

Server	Machine	State	Status of Last Action
AdminServer(admin)	machine1	RUNNING	None
erx1	machine1	SHUTDOWN	None
erx2	machine2	SHUTDOWN	None

4.8.1.20 Configure JPA for Domain on VM2

On VM2, edit setDomainEnv.sh script to add JPA modules via PRE_CLASSPATH:

```
$ cd $DOMAIN_HOME/bin  
$ cp setDomainEnv.sh setDomainEnv_orig.sh  
$ vi setDomainEnv.sh
```

Add the following two lines after the first line in the script:

```
PRE_CLASSPATH=[ORACLE_BASE]/oracle_common/modules/javax.persistence_2.1.jar:[WLS_HOME]/modules/com.oracle.weblogic.jpa21support_1.0.0.0_2-1.jar  
export PRE_CLASSPATH
```

Enter :wq to save the file and exit vi.

4.8.1.21 Install VistaLink on VM1

This section outlines the steps for installing VistaLink on VM1:

1. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Create a downloads directory if it doesn't exist:

```
$ mkdir -p /u01/downloads
```

3. Download vljConnector-1.5.0.028.jar, vljFoundationsLib-1.6.0.28.jar, log4j-1.2.17.jar and COMMON_vistalink_config_YYYYMMDD.zip to the downloads directory:

Download from AITC IEP eRx Downloads directory

4. Create Deployments/VistaLink directory if it doesn't exist:

```
$ mkdir -p /u01/downloads/vistalink
```

5. Download COMMON_vistalink_config_YYYYMMDD.zip to the Deployments/VistaLink directory:

Download from AITC IEP eRx Deployments/VistaLink directory

6. Unpack COMMON_vistalink_config_YYYYMMDD.zip file into DOMAIN_HOME:

```
$ cd $DOMAIN_HOME  
$ unzip /u01/deployments/vistalink/COMMON_vistalink_config_YYYYMMDD.zip
```

7. Modify configureVistaLink.sh (**Production environment only**):

```
$ vi $DOMAIN_HOME/bin/startWeblogic.sh
```

Add the following line to the bottom of the file:

```
export JAVA_OPTIONS="${JAVA_OPTIONS} -Dgov.va.med.environment.production=true"
```

8. Modify the Domain Startup script (startWebLogic.sh):

```
$ vi $DOMAIN_HOME/bin/startWeblogic.sh
```

9. Add call to configureVistaLink.sh after the setDomainEnv.sh call as shown:

```
. ${DOMAIN_HOME}/bin/setDomainEnv.sh $*  
. ${DOMAIN_HOME}/bin/configureVistaLink.sh $*
```

10. Modify the nodemanager.properties file:

```
$ vi $DOMAIN_HOME/nodemanager/nodemanager.properties
```

11. Ensure StartScriptEnabled=true:

```
StartScriptEnabled=true
```

4.8.1.22 Configure VistALink on VM1

1. Create Deployments/VistaLink directory if it doesn't exist:

```
$ mkdir -p /u01/downloads/vistalink
```

2. Download VistALink configuration zip file for the environment:

```
Download from AITC IEP eRx Deployments/VistaLink directory
```

3. Unzip VistALink configuration files for the environment:

```
$ cd $DOMAIN_HOME  
$ unzip /u01/deployments/vistalink/[ENV]_vistalink_config_YYYYMMDD.zip
```

4.8.1.23 Install VistALink on VM2

This section outlines the steps for installing VistALink on VM2:

1. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Create downloads directory if it doesn't exist:

```
$ mkdir -p /u01/downloads
```

3. Download vljConnector-1.5.0.028.jar, vljFoundationsLib-1.6.0.28.jar, log4j-1.2.17.jar and COMMON_vistalink_config_YYYYMMDD.zip to the downloads directory:

```
Download from AITC IEP eRx Downloads directory
```

4. Create Deployments/VistaLink directory if it doesn't exist:

```
$ mkdir -p /u01/downloads/vistalink
```

5. Download COMMON_vistalink_config_YYYYMMDD.zip to the Deployments/VistaLink directory:

```
Download from AITC IEP eRx Deployments/VistaLink directory
```

6. Unpack COMMON_vistalink_config_YYYYMMDD.zip file into DOMAIN_HOME:

```
$ cd $DOMAIN_HOME  
$ unzip /u01/deployments/vistalink/COMMON_vistalink_config_YYYYMMDD.zip
```

7. Modify configureVistaLink.sh (**Production environment only**):

```
$ vi $DOMAIN_HOME/bin/startWeblogic.sh
```

Add the following line to the bottom of the file:

```
export JAVA_OPTIONS="${JAVA_OPTIONS} -Dgov.va.med.environment.production=true"
```

8. Modify the Domain Startup script (startWebLogic.sh):

```
$ vi $DOMAIN_HOME/bin/startWeblogic.sh
```

9. Add call to configureVistalink.sh after the setDomainEnv.sh call as shown:

```
. ${DOMAIN_HOME}/bin/setDomainEnv.sh $*  
. ${DOMAIN_HOME}/bin/configureVistaLink.sh $*
```

10. Modify the nodemanager.properties file:

```
$ vi $DOMAIN_HOME/nodemanager/nodemanager.properties
```

11. Ensure StartScriptEnabled=true:

```
StartScriptEnabled=true
```

4.8.1.24 Configure VistALink on VM2

1. Create Deployments/VistaLink directory if it doesn't exist:

```
$ mkdir -p /u01/downloads/vistalink
```

2. Download VistALink configuration zip file for the environment:

```
Download from AITC IEP eRx Deployments/VistaLink directory
```

3. Unzip VistALink configuration files for the environment:

```
$ cd $DOMAIN_HOME  
$ unzip /u01/deployments/vistalink/[ENV]_vistalink_config_YYYYMMDD.zip
```

4.8.1.25 Stop and start Node Manager and Domain on VM1, VM2

This section outlines the steps for starting the node manager on the first WebLogic machine:

1. Stop the new domain on the VM1.

```
$ $DOMAIN_HOME/bin/stopWebLogic.sh
```

2. On VM1 stop the node manager.

```
$ $DOMAIN_HOME/bin/stopNodeManager.sh
```

3. On VM1, start the node manager.

```
$ DOMAIN_HOME/bin/startNodeManager.sh
```

4. On VM2 stop the node manager.

```
$ $DOMAIN_HOME/bin/stopNodeManager.sh
```

5. On VM2, start the node manager.

```
$ DOMAIN_HOME/bin/startNodeManager.sh
```

6. Start the domain on VM1.

```
$ $DOMAIN_HOME/bin/startWebLogic.sh
```

7. Wait for the **RUNNING** state before proceeding.

4.8.1.26 Deploy VistA Link Libraries

This section provides step-by-step instructions for deploying VistA Link Connector:

1. Navigate to the *Deployments* page.
2. From the *Deployments* screen, select **Install**.


Figure 62: Deploy VistA Link Connector – Deployments

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar, titled 'Domain Structure', shows a tree view of the domain 'erxdomain2' with various components like Environment, Servers, Clusters, and Deployments. The 'Deployments' node is currently selected. The main content area is titled 'Summary of Deployments' and contains a table of deployed applications. The table has columns for Name, State, Health, Type, Targets, and Deployment Order. One application, 'benefits', is listed as a Web Application targeted to 'dev1' with a deployment order of 100. There are buttons for Install, Update, Delete, Start, and Stop.

Name	State	Health	Type	Targets	Deployment Order
benefits	New		Web Application	dev1	100


3. Enter *Path*: /u01/downloads
4. Install a new deployment of **log4j-1.2.17.jar** by selecting the jar file as indicated, and then select **Next**.

Figure 63: Deploy Vista Link Connector – Select log4j Library to deploy



5. Select **All servers in the cluster** as the target for the deployment, and then select **Next**.


Figure 64: Deploy VistA Link Connector – Select Deployment Targets



6. All of the values should appear as illustrated in the figure below.

7. Select **Next**.


Figure 65: Deploy VistA Link Connector – Summary of Deployments Verification 1



8. Verify that all of the values appear as illustrated in the figure below.

9. Select **Finish**.

Figure 66: Deploy VistA Link Connector – Summary of Deployments Verification 2



10. The **Deployment Configuration** screen should appear as illustrated in the below figure.
11. Enter *Deployment Order: 1*
12. Select **Save**.

Figure 67: Deploy Vista Link Connector – Deployment Configuration Screen

The screenshot shows the Oracle WebLogic Server Administration Console interface. The left sidebar displays the 'Domain Structure' for 'erxdomain2', listing various server components like Environment, Servers, Clusters, and Deployments. The main content area is titled 'Settings for log4j-1' under the 'Overview' tab. It contains fields for 'Name' (log4j-1), 'Path' (/u01/downloads/log4j-1.2.17.jar), 'Staging Mode' (not specified), and 'Deployment Order' (set to 1). A 'Save' button is located at the bottom of this section. Below it, a table titled 'Applications that reference this Library' shows no items. At the bottom of the page, there is a footer with copyright information.

Name	Type
There are no items to display	

WebLogic Server Version: 12.1.3.0.0
Copyright (c) 1996-2014, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

13. Navigate to the *Deployments* page.
14. From the *Deployments* screen, select **Install**.


Figure 68: Deploy VistA Link Connector – Deployments

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar, titled 'Domain Structure', lists various components under 'exdomain2'. The 'Deployments' node is expanded, showing two entries: 'benefits' and 'log4j-1'. The right panel, titled 'Summary of Deployments', contains a table with the following data:

Name	State	Health	Type	Targets	Deployment Order
benefits	New		Web Application	dev1	100
log4j-1	New		Library	dev1	1


15. Enter *Path*: /u01/downloads
16. Install a new deployment of **vljConnector-1.6.0.028.jar** by selecting the jar file as indicated, and then select **Next**.

Figure 69: Deploy Vista Link Connector – Select vljConnector-1.6.0.028.jar Library to deploy



17. Select **All servers in the cluster** as the target for the deployment, and then select **Next**.


Figure 70: Deploy VistA Link Connector – Select Deployment Targets



18. All of the values should appear as illustrated in the figure below.

19. Select **Next**.


Figure 71: Deploy VistA Link Connector – Summary of Deployments Verification 1



20. Verify that all of the values appear as illustrated in the figure below.

21. Select **Finish**.

Figure 72: Deploy VistA Link Connector – Summary of Deployments Verification 2



22. The **Deployment Configuration** screen should appear as illustrated in the below figure.
23. Enter *Deployment Order: 1*
24. Select **Save**.

Figure 73: Deploy Vista Link Connector – Deployment Configuration Screen

The screenshot shows the Oracle WebLogic Server Administration Console interface. The left sidebar displays the domain structure under 'Domain Structure' for 'endomain2'. The main content area is titled 'Settings for vljConnector(1.6,1.6)' and shows the configuration for this Java EE library. Key fields include:

- Name:** vljConnector
- Specification Version:** 1.6
- Implementation Version:** 1.6
- Path:** / u01/ downloads/ vljConnector-1. 6. 0. 028.
- Staging Mode:** (not specified)
- Deployment Order:** 1
- Deployment Principal Name:** (empty field)

At the bottom, there is a 'Save' button and a section titled 'Applications that reference this Library' which is currently empty.

25. Navigate to the *Deployments* page.
26. From the *Deployments* screen, select **Install**.


Figure 74: Deploy VistA Link Connector – Deployments

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar, titled 'Change Center', includes sections for 'View changes and restarts' (warning: configuration editing is enabled), 'Domain Structure' (showing 'exdomain2' with various sub-nodes like Environment, Servers, Clusters, etc.), 'Deployments' (selected), Services, Security Realms, Interoperability, and Diagnostics. Below these are 'How do I...' and 'System Status' links. The main content area is titled 'Summary of Deployments' under the 'Control' tab. It contains a brief description of the page's purpose and instructions to click 'Install' to add new applications. A table lists the deployed applications:

Name	State	Health	Type	Targets	Deployment Order
benefits	New		Web Application	dev1	100
log4j-1	New		Library	dev1	1
vljConnector(1.6,1.6)	New		Library	dev1	1


27. Enter Path: /u01/downloads
28. Install a new deployment of **vljFoundationsLib-1.6.0.028.jar** by selecting the jar file as indicated, and then select **Next**.

Figure 75: Deploy Vista Link Connector – Select vljFoundationsLib to deploy



29. Select **All servers in the cluster** as the target for the deployment, and then select **Next**.


Figure 76: Deploy Vista Link Connector – Select Deployment Targets



30. All of the values should appear as illustrated in the figure below.

31. Select **Next**.


Figure 77: Deploy VistA Link Connector – Summary of Deployments Verification 1



32. Verify that all of the values appear as illustrated in the figure below.

33. Select **Finish**.

Figure 78: Deploy VistA Link Connector – Summary of Deployments Verification 2



34. The **Deployment Configuration** screen should appear as illustrated in the below figure.
35. Enter *Deployment Order: 1*
36. Select **Save**.

Figure 79: Deploy Vista Link Connector – Deployment Configuration Screen


The screenshot shows the Oracle WebLogic Server Administration Console interface. The left sidebar displays the 'Domain Structure' for 'exdomain2', including Environment, Deployments, Services, Security Realms, Interoperability, and Diagnostics. The main content area is titled 'Settings for vljFoundationsLib(1.6,1.6)'. It includes tabs for Overview, Targets, and Notes, with 'Overview' selected. A 'Save' button is located at the top right of the configuration area. The configuration details are as follows:

- Name:** vljFoundationsLib
- Specification Version:** 1.6
- Implementation Version:** 1.6
- Path:** /u01/downloads/vljFoundationsLib-1.6.0.028.jar
- Staging Mode:** (not specified)
- Deployment Order:** 1
- Deployment Principal Name:** (empty field)

Below the configuration area, there is a section titled 'Applications that reference this Library' which is currently empty, displaying the message 'There are no items to display'.

37. Navigate to the *Deployments* page.
 38. From the *Deployments* screen, select **Install**.

Figure 80: Deploy VistA Link Connector – Deployments




The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar shows the domain structure for 'exdomain2' under 'Environment'. The 'Deployments' node is expanded, showing various application and library modules. The main content area is titled 'Summary of Deployments' and contains a table of deployed items. The table has columns for Name, State, Health, Type, Targets, and Deployment Order. The 'vljConnector(1.6,1.6)' entry is highlighted.

Name	State	Health	Type	Targets	Deployment Order
benefits	New		Web Application	dev1	100
log4j-1	New		Library	dev1	1
vljConnector(1.6,1.6)	New		Library	dev1	1
vljFoundationsLib(1.6,1.6)	New		Library	dev1	1


39. Enter *Path*: /u01/downloads
40. Install a new deployment of **VistaLinkConsole-1.6.0.0.28.ear** by selecting file as indicated, and then select **Next**.

Figure 81: Deploy VistaA Link Connector – Select VistaLinkConsole to deploy




41. Select **All servers in the cluster** as the target for the deployment, and then select **Next**.

Figure 82: Deploy VistA Link Connector – Select Deployment Targets



42. Select **All servers in the cluster** as the target for the deployment, and then select **Next**.

Figure 83: Deploy VistA Link Connector – Select Deployment Targets



43. All of the values should appear as illustrated in the figure below.

44. Select **Next**.


Figure 84: Deploy Vista Link Connector – Summary of Deployments Verification 1

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. On the left, there's a sidebar with 'Change Center' and 'View changes and restarts'. Below that is the 'Domain Structure' tree, which includes 'Environment', 'Deployments', 'Services', 'Security Realms', 'Interoperability', and 'Diagnostics'. At the bottom of the sidebar are 'How do I...' and 'System Status' links. The main area is titled 'Install Application Assistant' and shows the 'Optional Settings' step. It has tabs for 'General', 'Security', 'Source Accessibility', and 'Plan Source Accessibility'. Under 'General', the deployment name is set to 'VistaLinkConsole-1.6.0.028'. Under 'Security', the radio button for 'DD Only: Use only roles and policies that are defined in the deployment descriptors.' is selected. Under 'Source Accessibility', the radio button for 'Use the defaults defined by the deployment's targets' is selected. Under 'Plan Source Accessibility', the radio button for 'Use the same accessibility as the application' is selected. At the bottom of the dialog are 'Back', 'Next', 'Finish', and 'Cancel' buttons. The status bar at the bottom of the browser window shows 'Welcome, weblogic' and 'Connected to: exdomain1'.

45. Verify that all of the values appear as illustrated in the figure below.


46. Select **Finish**.

Figure 85: Deploy VistA Link Connector – Summary of Deployments Verification 2



47. The **Deployment Configuration** screen should appear as illustrated in the below figure.
48. Enter *Deployment Order: 1*
49. Select **Save**.

Figure 86: Deploy VistaLink Connector – Deployment Configuration Screen



4.8.1.27 Deploy VistaLink Adapters

This section provides step-by-step instructions for deploying VistaLink Adapter.

1. The WebLogic Administrator stops the VM1 managed server, per section: 7.2.2, step **Error! Reference source not found.**
2. The System Administrator executes the eRx/IEP Configurator script containing adapter configuration on VM1, menu options 1, 2 and 3.
3. The WebLogic Administrator will start the VM1 managed server, per section 7.1.2.
4. The WebLogic Administrator stops the VM2 managed server, per section: 7.2.2, step **Error! Reference source not found.**
5. The System Administrator executes the eRx/IEP Configurator script containing adapter configuration on VM2, menu options 1, 2 and 3.
6. The WebLogic Administrator will start the VM2 managed server, per section 7.1.2.
7. The WebLogic navigates to the *Deployments* screen and selects **Install**.


Figure 87: Deploy VistA Link Connector – Deployments

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar, titled 'Domain Structure', lists various components under 'exdomain2'. The 'Deployments' node is selected and expanded. The main content area is titled 'Summary of Deployments' and contains a table of deployed applications.

Name	State	Health	Type	Targets	Deployment Order
benefits	New		Web Application	dev1	100


8. Enter *Path*: **[DOMAIN_HOME]/vistalink/resource_adapters, .**
9. Select the desired vljXXX_adapter to be installed, and then select **Next**.

Figure 88: Deploy VistA Link Connector – Select vlxxx_adapter to install




10. Select **Install this deployment as an application** as the target for the deployment, and then select **Next**.

Figure 89: Deploy VistA Link Connector – Select Deployment Type



11. Select **All servers in the cluster** as the target for the deployment, and then select **Next**.


Figure 90: Deploy VistA Link Connector – Select Deployment Targets



12. All of the values should appear as illustrated in the figure below.

13. Select **Next**.


Figure 91: Deploy VistA Link Connector – Adapter Optional Settings



14. Verify that all of the values appear as illustrated in the figure below.

15. Select **Finish**.

Figure 92: Deploy VistA Link Connector – Finish Adapter Installation



16. Navigate to Deployments, select the **vljXXX_adapter**, select Start > Servicing all Requests.

Figure 93: Deploy VistA Link Connector – Start Resource Adapter

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar displays the 'Domain Structure' for 'erxdomain1' under the 'Environments' section. The 'Deployments' section is expanded, showing various applications and adapters. A 'How do I...' panel on the left provides links for deploying enterprise applications, configuring them, updating, starting/stopping, monitoring, deploying EJB modules, and installing Web applications.

The main content area is titled 'Summary of Deployments' and contains a table of deployed applications. The table includes columns for Name, State, Health, Type, Targets, and Deployment Order. The 'vlj984_adapter' entry is selected, indicated by a checked checkbox in the first column and highlighted in blue. Other entries include 'dev-utils', 'INB_ERX-3.1.0.004', 'INB_ERX_UI-3.1.0.004', 'log4j-1', 'vlj500n_adapter', 'vlj994_adapter', and 'vljFoundationsLib(1.6,1.6)'. The status bar at the bottom of the table area shows 'Servicing all requests'.

Name	State	Health	Type	Targets	Deployment Order
dev-utils	Active	✓ OK	Web Application	dev1	100
INB_ERX-3.1.0.004	Active	✓ OK	Enterprise Application	dev1	100
INB_ERX_UI-3.1.0.004	Active	✓ OK	Enterprise Application	dev1	100
log4j-1	Active		Library	dev1	1
vlj500n_adapter	Active	✓ OK	Resource Adapter	dev1	100
vlj984_adapter	Installed	✓ OK	Resource Adapter	dev1	100
vlj994_adapter	Active	✓ OK	Resource Adapter	dev1	100
vljFoundationsLib(1.6,1.6)	Active		Library	dev1	1

4.8.2 Inbound eRx Application Installation

The following sections describe the steps to install and configure the Inbound eRx application. Most activities are to be performed by the WebLogic Administrator.

4.8.2.1 Install Inbound eRx Application

1. Shut down WebLogic (refer to Sections 4.8.2.3 and 4.8.2.4).
2. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```
3. Create the downloads directory if it doesn't exist:

```
$ mkdir -p /u01/downloads
```
4. Download Inbound eRx application to the downloads directory.
Download from AITC IEP eRx Downloads directory
5. Create the deployments directory if it doesn't exist:

```
$ mkdir -p /u01/deployments
```
6. Copy the application EAR to the deployments directory.
Download from AITC IEP eRx Downloads directory
7. Access the WebLogic Admin Console by directing a browser to:
[https://\[vm1_fqdn\]:7002/console/](https://[vm1_fqdn]:7002/console/) and log in with the **weblogic** account.
8. Navigate to the **Servers** page.
9. From the **Administration Console > Servers** page, select the **erx1** link to configure the server.

Figure 94: Install Inbound eRx Application – Configure Servers

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar displays the 'Domain Structure' under 'erxdomain1' with 'Servers' highlighted. The main content area is titled 'Summary of Servers' and shows a table of managed servers:

Server	Machine	State	Status of Last Action
AdminServer(admin)	machine1	RUNNING	None
erx1	machine1	SHUTDOWN	None
erx2	machine2	SHUTDOWN	None

10. The server configuration screen should appear as shown in the figure below.
11. Inspect the settings under the **General** tab. The *Listen Address* should be **[vm1_fqdn]**. The non-secure listening port (*Listen Port Enabled*) should be enabled and set to port **8001** (*Listen Port*). The secure listening port should be disabled (*SSL Listen Port Enabled*). These ports need to be consistent with the Apache Load Balancer/Proxy and local firewall settings.

Figure 95: Install Inbound eRx Application – Verify Server Settings

The screenshot shows the Oracle WebLogic Server Administration Console interface. On the left, there's a navigation sidebar with sections like 'Domain Structure' (including Environment, Servers, Clusters, Coherence Clusters, Machines, Virtual Hosts, Work Managers, and Startup and Shutdown Classes), 'Deployments' (Services, Messaging, Data Sources, Persistent Stores), and 'How do I...' (Configure default network connections, Create and configure machines, Configure clusters, Start and stop servers, Configure WLDF diagnostic volume, Apply a server template). Below that is a 'System Status' section showing 'Health of Running Servers' with counts for Failed (0), Critical (0), Overloaded (0), Warning (0), and OK (3). The main content area is titled 'Settings for ex1' and has tabs for Configuration, Protocols, Logging, Debug, Monitoring, Control, Deployments, Services, Security, Notes, Health Monitoring, Server Start, Web Services, and Coherence. The 'General' tab is selected. The configuration details are as follows:

- Name:** ex1
- Template:** (No value specified) [Change](#)
- Machine:** machine1
- Cluster:** dev1
- Listen Address:** vaauuserxappdev1.aac.va
- Listen Port Enabled** (checkbox checked)
- Listen Port:** 8001
- SSL Listen Port Enabled** (checkbox unchecked)
- SSL Listen Port:** 7002
- Client Cert Proxy Enabled** (checkbox unchecked)
- Java Compiler:** javac
- Diagnostic Volume:** Low

At the bottom of the configuration panel, there's a 'Save' button.

12. Review the setting under the **Keystores** tab as illustrated in the figure below. Verify the **Keystores** option is set to **Custom Identity and Custom Trust**, and that the fields under the **Identity** and **Trust** sections are filled with the same corresponding values.

Figure 96: Install Inbound eRx Application – Verify General & Keystore Settings

The screenshot shows the Oracle WebLogic Server Administration Console interface. The left sidebar displays the 'Domain Structure' for 'Chapter33IDP' and a 'System Status' section showing 2 OK servers. The main content area is titled 'Settings for OpenAMServer' and has tabs for Configuration, Protocols, Logging, Debug, Monitoring, Control, Deployments, Services, Security, and Notes. The 'Keystores' tab is selected. A sub-tab bar includes General, Cluster, Services, Keystores, SSL, Federation Services, Deployment, Migration, Tuning, Overload, and Health Monitoring. Under the Keystores tab, there is a note about keystores ensuring secure storage and management of private keys and trusted certificate authorities (CAs). The 'Keystores' section shows 'Custom Identity and Custom Trust' selected. Below this, the 'Identity' section contains fields for 'Custom Identity Keystore' (set to '/u01/weblogic/oracle_home/u'), 'Custom Identity Keystore Type' (set to 'JKS'), and 'Custom Identity Keystore Passphrase'. The 'Trust' section contains fields for 'Custom Trust Keystore' (set to '/u01/weblogic/oracle_home/u'), 'Custom Trust Keystore Type' (set to 'JKS'), and 'Custom Trust Keystore Passphrase'. A 'Save' button is located at the bottom of the form.

13. Verify the settings under the **SSL** tab. The *Private Key Alias* should be the Fully Qualified Domain Name of the server, and the *Passphrase* is xxxxxxxx.

Figure 97: Install Inbound eRx Application – Verify SSL Settings

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar displays the 'Domain Structure' for 'Chapter33IDP' and a 'System Status' section showing 'Health of Running Servers' with 0 Failed, 0 Critical, 0 Overloaded, 0 Warning, and 2 OK servers. The main content area is titled 'Settings for OpenAMServer' under the 'SSL' tab. It includes sections for 'Identity and Trust Locations', 'Identity', 'Private Key Location', 'Private Key Alias', 'Private Key Passphrase', 'Confirm Private Key Passphrase', 'Certificate Location', and 'Trusted Certificate Authorities'. A note at the top states: 'This page lets you view and define various Secure Sockets Layer (SSL) settings for this server instance. These settings help you to manage the security of message transmissions.' A 'Save' button is located at the bottom of the form.

14. Repeat the previous three steps for the **erx2** managed server to verify the *General Configuration*, *Keystores*, and *SSL* settings.

15. Navigate to the **Deployments** page.

16. From the **Deployments** page, select **Install**.

Figure 98: Install Inbound eRx Application – Summary of Deployments

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The left sidebar has a 'Domain Structure' tree with nodes like 'Environment', 'Deployments', 'Services', 'Security Realms', 'Interoperability', and 'Diagnostics'. A 'Change Center' panel says 'View changes and restarts' and 'Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.' Below it are 'How do I...' and 'System Status' buttons. The main content area is titled 'Summary of Deployments' with tabs for 'Control' (selected) and 'Monitoring'. It displays a table of deployed applications:


Name	State	Health	Type	Targets	Deployment Order
benefits	Active	OK	Web Application	dev1	100
log4j-1	Active	OK	Library	dev1	1
VistaLinkConsole-1.6.0.028	Active	OK	Enterprise Application	AdminServer	100
vlij442_adapter	Active	OK	Resource Adapter	dev1	100
vlij518_adapter	Active	OK	Resource Adapter	dev1	100
vlij983_adapter	Active	OK	Resource Adapter	dev1	100
vlijConnector(1.6,1.6)	Active	OK	Library	dev1	1
vlijFoundationsLib(1.6,1.6)	Active	OK	Library	dev1	1

At the bottom, there are 'Install', 'Update', 'Delete', 'Start', and 'Stop' buttons. The footer includes copyright information: 'WebLogic Server Version: 12.1.3.0.0', 'Copyright (c) 1996-2014, Oracle and/or its affiliates. All rights reserved.', and 'Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.' A status bar at the bottom right shows '100%'.

17. Install a new deployment of **INB_ERX-3.1.0.006.ear** using the .ear file as indicated in the figure below.


18. select **Next**.

Figure 99: Install Inbound eRx Application – Install New Deployment of INB_ERX



19. Accept the defaults for an application deployment.
20. Select **Next**.
21. Select the cluster and **All servers in the cluster** as the target for the deployment.
22. Select **Next**.

Figure 100: Install Inbound eRx Application – Select INB_ERX Deployment Targets



23. All of the values should appear as illustrated in the figure below.

24. Select **Next**.

Figure 101: Install Inbound eRx Application – Verify INB_ERX Deployment Settings






Figure 102: Install Inbound eRx Application – Verify INB_ERX Deployment Continued



25. All of the values should appear as illustrated in the figure below.

26. Select **Finish**.

Figure 103: Install Inbound eRx Application – Verify INB_ERX Deployment Settings (Finish)



27. The **Overview** tab should appear as illustrated in the figure below.


Figure 104: Install Inbound eRx Application – Verify INB_ERX Deployment Configuration Settings

The screenshot shows the Oracle WebLogic Server Administration Console interface. The title bar reads "ORACLE WebLogic Server Administration Console 12c". The left sidebar includes "Change Center", "View changes and restarts", "Domain Structure" (showing "endomain2" with "Environment", "Deployments", "Services", "Security Realms", "Interoperability", and "Diagnostics" nodes), "How do I...", and "System Status". The main content area is titled "Settings for INB_ERX-3.1.0.006" and has tabs for "Overview", "Deployment Plan", "Configuration", "Security", "Targets", "Control", "Testing", "Monitoring", and "Notes". The "Overview" tab is selected. It displays various deployment settings with their descriptions and "More Info..." links. Below these is a "Modules and Components" section with a table:

Name	Type
INB_ERX-3.1.0.006	Enterprise Application
EJBs	
None to display	
Modules	
/INB-ERX	Web Application
Web Services	
None to display	


28. Navigate to the **Deployments** page.
29. From the **Deployments** page, select **Install**.
30. Install a new deployment of **INB_ERX_UI-3.1.0.006.ear**, select the appropriate EAR file.
31. Select **Next**.

Figure 105: Install Inbound eRx Application – Install New Deployment of INB_ERX_UI



32. Accept the defaults for an application deployment.
33. Select **Next**.
34. Select the cluster and **All servers in the cluster** as the target for the deployment.
35. Select **Next**.


Figure 106: Install Inbound eRx Application – Select INB_ERX_UI Deployment Targets



36. All of the values should appear as illustrated in the figure below.

37. Select **Next**.


Figure 107: Install Inbound eRx Application – Verify INB_ERX_UI Deployment Settings



38. All of the values should appear as illustrated in the figure below.

39. Select **Finish**.

Figure 108: Install Inbound eRx Application – Verify INB_ERX_UI Deployment Settings (Finish)



40. The **Overview** tab should appear as illustrated in the figure below.

Figure 109: Install Inbound eRx Application – Verify INB_ERX_UI Deployment Configuration Settings

The screenshot shows the Oracle WebLogic Server Administration Console interface. The left sidebar displays the domain structure under 'Domain Structure' for 'endomain2'. The main content area is titled 'Settings for INB_ERX_UI-3.1.0.006' and shows the 'Overview' tab selected. The configuration details are as follows:

- Name:** INB_ERX_UI-3.1.0.006
- Path:** /u01/deployments/v.3.1.0.006/INB_ERX_UI-3.1.0.006.ear
- Deployment Plan:** (no plan specified)
- Staging Mode:** (not specified)
- Plan Staging Mode:** (not specified)
- Security Model:** DDOOnly
- Deployment Order:** 100
- Deployment Principal Name:** (empty field)

A note at the top of the configuration table states: "Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as Web applications and EJBs) that are contained in the enterprise application. Click on the name of the module to view and update its configuration."

The bottom section, 'Modules and Components', shows a table with one row:

Name	Type
INB_ERX_UI-3.1.0.006	Enterprise Application

41. Navigate to the **Servers** page in the WebLogic console.

42. Select the **Control** tab.

43. Select **erx1** and **erx2**, and then select **Start**.

Figure 110: Install Inbound eRx Application – Start erx Servers

Server	Machine	State	Status of Last Action
AdminServer(admin)	machine1	RUNNING	None
erx1	machine1	SHUTDOWN	None
erx2	machine2	SHUTDOWN	None

Figure 111: Install Inbound eRx Application – erx Servers Running

The screenshot shows the Oracle WebLogic Server Administration Console interface. The left sidebar contains a 'Domain Structure' tree for 'erxdomain1' under 'Environment', including 'Servers', 'Clusters', 'Coherence Clusters', 'Machines', 'Virtual Hosts', 'Work Managers', 'Startup and Shutdown Classes', 'Deployments', 'Services', 'Security Realms', 'Interoperability', and 'Diagnostics'. Below it is a 'How do I...' section with links for starting servers, managed servers, and clusters, as well as domain-wide administration. The main content area is titled 'Summary of Servers' with tabs for 'Configuration' and 'Control'. A message at the top states: 'A request has been sent to the Node Manager to start the selected servers.' The 'Control' tab is active, showing a table of servers:

<input type="checkbox"/>	Server	Machine	State	Status of Last Action
<input type="checkbox"/>	AdminServer(admin)	machine1	RUNNING	None
<input type="checkbox"/>	erx1	machine1	RUNNING	TASK COMPLETED
<input type="checkbox"/>	erx2	machine2	RUNNING	TASK COMPLETED

At the bottom of the page, there is a 'System Status' section titled 'Health of Running Servers' with a legend: Failed (0), Critical (0), Overloaded (0), Warning (0), and OK (1). The status bar at the bottom indicates: 'WebLogic Server Version: 12.1.3.0.0', 'Copyright (c) 1996-2014, Oracle and/or its affiliates. All rights reserved.', and 'Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.'

4.8.2.2 Create Startup/Shutdown Scripts

This section outlines the steps for creating startup/shutdown scripts:

1. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Create startup scripts with the following commands:

```
$ cat > startNodemanager_[domain].sh
tmp_domain_home="[$DOMAIN_HOME]"
cp ${tmp_domain_home}/nodemanager/nodemanager.log
${tmp_domain_home}/nodemanager/nodemanager_old.log
cat /dev/null > ${tmp_domain_home}/nodemanager/nodemanager.log
nohup ${tmp_domain_home}/bin/startNodeManager.sh 2>&1>
${tmp_domain_home}/nodemanager/nm.out &
<ctrl>d

$ cat > startWebLogic_[domain].sh
tmp_domain_home="[$DOMAIN_HOME]"
cp ${tmp_domain_home}/servers/AdminServer/logs/AdminServer.log
${tmp_domain_home}/servers/AdminServer/logs/AdminServer_old.log
cat /dev/null > ${tmp_domain_home}/servers/AdminServer/logs/AdminServer.log
nohup ${tmp_domain_home}/bin/startWebLogic.sh 2>&1>
${tmp_domain_home}/servers/AdminServer/logs/AdminServer.out &
<ctrl>d

$ cat > stopNodemanager_[domain].sh
tmp_domain_home="[$DOMAIN_HOME]"
${tmp_domain_home}/bin/stopNodeManager.sh
<ctrl>d

$ cat > stopWebLogic_[domain].sh
tmp_domain_home="[$DOMAIN_HOME]"
${tmp_domain_home}/bin/stopWebLogic.sh
<ctrl>d
```

4.8.2.3 Shut Down Domain

The section provides the steps for shutting down the domain:

1. On VM1, log into Linux login and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Shut down the **Administration Console** with the following command:

```
$ ./stopWebLogic_[domain].sh
```

4.8.2.4 Shut Down Nodemangers

This sections outlines the steps for shutting down the nodemanagers:

1. On VM1, Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Shut down Nodemanager with the following command:

```
$ ./stopNodemanager_[domain].sh
```

3. On VM2, Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

4. Shut down Nodemanager with the following command:

```
$ ./stopNodemanager_[domain].sh
```

4.8.3 Pentaho Installation

The following sections describe the steps to install the WebLogic application server. Most activities are to be performed by the WebLogic Administrator.

4.8.3.1 Pentaho Software Installation

The section provides step-by-step guidance on the installing the Pentaho software:

1. Log into Linux and sudo su to the kettle account:

```
$ sudo su - kettle
```

2. Create downloads directory if it doesn't exist:

```
$ mkdir -p /u01/downloads
```

3. Download Pentaho Data Integration Community Edition 8.2 archive (pdi-ce-8.2.0.0-342.zip) to the downloads directory.

Download from AITC IEP eRx Downloads directory

4. Download INB_ERX Pentaho configuration zip archive for [ENV].

Download pdi-[env]_cfg_[yyyymmdd].zip from AITC IEP eRx Deployments directory

5. Create a pentaho directory if it doesn't exist:

```
$ mkdir -p /u01/app/pentaho
```

6. On VM1, unzip the Pentaho Data Integration Community Edition 8.2 archive to the pentaho master1 installation directory:

```
$ cd /u01/app/pentaho  
$ unzip /u01/downloads/pdi-ce-8.2.0.0-342.zip  
$ mv data-integration pdi-[env]master1
```

7. On VM1, unzip the Pentaho Data Integration Community Edition 8.2 archive to the pentaho slave1 installation directory:

```
$ cd /u01/app/pentaho  
$ unzip /u01/downloads/pdi-ce-8.2.0.0-342.zip  
$ mv data-integration pdi-[env]slave1
```

8. On VM1, unzip the Pentaho Data Integration Community Edition 8.2 archive to the pentaho slave2 installation directory:

```
$ cd /u01/app/pentaho  
$ unzip /u01/downloads/pdi-ce-8.2.0.0-342.zip  
$ mv data-integration pdi-[env]slave2
```

9. On VM2, unzip the Pentaho Data Integration Community Edition 8.2 archive to the pentaho slave3 installation directory:

```
$ cd /u01/app/pentaho  
$ unzip /u01/downloads/pdi-ce-8.2.0.0-342.zip  
$ mv data-integration pdi-[env]slave3
```

10. On VM2, unzip the Pentaho Data Integration Community Edition 8.2 archive to the pentaho slave4 installation directory:

```
$ cd /u01/app/pentaho  
$ unzip /u01/downloads/pdi-ce-8.2.0.0-342.zip  
$ mv data-integration pdi-[env]slave4
```

11. On VM2, unzip the Pentaho Data Integration Community Edition 8.2 archive to the pentaho slave5 installation directory:

```
$ cd /u01/app/pentaho  
$ unzip /u01/downloads/pdi-ce-8.2.0.0-342.zip  
$ mv data-integration pdi-[env]slave5
```

12. On VM1, unzip the environment specific configuration archive to the pentaho master1 installation directory:

```
$ cd /u01/app/pentaho/pdi-[env]master1
$ unzip /u01/downloads/pdi-[env]_cfg_[yyyymmdd].zip
```

13. On VM1, unzip the environment specific configuration archive to the pentaho slave1 installation directory:

```
$ cd /u01/app/pentaho/pdi-[env]slave1
$ unzip /u01/downloads/pdi-[env]_cfg_[yyyymmdd].zip
```

14. On VM1, unzip the environment specific configuration archive to the pentaho slave2 installation directory:

```
$ cd /u01/app/pentaho/pdi-[env]slave2
$ unzip /u01/downloads/pdi-[env]_cfg_[yyyymmdd].zip
```

15. On VM2, unzip the environment specific configuration archive to the pentaho slave3 installation directory:

```
$ cd /u01/app/pentaho/pdi-[env]slave3
$ unzip /u01/downloads/pdi-[env]_cfg_[yyyymmdd].zip
```

16. On VM2, unzip the environment specific configuration archive to the pentaho slave4 installation directory:

```
$ cd /u01/app/pentaho/pdi-[env]slave4
$ unzip /u01/downloads/pdi-[env]_cfg_[yyyymmdd].zip
```

17. On VM2, unzip the environment specific configuration archive to the pentaho slave5 installation directory:

```
$ cd /u01/app/pentaho/pdi-[env]slave5
$ unzip /u01/downloads/pdi-[env]_cfg_[yyyymmdd].zip
```

18. On the Master VM, create master1, slave1 and slave2 startup scripts in the ~kettle directory:

```
$ cd ~
$ cat > ~/startCarte[Env]Master1.sh
unset DISPLAY
export KETTLE_HOME=/u01/app/pentaho/pdi-[env]master1
datestamp=`date +%Y%m%d_%H%M%S`
export PENTAHO_DI_JAVA_OPTIONS="-Xms1024m -Xmx2048m -XX:MaxPermSize=256m"
${KETTLE_HOME}/carte.sh ${KETTLE_HOME}/pwd/[env]master1-8080.xml >
${KETTLE_HOME}/logs/[env]master1-8080_${datestamp}.out 2>&1 &
<ctrl>d
$ chmod 755 ~/startCarte[Env]Master1.sh

$ cat > ~/startCarte[Env]Slave1.sh
unset DISPLAY
export KETTLE_HOME=/u01/app/pentaho/pdi-[env]slave1
datestamp=`date +%Y%m%d_%H%M%S`
export PENTAHO_DI_JAVA_OPTIONS="-Xms1024m -Xmx3072m -XX:MaxPermSize=256m"
${KETTLE_HOME}/carte.sh ${KETTLE_HOME}/pwd/[env]slave1-8081.xml >
${KETTLE_HOME}/logs/[env]slave1-8081_${datestamp}.out 2>&1 &
<ctrl>d
$ chmod 755 ~/startCarte[Env]Slave1.sh

$ cat > ~/startCarte[Env]Slave2.sh
unset DISPLAY
export KETTLE_HOME=/u01/app/pentaho/pdi-[env]slave1
datestamp=`date +%Y%m%d_%H%M%S`
export PENTAHO_DI_JAVA_OPTIONS="-Xms1024m -Xmx3072m -XX:MaxPermSize=256m"
${KETTLE_HOME}/carte.sh ${KETTLE_HOME}/pwd/[env]slave2-8082.xml >
${KETTLE_HOME}/logs/[env]slave2-8082_${datestamp}.out 2>&1 &
<ctrl>d
$ chmod 755 ~/startCarte[Env]Slave2.sh
```

19. On the Master VM, create slave3, slave4 and slave5 startup script in the ~kettle directory:

```
$ cd ~
$ cat > ~/startCarte[Env]Slave3.sh
unset DISPLAY
export KETTLE_HOME=/u01/app/pentaho/pdi-[env]slave3
datestamp=`date +%Y%m%d_%H%M%S`
export PENTAHO_DI_JAVA_OPTIONS="-Xms1024m -Xmx3072m -XX:MaxPermSize=256m"
${KETTLE_HOME}/carte.sh ${KETTLE_HOME}/pwd/[env]slavefx3-8083.xml >
${KETTLE_HOME}/logs/[env]slave3-8083_${datestamp}.out 2>&1 &
<ctrlr>d
$ chmod 755 ~/startCarte[Env]Slave3.sh

$ cat > ~/startCarte[Env]Slave4.sh
unset DISPLAY
export KETTLE_HOME=/u01/app/pentaho/pdi-[env]slave4
datestamp=`date +%Y%m%d_%H%M%S`
export PENTAHO_DI_JAVA_OPTIONS="-Xms1024m -Xmx3072m -XX:MaxPermSize=256m"
${KETTLE_HOME}/carte.sh ${KETTLE_HOME}/pwd/[env]slave4-8084.xml >
${KETTLE_HOME}/logs/[env]slave4-8084_${datestamp}.out 2>&1 &
<ctrlr>d
$ chmod 755 ~/startCarte[Env]Slave4.sh

$ cat > ~/startCarte[Env]Slave5.sh
unset DISPLAY
export KETTLE_HOME=/u01/app/pentaho/pdi-[env]slave5
datestamp=`date +%Y%m%d_%H%M%S`
export PENTAHO_DI_JAVA_OPTIONS="-Xms1024m -Xmx3072m -XX:MaxPermSize=256m"
${KETTLE_HOME}/carte.sh ${KETTLE_HOME}/pwd/[env]slave5-8085.xml >
${KETTLE_HOME}/logs/[env]slave5-8085_${datestamp}.out 2>&1 &
<ctrlr>d
$ chmod 755 ~/startCarte[Env]Slave5.sh
```

20. On the Master VM, create repository update script in the ~kettle directory:

```
$ cd ~
$ cat > ~/updateRepo[Env].sh
unset DISPLAY
export KETTLE_HOME=/u01/app/pentaho/pdi-[env]master1
datestamp=`date +%Y%m%d_%H%M%S`

${KETTLE_HOME}/import.sh -rep="[ENV] Repo" -user=admin -pass=admin -dir=/ -replace=Y -
norules=Y -file=${KETTLE_HOME}/erx_repo/inbound_main.xml | tee
${KETTLE_HOME}/logs/updateRepoDev1_${datestamp}.out 2>&1

${KETTLE_HOME}/import.sh -rep="[ENV] Repo" -user=admin -pass=admin -dir=/ -replace=Y -
norules=Y -file=${KETTLE_HOME}/erx_repo/inbound_vista_delivery.xml | tee -a
${KETTLE_HOME}/logs/updateRepoDev1_${datestamp}.out 2>&1

${KETTLE_HOME}/import.sh -rep="[ENV] Repo" -user=admin -pass=admin -dir=/ -replace=Y -
norules=Y -file=${KETTLE_HOME}/erx_repo/outbound_main.xml | tee -a
${KETTLE_HOME}/logs/updateRepoDev1_${datestamp}.out 2>&1
<ctrlr>d
$ chmod 755 ~/updateRepo[Env].sh
```

4.8.3.2 Pentaho Repository Definition Import

The section provides step-by-step guidance to import the Pentaho repository:

1. Log into Linux and sudo su to the kettle account:

```
$ sudo su - kettle
```

2. Create downloads directory if it doesn't exist:

```
$ mkdir -p /u01/downloads
```

3. Download INB_ERX Pentaho Repository Definition zip archive for [ENV].

Download PS_INB_ERX_Pentaho_[n.n.n.nnn].zip from AITC IEP eRx Deployments directory

4. Unpack repository definition in Master1 instance:

```
$ cd /u01/app/pentaho/pdi-[env]master1  
$ unzip /u01/app/downloads/PS_INB_ERX_Pentaho_[n.n.n.nnn].zip erx_repo/*
```

5. Update Pentaho repository:

```
$ cd ~  
$ ~/updateRepo [Env].sh
```

4.8.4 Nexus Repository Installation (DEV2 VM1 Only)

The following sections describe the steps to install the SonaType Nexus OSS repository server. All activities are to be performed by a Systems Administrator.

4.8.4.1 SonaType Nexus Software Installation

The section provides step-by-step guidance on the installing the SonaType Nexus repository software:

1. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Create downloads directory if it doesn't exist:

```
$ mkdir -p /u01/downloads
```

3. Download SonaType Nexus OSS repository software archive (nexus-3.5.2-01-unix.tar.gz) to the downloads directory.

Download from AITC IEP eRx Downloads directory

4. Return back in your normal Linux login account.

```
$ exit
```

5. Create the nexus software directory if it doesn't exist:

```
$ sudo mkdir -p /u01/app/nexus  
$ sudo chown nexusloc:weblogic /u01/app/nexus  
$ sudo chmod 755 /u01/app/nexus
```

6. Unpack Nexus repository software:

```
$ cd /u01/app/nexus  
$ sudo -u nexusloc tar xvzf /u01/downloads/nexus-3.5.2-01-unix.tar.gz  
$ sudo ln -s nexus-3.5.2-01 latest
```

7. Modify /u01/app/nexus/latest/bin/nexus.rc:

```
$sudo vi /u01/app/nexus/latest/bin/nexus.rc
```

8. Modify service user account:

```
run_as_user="nexusloc"
```

9. Modify /u01/app/nexus/sonatype-work/nexus3/etc/nexus.properties:

```
$sudo vi /u01/app/nexus/sonatype-work/nexus3/etc/nexus.properties
```

10. Modify as follows:

```
application-port=8061  
application-host=vaauserxappdev2.aac.va.gov  
nexus-context-path=/nexus/
```

11. Modify ~nexusol/.bashrc:

```
$ sudo vi ~nexusloc/.bashrc
```

12. Add NEXUS_HOME near the end of the file:

```
export NEXUS_HOME=/u01/app/nexus/latest
```

13. Modify /u01/app/nexus/latest/bin/nexus

```
$sudo vi /u01/app/nexus/latest/bin/nexus
```

14. Enable the INSTALL4_JAVA_HOME_OVERRIDE variable:

```
INSTALL4J_JAVA_HOME_OVERRIDE=/u01/app/java/latest
```

15. Modify HTTPD configuration:

```
$ sudo vi /etc/httpd/conf/httpd.conf
```

16. Add the following for Nexus reverse proxy:

```
#  
#       Reverse proxy to Nexus  
#  
ProxyPass /nexus/ http://vaauserxappdev2.aac.va.gov:8061/nexus/  
ProxyPassReverse /nexus/ http://vaauserxappdev2.aac.va.gov:8061/nexus/
```

17. Create symbolic link for /etc/init.d/nexus:

```
$ sudo ln -s /u01/app/nexus/latest/bin/nexus /etc/init.d/nexus
```

18. Enable the Nexus OSS repository service:

```
$ cd /etc/init.d  
$ sudo chkconfig -add nexus  
$ sudo chkconfig -levels 345 nexus on
```

4.8.5 VistA Patch Installation

Not applicable to patch PSO*7.0*589.

4.9 Installation Verification Procedure

Please refer to the installation steps in the previous sections, which outline the installation verification procedures within each step.

4.10 System Configuration

This section is not applicable to the Inbound eRx project.

4.11 Database Tuning

This section will be added in future versions of this document.

5. Back-Out Procedure

This section describes the back-out procedure for Inbound eRx. Back-out pertains to a return to the last known operational state of the software and appropriate platform settings.

The Inbound eRx system will provide data protection measures, such as back-up intervals and redundancies that are consistent with systems categorized as mission critical (12 hour restoration, 2 hour recover point objectives). This section outlines the backout strategy, considerations, testing, criteria for backout, risks, authority to approve, and the procedures to perform a backout for Inbound eRx.

5.1 Back-Out Strategy

The back-out strategy will follow VA guidelines and best practices as referenced in the Enterprise Operations (EO) National Data Center Hosting Services document.

5.2 Back-Out Considerations

Back-out considerations will follow VA guidelines and best practices as referenced in the EO National Data Center Hosting Services document.

5.2.1 Load Testing

This section is not applicable to the Inbound eRx project.

5.2.2 User Acceptance Testing

The results of User Acceptance Testing (UAT) will be added to this document in a future version, following the completion of UAT.

5.3 Back-Out Criteria

Back-out criteria will follow VA guidelines and best practices as referenced in the EO National Data Center Hosting Services document.

5.4 Back-Out Risks

There are no known risks related to a back-out.

5.5 Authority for Back-Out

The POCs with the authority to order the back-out is the Inbound eRx IPT, the VA PM, and other relevant stakeholders.

5.6 Back-Out Procedure

This section outlines the backout procedure for the following:

- Pentaho 8.2 upgrade patch PSO*7.0*589
- WebLogic

5.6.1 Back-Out of VistA Patch

Not applicable for patch PSO*7.0*589.

5.6.2 Back-Out of Database

This section outlines the steps for backing out Database changes on the local database server. These steps should be performed under strict guidance of the PRE Inbound eRx PM team.

5.6.2.1 Restore backup files from tape

Recover data procedures are in the EO National Data Center Hosting Services document.

5.6.2.2 Mount the instance

1. Set ORACLE_SID=IEPP
2. rman TARGET SYS/Password NOCATALOG
3. RMAN:> shutdown immediate;
RMAN:> startup mount;

5.6.2.3 Restore and recover the datafiles

1. RMAN> run
{
allocate channel dev1 type disk;
set until time "to_date('2011-12-30:00:00:00', 'yyyy-mm-dd:hh24:mi:ss')";
restore database;
recover database; }

5.6.2.4 Open the database and reset logs

1. RMAN> alter database open resetlogs;

5.6.3 Back-Out of WebLogic

This section outlines the steps for backing out a new version of the PRE Inbound eRx application deployed on a local WebLogic (application) server. This is a two-step process: first, remove the new release, and then deploy the rolled-back release. These steps should be performed under strict guidance of the PRE Inbound eRx PM team.

5.6.3.1 Remove New Release

1. Open and log into the WebLogic console. Use WebLogic username and password.
2. Within the **Domain Structure** panel in the left column of the WebLogic console, select the **Deployments** node.
3. Within the **Change Center** panel in the left column of the WebLogic console, select **Lock & Edit**.
4. WebLogic will now display the panel **Summary of Deployments** in the right column of the console, where all deployments for the WebLogic domain are listed.
5. Select the previously deployed Inbound eRx deployment, select **Stop**, and then select **Force Stop Now** from the drop-down list.
6. WebLogic will now display the panel Force Stop Application Assistant in the right column of the console for confirmation to start servicing requests.
7. Select **Yes** in the **Force Stop Application Assistant** panel in the right column of the WebLogic console.

8. WebLogic now returns to the **Summary of Deployments** panel in the right column of the console.
9. Verify that the State of the Inbound eRx deployment is **Prepared**.
10. Select the previously deployed Inbound eRx deployment, and then select **Delete**.
11. WebLogic will now display the panel **Delete Application Assistant** in the right column of the console for confirmation to start servicing requests.
12. Select **Yes** in the **Delete Application Assistant** panel in the right column of the WebLogic console.
13. WebLogic now returns to the Summary of Deployments panel in the right column of the console.
14. Verify that the Inbound eRx deployment has been deleted and is no longer present.

5.6.3.2 Deploy Back-out Release

The following steps detail the deployment of the rolled-back Inbound eRx application.

1. Use the WebLogic console that was started at the beginning of the roll-back process.
2. Within the **Domain Structure** panel in the left column of the WebLogic console, select the **Deployments** node.
3. Verify that application is in **Lock & Edit** mode. **Lock & Edit** mode is indicated by the “greyed-out” **Lock & Edit** selection button.
4. Select **Install** in the **Deployments** panel in the right column of the WebLogic console.
5. WebLogic will now display the panel, **Install Application Assistant** in the right column of the console where the Inbound eRx deployment will be found.
 - a. If the rolled-back Inbound eRx deployment has already been transferred to the Deployment Machine, navigate to the deployment file location using the links and file structure displayed within the **Location** panel within the Install Application Assistant in the right column of the console. Choose the ear file associated with the rolled-back release.
 - b. If the rolled-back Inbound eRx deployment has not been transferred to the Deployment Machine:
 - i. Select the **upload your file(s)** link in the **Install Application Assistant** panel in the right section of the console.
 - ii. Select the **Deployment Archive Browse** to see the **Choose file** dialogue used to select the Deployment Archive.
 - iii. Select **Next** in the **Upload a Deployment to the admin server** panel in the right column of the WebLogic console to return to the **Locate deployment to install and prepare for deployment** panel within the Install Application Assistant.
6. Once the rolled-back Inbound eRx deployment is located and selected, select **Next**.
7. WebLogic will now display the panel **Choose targeting style** within the Install Application Assistant in the right column of the console. Leave the default value selected, install this deployment as an application, and select **Next**.

8. Within the **Install Application Assistant** in the right column of the console, WebLogic will now display the panel **Select deployment targets**, where the Deployment Server will be selected as the target in the next step.
9. For the **Target**, select the **Deployment Server**.
10. Select **Next**.
11. Within the **Install Application Assistant**, WebLogic will now display the panel **Optional Settings** in the right column of the console, where the name of the deployment and the copy behavior are chosen.
12. Enter the **Name** for the deployment. Use: **INB_ERX-3.1.0.005**
13. Verify that the following default option for Security is selected:
DD Only: Use only roles and policies that are defined in the deployment descriptors.
14. Verify that the following default option for Source accessibility is selected:
Use the defaults defined by the deployment's targets.
15. Select **Next**.
16. Within the **Install Application Assistant**, in the right column of the console WebLogic, the panel **Review your choices and click Finish** will now be displayed, which summarizes the steps completed above.
17. Verify that the values match those entered in Steps 6 through 17 and select **Finish**.
18. WebLogic will now display the panel **Settings for Inbound eRx**, in the right column of the console, where the values previously entered are available as well as a setting to change the deployment order.
19. Leave all the values as defaulted by WebLogic and select **Save**.
20. Within the **Change Center** panel in the left column of the WebLogic console, select **Activate Changes**.
21. Within the **Domain Structure** panel in the left column of the WebLogic console, select the **Deployments** node.
22. WebLogic will now display the panel **Summary of Deployments** in the right column of the console, where all deployments for the WebLogic domain are listed.
23. Select the previously deployed INB_ERX-3.1.0.005 deployment, select **Start**, and then select **Servicing all requests** from the drop-down list.
24. WebLogic will now display the panel **Start Application Assistant** in the right column of the console for confirmation to start servicing requests.
25. Select **Yes** in the **Start Application Assistant** panel in the right column of the WebLogic console.
26. WebLogic now returns to the **Summary of Deployments** panel in the right column of the console.
27. Verify that the State of the INB_ERX-3.1.0.005 deployment is **Active**.

5.7 Back-out Verification Procedure

For verifying the patch backout for Inbound eRx reference PSO*7.0*551 Patch Description in Forum and pso_7_0_p551_ig detailing Deployment, Installation, Back-Out, and Rollback for PSO*7.0*551.

Depending on the approach taken for the back-out, the verification steps will vary. Please contact the Inbound eRx development/maintenance team for verification instructions.

6. Rollback Procedure

This section outlines the procedures for rolling back to a previous state of the data.

6.1 Rollback Considerations

Back-out considerations will follow VA guidelines and best practices as referenced in the EO National Data Center Hosting Services document.

6.2 Rollback Criteria

Rollback criteria will follow VA guidelines and best practices as referenced in the EO National Data Center Hosting Services document.

6.3 Rollback Risks

There are no known risks related to a Rollback.

6.4 Authority for Rollback

The POCs with the authority to order the Rollback are the Inbound eRx IPT, the VA PM, and other relevant stakeholders.

6.5 Rollback Procedure

6.5.1 Rollback of Database

This section outlines the steps for rollback of Database changes on the local database server. These steps should be performed under strict guidance of the PRE Inbound eRx PM team.

6.5.1.1 Restore backup files from tape

Recover data procedures are in the EO National Data Center Hosting Services document.

6.5.1.2 Mount the instance

28. Set ORACLE_SID=IEPP
29. rman TARGET SYS/Password NOCATALOG
30. RMAN:> shutdown immediate;
RMAN:> startup mount;

6.5.1.3 Restore and recover the datafiles

31. RMAN> run
 - {
 - allocate channel dev1 type disk;
 - set until time "to_date('2011-12-30:00:00:00', 'yyyy-mm-dd:hh24:mi:ss')";
 - restore database;
 - recover database; }

6.5.1.4 Open the database and reset logs

32. RMAN> alter database open resetlogs;

6.5.2 Rollback WebLogic

This section outlines the steps for rolling back to a previous version of the PRE Inbound eRx application deployed on a local WebLogic (application) server. This is a two-step process. First, remove the old release, and then deploy the rolled-back release. These steps should be performed under strict guidance of the PRE Inbound eRx PM team.

6.5.2.1 Remove New Release

1. Open and log into the WebLogic console. This is located at:
\\vaauspecdbs801.aac.dva.va.gov\erx\install\. Use WebLogic username and password.
2. Within the **Domain Structure** panel in the left column of the WebLogic console, select the **Deployments** node.
3. Within the **Change Center** panel in the left column of the WebLogic console, select **Lock & Edit**.
4. WebLogic will now display the panel **Summary of Deployments** in the right column of the console, where all deployments for the WebLogic domain are listed.
5. Select the previously deployed Inbound eRx deployment, select **Stop**, and then select **Force Stop Now** from the drop-down list.
6. WebLogic will now display the panel **Force Stop Application Assistant** in the right column of the console for confirmation to start servicing requests.
7. Select **Yes** in the **Force Stop Application Assistant** panel in the right column of the WebLogic console.
8. WebLogic now returns to the **Summary of Deployments** panel in the right column of the console.
9. Verify that the State of the Inbound eRx deployment is **Prepared**.
10. Select the previously deployed Inbound eRx deployment, and then select **Delete**.
11. WebLogic will now display the panel **Delete Application Assistant** in the right column of the console for confirmation to start servicing requests.
12. Select **Yes** in the **Delete Application Assistant** panel in the right column of the WebLogic console.
13. WebLogic now returns to the Summary of Deployments panel in the right column of the console.
14. Verify that the Inbound eRx deployment is deleted and no longer present.

6.5.2.2 Deploy Rolled-Back Release

The following steps detail the deployment of the rolled-back Inbound eRx application.

1. Use the WebLogic console that was started at the beginning of the roll-back process.
2. Within the **Domain Structure** panel in the left column of the WebLogic console, select the **Deployments** node.

3. Verify that the application is in **Lock & Edit** mode. **Lock & Edit** mode is indicated by the “greyed-out” **Lock & Edit** selection button.
4. Select the **Install** button in the **Deployments** panel in the right column of the WebLogic console.
5. WebLogic will now display the panel **Install Application Assistant** in the right column of the console, where the location of the Inbound eRx deployment will be found.
 - a. If the rolled-back Inbound eRx deployment has already been transferred to the Deployment Machine, navigate to the deployment file location using the links and file structure displayed within the **Location** panel, which is within the **Install Application Assistant** panel in the right column of the console. Choose the ear file associated with the rolled-back release.
 - b. If the rolled-back Inbound eRx deployment has not been transferred to the Deployment Machine:
 - i. Select on the **upload your file(s)** link in the **Install Application Assistant** panel in the right section of the console.
 - ii. Select the **Deployment Archive Browse** to see the **Choose file** dialogue used to select the Deployment Archive.
 - iii. Select **Next** in the **Upload a Deployment to the admin server** panel in the right column of the WebLogic console to return to the **Locate deployment to install and prepare for deployment** panel within the Install Application Assistant.
6. Once the rolled-back Inbound eRx deployment is located and selected, select **Next**.
7. WebLogic will now display the panel **Choose targeting style** within the Install Application Assistant in the right column of the console. Leave the default value selected, install this deployment as an application, and select **Next**.
8. Within the **Install Application Assistant** in the right column of the console, WebLogic will now display the panel **Select deployment targets**, where the Deployment Server will be selected as the target in the next step.
9. For the **Target**, select the **Deployment Server**.
10. Select **Next**.
11. Within the **Install Application Assistant**, WebLogic will now display the panel **Optional Settings** in the right column of the console, where the name of the deployment and the copy behavior are chosen.
12. Enter the **Name** for the deployment. Use: **INB_ERX-3.1.0.005**
13. Verify that the following default option for Security is selected:
 DD Only: Use only roles and policies that are defined in the deployment descriptors.
14. Verify that the following default option for Source accessibility is selected:
 Use the defaults defined by the deployment's targets.
15. Select **Next**.

16. Within the **Install Application Assistant**, in the right column of the console WebLogic, the panel **Review your choices and click Finish** will now be displayed, which summarizes the steps completed above.
17. Verify that the values match those entered in Steps 6 through 17 and select **Finish**.
18. WebLogic will now display the panel **Settings for Inbound eRx**, in the right column of the console, where the values previously entered are available as well as a setting to change the deployment order.
19. Leave all the values as defaulted by WebLogic and select **Save**.
20. Within the **Change Center** panel in the left column of the WebLogic console, select **Activate Changes**.
21. Within the **Domain Structure** panel in the left column of the WebLogic console, select the **Deployments** node.
22. WebLogic will now display the panel **Summary of Deployments** in the right column of the console, where all deployments for the WebLogic domain are listed.
23. Select the previously deployed **INB_ERX-3.1.0.005** deployment, select **Start**, and then select **Servicing all requests** from the drop-down list.
24. WebLogic will now display the panel **Start Application Assistant** in the right column of the console for confirmation to start servicing requests.
25. Select **Yes** in the **Start Application Assistant** panel in the right column of the WebLogic console.
26. WebLogic now returns to the **Summary of Deployments** panel in the right column of the console.
27. Verify that the State of the **INB_ERX-3.1.0.005** deployment is **Active**.

6.5.3 Rollback VistA Patch

Due to the fact that the data involved with inbound eRx is prescription related, data dictionary changes and existing data will not be rolled back. The system should maintain the new fields and records. The back-out procedure will dictate the usage/view of the new data. Any new message type will still be available to the user and will be impacted only by the back-out procedure. Message linking between NewRx and cancel/refill message types will be established. The rolling back of the data would sever this linkage, potentially causing major problems.

6.6 Rollback Verification Procedure

6.6.1 Validation of Roll Back Procedure

The user will be able to view the cancel and refill message types. All actions besides print will be locked so the user cannot take action on the record. This will create a view only scenario for cancel and refill message types.

7. Operational Procedures

This section outlines server startup and shutdown procedures.

7.1 Startup Procedures

7.1.1 Start Weblogic Node Managers and Admin Console

1. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. On VM1, start node managers:

```
$ ./startNodemanager_[domain].sh
```

3. On VM2, start node managers:

```
$ ./startNodemanager_[domain].sh
```

4. On VM1, wait for node manager startups to complete:

```
$ tail -f [DOMAIN_HOME]/nodemanager/nodemanager.log
```

5. On VM1, watch for the following log messages to indicate the node managers are up:

```
<INFO> <Secure socket listener started on port 5556, host [vm1_fqdn]>
```

6. On VM2, wait for node manager startups to complete:

```
$ tail -f [DOMAIN_HOME]/nodemanager/nodemanager.log
```

7. On VM2, watch for the following log messages to indicate the node managers are up:

```
<INFO> <Secure socket listener started on port 5556, host [vm2_fqdn]>
```

8. On VM1, start AdminServer:

```
$ ./startWebLogic_[domain].sh
```

9. On VM1, wait for the AdminServer startup to complete:

```
$ tail -f [DOMAIN_HOME]/servers/AdminServer/logs/AdminServer.out
```

10. On VM1, watch for the following log messages to indicate the AdminServer is up:

```
<Notice> <WebLogicServer> <BEA-000365> <Server state changed to RUNNING.>
```

7.1.2 Managed Servers

1. Log into the *[domain]* Admin Console, start **erx1** and **erx2** managed servers

2. Verify landing pages are responding:

```
https://[proxy_fqdn]/INB-ERX/  
https://[proxy_fqdn]/inbound/
```

7.1.3 Pentaho Services Startup

1. Log into Linux and sudo su to the kettle account:

```
$ sudo su - kettle
```

2. On VM1, start *[ENV]* Master Slave:

```
$ ./startCarte_[Env]Master1.sh
```

3. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), wait for the *[ENV]* Master Slave to start up by watching: [https://\[proxy_fqdn\]/master1/kettle/status/](https://[proxy_fqdn]/master1/kettle/status/)

4. On VM 1, start *[ENV]* Dynamic Slave1:

```
$ ./startCarte_[Env]Slave1.sh
```

5. On VM 1, start *[ENV]* Dynamic Slave2:

```
$ ./startCarte_[Env]Slave2.sh
```

6. On VM 2, start [ENV] Dynamic Slave3:

```
$ ./startCarte[Env]Slave3.sh
```
7. On VM 2, start [ENV] Dynamic Slave4:

```
$ ./startCarte[Env]Slave4.sh
```
8. On VM 2, start [ENV] Dynamic Slave5:

```
$ ./startCarte[Env]Slave5.sh
```
9. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), wait for the [ENV] Slave1 to start up by watching: [https://\[proxy_fqdn\]/slave1/kettle/status/](https://[proxy_fqdn]/slave1/kettle/status/)
10. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), wait for the [ENV] Slave2 to start up by watching: [https://\[proxy_fqdn\]/slave2/kettle/status/](https://[proxy_fqdn]/slave2/kettle/status/)
11. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), wait for the [ENV] Slave3 to start up by watching: [https://\[proxy_fqdn\]/slave3/kettle/status/](https://[proxy_fqdn]/slave3/kettle/status/)
12. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), wait for the [ENV] Slave4 to start up by watching: [https://\[proxy_fqdn\]/slave4/kettle/status/](https://[proxy_fqdn]/slave4/kettle/status/)
13. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), wait for the [ENV] Slave5 to start up by watching: [https://\[proxy_fqdn\]/slave5/kettle/status/](https://[proxy_fqdn]/slave5/kettle/status/)
14. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), check that all 5 dynamic slaves have registered with the master: [https://\[proxy_fqdn\]/slave1/kettle/getSlaves/](https://[proxy_fqdn]/slave1/kettle/getSlaves/)
15. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), start the message processing jobs:
[https://\[proxy_fqdn\]/slave1/kettle/runJob/?job=inbound_main/InboundMessageProcessing_JOB](https://[proxy_fqdn]/slave1/kettle/runJob/?job=inbound_main/InboundMessageProcessing_JOB)
[https://\[proxy_fqdn\]/slave2/kettle/runJob/?job=inbound_main/InboundMessageProcessingRetry_JOB](https://[proxy_fqdn]/slave2/kettle/runJob/?job=inbound_main/InboundMessageProcessingRetry_JOB)
[https://\[proxy_fqdn\]/slave3/kettle/runJob/?job=inbound_vista_delivery/InboundDeliverToVista_JOB](https://[proxy_fqdn]/slave3/kettle/runJob/?job=inbound_vista_delivery/InboundDeliverToVista_JOB)
[https://\[proxy_fqdn\]/slave4/kettle/runJob/?job=outbound_main/OutboundMessageProcessing_JOB](https://[proxy_fqdn]/slave4/kettle/runJob/?job=outbound_main/OutboundMessageProcessing_JOB)
[https://\[proxy_fqdn\]/slave5/kettle/runJob/?job=inbound_vista_delivery/InboundDeliverToVistaMbM_JOB](https://[proxy_fqdn]/slave5/kettle/runJob/?job=inbound_vista_delivery/InboundDeliverToVistaMbM_JOB)
16. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), check the InboundMessageProcessing_JOB status: [https://\[proxy_fqdn\]/slave1/kettle/status](https://[proxy_fqdn]/slave1/kettle/status), select the **InboundMessageProcessing_JOB** hyperlink and check the job status page.
17. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), check the InboundMessageProcessingRetry_JOB status: [https://\[proxy_fqdn\]/slave2/kettle/status](https://[proxy_fqdn]/slave2/kettle/status), select the **InboundMessageProcessingRetry_JOB** hyperlink and check the job status page.
18. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), check the InboundDeliverToVista_JOB status: [https://\[proxy_fqdn\]/slave3/kettle/status](https://[proxy_fqdn]/slave3/kettle/status), select the **InboundDeliverToVista_JOB** hyperlink and check the job status page.
19. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), check the OutboundMessageProcessing_JOB status: [https://\[proxy_fqdn\]/slave4/kettle/status](https://[proxy_fqdn]/slave4/kettle/status), select the **OutboundMessageProcessing** hyperlink and check the job status page.

20. From the CPanel ([https://\[proxy_fqdn\]/cpanel](https://[proxy_fqdn]/cpanel)), check the InboundDeliverToVistaMbM_JOB status: [https://\[proxy_fqdn\]/slave5/kettle/status](https://[proxy_fqdn]/slave5/kettle/status), select the **InboundDeliverToVistaMbM_JOB** hyperlink and check the job status page.

7.2 Shut Down Procedures

7.2.1 Pentaho Services Shutdown

1. Log into Linux and sudo su to the kettle account:

```
$ sudo su - kettle
```

2. As kettle on VM2:

```
$ /u01/app/pentaho/pdi-[env]slave3/carte.sh [vm2_fqdn] 8083 -s -u cluster -p cluster
$ /u01/app/pentaho/pdi-[env]slave4/carte.sh [vm2_fqdn] 8084 -s -u cluster -p cluster
$ /u01/app/pentaho/pdi-[env]slave5/carte.sh [vm2_fqdn] 8085 -s -u cluster -p cluster
```

3. As kettle on VM1:

```
$ /u01/app/pentaho/pdi-[env]slave1/carte.sh [vm1_fqdn] 8081 -s -u cluster -p cluster
$ /u01/app/pentaho/pdi-[env]slave2/carte.sh [vm1_fqdn] 8082 -s -u cluster -p cluster
$ /u01/app/pentaho/pdi-[env]master1/carte.sh [vm1_fqdn] 8080 -s -u cluster -p cluster
```

7.2.2 WebLogic Application Server Shutdown

1. Log into Linux and sudo su to the weblogic account:

```
$ sudo su - weblogic
```

2. Log into erxdomain1 Admin Console as weblogic

```
Stop erx1 and erx2 managed servers
Stop Admin console
```

3. On VM1, as weblogic:

```
$ ./stopWebLogic_[domain].sh
```

4. On VM1, as weblogic:

```
$ ./stopNodemanager_[domain].sh
```

5. On VM2, as weblogic:

```
$ ./stopNodemanager_[domain].sh
```

8. Appendices

This section provides additional reference information to use for the installation of various components.

8.1 Certificate Contents

Use the text in this section for the certificate configuration steps in Section 4.2.7.

8.1.1 va_root_ca_cert.txt

```
-----BEGIN CERTIFICATE-----  
MIIDfjCCAmagAwIBAgIQA39zv0pkaxAy6V04im+hDANBgkqhkiG9w0BAQUFADB  
MRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYCdmExHDAaB  
BAMTE1ZBIE1udGVybmFsIFJvb3QgQ0EwHhcNMjUxMjIyMTY0NDM1WhcNMjUxMjIy  
MTY1MzE5WjBHMRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYC  
dmExHDAaBqNVBAMTE1ZBIE1udGVybmFsIFJvb3QgQ0EwggEiMA0GCSqGS1b3DQEB  
AQUAA4IBDwAwggEKAoIBAQDVafeLiz6lsJVkI1+suHkVyCZAyyjSHuDcIxonjg  
EVk3mRUYZW3QPuvS2m3NjKujJw9eL4FwGN nou+CUEdTvpAMoIo9Xhcm3uzR1Gq+  
Gn6f9ichJYrttNkQo+JXPqgzlsNqUEFBRuQymmK7kZODAPn2N9VM1GjDGejDGCD5  
fxYJyhkurwNWmVjU18D3E6mMWM/1OyinGmTC6i4FQiJpVW5IauZDS0ceJhr2BSEW  
BuH8W6mAQ9ZdXkiUBZm4/AUVw6QayK9kHTpFHoyHl1pJ12iDIln1a+NJdzNJiz7U  
URdrW0LBSBApDXijKsAMmcyxMvk4ULONR9BewoCQRVrBAgMBAAGjZjbkMBMGCSsG  
AQQBgjcUAQgQGHqQAQwBBMAsGA1UDwQEAwIBhjAPBqNVHRMBAF8EBTADAQH/MB0G  
A1UdDgQWBBTjZG2vNo8cUIhkMxOg90HayccdzzaQBgkrBqEEAYI3FQEAEwIBADAN  
BgkqhkiG9w0BAQUFAAOCAQEAox6+zBW1kK1py0UarVb6G+cphwcPi/Gt4Ozs58Aq  
BiZ9j36GWzD/LtbbG3J7Lj/gE9sFqTV8cx9sES22TxHhcA5eSF3tOg6xWMzi9S  
npRvQGSHvyYLhQ5KbJPTW3w1t2WGmx1DRCXI0cvXONuPEWN2Y15vBbv7T2kA63M0  
oieYDKb6BMCzj3VBHF5WuoXXXcJBUEPWjtJffZ88kqFkHt1DKqjdBqZIp9r56pd  
4PujhowXB0dViWFJcK2wIM1NvHSkjzBluXzTkssdMUG8CiZPpkDHMu10PhPo3ZOH  
hiEE/Cj5hryyeF+iwSwQX6YkH2stk53By1ctdC/N8Egudg==  
-----END CERTIFICATE-----
```

8.1.2 va_internal_subordinate_ca_cert.txt

```
-----BEGIN CERTIFICATE-----  
MIIF2zCCBMOgAwIBAgIHPQAAAAAW2TANBgkqhkiG9w0BAQUFADBHMRMwEQYKCZIm  
izPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYCdExHDAaBgNVBAMTE1ZBIElu  
dGVybmrFsIFJvb3QgQ0EwHhcNMTMwODE1MDA0NzA4WhcNnjMwODEzMDA0NzA4WjBQ  
MRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYCdExJTAjBgNV  
BAMTHFZBIE1udGVybmrFsIFN1ym9yZGluyXR1IENBIDEwggeiMA0GCSqGSIb3DQE  
AQUAA4IBDwAwggEKAoIBAAC8gdm7W2s9uaWucxI+miZR0P/6U2psmLn+kht6Rmdd  
maar842z5/iSPHnhPCr6Gc69YZovnJK/hjM1uxsvluu6OCFgYRGKYfAO2XaXCju  
lyXmj0q09TGXJIpCKhpjNBWL8BtcgGmbbZt7WWILbvbONcscaewQ0hXOWs7P+E2  
maxhtxbg/tVmSLE6anLXCMThFuRy2B9ps/osh8WgW91PP9Jd0YwpFCSiU2PN1i  
9gvPr8GQD+5QPsg4ya/QFDBWycC2eDFLXI8Tx0nJKoTSWcT7ETjpJYFT7aqva  
w36Ws62KSUy/QXTWGcEIipRePlum8/7yI27av6hdppzAgMBAAGjggLBMIICvTAP  
BgnVHRMBAf8EBTADAQH/MB0GA1UDgQWBTeJbRYCv2TJ9qNPR86dkt3Ut1bEzAL  
BgnVHQ8EBAMCAYwEAYJKwYBBAGCNxUBBAMCAQiwiwYJKwYBBAGCNxUCBBYEFEWP  
QVzWUUmQmIUEwoAI9JTK0qHLMdwGCSSGAQQBjgcVBwQvMC0GJSsGAQQBjgcVCIH  
wzOB+fAGgaWfdTYggQiFwqpLBpr2G4H2/kACAWCQAQIwHwYDVR0jBBgwFoAU42Rt  
rzaxHFCB5DMToPTh2snHc8wgdgGA1UdHwSB0DCBzTCByqCBx6CBxIYwaHR0cDov  
L2Nybc5wa2kudmEuZ292L3BraS9jcmwvKfJbnR1cm5hbFJvb3QuY3JshoGPbGRh  
cDovL2xkYXAucGtpLnZhldvd19DTj1WQUludGVybmrFsUm9vdCxDTj1DRFAssQ049  
UETjLENOPVN1cnZpY2VzLERDPVZBLERDPUDpvj9jZXJ0aWZpY2F0ZVJ1dm9jYXRp  
b25MaXN0P2Jhc2U/b2JqZWN0Q2xhc3M9Y1JMRG1zdHJpYnV0aW9uUG9pbnQwggEL  
BggRBgEFBQcBAQSB/jCB+zCBkgYIKwYBBQHMAKGgYVsZGFwOi8vbGRhcC5wa2ku  
dmEuZ292L0NPVZBSW50ZXJuYWxSb290LENOPUFJQSxDTj1QS0ksQ049U2Vydmlj  
ZXM斯REM9VkesREM9R09WP2NQ2VYdg1maWNhdGU/YmFzZT9vYmp1Y3RDbGFczl  
ZXJ0aWZpY2F0aW9uQXV0aG9yaXR5MCMGCCsGAQUFBzABhhodHRwOi8vb2NzcC5w  
a2kudmEuZ292LzA/BggRBgEFBQcwaYozaHR0cDovL2FpYS5wa2kudmEuZ292L1BL  
SS9BSUEvKvEvVkJbnnR1cm5hbFJvb3QuY2VymA0GCSqGSIb3DQEBBQUAA4IBAQAJ  
5Tw4vh01QAUiebJ3zFow3esXmqyjRWeHhszbNzsYop1szqelsFP0h69IYuvKVC5  
eHz1CxZ6zF0dFgFOkDf65BKoIyQ4W9942rRzr8eKDiyFdb2dGqP1uS7VtcyX6kI4  
BmhW5P8G6wRrD6Az7G3WUMpHZYtoae8udOk861Zk9P7h7PlnElzH7inr307F/KjL  
kc9m/RRdktv9n2c3cEmA741fCxiQpI2/gWTXKKJKy5yourKbEUtu4o3qXHj121V  
/D02OIovcs7RYs1zuTkKj03/uqli85QKifnzpWyLfto0ucFIi9W9q2yuWPU6wIT  
eaQRaJrinDddHrgSBqN4  
-----END CERTIFICATE-----
```

8.1.3 va_root_ca_s2_cert.pem

```
-----BEGIN CERTIFICATE-----  
MIIDhzCCAm+gAwIBAgIQKNXLQBaCYqRGJ+LYwX8c6TANBgkqhkiG9w0BAQsFADBK  
MRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYCdExHzAdBgNV  
BAMTF1ZBLU1udGVybmrFsLVMyLVJDQTEtdjEwHhcNMTYxMDI2MTYxMzIwWhcNMzYx  
MDI2MTYyMjU5WkBMRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQB  
GRYCdExHzAdBgNVBAMTF1ZBLU1udGVybmrFsLVMyLVJDQTEtdjEwggEiMA0GCSqG  
S1b3DQEBAQUAA4IBDwAwggEKAoIBAAC7qJL6b5hzXU7o+1HgX32ods7AgOGinzA4  
f9Jfuzlrfp+ZvVrRgXwZlkKgfjyNQIIY6uI9fG8dwNLrBa0vWY0KwMJ4pbEj1+gy  
1UDOrh3e3fPd68L3m+sUx0K/z+ZSiKhK1MOP0wFQtYmtCdc7b5zy5NApGBCJAJB  
QcdrvH8MCxCOIZEPxsTjuSDpcea09eD4nYAEUVzg+N9K9esWF+SLZxsCnFgMuL/  
ikS093wsaoFyBe0H0wH7GDNmV/Zx1xy3krzGqszfGRmxb4pxkbqvrOGzju2RzoRx  
1YKYNB4brDR4BGW984fiijql0fbwCK4q17nhSi71TEnxRf1tCaPrAgMBAAGjATBn  
MBMGCCsGAQQBjgJUAgQGHgQAOQwBMAAsGA1UDwQEAwIBhjASBgnVHRMBAf8ECDAG  
AQH/AgEBMB0GA1UDgQWBQBLYthZhuM0ODTTD507FsZsBHGYTAQBgkrBgeEEAYI3  
FQEEAwIBADANBgkqhkiG9w0BAQsFAAOCAQEAaE16FdPpLptzZA1sdGREaSfDP46j  
e2m7Ne1z2CdT/goRS5q1+uxQpaUvH08Lxw9Nr6Chr018K1uHYMgLuFybf1mP0R  
B/XKKJATs zamkMUYRSGeSf1uXKNz4dqXu2yv9BvxyY2qdGUUpEyOmcuZwq/Zh1qv  
1Aqg67zeBt0R0ZnJmLiMq7yw2kQ8MtWlx2tcN0nZmtPOb3WkrvG2sgFZN064gP2  
YV1Kp9RaENjNwYNVyyTbq8CofUIYV2OfSbsI1GR3CQSqPO5CUJ/ScdWuWJVfhWL  
11H5112CCqk+7vaTBtK+QjBliAayTFyonUocbD5VBxB4Dv1CMk7uATrhNw==  
-----END CERTIFICATE-----
```

8.1.4 va_internal_ca1_s2_cert.pem

```
-----BEGIN CERTIFICATE-----  
MIIEoDCCA4igAwIBAgITFAAAAArskyEu6lBaeQAAAAAABDANBgkqhkiG9w0BAQsF  
ADBKMRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYCdExHzAd  
BgNVBAMTF1ZBLU1udGVybmFsLVMyLVJDQTEtdjEwHhcNMTYxMDI3MTY0MTA3WhcN  
MjYxMDI1MTY0MTA3WjBKMRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPy  
LGQBGRYCdExHzAdBgNVBAMTF1ZBLU1udGVybmFsLVMyLU1DQTEtdjEwggiMA0G  
CSqGSib3DQEBAQUAA4IBDwAwggEKAoIBAQC4bY+wR9CKBb6rxoRajhPAFJIPdwHe  
bp3Kz5Cx1PmQMk6AnqX3WWqm/qSebBHCNvqdqSgXMSdVxu0loC1hgBLvccwmxdc  
4rJD6Vydh3WEv74LayMIrZ106Qlcj+6GnVmMs/+FbEF9SynICY2RhmO8roLplo  
UnaNiC3Pruy972LHN/OE8Z7FMWIHB/GQHwX/1P05p0yv/8WsojctrW8S3d56V1H  
u4W4i1KZMoTxDR2JFpn6q22J4DjVG8ouOSyJQmXMFR+HcmVPAaJbAF1L0w0BOr1F  
3Ww4RFo/PwDEm+SopGiTfEmMaPGX377FL1EhWuI/I0yxtQT9zxt4rTTVAgMBAAGj  
ggF9MIIBeTAQBgkrBgeEAYI3FQEEAWIBADAdBgNVHQ4EFgQUG23f6z314g3vFrHQ  
319YGLbL5OwPAYJKwYBAGCNxUHBC8wLQY1KwYBBAGCNxU1gcjDM4H58aaBpZ8N  
hOCBCIXCqksGg+96htu7FwIBZAIBejALBgNVHQ8EBAMCAYwEgYDVR0TAQH/BAgw  
BgEB/wIBADAdBgNVHSMEGDAwBQBLYthZhuM00TTD507FsZsBHGYTBJBgNVHR8E  
QjBAMD6gPKA6hjhodHRwoi8vY3J3sLnBraS52YS5nb3YvcGtpL2Nybc9WQS1JbnR1  
cm5hbC1TMi1S0Q0ExLXYxLmNyDB7BgggrBgeFBQcBAQRvMG0wRwYIKwYBBQUHMAKG  
O2h0dHA6L9haWEucGtpLnZhLmdvd19wa2kvYWhl1ZBL1ZBLU1udGVybmFsLVMy  
LVJDQTEtdjEuY2VymCIGCCsGAQUFBzABhhZodHRwOi8vb2NzC5wa2kudmEuZ292  
MAOGCSqGSib3DQEBCwUA4IBAQCA/ZQYzX1u6rB0xITkVY5K8zPAjovsD6ynkr0B  
uCH+qOj3edjvQENG1JRVK89HqBNMspbtUsZz2TEVKNH5xWtY0jp6vJm1DYDUqSu  
bEMe3CeJpked9s8JZV/P4P9swPkJ2ZiptOlskqqnmCk7ZrJbevb4GPvQ+wCUf2r8  
t3ybYK5B1fyuX4L+h/GvdQWInS3Nt8hvdyMeW7y7rC+6IOIJRLlaO90tbBNzfIn  
VR6NHQuatOvd9HVwJKvPvp0F0PYtScUXus+mzrV6RXKtYrFEbUX9jcrVlq2ML2H  
A92Pm2HzYILqv/D2WQOCqZSKfpYr7jgekcgMBriisBlBq4D  
-----END CERTIFICATE-----
```

8.1.5 va_internal_ca2_s2_cert.pem

```
-----BEGIN CERTIFICATE-----  
MIIEoDCCA4igAwIBAgITFAAAAAOx9+1YJSJG4QAAAAAAzANBgkqhkiG9w0BAQsF  
ADBKMRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYCdExHzAd  
BgNVBAMTF1ZBLU1udGVybmFsLVMyLVJDQTEtdjEwHhcNMTYxMDI2MTgzNDM4WhcN  
MjYxMDI0MTgzNDM4WjBKMRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPy  
LGQBGRYCdExHzAdBgNVBAMTF1ZBLU1udGVybmFsLVMyLU1DQTEtdjEwggiMA0G  
CSqGSib3DQEBAQUAA4IBDwAwggEKAoIBAQC9UaJu7b6BP9ffk9eZyAjCoLZHAQXD  
QWiVrR1D1rkowF7cwSeoyPQ5yoMrH9TLQeb/GRVaL5UeHHw9bqbnXvMogGuV1O64  
vu42RDUEKofout/34LpBN9DC2JCsocNMVtwyoFuGJBYAeygZDNaLuI53tpzw74pa  
WkoiD5pXtoOjkuaRs2vMHD3kuzNeBdXFwo/145gnZFpxmJo/Dr3wGzDDi07h53S/  
VVAaaOXdPISVm1sieKtLeinyy9qbkxdC7k1MdMuYnRF92aZY+gezvpVqW7F1T8z  
pT35wqbxbE1oqRAM1MeB7D5M19Kp/bWOfZ/zwhH6Y61A91q4FsTsXxe1AgMBAAGj  
ggF9MIIBeTAQBgkrBgeEAYI3FQEEAWIBADAdBgNVHQ4EFgQU71TwDfev76TpwXs1  
g0+9o6wnA7cwPAYJKwYBAGCNxUHBC8wLQY1KwYBBAGCNxU1gcjDM4H58aaBpZ8N  
hOCBCIXCqksGg+96htu7FwIBZAIBejALBgNVHQ8EBAMCAYwEgYDVR0TAQH/BAgw  
BgEB/wIBADAdBgNVHSMEGDAwBQBLYthZhuM00TTD507FsZsBHGYTBJBgNVHR8E  
QjBAMD6gPKA6hjhodHRwoi8vY3J3sLnBraS52YS5nb3YvcGtpL2Nybc9WQS1JbnR1  
cm5hbC1TMi1S0Q0ExLXYxLmNyDB7BgggrBgeFBQcBAQRvMG0wRwYIKwYBBQUHMAKG  
O2h0dHA6L9haWEucGtpLnZhLmdvd19wa2kvYWhl1ZBL1ZBLU1udGVybmFsLVMy  
LVJDQTEtdjEuY2VymCIGCCsGAQUFBzABhhZodHRwOi8vb2NzC5wa2kudmEuZ292  
MAOGCSqGSib3DQEBCwUA4IBAQCX2482Kh858YMek32bsZoMRRCKgNEWBBH  
DwXpNu0zDjaxrvIPi+foEk/MvTn7PMsPqCPYnuRw31PCJ1uD00S/kUMMXJm30N314  
L4nmZz4BrhyZsYOyYHQJoE4KT2/Diw28XFJYH6FtDZnAl05s3xn1lg7NatBvBX0K  
WayJ1ETJkp2aPlon9u+Tq/YE++Y0ek3MCozimRW/iWxzq2cd2UfnRyt2fJugAiJ2  
S3AJbCWb5KTZilip9tRiHyXDxxcJ+N9FSQgZ1e/B62m9Xouh6VCTi3alCRY1MXSG  
2+yUvBNmGIB0+tacbQAyXEPAVhrE5B+VLS/7jrHDR5ap21n  
-----END CERTIFICATE-----
```

8.1.6 betrusted_production_ssp_ca_a1_cert.txt

-----BEGIN CERTIFICATE-----
MIIG6DCCBdCgAwIBAgICAzowDQYJKoZIhvcNAQELBQAwWTELMAkGA1UEBhMCVVMxGDAWBgNVBAoT
D1UuUy4gR292ZXJubWVu dDENMasGA1UECxMER1BLSTEhMB8GA1UEAxMYRmVkJbCBDb21tb24g
UG9saWN5IENBMB4XDTEwMTIwOTE5NTUyNFOXDTE5NDkwNFowgYgxCzAJBgNVBAYTA1VT
MRkwFwYDVQQKExBCZX RydXN0ZWQgVV M gSW5jM QwwCgYDVQQL EwNTU1AxJzA1BgNVBA sTHkJldHJ1
c3RLZCBQcm9kdWN0aW9uI FNTUCBDQSBBMTEhMCUGA1UEAxMeQmV0cnVzdGVkIFByb2R1Y3Rp b24g
U1NQIENBIEExMIIBIjANBgkqhkiG9w0BAQEFAOC A Q8AMIBCgKCAQEAn2gPTEBKtv o7JnaOXE7F
YH1PY05qXCVj bqe9LediLo3efZgsmFEK4ot1l61UC9PJAUiteerilKov9+ momu08xX1FyJdYAWm/
moYRLVUMiCuDgJVLpw7FgmQh7FBBAW7IHeBvCYZUU4Ozh9vdYuxKkcA5sz9HgFL7RUyblMA Pe179
JBp0dLvYEgBA+O25/VVLYeqD2wCQh kWkEIsWFDG1i6FjdVK/i lot4kUj8nHS/o9uiTe bYK+81Pg0
1K0jHhIzoxeTGdx9wVm kZ/A3FRtramPEQPaL2d/kY4tImmXW541hAn9Swy9Ur523tOxDpsNE1
VaN+7RU4Yt4Cxf6XrwIDAQABo4ID DCCA4QwDwYDVR0TAQH/BAUwAwEB/zBPBgNVHSAESDBGMAwG
CmCGSAF1AwIBAwYwDAYK YIZIAWUDAgEDETCB6QYIKwYBBQUHAQEEgdwwgdkwPwYIKwYBBQUHMAKG M2h0dHA6Ly9odHRwLmzw
a2kuZ292L2Zj cGNhL2NhQ2VydHN Jc3N1ZWRUb2Zj cGNhLnA3YzCB1QYIKwYBBQUHMAKGgYhsZGFw
O i8vbGRhcC5mcGtpLmdvdi9jb1GZWRlcmFsJT IwQ29tbW9u JT IwUG9saWN5JTIwQ0Esb3U9R1BL
SSxvPVUUuUy41MjBHb3Z1cm5tZw50LG M9V VM/Y0FDZXJ0aWz pY2F0ZTtia w5hc nksY3Jvc3NDZXJ0
aWz pY2F0ZVBhaXI7YmluYXJ5M1I B YIKwYBBQUHAQsEggEzMIIBFTA+Bgg rB gEFBQcwBYy aH R0
cDovL3NpYTEuc3NwLN0cm9uZy1pZC5uZxQvQ0EvU1NQ LUNLBUExLVN JQS5wN2Mwg dIGCCsGAQUF
BzAFhoHFbGRhcDovL2Rp c jEuc3NwLN0cm9uZy1pZC5uZxQvY249QmV0cnVzdGVk JTIwUH JvZH Vj
dG1vb iUyMFNTUCUyMENB JTIwQTEsb3U9QmV0cnVzdGVk JTIwVVM1MjBjbmMsYz1VUz9jQUN1cnRpZmljYXR1O2Jp
bmFyeSxjcm9zc0N1cnRpZmljYXR1UGFpcjtiaW5hcnkwDgYDVR0PAQH/BAQDAgHGBM8GA1UdIwQY
MBAfK0MenVc5f0YXhM Dqwo/Zf05wL8MIG4BgNVHR8EgbAwga0wKgAooCaGJGh0dHA6Ly9odHRw
LmZwa2kuZ292L2Zj cGNhL2NhM yBDB/oH2ge4Z5bGhDcDovL2xkYX AuZnBraS5nb3YvY241
M2RGZWR1cmFsJT IwQ29tbW9u JT IwUG9saWN5JTIwQ0Esb3U1M2RGUETJLG81M2RVL1Mu JT IwR292
ZXJubWVu dC xj JTNkV VM/Y2VydG1maWhdGVsZxZvY2F0aW9uTG lzdAdB gNVHQ4EFgQUu6Tp uYML
MnIaI Q6qz0Udt xYjyA0wDQYJKoZIhvcNAQELBQADggEBAK+k+1bsJuVspfA+1t3cJ918AIi8Ra4
rECJ2NqVdR9K4QdfN Omg0zAW2yb p vJ3ZD8y7vVzkzdkXwJsgM ZMLKYK93d4I/TjsMyZMQFSW09fV
Txn9E19ivIdzO+R27tYK8L1KhK S0Q1I6kytzeXiWTwpXHH0Y SUFpLNOr30gZUsuoWhpg/sb7VfQ
s+T2fNzXRRw3mgwbqQcx3WfdfLmf wCZC4gcirw1N0Sfo2GqgIc1/OzEL93tjh20SX PwJLkF2WN4k
HUmR1MQE0X8yQ+WYt6g151qWKNXoQ Mm+TT2W3Y8tEOQGXd+nLChi wKQyPCL1L+EmFqyIN+11tv m
AxH6k1M=-----END CERTIFICATE-----

8.1.7 federal_common_policy_ca_cert.txt

-----BEGIN CERTIFICATE-----
MIIEY DCCA0igAwIBAgICATAwDQYJKoZIhvcNAQELBQA wWTELMAkGA1UEBhMCVVMxGDAWBgNVBAoT
D1UuUy4gR292ZXJubWVu dDENMasGA1UECxMER1BLSTEhMB8GA1UEAxMYRmVkJbCBDb21tb24g
UG9saWN5IENBMB4XDTEwMTIwMTE2NDUyN1oXDTMwMTIwMTE2NDUyN1o wWTELMAkGA1UEBhMCVVMx
GDAWBgNVBAoT D1UuUy4gR292ZXJubWVu dDENMasGA1UECxMER1BLSTEhMB8GA1UEAxMYRmVkJb
bCBDb21tb24gUG9saWN5IENBMB1I B IjANBgkqhkiG9w0BAQEFAOC A Q8AMIBCgKCAQE A2HX7NRY0
WkG/Wq9cMAQUHK14RLXqJup1YcfNNnn4fNi9KV FmWSHjeav uel6wLbCh1bI1F iPQzB6+Duir3MPJ
1hLxp3JoGDG4FyKyPn66CG3G/dFYLGmgA/Aqo/Y/ISU937cyxY4nsyO14FKzXZbpsLjFxZ+7xaBu
gkC7xScFNknWj1dpDDSPzyd6KgqjQV+NHQOGgxXgVcHFmCye7Bpy3EjBPvmE0oSCwRvDdDa3ucc2
Mnr4MrbQNq41G DGMUHMh nv6D0zC1JO PpwX7e7zjHH5IQip9y i+dpLzvhW86/c1TpyBLqtsgqyFO
HQ1O5piF5asRRI2dP8QjwOMUb7+nQIDAQABo4IBMDCCASwvDwYDVR0TAQH/BAUwAwEB/zCB6QYI
KwYBBQUHAQsEgdwwgdkwPwYIKwYBBQUHMAWG M2h0dHA6Ly9odHRwLmZwa2kuZ292L2Zj cGNhL2Nh
Q2VydHN Jc3N1ZWRCeWZj cGNhLnA3YzCB1QYIKwYBBQUHMAWG gYhsZGFwO18vbGRhcC5mcGtpLmdv
di9jb1GZWRlcmFsJT IwQ29tbW9u JT IwUG9saWN5JTIwQ0Esb3U9R1BLSSxvPVUuUy41MjBhB3Z1
cm5tZw50LG M9V VM/Y0FDZXJ0aWz pY2F0ZTtia w5hc nksY3Jvc3NDZXJ0aWz pY2F0ZVBhaXI7Ymlu
YXJ5MA4GA1UdDwEB/wQE AwIBBjAdB gNVHQ4EFgQuRQx6dVz185jEeZgOrCj91/TnAvwwDQYJKoZI
hvcNAQELBQADggEBAI9z2uF/gLGH9uwsz9GEYx728Yi3mvIRte9UrYpuGDco71wb509Qt2wmGCMi
TR0mRyDpCzzicGJxqxHPkYnos/UqoEfAFMtOQsHdA4b81db70V316rgVN dF9IU+7LQd3nyKf1tN
nJaK0K1yn9psM Qz4p09+c+iR3Ah6cFqgr2KBWfgAdKL13VTKQVZ HvenAT+0g3e01Cd+uKML80cgX
2BLhb94u6b2akfI8WpQukSKAiaGMW MyDeiYzDQK1Dn0KJnNR6obLB6jI/WNaNZvSr79PMUjBhHD
NxuaGQ/1j/RqDG8z2escC KIN47lQ A2EC/0rskqTcLe4qN JMhtyznGI8=-----END CERTIFICATE-----

8.1.8 veterans_affairs_device_ca_b2_cert.txt

-----BEGIN CERTIFICATE-----
MIHVTCCBj2gAwIBAgICHGawDQYJKoZIhvcNAQEfbQAwgYgxCzAJBgNVBAYTA1VTMRkwFwYDVQQK
ExBCZXRydxN0ZwQgVVmgSw5jMqwCgYDVQQLewNTU1AxJzA1BgNVBAsThkJ1dHJ1c3R1ZCBQcm9k
dWN0aW9uiFNtUCBDQSBBMTEnMCUGA1UEAxMeQmV0cnVzdGVkIFByb2R1YRpB24gU1NQIENBIEEX
MB4XDTA4MDgwNzE1MjQwMFoXDTE4MDgwNzE1MjI0N1owcjETMBEGCgmSJomT8ixkARkWA2dvdjES
MBAGCgmSJomT8ixkARkWAnZhMREwDwYDVQQLewhTZXJ2aN1czEMMAoGA1UECxMDUEtJMSYwJAYD
VQQDEx1WZXR1cmFucyBBZmZhaXJzIERldmljZSBDSQSBMjCCASIwDQYJKoZIhvcNAQEBBQADggEP
ADCCAQoCggEBALTxrfB9i65LB1P1CvdruZNIsSG3WY0JxNQfIxTBZqsOneWFnR2wElFzhkxvjQRx
vQAfqz1gBum5cM1+7BmoFF9ueRP5uQGF++f+2leQ7HE+5ccw9D1Q4wBt1E/zRrcOPqhQ9Usybq44
XC1neNvQ56nGyw/KxgyqgycUqqjDIqWOIdQ/e12jSxa5qCmrzdLsEFpx9kvuWz8Wvn4K5Vwov/Pb
EMhvOmdxpXwEBwUALqhBtBeq52N0UG1wgoJJRii0uR5T+bK8QJ+NF7vzmnReWudTFhV3av9Wzhu
7banQGcS66HBc1h22F1YDefq2yEHpgmPOBvv8EC+3I1DnNh519cCAwEAAsOCA9wwggPYMA8GA1Ud
EwEB/wQFMAMBAf8wTwYDVR0gBEgwRjAMBgpghkgBZQMCQMGMAwGCMCGSAf1AwIBAwcwDAYKIZI
AWUDAgEDCDAMBgphkgBZQMCQMNMAwGCMCGSAf1AwIBAxEwgE+BggRbgEFBQcBAQSCATAwgges
MDoGCCsGAQUBFzAChi5odHRwOi8vYWhMS5zc3Atc3Ryb25nLw1kLm51dC9DQS9TU1AtQ0EtQTEu
cDdjMIG2BggRbgEFBQcwAoBaBqWxkYXA6Ly9kaXIxLnNzcC1zdHJvbmcTaWQubmV0l2NuPUJ1dHJ1
c3R1ZCUyMFByb2R1Y3RpB241MjBTU1A1MjBDQSUyMEExLG91PUJ1dHJ1c3R1ZCUyMFByb2R1Y3Rp
b241MjBTU1A1MjBDQSUyMEExLG91PVNTUCxvPUJ1dHJ1c3R1ZCUyMFVTJTIwSW5jLGM9VVM/Y0FD
ZXJ0aWZpY2F0ZTtiaW5hcnkwNQYIKwYBBQUHAGGKWh0dHA6Ly9vY3NwMS5zc3Atc3Ryb25nLw1k
Lm51dC9TU1AtQ0EtQTEvMIHBggRbgEFBQcBCwsByjCBxzA7BggRbgEFBQcwA4YvaHR0cDovL2Fp
YTEuc3NwLXN0cm9uZy1pZC5uZXQvQ0EvVkfKzxZpY2DQSUyMEExLG91PUJ1dHJ1c3R1ZCUyMFByb2R1Y3Rp
oi8vZG1yMS5zc3Atc3Ryb25nLw1kLm51dC9jbj1WZXR1cmFucyUyMEFmZmFpcnM1MjBEZXZpY2U1
MjBDQSUyMEIyLG91PVBLSSxvdT1TZXJ2aWN1cykYz12YSxkYz1nb3Y/Y0FDZXJ0aWZpY2F0ZTti
aW5hcnkwDgYDVR0PAQH/BaQDaGhGMB8GA1UdiwQYMBaAFLuK6bmDCzJyG1EOqs9FHbcWI8gNMIIIB
BgyDVR0fBIH+MIH7MDWgM6Axhi9odHRwOi8vY2RwMS5zc3Atc3Ryb25nLw1kLm51dC9DRFAvU1NQ
LUNBLUExLmNybDCBwaCBvqCBu4aBuGxkYXA6Ly9kaXIxLnNzcC1zdHJvbmcTaWQubmV0l2NuJTnk
QmV0cnVzdGVkJT1wUHJvZHvjdGlvb1uyMFNTUCUyMENBjT1wQTEsb3U1M2RCZXRydXN0ZwQ1MjBQ
cm9kdWN0aW9uJT1wU1NQJTIwQ0E1MjBBMSxvdSuZzFNTUCxvJTNkQmV0cnVzdGVkJT1wVVM1MjBJ
bmMsYyUzzFVTp2N1cnRpZmljYXR1UmV2b2NhdG1vbkxpc3QwhQYDVR0OBBYEFIGUNZ4qqHdgI2bs
Kp1uz7Z1GVBdMA0GCSqGS1b3DQEBBQUAA4IBAQBTnv1RJn0nM90ddS1Q6dX4nEB6LU7UEjESjgbt
b1Nx0IPcw+muXo4NYExTLIRj1kOI/MSaITk0UAnSALFFLPom36SdSQ9rjxKEkqO+4/FCCScH7wE
Crw5k1AfRdsqr5cgDj1fj+sPMCYpMX0vydIiUwkpoqGKQVA0V8A19/Z1VpmpuvWc8koggfs+Hly6
1g3JsJ2jiLFkSO+sbwN9ZqOQTOQgFPFbScZJKV1g8jTEo0YoX/w+nShjK5EMJwIz6yo1J8wvmjcN
1V1S3hkjxrOOqsf0/I+nz2hgybR/nkft3zk1zKeH4NPmug0F48mGSRsnkHzksgE8iSaCPkz3snJQ
-----END CERTIFICATE-----

8.1.9 vaww.esrdev.aac.va.gov_cert.txt

-----BEGIN CERTIFICATE-----
MIHizCCBnOgAwIBAgIDBTdaMA0GCSqGSIB3DQEBCwUAMHIxEzARBgoJkiaJk/IzZAEZFgNnb3YxEjAQBgoJkiaJk/IzZAEZFgJ2YTERMA8GA1UECxMIU2VydmljZXmxDDAKBqNVBAsTA1BLSTEEmMCQGA1UEAxMdVmVOZKJhbnMgQWZmYWlcyBeZXZpy2UGQ0EgQjIwHhcNMTUwOTE0MTcxNDI3WhcNMTgwODA3MTUyMjQ2WjBcMRMwEQYKCZImiZPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYCdmExEDAOBgnVBAsTB2R1dmljZXmxHzAdBgNVBAMTFnZhd3cuZXNyZGV2LmFhYy52YS5nb3YwggEiMA0GCSqGSIB3DQEBAQUAA4IBDwAwggEKAoIBAQCKYcAl0+9HukeVKIzrs0gKOhDskC1bu0oOJDGjc0t72mOz2rgj4+79J6AEovcy7nYiAsGYEmFmhwD13v3+aLk8E7P8xf5KFENycYhuxBI611100CISs7Wk2hprkGHR0HkTyxiuUknwzhQ+9qm3CqMGDVhXqNuEwWQoJ3us22drK4NBrZn+dMTeT1KHSo9QeoICwcBqqoeoKWlOF17UlnaAaCGrABMoncEO+b9QDZB5i83IxMuZFlhwve6JHsOXKe0t3H8WbKy9M3+kOtcxMTMOvesj7p+3mqDn/ckoRyDkMHC0Szs3jSpRr43IYIpDU4R2SOxgVq001f7/J+WIHrAgMBAAGjggQ+MIEojoCB7AYDVR0RBIhKMHghZ2YXd3LmVzcmRldi5hYWMDmEuZ292ghh2YXd3LmVzcmRldjMwLmFhYy52YS5nb3aCGHzh3cuZXNyZGV2MzEuYWFjLnZhLmdvdoIYdmF3dy51c3JkZXY0MC5hYWMDmEuZ292ghh2V2aGF1c3J3ZWlzLmFhYy52YS5nb3aCF3Zhd3cuZXNyZGV2MS5hYWMDmEuZ292ghd2YXd3LmVzcmRldjIuYWFjLnZhLmdvdoIYdmF3dy51c3JkZXYzLmFhYy52YS5nb3aCF3Zhd3cuZXNyZGV2NC5hYWMDmEuZ292MbcGA1UdIAQQMA4wDAYKYIZIAWUDAgEDCDCCATAGCCsGAQUFBwEBBIBIbjCCAR4wOwYIKwYBQUHMAKGL2h0dHA6Ly9haWExLnNzc1zdHJvbmctaWQubmV0L0NBL1ZBZGV2aWN1Q0EucDdjMIGABgrBqEFBQcwAoZ0bGRhcDovL2RcpjEuc3NwLN0cm9uZy1pZC5uZXQvY249VmV0ZXJhbnnM1MjBBZmZhaXJzJTIwRGV2aWN1JTlwiQ0E1MjBCMixvdT1QS0ksb3U9U2VydmljZXMsZGM9dmEsZGM9Z292P2NBQ2VydGlmaWNhdGUwIwYIKwYBQUHMAGGF2h0dHA6Ly9vY3NwLnBras52YS5nb3YvMDcGCCsGAQUFBzABhitodHRwOi8vb2NzcDEuc3NwLN0cm9uZy1pZC5uZXQvVketU1NQLUNBLUiMA4GA1UdDwEB/wQEAWIFoDAnBgNVHSUEIDAeBgggrBqEFBQcDAQYIKwYBBQUHAWIGCGCGSAF1AwYHMB8GA1UdIwQYMBaAFIGUNZ4qqHdgI2bsKp1uz71GVbdMIIBgQYDVR0fBIIBeDCCAXQwMKAuocGKmh0dHA6Ly9jcmwucGtpLnZhLmdvdi9QS0kvQ1JML3ZhZGV2aWN1LmNydbB0oOHkgcIZubGRhcDovL2xkYXAucGtpLnZhLmdvdi9jbiUzzFNTUEiyQUUsY241M2RDRFAsy241M2RQS0ksY241M2RTZXJ2aWN1cyxkYyUzzHZhLGRjJTNkZ292P2N1cnRpZmljYXR1UmV2b2NhdG1vbkxpc3QwnKAyoDCGLmh0dHA6Ly9jZHaxLnNzc1zdHJvbmctaWQubmV0L0NEUC92YWRldmljZS5jcmwwgZoggZCggY2GgYpsZGFwOi8vZG1yMS5zc3Atc3Ryb25nLW1kLm51dC9jbiUzzFZ1dGVyyW5zJTIwQwZmYWl1cyUyMERldmljZSUyMENBTIwQjIsb3U1M2RQS0ksb3U1M2RTZXJ2aWN1cyxkYyUzzHZhLGRjJTNkZ292P2N1cnRpZmljYXR1UmV2b2NhdG1vbkxpc3QwHQYDVR0OBByEFFauWBgfqlovaQ/3SJEigCTXVyhMA0GCSqGSIB3DQEBCwUA4IBAQAYuPXvhL4/EIzooFV5fAbwm822Vz7U49ZF/JSEBQqGQBhmwbFCu7wk1iu40Efkjz2nsFAeGzijfh1eaTiLC1q+wph5ez13kzbJNAUTmPlJZQfVGhx0rFQAvOqFs5YNakKkthHnbQAWvJ1n1Bje1on6YFu3L5eeJDwdO2CUBuoK/fc/m8Nxe47UTsoRG1uin6Y8P9QqlpJT6HqSHqsqanLkncU3wTh2vyJUtfMuJq0nBDvBg3PCxtoU2/wqkdFY+UEKHTjYXXkxPuXNVHQ6sdQNq3y584edm9phxMW2rmbxEN0oN7oQWUPBEAcrtkR84MxM1w6WTSh16YMV/dQzho-----END CERTIFICATE-----

8.1.10 vaww.esrstage1a.aac.va.gov.pem

-----BEGIN CERTIFICATE-----
MIIFiDCCBHCgAwIBAgIHPQAAAAC3pjANBgkqhkiG9w0BAQsFADBKMRMwEQYKCZIm
izPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYCdmExHzAdBgNVBAMTF1ZBLUlu
dGVybmfSLVMyLU1DQTETdjEwHhcNMTcwMzE0MjA1NjQ3WhcNMjAwMzEzMjA1NjQ3
WjCBwDELMAkGA1UEBhMCVVmxDjAMBgNVBAgTBVRleGFzMQ8wDQYDVQQHEwZBdXN0
aW4xKjAoBgNVBAoTIVVTIERlCGFydG11bnQgb2YgVmV0ZXJhbnMgQWZmYWlyczEN
MASGA1UECxMEQU1UQzEjMCEGA1UEAxMadmF3dy5lc3JzdGFnZTFhLmFhYy52YS5n
b3YxMDAuBgkqhkiG9w0BCQEWIWNkY293ZWJs2dpY2FkbW1uaXN0cmF0b3JzQHZh
LmdvdjCCASIwDQYJKoZIhvCNQEBBQADggEPADCCAQoCggEBAPvu747uobthNU4I
8G0jiQ2R3WY2F+LWYznx+6xaPSUyaawXZ8heBNng05CbkyWhQPpuDBAjpUjiYX9Q
9AM1LhJppZEi8NmBLFkojISALE1+3LM8NhFnA1wNcrMSjDY2HL68XZ77VKjgcJ
qFnF8Kd1deGe9fpDnWXDWITHh02HzYojKu415jb+Gicjzb/rI+RoYftY6MDQpLcu
1tVv9SXrnDLkeb+3fKOhmrecvUhFwdYClx1V5o55iDipZLLSxAAw0RHho8wXxBm
7J7c5SN150YV5Dsido6Ui4Rroe2ewiizQsVKNe9M0sw2agIUsx+LhIY49S/s/Nz1
hcYs2qUCAwEEAaOCAfowggH2MASGA1UdDwQEAWiFoDBYBqNVHREEUTBPghp2YXd3
LmVzcN0YWDlMWEmYWFjLnZhLmdvdIoadmF3dy5lc3JzdGFnZTFhLmFhYy52YS5n
b3aCFXzoYWWzcdlyjYuYWFjLnZhLmdvdjAdBgNVHQ4EFgQUnkF4Y5jfPVwdOyv/
XY1jZLS7r/YWYDVR0JBBgwFoAUG23f6z314g3vFrHQ319YGlB5OwsSQYDVR0f
BEIwQDA+oDygOoY4aHR0cDovL2Nybc5wa2kudmEuZ292L3BraS9jcmvvVketSW50
ZXJuYWwtUzItSUNBMS12MS5jcmwwewYIKwYBBQHUAEbzbMtMEcGCCsGAQUBzAC
hjtodHRwOi8vYWhLnBraS52YS5nb3YvcGtpL2FpYS92YS9WS1JbnR1cm5hbC1T
Mi1JQ0ExLXYxLmNlcjAiBgggrBgfBQcwAYYWaHR0cDovL29jc3AucGtpLnZhLmdv
djA9BgkrBgeEAYI3FQcEMDAuBiYrBgeEAYI3FQiByMMzgfnwBoGlnw2E4IEIhcKq
SwaDgp9ggeCLUgIBZAIBEjAdBgNVHSUEFjAUBggrBgfBQcDAgYIKwYBBQHU AwEw
JwYJKwYBBAGCNxUKBbowGDAKBggRgEfBQcDAjAKBggRgEfBQcDATANBgkqhkiG
9w0BAQsFAAOCAQEAhmljRtWAEQStJz2uPw8piDho8i1t3dz2j2/Zy0bmhb9e1Fg
jg4xR2qv4CpNuNinxgMhsrlXVtroy9UVK3CkmT6Js5DFuR0yQ9u4Ws dM0NxvxEa
Keh3hPwBRelcSKbMefn071CoBMLz9qsf9gMQ34vh1KzmVxfnt5FBK8LNE/a6uoDv
FxovRmOAA/qMGMZdMZEmb144+hAngFbFmwXkOFDQ01DBG8SAYfk1UNfBw92u+3jV
UApxi9bvnulp8UyHsG9QEa+fs49v1qhp4UGiY7CWLhnZbaHNLoYhpioVSruPnMa+
a4vuHW2QSxKVtY+2P3gJpXoUlSLoAJJtKi2njw==
-----END CERTIFICATE-----

8.1.11 vaww.esrstage1b.aac.va.gov.pem

-----BEGIN CERTIFICATE-----
MIIFiDCCBHCgAwIBAgIHPQAAAAC3pzANBgkqhkiG9w0BAQsFADBKMRMwEQYKCZIm
izPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRYCdmExHzAdBgNVBAMTF1ZBLUlu
dGVybmfSLVMyLU1DQTETdjEwHhcNMTcwMzE0MjEwNzA5WhcNMjAwMzEzMjEwNzA5
WjCBwDELMAkGA1UEBhMCVVmxDjAMBgNVBAgTBVRleGFzMQ8wDQYDVQQHEwZBdXN0
aW4xKjAoBgNVBAoTIVVTIERlCGFydG11bnQgb2YgVmV0ZXJhbnMgQWZmYWlyczEN
MASGA1UECxMEQU1UQzEjMCEGA1UEAxMadmF3dy5lc3JzdGFnZTFiLmFhYy52YS5n
b3YxMDAuBgkqhkiG9w0BCQEWIWNkY293ZWJs2dpY2FkbW1uaXN0cmF0b3JzQHZh
LmdvdjCCASIwDQYJKoZIhvCNQEBBQADggEPADCCAQoCggEBACKj1U0RxzhQg8ij
tPGY1wH7q5TDfsSvQuoPBbgOF53MYR8VotqM0JViggyP4G/TmYJ/HMvaP/2K1tS5
60hHGIPMg01Xa9ZbxhR6u8rp/A7Qix96jkWzHuuP4OEijW9j23xGcfx31LaeL4HF
amhrYnIDpYBpkqltVNlHBQinJE/FcReCpbhHrHFJyr0L+dmkjQWC/CL44qtsIeo
dM67p87NswoKcraiRsBw+CosJFZH6WGKgTFDuYzn9ZNpPeBRBUmds770SCAKukGY
1WIFBXm1AjckGjVu0E9f5N0D8tSpfrynxpnSIOChCtkYLwuj14oGj0Iuee9qsn5
jKyvulcCAwEEAaOCAfowggH2MASGA1UdDwQEAWiFoDBYBqNVHREEUTBPghp2YXd3
LmVzcN0YWDlMWEmYWFjLnZhLmdvdIoadmF3dy5lc3JzdGFnZTFiLmFhYy52YS5n
b3aCFXzoYWWzcdlyjQuYWFjLnZhLmdvdjAdBgNVHQ4EFgQU61ixAn4MoiuQ4n41
gmSf+uKn4TUwHwYDVR0jBBgwFoAUG23f6z314g3vFrHQ319YGlB5OwsSQYDVR0f
BEIwQDA+oDygOoY4aHR0cDovL2Nybc5wa2kudmEuZ292L3BraS9jcmvvVketSW50
ZXJuYWwtUzItSUNBMS12MS5jcmwwewYIKwYBBQHUAEbzbMtMEcGCCsGAQUBzAC
hjtodHRwOi8vYWhLnBraS52YS5nb3YvcGtpL2FpYS92YS9WS1JbnR1cm5hbC1T
Mi1JQ0ExLXYxLmNlcjAiBgggrBgfBQcwAYYWaHR0cDovL29jc3AucGtpLnZhLmdv
djA9BgkrBgeEAYI3FQcEMDAuBiYrBgeEAYI3FQiByMMzgfnwBoGlnw2E4IEIhcKq
SwaDgp9ggeCLUgIBZAIBEjAdBgNVHSUEFjAUBggrBgfBQcDAgYIKwYBBQHU AwEw
JwYJKwYBBAGCNxUKBbowGDAKBggRgEfBQcDAjAKBggRgEfBQcDATANBgkqhkiG
9w0BAQsFAAOCAQEAFNLz/wWJSdzIVUGd4bzXTAXktnnPlanNirLbW3qNoWyilft
4uNL6E5LFsDTMohvwjOGHaphdJmAp9HD4ZJ1TWXb1XNxe2yPa6jCKspJvc2j421s
fws0ZxOueels/XQZWNjs6qbEOOsJ4PtWOb1Myq/1V1tTWAOTzu3snjH1pVyHmHZ6
3514mHmZJtHmEV1Dg3DzrTvw0ejzgnq3MpVn25Np+Msi0uyLT8qcUjhWgrJS2Aw5
2qyA2n9vfQTcmg5U6eSyzJ14gCoG5xhZaHamTW4FySAwmcqKyjM4hkySTSKKLqsZ
5Q65eFKajsUIW+jxD63HuiweHP8vrzl/4M1vkg==
-----END CERTIFICATE-----

8.1.12 vaww.esrpre-prod.aac.va.gov.pem

-----BEGIN CERTIFICATE-----
MIIFojCCBIqgAwIBAgIHPQAAAADC6jANBgkqhkiG9w0BAQsFADBKM RMwEQYKCZIm
iZPyLGQBGRYDZ292MRIwEAYKCZImiZPyLGQBGRY CdmExHzAdBgNVBAMTF1ZBLUlu
dGVyb mFsLVM MyLU1DQTEtdjEwHhcNMTcwNDA0MTEz MzAxWhcNMjAwNDAzMT EzMzAx
WjCBwTELMAkGA1UEBhMCVVMx DjAMBgNVBAgTBVRleGFzMQ8wDQYDVQQHEwZBdXN0
aW4xKjAoBgNVBAoTIVVTIERl cGFydG11bnQgb2YgVmV0ZXJhb nMgQWZmYWlyczEN
MASGA1UECxMEQU1UQzEkMCIGA1UEAxMbdmF3dy5lc3JwcmUtcHJvZC5hYW MdmEu
Z292MTAwLgYJKoZIhv cNAQkBF iFjZGNvd2VibG9naWNhZG1pbmlzdHJhdG9yc0B2
YS5nb3Ywg gEiMA0GCSqGSIB3DQEBAQUAA4IBDwAwggEKAoIBAQDSSFJ9AnbkaLXB
J7ngjAHZGn kTQM8eK13k7iYUKLYjh mH9ZuIiYQ QEVqh1bsM+Y1vdFXLj c1Vg7P10
ntkSG/QBz6VDhd8RkeOEkLmT4/88VZn1bGRAAp Vp3UM6dy5r9fkN0yRgoUBVqs
hPaj0m2Z6UQkKz589eS01CCWSWz15K6dFDFvI qmmb0yyfvZ8+1P7BqbI7cOsJAhx
5sDzBKAR3JVsGM+7f5oX/euIyuRagrBcbQPrG6Moc5owEk h6t1s2+m6BiVHENIBn
sGHaIW hg+b1zsQ9vwYjc/9bGHJ7D9281a/LRPersWKL2uS qQcHA7PfJm8wLpkO5Y
+/O7iyNVAgMBAAGj ggITMIICDzALBgNVHQ8EBAMCBaA w cQYDVR0RBGowaiI bdmF3
dy5lc3JwcmUtcHJvZC5hYW MdmEuZ292gh t2YX d3LmVzc nByZS1wcm9kLmFhYy52
YS5nb3aCFXzoY WVzcd1YjcuWFjLnZhLmdvd oIVdmh hZ XNy d2ViOC5hYW MdmEu
Z292MB0GA1UdQgQWBQJAFTU t3mxMbBdr/ODTQUQMY2WBjAfBgNVHSMEGDAw gBQb
bd/rPeXiDe8WsdDeX1gaVsvk7DBJBgNVHR8EQjBAMD6gPKA6hj hodHRwOi8vY3Js
LnBraS52YS5nb3YvcGtpL2Nybc9WQS1JbnR1cm5hbC1TM11JQ0ExLXYxLmNy bDB7
BggrB gEFBQcBAQRvMG0wRwYIKwYBBQUHMAKG02h0dHA6Ly9haWEucGtpLnZhLmdv
di9wa2kvYWhl3ZhL1ZBLU1udGv ybmFsLVMyL U1DQTEtdjEuY2V yMCI GCCsGAQUF
BzAbhhZodHRwOi8vb2Nzcc5wa2kudmEuZ292MD0GCSSgAQQB gjcVBwQwMC4GJisG
AQQB gjcVC IHIwzOB+fAGGaWF DYTggQi FwqpLB oOCn2CB4ItS AgFkAgESMB0GA1UD
JQQWMBQGCCsGAQUF BwMCBgg rBqEFBQc DATA nBgrBqEEAYI3FQoEGjAYMAoGCCsG
AQUFBwMCMAoGCCsGAQUF BwMBMA0GCSqGSIB3DQEBCwUAA4IBAQAgJ6f4AoV71ndB
myYN1S76+rZGccqOoHKSF07406os8b8qcRSc tJOIRxzWME8wi y55PHS5nkh n0wm
oWna2P6Efec2FQ8ZURsb i8IefwU X7ISWJ99+6C+1L6VrCh1hEQOPXT Rdbqm8H3dR
cvh1HNQ3MtXuswI3sFvBqmYFsXsOtRwiRzFuiT7K4v5kW3Kkre5bsjSLBXq1VFjT
PTVMIcH3QgP6hbjfgJtQoHfDoQFFSa6DjbGvja4Y+rQMqiBC1VN1ZLG44VqsDlyC
u5AO830gi/i1gf30Iyv1J1/mXJT1LdAUZjG5dPt wT4/Jx3Kqj7cDWdy54ddD1RJb
IyXeTQaF
-----END CERTIFICATE-----

8.1.13 das-test.va.gov.pem

-----BEGIN CERTIFICATE-----
MIIG7TCCBdWgAwIBAgIDBZs1mA0GCSqGS1b3DQEBCwUAMHIxEzARBgoJkiaJk/I
sZAEZFgJ2YTERMA8GA1UECxMIU2VydmljZXMX
DDAKBgNVBAsTA1BLSTEmMCQGA1UEAxMdVmV0ZXJhbnMgQWZmYWlycyBEZXZpY2Ug
Q0EgQjIwHhcNMTYwNjEwMTMxOTUwWhcNMtGwODA3MTUyMjQ2WjBVMRMwEQYKCZIm
iZPyLGQBGRYDZ292MR1wEAYKCZImiZPyLGQBGRYCdmExEDAOBgNVBAsTB2Rldmlj
ZXMXGDAWBgNVBAMTD2Rhcy10ZXN0LnZhLmdvdjCCASIwDQYJKoZIhvcNAQEBBQAD
ggEPADCCAQoCggEBAKJg1wPGT7Wr1lFYJ5HkivoJkwR3nulq6n9hD3m+ENX1RbDP
HOrTxOXg2YpSK/ORDvBN4OXD+NVaVyy4XyWzG2ZIF06wGX9ooGTU2EA/MMKh3ts
XDWB0IEGjDQ3CuNCZ2J3FF+SSBYtRFRI1CgYt/77kC4GafjDsFy6MfiXdis9O6R
RSaXPCFdF7qRqq3Lx8QrlsP5rYj4f95HRGKqn4X/5S1z5Us8O+ZReWALUAMtAWr6
ZZB8CYhcSxPsvPw7wN15IYjKGeg9/DaXeszHFK7tW3VPOg6/g8gSVsOBV1VayUWx
IjzeXen1DWpusmLkD7a9aVeBLE1+w0amYXmGEUMCAwEAAaOC46cwggQjMFYGA1Ud
EQRPM2CD2Rhcy10ZXN0LnZhLmdvdjcdmFhdXnkYXNhCBpbnQwMDIuYWFjLnZh
LmdvdjcdmFhdXnkYXNhCBpbnQwMDMuYWFjLnZhLmdvdjAXBgNVHSAEEADAoMawG
CmGSASF1AwIBAwgwggEwBgrBgfFBQcBAQSCASIwggEeMDsGCCsGAQUFBzAChi9o
dHRwoi8vYwlhMS5zc3Atc3Ryb25nLw1kLm51dC9DQS9WQWRldmljZUNBLnA3YzCB
gAYIKwYBQUHMAKGdGxkYXA6Ly9kaXIxLnNzcC1zdHJvbmctaWQubmV0L2NuPVZ1
dGVyYW5zJTIwQWZmYWlycyUyMER1dmljZSUyMENBJTlWQjIsb3U9UEtJLG91PVN1
cnZpY2VzLGRjPXZhLGRjPWdvdj9jQUN1cnRpZmljYXR1CMGCCsGAQUFBzABhhdo
dHRwoi8vb2NzcC5wa2kudmEuZ292LzA3BgrBgfFBQcwAYYraHR0cDovL29jc3Ax
LnNzcC1zdHJvbmctaWQubmV0L1ZBLVNTUC1DQS1CMjAOBgNVHQ8BAf8EBAMCBaAw
JwYDVRO1BCAwHgYIKwYBQUHawEGCCsGAQUFBwMCBghhgkgBZQMGBzAfBgNVHSM
GD4AwGBSB1DWeKgh3YCNm7Cqdb8+2dR1QXTCCAYEGA1UdHwSCAXgwggFOMDCgLqAs
hipodHRwoi8vY3JsLnBraS52YS5nb3YvUEtJL0NSTC92YWR1dmljZS5jcmwwdKBy
oHCgbmxkYXA6Ly9sZGFwLnBraS52YS5nb3YvY241M2RTU1BCMkFFLGnuJTNkQ0RQ
LGNujJTNkUEtJLGNujJTNkU2VydmljZXMsZGM1M2R2YSxkYyUzZGdvdj9jZXJ0aWZp
Y2F0ZVJ1dm9jYXRpb25MaXN0MDsgMqAwhi5odHRwOi8vY2RwMS5zc3Atc3Ryb25n
Lw1kLm51dC9DRFAvdmFkZXZpY2UuY3JsMIGoIIGNhoGKbGRhcDovL2RpjcEu
c3NwLN0cm9uZy1pZC5uZXQvY241M2RWZXr1cmFucyUyMEFmZmFpcnM1MjBEZXZp
Y2U1MjBDQSuYMBIyLG91JTNkUEtJLG91JTNkU2VydmljZXMsZGM1M2R2YSxkYyUz
ZGdvdj9jZXJ0aWZpY2F0ZVJ1dm9jYXRpb25MaXN0MB0GA1UdDgQWBBRJxg3+eZpU
APnLc56q/SjzkLYrFzANBgkqhkiG9w0BAQsFAAOCAQEAYW2Jns8JhfoGH0DTQrYr
bw82XEjGW/jwGlrVzsRNrt3ncBLdj2Zis0QjD09mArG5s/xHpa35aQZjUGQAgv/t
wZ3j111H0jZIAch6tn7YRzhpqA7u5of8eUTpuAeJtVFeIo9RUR871DWWyPWPW7
D4LGcLB4HpfBb/4BMXQnM1cyCsXYSkXDQH1+xPzUUQkJpi7JRdoMLPxZ2r9ewJf
dDbn8FEnxmNkI15G7qCmaW2cmfitnsJ8hoZC+rLL7B3+0/kzZL3O2yzX2WXmUWzk
Z3MF3C9K+LOWsrTwVUOkivJL6xrbI6j2dOGpgShDnn7d5+ftgHsXi3GdbEHYx2Ah
4w==
-----END CERTIFICATE-----

8.1.14 das-sqa.va.gov.pem

-----BEGIN CERTIFICATE-----
MIIG7DCCBdSgAwIBAgIDBbrogMA0GCSqGSIb3DQEBCwUAMHIxEzARBgoJkiaJk/I
sZAEZFgJ2YTERMA8GA1UECxMIU2VydmljZXmx
DDAKBgNVBAsTA1BLSTEmCQGA1UEAxMdVmV0ZXJhbnMgQWZmYWlycyBEZXZpY2Ug
Q0EgQjIwHhcNMTYwODI2MTY0NzE3WhcNMNTgwODA3MTUyMjQ2WjBUMRMwEQYKCZIm
iZPyLGQBGRYDZ292MRlweAYKCZImiZPyLGQBGRYCdmExEDAOBgNVBAsTB2Rldmlj
ZXmxFzAVBgNVBAMTDmRhcy1zcWEudmEuZ292MIIBIjANBgkqhkiG9w0BAQEFAAO
AQ8AMIIIBCgKCAQEaqRt193fnT1YYwqxIC6XMccOosJorP1Wop43czuqGH0P3Z2uj
f5ubSi8jfVqQGhuWVJ6mjAxJQevjpuFddu3GGWMVvofa96wA852qdMcXtj8z9exH
L1rN86o+8CkU7yj9iFsassSWf0a0CLK3jz+GiGakmtztnoZoXc2T+e3NaJhASIdjU
IZH5hVB4qi4PgmcW6rL7SAoetcMtAFS0DK8s+VLxSeAzDjvybAc6jXgUXDYNK
Dr3HtWDy3AKz3kOkva4ipDnxrcNPKJN01EM+RMKy7s23BjmBq3EHnB+4fT6t62DL
OJhKq7jqJCBLNeEHnth7+i3VVLON4eEqPxQIDAQABo4IDpzCCA6MwVgYDVR0R
BE8wTYIOZGFzLXNxYS52YS5nb3aCHZhYXVzZGFzYXBwc3PhMDAxLmFhYy52YS5n
b3aCHXZhYXVzZGFzYXBwc3FhMDAyLmFhYy52YS5nb3YgMBcGA1UdIAQQMA4wDAYK
YZIAWUDAgEDCDCCATAGCCsGAQUFBwEBBIIBIjCCAR4wOwYIKwYBBQUHMAKGL2h0
dHA6Ly9haWEExLnNzcC1zdHJvbmctaWQubmVOL0NBL1ZBZGV2aN1Q0EucDdjMIGA
BggrBggFBQcwAoZ0bGRhcDovl2RpjcEuc3NwLXN0cm9uZylpZC5uZXQvY249VmV0
ZXJhbnnM1MjBBZmZhaJzJTIwRGv2aWN1JTIwQ0ElMjBCmixvdT1QS0ksb3U9U2V
dm1jZXMsZGM9dmEsZGM9Z292P2NBQ2VydG1maWNhdGUwIwYIKwYBBQUHMAFF2h0
dHA6Ly9vY3NwLnBraS52YS5nb3YvMDcGCCsGAQUFBzABhitodHRwOi8vb2NzcDEu
c3NwLXN0cm9uZy1pZC5uZXQvVketU1NQLUNBLUiYMA4GA1UdDwEB/wQEAvIFoDAn
BgNVHSEIDAeBggrBggFBQcDAQYIKwYBBQUHAWIGCGCGSAF1AwYHMB8GA1UdIwQY
MBAfFIGUNZ4qqHdgI2bsKp1uz7Z1GVBdMIIbgQYDVR0fbIIbeDCCAXQwMKAuocYg
Kmh0dHA6Ly9jcmwucGtpLnZhLmdvdi9QS0kvQ1JML3zhZGV2aWN1LmNybdB0oHKg
cIZubGRhcDovLzxKYXAucGtpLnZhLmdvdi9jbiUzzFNTUEiyQUUsY241M2RDRFAs
Y241M2RQS0ksY241M2RTZXJ2aWN1cyxkYyUzHZhLGRjJTNkZ292P2N1cnRpZmlj
YXR1UmV2b2NhgdG1vbkxpc3QwNKAyodCGLmh0dHA6Ly9jZHAxLnNzcC1zdHJvbmc
taWQubmV0L0NEUC92YWR1dm1jZS5jcmwgZoggZCggY2GgYpsZGFwOi8vZG1yMS5z
c3Atc3Ryb25hLW1kLm5ldc9jbiUzZfZ1dGVyYW5zJTIwQWZmYWlycyUyMERldmlj
ZSUyMENBJTIwQjIsb3U1M2RQS0ksb3U1M2RTZXJ2aWN1cyxkYyUzHZhLGRjJTNk
Z292P2N1cnRpZmljYXR1UmV2b2NhgdG1vbkxpc3QwHQYDVR0OBByEFM46SuxQAM8n
ayR/h1Jgt/b0caNbMA0GCSqGSIb3DQEBCwUAA4IBAQAOz+ie401LRty9CTpt7qtm
CCg805Msj5PDTh2QM2nX+VRiwV3cMldgsoK0gr9SKvjx+8sArMQLkzC21XavuwVh
Qn42mKm1XJvk3kbJx7Na0tg+8etepzHv1tfORJ1taCt1NTPIU8IBAxZWsYh81218
k8u7/KtnsK6zqiBRAoNloovM120CDxeWnFRzSLrTV91Z5V+gr1K1EIS3WkiHO7d+n
wqYnZB4fA0mjJ83Mrt8IxITZTP8Qn1LoyPR/vfoqOUamxRBWlIo4wTvEvN6+9hJ3
GQhfO9E/17v51vh7Wor58X+iRIBvj04PyU9PB8/ZYTst/t5IoucbMCir77ZEk0B
-----END CERTIFICATE-----

8.1.15 das.va.gov.pem

```
-----BEGIN CERTIFICATE-----  
MIIEhzCCBmOgAwIBAgIDBFJ1MA0GCSqGSIb3DQEBCwUAMHIxEzARBgoJkiaJk/I  
sZAEZFgNnb3YxEjAQBgoJkiaJk/I sZAEZFgJ2YTERMA8GA1UECxMIU2VydmljZXMx  
DDAKBgNVBAsTA1BLSTEmMCQGA1UEAxMdVmV0ZXJhbnMgQWZmYWlycyBEZXZpY2Ug  
Q0EgQjIwHhcNMTCwMTk1MTE1WhcNMTCwODA3MTUyMjQ2WjBQMRMwEQYKCZIm  
iZPyLGQBGRYDZ292MRlweAYKCZImiZPyLGQBGRYCdmExEDAOBgNVBAsTB2Rldmlj  
ZXMxEzARBgNVBAMTCmRhcy52YS5nb3YwggEiMA0GCSqGSIb3DQEBAQUAA4IBDwAw  
ggEKAoIBAQDZSc8gGHDms81rMeAffccObXAmUPpiG49PECDwNnIkPu6oSd3xEUuZ  
9AWR7S+tR8yzca2G8GaJj0OQxgT2C4vz2nniuNtEkA1sTf2eNbMN7kcEo6SJX  
P+GUEmpszqxVi0i0nzvOieFkfVfhu5rxI5fwUdnxYj7DErCMTiQt1GAvEittYK5  
pZJSvGuth+VHGVD3u6z1L1Gx+2z0DZYUJriB9nX0JzTAAPFr9maxac5qMwAwbNz  
3bcpu1myOaYkMHFeIBU6qLs8voQ1i/rUlg6dDAK0amt+dvNYA4q2g+HMoOXRxj  
yzut+1oAMc8rzjBCJuJiAX4hJanLV7KnAgMBAAGjggQ6M1ENjCB6AYDVRORBIHg  
MIHdggpkYXMu dmEuZ292ghx2YWF1c2Rhc2FwcHJwZDAwMS5hYWMu dmEuZ292ghx2  
YWF1c2Rhc2FwcHByZDAwMi5hYWMu dmEuZ292ghx2YWF1c2Rhc2FwcHByZDAwMy5h  
YWMu dmEuZ292ghx2YWF1c2Rhc2FwcHByZDAwNC5hYWMu dmEuZ292ghx2YWF1c2Rhc  
2FwcHByZDAwNS5hYWMu dmEuZ292ghx2YWF1c2Rhc2FwcHByZDAwNi5hYWMu dmEu  
Z292ght2YWF1c2Rhc2FwcHByZDQzLmFhYy52YS5nb3YwFwYDVR0gBBAwDjAMBpg  
hkgBZQMCAQMIMIIBAYIKwYBBQHUQAEEggEiMII BHjA7BgggrBgEFBQcwAoYvaHR0  
cDovL2FpYTEuc3NwLXN0cm9uZy1pZC5uZXQvQ0EvVkJkZxZpY2VDQS5wN2MwgYAG  
CCsGAQUFBzAChnRsZGFwOi8vZGlyMS5zc3Atc3Ryb25nLw1kLm51dC9jb1WZXr1  
cmFucyUyMEFmZmFpcnM1MjBEZxZpY2U1MjBDQSuYMEIyLG91FVBLSsxvdT1TZXJ2  
aWN1cyxkYz12YSxkYz1nb3Y/Y0FDZXJ0aWzpy2F0ZTAjBgggrBgEFBQcwAYYXaHR0  
cDovL29jc3AucGtpLnZhLmdvdi8wNwYIKwYBBQHUQAEGgEiMII BHjA7BgggrBgEFBQcwAoYvaHR0  
c3Atc3Ryb25nLw1kLm51dC9wQS1TU1AtQ0EtQjIwDgYDVR0PAQH/BAQDAgWgMCCG  
A1UdJQQgMB4GCCsGAQUFBwMBBgggrBgEFBQcDAgYIYZIAWUDBgcwHwYDVR0jBggw  
FOAUgZQ1niqod2AjZuwqnW7PtNUZUF0wggGBBgNVHR8EggF4MIIBdDAwoC6gLIYq  
aHR0cDovL2NybC5wa2kudmEuZ292L1BLSS9DUkwvdmFkZxZpY2UuY3JsmHSGcqBw  
hm5sZGFwOi8vbGRhcC5wa2kudmEuZ292L2NuJTNkU1NQQjJBRSxjbiUzzENEUCxj  
biUzzFBLSsxjbiUzzFN1cnZpY2VzLGrjJTNkdmEsZGM1M2Rnb3Y/Y2VydGlmaWNh  
dGVsZXZvY2F0aW9uTG1zdDA0cDKgMIYuaHR0cDovL2NkcDEuc3NwLXN0cm9uZy1p  
ZC5uZXQv0RQ13ZhZGV2aN1lmNybdCBk6CbkKCBjYaB1mxkYXA6Ly9kaXIxLnNz  
cC1zdHJvbmctaWQubmV0L2NuJTNkVmV0ZXJhbnM1MjBBZmZhaXJzJTIwRGV2aWN1  
JTIwQ0ElMjBCMlxvdSUzZFBLSsxvdSUzZFN1cnZpY2VzLGrjJTNkdmEsZGM1M2Rn  
b3Y/Y2VydGlmaWNhdGVSZXZvY2F0aW9uTG1zdDADBgNVHQ4EFgQUvahLuziprIjqH  
vyKPG1FwBP6elTwxDQYJKoZIhvcNAQELBQADggEBACOKYWvcihUGT0M9q/dw2FeN  
jHzc9ghlsLxD0H1z5zpUfo7vCN5Xvc kRtPJBxAgPfBma+Cvm4MvJ09Cz6XTKkfZL  
j0qRm1dg9n61+bIEiX2wgvDT8yBYQRC+eoM6UdoSN7hk60xxZnvahJAdGEStwl2+  
FdtejxfiRJr0kA9he/Yr11EJ2NmWK1YWG6UPzGa1rT4H/OQGTItdxr1VIAff75Ub  
08914vVubkSLAgiwd5xpQns27uj30gQUjvJvSwU59/cdMoAw+XLNB1gXvcb3ep1K  
3SbuZJIJRbhg8Hzn4D6aX/g+g0ZPjATMZWBNLpgPYX/dW5rYjhbs5d5rXUi kgc=  
-----END CERTIFICATE-----
```