VELLORE INSTITUTE OF TECHNOLOGY
School of Computer Science and Engineering (SCOPE)

SmartVision-Ed

A Real-Time Computer Vision-Based Student Engagement, Attention Analytics & Multi-Modal Academic Dropout Early Warning System

Course Name:	Computer Vision (CSE3002 / CSE4001)
Evaluation Component:	VITyarthi - Build Your Own Project (Flipped Course)
Student Name:	**Khushal Mahajan**
Registration Number:	**24MIM10014**
Academic Program:	Integrated M.Tech in Computer Science & Engineering
Submission Date:	October 2026

Academic Integrity Statement:
I hereby declare that this project, titled SmartVision-Ed, is my original work developed for the course evaluation. All algorithmic implementations, computer vision pipelines, mathematical models, and documentation were independently designed and implemented by Khushal Mahajan (24MIM10014) with strict adherence to academic ethics (Plagiarism < 50%).

1. Introduction

In modern tertiary education institutions like Vellore Institute of Technology (VIT), the transition to large-scale lecture formats, hybrid classrooms, and digital learning platforms presents significant challenges for instructors attempting to gauge individual and cohort-wide cognitive engagement. Human instructors, constrained by cognitive bandwidth and visual field limitations, cannot continuously track the subtle, compounding symptoms of student disengagement, micro-sleep, and cognitive overload.

SmartVision-Ed bridges this gap by leveraging real-time Computer Vision (CV) to quantify physiological indicators of classroom alertness without requiring wearable sensors or invasive hardware. By utilizing facial geometry, Eye Aspect Ratio (EAR), 3D Head Pose estimation via Perspective-n-Point (solvePnP), and Mouth Aspect Ratio (MAR), the system extracts instantaneous and temporal attention metrics. These visual signals are seamlessly fused with longitudinal academic indicators (attendance, internal assessment marks, and LMS activity) into a unified Composite Academic Vulnerability Score (CAVS) that triggers proactive early warnings prior to academic failure or debarment.

2. Problem Statement & Objectives

2.1 Problem Statement

Conventional academic retention mechanisms rely almost exclusively on *lagging indicators*. Notices regarding attendance shortages (e.g., dropping below the mandatory 75% university debarment threshold) or failing internal assessment marks are typically generated weeks after cognitive disengagement has set in. Consequently, academic advisors and proctors are forced into a reactive posture where remedial intervention is often too late.

2.2 Project Objectives

- **Objective 1:** Design and implement a robust, real-time Computer Vision perception pipeline capable of localizing facial landmarks, computing EAR for drowsiness detection, and solving 3D head orientation at ≥ 30 FPS.
- **Objective 2:** Implement a temporal smoothing and state-machine tracker using Exponential Moving Averages (EMA) to filter involuntary saccades and isolate genuine cognitive fatigue events.
- **Objective 3:** Construct a multi-modal academic risk model (CAVS) combining visual attention, lecture attendance, internal marks, and LMS participation into an actionable early dropout warning system.
- **Objective 4:** Embed privacy-preserving mechanisms (cryptographic pseudonymization and Gaussian facial de-identification) to safeguard student data in accordance with ethical AI standards.

3. Functional Requirements

The system fulfills four major functional modules as specified in the project guidelines:

Module	Functional Capability	Input / Output Structure
M1: Vision Perception & Landmark Engine	Extracts 68-point facial landmarks, calculates EAR and MAR metrics, and resolves 3D head pose Euler angles via solvePnP.	**In:** Raw video frames (RGB, 640x480) **Out:** Facial coordinate vectors, EAR, MAR, Yaw, Pitch, Roll
M2: Temporal Attention & Affect Tracker	Smooths instantaneous attention via EMA (α=0.25), counts blink frequencies, and detects sustained drowsiness and distraction episodes.	**In:** Frame telemetry stream **Out:** Smoothed Attention %, Fatigue Index, Dominant Affect state

M3: Multi-Modal Academic Risk Engine (CAVS)	Computes Composite Academic Vulnerability Score and classifies students into Low Risk, Moderate Risk, and Critical Early Warning.	**In:** Vision Attention, Attendance %, Internals, LMS % **Out:** CAVS score (0-100), Risk Tier, Early Warning Flag
M4: Telemetry HUD & Intervention Reporting	Renders live canvas telemetry HUD, interactive What-If scenario simulator, and generates automated PDF reports.	**In:** Student profiles & session stats **Out:** Interactive Web Dashboard, Prescriptive Alerts, PDF report

4. Non-Functional Requirements

• **NFR 1 — Performance & Throughput:** The computer vision pipeline processes frames at ≥ 30 frames per second with per-frame inference latency < 35 milliseconds on standard commodity CPU hardware without requiring high-end dedicated GPUs.

• **NFR 2 — Security, Privacy & Anonymization:** Strict biometric de-identification is enforced. The privacy filter applies Gaussian facial ROI blurring and derives salted SHA-256 pseudonym tokens (e.g., ANON-8B4E19C0). No raw biometric face templates are persisted in persistent databases.

• **NFR 3 — Usability & Responsive Interface:** The web dashboard implements a modern cyber-academic visual system with dark mode glassmorphism, responsive data tables, interactive risk sliders, and live canvas charts.

• **NFR 4 — Reliability & Fault Tolerance:** Comprehensive validation handles missing camera frames, anomalous lighting shifts, and extreme facial occlusions via mathematical fallbacks and synthetic signal simulation.

• **NFR 5 — Maintainability & Code Quality:** Modular architecture adhering to PEP-8 standards with 100% unit test coverage for mathematical formulas and zero external runtime coupling.

5. System Architecture

SmartVision-Ed is structured across a four-tier decoupled architecture: (1) Ingestion & Privacy Layer, (2) Computer Vision Feature Engine, (3) Temporal Risk Modeling Core, and (4) Presentation & Intervention Layer. This design guarantees clean separation of concerns and high throughput.




Figure 5.1: Four-Tier System Architecture of SmartVision-Ed (Author: Khushal Mahajan, 24MIM10014)

6. Design Diagrams

6.1 Process Workflow Diagram




Figure 6.1: End-to-End Processing Workflow from Video Ingestion to Risk Alert Triggering

6.2 UML Use Case & Actor Interactions

The system interfaces with three primary human actors: (1) **Course Instructor**, who monitors cohort engagement heatmaps and dynamic lecture pacing cues; (2) **Faculty Advisor / Proctor**, who receives automated early debarment warnings and reviews prescriptive interventions; and (3) **Student**, who interacts with privacy-preserving self-assessment dashboards.

6.3 Database Schema & Telemetry Design (ER Representation)

Entity	Primary / Foreign Keys	Core Attributes & Types
STUDENT_RECORD	student_id (PK, VARCHAR) anonymized_token (VARCHAR)	student_name, course_id, attendance_pct (FLOAT), internal_marks (FLOAT), lms_score (FLOAT)
FRAME_TELEMETRY	telemetry_id (PK, INT) student_id (FK, VARCHAR)	timestamp (FLOAT), ear_avg (FLOAT), yaw (FLOAT), pitch (FLOAT), dominant_affect (VARCHAR), attention_score (FLOAT)
SESSION_METRICS	session_id (PK, VARCHAR) student_id (FK, VARCHAR)	duration_sec, mean_attention, focus_time_pct, drowsiness_alerts, fatigue_index, cavs_score
EARLY_WARNING_LOG	alert_id (PK, INT) student_id (FK, VARCHAR)	trigger_date, risk_category, debarment_risk (BOOL), contributing_factors (JSON), interventions (JSON)

7. Design Decisions & Rationale

1. Perspective-n-Point (solvePnP) vs. Deep 3D Head Pose CNNs: The decision to use cv2.solvePnP with canonical 3D facial model geometry was chosen over heavyweight convolutional networks (e.g., HopeNet). solvePnP delivers deterministic, mathematically rigorous Euler angles (Yaw, Pitch, Roll) with sub-millisecond execution times and zero GPU dependency.

2. Eye Aspect Ratio (EAR) vs. Binary Eye-Closure Classifiers: Rather than training an error-prone binary CNN classifier on cropped eye regions, the mathematical formulation of EAR (Soukupova & Cech, 2016) provides continuous, scalar ocular measurements. This enables nuanced distinction between normal physiological blinks (duration ≤ 250ms) and micro-sleep / drowsiness episodes (> 450ms).

3. Temporal Exponential Moving Average (EMA) vs. Simple Sliding Average: EMA filtering with $\alpha = 0.25$ was selected to smooth sudden saccadic movements while maintaining responsiveness to genuine distraction events.

8. Implementation Details & Mathematical Formulations

8.1 Eye Aspect Ratio (EAR) Formulation

Ocular openness is computed from 6 coordinate pairs across each eye contour according to the equation:

$$EAR = (|| p2 - p6 || + || p3 - p5 ||) / (2 \times || p1 - p4 ||)$$

Where p1 through p6 represent sequential 2D landmarks along the eye circumference. An EAR drop below 0.18 sustained for more than 14 frames indicates a confirmed drowsiness episode.

8.2 Mouth Aspect Ratio (MAR) Yawn Detection

Yawn events are characterized by vertical mouth expansion according to the formulation:

$$MAR = (|| m2 - m8 || + || m3 - m7 || + || m4 - m6 ||) / (2 \times || m1 - m5 ||)$$

A threshold of MAR > 0.65 flags involuntary fatigue yawning.

8.3 Composite Academic Vulnerability Score (CAVS)

The multi-modal risk engine combines visual and academic telemetry through the weighted equation:

$$CAVS = 100 - [0.30 \times V_att + 0.25 \times A_tt + 0.25 \times I_mk + 0.20 \times L_ms]$$

Where V_att is visual attention %, A_tt is lecture attendance %, I_mk is internal assessment score, and L_ms is LMS activity score.

9. Experimental Results & Visual Telemetry

The system was evaluated across simulated classroom scenarios featuring varied student cognitive states. Below are the quantitative visual results:




Figure 9.1: Ocular Dynamics & Micro-Sleep Episode Detection via EAR Tracking




Figure 9.2: Cohort CAVS Vulnerability Score Distribution Highlighting Early Warning Tiers

Table 9.1: Evaluation Results for Monitored Student Cohort

Student ID	Student Name	Att %	Internals	Vision Att %	CAVS Score	Risk Category
24MIM10014	Khushal Mahajan	94.5%	92.0	86.4%	10.6	Low Risk
24MIM10002	Aarav Sharma	82.0%	74.0	71.5%	25.9	Low Risk
24MIM10023	Rohan Verma	68.5%	42.0	45.2%	51.2	Critical Warning
24MIM10037	Priya Nair	91.0%	85.0	82.8%	13.2	Low Risk
24MIM10051	Aditya Rao	72.0%	58.0	53.0%	41.4	Critical Warning
24MIM10078	Vikram Sethi	61.0%	38.0	40.1%	57.8	Critical Warning

10. Testing Approach & Validation Results

A rigorous, multi-level testing methodology was adopted. Unit tests, mathematical verification, and system integration tests were executed via Python's automated test framework with 100% test success rate.

Test Identifier	Target Functionality	Expected Outcome	Test Status
TC-CV-01	EAR Calculation (Open Eye)	EAR > 0.25 (Norm: 0.30)	**PASSED**
TC-CV-02	EAR Calculation (Closed Eye)	EAR < 0.15 (Norm: 0.10)	**PASSED**
TC-CV-03	MAR Yawn Detector	Normal < 0.40, Yawn > 0.65	**PASSED**
TC-CV-04	PnP Head Pose Decomposition	Yaw/Pitch < 20° Screen-Facing	**PASSED**
TC-CV-05	Cryptographic Pseudonymization	Deterministic SHA-256 tokens	**PASSED**
TC-CV-06	EMA Temporal Smoothing	Noise dampening > 65% focus	**PASSED**
TC-CV-07	CAVS Mathematical Formula	Score in [0.0, 100.0] range	**PASSED**
TC-CV-08	Debarment Alert (< 75% Att)	Automatic Critical Warning flag	**PASSED**

11. Challenges Faced & Mitigations

• **OpenCV PnP Axis Inversion:** Resolving rotation vector ambiguity in *solvePnP* required harmonizing the 3D canonical facial model coordinate frame with standard OpenCV camera coordinates (where Y points downwards). This was overcome by leveraging *cv2.RQDecomp3x3* for clean Euler angle extraction.

• **High-Frequency Saccadic Eye Movements:** Natural human eye blinks (lasting 100-250ms) cause instantaneous EAR drops that falsely trigger fatigue alarms if analyzed on a single-frame basis. This was mitigated by implementing a temporal sliding window state machine with consecutive frame persistence requirements (> 14 frames).

• **Biometric Privacy & Ethics:** Deploying computer vision in student environments requires rigorous privacy safeguards. We implemented a dedicated de-identification filter applying Gaussian blurring on facial regions and generating salted SHA-256 tokens to ensure zero student facial images are persisted.

12. Learnings & Key Takeaways

Through the development of SmartVision-Ed, profound insights were gained into real-time computer vision system design, 3D geometric projection mathematics, and ethical AI deployment. Integrating optical geometric cues (EAR, MAR, PnP) with academic records highlighted the power of multi-modal machine learning in solving critical real-world educational challenges. Furthermore, optimizing computational throughput to achieve ≥ 30 FPS demonstrated the importance of algorithmic efficiency over brute-force neural network approaches.

13. Future Enhancements

- **Edge AI Deployment:** Porting the vision pipeline to edge hardware (such as NVIDIA Jetson Orin Nano or Raspberry Pi 5) for standalone classroom sensor pods.
- **Multi-Student Pan-Tilt-Zoom (PTZ) Tracking:** Expanding from single-user desktop streams to multi-face panoramic classroom monitoring with automated identity assignment.
- **Gaze Heatmap Fixation:** Incorporating optical gaze fixation tracking to determine specifically which slide sections or whiteboard zones capture student interest.

14. References

[1] Soukupová, T., & ■ech, J. (2016). *Real-Time Eye Blink Detection using Facial Landmarks*. 21st Computer Vision Winter Workshop (CVWW).

[2] Kazemi, V., & Sullivan, J. (2014). *One Millisecond Face Alignment with an Ensemble of Regression Trees*. IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 1867-1874.

[3] Bradski, G. (2000). *The OpenCV Library*. Dr. Dobb's Journal of Software Tools.

[4] Baker, R. S., & Inventado, P. S. (2014). *Educational Data Mining and Learning Analytics*. In Learning Analytics (pp. 61-75). Springer.

[5] Vellore Institute of Technology. (2024). *Academic Regulations & Continuous Assessment Guidelines*. VIT University Publications.