

Instance-Based Learning

www.biostat.wisc.edu/~dpage/cs760/

Nearest-neighbor classification

learning task


- given a training set $(\mathbf{x}_1, y_1) \dots (\mathbf{x}_n, y_n)$, do nothing (it's sometimes called a *lazy learner*)

classification task

- **given:** an instance \mathbf{x}_q to classify
- find the training-set instance \mathbf{x}_i that is most similar to \mathbf{x}_q
- return the class value y_i

The decision regions for nearest-neighbor classification

Voronoi Diagram: Each polyhedron indicates the region of feature space that is in the nearest neighborhood of each training instance



k -nearest-neighbor classification

classification task

- **given:** an instance x_q to classify
- find the k training-set instances $(x_1, y_1) \dots (x_k, y_k)$ that are most similar to x_q
- return the class value

$$\hat{y} \leftarrow \operatorname{argmax}_{v \in \text{values}(Y)} \sum_{i=1}^k \delta(v, y_i)$$

$$\delta(a, b) = \begin{cases} 1 & \text{if } a = b \\ 0 & \text{otherwise} \end{cases}$$

(i.e. return the class that the plurality of the neighbors have)

How can we determine similarity/distance

suppose all features are nominal (discrete)

- Hamming distance: count the number of features for which two instances differ

suppose all features are continuous

- Euclidean distance:

$$d(\mathbf{x}_i, \mathbf{x}_j) = \sqrt{\sum_f (x_{if} - x_{jf})^2} \quad \text{where } x_{if} \text{ represents the } f^{\text{th}} \text{ feature of } \mathbf{x}_i$$

- Could also use Manhattan distance: sum the differences in feature values – continuous analog to Hamming distance

How can we determine similarity/distance

- if we have a mix of discrete/continuous features:

$$d(\mathbf{x}_i, \mathbf{x}_j) = \sum_f \begin{cases} |x_{if} - x_{jf}| & \text{if } f \text{ is continuous} \\ 1 - \delta(x_{if}, x_{jf}) & \text{if } f \text{ is discrete} \end{cases}$$

- If all feature are of equal importance, want to apply to continuous features some type of normalization (values range 0 to 1) or standardization (values distributed according to standard normal)

k-nearest-neighbor *regression*

learning task

- given a training set $(\mathbf{x}_1, y_1) \dots (\mathbf{x}_n, y_n)$, do nothing

prediction task

- **given:** an instance \mathbf{x}_q to make a prediction for
- find the *k* training-set instances $(\mathbf{x}_1, y_1) \dots (\mathbf{x}_k, y_k)$ that are most similar to \mathbf{x}_q
- return the value

$$\hat{y} \leftarrow \frac{1}{k} \sum_{i=1}^k y_i$$

Distance-weighted nearest neighbor

We can have instances contribute to a prediction according to their distance from x_q

classification:

$$\hat{y} \leftarrow \operatorname{argmax}_{v \in \text{values}(Y)} \sum_{i=1}^k w_i \delta(v, y_i)$$

$$w_i = \frac{1}{d(x_q, x_i)^2}$$

regression:

$$\hat{y} \leftarrow \frac{\sum_{i=1}^k w_i y_i}{\sum_{i=1}^k w_i}$$

Strengths of instance-based learning

- simple to implement
- “training” is very efficient
- adapts well to on-line learning
- robust to noisy training data (when $k > 1$)
- often works well in practice

Limitations of instance-based learning

- sensitive to range of feature values
- sensitive to irrelevant and correlated features, although...
 - there are variants that learn weights for different features
 - later we'll talk about *feature selection* methods
- classification can be inefficient, although edited methods and k - d trees can help alleviate this weakness
- doesn't provide much insight into problem domain because there is no explicit model