

# API Documentation

Assessment webs5

Wouter van Geel  
Gijsbert van Corstanje

Version 1.0



# Authentication

Please send with every protected request an authentication token.  
The provided authentication tokens can have user (read) or admin (crud) rights.

```
$.ajax({  
  url : [request_url],  
  headers: {  
    'auth' : [token]  
  }  
});
```

# Examples

Example of a jQuery Ajax call.

Default the API will give an JSON response.

Add *?format=html* to the URI to change the response data type to HTML.

```
$.ajax({  
    url : "/venues",  
    headers: {  
        'auth' : "provideTokenHere"  
    },  
    dataType: "json",  
    type : "GET",  
    success : function(data) {  
        // Do something here  
    }  
});
```

# Overview

Overview of all current implemented API endpoints.

Base url: <http://venuerace-gw.herokuapp.com/>

Method	Endpoint	Description	Auth protection
GET	/venues	Return all venues	user
POST	/venues	Add venue	admin
GET	/venues/:Name	Returns venue details	user
PUT	/venues/:Name	Update venue details	admin
DELETE	/venues/:Name	Delete venue	admin
GET	/races	Return all races	user
POST	/races	Add race	admin
GET	/races/:Name	Returns race details	user
PUT	/races/:Name	Update race details	admin
DELETE	/races/:Name	Delete race	admin

## General responses

Response Code	Return value
200 - OK	n/a
401 - UNAUTHORIZED	<pre>{   error: "no valid authorization key" }</pre>

# Requests

## Venues

<b>URL</b>	/venues
<b>Method</b>	GET
<b>URL Params</b>	n/a
<b>Data Params</b>	n/a
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> <pre>{   "count": 100,   "results": [     {       "name": "BlaBlaBla2",       "category": "Dutch"     },     {       "name": "Smaak d'Italia",       "category": "Ice parlor"     }     ...   ] }</pre>
<b>Error response</b>	n/a

<b>URL</b>	/venues
<b>Method</b>	POST
<b>URL Params</b>	n/a
<b>Data Params</b>	<pre>{   "name": "Example",   "category": "Dutch" }</pre>
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> <pre>{   "count": 100,   "results": [     {       "name": "BlaBlaBla2",       "category": "Dutch"     },     {       "name": "Smaak d'Italia",       "category": "Ice parlor"     }     ...   ] }</pre>
<b>Error response</b>	n/a

<b>URL</b>	/venue/:Name
<b>Method</b>	GET
<b>URL Params</b>	n/a
<b>Data Params</b>	n/a
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> <pre>{   "name": "Example",   "category": "Dutch" }</pre>
<b>Error response</b>	<pre>{   "message": "Not Found" }</pre>

<b>URL</b>	/venue/:Name
<b>Method</b>	PUT
<b>URL Params</b>	n/a
<b>Data Params</b>	<pre>{   "name": "Example",   "category": "Dutch" }</pre>
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> <pre>{   "redirect": "/venues" }</pre>
<b>Error response</b>	<pre>{   "message": "Not Found" }</pre>



<b>URL</b>	/venue/:Name
<b>Method</b>	DELETE
<b>URL Params</b>	n/a
<b>Data Params</b>	n/a
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> { "redirect": "/venues" }
<b>Error response</b>	{ "message": "Not Found" }

## Races

<b>URL</b>	/races
<b>Method</b>	GET
<b>URL Params</b>	n/a
<b>Data Params</b>	n/a
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> <pre>{   "count": 1,   "results": [     {       "name": "testRace"     },     ...   ] }</pre>
<b>Error response</b>	n/a

<b>URL</b>	/races
<b>Method</b>	POST
<b>URL Params</b>	n/a
<b>Data Params</b>	<pre>{   "name": "Example",   "Status": "not_started" }</pre>
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> <pre>{   "count": 1,   "results": [     {       "name": "testRace"     }   ] }</pre>
<b>Error response</b>	n/a

<b>URL</b>	/races/:Name
<b>Method</b>	GET
<b>URL Params</b>	n/a
<b>Data Params</b>	n/a
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> <pre>{   "name": "testRace",   "status": "not_started" }</pre>
<b>Error response</b>	<pre>{   "message": "Not Found" }</pre>

<b>URL</b>	/races/:Name
<b>Method</b>	PUT
<b>URL Params</b>	n/a
<b>Data Params</b>	<pre>{   "name": "Example",   "status": "started" }</pre>
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> <pre>{   "redirect": "/races" }</pre>
<b>Error response</b>	<pre>{   "message": "Not Found" }</pre>

<b>URL</b>	/races/:Name
<b>Method</b>	DELETE
<b>URL Params</b>	n/a
<b>Data Params</b>	n/a
<b>Success response</b>	<b>Code:</b> 200 OK <b>Content:</b> { "redirect": "/races" }
<b>Error response</b>	{ "message": "Not Found" }