API Documentation

Assessment webs5



Authentication

Please send with every request an basic authentication code. The authentication code can be acquired in javascript by using the following code:

btoa(adminUserData.local.email + ":" + adminUserData.local.password);

There are two supported user authorization groups: "user" and "admin".

Examples

Example of a jQuery Ajax call.

Default the API will give an HTML response. Add "Content-Type": "application/json" in the header to get a response in JSON.

Overview

Overview of all current implemented API endpoints. Base url: https://venuerace-gw.herokuapp.com/

Method	Endpoint	Description	Auth protection
GET	/venues	Return all venues	user
POST	/venues	Add venue	admin
GET	/venues/:id	Returns venue details	user
PUT	/venues/:id	Update venue details	admin
DELETE	/venues/:id	Delete venue	admin
GET	/races	Return all races	user
POST	/races	Add race	admin
GET	/races/:name	Returns race details	user
PUT	/races/:name	Update race details	admin
DELETE	/races/:name	Delete race	admin
GET	/races/:name/venues	Returns all venues from race	user
POST	/races/:name/venues	Add venue to race	admin
DELETE	/races/:name/venues/:i d	Remove venue from race	admin
GET	/races/:name/participa nts	Returns all participants in race	user
POST	/races/:name/participa nts	Add participant to race	admin
GET	/races/:name/participa nts/:userld	Returns participant details and visited venues	user
PUT	/races/:name/participa nts/:userld	Update participant details	admin
DELETE	/races/:name/participa nts/:userId	Remove participant from race	admin

General responses

Response Code	Return value
200 - OK	n/a
400 - BAD REQUEST	{ Message: "Missing Required Fields" }
401 - UNAUTHORIZED	{ error: "no valid authorization key" }
404 - NOT FOUND	{ Message: "Not Found" }

Requests

Venues

···	,
URL	/venues
Method	GET
URL Params	Limit: aantal gewenste venues Page: gewenste pagina Name: gewenste (deel)naam van venue
Data Params	n/a
Success response	<pre>Code: 200 OK Content: { "limit": 10, "page": 0, "count": 10, "results": [{ "id": "642", "name": "Friture Aod Naer", "category": "Snackbars" }, { "id": "646", "name": "Hong Kong2", "category": "Chinese indian2" },] }</pre>
Error response	n/a

URL	/venues
Method	POST
URL Params	n/a
Data Params	<pre>{ "name": "Example", "category": "Dutch" }</pre>
Success response	<pre>Code: 200 OK Content: { "id": "576a44e308b22c0025f47e24", "name": "Example", "category": "Dutch" }</pre>
Error response	n/a

URL	/venue/:id
Method	GET
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: { "id": "642", "name": "Friture Aod Naer", "category": "Snackbars", "local": false }</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>

URL	/venue/:id
Method	PUT
URL Params	n/a
Data Params	<pre>"name": "Example", "category": "Dutch" }</pre>
Success response	<pre>Code: 200 OK Content: { "id": "999", "name": "Example", "category": "Dutch", "local": true }</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>

URL	/venue/:id
Method	DELETE
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: { "status": 200, "message": "':id' Successfully Deleted" }</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>

Races

URL	/races
Method	GET
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: { "count": 4, "races": [</pre>
Error response	n/a

URL	/races
Method	POST
URL Params	n/a
Data Params	<pre>{ "name":"Example", "Status":"not_started" }</pre>
Success response	<pre>Code: 200 OK Content: { "name": "Example", "Status": "not_started" }</pre>
Error response	<pre>Code: 400 BAD REQUEST Content: { "status": 400, "message": "There are already 5 races." }</pre>

URL	/races/:name
Method	GET
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: { "name": "testRace", "status": "not_started", "Venues": [</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>

```
URL
             /races/:name
             PUT
Method
URL Params
             n/a
Data Params
             {
                 "name": "Example",
                 "status": "started"
             }
             Code: 200 OK
Success
             Content:
response
               "Id": "a2o3038n13y4a",
               "name": "Example",
               "status": "started",
               " v": 4,
               "Participants:
                  "id": "02740a02943023",
                  "id": "286843as928a9929ff",
                  "winner": false,
                  "Venues" :
                     "313", "142"
               ],
               "Venues":
                  "139"
               ]
             }
             Code: 404 NOT FOUND
Error
response
             Content:
               "message": "Not Found"
```

URL	/races/:name
Method	DELETE
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: { "message": "/:name successfully deleted" }</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>

URL	/races/:name/venues
Method	GET
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: ["venuelid", "venue2id"]</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>

URL	/races/:name/venues
Method	POST
URL Params	n/a
Data Params	{ "Id": "newId" }
Success response	<pre>Code: 200 OK Content: ["venuelid", "venue2id", "newId"]</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>

URL	/races/:name/venues/:id
Method	DELETE
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: { "message": "':id' Successfully deleted" }</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>
Error response	Code: 400 NOT FOUND Content: { "message": "Race Not Found" }

URL	/races/:name/participants
Method	GET
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: [</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>
Error response	<pre>Code: 400 Content: { "message": "Venue Already Exists" }</pre>
Error response	Code: 404 Content: { "message": "Race Not Found" }

```
URL
             /races/:name/participants
Method
             POST
URL Params
             n/a
Data Params
                "userId": "newId"
              }
             Code: 200 OK
Success
             Content:
response
                " id": "5769d1671aca70e812e68b31",
                "status": "ended",
                "name": "venueName",
                " v": 8,
                "participants": [
                    "id": "572f51370895711100aa2fec",
                    " id": "5769d1f706c775d80b3ecf72",
                    "winner": false,
                    "venues": [
                      "642",
                      "646"
                    ]
                  },
                  {
                    "id": "5769d1f706c775d80b3ecf72",
                    " id": "newId",
                    "winner": false,
                    "venues": []
                  }
                ],
                "venues": [
                 "642",
                  "646"
                ]
              }
Error
             Code: 404 NOT FOUND
response
             Content:
                "message": "Not Found"
Error
             Code: 404 NOT FOUND
response
             Content:
                "message": "Race Not Found"
```

```
Error Code: 400 Content:
{
    "message": "User Not Found"
}
```

URL	/races/:name/participants/:userId
Method	GET
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: { "id": "5769d1f706c775d80b3ecf72", "_id": "576a400408b22c0025f47e21", "winner": false, "venues": [</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>

URL	/races/:name/participants/:userId
Method	GET
URL Params	n/a
Data Params	n/a
Success response	<pre>Code: 200 OK Content: { "id": "5769d1f706c775d80b3ecf72", "_id": "576a400408b22c0025f47e21", "winner": false, "venues": [</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>

URL	/races/:name/participants/:userId
Method	PUT
URL Params	n/a
Data Params	{ "venueId": "642" }
Success response	<pre>Code: 200 OK Content: { "id": "5769d1f706c775d80b3ecf72", "_id": "576a400408b22c0025f47e21", "winner": false, "venues": [</pre>
Error response	<pre>Code: 404 NOT FOUND Content: { "message": "Not Found" }</pre>