


Key Establishment and Remote Authentication

Content


- ▶ Remote authentication
- ▶ Key establishment (and authentication)
- ▶ We look at two main key establishment problems:
 - A and B share a long term key and want to negotiate a session key.
 - A wants to have a shared key with B. Both trust a third party C.

Remote Authentication

- ▶ Authentication over a network
- ▶ Trivial variant: Send name and password just as in OS login
 - ▶ Used by Basic Access Authentication in HTTP




- ▶ Variant: Send name and the hash of the password



- ▶ **Replay attack:** Resending an eavesdropped hash will authenticate anyone with the hash
- ▶ Do the two methods differ in security in any way?

Avoid Sending Password

- ▶ Challenge response protocol
 - Server sends challenge, client sends response
 - Response depends on challenge



- ▶ **Example 1:** Encrypt challenge using (hash of) password as key
 - NTLM uses block cipher DES
- ▶ **Example 2:** Use a hash function including both challenge and password
 - Digest Access Authentication in HTTP uses a variant of this
- ▶ **Replay attack:** If same challenge is used twice, an attacker can replay an eavesdropped response to get authenticated
 - Solution 1: challenge is a "number used once", a **nonce**
 - Solution 2: (part of) challenge is a time stamp
- ▶ More details in the course "Web Security"

Key Establishment and Authentication

Different keys

- ▶ **Long term keys** – Rarely or never changed. Use sparingly.
- ▶ **Session keys** – Often changed. If lost or broken, only current session is affected.
 - Each key is used to encrypt a limited amount of data
 - Asymmetric long term keys can be used to negotiate symmetric keys.

Slow encryption → fast encryption

- Key is not valid for a long time → **key freshness**
- ▶ Common to separate keys depending on application
 - Symmetric: One for encryption, one for message authentication
 - Asymmetric: Different key pairs for encryption and digital signatures
- ▶ We want to know *who* we are establishing keys with so authentication is included
 - Mutual vs. Unilateral authentication

Key Establishment


- ▶ Key Establishment divided into
 - **Key Transport** – one party creates/obtains secret key and securely transfers it to the other party (also called key distribution)
 - **Key Agreement** – Both parties contribute to the generation of the secret key
- ▶ Other terms
 - **(Implicit) Key Authentication** – One party knows that no one besides a specifically identified second party may gain access to a secret key
 - **Key Confirmation** – One party is assured that the second party has possession of a secret key (but identity of the other party may not be known)
 - **Explicit Key Authentication** – Both implicit key authentication and key confirmation

EIT060 - Computer Security

5

Authenticated Key Exchange Protocol 2

- ▶ Bellare and Rogaway, 1994
- ▶ No trusted third party involved
- ▶ A and B share two common *symmetric* keys, K and K' and wish to negotiate a session key.
- ▶ h and h' are keyed hash functions (MACs), n is a nonce (number used once)




Protocol provides (implicit) key authentication and mutual entity authentication

EIT060 - Computer Security

6

Pre-shared Keys

- ▶ Consider a system of n users, everyone having pre-shared key with each other
- ▶ There are $n(n-1)/2$ different keys
- ▶ Some problems:
 - Each user needs to securely store $n-1$ keys
 - Distribution of pre-shared keys require distribution of about n^2 keys




EIT060 - Computer Security

7

Diffie-Hellman Protocol

- ▶ Diffie and Hellman
- ▶ Key agreement protocol
- ▶ A and B do not share any secret (long term key) in advance
- ▶ p is a large prime, g is element of large order in multiplicative group mod p .




Based on the DLP problem (discrete logarithm problem)

EIT060 - Computer Security

8

Problem with Diffie-Hellman

- ▶ No key authentication – no party knows with whom they share the secret
- ▶ **Man-in-the-middle attack**




EIT060 - Computer Security

9

Station-to-Station (STS) Protocol

- ▶ Authentication added to Diffie-Hellman
- ▶ S_x is x's signature key and sS_x is the signature produced by S_x .



As before, $K = g^{ab} \bmod p$

Provides *mutual entity authentication* and *explicit key authentication*

A PKI (Public Key Infrastructure) is needed

EIT060 - Computer Security


10

Password-based Protocols

- ▶ Long-term keys need to be stored on clients
- ▶ A password can represent a key
- ▶ Convenient for human interaction – Easier to remember a password
- ▶ P is password, eP is encryption with password (mapped to encryption key), K_s is session key, eK_s is encryption with session key

Simple protocol:

Problem: Offline dictionary attacks or brute force attacks on password using data redundancy possible.
Passwords are often badly chosen




EIT060 - Computer Security

11

Password-based Protocols

- ▶ Encrypted Key Exchange (EKE) (*Bellare and Merritt 1992*)
- ▶ Use a temporary public key K_a encrypted with password to encrypt session key



Guess P' gives K'_a and $eK'_a(K'_s)$, now either
 1. Brute force K'_s and check if $eK'_a(K'_s) = eK_a(K_s)'$
 OR
 2. Find private key corresponding to K'_a


EIT060 - Computer Security

12

Using a Trusted Third Party

- ▶ A and B each share a secret key with server S .
 - K_{as} : secret key shared between A and S (long term)
 - K_{bs} : secret key shared between B and S (long term)
- ▶ **Goal:** Obtain, from S , secret key shared between A and B
 - K_{ab} : session key created by S , for use between A and B
- ▶ **First attempt:**

Trusted third party



Problem?


EIT060 - Computer Security

13

Needham-Schroeder Protocol

- ▶ Key transport protocol, 1978
- ▶ n_a, n_b : Nonces generated by A and B . Used to prevent replay attacks

Trusted third party




EIT060 - Computer Security

14

Problem with Needham-Schroeder

- ▶ B does not know if K_{ab} is fresh or not!
- ▶ What if we can break one session key?
- ▶ Then replay attack is possible (Denning – Sacco 1981)
- ▶ Assume adversary M breaks K_{ab} , and enter protocol at message 3


**Solution:** Include lifetimes for tickets

EIT060 - Computer Security

15

Kerberos

- ▶ Basically Needham-Schroeder with timestamps and limited lifetimes for session keys

Core protocol:

EIT060 - Computer Security

16

Kerberos


- ▶ A Kerberos Authentication Server (KAS) is used together with one or several Ticket Granting Servers TGS.
- ▶ A principal is a user or a server.
- ▶ KAS authenticates principals at login and issues Ticket Granting Tickets (TGTs), which enable principals to obtain other tickets from TGSs.
- ▶ TGSs issues tickets that give principals access to network services demanding authentication.
- ▶ Kerberos 4 uses DES as symmetric cipher, Kerberos 5 can use other algorithms
- ▶ Users authenticate using passwords

EIT060 - Computer Security

17

Kerberos

- 1: A, TGS, n_a
- 2: $eK_{as}(K_{a,tgs}, n_a, L_1, TGS), \overbrace{eK_{tgs}(K_{a,tgs}, A, L_1)}^{TGT}$
- 3: $\overbrace{eK_{tgs}(K_{a,tgs}, A, L_1)}^{TGT}, \overbrace{eK_{a,tgs}(A, T_a), B, n'_a}^{Authenticator}$
- 4: $eK_{a,tgs}(K_{ab}, n'_a, L_2, B), \overbrace{eK_{bs}(K_{ab}, A, L_2)}^{Ticket_B}$
- 5: $\overbrace{eK_{bs}(K_{ab}, A, L_2)}^{Ticket_B}, \overbrace{eK_{ab}(A, T'_a)}^{Authenticator}$
- 6: $eK_{ab}(T'_a)$



EIT060 - Computer Security

18

Kerberos

- ▶ Revocation – access rights are revoked by updating KAS, TGS databases. However, issued tickets are valid until they expire.
- ▶ A realm has a KAS, one or more TGSs and a set of servers. It is possible to get tickets for other realms. KAS_x and KAS_y must share keys.
- ▶ Limitations of Kerberos:
 - synchronous clocks.
 - servers must be on-line, trust in servers.
 - password attacks still possible, implementation errors.
- ▶ Secure protocol is not enough, implementation also has to be secure

EIT060 - Computer Security

19