


Background

Synaptic learning and memory

Learning and memory involve the interplay between neuronal activity and synaptic plasticity.




Theorists frequently neglect the question of how plasticity is implemented. A synapse is often modeled as a single number: the synaptic weight.

Complex synapses


In reality, a synapse is a complex dynamical system.

We will describe a synapse by stochastic processes on a finite number of states, M .

Potentiation and depression cause transitions between these states.



[Coba et al. (2009)]



Storage capacity of synaptic memory


A classical perceptron, when used as a recognition memory device, has a memory capacity $\propto N$, the number of synapses.

However, this requires synapses' dynamic range to be also $\propto N$.

If synaptic efficacies are limited to a fixed dynamic range,
→ strong tradeoff between learning and forgetting
– due to new memories overwriting old.

If we wish to store new memories rapidly, then memory capacity is $\propto \log N$.

[Amit and Fusi (1992), Amit and Fusi (1994)]





[Petersen et al. (1998), O'Connor et al. (2005)]

To circumvent this tradeoff, it is essential to enlarge our theoretical conception of a synapse as a single number.

Cascade and serial models


Two example models of complex synapses with different memory storage properties.



[Fusi et al. (2005), Leibold and Kempster (2008), Ben-Dayan Rubin and Fusi (2007)]

Timescales of memory


Memories stored in different places for different timescales



Also: Cerebellar cortex vs. cerebellar nuclei.

[Squire and Alvarez (1995), Krakauer and Shadmehr (2006)]

Different synapses have different molecular structures.



[Emes RD, Grant SGN. 2012. Annu. Rev. Neurosci. 35:111-31]


[Emes and Grant (2012)]

Questions

- Can we understand the space of *all possible* synaptic models?
- How does the structure (topology) of a synaptic model affect its function (memory curve)?
- Can synaptic structure be tuned to store memories over different timescales?
- How does synaptic complexity (number of states) extend the frontiers of possibility for memory?
- Which synaptic state transition topologies maximize measures of memory?

Framework

Synaptic state transition models




Assumptions:

- Candidate plasticity events occur independently at each synapse,
- Each synapse responds with the same state-dependent rules,
- Synaptic weight takes only two values, ± 1 .

[Fusi et al. (2005), Fusi and Abbott (2007), Barrett and van Rossum (2008)]

Recognition memory

The synapses are given a sequence of patterns (potentiation & depression) to store



Later: presented with a pattern. Has it been seen before?

Memory curve

Ideal observer approach: read synaptic weights directly → upper bound on what could be read from network activity.

Measure overlap between $\tilde{w}(t)$, the N -element vector of synaptic strengths, and \tilde{w}_{ideal} , the pattern we are testing.


Performance measured by signal-to-noise ratio, with mean recall time: τ .

$$SNR(\tau) = \frac{1}{\tau} \int_0^\infty dt e^{-t/\tau} \frac{\langle \tilde{w}_{ideal} \cdot \tilde{w}(t) \rangle - \langle \tilde{w}_{ideal} \cdot \tilde{w}(\infty) \rangle}{\sqrt{\text{Var}(\tilde{w}_{ideal} \cdot \tilde{w}(\infty))}}.$$


The memory envelope

Proven upper bounds


Proven upper bounds on initial SNR and late time tail → upper bound on memory curve at *any* time.



Initial SNR: deterministic binary synapse



Late times: serial model with "sticky" end states




[Lahiri and Ganguli (2013)]


No model can ever go above this envelope. Is it achievable?

Numeric upper bounds

Find maximum memory curve at each time numerically:



At any single timescale: best model has serial topology.




Earlier times: shorten the chain.
Later times: make end state "sticky".

Conclusions

Take-home message

Real synaptic structures are limited by the set of molecular building blocks, and they have a larger set of priorities. What can we conclude?



Experimental tests?

Subject a synapse to a sequence of candidate plasticity events. Observe the changes in synaptic efficacy.

Expectation-Maximization algorithms: Sequence of hidden states → estimate transition probabilities
Transition probabilities → estimate sequence of hidden states

Problems:

- Need a long sequence of plasticity events.
- Need to control candidate plasticity events.
- Need to measure synaptic efficacies.

Summary

- We have formulated a general theory of learning and memory with complex synapses.
- We find a memory envelope: a single curve that cannot be exceeded by the memory curve of *any* synaptic model.
- Synaptic complexity (M internal states) raises the memory envelope linearly in M for times $> \mathcal{O}(M)$.
- We understood what types of synaptic structure are useful for storing memories for different timescales.

References

- [M. P. Coba, A. J. Pocklington, M. O. Collins, M. V. Kopanitsa, R. T. Uren, S. Swamy, M. D. Croning, J. S. Choudhary, and S. G. Grant, "Neurotransmitters drive combinatorial multistate postsynaptic density networks", *Sci Signal*, 2(68):ra19, (2009) .
- [D. J. Amit and S. Fusi, "Constraints on learning in dynamic synapses", *Network: Computation in Neural Systems*, 3(4):443–464, (1992) .
- [D. J. Amit and S. Fusi, "Learning in neural networks with material synapses", *Neural Computation*, 6(5):957–982, (1994) .
- [Carl C. H. Petersen, Robert C. Malenka, Roger A. Nicoll, and John J. Hopfield, "All-or-none potentiation at CA3-CA1 synapses", *Proc. Natl. Acad. Sci. U.S.A.*, 95(8):4732–4737, (1998) .
- [Daniel H. O'Connor, Gayle M. Wittenberg, and Samuel S.-H. Wang, "Graded bidirectional synaptic plasticity is composed of switch-like unitary events", *Proc. Natl. Acad. Sci. U.S.A.*, 102(27):9679–9684, (2005) .
- [S. Fusi, P. J. Drew, and L. F. Abbott, "Cascade models of synaptically stored memories", *Neuron*, 45(4):599–611, (Feb, 2005) .
- [Christian Leibold and Richard Kempster, "Sparseness Constrains the Prolongation of Memory Lifetime via Synaptic Metaplasticity", *Cerebral Cortex*, 18(1):67–77, (2008) .
- [Daniel D Ben-Dayan Rubin and Stefano Fusi, "Long memory lifetimes require complex synapses and limited sparseness", *Frontiers in computational neuroscience*, 1(November):1–14, (2007) .
- [Larry R Squire and Pablo Alvarez, "Retrograde amnesia and memory consolidation: a neurobiological perspective", *Current Opinion in Neurobiology*, 5(2):169–177, (April, 1995) . ISSN 09594388.
- [John W Krakauer and Reza Shadmehr, "Consolidation of motor memory.", *Trends in neurosciences*, 29(1):58–64, (January, 2006) . ISSN 0166-2236.
- [Richard D. Emes and Seth G.N. Grant, "Evolution of Synapse Complexity and Diversity", *Annual Review of Neuroscience*, 35(1):111–131, (2012) .
- [S. Fusi and L. F. Abbott, "Limits on the memory storage capacity of bounded synapses", *Nat. Neurosci.*, 10(4):485–493, (Apr, 2007) .
- [A. B. Barrett and M. C. van Rossum, "Optimal learning rules for discrete synapses", *PLoS Comput. Biol.*, 4(11):e1000230, (Nov, 2008) .
- [Subhaneil Lahiri and Surya Ganguli. "A memory frontier for complex synapses". In C.J.C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K.Q. Weinberger, editors, *Advances in Neural Information Processing Systems 26*, pages 1034–1042. NIPS, 2013. URL <http://papers.nips.cc/paper/4872-a-memory-frontier-for-complex-synapses>.

Acknowledgements

SL and SG thank the Swartz Foundation, Burroughs Wellcome Foundation, Stanford Bio-X Neuroventures, Genentech and DARPA for funding, and Larry Abbott, Stefano Fusi, Marcus Benna, David Sussillo and Jascha Sohl-Dickstein for useful conversations.