Problem A. Thermometer

Time Limit 2000 ms

Problem Statement

Takahashi measured his body temperature and found it to be X °C.

Body temperature is classified into the following:

- Higher than or equal to 38.0 °C: “High fever”
- Higher than or equal to 37.5 °C and lower than 38.0 °C: “Fever”
- Lower than 37.5 °C: “Normal”

Which classification does Takahashi's body temperature fall into? Present the answer as an integer according to the Output section.

Constraints

- $30 \leq X \leq 50$
- X is given to one decimal place.

Input

The input is given from Standard Input in the following format:

```
X
```

Output

Print an integer specified below corresponding to Takahashi's body temperature classification.

- High fever: 1
- Fever: 2
- Normal: 3

Sample 1

Input	Output
40.0	1

His body temperature is $40.0\ ^\circ\mathrm{C}$, which is classified as a high fever. Thus, print 1.

Sample 2

Input	Output
37.7	2

His body temperature is $37.7\ ^\circ\mathrm{C}$, which is classified as a fever. Thus, print 2.

Sample 3

Input	Output
36.6	3

His body temperature is $36.6\ ^\circ\mathrm{C}$, which is classified as a normal temperature. Thus, print 3
.

Problem B. Boy or Girl

Time Limit	1000 ms
Mem Limit	262144 kB
Input File	stdin
Output File	stdout

Those days, many boys use beautiful girls' photos as avatars in forums. So it is pretty hard to tell the gender of a user at the first glance. Last year, our hero went to a forum and had a nice chat with a beauty (he thought so). After that they talked very often and eventually they became a couple in the network.

But yesterday, he came to see "her" in the real world and found out "she" is actually a very strong man! Our hero is very sad and he is too tired to love again now. So he came up with a way to recognize users' genders by their user names.

This is his method: if the number of distinct characters in one's user name is odd, then he is a male, otherwise she is a female. You are given the string that denotes the user name, please help our hero to determine the gender of this user by his method.

Input

The first line contains a non-empty string, that contains only lowercase English letters — the user name. This string contains at most 100 letters.

Output

If it is a female by our hero's method, print `"CHAT WITH HER!"` (without the quotes), otherwise, print `"IGNORE HIM!"` (without the quotes).

Examples

Input	Output
`wjmzbmr`	`CHAT WITH HER!`

Input	Output
xiaodao	IGNORE HIM!

Input	Output
sevenkplus	CHAT WITH HER!

Note

For the first example. There are 6 distinct characters in "wjmzbmr". These characters are: "w", "j", "m", "z", "b", "r". So wjmzbmr is a female and you should print "CHAT WITH HER!".

Problem C. Increasing Array

Time Limit 1000 ms
Mem Limit 524288 kB

You are given an array of n integers. You want to modify the array so that it is increasing, i.e., every element is at least as large as the previous element.

On each move, you may increase the value of any element by one. What is the minimum number of moves required?

Input

The first input line contains an integer n: the size of the array.

Then, the second line contains n integers $x_1, x_2, \ldots, x_n$: the contents of the array.

Output

Print the minimum number of moves.

Constraints

- $1 \leq n \leq 2 \cdot 10^5$
- $1 \leq x_i \leq 10^9$

Example

Input	Output
5 3 2 5 1 7	5

Problem D. Half and Half

Time Limit 2000 ms

Problem Statement

"Pizza At", a fast food chain, offers three kinds of pizza: "A-pizza", "B-pizza" and "AB-pizza". A-pizza and B-pizza are completely different pizzas, and AB-pizza is one half of A-pizza and one half of B-pizza combined together. The prices of one A-pizza, B-pizza and AB-pizza are A yen, B yen and C yen (yen is the currency of Japan), respectively.

Nakahashi needs to prepare X A-pizzas and Y B-pizzas for a party tonight. He can only obtain these pizzas by directly buying A-pizzas and B-pizzas, or buying two AB-pizzas and then rearrange them into one A-pizza and one B-pizza. At least how much money does he need for this? It is fine to have more pizzas than necessary by rearranging pizzas.

Constraints

- $1 \leq A, B, C \leq 5000$
- $1 \leq X, Y \leq 10^5$
- All values in input are integers.

Input

Input is given from Standard Input in the following format:

A B C X Y

Output

Print the minimum amount of money required to prepare X A-pizzas and Y B-pizzas.

Sample 1

Input	Output
1500 2000 1600 3 2	7900

It is optimal to buy four AB-pizzas and rearrange them into two A-pizzas and two B-pizzas, then buy additional one A-pizza.

Sample 2

Input	Output
1500 2000 1900 3 2	8500

It is optimal to directly buy three A-pizzas and two B-pizzas.

Sample 3

Input	Output
1500 2000 500 90000 100000	100000000

It is optimal to buy 200000 AB-pizzas and rearrange them into 100000 A-pizzas and 100000 B-pizzas. We will have 10000 more A-pizzas than necessary, but that is fine.

Problem E. Negatives and Positives

Time Limit 2000 ms
Mem Limit 262144 kB

Given an array a consisting of n elements, find the maximum possible sum the array can have after performing the following operation **any number of times**:

- Choose 2 **adjacent** elements and flip both of their signs. In other words choose an index i such that $1 \le i \le n-1$ and assign $a_i = -a_i$ and $a_{i+1} = -a_{i+1}$.

Input

The input consists of multiple test cases. The first line contains an integer t ($1 \le t \le 1000$) — the number of test cases. The descriptions of the test cases follow.

The first line of each test case contains an integer n ($2 \le n \le 2 \cdot 10^5$) — the length of the array.

The following line contains n space-separated integers $a_1, a_2, \ldots, a_n$ ($-10^9 \le a_i \le 10^9$).

It is guaranteed that the sum of n over all test cases does not exceed $2 \cdot 10^5$.

Output

For each test case, output the maximum possible sum the array can have after performing the described operation any number of times.

Examples

Input	Output
5 3 -1 -1 -1 5 1 5 -5 0 2 3 1 2 3 6 -1 10 9 8 7 6 2 -1 -1	1 13 6 39 2

Note

For the first test case, by performing the operation on the first two elements, we can change the array from $[-1, -1, -1]$ to $[1, 1, -1]$, and it can be proven this array obtains the maximum possible sum which is $1 + 1 + (-1) = 1$.

For the second test case, by performing the operation on -5 and 0, we change the array from $[1, 5, -5, 0, 2]$ to $[1, 5, -(-5), -0, 2] = [1, 5, 5, 0, 2]$, which has the maximum sum since all elements are non-negative. So, the answer is $1 + 5 + 5 + 0 + 2 = 13$.

For the third test case, the array already contains only positive numbers, so performing operations is unnecessary. The answer is just the sum of the whole array, which is $1 + 2 + 3 = 6$.

Problem F. Anyway Takahashi

Time Limit 2000 ms

Problem Statement

You are given integers a, b, c, and d. Print two lines as follows.

The first line should contain the result of calculating $(a+b) \times (c-d)$ as an integer.
The second line should contain `Takahashi`, regardless of the input.

Constraints

- $-100 \leq a, b, c, d \leq 100$
- a, b, c, and d are integers.

Input

The input is given from Standard Input in the following format:

```
a b c d
```

Output

Print two lines according to the Problem Statement.

Sample 1

Input	Output
`1 2 5 3`	`6` `Takahashi`

We have $(1+2) \times (5-3) = 3 \times 2 = 6$, so the first line should contain 6.
The second line should contain `Takahashi`. Lowercasing the first character or incorrect spelling will not be accepted, so be careful.

Sample 2

Input	Output
10 -20 30 -40	-700 Takahashi

The input or output may contain negative numbers.

Sample 3

Input	Output
100 100 100 -100	40000 Takahashi

Problem G. Seats 2

Time Limit 2000 ms

Problem Statement

There are N seats arranged in a row. Each seat can accommodate at most one person. Determine whether it is possible to seat M people in the seats satisfying the following condition.

> No two adjacent seats may both be occupied.

Constraints

- $1 \leq N, M \leq 100$
- All input values are integers.

Input

The input is given from Standard Input in the following format:

```
N M
```

Output

Output `Yes` if it is possible to seat the people satisfying the condition, and `No` otherwise.

Sample 1

Input	Output
6 3	Yes

For example, seating people in the first, third, and sixth seats from the left is one valid way. Thus, output `Yes`.

Sample 2

Input	Output
4 3	No

There is no valid way to seat the people satisfying the condition. Thus, output `No`.

Sample 3

Input	Output
5 3	Yes

Sample 4

Input	Output
44 7	Yes

Problem H. String Transformation

Time Limit 2000 ms

Problem Statement

You are given strings S and T consisting of lowercase English letters.

You can perform the following operation on S any number of times:

Operation: Choose two distinct lowercase English letters c_1 and c_2, then replace every occurrence of c_1 with c_2, and every occurrence of c_2 with c_1.

Determine if S and T can be made equal by performing the operation zero or more times.

Constraints

- $1 \leq |S| \leq 2 \times 10^5$
- $|S| = |T|$
- S and T consists of lowercase English letters.

Input

Input is given from Standard Input in the following format:

S
T

Output

If S and T can be made equal, print `Yes`; otherwise, print `No`.

Sample 1

Input	Output
`azzel` `apple`	`Yes`

`azzel` can be changed to `apple`, as follows:

- Choose `e` as c_1 and `l` as c_2. `azzel` becomes `azzle`.
- Choose `z` as c_1 and `p` as c_2. `azzle` becomes `apple`.

Sample 2

Input	Output
chokudai redcoder	No

No sequences of operation can change `chokudai` to `redcoder`.

Sample 3

Input	Output
abcdefghijklmnopqrstuvwxyz ibyhqfrekavclxjstdwgpzmonu	Yes

Problem I. Weird Algorithm

Time Limit 1000 ms
Mem Limit 524288 kB

Consider an algorithm that takes as input a positive integer n. If n is even, the algorithm divides it by two, and if n is odd, the algorithm multiplies it by three and adds one. The algorithm repeats this, until n is one. For example, the sequence for $n = 3$ is as follows:

$$3 \to 10 \to 5 \to 16 \to 8 \to 4 \to 2 \to 1$$

Your task is to simulate the execution of the algorithm for a given value of n.

Input

The only input line contains an integer n.

Output

Print a line that contains all values of n during the algorithm.

Constraints

- $1 \leq n \leq 10^6$

Example

Input	Output
3	3 10 5 16 8 4 2 1

Problem J. Assembly via Minimums

Time Limit 2000 ms
Mem Limit 262144 kB

Sasha has an array a of n integers. He got bored and for all i, j $(i < j)$, he wrote down the minimum value of a_i and a_j. He obtained a new array b of size $\frac{n \cdot (n-1)}{2}$.

For example, if $a = [2, 3, 5, 1]$, he would write [
$\min(2, 3), \min(2, 5), \min(2, 1), \min(3, 5), \min(3, 1), min(5, 1)] = [2, 2, 1, 3, 1, 1]$.

Then, he randomly **shuffled** all the elements of the array b.

Unfortunately, he forgot the array a, and your task is to restore any possible array a from which the array b could have been obtained.

The elements of array a should be in the range $[-10^9, 10^9]$.

Input

The first line contains a single integer t $(1 \le t \le 200)$ — the number of test cases.

The first line of each test case contains a single integer n $(2 \le n \le 10^3)$ — the length of array a.

The second line of each test case contains $\frac{n \cdot (n-1)}{2}$ integers $b_1, b_2, \ldots, b_{\frac{n \cdot (n-1)}{2}}$ $(-10^9 \le b_i \le 10^9)$ — the elements of array b.

It is guaranteed that the sum of n over all tests does not exceed 10^3 and for each array b in the test, there exists an original array.

Output

For each test case, output any possible array a of length n.

Examples

Input	Output
5 3 1 3 1 2 10 4 7 5 3 5 3 3 5 2 2 2 2 2 2 2 2 2 2 5 3 0 0 -2 0 -2 0 0 -2 -2	1 3 3 10 10 7 5 3 12 2 2 2 2 2 0 -2 0 3 5

Note

In the first sample, Sasha chose the array $[1, 3, 3]$, then the array b will look like $[\min(a_1, a_2) = 1, \min(a_1, a_3) = 1, \min(a_2, a_3) = 3]$, after shuffling its elements, the array can look like $[1, 3, 1]$.

In the second sample, there is only one pair, so the array $[10, 10]$ is suitable. Another suitable array could be $[15, 10]$.

Problem K. Discord

Time Limit 2000 ms

Problem Statement

N people numbered $1, 2, \ldots, N$ were in M photos. In each of the photos, they stood in a single line. In the i-th photo, the j-th person from the left is person $a_{i,j}$.

Two people who did not stand next to each other in any of the photos may be in a bad mood.

How many pairs of people may be in a bad mood? Here, we do not distinguish a pair of person x and person y, and a pair of person y and person x.

Constraints

- $2 \leq N \leq 50$
- $1 \leq M \leq 50$
- $1 \leq a_{i,j} \leq N$
- $a_{i,1}, \ldots, a_{i,N}$ contain each of $1, \ldots, N$ exactly once.
- All values in the input are integers.

Input

The input is given from Standard Input in the following format:

$$
\begin{array}{l}
N \ \ M \\
a_{1,1} \ \ \ldots \ \ a_{1,N} \\
\vdots \\
a_{M,1} \ \ \ldots \ \ a_{M,N}
\end{array}
$$

Output

Print the answer.

Sample 1

Input	Output
4 2 1 2 3 4 4 3 1 2	2

The pair of person 1 and person 4, and the pair of person 2 and person 4, may be in a bad mood.

Sample 2

Input	Output
3 3 1 2 3 3 1 2 1 2 3	0

Sample 3

Input	Output
10 10 4 10 7 2 8 3 9 1 6 5 3 6 2 9 1 8 10 7 4 5 9 3 4 5 7 10 1 8 2 6 7 3 1 8 4 9 5 6 2 10 5 2 1 4 10 7 9 8 3 6 5 8 1 6 9 3 2 4 7 10 8 10 3 4 5 7 2 9 6 1 3 10 2 7 8 5 1 4 9 6 10 6 1 5 4 2 3 8 9 7 4 5 9 1 8 2 7 6 3 10	6

Problem L. Smallest Difference

Time Limit	1000 ms
Mem Limit	262144 kB
OS	Windows
Statement	Statements (en)

You are given an array a consists of n elements, find the maximum number of elements you can select from the array such that the absolute difference between any two of the chosen elements is ≤ 1.

Input

The first line contains an integer $T (1 \leq T \leq 100)$, in which T is the number of test cases.

The first line of each test case consist of an integer $n (2 \leq n \leq 10^4)$, in which n is size of the array a

The a line follow containing n elements $a_1, a_2, \ldots, a_n (1 \leq a_i \leq 10^4)$, giving the array a.

Output

For each test case, print a single line containing the maximum number of elements you can select from the array such that the absolute difference between any two of the chosen elements is ≤ 1.

Examples

Input	Output
2 3 1 2 3 5 2 2 3 4 5	2 3

Problem M. Remove Two Letters

Time Limit 2000 ms
Mem Limit 262144 kB

Dmitry has a string s, consisting of lowercase Latin letters.

Dmitry decided to remove two **consecutive** characters from the string s and you are wondering how many different strings can be obtained after such an operation.

For example, Dmitry has a string "aaabcc". You can get the following different strings: "abcc"(by deleting the first two or second and third characters), "aacc"(by deleting the third and fourth characters),"aaac"(by deleting the fourth and the fifth character) and "aaab" (by deleting the last two).

Input

The first line of input data contains a single integer t ($1 \le t \le 10^4$) — number of test cases.

The descriptions of the test cases follow.

The first line of the description of each test case contains an integer n ($3 \le n \le 2 \cdot 10^5$).

The second line of the description of each test case contains a string s of length n consisting of lowercase Latin letters.

It is guaranteed that the sum of n for all test cases does not exceed $2 \cdot 10^5$.

Output

For each test case print one integer — the number of distinct strings that can be obtained by removing two consecutive letters.

Examples

Input	Output
7 6 aaabcc 10 aaaaaaaaaa 6 abcdef 7 abacaba 6 cccfff 4 abba 5 ababa	4 1 5 3 3 3 1

Note

The first example is explained in the statement.

In the third example, the following strings are obtained: "cdef", "adef", "abef", "abcf", "abcd".

In the seventh example, any deletion will result in the string "aba".

Problem N. Find Divisible

Time Limit 2000 ms
Mem Limit 262144 kB

You are given a range of positive integers from l to r.

Find such a pair of integers (x, y) that $l \le x, y \le r$, $x \ne y$ and x divides y.

If there are multiple answers, print any of them.

You are also asked to answer T independent queries.

Input

The first line contains a single integer T ($1 \le T \le 1000$) — the number of queries.

Each of the next T lines contains two integers l and r ($1 \le l \le r \le 998244353$) — inclusive borders of the range.

It is guaranteed that testset only includes queries, which have at least one suitable pair.

Output

Print T lines, each line should contain the answer — two integers x and y such that $l \le x, y \le r$, $x \ne y$ and x divides y. The answer in the i-th line should correspond to the i-th query from the input.

If there are multiple answers, print any of them.

Examples

Input	Output
3 1 10 3 14 1 10	1 7 3 9 5 10

Problem O. 1D Keyboard

Time Limit 2000 ms

Problem Statement

There is a keyboard with 26 keys arranged on a number line.

The arrangement of this keyboard is represented by a string S, which is a permutation of `ABCDEFGHIJKLMNOPQRSTUVWXYZ`. The key corresponding to the character S_x is located at coordinate x $(1 \leq x \leq 26)$. Here, S_x denotes the x-th character of S.

You will use this keyboard to input `ABCDEFGHIJKLMNOPQRSTUVWXYZ` in this order, typing each letter exactly once with your right index finger. To input a character, you need to move your finger to the coordinate of the key corresponding to that character and press the key.

Initially, your finger is at the coordinate of the key corresponding to `A`. Find the minimal possible total traveled distance of your finger from pressing the key for `A` to pressing the key for `Z`. Here, pressing a key does not contribute to the distance.

Constraints

- S is a permutation of `ABCDEFGHIJKLMNOPQRSTUVWXYZ`.

Input

The input is given from Standard Input in the following format:

```
S
```

Output

Print the answer.

Sample 1

Input	Output
ABCDEFGHIJKLMNOPQRSTUVWXYZ	25

From pressing the key for `A` to pressing the key for `Z`, you need to move your finger 1 unit at a time in the positive direction, resulting in a total traveled distance of 25. It is impossible to press all keys with a total traveled distance less than 25, so print `25`.

Sample 2

Input	Output
MGJYIZDKSBHPVENFLQURTCWOAX	223

Problem P. Beautiful Matrix

Time Limit	2000 ms
Mem Limit	262144 kB
Input File	stdin
Output File	stdout

You've got a 5×5 matrix, consisting of 24 zeroes and a single number one. Let's index the matrix rows by numbers from 1 to 5 from top to bottom, let's index the matrix columns by numbers from 1 to 5 from left to right. In one move, you are allowed to apply one of the two following transformations to the matrix:

1. Swap two neighboring matrix rows, that is, rows with indexes i and $i + 1$ for some integer i $(1 \le i < 5)$.
2. Swap two neighboring matrix columns, that is, columns with indexes j and $j + 1$ for some integer j $(1 \le j < 5)$.

You think that a matrix looks *beautiful*, if the single number one of the matrix is located in its middle (in the cell that is on the intersection of the third row and the third column). Count the minimum number of moves needed to make the matrix beautiful.

Input

The input consists of five lines, each line contains five integers: the j-th integer in the i-th line of the input represents the element of the matrix that is located on the intersection of the i-th row and the j-th column. It is guaranteed that the matrix consists of 24 zeroes and a single number one.

Output

Print a single integer — the minimum number of moves needed to make the matrix beautiful.

Examples

Input	Output
0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	3

Input	Output
0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0	1

Problem Q. Isosceles

Time Limit 2000 ms

Problem Statement

There is a triangle ABC with positive area.
The lengths of the three sides of triangle ABC are a, b, c.

Determine whether triangle ABC is isosceles.

Constraints

- $1 \leq a, b, c \leq 10$
- A triangle with side lengths a, b, c exists, and its area is positive.
- a, b, c are integers.

Input

The input is given from Standard Input in the following format:

```
a b c
```

Output

If triangle ABC is isosceles, output `Yes`; otherwise, output `No`.

Sample 1

Input	Output
4 2 4	Yes

Since $a = c$, triangle ABC is isosceles. Thus, output `Yes`.

Sample 2

Input	Output
3 4 5	No

Since the three side lengths of triangle ABC are all different, it is not isosceles. Thus, output `No`.

Sample 3

Input	Output
10 10 10	Yes

Note that an equilateral triangle is a kind of isosceles triangle.

Problem R. Petya and Strings

Time Limit	2000 ms
Mem Limit	262144 kB
Input File	stdin
Output File	stdout

Little Petya loves presents. His mum bought him two strings of the same size for his birthday. The strings consist of uppercase and lowercase Latin letters. Now Petya wants to compare those two strings lexicographically. The letters' case does not matter, that is an uppercase letter is considered equivalent to the corresponding lowercase letter. Help Petya perform the comparison.

Input

Each of the first two lines contains a bought string. The strings' lengths range from 1 to 100 inclusive. It is guaranteed that the strings are of the same length and also consist of uppercase and lowercase Latin letters.

Output

If the first string is less than the second one, print "-1". If the second string is less than the first one, print "1". If the strings are equal, print "0". Note that the letters' case is not taken into consideration when the strings are compared.

Examples

Input	Output
aaaa aaaA	0

Input	Output
abs Abz	-1

Input	Output
abcdefg AbCdEfF	1

Note

If you want more formal information about the lexicographical order (also known as the "dictionary order" or "alphabetical order"), you can visit the following site:

- http://en.wikipedia.org/wiki/Lexicographical_order

Problem S. Next

Time Limit 2000 ms

Problem Statement

You are given N integers $A_1, A_2, \ldots, A_N$. Find the largest among those integers that are not the largest.

The constraints of this problem guarantee that the answer exists.

Constraints

- $2 \leq N \leq 100$
- $1 \leq A_i \leq 100$
- It is not the case that all $A_1, A_2, \ldots, A_N$ are equal.
- All input values are integers.

Input

The input is given from Standard Input in the following format:

$$N$$
$$A_1 \ A_2 \ \ldots \ A_N$$

Output

Print the answer.

Sample 1

Input	Output
5 2 1 3 3 2	2

The largest integer among $2, 1, 3, 3, 2$ is 3.

The integers that are not 3 among 2, 1, 3, 3, 2 are 2, 1, 2, among which the largest is 2.

Sample 2

Input	Output
4 4 3 2 1	3

Sample 3

Input	Output
8 22 22 18 16 22 18 18 22	18

Problem T. Count ABC Again

Time Limit 2000 ms

Problem Statement

You are given a string S of length N. You are also given Q queries, which you should process in order.

The i-th query is as follows:

- Given an integer X_i and a character C_i, replace the X_i-th character of S with C_i. Then, print the number of times the string `ABC` appears as a substring in S.

Here, a **substring** of S is a string obtained by deleting zero or more characters from the beginning and zero or more characters from the end of S.
For example, `ab` is a substring of `abc`, but `ac` is not a substring of `abc`.

Constraints

- $3 \leq N \leq 2 \times 10^5$
- $1 \leq Q \leq 2 \times 10^5$
- S is a string of length N consisting of uppercase English letters.
- $1 \leq X_i \leq N$
- C_i is an uppercase English letter.

Input

The input is given from Standard Input in the following format:

$$
\begin{array}{l}
N \ \ Q \\
S \\
X_1 \ \ C_1 \\
X_2 \ \ C_2 \\
\vdots \\
X_Q \ \ C_Q
\end{array}
$$

Output

Print Q lines. The i-th line $(1 \leq i \leq Q)$ should contain the answer to the i-th query.

Sample 1

Input	Output
7 4 ABCDABC 4 B 3 A 5 C 4 G	2 1 1 0

After processing each query, S becomes as follows.

- After the first query: $S =$ `ABCBABC`. In this string, `ABC` appears twice as a substring.
- After the second query: $S =$ `ABABABC`. In this string, `ABC` appears once as a substring.
- After the third query: $S =$ `ABABCBC`. In this string, `ABC` appears once as a substring.
- After the fourth query: $S =$ `ABAGCBC`. In this string, `ABC` appears zero times as a substring.

Sample 2

Input	Output
3 3 ABC 1 A 2 B 3 C	1 1 1

There are cases where S does not change through processing a query.

Sample 3

Input	Output
15 10 BBCCBCACCBACACA 9 C 11 B 5 B 11 B 4 A 8 C 8 B 5 B 7 B 14 B	0 0 0 0 1 1 2 2 1 1