Search endpoint descriptions

Manage search resources including alerts triggered by searches, Python search command information, saved searches, search results, and scheduled view objects.

Semantic API versioning

Beginning with Splunk Enterprise version 9.0.1 and Splunk Cloud Platform version 9.0.2208, some REST API endpoints are available in multiple versions. The v1 instances of some endpoints are deprecated, and v2 instances of these endpoints are available. Plan to migrate to the v2 instances of each of the following endpoints:

- search/v2/jobs/export
- search/v2/jobs/{search_id}/events
- search/v2/jobs/{search_id}/results
- search/v2/jobs/{search_id}/results_preview
- search/v2/parser

You can address all original v1 endpoints either without a version number or with a v1 in the URI, but you can address v2 endpoints only with a v2 in the URI. Refer to the individual v2 endpoints for examples.

Legacy versioning deprecation

Beginning with Splunk Enterprise 9.0.1, the legacy versioning scheme from Splunk Enterprise 6.1 and lower is deprecated and will be removed in future versions of Splunk Enterprise. REST API endpoint behavior will not vary by Splunk Enterprise product version, but rather by API version only.

Do not include a Splunk Enterprise version number in URIs. Plan to migrate to the semantic versioning scheme with only v1 or v2 specified in URIs.

Avoid versioning endpoints like the following example:

CODE

```
https://localhost:8089/v6.1/services/search/jobs/export
```

Instead, refer to this v1 endpoint without any version or with v1 only, like the following example:

CODE

```
https://localhost:8089/services/search/jobs/export
```

CODE

```
https://localhost:8089/services/search/v1/jobs/export
```

Refer to this v2 endpoint like the following example:

CODE

```
https://localhost:8089/services/search/v2/jobs/export
```

Locate the source of your deprecated REST calls

If any apps or users in your environment are still using deprecated REST API version 1.0 endpoints, you should identify the source of the calls and transition all apps and users to version 2 instances of those endpoints.

1. Identify which apps are making deprecated REST calls by running the following search, which lists the calls to each deprecated endpoint in use by any apps in your environment.
   CODE

   ```
   index=_internal source=*splunkd*.log "A REST call to the deprecated endpoint"
   ```

   Once you have identified which apps are using the deprecated endpoints, update the apps to make sure that they call version 2 instances of those endpoints instead.
2. After you're sure that all apps in your environment have been upgraded to the version 2 REST API endpoints, check whether any users are still calling the deprecated endpoints. Run the following search, which lists the users and deprecated endpoints they are calling.
   CODE

   ```
   index=_internal (sourcetype=splunkd_access) method="GET"
   | where
       uri like "%/results_preview?search=%"
       OR uri like "%/results_preview?%&search=%"

       OR uri like "%/events?search=%"
   ```

```
    OR uri like "%/events?%&search=%"

    OR uri like "%/results?search=%"
    OR uri like "%/results?%&search=%"

    OR uri like "%/jobs/export?search=%"
    OR uri like "%/jobs/export?%&search=%"
    OR uri like "%/jobs/export%"

    OR uri like "%/parser%"
| table uri, user, useragent
```

Now that you know which users are calling deprecated endpoints, let them know that they must upgrade to version 2 instances of those endpoints.

Usage details

Review ACL information for an endpoint

To check Access Control List (ACL) properties for an endpoint, append `/acl` to the path. For more information see Access Control List in the *REST API User Manual*.

Authentication and Authorization

Username and password authentication is required for access to endpoints and REST operations.

Splunk users must have role and/or capability-based authorization to use REST endpoints. Users with an administrative role, such as `admin`, can access authorization information in Splunk Web. To view the roles assigned to a user, select Settings > Access controls and click Users. To determine the capabilities assigned to a role, select Settings > Access controls and click Roles.

App and user context

Typically, knowledge objects, such as saved searches or event types, have an app/user context that is the namespace. For more information about specifying a namespace, see Namespace in the *REST API User Manual*.

Splunk Cloud URL for REST API access

Splunk Cloud has a different host and management port syntax than Splunk Enterprise. Use the following URL for Splunk Cloud deployments. If necessary, submit a support case using the Splunk Support Portal to open port 8089 on your deployment.

CODE

```
https://<deployment-name>.splunkcloud.com:8089
```

Free trial Splunk Cloud accounts cannot access the REST API.

See Using the REST API in Splunk Cloud in the the *Splunk REST API Tutorials* for more information.

alerts/alert_actions

CODE

```
https://<host>:<mPort>/services/alerts/alert_actions
```

Access alert actions.

GET

Access a list of alert actions.

Request parameters

Pagination and filtering parameters can be used with this method.

Returned values

Varies depending on the type of alert.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/-/alerts/alert_actions
```

XML Response

JSON

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>alert_actions</title>
  <id>https://localhost:8089/servicesNS/-/-/alerts/alert_actions</id>
  <updated>2018-12-10T16:45:47-05:00</updated>
  <generator build="8c86330ac18" version="7.2.0"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/-/-/alerts/alert_actions/_reload" rel="_reload"/>
  <link href="/servicesNS/-/-/alerts/alert_actions/_acl" rel="_acl"/>
  <opensearch:totalResults>9</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>email</title>
    <id>https://localhost:8089/servicesNS/nobody/system/alerts/alert_actions/email</id>
    <updated>1969-12-31T19:00:00-05:00</updated>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/email" rel="alternate"/>
    <author>
      <name>nobody</name>
    </author>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/email" rel="list"/>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/email/_reload" rel="_reload"/>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/email" rel="edit"/>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/email/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="auth_password"></s:key>
        <s:key name="auth_username"></s:key>
        <s:key name="bcc"></s:key>
        <s:key name="cc"></s:key>
        <s:key name="cipherSuite">ECDHE-ECDSA-AES256-GCM-SHA384:ECDHE-RSA-AES256-GCM-SHA384:ECDHE-ECDSA-AES128-GCM-SHA256:ECDHE-RSA-AES128-GCM-
SHA256:ECDHE-ECDSA-AES256-SHA384:ECDHE-RSA-AES256-SHA384:ECDHE-ECDSA-AES128-SHA256:ECDHE-RSA-AES128-SHA256</s:key>
        <s:key name="command"><![CDATA[$action.email.preprocess_results{default=""}$ | sendemail "results_link=$results.url$" "ssname=$name$"
"graceful=$graceful{default=True}$" "trigger_time=$trigger_time$" maxinputs="$action.email.maxresults{default=10000}$"
maxtime="$action.email.maxtime{default=5m}$" results_file="$results.file$"]]></s:key>
        <s:key name="content_type">html</s:key>
        <s:key name="description">Send an email notification to specified recipients</s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">system</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">0</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">nobody</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list>
                    <s:item>admin</s:item>
                  </s:list>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">system</s:key>
          </s:dict>
        </s:key>
        <s:key name="eai:appName">system</s:key>
        <s:key name="eai:userName">nobody</s:key>
        <s:key name="footer.text">If you believe you've received this email in error, please see your Splunk administrator.

splunk > the engine for machine data</s:key>
        <s:key name="forceCsvResults">auto</s:key>
        <s:key name="format">table</s:key>
        <s:key name="from">splunk</s:key>
        <s:key name="hostname"></s:key>
        <s:key name="icon_path">mod_alert_icon_email.png</s:key>
        <s:key name="include.results_link">1</s:key>
        <s:key name="include.search">0</s:key>
        <s:key name="include.trigger">0</s:key>
        <s:key name="include.trigger_time">0</s:key>
        <s:key name="include.view_link">1</s:key>
        <s:key name="inline">0</s:key>
```

```
      <s:key name="label">Send email</s:key>
      <s:key name="mailserver">localhost</s:key>
      <s:key name="maxresults">10000</s:key>
      <s:key name="maxtime">5m</s:key>
      <s:key name="message.alert">The alert condition for '$name$' was triggered.</s:key>
      <s:key name="message.report">The scheduled report '$name$' has run.</s:key>
      <s:key name="pdf.footer_center">title</s:key>
      <s:key name="pdf.footer_enabled">1</s:key>
      <s:key name="pdf.footer_left">logo</s:key>
      <s:key name="pdf.footer_right">timestamp,pagination</s:key>
      <s:key name="pdf.header_center">description</s:key>
      <s:key name="pdf.header_enabled">1</s:key>
      <s:key name="pdf.html_image_rendering">1</s:key>
      <s:key name="pdfview"></s:key>
      <s:key name="preprocess_results"></s:key>
      <s:key name="priority">3</s:key>
      <s:key name="reportCIDFontList">gb cns jp kor</s:key>
      <s:key name="reportFileName">$name$-$time:%Y-%m-%d$</s:key>
      <s:key name="reportIncludeSplunkLogo">1</s:key>
      <s:key name="reportPaperOrientation">portrait</s:key>
      <s:key name="reportPaperSize">letter</s:key>
      <s:key name="sendcsv">0</s:key>
      <s:key name="sendpdf">0</s:key>
      <s:key name="sendresults">0</s:key>
      <s:key name="sslVersions">tls1.2</s:key>
      <s:key name="subject">Splunk Alert: $name$</s:key>
      <s:key name="subject.alert">Splunk Alert: $name$</s:key>
      <s:key name="subject.report">Splunk Report: $name$</s:key>
      <s:key name="to"></s:key>
      <s:key name="track_alert">1</s:key>
      <s:key name="ttl">86400</s:key>
      <s:key name="useNSSubject">0</s:key>
      <s:key name="use_ssl">0</s:key>
      <s:key name="use_tls">0</s:key>
      <s:key name="width_sort_columns">1</s:key>
    </s:dict>
  </content>
</entry>
<entry>
  <title>logevent</title>
  <id>https://localhost:8089/servicesNS/nobody/alert_logevent/alerts/alert_actions/logevent</id>
  <updated>1969-12-31T19:00:00-05:00</updated>
  <link href="/servicesNS/nobody/alert_logevent/alerts/alert_actions/logevent" rel="alternate"/>
  <author>
    <name>nobody</name>
  </author>
  <link href="/servicesNS/nobody/alert_logevent/alerts/alert_actions/logevent" rel="list"/>
  <link href="/servicesNS/nobody/alert_logevent/alerts/alert_actions/logevent/_reload" rel="_reload"/>
  <link href="/servicesNS/nobody/alert_logevent/alerts/alert_actions/logevent" rel="edit"/>
  <link href="/servicesNS/nobody/alert_logevent/alerts/alert_actions/logevent/disable" rel="disable"/>
  <content type="text/xml">
    <s:dict>
      <s:key name="command">sendalert $action_name$ results_file="$results.file$" results_link="$results.url$"</s:key>
      <s:key name="description">Send log event to Splunk receiver endpoint</s:key>
      <s:key name="disabled">0</s:key>
      <s:key name="eai:acl">
        <s:dict>
          <s:key name="app">alert_logevent</s:key>
          <s:key name="can_change_perms">1</s:key>
          <s:key name="can_list">1</s:key>
          <s:key name="can_share_app">1</s:key>
          <s:key name="can_share_global">1</s:key>
          <s:key name="can_share_user">0</s:key>
          <s:key name="can_write">1</s:key>
          <s:key name="modifiable">1</s:key>
          <s:key name="owner">nobody</s:key>
          <s:key name="perms">
            <s:dict>
              <s:key name="read">
                <s:list>
                  <s:item>*</s:item>
                </s:list>
              </s:key>
              <s:key name="write">
                <s:list>
                  <s:item>*</s:item>
                </s:list>
              </s:key>
            </s:dict>
          </s:key>
          <s:key name="removable">0</s:key>
          <s:key name="sharing">global</s:key>
        </s:dict>
      </s:key>
      <s:key name="eai:appName">alert_logevent</s:key>
      <s:key name="eai:userName">nobody</s:key>
      <s:key name="forceCsvResults">auto</s:key>
      <s:key name="hostname"></s:key>
      <s:key name="icon_path">logevent.png</s:key>
      <s:key name="is_custom">1</s:key>
      <s:key name="label">Log Event</s:key>
```

```
        <s:key name="maxresults">10000</s:key>
        <s:key name="maxtime">5m</s:key>
        <s:key name="param.host"></s:key>
        <s:key name="param.index">main</s:key>
        <s:key name="param.source">alert:$name$</s:key>
        <s:key name="param.sourcetype">generic_single_line</s:key>
        <s:key name="payload_format">json</s:key>
        <s:key name="track_alert">0</s:key>
        <s:key name="ttl">10p</s:key>
      </s:dict>
    </content>
  </entry>
  <entry>
    <title>lookup</title>
    <id>https://localhost:8089/servicesNS/nobody/system/alerts/alert_actions/lookup</id>
    <updated>1969-12-31T19:00:00-05:00</updated>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/lookup" rel="alternate"/>
    <author>
      <name>nobody</name>
    </author>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/lookup" rel="list"/>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/lookup/_reload" rel="_reload"/>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/lookup" rel="edit"/>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/lookup/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="append">0</s:key>
        <s:key name="command">outputlookup "$action.lookup.filename$" append=$action.lookup.append$</s:key>
        <s:key name="description">Output the results of the search to a CSV lookup file</s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">system</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">0</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">nobody</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list>
                    <s:item>admin</s:item>
                  </s:list>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">system</s:key>
          </s:dict>
        </s:key>
        <s:key name="eai:appName">system</s:key>
        <s:key name="eai:userName">nobody</s:key>
        <s:key name="filename"></s:key>
        <s:key name="forceCsvResults">auto</s:key>
        <s:key name="hostname"></s:key>
        <s:key name="icon_path">mod_alert_icon_lookup.png</s:key>
        <s:key name="label">Output results to lookup</s:key>
        <s:key name="maxresults">10000</s:key>
        <s:key name="maxtime">5m</s:key>
        <s:key name="track_alert">0</s:key>
        <s:key name="ttl">10p</s:key>
      </s:dict>
    </content>
  </entry>
  <entry>
    <title>outputtelemetry</title>
    <id>https://localhost:8089/servicesNS/nobody/splunk_instrumentation/alerts/alert_actions/outputtelemetry</id>
    <updated>1969-12-31T19:00:00-05:00</updated>
    <link href="/servicesNS/nobody/splunk_instrumentation/alerts/alert_actions/outputtelemetry" rel="alternate"/>
    <author>
      <name>nobody</name>
    </author>
    <link href="/servicesNS/nobody/splunk_instrumentation/alerts/alert_actions/outputtelemetry" rel="list"/>
    <link href="/servicesNS/nobody/splunk_instrumentation/alerts/alert_actions/outputtelemetry/_reload" rel="_reload"/>
    <link href="/servicesNS/nobody/splunk_instrumentation/alerts/alert_actions/outputtelemetry" rel="edit"/>
    <link href="/servicesNS/nobody/splunk_instrumentation/alerts/alert_actions/outputtelemetry/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="command"><![CDATA[outputtelemetry input=$action.outputtelemetry.param.input$ anonymous=$action.outputtelemetry.param.anonymous$
license=$action.outputtelemetry.param.license$ support=$action.outputtelemetry.param.support$ component=$action.outputtelemetry.param.component$
type=$action.outputtelemetry.param.type$ optinrequired=$action.outputtelemetry.param.optinrequired$]]></s:key>
        <s:key name="description">Custom action to output results to telemetry endpoint</s:key>
```

```
      <s:key name="disabled">0</s:key>
      <s:key name="eai:acl">
        <s:dict>
          <s:key name="app">splunk_instrumentation</s:key>
          <s:key name="can_change_perms">1</s:key>
          <s:key name="can_list">1</s:key>
          <s:key name="can_share_app">1</s:key>
          <s:key name="can_share_global">1</s:key>
          <s:key name="can_share_user">0</s:key>
          <s:key name="can_write">1</s:key>
          <s:key name="modifiable">1</s:key>
          <s:key name="owner">nobody</s:key>
          <s:key name="perms">
            <s:dict>
              <s:key name="read">
                <s:list>
                  <s:item>*</s:item>
                </s:list>
              </s:key>
              <s:key name="write">
                <s:list>
                  <s:item>admin</s:item>
                </s:list>
              </s:key>
            </s:dict>
          </s:key>
          <s:key name="removable">0</s:key>
          <s:key name="sharing">global</s:key>
        </s:dict>
      </s:key>
      <s:key name="eai:appName">splunk_instrumentation</s:key>
      <s:key name="eai:userName">nobody</s:key>
      <s:key name="forceCsvResults">auto</s:key>
      <s:key name="hostname"></s:key>
      <s:key name="icon_path">outputtelemetry.png</s:key>
      <s:key name="is_custom">1</s:key>
      <s:key name="label">Output results to telemetry endpoint</s:key>
      <s:key name="maxresults">10000</s:key>
      <s:key name="maxtime">5m</s:key>
      <s:key name="param.anonymous">1</s:key>
      <s:key name="param.component"></s:key>
      <s:key name="param.input"></s:key>
      <s:key name="param.license">0</s:key>
      <s:key name="param.optinrequired">1</s:key>
      <s:key name="param.support">1</s:key>
      <s:key name="param.type">event</s:key>
      <s:key name="track_alert">0</s:key>
      <s:key name="ttl">120</s:key>
    </s:dict>
  </content>
</entry>
<entry>
  <title>populate_lookup</title>
  <id>https://localhost:8089/servicesNS/nobody/system/alerts/alert_actions/populate_lookup</id>
  <updated>1969-12-31T19:00:00-05:00</updated>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/populate_lookup" rel="alternate"/>
  <author>
    <name>nobody</name>
  </author>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/populate_lookup" rel="list"/>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/populate_lookup/_reload" rel="_reload"/>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/populate_lookup" rel="edit"/>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/populate_lookup/disable" rel="disable"/>
  <content type="text/xml">
    <s:dict>
      <s:key name="command">copyresults dest="$action.populate_lookup.dest$"  sid="$search_id$"</s:key>
      <s:key name="dest"></s:key>
      <s:key name="disabled">0</s:key>
      <s:key name="eai:acl">
        <s:dict>
          <s:key name="app">system</s:key>
          <s:key name="can_change_perms">1</s:key>
          <s:key name="can_list">1</s:key>
          <s:key name="can_share_app">1</s:key>
          <s:key name="can_share_global">1</s:key>
          <s:key name="can_share_user">0</s:key>
          <s:key name="can_write">1</s:key>
          <s:key name="modifiable">1</s:key>
          <s:key name="owner">nobody</s:key>
          <s:key name="perms">
            <s:dict>
              <s:key name="read">
                <s:list>
                  <s:item>*</s:item>
                </s:list>
              </s:key>
              <s:key name="write">
                <s:list>
                  <s:item>admin</s:item>
                </s:list>
              </s:key>
```

```
            </s:dict>
          </s:key>
          <s:key name="removable">0</s:key>
          <s:key name="sharing">system</s:key>
        </s:dict>
      </s:key>
      <s:key name="eai:appName">system</s:key>
      <s:key name="eai:userName">nobody</s:key>
      <s:key name="forceCsvResults">auto</s:key>
      <s:key name="hostname"></s:key>
      <s:key name="maxresults">10000</s:key>
      <s:key name="maxtime">5m</s:key>
      <s:key name="track_alert">0</s:key>
      <s:key name="ttl">120</s:key>
    </s:dict>
  </content>
</entry>
<entry>
  <title>rss</title>
  <id>https://localhost:8089/servicesNS/nobody/system/alerts/alert_actions/rss</id>
  <updated>1969-12-31T19:00:00-05:00</updated>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/rss" rel="alternate"/>
  <author>
    <name>nobody</name>
  </author>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/rss" rel="list"/>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/rss/_reload" rel="_reload"/>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/rss" rel="edit"/>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/rss/disable" rel="disable"/>
  <content type="text/xml">
    <s:dict>
      <s:key name="command">createrss "path=$name$.xml" "name=$name$" "link=$results.url$" "descr=Alert trigger: $name$, results.count=$results.count$
" "count=30" "graceful=$graceful{default=1}$" maxtime="$action.rss.maxtime{default=1m}$"</s:key>
      <s:key name="disabled">0</s:key>
      <s:key name="eai:acl">
        <s:dict>
          <s:key name="app">system</s:key>
          <s:key name="can_change_perms">1</s:key>
          <s:key name="can_list">1</s:key>
          <s:key name="can_share_app">1</s:key>
          <s:key name="can_share_global">1</s:key>
          <s:key name="can_share_user">0</s:key>
          <s:key name="can_write">1</s:key>
          <s:key name="modifiable">1</s:key>
          <s:key name="owner">nobody</s:key>
          <s:key name="perms">
            <s:dict>
              <s:key name="read">
                <s:list>
                  <s:item>*</s:item>
                </s:list>
              </s:key>
              <s:key name="write">
                <s:list>
                  <s:item>admin</s:item>
                </s:list>
              </s:key>
            </s:dict>
          </s:key>
          <s:key name="removable">0</s:key>
          <s:key name="sharing">system</s:key>
        </s:dict>
      </s:key>
      <s:key name="eai:appName">system</s:key>
      <s:key name="eai:userName">nobody</s:key>
      <s:key name="forceCsvResults">auto</s:key>
      <s:key name="hostname"></s:key>
      <s:key name="maxresults">10000</s:key>
      <s:key name="maxtime">1m</s:key>
      <s:key name="track_alert">0</s:key>
      <s:key name="ttl">86400</s:key>
    </s:dict>
  </content>
</entry>
<entry>
  <title>script</title>
  <id>https://localhost:8089/servicesNS/nobody/system/alerts/alert_actions/script</id>
  <updated>1969-12-31T19:00:00-05:00</updated>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/script" rel="alternate"/>
  <author>
    <name>nobody</name>
  </author>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/script" rel="list"/>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/script/_reload" rel="_reload"/>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/script" rel="edit"/>
  <link href="/servicesNS/nobody/system/alerts/alert_actions/script/disable" rel="disable"/>
  <content type="text/xml">
    <s:dict>
      <s:key name="command">runshellscript "$action.script.filename$" "$results.count$" "$search$" "$search$" "$name$" "Saved Search [$name$]
$counttype$($results.count$)" "$results.url$" "$deprecated_arg$" "$search_id$" "$results.file$" maxtime="$action.script.maxtime{default=5m}$"</s:key>
      <s:key name="description">Invoke a custom script</s:key>
```

```
        <s:key name="disabled">0</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">system</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">0</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">nobody</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list>
                    <s:item>admin</s:item>
                  </s:list>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">system</s:key>
          </s:dict>
        </s:key>
        <s:key name="eai:appName">system</s:key>
        <s:key name="eai:userName">nobody</s:key>
        <s:key name="filename"></s:key>
        <s:key name="forceCsvResults">auto</s:key>
        <s:key name="hostname"></s:key>
        <s:key name="icon_path">mod_alert_icon_script.png</s:key>
        <s:key name="label">Run a script</s:key>
        <s:key name="maxresults">10000</s:key>
        <s:key name="maxtime">5m</s:key>
        <s:key name="track_alert">1</s:key>
        <s:key name="ttl">600</s:key>
      </s:dict>
    </content>
  </entry>
  <entry>
    <title>summary_index</title>
    <id>https://localhost:8089/servicesNS/nobody/system/alerts/alert_actions/summary_index</id>
    <updated>1969-12-31T19:00:00-05:00</updated>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/summary_index" rel="alternate"/>
    <author>
      <name>nobody</name>
    </author>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/summary_index" rel="list"/>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/summary_index/_reload" rel="_reload"/>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/summary_index" rel="edit"/>
    <link href="/servicesNS/nobody/system/alerts/alert_actions/summary_index/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="_name">summary</s:key>
        <s:key name="command"><![CDATA[summaryindex spool=t uselb=t addtime=t index="$action.summary_index._name{required=yes}$"
file="$name_hash$_$#random$.stash_new" name="$name$" marker="$action.summary_index*{format=$KEY=\\\"$VAL\\\", key_regex="action.summary_index.(?!
(?:command|inline|maxresults|maxtime|ttl|track_alert|(?:_.*))$)(.*)"}$"]]></s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">system</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">0</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">nobody</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list>
                    <s:item>admin</s:item>
                  </s:list>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">system</s:key>
          </s:dict>
```

```
        </s:key>
        <s:key name="eai:appName">system</s:key>
        <s:key name="eai:userName">nobody</s:key>
        <s:key name="forceCsvResults">auto</s:key>
        <s:key name="hostname"></s:key>
        <s:key name="inline">1</s:key>
        <s:key name="maxresults">10000</s:key>
        <s:key name="maxtime">5m</s:key>
        <s:key name="track_alert">0</s:key>
        <s:key name="ttl">120</s:key>
      </s:dict>
    </content>
  </entry>
  <entry>
    <title>webhook</title>
    <id>https://localhost:8089/servicesNS/nobody/alert_webhook/alerts/alert_actions/webhook</id>
    <updated>1969-12-31T19:00:00-05:00</updated>
    <link href="/servicesNS/nobody/alert_webhook/alerts/alert_actions/webhook" rel="alternate"/>
    <author>
      <name>nobody</name>
    </author>
    <link href="/servicesNS/nobody/alert_webhook/alerts/alert_actions/webhook" rel="list"/>
    <link href="/servicesNS/nobody/alert_webhook/alerts/alert_actions/webhook/_reload" rel="_reload"/>
    <link href="/servicesNS/nobody/alert_webhook/alerts/alert_actions/webhook" rel="edit"/>
    <link href="/servicesNS/nobody/alert_webhook/alerts/alert_actions/webhook/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="command">sendalert $action_name$ results_file="$results.file$" results_link="$results.url$"</s:key>
        <s:key name="description">Generic HTTP POST to a specified URL</s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">alert_webhook</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">0</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">nobody</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">global</s:key>
          </s:dict>
        </s:key>
        <s:key name="eai:appName">alert_webhook</s:key>
        <s:key name="eai:userName">nobody</s:key>
        <s:key name="forceCsvResults">auto</s:key>
        <s:key name="hostname"></s:key>
        <s:key name="icon_path">webhook.png</s:key>
        <s:key name="is_custom">1</s:key>
        <s:key name="label">Webhook</s:key>
        <s:key name="maxresults">10000</s:key>
        <s:key name="maxtime">5m</s:key>
        <s:key name="param.user_agent">Splunk/$server.guid$</s:key>
        <s:key name="payload_format">json</s:key>
        <s:key name="track_alert">0</s:key>
        <s:key name="ttl">10p</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```


alerts/fired_alerts

CODE

```
https://<host>:<mPort>/services/alerts/fired_alerts
```

Access fired alerts.

GET

Access a fired alerts summary.

Request parameters

Pagination and filtering parameters can be used with this method.

Returned values

Name	Description
triggered_alert_count	Trigger count for this alert.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/-/alerts/fired_alerts
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/"
      xmlns:s="http://dev.splunk.com/ns/rest">
  <title>alerts</title>
  <id>https://localhost:8089/services/alerts/fired_alerts</id>
  <updated>2011-07-11T19:27:22-07:00</updated>
  <generator version="102807"/>
  <author>
    <name>Splunk</name>
  </author>
  < opensearch nodes elided for brevity. >
  <s:messages/>
  <entry>
    <title>-</title>
    <id>https://localhost:8089/servicesNS/admin/search/alerts/fired_alerts/-</id>
    <updated>2011-07-11T19:27:22-07:00</updated>
    <link href="/servicesNS/admin/search/alerts/fired_alerts/-" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/alerts/fired_alerts/-" rel="list"/>
    <content type="text/xml">
      <s:dict>
        < eai:acl elided >
        <s:key name="triggered_alert_count">0</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

alerts/fired_alerts/{name}

JSON

```
https://<host>:<mPort>/services/alerts/fired_alerts/{name}
```

Access or delete the `{name}` triggered alert.

GET

List unexpired triggered instances of this alert.

Request parameters

None

Returned values

Name	Description
actions	Any additional alert actions triggered by this alert.
alert_type	Indicates if the alert was historical or real-time.
digest_mode	

Name	Description
expiration_time_rendered	
savedsearch_name	Name of the saved search that triggered the alert.
severity	Indicates the severity level of an alert. Severity level ranges from Info, Low, Medium, High, and Critical. Default is Medium. Severity levels are informational in purpose and have no additional functionality.
sid	The search ID of the search that triggered the alert.
trigger_time	The time the alert was triggered.
trigger_time_rendered	
triggered_alerts	

Application usage

Specify - for {name} to return all fired alerts.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/alerts/fired_alerts/MyAlert
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:s="http://dev.splunk.com/ns/rest"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>alerts</title>
  <id>https://localhost:8089/servicesNS/admin/search/alerts/fired_alerts</id>
  <updated>2012-10-25T09:20:04-07:00</updated>
  <generator build="138753" version="5.0"/>
  <author>
    <name>Splunk</name>
  </author>
  <!-- opensearch nodes elided for brevity. -->
  <s:messages/>
  <entry>
    <title>rt_scheduler__admin__search__MyAlert_at_1351181001_5.31_1351181987</title>
    <id>https://localhost:8089/servicesNS/nobody/search/alerts/fired_alerts/rt_scheduler__admin__search__MyAlert_at_1351181001_5.31_1351181987</id>
    <updated>2012-10-25T09:19:47-07:00</updated>
    <link href="/servicesNS/nobody/search/alerts/fired_alerts/rt_scheduler__admin__search__MyAlert_at_1351181001_5.31_1351181987" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <published>2012-10-25T09:19:47-07:00</published>
    <link href="/servicesNS/nobody/search/alerts/fired_alerts/rt_scheduler__admin__search__MyAlert_at_1351181001_5.31_1351181987" rel="list"/>
    <link href="/servicesNS/nobody/search/alerts/fired_alerts/rt_scheduler__admin__search__MyAlert_at_1351181001_5.31_1351181987" rel="remove"/>
    <link href="/servicesNS/nobody/search/search/jobs/rt_scheduler__admin__search__MyAlert_at_1351181001_5.31" rel="job"/>
    <link href="/servicesNS/nobody/search/saved/searches/MyAlert" rel="savedsearch"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="actions"/>
        <s:key name="alert_type">real time</s:key>
        <s:key name="digest_mode">0</s:key>
        <!-- eai:acl elided -->
        <s:key name="expiration_time_rendered">2012-10-26 09:19:47 PDT</s:key>
        <s:key name="savedsearch_name">MyAlert</s:key>
        <s:key name="severity">3</s:key>
        <s:key name="sid">rt_scheduler__admin__search__MyAlert_at_1351181001_5.31</s:key>
        <s:key name="trigger_time">1351181987</s:key>
        <s:key name="trigger_time_rendered">2012-10-25 09:19:47 PDT</s:key>
        <s:key name="triggered_alerts">5</s:key>
      </s:dict>
    </content>
  </entry>
  . . . elided . . .
</feed>
```

DELETE

Delete the record of this triggered alert.

Request parameters

None.

Response keys

None.

Example request and response

CODE

```
curl -k -u admin:pass --request DELETE
https://localhost:8089/servicesNS/admin/search/alerts/fired_alerts/scheduler__admin__search_aGF2ZV9ldmVudHM_at_1310437740_5d3dfde563194ffd_1310437749
```

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/"
      xmlns:s="http://dev.splunk.com/ns/rest">
  <title>alerts</title>
  <id>https://localhost:8089/servicesNS/admin/search/alerts/fired_alerts</id>
  <updated>2011-07-11T19:35:25-07:00</updated>
  <generator version="102807"/>
  <author>
    <name>Splunk</name>
  </author>
  <!-- opensearch nodes elided for brevity. -->
  <s:messages/>
</feed>
```

alerts/metric_alerts

CODE

```
https://<host>:<mPort>/services/alerts/metric_alerts
```

This endpoint lets you access and create streaming metric alerts.

Authentication and authorization

Only users whose roles have the `metric_alerts` capability can use this endpoint.

GET

Access streaming metric alert configurations.

Request parameters

None specific to this method. Pagination and filtering parameters can be used with this method.

Returned values

Name	Description
action.<action_name>	Indicates whether the `<action_name>` is enabled or disabled for a particular metric alert. Valid values for `action_name` are: • `email` • `logevent` • `rss` • `script` • `webhook` For more information about the alert action options see the `alert_actions.conf` file.
action.<action_name>.<parameter>	Overrides the setting defined for an action in the `alert_actions.conf` file with a new setting that is valid only for the metric alert configuration to which it is applied.
condition	Specifies an alert condition for one or more metric_name and aggregation pairs. The alert conditions can include multiple Boolean operators, eval functions, and metric aggregations. The Splunk software applies this evaluation to the results of the alert search on a regular interval. When the alert condition evaluates to 'true', the alert is triggered. Must reference at least one `'<mstats_aggregation>(<metric_name>)'` clause in single quotes. The condition can also reference dimensions specified in the `groupby` setting.
description	Description of the metric alert.
filter	Provides one or more Boolean expressions like `<dimension_field>=<value>` to define the search result dataset to monitor for the alert condition. Does not support subsearches, macros, tags, event types, or time modifiers such as 'earliest' or 'latest'. Combines with the `metric_indexes` setting to provide the complete search filter for the alert.

Name	Description
groupby	The list of dimension fields, delimited by comma, for the group-by clause of the alert search. This leads to multiple aggregation values, one per group, instead of one single value.
label.<label-name>	Arbitrary key-value pairs for labeling this alert.
metric_indexes	Specifies one or more metric indexes, delimited by comma. Combines with the `filter` setting to provide the complete search filter for the alert.
splunk_ui.<label-name>	An arbitrary key-value pair that is automatically generated by the Splunk software for its internal use only. Do not change it.
trigger.expires	Sets the period of time that a triggered alert record displays on the Triggered Alerts page.
trigger.max_tracked	Specifies the maximum number of instances of this alert that can display in the Triggered Alerts page. When this threshold is passed, the Splunk software removes the earliest instances from the Triggered Alerts page to honor this maximum number.
trigger.suppress	Specifies the suppression period to silence alert actions and notifications. • The suppression period goes into effect when an alert is triggered. • During this period, if the alert is triggered again, its actions do not happen and its notifications do not go out. • When the period elapses, a subsequent triggering of the alert causes alert actions and notifications to take place as usual, and the alert is suppressed again.

Example request and response

XML Request

CODE

```
$ curl -k -u admin:changeme https://localhost:8089/services/alerts/metric_alerts
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>metric_alerts</title>
  <id>https://localhost:8089/services/alerts/metric_alerts</id>
  <updated>2019-09-16T15:03:59-07:00</updated>
  <generator build="7170447726604e6ce5018fa5c563f5b631656bdf" version="20190910"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/alerts/metric_alerts/_new" rel="create"/>
  <link href="/services/alerts/metric_alerts/_reload" rel="_reload"/>
  <link href="/services/alerts/metric_alerts/_acl" rel="_acl"/>
  <opensearch:totalResults>2</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>malert-001</title>
    <id>https://localhost:8089/servicesNS/admin/search/alerts/metric_alerts/malert-001</id>
    <updated>2019-09-16T14:50:17-07:00</updated>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001" rel="list"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001" rel="edit"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001" rel="remove"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="_group_key">streamalert_0a01bceb2f9624ac</s:key>
        <s:key name="condition">'sum(spl.intr.resource_usage.Hostwide.data.cpu_count)'>=10</s:key>
        <s:key name="description"></s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">search</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">1</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">admin</s:key>
            <s:key name="perms"/>
```

```
            <s:key name="removable">1</s:key>
            <s:key name="sharing">user</s:key>
          </s:dict>
        </s:key>
        <s:key name="eai:appName">search</s:key>
        <s:key name="eai:userName">admin</s:key>
        <s:key name="filter">region=east</s:key>
        <s:key name="groupby"></s:key>
        <s:key name="metric_indexes">_metrics</s:key>
        <s:key name="trigger.expires">24h</s:key>
        <s:key name="trigger.max_tracked">20</s:key>
        <s:key name="trigger.suppress"></s:key>
      </s:dict>
    </content>
  </entry>
  <entry>
    <title>mpool used high</title>
    <id>https://localhost:8089/servicesNS/admin/search/alerts/metric_alerts/mpool%20used%20high</id>
    <updated>2019-09-16T09:59:35-07:00</updated>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/mpool%20used%20high" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/mpool%20used%20high" rel="list"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/mpool%20used%20high/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/mpool%20used%20high" rel="edit"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/mpool%20used%20high" rel="remove"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/mpool%20used%20high/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="_group_key">streamalert_d8b75eedcf404743</s:key>
        <s:key name="action.email">0</s:key>
        <s:key name="action.logevent">0</s:key>
        <s:key name="action.rss">0</s:key>
        <s:key name="action.script">0</s:key>
        <s:key name="action.webhook">1</s:key>
        <s:key name="action.webhook.command">sendalert $action_name$ results_file="$results.file$" results_link="$results.url$"</s:key>
        <s:key name="action.webhook.description">Generic HTTP POST to a specified URL</s:key>
        <s:key name="action.webhook.forceCsvResults">auto</s:key>
        <s:key name="action.webhook.icon_path">webhook.png</s:key>
        <s:key name="action.webhook.is_custom">1</s:key>
        <s:key name="action.webhook.label">Webhook</s:key>
        <s:key name="action.webhook.maxresults">10000</s:key>
        <s:key name="action.webhook.maxtime">5m</s:key>
        <s:key name="action.webhook.param.user_agent">Splunk/$server.guid$</s:key>
        <s:key name="action.webhook.payload_format">json</s:key>
        <s:key name="action.webhook.track_alert">0</s:key>
        <s:key name="action.webhook.ttl">10p</s:key>
        <s:key name="condition">'max(spl.mlog.mpool.used)' > 10000</s:key>
        <s:key name="description">spl.mlog.mpool.used too high</s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">search</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">1</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">admin</s:key>
            <s:key name="perms"/>
            <s:key name="removable">1</s:key>
            <s:key name="sharing">user</s:key>
          </s:dict>
        </s:key>
        <s:key name="eai:appName">search</s:key>
        <s:key name="eai:userName">admin</s:key>
        <s:key name="filter"></s:key>
        <s:key name="groupby"></s:key>
        <s:key name="metric_indexes">_metrics</s:key>
        <s:key name="splunk_ui.displayview">analytics_workspace</s:key>
        <s:key name="splunk_ui.managedBy">Analytics Workspace</s:key>
        <s:key name="splunk_ui.severity">1</s:key>
        <s:key name="splunk_ui.track">1</s:key>
        <s:key name="trigger.expires">24h</s:key>
        <s:key name="trigger.max_tracked">20</s:key>
        <s:key name="trigger.suppress">3m</s:key>
        <s:key name="triggered_alert_count">20</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```


POST

Create a streaming metric alert.

Request parameters

Name	Type	Description
action.<action-name>	Boolean	Indicates whether the `<action_name>` is enabled or disabled for a particular metric alert. Valid values for `action_name` are: • `email` • `logevent` • `rss` • `script` • `webhook` For more information about the alert action options see the `alert_actions.conf` file.
action.<action-name>.<parameter>	String	Override the global setting defined for an `<action-name>` in the `alert_actions.conf` file with a new setting that is valid only for the metric alert configuration to which it is applied.
condition required	Boolean `eval` expression	Specifies an alert condition for one or more metric_name and aggregation pairs. You can set alert conditions that include multiple Boolean operators, eval functions, and metric aggregations. The Splunk software applies this evaluation to the results of the alert search on a regular interval. When the alert condition evaluates to 'true', the alert is triggered. Must reference at least one `'<mstats_aggregation>(<metric_name>)'` clause in single quotes. The condition can also reference dimensions specified in the `groupby` setting.
description	String	Provide a description of the streaming metric alert.
filter	String	Specify one or more Boolean expressions like `<dimension_field>=<value>` to define the search result dataset to monitor for an alert condition. Link multiple Boolean expressions with the `AND` operator. The filter does not support subsearches, macros, tags, event types, or time modifiers such as 'earliest' or 'latest'. This setting combines with the `metric_indexes` setting to provide the complete search filter for the alert.
groupby	String	Provide a list of dimension fields, delimited by comma, for the group-by clause of the alert search. This results in multiple aggregation values, one per group, instead of one aggregation value.
label.<label-name>	String	Provide an arbitrary key-value pair to label or tag this alert. This key-value pair is not used by the Splunk alerting framework. You can design applications that use the alert label when they call the `alerts/metric_alerts` endpoint.
metric_indexes required	String	Specify one or more metric indexes, delimited by comma. Combines with the filter setting to define the search result dataset that the alert monitors for the alert condition.
name required	String	Specify the name of the streaming metric alert.
trigger.expires	String	Set the period of time that a triggered alert record displays on the Triggered Alerts page. • Use `<positive integer><time-unit>`, where `<time_unit>` can be 'm' for minutes, 'h' for hours, and 'd' for days. • Set to 0 to make triggered alerts expire immediately so they do not appear on the Triggered Alerts page at all. Default is 24h.
trigger.max_tracked	Number	Specify the maximum number of instances of this alert that can display in the triggered alerts dashboard. When this threshold is passed, the Splunk software removes the earliest jinstances from the dashboard to honor this maximum number. Set to 0 to remove the cap. Defaults to 20.

Name	Type	Description
trigger.suppress	String	Define the suppression period to silence alert actions and notifications. • The suppression period goes into effect when an alert is triggered. • During this period, if the alert is triggered again, its actions do not happen and its notifications do not go out. • When the period elapses, a subsequent triggering of the alert causes alert actions and notifications to take place as usual, and the alert is suppressed again. Use `<number>m` to specify a timespan in minutes. Default is 0m.

Returned values

None.

Example request and response

XML Request

CODE

```
$ curl -k -u admin:changeme https://localhost:8089/services/alerts/metric_alerts -X POST -d name=malert-001 -d
condition="'sum(spl.intr.resource_usage.Hostwide.data.cpu_count)'%3E%3D10" -d filter=region%3Deast -d metric_indexes=_metrics
```

XML response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>metric_alerts</title>
  <id>https://localhost:8089/services/alerts/metric_alerts</id>
  <updated>2019-09-16T15:07:52-07:00</updated>
  <generator build="7170447726604e6ce5018fa5c563f5b631656bdf" version="20190910"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/alerts/metric_alerts/_new" rel="create"/>
  <link href="/services/alerts/metric_alerts/_reload" rel="_reload"/>
  <link href="/services/alerts/metric_alerts/_acl" rel="_acl"/>
  <opensearch:totalResults>0</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
</feed>
```

alerts/metric_alerts/{alert_name}

JSON

```
https://<host>:<mPort>/services/alerts/metric_alerts/{alert_name}
```

This endpoint lets you create, update, delete, enable, and disable streaming metric alerts.

Authentication and authorization

Only users whose roles have the `metric_alerts` capability can use this endpoint.

GET

Access the named streaming metric alert.

Request parameters

None specific to this method. Pagination and filtering parameters can be used with this method.

Returned values

Name	Description

Name	Description
action.<action_name>	Indicates whether the `<action_name>` is enabled or disabled for a particular metric alert. Valid values for `action_name` are: • `email` • `logevent` • `rss` • `script` • `webhook` For more information about the alert action options see the `alert_actions.conf` file.
action.<action_name>.<parameter>	Overrides the setting defined for an action in the `alert_actions.conf` file with a new setting that is valid only for the metric alert configuration to which it is applied.
condition	Specifies an alert condition for one or more metric_name and aggregation pairs. The alert conditions can include multiple Boolean operators, eval functions, and metric aggregations. The Splunk software applies this evaluation to the results of the alert search on a regular interval. When the alert condition evaluates to 'true', the alert is triggered. Must reference at least one `'<mstats_aggregation>(<metric_name>)'` clause in single quotes. The condition can also reference dimensions specified in the `groupby` setting.
description	Description of the metric alert.
groupby	The list of dimension fields, delimited by comma, for the group-by clause of the alert search. This leads to multiple aggregation values, one per group, instead of one single value.
filter	Provides one or more Boolean expressions like `<dimension_field>=<value>` to define the search result dataset to monitor for the alert condition. Does not support subsearches, macros, tags, event types, or time modifiers such as 'earliest' or 'latest'. Combines with the `metric_indexes` setting to provide the complete search filter for the alert.
label.<label-name>	Arbitrary key-value pairs for labeling this alert.
metric_indexes	Specifies one or more metric indexes, delimited by comma. Combines with the `filter` setting to provide the complete search filter for the alert.
splunk_ui.<label-name>	An arbitrary key-value pair that is automatically generated by the Splunk software for its internal use only. Do not change it.
trigger.expires	Sets the period of time that a triggered alert record displays on the Triggered Alerts page.
trigger.max_tracked	Specifies the maximum number of instances of this alert that can display in the Triggered Alerts page. When this threshold is passed, the Splunk software removes the earliest instances from the Triggered Alerts page to honor this maximum number.
trigger.suppress	Specifies the suppression period to silence alert actions and notifications. • The suppression period goes into effect when an alert is triggered. • During this period, if the alert is triggered again, its actions do not happen and its notifications do not go out. • When the period elapses, a subsequent triggering of the alert causes alert actions and notifications to take place as usual, and the alert is suppressed again.

Example request and response

XML Request

CODE

```
$ curl -k -u admin:pass123 https://localhost:8089/services/alerts/metric_alerts/malert-001
```

XML Response

JSON

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>metric_alerts</title>
  <id>https://localhost:8089/services/alerts/metric_alerts</id>
  <updated>2019-09-16T14:51:17-07:00</updated>
  <generator build="7170447726604e6ce5018fa5c563f5b631656bdf" version="20190910"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/alerts/metric_alerts/_new" rel="create"/>
  <link href="/services/alerts/metric_alerts/_reload" rel="_reload"/>
  <link href="/services/alerts/metric_alerts/_acl" rel="_acl"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
```

```
  <s:messages/>
  <entry>
    <title>malert-001</title>
    <id>https://localhost:8089/servicesNS/admin/search/alerts/metric_alerts/malert-001</id>
    <updated>2019-09-16T14:50:17-07:00</updated>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001" rel="list"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001" rel="edit"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001" rel="remove"/>
    <link href="/servicesNS/admin/search/alerts/metric_alerts/malert-001/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="_group_key">streamalert_0a01bceb2f9624ac</s:key>
        <s:key name="action.email">0</s:key>
        <s:key name="action.email.auth_password"></s:key>
        <s:key name="action.email.auth_username"></s:key>
        <s:key name="action.email.bcc"></s:key>
        <s:key name="action.email.cc"></s:key>
        <s:key name="action.email.cipherSuite">ECDHE-ECDSA-AES256-GCM-SHA384:ECDHE-RSA-AES256-GCM-SHA384:ECDHE-ECDSA-AES128-GCM-SHA256:ECDHE-RSA-AES128-
GCM-SHA256:ECDHE-ECDSA-AES256-SHA384:ECDHE-RSA-AES256-SHA384:ECDHE-ECDSA-AES128-SHA256:ECDHE-RSA-AES128-SHA256</s:key>
        <s:key name="action.email.command"><![CDATA[$action.email.preprocess_results{default=""}$ | sendemail "results_link=$results.url$"
"ssname=$name$" "graceful=$graceful{default=True}$" "trigger_time=$trigger_time$" maxinputs="$action.email.maxresults{default=10000}$"
maxtime="$action.email.maxtime{default=5m}$" results_file="$results.file$"]]></s:key>
        <s:key name="action.email.content_type">html</s:key>
        <s:key name="action.email.description">Send an email notification to specified recipients</s:key>
        <s:key name="action.email.footer.text">If you believe you've received this email in error, please see your Splunk administrator.

splunk > the engine for machine data</s:key>
        <s:key name="action.email.forceCsvResults">auto</s:key>
        <s:key name="action.email.format">table</s:key>
        <s:key name="action.email.from">splunk</s:key>
        <s:key name="action.email.hostname"></s:key>
        <s:key name="action.email.icon_path">mod_alert_icon_email.png</s:key>
        <s:key name="action.email.include.results_link">1</s:key>
        <s:key name="action.email.include.search">0</s:key>
        <s:key name="action.email.include.trigger">0</s:key>
        <s:key name="action.email.include.trigger_time">0</s:key>
        <s:key name="action.email.include.view_link">1</s:key>
        <s:key name="action.email.inline">0</s:key>
        <s:key name="action.email.label">Send email</s:key>
        <s:key name="action.email.mailserver">localhost</s:key>
        <s:key name="action.email.maxresults">10000</s:key>
        <s:key name="action.email.maxtime">5m</s:key>
        <s:key name="action.email.message.alert">The alert condition for '$name$' was triggered.</s:key>
        <s:key name="action.email.message.report">The scheduled report '$name$' has run.</s:key>
        <s:key name="action.email.pdf.footer_center">title</s:key>
        <s:key name="action.email.pdf.footer_enabled">1</s:key>
        <s:key name="action.email.pdf.footer_left">logo</s:key>
        <s:key name="action.email.pdf.footer_right">timestamp,pagination</s:key>
        <s:key name="action.email.pdf.header_center">description</s:key>
        <s:key name="action.email.pdf.header_enabled">1</s:key>
        <s:key name="action.email.pdf.html_image_rendering">1</s:key>
        <s:key name="action.email.pdfview"></s:key>
        <s:key name="action.email.preprocess_results"></s:key>
        <s:key name="action.email.priority">3</s:key>
        <s:key name="action.email.reportCIDFontList">gb cns jp kor</s:key>
        <s:key name="action.email.reportFileName">$name$-$time:%Y-%m-%d$</s:key>
        <s:key name="action.email.reportIncludeSplunkLogo">1</s:key>
        <s:key name="action.email.reportPaperOrientation">portrait</s:key>
        <s:key name="action.email.reportPaperSize">letter</s:key>
        <s:key name="action.email.sendcsv">0</s:key>
        <s:key name="action.email.sendpdf">0</s:key>
        <s:key name="action.email.sendresults">0</s:key>
        <s:key name="action.email.sslVersions">tls1.2</s:key>
        <s:key name="action.email.subject">Splunk Alert: $name$</s:key>
        <s:key name="action.email.subject.alert">Splunk Alert: $name$</s:key>
        <s:key name="action.email.subject.report">Splunk Report: $name$</s:key>
        <s:key name="action.email.to"></s:key>
        <s:key name="action.email.track_alert">1</s:key>
        <s:key name="action.email.ttl">86400</s:key>
        <s:key name="action.email.useNSSubject">0</s:key>
        <s:key name="action.email.use_ssl">0</s:key>
        <s:key name="action.email.use_tls">0</s:key>
        <s:key name="action.email.width_sort_columns">1</s:key>
        <s:key name="action.logevent">0</s:key>
        <s:key name="action.logevent.command">sendalert $action_name$ results_file="$results.file$" results_link="$results.url$"</s:key>
        <s:key name="action.logevent.description">Send log event to Splunk receiver endpoint</s:key>
        <s:key name="action.logevent.forceCsvResults">auto</s:key>
        <s:key name="action.logevent.hostname"></s:key>
        <s:key name="action.logevent.icon_path">logevent.png</s:key>
        <s:key name="action.logevent.is_custom">1</s:key>
        <s:key name="action.logevent.label">Log Event</s:key>
        <s:key name="action.logevent.maxresults">10000</s:key>
        <s:key name="action.logevent.maxtime">5m</s:key>
        <s:key name="action.logevent.param.host"></s:key>
        <s:key name="action.logevent.param.index">main</s:key>
        <s:key name="action.logevent.param.source">alert:$name$</s:key>
```

```
        <s:key name="action.logevent.param.sourcetype">generic_single_line</s:key>
        <s:key name="action.logevent.payload_format">json</s:key>
        <s:key name="action.logevent.track_alert">0</s:key>
        <s:key name="action.logevent.ttl">10p</s:key>
        <s:key name="action.lookup">0</s:key>
        <s:key name="action.lookup.append">0</s:key>
        <s:key name="action.lookup.command">outputlookup "$action.lookup.filename$" append=$action.lookup.append$</s:key>
        <s:key name="action.lookup.description">Output the results of the search to a CSV lookup file</s:key>
        <s:key name="action.lookup.filename"></s:key>
        <s:key name="action.lookup.forceCsvResults">auto</s:key>
        <s:key name="action.lookup.hostname"></s:key>
        <s:key name="action.lookup.icon_path">mod_alert_icon_lookup.png</s:key>
        <s:key name="action.lookup.label">Output results to lookup</s:key>
        <s:key name="action.lookup.maxresults">10000</s:key>
        <s:key name="action.lookup.maxtime">5m</s:key>
        <s:key name="action.lookup.track_alert">0</s:key>
        <s:key name="action.lookup.ttl">10p</s:key>
        <s:key name="action.populate_lookup">0</s:key>
        <s:key name="action.populate_lookup.command">copyresults dest="$action.populate_lookup.dest$"  sid="$search_id$"</s:key>
        <s:key name="action.populate_lookup.dest"></s:key>
        <s:key name="action.populate_lookup.forceCsvResults">auto</s:key>
        <s:key name="action.populate_lookup.hostname"></s:key>
        <s:key name="action.populate_lookup.maxresults">10000</s:key>
        <s:key name="action.populate_lookup.maxtime">5m</s:key>
        <s:key name="action.populate_lookup.track_alert">0</s:key>
        <s:key name="action.populate_lookup.ttl">120</s:key>
        <s:key name="action.rss">0</s:key>
        <s:key name="action.rss.command">createrss "path=$name$.xml" "name=$name$" "link=$results.url$" "descr=Alert trigger: $name$,
results.count=$results.count$ " "count=30" "graceful=$graceful{default=1}$" maxtime="$action.rss.maxtime{default=1m}$"</s:key>
        <s:key name="action.rss.forceCsvResults">auto</s:key>
        <s:key name="action.rss.hostname"></s:key>
        <s:key name="action.rss.maxresults">10000</s:key>
        <s:key name="action.rss.maxtime">1m</s:key>
        <s:key name="action.rss.track_alert">0</s:key>
        <s:key name="action.rss.ttl">86400</s:key>
        <s:key name="action.script">0</s:key>
        <s:key name="action.script.command">runshellscript "$action.script.filename$" "$results.count$" "$search$" "$search$" "$name$" "Saved Search
[$name$] $counttype$($results.count$)" "$results.url$" "$deprecated_arg$" "$search_id$" "$results.file$" maxtime="$action.script.maxtime{default=5m}$"
</s:key>
        <s:key name="action.script.description">Invoke a custom script</s:key>
        <s:key name="action.script.filename"></s:key>
        <s:key name="action.script.forceCsvResults">auto</s:key>
        <s:key name="action.script.hostname"></s:key>
        <s:key name="action.script.icon_path">mod_alert_icon_script.png</s:key>
        <s:key name="action.script.label">Run a script</s:key>
        <s:key name="action.script.maxresults">10000</s:key>
        <s:key name="action.script.maxtime">5m</s:key>
        <s:key name="action.script.track_alert">1</s:key>
        <s:key name="action.script.ttl">600</s:key>
        <s:key name="action.summary_index">0</s:key>
        <s:key name="action.summary_index._name">summary</s:key>
        <s:key name="action.summary_index.command"><![CDATA[summaryindex spool=t uselb=t addtime=t index="$action.summary_index._name{required=yes}$"
file="$name_hash$_$#random$.stash_new" name="$name$" marker="$action.summary_index*{format=$KEY=\\\"$VAL\\\", key_regex="action.summary_index.(?!
(?:command|forceCsvResults|inline|maxresults|maxtime|python\\.version|ttl|track_alert|(?:_.*))$)(.*)"}$"]]></s:key>
        <s:key name="action.summary_index.forceCsvResults">auto</s:key>
        <s:key name="action.summary_index.hostname"></s:key>
        <s:key name="action.summary_index.inline">1</s:key>
        <s:key name="action.summary_index.maxresults">10000</s:key>
        <s:key name="action.summary_index.maxtime">5m</s:key>
        <s:key name="action.summary_index.track_alert">0</s:key>
        <s:key name="action.summary_index.ttl">120</s:key>
        <s:key name="action.webhook">0</s:key>
        <s:key name="action.webhook.command">sendalert $action_name$ results_file="$results.file$" results_link="$results.url$"</s:key>
        <s:key name="action.webhook.description">Generic HTTP POST to a specified URL</s:key>
        <s:key name="action.webhook.forceCsvResults">auto</s:key>
        <s:key name="action.webhook.hostname"></s:key>
        <s:key name="action.webhook.icon_path">webhook.png</s:key>
        <s:key name="action.webhook.is_custom">1</s:key>
        <s:key name="action.webhook.label">Webhook</s:key>
        <s:key name="action.webhook.maxresults">10000</s:key>
        <s:key name="action.webhook.maxtime">5m</s:key>
        <s:key name="action.webhook.param.user_agent">Splunk/$server.guid$</s:key>
        <s:key name="action.webhook.payload_format">json</s:key>
        <s:key name="action.webhook.track_alert">0</s:key>
        <s:key name="action.webhook.ttl">10p</s:key>
        <s:key name="condition">'sum(spl.intr.resource_usage.Hostwide.data.cpu_count)'>=10</s:key>
        <s:key name="description"></s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">search</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">1</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">admin</s:key>
            <s:key name="perms"/>
            <s:key name="removable">1</s:key>
```

```
          <s:key name="sharing">user</s:key>
        </s:dict>
      </s:key>
      <s:key name="eai:appName">search</s:key>
      <s:key name="eai:attributes">
        <s:dict>
          <s:key name="optionalFields">
            <s:list>
              <s:item>condition</s:item>
              <s:item>description</s:item>
              <s:item>disabled</s:item>
              <s:item>filter</s:item>
              <s:item>groupby</s:item>
              <s:item>metric_indexes</s:item>
              <s:item>trigger.condition</s:item>
              <s:item>trigger.expires</s:item>
              <s:item>trigger.max_tracked</s:item>
              <s:item>trigger.per_group</s:item>
              <s:item>trigger.suppress</s:item>
            </s:list>
          </s:key>
          <s:key name="requiredFields">
            <s:list/>
          </s:key>
          <s:key name="wildcardFields">
            <s:list>
              <s:item>action\..*</s:item>
              <s:item>label\..*</s:item>
              <s:item>splunk_ui\..*</s:item>
            </s:list>
          </s:key>
        </s:dict>
      </s:key>
      <s:key name="eai:userName">admin</s:key>
      <s:key name="filter">region=east</s:key>
      <s:key name="groupby"></s:key>
      <s:key name="metric_indexes">_metrics</s:key>
      <s:key name="trigger.expires">24h</s:key>
      <s:key name="trigger.max_tracked">20</s:key>
      <s:key name="trigger.suppress"></s:key>
    </s:dict>
  </content>
 </entry>
</feed>
```


POST

Update the named streaming metric alert.

Request parameters

Name	Type	Description
action.<action-name>	Boolean	Indicates whether the `<action_name>` is enabled or disabled for a particular metric alert. Valid values for `<action_name>` are: • `email` • `logevent` • `rss` • `script` • `webhook` For more information about the alert action options see the `alert_actions.conf` file.
action.<action-name>.<parameter>	String	Override the global setting defined for an `<action-name>` in the `alert_actions.conf` file with a new setting that is valid only for the metric alert configuration to which it is applied.
condition required	Boolean `eval` expression	Specifies an alert condition for one or more metric_name and aggregation pairs. You can set alert conditions that include multiple Boolean operators, eval functions, and metric aggregations. The Splunk software applies this evaluation to the results of the alert search on a regular interval. When the alert condition evaluates to 'true', the alert is triggered. Must reference at least one `'<mstats_aggregation>(<metric_name>)'` clause in single quotes. The condition can also reference dimensions specified in the `groupby` setting.
description	String	Provide a description of the streaming metric alert.
groupby	String	Provide a list of dimension fields, delimited by comma, for the group-by clause of the alert search. This results in multiple aggregation values, one per group, instead of one aggregation value.

Name	Type	Description
filter	String	Specify one or more Boolean expressions like `<dimension_field>=<value>` to define the search result dataset to monitor for an alert condition. Link multiple Boolean expressions with the 'AND' operator. The filter does not support subsearches, macros, tags, event types, or time modifiers such as 'earliest' or 'latest'. This setting combines with the `metric_indexes` setting to provide the complete search filter for the alert.
label.<label-name>	String	Provide an arbitrary key-value pair to label or tag this alert. This key-value pair is not used by the Splunk alerting framework. You can design applications that use the alert label when they call the `alerts/metric_alerts` endpoint.
metric_indexes required	String	Specify one or more metric indexes, delimited by comma. Combines with the filter setting to define the search result dataset that the alert monitors for the alert condition.
trigger.expires	String	Set the period of time that a triggered alert record displays on the Triggered Alerts page. • Use `<positive integer><time-unit>`, where `<time_unit>` can be 'm' for minutes, 'h' for hours, and 'd' for days. • Set to 0 to make triggered alerts expire immediately so they do not appear on the Triggered Alerts page at all. Default is 24h.
trigger.max_tracked	Number	Specify the maximum number of instances of this alert that can display in the triggered alerts dashboard. When this threshold is passed, the Splunk software removes the earliest instances from the dashboard to honor this maximum number. Set to 0 to remove the cap. Defaults to 20.
trigger.suppress	String	Define the suppression period to silence alert actions and notifications. • The suppression period goes into effect when an alert is triggered. • During this period, if the alert is triggered again, its actions do not happen and its notifications do not go out. • When the period elapses, a subsequent triggering of the alert causes alert actions and notifications to take place as usual, and the alert is suppressed again. Use `<number>`m to specify a timespan in minutes. Default is 0m.

Returned values

None.

Example request and response

XML Request

$ curl -k -u admin:changeme https://localhost:8089/services/alerts/metric_alerts/malert-002 -d description="updated description of malert-002" -d trigger.expires=1h

XML response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>metric_alerts</title>
  <id>https://localhost:8089/services/alerts/metric_alerts</id>
  <updated>2019-09-16T14:38:38-07:00</updated>
  <generator build="7170447726604e6ce5018fa5c563f5b631656bdf" version="20190910"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/alerts/metric_alerts/_new" rel="create"/>
  <link href="/services/alerts/metric_alerts/_reload" rel="_reload"/>
  <link href="/services/alerts/metric_alerts/_acl" rel="_acl"/>
  <opensearch:totalResults>0</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
</feed>
```

DELETE

Deletes the named metric alert.

Request parameters

None specific to this method.

Returned values

None specific to this method.

Example request and response

Remove the `[malert-002]` stanza from `metric_alerts.conf`.

XML Request

CODE

```
curl -k -u admin:changeme https://localhost:8089/services/alerts/metric_alerts/malert-002 -X DELETE
```

XML response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>metric_alerts</title>
  <id>https://localhost:8089/services/alerts/metric_alerts</id>
  <updated>2019-09-16T14:38:38-07:00</updated>
  <generator build="7170447726604e6ce5018fa5c563f5b631656bdf" version="20190910"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/alerts/metric_alerts/_new" rel="create"/>
  <link href="/services/alerts/metric_alerts/_reload" rel="_reload"/>
  <link href="/services/alerts/metric_alerts/_acl" rel="_acl"/>
  <opensearch:totalResults>0</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
</feed>
```

data/commands

CODE

```
https://<host>:<mPort>/services/data/commands
```

Access Python search commands.

GET

Access Python search commands.

Request parameters

Pagination and filtering parameters can be used with this method.

Returned values

Name	Description
changes_colorder	Indicates whether the script output should be used to change the column ordering of the fields.
disabled	Indicates if the command is disabled.
enableheader	Indicate whether or not your script is expecting header information or not. Currently, the only thing in the header information is an auth token. If set to true the command expects as input a head section + '\ ' then the csv input. *Note:* Should be set to true if you use splunk.Intersplunk
filename	Name of script file for command. <stanza-name>.pl for perl. <stanza-name>.py for python.
generates_timeorder	If generating = false and streaming = true, indicates if the command changes the order of events w/respect to time.

Name	Description
generating	Indicates if the command generates new events.
maxinputs	Maximum number of events that can be passed to the command for each invocation. This limit cannot exceed the value of maxresultrows in limits.conf. 0 indicates no limit. Defaults to 50000.
outputheader	If true, the output of script should be a header section + blank line + csv output. If false, script output should be pure csv only.
passauth	If true, passes an authentication token on the start of input.
required_fields	A list of fields that this command may use. Informs previous commands that they should retain/extract these fields if possible. No error is generated if a field specified is missing. Defaults to '*'.
requires_preop	Indicates whether the command sequence specified by the streaming_preop key is required for proper execution or is it an optimization only. Default is false (stremaing_preop not required).
retainsevents	Indicates whether the command retains events (the way the sort/dedup/cluster commands do) or whether the command transforms them (the way the stats command does).
streaming	Indicates whether the command is streamable.
supports_getinfo	Indicates whether the command supports dynamic probing for settings (first argument invoked == __GETINFO__ or __EXECUTE__).
supports_rawargs	Indicates whether the command supports raw arguments being passed to it or if it uses parsed arguments (where quotes are stripped).
type	Specifies the type of command. The only valid value for this attribute is `python`.

Example request and response

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/nobody/search/data/commands
```

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/"
      xmlns:s="http://dev.splunk.com/ns/rest">
  <title>commandsconf</title>
  <id>https://localhost:8089/servicesNS/nobody/search/data/commands</id>
  <updated>2011-07-07T00:52:26-07:00</updated>
  <generator version="102807"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/nobody/search/data/commands/_reload" rel="_reload"/>
  <s:messages/>
  <entry>
    <title>bucketdir</title>
    <id>https://localhost:8089/servicesNS/nobody/search/data/commands/bucketdir</id>
    <updated>2011-07-07T00:52:26-07:00</updated>
    <link href="/servicesNS/nobody/search/data/commands/bucketdir" rel="alternate"/>
    <author>
      <name>nobody</name>
    </author>
    <link href="/servicesNS/nobody/search/data/commands/bucketdir" rel="list"/>
    <link href="/servicesNS/nobody/search/data/commands/bucketdir/_reload" rel="_reload"/>
    <link href="/servicesNS/nobody/search/data/commands/bucketdir/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="changes_colorder">1</s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:appName">search</s:key>
        <s:key name="eai:userName">admin</s:key>
        <s:key name="enableheader">1</s:key>
        <s:key name="filename">bucketdir.py</s:key>
        <s:key name="generates_timeorder">0</s:key>
        <s:key name="generating">0</s:key>
        <s:key name="maxinputs">50000</s:key>
        <s:key name="outputheader">0</s:key>
        <s:key name="passauth">0</s:key>
        <s:key name="required_fields">*</s:key>
        <s:key name="requires_preop">0</s:key>
        <s:key name="retainsevents">0</s:key>
        <s:key name="streaming">0</s:key>
        <s:key name="supports_getinfo">0</s:key>
        <s:key name="supports_rawargs">1</s:key>
        <s:key name="type">python</s:key>
      </s:dict>
```

```
    </content>
  </entry>
</feed>
```

data/commands/{name}

JSON

`https://<host>:<mPort>/services/data/commands/{name}`

Get information about the `{name}` python search command.

GET

Access search command information.

Request parameters

None

Returned values

Name	Description
changes_colorder	Indicates whether the script output should be used to change the column ordering of the fields.
disabled	Indicates if the command is disabled.
enableheader	Indicate whether or not your script is expecting header information or not. Currently, the only thing in the header information is an auth token. If set to true the command expects as input a head section + '\ ' then the csv input. *Note:* Should be set to true if you use splunk.Intersplunk
filename	Name of script file for command. <stanza-name>.pl for perl. <stanza-name>.py for python.
generates_timeorder	If generating = false and streaming = true, indicates if the command changes the order of events w/respect to time.
generating	Indicates if the command generates new events.
maxinputs	Maximum number of events that can be passed to the command for each invocation. This limit cannot exceed the value of maxresultrows in limits.conf. 0 indicates no limit. Defaults to 50000.
outputheader	If true, the output of script should be a header section + blank line + csv output. If false, script output should be pure csv only.
passauth	If true, passes an authentication token on the start of input.
required_fields	A list of fields that this command may use. Informs previous commands that they should retain/extract these fields if possible. No error is generated if a field specified is missing. Defaults to '*'.
requires_preop	Indicates whether the command sequence specified by the streaming_preop key is required for proper execution or is it an optimization only. Default is false (stremaing_preop not required).
retainsevents	Indicates whether the command retains events (the way the sort/dedup/cluster commands do) or whether the command transforms them (the way the stats command does).
streaming	Indicates whether the command is streamable.
supports_getinfo	Indicates whether the command supports dynamic probing for settings (first argument invoked == __GETINFO__ or __EXECUTE__).
supports_rawargs	Indicates whether the command supports raw arguments being passed to it or if it uses parsed arguments (where quotes are stripped).
type	Specifies the type of command. The only valid value for this attribute is `python`.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/nobody/search/data/commands/input
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/"
      xmlns:s="http://dev.splunk.com/ns/rest">
  <title>commandsconf</title>
  <id>https://localhost:8089/servicesNS/nobody/search/data/commands</id>
  <updated>2011-07-07T00:52:26-07:00</updated>
  <generator version="102807"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/nobody/search/data/commands/_reload" rel="_reload"/>
  <s:messages/>
  <entry>
    <title>input</title>
    <id>https://localhost:8089/servicesNS/nobody/search/data/commands/input</id>
    <updated>2011-07-07T00:52:26-07:00</updated>
    <link href="/servicesNS/nobody/search/data/commands/input" rel="alternate"/>
    <author>
      <name>nobody</name>
    </author>
    <link href="/servicesNS/nobody/search/data/commands/input" rel="list"/>
    <link href="/servicesNS/nobody/search/data/commands/input/_reload" rel="_reload"/>
    <link href="/servicesNS/nobody/search/data/commands/input/disable" rel="disable"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="changes_colorder">1</s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:appName">search</s:key>
        <s:key name="eai:attributes">
          <s:dict>
            <s:key name="optionalFields">
              <s:list/>
            </s:key>
            <s:key name="requiredFields">
              <s:list/>
            </s:key>
            <s:key name="wildcardFields">
              <s:list/>
            </s:key>
          </s:dict>
        </s:key>
        <s:key name="eai:userName">admin</s:key>
        <s:key name="enableheader">1</s:key>
        <s:key name="filename">input.py</s:key>
        <s:key name="generates_timeorder">0</s:key>
        <s:key name="generating">0</s:key>
        <s:key name="maxinputs">50000</s:key>
        <s:key name="outputheader">0</s:key>
        <s:key name="passauth">1</s:key>
        <s:key name="required_fields">*</s:key>
        <s:key name="requires_preop">0</s:key>
        <s:key name="retainsevents">0</s:key>
        <s:key name="streaming">0</s:key>
        <s:key name="supports_getinfo">0</s:key>
        <s:key name="supports_rawargs">1</s:key>
        <s:key name="type">python</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

saved/searches

CODE

```
https://<host>:<mPort>/services/saved/searches
```

Access and create saved searches.

GET

Access saved search configurations.

Request parameters

Name	Type	Default	Description

Name	Type	Default	Description
earliest_time	String		For scheduled searches display all the scheduled times starting from this time (not just the next run time)
latest_time	String		For scheduled searches display all the scheduled times until this time (not just the next run time)
listDefaultActionArgs	Boolean		Indicates whether to list default actions.
add_orphan_field	Boolean		Indicates whether the response includes a boolean value for each saved search to show whether the search is orphaned, meaning that it has no valid owner. When *add_orphan_field* is set to `true`, the response includes the orphaned search indicators, either `0` to indicate that a search is not orphaned or `1` to indicate that the search is orphaned. Admins can use this setting to check for searches without valid owners and resolve related issues.

Pagination and filtering parameters can be used with this method.

This endpoint returns an unusually high number of values. To limit the number of returned values, specify the `f` filtering parameter.

Returned values

Name	Description
action.<action_name>	Indicates whether the `<action_name>` is enabled or disabled for a particular search. For more information about the alert action options see the `alert_actions.conf` file.
action.<action_name>.<parameter>	Overrides the setting defined for an action in the `alert_actions.conf` file with a new setting that is valid only for the search configuration to which it is applied.
action.email	Indicates the state of the email action.
action.email.auth_password	The password to use when authenticating with the SMTP server. Normally this value is set when editing the email settings, however you can set a clear text password here that is encrypted on the next restart. Defaults to empty string.
action.email.auth_username	The username to use when authenticating with the SMTP server. If this is empty string, no authentication is attempted. Defaults to empty string. *Note:* Your SMTP server might reject unauthenticated emails.
action.email.bcc	BCC email address to use if action.email is enabled.
action.email.cc	CC email address to use if action.email is enabled.
action.email.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.email.format	Specify the format of text in the email. This value also applies to any attachments. Valid values: (plain | html | raw | csv)
action.email.from	Email address from which the email action originates.
action.email.hostname	Sets the hostname used in the web link (url) sent in email actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) When this value is a simple hostname, the protocol and port which are configured within splunk are used to construct the base of the url. When this value begins with 'http://', it is used verbatim. *Note:* This means the correct port must be specified if it is not the default port for http or https. This is useful in cases when the Splunk server is not aware of how to construct a url that can be referenced externally, such as SSO environments, other proxies, or when the server hostname is not generally resolvable. Defaults to current hostname provided by the operating system, or if that fails "localhost." When set to empty, default behavior is used.

Name	Description
action.email.inline	Indicates whether the search results are contained in the body of the email. Results can be either inline or attached to an email. See action.email.sendresults.
action.email.mailserver	Set the address of the MTA server to be used to send the emails. Defaults to <LOCALHOST> (or whatever is set in alert_actions.conf).
action.email.maxresults	Sets the global maximum number of search results to send when email.action is enabled.
action.email.maxtime	Specifies the maximum amount of time the execution of an email action takes before the action is aborted.
action.email.preprocess_results	Search string to preprocess results before emailing them. Defaults to empty string (no preprocessing). Usually the preprocessing consists of filtering out unwanted internal fields.
action.email.reportPaperOrientation	Specifies the paper orientation: portrait or landscape.
action.email.reportPaperSize	Specifies the paper size for PDFs. Defaults to letter. Valid values: (letter | legal | ledger | a2 | a3 | a4 | a5)
action.email.reportServerEnabled	Not supported.
action.email.reportServerURL	Not supported.
action.email.sendpdf	Indicates whether to create and send the results as a PDF.
action.email.sendresults	Indicates whether to attach the search results in the email. Results can be either attached or inline. See action.email.inline.
action.email.subject	Specifies an email subject. Defaults to SplunkAlert-<savedsearchname>.
action.email.to	List of recipient email addresses. Required if this search is scheduled and the email alert action is enabled.
action.email.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.email.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows <Integer>, int is the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p].
action.email.use_ssl	Indicates whether to use SSL when communicating with the SMTP server.
action.email.use_tls	Indicates whether to use TLS (transport layer security) when communicating with the SMTP server (starttls).
action.populate_lookup	The state of the populate lookup action.
action.populate_lookup.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.populate_lookup.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.populate_lookup.maxresults	The maximum number of search results sent using alerts.
action.populate_lookup.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 5m. Valid values are: Integer[m|s|h|d]
action.populate_lookup.track_alert	Indicates whether the execution of this action signifies a trackable alert.

Name	Description
action.populate_lookup.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, then this specifies the number of scheduled periods. Defaults to 10p. If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p]
action.rss	The state of the RSS action.
action.rss.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.rss.hostname	Sets the hostname used in the web link (url) sent in alert actions.
action.rss.maxresults	Sets the maximum number of search results sent using alerts.
action.rss.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 1m.
action.rss.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.rss.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
action.script	The state of the script action.
action.script.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.script.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See *action.email.hostname* for details.
action.script.maxresults	The maximum number of search results sent using alerts.
action.script.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted.
action.script.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.script.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 600 (10 minutes). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
action.summary_index	Specifies whether the summary index action is enabled for this search.
action.summary_index._type"	Specifies the data type of the summary index where the Splunk software saves the results of the scheduled search. Can be set to `event` or `metric`.
action.summary_index.force_realtime_schedule	By default, *realtime_schedule* is `false` for a report configured for summary indexing. When set to `1` or `true`, this setting overrides *realtime_schedule*. Setting this setting to `true` can cause gaps in summary data, as a *realtime_schedule* search is skipped if search concurrency limits are violated.
action.summary_index.inline	Determines whether to execute the summary indexing action as part of the scheduled search. *Note:* This option is considered only if the summary index action is enabled and is always executed (in other words, if counttype = always).
action.summary_index.maxresults	Sets the maximum number of search results sent using alerts.
action.summary_index.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 5m.
action.summary_index.track_alert	Indicates whether the execution of this action signifies a trackable alert.

Name	Description
action.summary_index.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 10p.
alert.digest_mode	Indicates if alert actions are applied to the entire result set or to each individual result.
alert.expires	Sets the period of time to show the alert in the dashboard. Defaults to 24h. Uses [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
alert.managedBy	Specifies the feature or component that created the alert.
alert.severity	The alert severity level. Valid values are: 1 DEBUG 2 INFO 3 WARN 4 ERROR 5 SEVERE 6 FATAL
alert.suppress	Indicates whether alert suppression is enabled for this scheduled search.
alert.suppress.fields	List of fields to use when suppressing per-result alerts. Must be specified if the digest mode is disabled and suppression is enabled.
alert.suppress.group_name	Optional setting. Used to define an alert suppression group for a set of alerts that are running over identical or very similar datasets. Alert suppression groups can help you avoid getting multiple triggered alert notifications for the same data.
alert.suppress.period	Specifies the suppression period. Only valid if alert.suppress is enabled. Uses [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
alert.track	Specifies whether to track the actions triggered by this scheduled search. `auto` - (Default) Determine whether to apply alert tracking to this search, based on the tracking setting of each action. Do not track scheduled searches that always trigger actions. `true` - Force alert tracking for this search. Default. `false` - Disable alert tracking for this search.
alert_comparator	One of the following strings: greater than less than equal to rises by drops by rises by perc drops by perc Used with *alert_threshold* to trigger alert actions.
alert_condition	A conditional search that is evaluated against the results of the saved search. Defaults to an empty string. Alerts are triggered if the specified search yields a non-empty search result list. *Note:* If you specify an *alert_condition*, do not set counttype, relation, or quantity.
alert_threshold	Valid values are: Integer[%] Specifies the value to compare (see *alert_comparator*) before triggering the alert actions. If expressed as a percentage, indicates value to use when alert_comparator is set to *rises by perc" or "drops by perc."*
alert_type	What to base the alert on, overridden by *alert_condition* if it is specified. Valid values are: always, custom, number of events, number of hosts, number of sources.

Name	Description

allow_skew	Allows the search scheduler to distribute scheduled searches randomly and more evenly over their specified search periods.
	
	CAUTION: This setting does not require adjusting in most use cases. Check with an admin before making any updates.
	
	When set to a non-zero value for searches with the following `cron_schedule` values, the search scheduler randomly skews the second, minute, and hour on which the search runs.
	
	CODE
	
	`* * * * *  Every minute.`
	`*/M * * * *  Every M minutes (M > 0).`
	`0 * * * *  Every hour.`
	`0 */H * * *  Every H hours (H > 0).`
	`0 0 * * *  Every day (at midnight).`
	
	When set to a non-zero value for a search that has any other `cron_schedule` setting, the search scheduler can randomly skew only the second on which the search runs.
	
	The amount of skew for a specific search remains constant between edits of the search.
	
	A value of `0` disallows skew. `0` is the default setting.
	
	Percentage
	
	`<int>` followed by `%` specifies the maximum amount of time to skew as a percentage of the scheduled search period.
	
	Duration
	
	`<int><unit>` specifies a maximum duration. The `<unit>` can be omitted only when the `<int>` is `0`.
	
	Valid duration units:
	
	• `m`
	• `min`
	• `minute`
	• `mins`
	• `minutes`
	• `h`
	• `hr`
	• `hour`
	• `hrs`
	• `hours`
	• `d`
	• `day`
	• `days`
	
	Examples
	
	CODE
	
	`100% (for an every-5-minute search) = 5 minutes maximum`
	`50% (for an every-minute search) = 30 seconds maximum`
	`5m = 5 minutes maximum`
	`1h = 1 hour maximum`

auto_summarize	Specifies whether the search scheduler should ensure that the data for this search is automatically summarized.
auto_summarize.command	A search template to use to construct the auto-summarization for the search. Do not change.
auto_summarize.cron_schedule	Cron schedule to use to probe or generate the summaries for this search
auto_summarize.dispatch.<arg-name>	Dispatch options that can be overridden when running the summary search.
auto_summarize.max_concurrent	The maximum number of concurrent instances of this auto summarizing search that the scheduler is allowed to run.
auto_summarize.max_disabled_buckets	The maximum number of buckets with suspended summarization before the summarization search is completely stopped and the summarization of the search is suspended for the value specified by the *auto_summarize.suspend_period* setting.
auto_summarize.max_summary_ratio	The maximum ratio of summary_size/bucket_size, which specifies when to stop summarization and deem it unhelpful for a bucket.
auto_summarize.max_summary_size	The minimum summary size, in bytes, before testing whether the summarization is helpful.
auto_summarize.max_time	The maximum time, in seconds, that the auto-summarization search is allowed to run.
auto_summarize.suspend_period	The amount of time to suspend summarization of the search if the summarization is deemed unhelpful.
auto_summarize.timespan	Comma-delimited list of time ranges that each summarized chunk should span. Comprises the list of available summary ranges for which summaries would be available. Does not support `1w` timespans.

Name	Description
auto_summarize.workload_pool	Sets the name of the workload pool that is used by the auto-summarization of this search.
cron_schedule	The cron schedule to run this search. For more information, refer to the description of this parameter in the POST endpoint.
defer_scheduled_searchable_idxc	Specifies whether to defer a continuous saved search during a searchable rolling restart or searchable rolling upgrade of an indexer cluster.
description	Human-readable description of this saved search.
disabled	Indicates whether this saved search is disabled.
dispatch.allow_partial_results	Specifies whether the search job can proceed to provide partial results if a search peer fails. When set to false, the search job fails if a search peer providing results for the search job fails.
dispatch.auto_cancel	Specifies the amount of inactive time, in seconds, after which the search job is automatically canceled.
dispatch.auto_pause	Specifies the amount of inactive time, in seconds, after which the search job is automatically paused.
dispatch.buckets	The maximum number of timeline buckets.
dispatch.earliest_time	A time string that specifies the earliest time for this search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.
dispatch.index_earliest	Specifies the earliest index time for this search. Can be a relative or absolute time.
dispatch.index_latest	Specifies the latest index time for this saved search. Can be a relative or absolute time.
dispatch.indexedRealtime	Specifies whether to use 'indexed-realtime' mode when doing real-time searches.
dispatch.indexedRealtimeMinSpan	Specifies the minimum number of seconds to wait between component index searches.
dispatch.indexedRealtimeOffset	Specifies the number of seconds to wait for disk flushes to finish.
dispatch.indexedRealtimeMinSpan	Allows for a per-job override of the `[search] indexed_realtime_default_span` setting in `limits.conf`. The default for saved searches is "unset", falling back to the `limits.conf` setting.
dispatch.latest_time	A time string that specifies the latest time for the saved search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.
dispatch.lookups	Indicates if lookups are enabled for this search.
dispatch.max_count	The maximum number of results before finalizing the search.
dispatch.max_time	Indicates the maximum amount of time (in seconds) before finalizing the search.
dispatch.reduce_freq	Specifies how frequently the MapReduce reduce phase runs on accumulated map values.
dispatch.rt_backfill	Specifies whether to do real-time window backfilling for scheduled real-time searches.
dispatch.rt_maximum_span	Sets the maximum number of seconds to search data that falls behind real time.
dispatch.sample_ratio	The integer value used to calculate the sample ratio. The formula is `1 / <integer>`.
dispatch.spawn_process	This parameter is deprecated and will be removed in a future release. Do not use this parameter. Specifies whether new search process is spawned when this saved search is executed. Searches against indexes must run in a separate process.
dispatch.time_format	Time format string that defines the time format for specifying the earliest and latest time.
dispatch.ttl	Indicates the time to live (ttl), in seconds, for the artifacts of the scheduled search, if no actions are triggered.
dispatchAs	When the saved search is dispatched using the "saved/searches/{name}/dispatch" endpoint, this setting controls what user that search is dispatched as. Only meaningful for shared saved searches. Can be set to `owner` or `user`.
displayview	Defines the default UI view name (not label) in which to load the results. Accessibility is subject to the user having sufficient permissions.
durable.backfill_type	Specifies how the Splunk software backfills the lost search results of failed scheduled search jobs. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*. Valid values are `auto`, `time_interval`, and `time_whole`.

Name	Description
durable.lag_time	Specifies the search time delay, in seconds, that a durable search uses to catch events that are ingested or indexed late. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.max_backfill_intervals	Specifies the maximum number of cron intervals (previous scheduled search jobs) that the Splunk software can attempt to backfill for this search, when those jobs have incomplete events. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.track_time_type	Indicates that a scheduled search is durable and specifies how the search tracks events. A value of `_time` means the durable search tracks each event by its event timestamp , based on time information included in the event. A value of `_indextime` means the durable search tracks each event by its indexed timestamp. The search is not durable if this setting is unset or is set to `none`.
earliest_time	For scheduled searches display all the scheduled times starting from this time (not just the next run time).
is_scheduled	Indicates if this search is to be run on a schedule
is_visible	Indicates if this saved search appears in the visible saved search list.
latest_time	For scheduled searches display all the scheduled times until this time (not just the next run time).
listDefaultActionArgs	List default values of *actions.**, even though some of the actions may not be specified in the saved search.
max_concurrent	The maximum number of concurrent instances of this search the scheduler is allowed to run.
next_scheduled_time	Time when the scheduler runs this search again.
orphan	If `add_orphan_field` has been specified in the GET request, indicates whether the search is orphaned.
qualifiedSearch	The exact search string that the scheduler would run.
realtime_schedule	Controls the way the scheduler computes the next execution time of a scheduled search. If this value is set to 1, the scheduler bases its determination of the next scheduled search execution time on the current time. If this value is set to 0, the scheduler bases its determination of the next scheduled search on the last search execution time. This is called continuous scheduling. See the POST parameter for this attribute for details.
request.ui_dispatch_app	A field used by Splunk Web to denote the app this search should be dispatched in.
request.ui_dispatch_view	Specifies a field used by Splunk Web to denote the view this search should be displayed in.
restart_on_searchpeer_add	Specifies whether to restart a real-time search managed by the scheduler when a search peer becomes available for this saved search. *Note:* The peer can be a newly added peer or a peer down and now available.
run_n_times	Runs this search exactly the specified number of times. Does not run the search again until the Splunk platform is restarted.
run_on_startup	Indicates whether this search runs on startup. If it does not run on startup, it runs at the next scheduled time. Defaults to 0. This parameter should be set to 1 for scheduled searches that populate lookup tables.

Name	Description

schedule_priority	Indicates the scheduling priority of a specific search. One of the following values.
	CODE
	`[ default | higher | highest ]`
	default
	No scheduling priority increase.
	higher
	Scheduling priority is higher than other searches of the same scheduling tier. While there are four tiers of priority for scheduled searches, only the following are affected by this property:
	CODE
	`* real-Time-Scheduled (realtime_schedule=1).`
	`  * continuous-Scheduled (realtime_schedule=0).`
	highest
	Scheduling priority is higher than other searches regardless of scheduling tier. However, real-time-scheduled searches with `priority = highest` always have priority over continuous scheduled searches with `priority = highest`.
	This is the high-to-low priority order (where RTSS = real-time-scheduled search, CSS = continuous-scheduled search, d = default, h = higher, H = highest).
	CODE
	`RTSS(H) > CSS(H) > RTSS(h) > RTSS(d) > CSS(h) > CSS(d)`
	Changing the priority requires the search owner to have the `edit_search_schedule_priority` capability in order to make non-default settings.
	Defaults to `default`.
	For more details, see `savedsearches.conf.spec`.

schedule_window	Time window (in minutes) during which the search has lower priority. The scheduler can give higher priority to more critical searches during this window. The window must be smaller than the search period. If set to `auto`, the scheduler prioritizes searches automatically.
search	Search expression to filter the response. The response matches field values against the search expression. For example: search=foo matches any object that has "foo" as a substring in a field. search=field_name%3Dfield_value restricts the match to a single field. URI-encoding is required in this example.
vsid	The viewstate id associated with the UI view listed in 'displayview'. Must match up to a stanza in viewstates.conf.

Example requests and responses

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/saved/searches
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:s="http://dev.splunk.com/ns/rest"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>savedsearch</title>
  <id>https://fool01:8092/services/saved/searches</id>
  <updated>2021-04-29T09:22:44-07:00</updated>
  <generator build="84cbec3d51a6" version="8.2.2105"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/saved/searches/_new" rel="create"/>
  <link href="/services/saved/searches/_reload" rel="_reload"/>
  <link href="/services/saved/searches/_acl" rel="_acl"/>
  <opensearch:totalResults>8</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>Errors in the last 24 hours</title>
    <id>https://fool01:8092/servicesNS/nobody/search/saved/searches/Errors%20in%20the%20last%2024%20hours</id>
    <updated>1969-12-31T16:00:00-08:00</updated>
    <link href="/servicesNS/nobody/search/saved/searches/Errors%20in%20the%20last%2024%20hours" rel="alternate"/>
    <author>
      <name>nobody</name>
```

```
    </author>
    <link href="/servicesNS/nobody/search/saved/searches/Errors%20in%20the%20last%2024%20hours" rel="list"/>
    <link href="/servicesNS/nobody/search/saved/searches/Errors%20in%20the%20last%2024%20hours/_reload" rel="_reload"/>
    <link href="/servicesNS/nobody/search/saved/searches/Errors%20in%20the%20last%2024%20hours" rel="edit"/>
    <link href="/servicesNS/nobody/search/saved/searches/Errors%20in%20the%20last%2024%20hours/disable" rel="disable"/>
    <link href="/servicesNS/nobody/search/saved/searches/Errors%20in%20the%20last%2024%20hours/dispatch" rel="dispatch"/>
    <link href="/servicesNS/nobody/search/saved/searches/Errors%20in%20the%20last%2024%20hours/embed" rel="embed"/>
    <link href="/servicesNS/nobody/search/saved/searches/Errors%20in%20the%20last%2024%20hours/history" rel="history"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="action.email">0</s:key>
        <s:key name="action.email.sendresults"></s:key>
        <s:key name="action.email.to"></s:key>
        <s:key name="action.populate_lookup">0</s:key>
        <s:key name="action.rss">0</s:key>
        <s:key name="action.script">0</s:key>
        <s:key name="action.summary_index">0</s:key>
        <s:key name="action.summary_index.force_realtime_schedule">0</s:key>
        <s:key name="actions"></s:key>
        <s:key name="alert.digest_mode">1</s:key>
        <s:key name="alert.expires">24h</s:key>
        <s:key name="alert.managedBy"></s:key>
        <s:key name="alert.severity">3</s:key>
        <s:key name="alert.suppress"></s:key>
        <s:key name="alert.suppress.fields"></s:key>
        <s:key name="alert.suppress.group_name"></s:key>
        <s:key name="alert.suppress.period"></s:key>
        <s:key name="alert.track">0</s:key>
        <s:key name="alert_comparator"></s:key>
        <s:key name="alert_condition"></s:key>
        <s:key name="alert_threshold"></s:key>
        <s:key name="alert_type">always</s:key>
        <s:key name="allow_skew">0</s:key>
        <s:key name="auto_summarize">0</s:key>
        <s:key name="auto_summarize.command"><![CDATA[| summarize override=partial timespan=$auto_summarize.timespan$
max_summary_size=$auto_summarize.max_summary_size$ max_summary_ratio=$auto_summarize.max_summary_ratio$
max_disabled_buckets=$auto_summarize.max_disabled_buckets$ max_time=$auto_summarize.max_time$ [ $search$ ]]]></s:key>
        <s:key name="auto_summarize.cron_schedule">*/10 * * * *</s:key>
        <s:key name="auto_summarize.dispatch.earliest_time"></s:key>
        <s:key name="auto_summarize.dispatch.latest_time"></s:key>
        <s:key name="auto_summarize.dispatch.time_format">%FT%T.%Q%:z</s:key>
        <s:key name="auto_summarize.dispatch.ttl">60</s:key>
        <s:key name="auto_summarize.max_concurrent">1</s:key>
        <s:key name="auto_summarize.max_disabled_buckets">2</s:key>
        <s:key name="auto_summarize.max_summary_ratio">0.1</s:key>
        <s:key name="auto_summarize.max_summary_size">52428800</s:key>
        <s:key name="auto_summarize.max_time">3600</s:key>
        <s:key name="auto_summarize.suspend_period">24h</s:key>
        <s:key name="auto_summarize.timespan"></s:key>
        <s:key name="auto_summarize.workload_pool"></s:key>
        <s:key name="cron_schedule"></s:key>
        <s:key name="defer_scheduled_searchable_idxc">0</s:key>
        <s:key name="description"></s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="dispatch.allow_partial_results">1</s:key>
        <s:key name="dispatch.auto_cancel">0</s:key>
        <s:key name="dispatch.auto_pause">0</s:key>
        <s:key name="dispatch.buckets">0</s:key>
        <s:key name="dispatch.earliest_time">-1d</s:key>
        <s:key name="dispatch.index_earliest"></s:key>
        <s:key name="dispatch.index_latest"></s:key>
        <s:key name="dispatch.indexedRealtime"></s:key>
        <s:key name="dispatch.indexedRealtimeMinSpan"></s:key>
        <s:key name="dispatch.indexedRealtimeOffset"></s:key>
        <s:key name="dispatch.latest_time"></s:key>
        <s:key name="dispatch.lookups">1</s:key>
        <s:key name="dispatch.max_count">500000</s:key>
        <s:key name="dispatch.max_time">0</s:key>
        <s:key name="dispatch.reduce_freq">10</s:key>
        <s:key name="dispatch.rt_backfill">0</s:key>
        <s:key name="dispatch.rt_maximum_span"></s:key>
        <s:key name="dispatch.sample_ratio">1</s:key>
        <s:key name="dispatch.spawn_process">1</s:key>
        <s:key name="dispatch.time_format">%FT%T.%Q%:z</s:key>
        <s:key name="dispatch.ttl">2p</s:key>
        <s:key name="dispatchAs">owner</s:key>
        <!-- display settings elided-->
        <s:key name="displayview"></s:key>
        <s:key name="durable.backfill_type">auto</s:key>
        <s:key name="durable.lag_time">0</s:key>
        <s:key name="durable.max_backfill_intervals">0</s:key>
        <s:key name="durable.track_time_type"></s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">search</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">0</s:key>
            <s:key name="can_write">1</s:key>
```

```
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">nobody</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list>
                    <s:item>admin</s:item>
                  </s:list>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">app</s:key>
          </s:dict>
        </s:key>
        <s:key name="embed.enabled">0</s:key>
        <s:key name="federated.provider"></s:key>
        <s:key name="is_scheduled">0</s:key>
        <s:key name="is_visible">1</s:key>
        <s:key name="max_concurrent">1</s:key>
        <s:key name="next_scheduled_time"></s:key>
        <s:key name="qualifiedSearch">search error OR failed OR severe OR ( sourcetype=access_* ( 404 OR 500 OR 503 ) )</s:key>
        <s:key name="realtime_schedule">1</s:key>
        <s:key name="request.ui_dispatch_app"></s:key>
        <s:key name="request.ui_dispatch_view"></s:key>
        <s:key name="restart_on_searchpeer_add">1</s:key>
        <s:key name="run_n_times">0</s:key>
        <s:key name="run_on_startup">0</s:key>
        <s:key name="schedule_as">auto</s:key>
        <s:key name="schedule_priority">default</s:key>
        <s:key name="schedule_window">0</s:key>
        <s:key name="search">error OR failed OR severe OR ( sourcetype=access_* ( 404 OR 500 OR 503 ) )</s:key>
        <s:key name="skip_scheduled_realtime_idxc">0</s:key>
        <s:key name="vsid"></s:key>
        <s:key name="workload_pool"></s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```


POST

Create a saved search.

Request parameters

Name	Type	Description
action.<action_name>	Boolean	Enable or disable an alert action. See `alert_actions.conf` for available alert action types. `action_name` defaults to an empty string.
action.<action_name>.<parameter>		Use this syntax to configure action parameters. See `alert_actions.conf` for parameter options.
action.summary_index._type"	String	Specifies the data type of the summary index where the Splunk software saves the results of the scheduled search. Can be set to `event` or `metric`.
action.summary_index.force_realtime_schedule	Boolean	By default, *realtime_schedule* is `false` for a report configured for summary indexing. When set to `1` or `True`, this setting overrides *realtime_schedule*. Setting this setting to `true` can cause gaps in summary data, as a *realtime_schedule* search is skipped if search concurrency limits are violated.
actions	String	A comma-separated list of actions to enable. For example: rss,email
alert.digest_mode	Boolean	Specifies whether alert actions are applied to the entire result set or on each individual result. Defaults to 1.
alert.expires	Number	Valid values: [number][time-unit] Sets the period of time to show the alert in the dashboard. Defaults to 24h. Use [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.

Name	Type	Description
alert.severity	Enum	Valid values: (1 | 2 | 3 | 4 | 5 | 6) Sets the alert severity level. Valid values are: 1 DEBUG 2 INFO 3 WARN (default) 4 ERROR 5 SEVERE 6 FATAL
alert.suppress	Boolean	Indicates whether alert suppression is enabled for this scheduled search.
alert.suppress.fields	String	Comma delimited list of fields to use for suppression when doing per result alerting. Required if suppression is turned on and per result alerting is enabled.
alert.suppress.group_name	String	Optional setting. Used to define an alert suppression group for a set of alerts that are running over identical or very similar datasets. Alert suppression groups can help you avoid getting multiple triggered alert notifications for the same data.
alert.suppress.period	Number	Valid values: [number][time-unit] Specifies the suppression period. Only valid if *alert.suppress* is enabled. Use [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
alert.track	String	Valid values: (true | false | auto) Specifies whether to track the actions triggered by this scheduled search. `auto` - Determine whether to apply alert tracking to this search, based on the tracking setting of each action. Do not track scheduled searches that always trigger actions. Default. `true` - Force alert tracking for this search. `false` - Disable alert tracking for this search.
alert_comparator	String	One of the following strings: greater than, less than, equal to, rises by, drops by, rises by perc, drops by perc. Used with *alert_threshold* to trigger alert actions.
alert_condition	String	Contains a conditional search that is evaluated against the results of the saved search. Defaults to an empty string. Alerts are triggered if the specified search yields a non-empty search result list. Note: If you specify an alert_condition, do not set counttype, relation, or quantity.
alert_threshold	Number	Valid values are: Integer[%] Specifies the value to compare (see *alert_comparator*) before triggering the alert actions. If expressed as a percentage, indicates value to use when *alert_comparator* is set to "rises by perc" or "drops by perc."
alert_type	String	What to base the alert on, overridden by *alert_condition* if it is specified. Valid values are: always, custom, number of events, number of hosts, number of sources.

Name	Type	Description

allow_skew	`0 | <percentage> | <duration>`	Allows the search scheduler to distribute scheduled searches randomly and more evenly over their specified search periods. Defaults to `0` (skew disabled).
		
		CAUTION: This setting does not require adjusting in most use cases. Check with an admin before making any updates.
		
		When set to a non-zero value for searches with the following *cron_schedule' values, the search scheduler randomly skews the second, minute, and hour on which the search runs.*
		
		CODE
		
		`* * * * *  Every minute.`
		`*/M * * * *  Every M minutes (M > 0).`
		`0 * * * *  Every hour.`
		`0 */H * * *  Every H hours (H > 0).`
		`0 0 * * *  Every day (at midnight).`
		
		When set to a non-zero value for a search that has any other `cron_schedule` setting, the search scheduler can randomly skew only the second on which the search runs.
		
		The amount of skew for a specific search remains constant between edits of the search.
		
		A value of `0` disallows skew. `0` is the default setting.
		
		Percentage
		
		`<int>` followed by `%` specifies the maximum amount of time to skew as a percentage of the scheduled search period.
		
		Duration
		
		`<int><unit>` specifies a maximum duration. The `<unit>` can be omitted only when the `<int>` is `0`.
		
		Valid duration units:
		
		• `m`
		• `min`
		• `minute`
		• `mins`
		• `minutes`
		• `h`
		• `hr`
		• `hour`
		• `hrs`
		• `hours`
		• `d`
		• `day`
		• `days`
		
		Examples
		
		CODE
		
		`100% (for an every-5-minute search) = 5 minutes maximum`
		`50% (for an every-minute search) = 30 seconds maximum`
		`5m = 5 minutes maximum`
		`1h = 1 hour maximum`

*args.**	String	Wildcard argument that accepts any saved search template argument, such as args.username=foobar when the search is search $username$.
auto_summarize	Boolean	Indicates whether the scheduler should ensure that the data for this search is automatically summarized. Defaults to 0.
auto_summarize.command	String	An auto summarization template for this search. See auto summarization options in `savedsearches.conf` for more details. Do not change unless you understand the architecture of saved search auto summarization.
auto_summarize.cron_schedule	String	Cron schedule that probes and generates the summaries for this saved search. The default value, `*/10 * * * *` , corresponds to "every ten hours".

Name	Type	Description
auto_summarize.dispatch.earliest_time	String	A time string that specifies the earliest time for summarizing this search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.
auto_summarize.dispatch.latest_time	String	A time string that specifies the latest time for summarizing this saved search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
auto_summarize.dispatch.time_format	String	Defines the time format used to specify the earliest and latest time. Defaults to `%FT%T.%Q%:z`
auto_summarize.dispatch.ttl	String	Valid values: Integer[p] Indicates the time to live (ttl), in seconds, for the artifacts of the summarization of the scheduled search. Defaults to 60.
auto_summarize.max_concurrent	Number	The maximum number of concurrent instances of this auto summarizing search that the scheduler is allowed to run.
auto_summarize.max_disabled_buckets	Number	The maximum number of buckets with the suspended summarization before the summarization search is completely stopped, and the summarization of the search is suspended for auto_summarize.suspend_period. Defaults to 2.
auto_summarize.max_summary_ratio	Number	The maximum ratio of summary_size/bucket_size, which specifies when to stop summarization and deem it unhelpful for a bucket. Defaults to 0.1. *Note:* The test is only performed if the summary size is larger than auto_summarize.max_summary_size.
auto_summarize.max_summary_size	Number	The minimum summary size, in bytes, before testing whether the summarization is helpful. The default value, `52428800`, is equivalent to 5MB.
auto_summarize.max_time	Number	The maximum time, in seconds, that the summary search is allowed to run. Defaults to 3600. *Note:* This is an approximate time. The summary search stops at clean bucket boundaries.
auto_summarize.suspend_period	String	The amount of time to suspend summarization of this search if the summarization is deemed unhelpful. Defaults to 24h.
auto_summarize.timespan	String	Comma-delimited list of time ranges that each summarized chunk should span. Comprises the list of available granularity levels for which summaries would be available. Does not support `1w` timespans. For example, a timechart over the last month whose granularity is at the day level should set this to `1d`. If you need the same data summarized at the hour level for weekly charts, use: `1h,1d`.
cron_schedule	String	Valid values: cron string The cron schedule to execute this search. For example: `*/5 * * * *` causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: `00,20,40 * * * *`, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of `03,23,43 * * * *` runs the search every hour at hh:03, hh:23, hh:43. To reduce system load, schedule your searches so that they are staggered over time. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes.
description	String	Human-readable description of this saved search. Defaults to empty string.
disabled	Boolean	Indicates whether the saved search is enabled. Defaults to 0. Disabled saved searches are not visible in Splunk Web.
*dispatch.**	String	Wildcard argument that accepts any dispatch related argument.

Name	Type	Description
dispatch.allow_partial_results	Boolean	Specifies whether the search job can proceed to provide partial results if a search peer fails. When set to false, the search job fails if a search peer providing results for the search job fails.
dispatch.auto_cancel	Number	Specifies the amount of inactive time, in seconds, after which the search job is automatically canceled.
dispatch.auto_pause	Number	Specifies the amount of inactive time, in seconds, after which the search job is automatically paused.
dispatch.buckets	Number	The maximum number of timeline buckets. Defaults to 0.
dispatch.earliest_time	String	A time string that specifies the earliest time for this search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.
dispatch.index_earliest	String	A time string that specifies the earliest index time for this search. Can be a relative or absolute time.
dispatch.index_latest	String	A time string that specifies the latest index time for this saved search. Can be a relative or absolute time.
dispatch.indexedRealtime	Boolean	Indicates whether to used indexed-realtime mode when doing real-time searches.
dispatch.indexedRealtimeOffset	Number	Allows for a per-job override of the `[search] indexed_realtime_disk_sync_delay` setting in `limits.conf`. Default for saved searches is "unset", falling back to `limits.conf` setting.
dispatch.indexedRealtimeMinSpan	Number	Allows for a per-job override of the `[search] indexed_realtime_default_span` setting in `limits.conf`. Default for saved searches is "unset", falling back to the `limits.conf` setting.
dispatch.latest_time	String	A time string that specifies the latest time for this saved search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.
dispatch.lookups	Boolean	Enables or disables the lookups for this search. Defaults to 1.
dispatch.max_count	Number	The maximum number of results before finalizing the search. Defaults to 500000.
dispatch.max_time	Number	Indicates the maximum amount of time (in seconds) before finalizing the search. Defaults to 0.
dispatch.reduce_freq	Number	Specifies, in seconds, how frequently the MapReduce reduce phase runs on accumulated map values. Defaults to 10.
dispatch.rt_backfill	Boolean	Whether to back fill the real time window for this search. Parameter valid only if this is a real time search. Defaults to 0.
dispatch.rt_maximum_span	Number	Allows for a per-job override of the `[search] indexed_realtime_maximum_span` setting in `limits.conf`. Default for saved searches is "unset", falling back to the `limits.conf` setting.
dispatch.sample_ratio	Number	The integer value used to calculate the sample ratio. The formula is `1 / <integer>`.
dispatch.spawn_process	Boolean	This parameter is deprecated and will be removed in a future release. Do not use this parameter. Specifies whether to spawn a new search process when this saved search is executed. Defaults to 1. Searches against indexes *must* run in a separate process.
dispatch.time_format	String	A time format string that defines the time format for specifying the earliest and latest time. Defaults to `%FT%T.%Q%:z`.

Name	Type	Description
dispatch.ttl	Number	Valid values: Integer[p]. Defaults to 2p. Indicates the time to live (in seconds) for the artifacts of the scheduled search, if no actions are triggered. If an action is triggered, the action ttl is used. If multiple actions are triggered, the maximum ttl is applied to the artifacts. To set the action ttl, refer to `alert_actions.conf.spec`. If the integer is followed by the letter 'p', the ttl is interpreted as a multiple of the scheduled search period.
dispatchAs	String	When the saved search is dispatched using the "saved/searches/{name}/dispatch" endpoint, this setting controls what user that search is dispatched as. Only meaningful for shared saved searches. Can be set to `owner` or `user`.
displayview	String	Defines the default UI view name (not label) in which to load the results. Accessibility is subject to the user having sufficient permissions.
durable.backfill_type	String	Specifies how the Splunk software backfills the lost search results of failed scheduled search jobs. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*. Valid values are `auto`, `time_interval`, and `time_whole`. `time_whole` - The Splunk software schedules a single backfill search job with a time range that spans the combined time ranges of all failed scheduled search jobs. The `time_whole` setting can be applied only to searches that are streaming, where the results are raw events without additional aggregation. `time_interval` - The Splunk software schedules multiple backfill search jobs, one for each failed scheduled search job. The backfill jobs have time ranges that match those of the failed jobs. The `time_interval` setting can be applied to both streaming and non-streaming searches. `auto` - The Splunk software decides the backfill type by checking whether the search is streaming or not. If the search is streaming, the Splunk software uses the `time_whole` backfill type. Otherwise, it uses the `time_interval` backfill type.
durable.lag_time	Number	Specifies the search time delay, in seconds, that a durable search uses to catch events that are ingested or indexed late. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.max_backfill_intervals	Number	Specifies the maximum number of cron intervals (previous scheduled search jobs) that the Splunk software can attempt to backfill for this search, when those jobs have incomplete events. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.track_time_type	String	Indicates that a scheduled search is durable and specifies how the search tracks events. A durable search is a search that tries to ensure the delivery of all results, even when the search process is slowed or stopped by runtime issues like rolling restarts, network bottlenecks, and even downed servers. Applies only to scheduled searches. A value of `_time` means the durable search tracks each event by its event timestamp , based on time information included in the event. A value of `_indextime` means the durable search tracks each event by its indexed timestamp. The search is not durable if this setting is unset or is set to `none`.
is_scheduled	Boolean	Whether this search is to be run on a schedule
is_visible	Boolean	Specifies whether this saved search should be listed in the visible saved search list. Defaults to 1.
max_concurrent	Number	The maximum number of concurrent instances of this search the scheduler is allowed to run. Defaults to 1.
name	String	Required. A name for the search.
next_scheduled_time	String	Read-only attribute. Value ignored on POST. There are some old clients who still send this value
qualifiedSearch	String	Read-only attribute. Value ignored on POST. This value is computed during runtime.

Name	Type	Description
realtime_schedule	Boolean	Controls the way the scheduler computes the next execution time of a scheduled search. Defaults to 1. If this value is set to 1, the scheduler bases its determination of the next scheduled search execution time on the current time. If this value is set to 0, the scheduler bases its determination of the next scheduled search on the last search execution time. This is called continuous scheduling. If set to 0, the scheduler never skips scheduled execution periods. However, the execution of the saved search might fall behind depending on the scheduler load. Use continuous scheduling whenever you enable the summary index option. If set to 1, the scheduler might skip some execution periods to make sure that the scheduler is executing the searches running over the most recent time range. The scheduler tries to execute searches that have realtime_schedule set to 1 before it executes searches that have continuous scheduling (realtime_schedule = 0).
request.ui_dispatch_app	String	Specifies a field used by Splunk Web to denote the app this search should be dispatched in.
request.ui_dispatch_view	String	Specifies a field used by Splunk Web to denote the view this search should be displayed in.
restart_on_searchpeer_add	Boolean	Specifies whether to restart a real-time search managed by the scheduler when a search peer becomes available for this saved search. Defaults to 1. Note: The peer can be a newly added peer or a peer down and now available.
run_n_times	Number	Runs this search exactly the specified number of times. Does not run the search again until the Splunk platform is restarted.
run_on_startup	Boolean	Indicates whether this search runs on startup. If it does not run on startup, it runs at the next scheduled time. Defaults to 0. Set *run_on_startup* to `1` for scheduled searches that populate lookup tables.

schedule_priority	String	Configures the scheduling priority of a specific search. One of the following values.
		CODE
		`[ default | higher | highest ]`
		
		default
		
		No scheduling priority increase.
		
		higher
		
		Scheduling priority is higher than other searches of the same scheduling tier. While there are four tiers of priority for scheduled searches, only the following are affected by this property:
		
		CODE
		`* real-Time-Scheduled (realtime_schedule=1).`
		`* continuous-Scheduled (realtime_schedule=0).`
		
		highest
		
		Scheduling priority is higher than other searches regardless of scheduling tier. However, real-time-scheduled searches with `priority = highest` always have priority over continuous scheduled searches with `priority = highest`.
		
		This is the high-to-low priority order (where RTSS = real-time-scheduled search, CSS = continuous-scheduled search, d = default, h = higher, H = highest).
		
		CODE
		`RTSS(H) > CSS(H) > RTSS(h) > RTSS(d) > CSS(h) > CSS(d)`
		
		Changing the priority requires the search owner to have the `edit_search_schedule_priority` capability in order to make non-default settings.
		
		Defaults to `default`.
		
		For more details, see `savedsearches.conf.spec`.

Name	Type	Description
schedule_window	Number or `auto`	Time window (in minutes) during which the search has lower priority. Defaults to 0. The scheduler can give higher priority to more critical searches during this window. The window must be smaller than the search period. Set to `auto` to let the scheduler determine the optimal window value automatically. Requires the `edit_search_schedule_window` capability to override `auto`.
search	String	Required. The search to save.
vsid	String	Defines the viewstate id associated with the UI view listed in 'displayview'. Must match up to a stanza in viewstates.conf.
workload_pool	String	Specifies the new workload pool where the existing running search will be placed.

Returned values

Name	Description
action.<action_name>	Indicates whether the `<action_name>` is enabled or disabled for a particular search. For more information about the alert action options see the `alert_actions.conf` file.
action.<action_name>.<parameter>	Overrides the setting defined for an action in the `alert_actions.conf` file with a new setting that is valid only for the search configuration to which it is applied.
action.email	Indicates the state of the email action.
action.email.auth_password	The password to use when authenticating with the SMTP server. Normally this value is set when editing the email settings, however you can set a clear text password here and it is encrypted on the next restart. Defaults to empty string.
action.email.auth_username	The username to use when authenticating with the SMTP server. If this is empty string, no authentication is attempted. Defaults to empty string. *Note:* Your SMTP server might reject unauthenticated emails.
action.email.bcc	BCC email address to use if action.email is enabled.
action.email.cc	CC email address to use if action.email is enabled.
action.email.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.email.format	Specify the format of text in the email. This value also applies to any attachments.< Valid values: (plain | html | raw | csv)
action.email.from	Email address from which the email action originates. Defaults to splunk@$LOCALHOST or whatever value is set in alert_actions.conf.
action.email.hostname	Sets the hostname used in the web link (url) sent in email actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) When this value is a simple hostname, the protocol and port which are configured within splunk are used to construct the base of the url. When this value begins with 'http://', it is used verbatim. NOTE: This means the correct port must be specified if it is not the default port for http or https. This is useful in cases when the Splunk server is not aware of how to construct a url that can be referenced externally, such as SSO environments, other proxies, or when the server hostname is not generally resolvable. Defaults to current hostname provided by the operating system, or if that fails "localhost". When set to empty, default behavior is used.
action.email.inline	Indicates whether the search results are contained in the body of the email. Results can be either inline or attached to an email. See action.email.sendresults.
action.email.mailserver	Set the address of the MTA server to be used to send the emails. Defaults to <LOCALHOST> (or whatever is set in alert_actions.conf).

Name	Description
action.email.maxresults	Sets the global maximum number of search results to send when email.action is enabled.
action.email.maxtime	Specifies the maximum amount of time the execution of an email action takes before the action is aborted.
action.email.pdfview	The name of the view to deliver if sendpdf is enabled
action.email.preprocess_results	Search string to preprocess results before emailing them. Defaults to empty string (no preprocessing). Usually the preprocessing consists of filtering out unwanted internal fields.
action.email.reportCIDFontList	Space-separated list. Specifies the set (and load order) of CID fonts for handling Simplified Chinese(gb), Traditional Chinese(cns), Japanese(jp), and Korean(kor) in Integrated PDF Rendering. If multiple fonts provide a glyph for a given character code, the glyph from the first font specified in the list is used. To skip loading any CID fonts, specify the empty string. Default value: "gb cns jp kor"
action.email.reportIncludeSplunkLogo	Indicates whether to include the Splunk logo with the report.
action.email.reportPaperOrientation	Specifies the paper orientation: portrait or landscape.
action.email.reportPaperSize	Specifies the paper size for PDFs. Defaults to letter. Valid values: (letter | legal | ledger | a2 | a3 | a4 | a5)
action.email.reportServerEnabled	Not supported.
action.email.reportServerURL	Not supported.
action.email.sendpdf	Indicates whether to create and send the results as a PDF.
action.email.sendresults	Indicates whether to attach the search results in the email. Results can be either attached or inline. See action.email.inline.
action.email.subject	Specifies an email subject. Defaults to SplunkAlert-<savedsearchname>.
action.email.to	List of recipient email addresses. Required if this search is scheduled and the email alert action is enabled.
action.email.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.email.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows <Integer>, int is the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p].
action.email.use_ssl	Indicates whether to use SSL when communicating with the SMTP server.
action.email.use_tls	Indicates whether to use TLS (transport layer security) when communicating with the SMTP server (starttls).
action.email.width_sort_columns	Indicates whether columns should be sorted from least wide to most wide, left to right. Only valid if format=text.
action.populate_lookup	Indicates the state of the populate lookup action.
action.populate_lookup.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.populate_lookup.dest	Lookup name of path of the lookup to populate.
action.populate_lookup.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.populate_lookup.maxresults	The maximum number of search results sent using alerts.

Name	Description
action.populate_lookup.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 5m. Valid values are: Integer[m|s|h|d]
action.populate_lookup.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.populate_lookup.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, then this specifies the number of scheduled periods. Defaults to 10p. If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p]
action.rss	Indicates the state of the RSS action.
action.rss.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.rss.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.rss.maxresults	Sets the maximum number of search results sent using alerts.
action.rss.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Valid values are Integer[m |s |h |d].
action.rss.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.rss.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
action.script	Indicates the state of the script for this action.
action.script.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.script.filename	File name of the script to call. Required if script action is enabled
action.script.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.script.maxresults	Sets the maximum number of search results sent using alerts.
action.script.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted.
action.script.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.script.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 600 (10 minutes). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
action.summary_index	Indicates the state of the summary index.

Name	Description
action.summary_index._name	Specifies the name of the summary index where the results of the scheduled search are saved. Defaults to "summary."
action.summary_index.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.summary_index.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.summary_index.inline	Determines whether to execute the summary indexing action as part of the scheduled search. *Note:* This option is considered only if the summary index action is enabled and is always executed (in other words, if counttype = always).
action.summary_index.maxresults	Sets the maximum number of search results sent using alerts.
action.summary_index.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 5m. Valid values are: Integer[m|s|h|d]
action.summary_index.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.summary_index.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 10p. If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
actions	Actions triggerd by this alert.
alert.digest_mode	Indicates if the alert actions are applied to the entire result set or to each individual result.
alert.expires	Sets the period of time to show the alert in the dashboard. Defaults to 24h. Use [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour. Valid values: [number][time-unit]
alert.severity	Valid values: (1 | 2 | 3 | 4 | 5 | 6) Sets the alert severity level. Valid values are: 1 DEBUG 2 INFO 3 WARN 4 ERROR 5 SEVERE 6 FATAL
alert.suppress	Indicates whether alert suppression is enabled for this schedules search.
alert.suppress.fields	Fields to use for suppression when doing per result alerting. Required if suppression is turned on and per result alerting is enabled.
alert.suppress.period	Specifies the suppresion period. Only valid if alert.supress is enabled. Uses [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
alert.track	Specifies whether to track the actions triggered by this scheduled search. auto - determine whether to track or not based on the tracking setting of each action, do not track scheduled searches that always trigger actions. true - force alert tracking. false - disable alert tracking for this search.

Name	Description
alert_comparator	One of the following strings: greater than, less than, equal to, rises by, drops by, rises by perc, drops by perc
alert_condition	A conditional search that is evaluated against the results of the saved search. Defaults to an empty string. Alerts are triggered if the specified search yields a non-empty search result list. *Note:* If you specify an alert_condition, do not set counttype, relation, or quantity.
alert_threshold	Valid values are: Integer[%] Specifies the value to compare (see alert_comparator) before triggering the alert actions. If expressed as a percentage, indicates value to use when alert_comparator is set to "rises by perc" or "drops by perc."
alert_type	What to base the alert on, overriden by alert_condition if it is specified. Valid values are: always, custom, number of events, number of hosts, number of sources.

allow_skew	`0 | <percentage> | <duration>`
	
	Allows the search scheduler to distribute scheduled searches randomly and more evenly over their specified search periods.
	
	CAUTION: This setting does not require adjusting in most use cases. Check with an admin before making any updates.
	
	When set to a non-zero value for searches with the following `cron_schedule` values, the search scheduler randomly skews the second, minute, and hour on which the search runs.
	
	CODE
	
	`* * * * *  Every minute.`
	`*/M * * * *  Every M minutes (M > 0).`
	`0 * * * *  Every hour.`
	`0 */H * * *  Every H hours (H > 0).`
	`0 0 * * *  Every day (at midnight).`
	
	When set to a non-zero value for a search that has any other `cron_schedule` setting, the search scheduler can randomly skew only the second on which the search runs.
	
	The amount of skew for a specific search remains constant between edits of the search.
	
	A value of `0` disallows skew. `0` is the default setting.
	
	Percentage
	
	`<int>` followed by `%` specifies the maximum amount of time to skew as a percentage of the scheduled search period.
	
	Duration
	
	`<int><unit>` specifies a maximum duration. The `<unit>` can be omitted only when the `<int>` is `0` (which disables skew).
	
	Valid duration units:
	
	• `m`
	• `min`
	• `minute`
	• `mins`
	• `minutes`
	• `h`
	• `hr`
	• `hour`
	• `hrs`
	• `hours`
	• `d`
	• `day`
	• `days`
	
	Examples
	
	CODE
	
	`100% (for an every-5-minute search) = 5 minutes maximum`
	`50% (for an every-minute search) = 30 seconds maximum`
	`5m = 5 minutes maximum`
	`1h = 1 hour maximum`

*args.**	Wildcard argument that accepts any saved search template argument, such as args.username=foobar when the search is search $username$.
auto_summarize	Indicates whether the scheduler should ensure that the data for this search is automatically summarized.
auto_summarize.command	A search template that constructs the auto summarization for this search. Caution: Advanced feature. Do not change unless you understand the architecture of auto summarization of saved searches.
auto_summarize.cron_schedule	Cron schedule that probes and generates the summaries for this saved search.

Name	Description
auto_summarize.dispatch.earliest_time	A time string that specifies the earliest time for summarizing this search. Can be a relative or absolute time.
auto_summarize.dispatch.latest_time	A time string that specifies the latest time for this saved search. Can be a relative or absolute time.
auto_summarize.dispatch.time_format	Time format used to specify the earliest and latest times.
auto_summarize.dispatch.ttl	Indicates the time to live (in seconds) for the artifacts of the summarization of the scheduled search. If the integer is followed by the letter 'p', the ttl is interpreted as a multiple of the scheduled search period.
auto_summarize.max_disabled_buckets	The maximum number of buckets with the suspended summarization before the summarization search is completely stopped, and the summarization of the search is suspended for auto_summarize.suspend_period.
auto_summarize.max_summary_ratio	The maximum ratio of summary_size/bucket_size, which specifies when to stop summarization and deem it unhelpful for a bucket. *Note:* The test is only performed if the summary size is larger than auto_summarize.max_summary_size.
auto_summarize.max_summary_size	The minimum summary size, in bytes, before testing whether the summarization is helpful.
auto_summarize.max_time	Maximum time (in seconds) that the summary search is allowed to run. *Note:* This is an approximate time. The summary search stops at clean bucket boundaries.
auto_summarize.suspend_period	Time specifier indicating when to suspend summarization of this search if the summarization is deemed unhelpful.
auto_summarize.timespan	The list of time ranges that each summarized chunk should span. This comprises the list of available granularity levels for which summaries would be available. For example a timechart over the last month whose granularity is at the day level should set this to 1d. If you need the same data summarized at the hour level for weekly charts, use: 1h,1d.
cron_schedule	The cron schedule to execute this search. For example: */5 * * * * causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: 00,20,40 * * * *, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of 03,23,43 * * * * runs the search every hour at hh:03, hh:23, hh:43. Splunk recommends that you schedule your searches so that they are staggered over time. This reduces system load. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes. Valid values: cron string
description	Description of this saved search. Defaults to empty string.
disabled	Indicates if this saved search is disabled.
*dispatch.**	* represents any custom dispatch field.
dispatch.buckets	The maximum nuber of timeline buckets.
dispatch.earliest_time	A time string that specifies the earliest time for this search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
dispatch.indexedRealtime	Indicates whether to used indexed-realtime mode when doing real-time searches.
dispatch.latest_time	A time string that specifies the latest time for the saved search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
dispatch.lookups	Indicates if lookups are enabled for this search.
dispatch.max_count	The maximum number of results before finalizing the search.
dispatch.max_time	Indicates the maximum amount of time (in seconds) before finalizing the search.
dispatch.reduce_freq	Specifies how frequently the MapReduce reduce phase runs on accumulated map values.
dispatch.rt_backfill	Indicates whether to back fill the real time window for this search. Parameter valid only if this is a real time search
dispatch.spawn_process	This parameter is deprecated and will be removed in a future release. Do not use this parameter. Indicates whether a new search process spawns when this saved search is executed.

Name	Description
dispatch.time_format	Time format string that defines the time format for specifying the earliest and latest time.
dispatch.ttl	Indicates the time to live (in seconds) for the artifacts of the scheduled search, if no actions are triggered. If an action is triggered, the action ttl is used. If multiple actions are triggered, the maximum ttl is applied to the artifacts. To set the action ttl, refer to `alert_actions.conf.spec`. If the integer is followed by the letter 'p', the ttl is interpreted as a multiple of the scheduled search period.
displayview	Defines the default UI view name (not label) in which to load the results. Accessibility is subject to the user having sufficient permissions.
durable.backfill_type	Specifies how the Splunk software backfills the lost search results of failed scheduled search jobs. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*. Valid values are `auto`, `time_interval`, and `time_whole`.
durable.lag_time	Specifies the search time delay, in seconds, that a durable search uses to catch events that are ingested or indexed late. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.max_backfill_intervals	Specifies the maximum number of cron intervals (previous scheduled search jobs) that the Splunk software can attempt to backfill for this search, when those jobs have incomplete events. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.track_time_type	Indicates that a scheduled search is durable and specifies how the search tracks events. A value of `_time` means the durable search tracks each event by its event timestamp , based on time information included in the event. A value of `_indextime` means the durable search tracks each event by its indexed timestamp. The search is not durable if this setting is unset or is set to `none`.
is_scheduled	Indicates if this search is to be run on a schedule.
is_visible	Indicates if this saved search appears in the visible saved search list.
max_concurrent	The maximum number of concurrent instances of this search the scheduler is allowed to run.
next_scheduled_time	The time when the scheduler runs this search again.
qualifiedSearch	The exact search string that the scheduler would run.
realtime_schedule	Controls the way the scheduler computes the next execution time of a scheduled search. If this value is set to 1, the scheduler bases its determination of the next scheduled search execution time on the current time. If this value is set to 0, the scheduler bases its determination of the next scheduled search on the last search execution time. This is called continuous scheduling. If set to 0, the scheduler never skips scheduled execution periods. However, the execution of the saved search might fall behind depending on the scheduler load. Use continuous scheduling whenever you enable the summary index option. If set to 1, the scheduler might skip some execution periods to make sure that the scheduler is executing the searches running over the most recent time range. The scheduler tries to execute searches that have realtime_schedule set to 1 before it executes searches that have continuous scheduling (realtime_schedule = 0).
request.ui_dispatch_app	A field used by Splunk Web to denote the app this search should be dispatched in.
request.ui_dispatch_view	Specifies a field used by Splunk Web to denote the view this search should be displayed in.
restart_on_searchpeer_add	Indicates whether to restart a real-time search managed by the scheduler when a search peer becomes available for this saved search. *Note:* The peer can be a newly added peer or a peer down and now available.
run_on_startup	Indicates whether this search runs on startup. If it does not run on startup, it runs at the next scheduled time. Splunk recommends that you set run_on_startup to true for scheduled searches that populate lookup tables.
schedule_window	Time window (in minutes) during which the search has lower priority. The scheduler can give higher priority to more critical searches during this window. The window must be smaller than the search period. If set to `auto`, the scheduler prioritizes searches automatically.
search	Search expression to filter the response. The response matches field values against the search expression. For example: search=foo matches any object that has "foo" as a substring in a field. search=field_name%3Dfield_value restricts the match to a single field. URI-encoding is required in this example.

Name	Description
vsid	The viewstate id associated with the UI view listed in 'displayview'. Matches to a stanza in viewstates.conf.

Example request and response

XML Request

CODE

```
curl -k -u admin:chang2me https://fool01:8092/services/saved/searches/ \
 -d name=test_durable \
 -d cron_schedule="*/3 * * * *" \
 -d description="This test job is a durable saved search" \
 -d dispatch.earliest_time="-24h@h" -d dispatch.latest_time=now \
 --data-urlencode search="search index="_internal" | stats count by host" \
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:s="http://dev.splunk.com/ns/rest"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>savedsearch</title>
  <id>https://fool01:8092/services/saved/searches</id>
  <updated>2021-04-29T09:56:53-07:00</updated>
  <generator build="84cbec3d51a6" version="8.2.2105"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/saved/searches/_new" rel="create"/>
  <link href="/services/saved/searches/_reload" rel="_reload"/>
  <link href="/services/saved/searches/_acl" rel="_acl"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>test_durable</title>
    <id>https://fool01:8092/servicesNS/admin/search/saved/searches/test_durable</id>
    <updated>2021-04-29T09:56:53-07:00</updated>
    <link href="/servicesNS/admin/search/saved/searches/test_durable" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/saved/searches/test_durable" rel="list"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable" rel="edit"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable" rel="remove"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/move" rel="move"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/disable" rel="disable"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/dispatch" rel="dispatch"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/embed" rel="embed"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/history" rel="history"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="action.email">0</s:key>
        <!-- action settings elided -->
        <s:key name="alert.digest_mode">1</s:key>
        <s:key name="alert.expires">24h</s:key>
        <s:key name="alert.managedBy"></s:key>
        <s:key name="alert.severity">3</s:key>
        <s:key name="alert.suppress"></s:key>
        <s:key name="alert.suppress.fields"></s:key>
        <s:key name="alert.suppress.group_name"></s:key>
        <s:key name="alert.suppress.period"></s:key>
        <s:key name="alert.track">0</s:key>
        <s:key name="alert_comparator"></s:key>
        <s:key name="alert_condition"></s:key>
        <s:key name="alert_threshold"></s:key>
        <s:key name="alert_type">always</s:key>
        <s:key name="allow_skew">0</s:key>
        <s:key name="auto_summarize">0</s:key>
        <s:key name="auto_summarize.command"><![CDATA[| summarize override=partial timespan=$auto_summarize.timespan$
max_summary_size=$auto_summarize.max_summary_size$ max_summary_ratio=$auto_summarize.max_summary_ratio$
max_disabled_buckets=$auto_summarize.max_disabled_buckets$ max_time=$auto_summarize.max_time$ [ $search$ ]]]></s:key>
        <s:key name="auto_summarize.cron_schedule">*/10 * * * *</s:key>
        <s:key name="auto_summarize.dispatch.earliest_time"></s:key>
        <s:key name="auto_summarize.dispatch.latest_time"></s:key>
        <s:key name="auto_summarize.dispatch.time_format">%FT%T.%Q%:z</s:key>
        <s:key name="auto_summarize.dispatch.ttl">60</s:key>
        <s:key name="auto_summarize.max_concurrent">1</s:key>
        <s:key name="auto_summarize.max_disabled_buckets">2</s:key>
        <s:key name="auto_summarize.max_summary_ratio">0.1</s:key>
        <s:key name="auto_summarize.max_summary_size">52428800</s:key>
        <s:key name="auto_summarize.max_time">3600</s:key>
        <s:key name="auto_summarize.suspend_period">24h</s:key>
```

```
<s:key name="auto_summarize.timespan"></s:key>
<s:key name="auto_summarize.workload_pool"></s:key>
<s:key name="cron_schedule">*/3 * * * *</s:key>
<s:key name="defer_scheduled_searchable_idxc">0</s:key>
<s:key name="description">This test job is a durable saved search</s:key>
<s:key name="disabled">0</s:key>
<s:key name="dispatch.allow_partial_results">1</s:key>
<s:key name="dispatch.auto_cancel">0</s:key>
<s:key name="dispatch.auto_pause">0</s:key>
<s:key name="dispatch.buckets">0</s:key>
<s:key name="dispatch.earliest_time">-24h@h</s:key>
<s:key name="dispatch.index_earliest"></s:key>
<s:key name="dispatch.index_latest"></s:key>
<s:key name="dispatch.indexedRealtime"></s:key>
<s:key name="dispatch.indexedRealtimeMinSpan"></s:key>
<s:key name="dispatch.indexedRealtimeOffset"></s:key>
<s:key name="dispatch.latest_time">now</s:key>
<s:key name="dispatch.lookups">1</s:key>
<s:key name="dispatch.max_count">500000</s:key>
<s:key name="dispatch.max_time">0</s:key>
<s:key name="dispatch.reduce_freq">10</s:key>
<s:key name="dispatch.rt_backfill">0</s:key>
<s:key name="dispatch.rt_maximum_span"></s:key>
<s:key name="dispatch.sample_ratio">1</s:key>
<s:key name="dispatch.spawn_process">1</s:key>
<s:key name="dispatch.time_format">%FT%T.%Q%:z</s:key>
<s:key name="dispatch.ttl">2p</s:key>
<s:key name="dispatchAs">owner</s:key>
<!-- display settings elided -->
<s:key name="displayview"></s:key>
<s:key name="durable.backfill_type">auto</s:key>
<s:key name="durable.lag_time">0</s:key>
<s:key name="durable.max_backfill_intervals">0</s:key>
<s:key name="durable.track_time_type"></s:key>
<s:key name="eai:acl">
  <s:dict>
    <s:key name="app">search</s:key>
    <s:key name="can_change_perms">1</s:key>
    <s:key name="can_list">1</s:key>
    <s:key name="can_share_app">1</s:key>
    <s:key name="can_share_global">1</s:key>
    <s:key name="can_share_user">1</s:key>
    <s:key name="can_write">1</s:key>
    <s:key name="modifiable">1</s:key>
    <s:key name="owner">admin</s:key>
    <s:key name="perms"/>
    <s:key name="removable">1</s:key>
    <s:key name="sharing">user</s:key>
  </s:dict>
</s:key>
<s:key name="eai:attributes">
  <s:dict>
    <s:key name="optionalFields">
      <s:list>
        <!-- action settings elided -->
        <s:item>actions</s:item>
        <s:item>alert.digest_mode</s:item>
        <s:item>alert.expires</s:item>
        <s:item>alert.managedBy</s:item>
        <s:item>alert.severity</s:item>
        <s:item>alert.suppress</s:item>
        <s:item>alert.suppress.fields</s:item>
        <s:item>alert.suppress.group_name</s:item>
        <s:item>alert.suppress.period</s:item>
        <s:item>alert.track</s:item>
        <s:item>alert_comparator</s:item>
        <s:item>alert_condition</s:item>
        <s:item>alert_threshold</s:item>
        <s:item>alert_type</s:item>
        <s:item>allow_skew</s:item>
        <s:item>auto_summarize</s:item>
        <s:item>auto_summarize.command</s:item>
        <s:item>auto_summarize.cron_schedule</s:item>
        <s:item>auto_summarize.dispatch.earliest_time</s:item>
        <s:item>auto_summarize.dispatch.latest_time</s:item>
        <s:item>auto_summarize.dispatch.time_format</s:item>
        <s:item>auto_summarize.dispatch.ttl</s:item>
        <s:item>auto_summarize.max_concurrent</s:item>
        <s:item>auto_summarize.max_disabled_buckets</s:item>
        <s:item>auto_summarize.max_summary_ratio</s:item>
        <s:item>auto_summarize.max_summary_size</s:item>
        <s:item>auto_summarize.max_time</s:item>
        <s:item>auto_summarize.suspend_period</s:item>
        <s:item>auto_summarize.timespan</s:item>
        <s:item>auto_summarize.workload_pool</s:item>
        <s:item>cron_schedule</s:item>
        <s:item>defer_scheduled_searchable_idxc</s:item>
        <s:item>description</s:item>
        <s:item>disabled</s:item>
        <s:item>dispatch.allow_partial_results</s:item>
        <s:item>dispatch.auto_cancel</s:item>
```

```
            <s:item>dispatch.auto_pause</s:item>
            <s:item>dispatch.buckets</s:item>
            <s:item>dispatch.earliest_time</s:item>
            <s:item>dispatch.index_earliest</s:item>
            <s:item>dispatch.index_latest</s:item>
            <s:item>dispatch.indexedRealtime</s:item>
            <s:item>dispatch.indexedRealtimeMinSpan</s:item>
            <s:item>dispatch.indexedRealtimeOffset</s:item>
            <s:item>dispatch.latest_time</s:item>
            <s:item>dispatch.lookups</s:item>
            <s:item>dispatch.max_count</s:item>
            <s:item>dispatch.max_time</s:item>
            <s:item>dispatch.reduce_freq</s:item>
            <s:item>dispatch.rt_backfill</s:item>
            <s:item>dispatch.rt_maximum_span</s:item>
            <s:item>dispatch.sample_ratio</s:item>
            <s:item>dispatch.spawn_process</s:item>
            <s:item>dispatch.time_format</s:item>
            <s:item>dispatch.ttl</s:item>
            <s:item>dispatchAs</s:item>
            <!-- display settings elided -->
            <s:item>displayview</s:item>
            <s:item>durable.backfill_type</s:item>
            <s:item>durable.lag_time</s:item>
            <s:item>durable.max_backfill_intervals</s:item>
            <s:item>durable.track_time_type</s:item>
            <s:item>estimatedResultCount</s:item>
            <s:item>federated.provider</s:item>
            <s:item>hint</s:item>
            <s:item>is_scheduled</s:item>
            <s:item>is_visible</s:item>
            <s:item>max_concurrent</s:item>
            <s:item>next_scheduled_time</s:item>
            <s:item>numFields</s:item>
            <s:item>qualifiedSearch</s:item>
            <s:item>realtime_schedule</s:item>
            <s:item>request.ui_dispatch_app</s:item>
            <s:item>request.ui_dispatch_view</s:item>
            <s:item>restart_on_searchpeer_add</s:item>
            <s:item>run_n_times</s:item>
            <s:item>run_on_startup</s:item>
            <s:item>schedule_as</s:item>
            <s:item>schedule_priority</s:item>
            <s:item>schedule_window</s:item>
            <s:item>search</s:item>
            <s:item>skip_scheduled_realtime_idxc</s:item>
            <s:item>vsid</s:item>
            <s:item>workload_pool</s:item>
          </s:list>
        </s:key>
        <s:key name="requiredFields">
          <s:list>
            <s:item>name</s:item>
          </s:list>
        </s:key>
        <s:key name="wildcardFields">
          <s:list>
            <s:item>action\..*</s:item>
            <s:item>args\..*</s:item>
            <s:item>dispatch\..*</s:item>
            <s:item>display\.statistics\.format\..*</s:item>
            <s:item>display\.visualizations\.custom\..*</s:item>
            <s:item>durable\..*</s:item>
          </s:list>
        </s:key>
      </s:dict>
    </s:key>
    <s:key name="embed.enabled">0</s:key>
    <s:key name="federated.provider"></s:key>
    <s:key name="is_scheduled">0</s:key>
    <s:key name="is_visible">1</s:key>
    <s:key name="max_concurrent">1</s:key>
    <s:key name="next_scheduled_time"></s:key>
    <s:key name="qualifiedSearch">search search index=_internal | stats count by host</s:key>
    <s:key name="realtime_schedule">1</s:key>
    <s:key name="request.ui_dispatch_app"></s:key>
    <s:key name="request.ui_dispatch_view"></s:key>
    <s:key name="restart_on_searchpeer_add">1</s:key>
    <s:key name="run_n_times">0</s:key>
    <s:key name="run_on_startup">0</s:key>
    <s:key name="schedule_as">auto</s:key>
    <s:key name="schedule_priority">default</s:key>
    <s:key name="schedule_window">0</s:key>
    <s:key name="search">search index=_internal | stats count by host</s:key>
    <s:key name="skip_scheduled_realtime_idxc">0</s:key>
    <s:key name="vsid"></s:key>
    <s:key name="workload_pool"></s:key>
  </s:dict>
 </content>
</entry>
</feed>
```

saved/searches/{name}

JSON

```
https://<host>:<mPort>/services/saved/searches/{name}
```

Manage the {name} saved search.

DELETE

Delete the named saved search.

Request parameters

None

Returned values

None

Example request and response

CODE

```
curl -k -u admin:pass --request DELETE https://localhost:8089/servicesNS/admin/search/saved/searches/MySavedSearch
```

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/"
      xmlns:s="http://dev.splunk.com/ns/rest">
  <title>savedsearch</title>
  <id>https://localhost:8089/servicesNS/admin/search/saved/searches</id>
  <updated>2011-07-13T12:09:05-07:00</updated>
  <generator version="102824"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/admin/search/saved/searches/_new" rel="create"/>
  <link href="/servicesNS/admin/search/saved/searches/_reload" rel="_reload"/>
  <!-- opensearch nodes elided for brevity. -->
  <s:messages/>
</feed>
```

GET

Access the named saved search.

Request parameters

Name	Type	Default	Description
earliest_time	String		If the search is scheduled display scheduled times starting from this time
latest_time	String		If the search is scheduled display scheduled times ending at this time
listDefaultActionArgs	Boolean		Indicates whether to list default actions.
add_orphan_field	Boolean		Indicates whether the response includes a boolean value for each saved search to show whether the search is orphaned, meaning that it has no valid owner. When *add_orphan_field* is set to `true`, the response includes the orphaned search indicators, either `0` to indicate that a search is not orphaned or `1` to indicate that the search is orphaned. Admins can use this setting to check for searches without valid owners and resolve related issues.

Returned values

Name	Description
action.<action_name>	Indicates whether the `<action_name>` is enabled or disabled for a particular search. For more information about the alert action options see the `alert_actions.conf` file.

Name	Description
action.<action_name>.<parameter>	Overrides the setting defined for an action in the `alert_actions.conf` file with a new setting that is valid only for the search configuration to which it is applied.
action.email	Indicates the state of the email action.
action.email.auth_password	The password to use when authenticating with the SMTP server. Normally this value is set when editing the email settings, however you can set a clear text password here that is encrypted on the next restart. Defaults to empty string.
action.email.auth_username	The username to use when authenticating with the SMTP server. If this is empty string, no authentication is attempted. Defaults to empty string. *Note:* Your SMTP server might reject unauthenticated emails.
action.email.bcc	BCC email address to use if action.email is enabled.
action.email.cc	CC email address to use if action.email is enabled.
action.email.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.email.format	Specify the format of text in the email. This value also applies to any attachments. Valid values: (plain | html | raw | csv)
action.email.from	Email address from which the email action originates.
action.email.hostname	Sets the hostname used in the web link (url) sent in email actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) When this value is a simple hostname, the protocol and port which are configured within splunk are used to construct the base of the url. When this value begins with 'http://', it is used verbatim. *Note:* This means the correct port must be specified if it is not the default port for http or https. This is useful in cases when the Splunk server is not aware of how to construct a url that can be referenced externally, such as SSO environments, other proxies, or when the server hostname is not generally resolvable. Defaults to current hostname provided by the operating system, or if that fails "localhost." When set to empty, default behavior is used.
action.email.inline	Indicates whether the search results are contained in the body of the email. Results can be either inline or attached to an email. See action.email.sendresults.
action.email.mailserver	Set the address of the MTA server to be used to send the emails. Defaults to <LOCALHOST> (or whatever is set in alert_actions.conf).
action.email.maxresults	Sets the global maximum number of search results to send when email.action is enabled.
action.email.maxtime	Specifies the maximum amount of time the execution of an email action takes before the action is aborted.
action.email.preprocess_results	Search string to preprocess results before emailing them. Defaults to empty string (no preprocessing). Usually the preprocessing consists of filtering out unwanted internal fields.
action.email.reportPaperOrientation	Specifies the paper orientation: portrait or landscape.
action.email.reportPaperSize	Specifies the paper size for PDFs. Defaults to letter. Valid values: (letter | legal | ledger | a2 | a3 | a4 | a5)
action.email.reportServerEnabled	Not supported.
action.email.reportServerURL	Not supported.
action.email.sendpdf	Indicates whether to create and send the results as a PDF.
action.email.sendresults	Indicates whether to attach the search results in the email. Results can be either attached or inline. See action.email.inline.
action.email.subject	Specifies an email subject. Defaults to SplunkAlert-<savedsearchname>.

Name	Description
action.email.to	List of recipient email addresses. Required if this search is scheduled and the email alert action is enabled.
action.email.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.email.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows <Integer>, int is the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p].
action.email.use_ssl	Indicates whether to use SSL when communicating with the SMTP server.
action.email.use_tls	Indicates whether to use TLS (transport layer security) when communicating with the SMTP server (starttls).
action.populate_lookup	The state of the populate lookup action.
action.populate_lookup.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.populate_lookup.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.populate_lookup.maxresults	The maximum number of search results sent using alerts.
action.populate_lookup.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 5m. Valid values are: Integer[m|s|h|d]
action.populate_lookup.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.populate_lookup.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, then this specifies the number of scheduled periods. Defaults to 10p. If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p]
action.rss	The state of the RSS action.
action.rss.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.rss.hostname	Sets the hostname used in the web link (url) sent in alert actions.
action.rss.maxresults	Sets the maximum number of search results sent using alerts.
action.rss.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 1m.
action.rss.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.rss.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
action.script	The state of the script action.
action.script.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.

Name	Description
action.script.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See *action.email.hostname* for details.
action.script.maxresults	The maximum number of search results sent using alerts.
action.script.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted.
action.script.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.script.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 600 (10 minutes). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
action.summary_index	The state of the summary index action.
action.summary_index._name	Specifies the name of the summary index where the results of the scheduled search are saved. Defaults to "summary."
action.summary_index._type"	Specifies the data type of the summary index where the Splunk software saves the results of the scheduled search. Can be set to `event` or `metric`.
action.summary_index.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.summary_index.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.summary_index.force_realtime_schedule	By default, *realtime_schedule* is `false` for a report configured for summary indexing. When set to `1` or `true`, this setting overrides *realtime_schedule*. Setting this setting to `true` can cause gaps in summary data, as a *realtime_schedule* search is skipped if search concurrency limits are violated.
action.summary_index.inline	Determines whether to execute the summary indexing action as part of the scheduled search. *Note:* This option is considered only if the summary index action is enabled and is always executed (in other words, if counttype = always).
action.summary_index.maxresults	Sets the maximum number of search results sent using alerts.
action.summary_index.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 5m.
action.summary_index.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.summary_index.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 10p. If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
alert.digest_mode	Specifies whether alert actions are applied to the entire result set or to each individual result.
alert.expires	Sets the period of time to show the alert in the dashboard. Defaults to 24h.
alert.managedBy	Specifies the feature or component that created the alert.

Name	Description
alert.severity	Valid values: (1 | 2 | 3 | 4 | 5 | 6) Sets the alert severity level. Valid values are: 1 DEBUG 2 INFO 3 WARN 4 ERROR 5 SEVERE 6 FATAL
alert.suppress	Indicates whether alert suppression is enabled for this schedules search.
alert.suppress.fields	List of fields to use when suppressing per-result alerts. Must be specified if the digest mode is disabled and suppression is enabled.
alert.suppress.group_name	Optional setting. Used to define an alert suppression group for a set of alerts that are running over identical or very similar datasets. Alert suppression groups can help you avoid getting multiple triggered alert notifications for the same data.
alert.suppress.period	Specifies the suppression period. Only valid if alert.suppress is enabled. Uses [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
alert.track	Specifies whether to track the actions triggered by this scheduled search. `auto` - (Default) Determine whether to apply alert tracking to this search, based on the tracking setting of each action. Do not track scheduled searches that always trigger actions. `true` - Force alert tracking for this search. Default. `false` - Disable alert tracking for this search.
alert_comparator	One of the following strings: greater than less than equal to rises by drops by rises by perc drops by perc Used with *alert_threshold* to trigger alert actions.
alert_condition	A conditional search that is evaluated against the results of the saved search. Defaults to an empty string. Alerts are triggered if the specified search yields a non-empty search result list. *Note:* If you specify an *alert_condition*, do not set counttype, relation, or quantity.
alert_threshold	Valid values are: Integer[%] Specifies the value to compare (see *alert_comparator*) before triggering the alert actions. If expressed as a percentage, indicates value to use when alert_comparator is set to *rises by perc" or "drops by perc."*
alert_type	What to base the alert on, overridden by *alert_condition* if it is specified. Valid values are: always, custom, number of events, number of hosts, number of sources. Typically, reports return the "always" value, while alerts can return any other value.

Name	Description

allow_skew	`0 | <percentage> | <duration>`
	
	Allows the search scheduler to distribute scheduled searches randomly and more evenly over their specified search periods.
	
	CAUTION: This setting does not require adjusting in most use cases. Check with an admin before making any updates.
	
	When set to a non-zero value for searches with the following `cron_schedule` values, the search scheduler randomly skews the second, minute, and hour on which the search runs.
	
	CODE
	
	`* * * * *  Every minute.`
	`*/M * * * *  Every M minutes (M > 0).`
	`0 * * * *  Every hour.`
	`0 */H * * *  Every H hours (H > 0).`
	`0 0 * * *  Every day (at midnight).`
	
	When set to a non-zero value for a search that has any other `cron_schedule` setting, the search scheduler can randomly skew only the second on which the search runs.
	
	The amount of skew for a specific search remains constant between edits of the search.
	
	A value of `0` disallows skew. `0` is the default setting.
	
	Percentage
	
	`<int>` followed by `%` specifies the maximum amount of time to skew as a percentage of the scheduled search period.
	
	Duration
	
	`<int><unit>` specifies a maximum duration. The `<unit>` can be omitted only when the `<int>` is `0`.
	
	Valid duration units:
	
	• `m`
	• `min`
	• `minute`
	• `mins`
	• `minutes`
	• `h`
	• `hr`
	• `hour`
	• `hrs`
	• `hours`
	• `d`
	• `day`
	• `days`
	
	Examples
	
	CODE
	
	`100% (for an every-5-minute search) = 5 minutes maximum`
	`50% (for an every-minute search) = 30 seconds maximum`
	`5m = 5 minutes maximum`
	`1h = 1 hour maximum`

auto_summarize	Specifies whether the search scheduler should ensure that the data for this search is automatically summarized.
auto_summarize.command	A search template to use to construct the auto-summarization for the search. Do not change.
auto_summarize.cron_schedule	Cron schedule to use to probe or generate the summaries for this search
auto_summarize.dispatch.<arg-name>	Dispatch options that can be overridden when running the summary search.
auto_summarize.max_concurrent	The maximum number of concurrent instances of this auto summarizing search that the scheduler is allowed to run.
auto_summarize.max_disabled_buckets	The maximum number of buckets with suspended summarization before the summarization search is completely stopped and the summarization of the search is suspended for the value specified by the *auto_summarize.suspend_period* setting.
auto_summarize.max_summary_ratio	The maximum ratio of summary_size/bucket_size, which specifies when to stop summarization and deem it unhelpful for a bucket.
auto_summarize.max_summary_size	The minimum summary size, in bytes, before testing whether the summarization is helpful.
auto_summarize.max_time	The maximum time, in seconds, that the auto-summarization search is allowed to run.
auto_summarize.suspend_period	The amount of time to suspend summarization of the search if the summarization is deemed unhelpful.

Name	Description
auto_summarize.timespan	Comma-delimited list of time ranges that each summarized chunk should span. Comprises the list of available summary ranges for which summaries would be available. Does not support `1w` timespans.
auto_summarize.workload_pool	Sets the name of the workload pool that is used by the auto-summarization of this search.
cron_schedule	The cron schedule to run this search. For more information, refer to the description of this parameter in the POST endpoint.
defer_scheduled_searchable_idxc	Specifies whether to defer a continuous saved search during a searchable rolling restart or searchable rolling upgrade of an indexer cluster.
description	Description of this saved search.
disabled	Indicates if this saved search is disabled.
dispatch.allow_partial_results	Specifies whether the search job can proceed to provide partial results if a search peer fails. When set to false, the search job fails if a search peer providing results for the search job fails.
dispatch.auto_cancel	Specifies the amount of inactive time, in seconds, after which the search job is automatically canceled.
dispatch.auto_pause	Specifies the amount of inactive time, in seconds, after which the search job is automatically paused.
dispatch.buckets	The maximum number of timeline buckets.
dispatch.earliest_time	A time string that specifies the earliest time for this search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.
dispatch.index_earliest	Specifies the earliest index time for this search. Can be a relative or absolute time.
dispatch.index_latest	Specifies the latest index time for this saved search. Can be a relative or absolute time.
dispatch.indexedRealtime	Specifies whether to use 'indexed-realtime' mode when doing real-time searches.
dispatch.indexedRealtimeMinSpan	Specifies the minimum number of seconds to wait between component index searches.
dispatch.indexedRealtimeOffset	Specifies the number of seconds to wait for disk flushes to finish.
dispatch.indexedRealtimeMinSpan	Allows for a per-job override of the `[search] indexed_realtime_default_span` setting in `limits.conf`. The default for saved searches is "unset", falling back to the `limits.conf` setting.
dispatch.latest_time	A time string that specifies the latest time for this saved search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.
dispatch.lookups	Indicates if lookups are enabled for this search.
dispatch.max_count	The maximum number of results before finalizing the search.
dispatch.max_time	Indicates the maximum amount of time (in seconds) before finalizing the search.
dispatch.reduce_freq	Specifies how frequently the MapReduce reduce phase runs on accumulated map values.
dispatch.rt_backfill	Specifies whether to do real-time window backfilling for scheduled real-time searches.
dispatch.rt_maximum_span	Sets the maximum number of seconds to search data that falls behind real time.
dispatch.sample_ratio	The integer value used to calculate the sample ratio. The formula is `1 / <integer>`.
dispatch.spawn_process	This parameter is deprecated and will be removed in a future release. Do not use this parameter. Indicates whether a new search process spawns when this saved search is executed.
dispatch.time_format	A time format string that defines the time format for specifying the earliest and latest time.
dispatch.ttl	Indicates the time to live (ttl), in seconds, for the artifacts of the scheduled search, if no actions are triggered.
displayview	Defines the default Splunk Web view name (not label) in which to load the results. Accessibility is subject to the user having sufficient permissions.
durable.backfill_type	Specifies how the Splunk software backfills the lost search results of failed scheduled search jobs. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*. Valid values are `auto`, `time_interval`, and `time_whole`.

Name	Description
durable.lag_time	Specifies the search time delay, in seconds, that a durable search uses to catch events that are ingested or indexed late. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.max_backfill_intervals	Specifies the maximum number of cron intervals (previous scheduled search jobs) that the Splunk software can attempt to backfill for this search, when those jobs have incomplete events. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.track_time_type	Indicates that a scheduled search is durable and specifies how the search tracks events. A value of `_time` means the durable search tracks each event by its event timestamp , based on time information included in the event. A value of `_indextime` means the durable search tracks each event by its indexed timestamp. The search is not durable if this setting is unset or is set to `none`.
earliest_time	For scheduled searches display all the scheduled times starting from this time.
is_scheduled	Indicates if this search is to be run on a schedule.
is_visible	Indicates if this saved search appears in the visible saved search list.
latest_time	For scheduled searches display all the scheduled times until this time (not just the next run time).
listDefaultActionArgs	List default values of actions.*, even though some of the actions may not be specified in the saved search.
max_concurrent	The maximum number of concurrent instances of this search the scheduler is allowed to run.
next_scheduled_time	The time when the scheduler runs this search again.
orphan	If the `add_orphan_field` parameter is passed in with the GET request, this field indicates whether the search is orphaned.
qualifiedSearch	The exact search command for this saved search.
realtime_schedule	Controls the way the scheduler computes the next execution time of a scheduled search. If this value is set to 1, the scheduler bases its determination of the next scheduled search execution time on the current time. If this value is set to 0, the scheduler bases its determination of the next scheduled search on the last search execution time. This is called continuous scheduling. See the POST parameter for this attribute for details.
request.ui_dispatch_app	A field used by Splunk Web to denote the app this search should be dispatched in.
request.ui_dispatch_view	Specifies a field used by Splunk Web to denote the view this search should be displayed in.
restart_on_searchpeer_add	Indicates whether to restart a real-time search managed by the scheduler when a search peer becomes available for this saved search. *Note:* The peer can be a newly added peer or a peer down and now available.
run_n_times	Runs this search exactly the specified number of times. Does not run the search again until the Splunk platform is restarted.
run_on_startup	Indicates whether this search runs on startup. If it does not run on startup, it runs at the next scheduled time. Set run_on_startup to true for scheduled searches that populate lookup tables.

Name	Description

schedule_priority	Indicates the scheduling priority of a specific search. One of the following values.
	CODE
	`[ default | higher | highest ]`
	Raises the scheduling priority of the named search.
	default
	No scheduling priority increase.
	higher
	Scheduling priority is higher than other searches of the same scheduling tier. While there are four tiers of priority for scheduled searches, only the following are affected by this property:
	CODE
	`* real-Time-Scheduled (realtime_schedule=1).`
	`* continuous-Scheduled (realtime_schedule=0).`
	highest
	Scheduling priority is higher than other searches regardless of scheduling tier. However, real-time-scheduled searches with `priority = highest` always have priority over continuous scheduled searches with `priority = highest`.
	The high-to-low priority order (where RTSS = real-time-scheduled search,
	CODE
	`CSS = continuous-scheduled search, d = default, h = higher, H = highest) is:`
	CODE
	`RTSS(H) > CSS(H) > RTSS(h) > RTSS(d) > CSS(h) > CSS(d)`
	Requires the search owner to have the `edit_search_schedule_priority` capability in order to make non-default settings.
	Defaults to `default`.
	For more details, see `savedsearches.conf.spec`.

schedule_window	Time window (in minutes) during which the search has lower priority. The scheduler can give higher priority to more critical searches during this window. The window must be smaller than the search period. If set to `auto`, the scheduler determines the optimal time window automatically.
search	Search expression to filter the response. The response matches field values against the search expression. For example: search=foo matches any object that has "foo" as a substring in a field. search=field_name%3Dfield_value restricts the match to a single field. URI-encoding is required in this example.
vsid	Defines the viewstate id associated with the UI view listed in 'displayview'. Must match up to a stanza in viewstates.conf.

Example request and response

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/saved/searches/MySavedSearch
```

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>savedsearch</title>
  <id>https://fool01:8092/services/saved/searches</id>
  <updated>2021-04-29T10:00:27-07:00</updated>
  <generator build="84cbec3d51a6" version="8.2.2105"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/saved/searches/_new" rel="create"/>
  <link href="/services/saved/searches/_reload" rel="_reload"/>
  <link href="/services/saved/searches/_acl" rel="_acl"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>MySavedSearch</title>
    <id>https://fool01:8092/servicesNS/admin/search/saved/searches/MySavedSearch</id>
    <updated>2021-04-29T09:58:12-07:00</updated>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch" rel="list"/>
```

```
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch" rel="edit"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch" rel="remove"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch/move" rel="move"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch/disable" rel="disable"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch/dispatch" rel="dispatch"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch/embed" rel="embed"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch/history" rel="history"/>
    <content type="text/xml">
      <s:dict>
        < ---- action settings elided  ---- >
        <s:key name="actions"></s:key>
        <s:key name="alert.digest_mode">1</s:key>
        <s:key name="alert.expires">24h</s:key>
        <s:key name="alert.managedBy"></s:key>
        <s:key name="alert.severity">3</s:key>
        <s:key name="alert.suppress"></s:key>
        <s:key name="alert.suppress.fields"></s:key>
        <s:key name="alert.suppress.group_name"></s:key>
        <s:key name="alert.suppress.period"></s:key>
        <s:key name="alert.track">0</s:key>
        <s:key name="alert_comparator"></s:key>
        <s:key name="alert_condition"></s:key>
        <s:key name="alert_threshold"></s:key>
        <s:key name="alert_type">always</s:key>
        <s:key name="allow_skew">0</s:key>
        <s:key name="auto_summarize">0</s:key>
        <s:key name="auto_summarize.command"><![CDATA[| summarize override=partial timespan=$auto_summarize.timespan$
max_summary_size=$auto_summarize.max_summary_size$ max_summary_ratio=$auto_summarize.max_summary_ratio$
max_disabled_buckets=$auto_summarize.max_disabled_buckets$ max_time=$auto_summarize.max_time$ [ $search$ ]]]></s:key>
        <s:key name="auto_summarize.cron_schedule">*/10 * * * *</s:key>
        <s:key name="auto_summarize.dispatch.earliest_time"></s:key>
        <s:key name="auto_summarize.dispatch.latest_time"></s:key>
        <s:key name="auto_summarize.dispatch.time_format">%FT%T.%Q%:z</s:key>
        <s:key name="auto_summarize.dispatch.ttl">60</s:key>
        <s:key name="auto_summarize.max_concurrent">1</s:key>
        <s:key name="auto_summarize.max_disabled_buckets">2</s:key>
        <s:key name="auto_summarize.max_summary_ratio">0.1</s:key>
        <s:key name="auto_summarize.max_summary_size">52428800</s:key>
        <s:key name="auto_summarize.max_time">3600</s:key>
        <s:key name="auto_summarize.suspend_period">24h</s:key>
        <s:key name="auto_summarize.timespan"></s:key>
        <s:key name="auto_summarize.workload_pool"></s:key>
        <s:key name="cron_schedule">*/3 * * * *</s:key>
        <s:key name="defer_scheduled_searchable_idxc">0</s:key>
        <s:key name="description">This test job is a durable saved search</s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="dispatch.allow_partial_results">1</s:key>
        <s:key name="dispatch.auto_cancel">0</s:key>
        <s:key name="dispatch.auto_pause">0</s:key>
        <s:key name="dispatch.buckets">0</s:key>
        <s:key name="dispatch.earliest_time">-24h@h</s:key>
        <s:key name="dispatch.index_earliest"></s:key>
        <s:key name="dispatch.index_latest"></s:key>
        <s:key name="dispatch.indexedRealtime"></s:key>
        <s:key name="dispatch.indexedRealtimeMinSpan"></s:key>
        <s:key name="dispatch.indexedRealtimeOffset"></s:key>
        <s:key name="dispatch.latest_time">now</s:key>
        <s:key name="dispatch.lookups">1</s:key>
        <s:key name="dispatch.max_count">500000</s:key>
        <s:key name="dispatch.max_time">0</s:key>
        <s:key name="dispatch.reduce_freq">10</s:key>
        <s:key name="dispatch.rt_backfill">0</s:key>
        <s:key name="dispatch.rt_maximum_span"></s:key>
        <s:key name="dispatch.sample_ratio">1</s:key>
        <s:key name="dispatch.spawn_process">1</s:key>
        <s:key name="dispatch.time_format">%FT%T.%Q%:z</s:key>
        <s:key name="dispatch.ttl">2p</s:key>
        <s:key name="dispatchAs">owner</s:key>
        < ---- display settings elided  ---- >
        <s:key name="displayview"></s:key>
        <s:key name="durable.backfill_type">time_interval</s:key>
        <s:key name="durable.lag_time">30</s:key>
        <s:key name="durable.max_backfill_intervals">100</s:key>
        <s:key name="durable.track_time_type">_time</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app">search</s:key>
            <s:key name="can_change_perms">1</s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_share_app">1</s:key>
            <s:key name="can_share_global">1</s:key>
            <s:key name="can_share_user">1</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">1</s:key>
            <s:key name="owner">admin</s:key>
            <s:key name="perms"/>
            <s:key name="removable">1</s:key>
            <s:key name="sharing">user</s:key>
          </s:dict>
        </s:key>
```

```
<s:key name="eai:attributes">
  <s:dict>
    <s:key name="optionalFields">
      <s:list>
        < ---- action settings elided  ---- >
        <s:item>actions</s:item>
        <s:item>alert.digest_mode</s:item>
        <s:item>alert.expires</s:item>
        <s:item>alert.managedBy</s:item>
        <s:item>alert.severity</s:item>
        <s:item>alert.suppress</s:item>
        <s:item>alert.suppress.fields</s:item>
        <s:item>alert.suppress.group_name</s:item>
        <s:item>alert.suppress.period</s:item>
        <s:item>alert.track</s:item>
        <s:item>alert_comparator</s:item>
        <s:item>alert_condition</s:item>
        <s:item>alert_threshold</s:item>
        <s:item>alert_type</s:item>
        <s:item>allow_skew</s:item>
        <s:item>auto_summarize</s:item>
        <s:item>auto_summarize.command</s:item>
        <s:item>auto_summarize.cron_schedule</s:item>
        <s:item>auto_summarize.dispatch.earliest_time</s:item>
        <s:item>auto_summarize.dispatch.latest_time</s:item>
        <s:item>auto_summarize.dispatch.time_format</s:item>
        <s:item>auto_summarize.dispatch.ttl</s:item>
        <s:item>auto_summarize.max_concurrent</s:item>
        <s:item>auto_summarize.max_disabled_buckets</s:item>
        <s:item>auto_summarize.max_summary_ratio</s:item>
        <s:item>auto_summarize.max_summary_size</s:item>
        <s:item>auto_summarize.max_time</s:item>
        <s:item>auto_summarize.suspend_period</s:item>
        <s:item>auto_summarize.timespan</s:item>
        <s:item>auto_summarize.workload_pool</s:item>
        <s:item>cron_schedule</s:item>
        <s:item>defer_scheduled_searchable_idxc</s:item>
        <s:item>description</s:item>
        <s:item>disabled</s:item>
        <s:item>dispatch.allow_partial_results</s:item>
        <s:item>dispatch.auto_cancel</s:item>
        <s:item>dispatch.auto_pause</s:item>
        <s:item>dispatch.buckets</s:item>
        <s:item>dispatch.earliest_time</s:item>
        <s:item>dispatch.index_earliest</s:item>
        <s:item>dispatch.index_latest</s:item>
        <s:item>dispatch.indexedRealtime</s:item>
        <s:item>dispatch.indexedRealtimeMinSpan</s:item>
        <s:item>dispatch.indexedRealtimeOffset</s:item>
        <s:item>dispatch.latest_time</s:item>
        <s:item>dispatch.lookups</s:item>
        <s:item>dispatch.max_count</s:item>
        <s:item>dispatch.max_time</s:item>
        <s:item>dispatch.reduce_freq</s:item>
        <s:item>dispatch.rt_backfill</s:item>
        <s:item>dispatch.rt_maximum_span</s:item>
        <s:item>dispatch.sample_ratio</s:item>
        <s:item>dispatch.spawn_process</s:item>
        <s:item>dispatch.time_format</s:item>
        <s:item>dispatch.ttl</s:item>
        <s:item>dispatchAs</s:item>
        < ---- display settings elided  ---- >
        <s:item>displayview</s:item>
        <s:item>durable.backfill_type</s:item>
        <s:item>durable.lag_time</s:item>
        <s:item>durable.max_backfill_intervals</s:item>
        <s:item>durable.track_time_type</s:item>
        <s:item>estimatedResultCount</s:item>
        <s:item>federated.provider</s:item>
        <s:item>hint</s:item>
        <s:item>is_scheduled</s:item>
        <s:item>is_visible</s:item>
        <s:item>max_concurrent</s:item>
        <s:item>next_scheduled_time</s:item>
        <s:item>numFields</s:item>
        <s:item>qualifiedSearch</s:item>
        <s:item>realtime_schedule</s:item>
        <s:item>request.ui_dispatch_app</s:item>
        <s:item>request.ui_dispatch_view</s:item>
        <s:item>restart_on_searchpeer_add</s:item>
        <s:item>run_n_times</s:item>
        <s:item>run_on_startup</s:item>
        <s:item>schedule_as</s:item>
        <s:item>schedule_priority</s:item>
        <s:item>schedule_window</s:item>
        <s:item>search</s:item>
        <s:item>skip_scheduled_realtime_idxc</s:item>
        <s:item>vsid</s:item>
        <s:item>workload_pool</s:item>
      </s:list>
    </s:key>
```

```
            <s:key name="requiredFields">
              <s:list/>
            </s:key>
            <s:key name="wildcardFields">
              <s:list>
                <s:item>action\..*</s:item>
                <s:item>args\..*</s:item>
                <s:item>dispatch\..*</s:item>
                <s:item>display\.statistics\.format\..*</s:item>
                <s:item>display\.visualizations\.custom\..*</s:item>
                <s:item>durable\..*</s:item>
              </s:list>
            </s:key>
          </s:dict>
        </s:key>
        <s:key name="embed.enabled">0</s:key>
        <s:key name="federated.provider"></s:key>
        <s:key name="is_scheduled">0</s:key>
        <s:key name="is_visible">1</s:key>
        <s:key name="max_concurrent">1</s:key>
        <s:key name="next_scheduled_time"></s:key>
        <s:key name="qualifiedSearch">search search index=_internal | stats count by host</s:key>
        <s:key name="realtime_schedule">1</s:key>
        <s:key name="request.ui_dispatch_app"></s:key>
        <s:key name="request.ui_dispatch_view"></s:key>
        <s:key name="restart_on_searchpeer_add">1</s:key>
        <s:key name="run_n_times">0</s:key>
        <s:key name="run_on_startup">0</s:key>
        <s:key name="schedule_as">auto</s:key>
        <s:key name="schedule_priority">default</s:key>
        <s:key name="schedule_window">0</s:key>
        <s:key name="search">search index=_internal | stats count by host</s:key>
        <s:key name="skip_scheduled_realtime_idxc">0</s:key>
        <s:key name="vsid"></s:key>
        <s:key name="workload_pool"></s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```


POST

Update the named saved search.

Request parameters

Name	Type	Description
action.<action_name>	Boolean	Enable or disable an alert action. See `alert_actions.conf` for available alert action types. `action_name` defaults to the empty string.
action.<action_name>.<parameter>	String or Number	Use this syntax to configure action parameters. See `alert_actions.conf` for parameter options.
action.summary_index._type"	String	Specifies the data type of the summary index where the Splunk software saves the results of the scheduled search. Can be set to `event` or `metric`.
action.summary_index.force_realtime_schedule	Boolean	By default, *realtime_schedule* is `false` for a report configured for summary indexing. When set to `1` or `True`, this setting overrides *realtime_schedule*. Setting this setting to `true` can cause gaps in summary data, as a *realtime_schedule* search is skipped if search concurrency limits are violated.
actions	String	A comma-separated list of actions to enable. For example: rss,email
alert.digest_mode	Boolean	Specifies whether alert actions are applied to the entire result set or on each individual result. Defaults to 1 (true).
alert.expires	Number	Valid values: [number][time-unit] Sets the period of time to show the alert in the dashboard. Defaults to 24h. Use [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.

Name	Type	Description
alert.severity	Enum	Valid values: (1 | 2 | 3 | 4 | 5 | 6) Sets the alert severity level. Valid values are: 1 DEBUG 2 INFO 3 WARN 4 ERROR 5 SEVERE 6 FATAL Defaults to 3.
alert.suppress	Boolean	Indicates whether alert suppression is enabled for this scheduled search.
alert.suppress.fields	String	Comma delimited list of fields to use for suppression when doing per result alerting. Required if suppression is turned on and per result alerting is enabled.
alert.suppress.group_name	String	Optional setting. Used to define an alert suppression group for a set of alerts that are running over identical or very similar datasets. Alert suppression groups can help you avoid getting multiple triggered alert notifications for the same data.
alert.suppress.period	Number	Valid values: [number][time-unit] Specifies the suppression period. Only valid if *alert.suppress* is enabled. Use [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
alert.track	Enum	Valid values: (true | false | auto) Specifies whether to track the actions triggered by this scheduled search. `auto` - Determine whether to apply alert tracking to this search, based on the tracking setting of each action. Do not track scheduled searches that always trigger actions. Default. `true` - Force alert tracking for this search. `false` - Disable alert tracking for this search.
alert_comparator	String	One of the following strings: greater than, less than, equal to, rises by, drops by, rises by perc, drops by perc. Used with *alert_threshold* to trigger alert actions.
alert_condition	String	Contains a conditional search that is evaluated against the results of the saved search. Defaults to an empty string. Alerts are triggered if the specified search yields a non-empty search result list. Note: If you specify an alert_condition, do not set counttype, relation, or quantity.
alert_threshold	Number	Valid values are: Integer[%] Specifies the value to compare (see *alert_comparator*) before triggering the alert actions. If expressed as a percentage, indicates value to use when *alert_comparator* is set to "rises by perc" or "drops by perc."
alert_type	String	What to base the alert on, overridden by *alert_condition* if it is specified. Valid values are: always, custom, number of events, number of hosts, number of sources.

Name	Type	Description

allow_skew	`0 | <percentage> | <duration>`	Allows the search scheduler to distribute scheduled searches randomly and more evenly over their specified search periods.
		
		CAUTION: This setting does not require adjusting in most use cases. Check with an admin before making any updates.
		
		When set to a non-zero value for searches with the following *cron_schedule* values, the search scheduler randomly skews the second, minute, and hour on which the search runs.
		
		CODE
		
		`* * * * *  Every minute.`
		`*/M * * * *  Every M minutes (M > 0).`
		`0 * * * *  Every hour.`
		`0 */H * * *  Every H hours (H > 0).`
		`0 0 * * *  Every day (at midnight).`
		
		When set to a non-zero value for a search that has any other `cron_schedule` setting, the search scheduler can randomly skew only the second on which the search runs.
		
		The amount of skew for a specific search remains constant between edits of the search.
		
		A value of `0` disallows skew. `0` is the default setting.
		
		Percentage
		
		`<int>` followed by `%` specifies the maximum amount of time to skew as a percentage of the scheduled search period.
		
		Duration
		
		`<int><unit>` specifies a maximum duration. The `<unit>` can be omitted only when the `<int>` is `0`.
		
		Valid duration units:
		
		• `m`
		• `min`
		• `minute`
		• `mins`
		• `minutes`
		• `h`
		• `hr`
		• `hour`
		• `hrs`
		• `hours`
		• `d`
		• `day`
		• `days`
		
		Examples
		
		CODE
		
		`100% (for an every-5-minute search) = 5 minutes maximum`
		`50% (for an every-minute search) = 30 seconds maximum`
		`5m = 5 minutes maximum`
		`1h = 1 hour maximum`

*args.**	String	Wildcard argument that accepts any saved search template argument, such as args.username=foobar when the search is search $username$.
auto_summarize	Boolean	Indicates whether the scheduler should ensure that the data for this search is automatically summarized. Defaults to 0.
auto_summarize.command	String	An auto summarization template for this search. See auto summarization options in `savedsearches.conf` for more details. Do not change unless you understand the architecture of saved search auto summarization.
auto_summarize.cron_schedule	String	Cron schedule that probes and generates the summaries for this saved search. The default value is `*/10 * * * *` and corresponds to "every ten hours".
auto_summarize.dispatch.earliest_time	String	A time string that specifies the earliest time for summarizing this search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.

Name	Type	Description
auto_summarize.dispatch.latest_time	String	A time string that specifies the latest time for summarizing this saved search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
auto_summarize.dispatch.time_format	String	Defines the time format that Splunk software uses to specify the earliest and latest time. Defaults to `%FT%T.%Q%:z`
auto_summarize.dispatch.ttl	String	Valid values: Integer[p]. Indicates the time to live (ttl), in seconds, for the artifacts of the summarization of the scheduled search. Defaults to 60.
auto_summarize.max_disabled_buckets	Number	The maximum number of buckets with the suspended summarization before the summarization search is completely stopped, and the summarization of the search is suspended for auto_summarize.suspend_period. Defaults to 2.
auto_summarize.max_summary_ratio	Number	The maximum ratio of summary_size/bucket_size, which specifies when to stop summarization and deem it unhelpful for a bucket. Defaults to `0.1` *Note:* The test is only performed if the summary size is larger than auto_summarize.max_summary_size.
auto_summarize.max_summary_size	Number	The minimum summary size, in bytes, before testing whether the summarization is helpful. The default value is `52428800` and is equivalent to 5MB.
auto_summarize.max_time	Number	Maximum time (in seconds) that the summary search is allowed to run. Defaults to 3600. *Note:* This is an approximate time. The summary search stops at clean bucket boundaries.
auto_summarize.suspend_period	String	Time specifier indicating when to suspend summarization of this search if the summarization is deemed unhelpful. Defaults to 24h.
auto_summarize.timespan	String	Comma-delimited list of time ranges that each summarized chunk should span. Comprises the list of available granularity levels for which summaries would be available. Does not support `1w` timespans. For example, a timechart over the last month whose granularity is at the day level should set this to `1d`. If you need the same data summarized at the hour level for weekly charts, use: `1h,1d`.
cron_schedule	String	Valid values: cron string The cron schedule to execute this search. For example: */5 * * * * causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: 00,20,40 * * * *, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of 03,23,43 * * * * runs the search every hour at hh:03, hh:23, hh:43. Splunk recommends that you schedule your searches so that they are staggered over time. This reduces system load. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes.
description	String	Human-readable description of this saved search. Defaults to empty string.
disabled	Boolean	Indicates if the saved search is enabled. Defaults to 0. Disabled saved searches are not visible in Splunk Web.
*dispatch.**	String	Wildcard argument that accepts any dispatch related argument.
dispatch.allow_partial_results	Boolean	Specifies whether the search job can proceed to provide partial results if a search peer fails. When set to false, the search job fails if a search peer providing results for the search job fails.
dispatch.auto_cancel	Number	Specifies the amount of inactive time, in seconds, after which the search job is automatically canceled.

Name	Type	Description
dispatch.auto_pause	Number	Specifies the amount of inactive time, in seconds, after which the search job is automatically paused.
dispatch.buckets	Number	The maximum number of timeline buckets. Defaults to 0.
dispatch.earliest_time	String	A time string that specifies the earliest time for this search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.
dispatch.index_earliest	String	A time string that specifies the earliest index time for this search. Can be a relative or absolute time.
dispatch.index_latest	String	A time string that specifies the latest index time for this saved search. Can be a relative or absolute time.
dispatch.indexedRealtime	Boolean	Indicates whether to used indexed-realtime mode when doing real-time searches.
dispatch.indexedRealtimeOffset	Integer	Allows for a per-job override of the `[search] indexed_realtime_disk_sync_delay` setting in `limits.conf`. Default for saved searches is "unset", falling back to `limits.conf` setting.
dispatch.indexedRealtimeMinSpan	Integer	Allows for a per-job override of the `[search] indexed_realtime_default_span` setting in `limits.conf`. Default for saved searches is "unset", falling back to the `limits.conf` setting.
dispatch.latest_time	String	A time string that specifies the latest time for this saved search. Can be a relative or absolute time. If this value is an absolute time, use the *dispatch.time_format* to format the value.
dispatch.lookups	Boolean	Enables or disables the lookups for this search. Defaults to 1.
dispatch.max_count	Number	The maximum number of results before finalizing the search. Defaults to 500000.
dispatch.max_time	Number	Indicates the maximum amount of time (in seconds) before finalizing the search. Defaults to 0.
dispatch.reduce_freq	Number	Specifies, in seconds, how frequently the MapReduce reduce phase runs on accumulated map values. Defaults to 10.
dispatch.rt_backfill	Boolean	Whether to back fill the real time window for this search. Parameter valid only if this is a real time search. Defaults to 0.
dispatch.rt_maximum_span	Number	Allows for a per-job override of the `[search] indexed_realtime_maximum_span` setting in `limits.conf`. Default for saved searches is "unset", falling back to the `limits.conf` setting.
dispatch.sample_ratio	Number	The integer value used to calculate the sample ratio. The formula is `1 / <integer>`.
dispatch.spawn_process	Boolean	This parameter is deprecated and will be removed in a future release. Do not use this parameter. Specifies whether a new search process spawns when this saved search is executed. Defaults to 1. Searches against indexes *must* run in a separate process.
dispatch.time_format	String	A time format string that defines the time format for specifying the earliest and latest time. Defaults to `%FT%T.%Q%:z`
dispatch.ttl	Number	Valid values: Integer[p]. Defaults to 2p. Indicates the time to live (in seconds) for the artifacts of the scheduled search, if no actions are triggered. If an action is triggered, the ttl changes to that action ttl. If multiple actions are triggered, the maximum ttl is applied to the artifacts. To set the action ttl, refer to `alert_actions.conf.spec`. If the integer is followed by the letter 'p', the ttl is handled as a multiple of the scheduled search period.

Name	Type	Description
dispatchAs	String	When the saved search is dispatched using the "saved/searches/{name}/dispatch" endpoint, this setting controls what user that search is dispatched as. Only meaningful for shared saved searches. Can be set to `owner` or `user`.
displayview	String	Defines the default UI view name (not label) in which to load the results. Accessibility is subject to the user having sufficient permissions.
durable.backfill_type	String	Specifies how the Splunk software backfills the lost search results of failed scheduled search jobs. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*. Valid values are `auto`, `time_interval`, and `time_whole`. `time_whole` - The Splunk software schedules a single backfill search job with a time range that spans the combined time ranges of all failed scheduled search jobs. The `time_whole` setting can be applied only to searches that are streaming, where the results are raw events without additional aggregation. `time_interval` - The Splunk software schedules multiple backfill search jobs, one for each failed scheduled search job. The backfill jobs have time ranges that match those of the failed jobs. The `time_interval` setting can be applied to both streaming and non-streaming searches. `auto` - The Splunk software decides the backfill type by checking whether the search is streaming or not. If the search is streaming, the Splunk software uses the `time_whole` backfill type. Otherwise, it uses the `time_interval` backfill type.
durable.lag_time	Number	Specifies the search time delay, in seconds, that a durable search uses to catch events that are ingested or indexed late. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.max_backfill_intervals	Number	Specifies the maximum number of cron intervals (previous scheduled search jobs) that the Splunk software can attempt to backfill for this search, when those jobs have incomplete events. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.track_time_type	String	Indicates that a scheduled search is durable and specifies how the search tracks events. A durable search is a search that tries to ensure the delivery of all results, even when the search process is slowed or stopped by runtime issues like rolling restarts, network bottlenecks, and even downed servers. Applies only to scheduled searches. A value of `_time` means the durable search tracks each event by its event timestamp , based on time information included in the event. A value of `_indextime` means the durable search tracks each event by its indexed timestamp. The search is not durable if this setting is unset or is set to `none`.
is_scheduled	Boolean	Whether this search is to be run on a schedule
is_visible	Boolean	Specifies whether this saved search should be listed in the visible saved search list. Defaults to 1.
max_concurrent	Number	The maximum number of concurrent instances of this search the scheduler is allowed to run. Defaults to 1.
next_scheduled_time	String	Read-only attribute. Value ignored on POST. There are some old clients who still send this value
qualifiedSearch	String	Read-only attribute. Value ignored on POST. The value is computed during runtime.

Name	Type	Description
realtime_schedule	Boolean	Defaults to 1. Controls the way the scheduler computes the next execution time of a scheduled search. If this value is set to 1, the scheduler bases its determination of the next scheduled search execution time on the current time. If this value is set to 0, the scheduler bases its determination of the next scheduled search on the last search execution time. This is called continuous scheduling. If set to 0, the scheduler never skips scheduled execution periods. However, the execution of the saved search might fall behind depending on the scheduler load. Use continuous scheduling whenever you enable the summary index option. If set to 1, the scheduler might skip some execution periods to make sure that the scheduler is executing the searches running over the most recent time range. The scheduler tries to execute searches that have realtime_schedule set to 1 before it executes searches that have continuous scheduling (realtime_schedule = 0).
request.ui_dispatch_app	String	Specifies a field used by Splunk Web to denote the app this search should be dispatched in.
request.ui_dispatch_view	String	Specifies a field used by Splunk Web to denote the view this search should be displayed in.
restart_on_searchpeer_add	Boolean	Specifies whether to restart a real-time search managed by the scheduler when a search peer becomes available for this saved search. Defaults to 1. Note: The peer can be a newly added peer or a peer down and now available.
run_n_times	Number	Runs this search exactly the specified number of times. Does not run the search again until the Splunk platform is restarted.
run_on_startup	Boolean	Indicates whether this search runs at startup. If it does not run on startup, it runs at the next scheduled time. Defaults to 0. Set to 1 for scheduled searches that populate lookup tables.
schedule_window	Number or `auto`	Time window (in minutes) during which the search has lower priority. Defaults to 0. The scheduler can give higher priority to more critical searches during this window. The window must be smaller than the search period. Set to `auto` to let the scheduler determine the optimal window value automatically. Requires the `edit_search_schedule_window` capability to override `auto`.
search	String	Required. The search to save.

Name	Type	Description
schedule_priority	See description	Raises the scheduling priority of the named search. Use one of the following options. default No scheduling priority increase. higher Scheduling priority is higher than other searches of the same scheduling tier. While there are four tiers of priority for scheduled searches, only the following search types are affected by this property. real-time scheduled (realtime_schedule=1). continuous scheduled (realtime_schedule=0). highest Scheduling priority is higher than other searches regardless of scheduling tier. However, real-time-scheduled searches with `priority = highest` always have priority over continuous scheduled searches with `priority = highest`. Requires the search owner to have the `edit_search_schedule_priority` capability in order to make non-default settings. Defaults to `default`. For more details, see `savedsearches.conf.spec`.
vsid	String	Defines the viewstate id associated with the UI view listed in 'displayview'. Must match up to a stanza in viewstates.conf.
workload_pool	String	Specifies the new workload pool where the existing running search will be placed.

Returned values

Name	Description
action.<action_name>	Indicates whether the `<action_name>` is enabled or disabled for a particular search. For more information about the alert action options see the `alert_actions.conf` file.
action.<action_name>.<parameter>	Overrides the setting defined for an action in the `alert_actions.conf` file with a new setting that is valid only for the search configuration to which it is applied.
action.email	Indicates the state of the email action.
action.email.auth_password	The password to use when authenticating with the SMTP server. Normally this value is set when editing the email settings, however you can set a clear text password here and it is encrypted on the next restart. Defaults to empty string.
action.email.auth_username	The username to use when authenticating with the SMTP server. If this is empty string, no authentication is attempted. Defaults to empty string. *Note:* Your SMTP server might reject unauthenticated emails.
action.email.bcc	BCC email address to use if action.email is enabled.
action.email.cc	CC email address to use if action.email is enabled.
action.email.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.email.format	Specify the format of text in the email. This value also applies to any attachments.< Valid values: (plain | html | raw | csv)
action.email.from	Email address from which the email action originates. Defaults to splunk@$LOCALHOST or whatever value is set in alert_actions.conf.

Name	Description
action.email.hostname	Sets the hostname used in the web link (url) sent in email actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) When this value is a simple hostname, the protocol and port which are configured within splunk are used to construct the base of the url. When this value begins with 'http://', it is used verbatim. NOTE: This means the correct port must be specified if it is not the default port for http or https. This is useful in cases when the Splunk server is not aware of how to construct a url that can be referenced externally, such as SSO environments, other proxies, or when the server hostname is not generally resolvable. Defaults to current hostname provided by the operating system, or if that fails "localhost". When set to empty, default behavior is used.
action.email.inline	Indicates whether the search results are contained in the body of the email. Results can be either inline or attached to an email. See action.email.sendresults.
action.email.mailserver	Set the address of the MTA server to be used to send the emails. Defaults to <LOCALHOST> (or whatever is set in alert_actions.conf).
action.email.maxresults	Sets the global maximum number of search results to send when email.action is enabled.
action.email.maxtime	Specifies the maximum amount of time the execution of an email action takes before the action is aborted.
action.email.pdfview	The name of the view to deliver if sendpdf is enabled
action.email.preprocess_results	Search string to preprocess results before emailing them. Defaults to empty string (no preprocessing). Usually the preprocessing consists of filtering out unwanted internal fields.
action.email.reportCIDFontList	Space-separated list. Specifies the set (and load order) of CID fonts for handling Simplified Chinese(gb), Traditional Chinese(cns), Japanese(jp), and Korean(kor) in Integrated PDF Rendering. If multiple fonts provide a glyph for a given character code, the glyph from the first font specified in the list is used. To skip loading any CID fonts, specify the empty string. Default value: "gb cns jp kor"
action.email.reportIncludeSplunkLogo	Indicates whether to include the Splunk logo with the report.
action.email.reportPaperOrientation	Specifies the paper orientation: portrait or landscape.
action.email.reportPaperSize	Specifies the paper size for PDFs. Defaults to letter. Valid values: (letter | legal | ledger | a2 | a3 | a4 | a5)
action.email.reportServerEnabled	Not supported.
action.email.reportServerURL	Not supported.
action.email.sendpdf	Indicates whether to create and send the results as a PDF.
action.email.sendresults	Indicates whether to attach the search results in the email. Results can be either attached or inline. See action.email.inline.
action.email.subject	Specifies an email subject. Defaults to SplunkAlert-<savedsearchname>.
action.email.to	List of recipient email addresses. Required if this search is scheduled and the email alert action is enabled.
action.email.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.email.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows <Integer>, int is the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p].
action.email.use_ssl	Indicates whether to use SSL when communicating with the SMTP server.
action.email.use_tls	Indicates whether to use TLS (transport layer security) when communicating with the SMTP server (starttls).

Name	Description
action.email.width_sort_columns	Indicates whether columns should be sorted from least wide to most wide, left to right. Only valid if format=text.
action.populate_lookup	Indicates the state of the populate lookup action.
action.populate_lookup.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.populate_lookup.dest	Lookup name of path of the lookup to populate.
action.populate_lookup.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.populate_lookup.maxresults	The maximum number of search results sent using alerts.
action.populate_lookup.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 5m. Valid values are: Integer[m|s|h|d]
action.populate_lookup.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.populate_lookup.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, then this specifies the number of scheduled periods. Defaults to 10p. If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p]
action.rss	Indicates the state of the RSS action.
action.rss.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.rss.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.rss.maxresults	Sets the maximum number of search results sent using alerts.
action.rss.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Valid values are Integer[m |s |h |d].
action.rss.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.rss.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
action.script	Indicates the state of the script for this action.
action.script.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.script.filename	File name of the script to call. Required if script action is enabled

Name	Description
action.script.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.script.maxresults	Sets the maximum number of search results sent using alerts.
action.script.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted.
action.script.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.script.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 600 (10 minutes). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
action.summary_index	Indicates the state of the summary index.
action.summary_index._name	Specifies the name of the summary index where the results of the scheduled search are saved. Defaults to "summary."
action.summary_index.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.summary_index.hostname	Sets the hostname used in the web link (url) sent in alert actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) See action.email.hostname for details.
action.summary_index.inline	Determines whether to execute the summary indexing action as part of the scheduled search. *Note:* This option is considered only if the summary index action is enabled and is always executed (in other words, if counttype = always).
action.summary_index.maxresults	Sets the maximum number of search results sent using alerts.
action.summary_index.maxtime	Sets the maximum amount of time the execution of an action takes before the action is aborted. Defaults to 5m. Valid values are: Integer[m|s|h|d]
action.summary_index.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.summary_index.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows Integer, specifies the number of scheduled periods. Defaults to 10p. If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are: Integer[p]
actions	Actions triggerd by this alert.
alert.digest_mode	Indicates if the alert actions are applied to the entire result set or to each individual result.
alert.expires	Sets the period of time to show the alert in the dashboard. Defaults to 24h. Use [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour. Valid values: [number][time-unit]

Name	Description
alert.severity	Valid values: (1 | 2 | 3 | 4 | 5 | 6) Sets the alert severity level. Valid values are: 1 DEBUG 2 INFO 3 WARN 4 ERROR 5 SEVERE 6 FATAL
alert.suppress	Indicates whether alert suppression is enabled for this schedules search.
alert.suppress.fields	Fields to use for suppression when doing per result alerting. Required if suppression is turned on and per result alerting is enabled.
alert.suppress.period	Specifies the suppresion period. Only valid if alert.supress is enabled. Uses [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
alert.track	Specifies whether to track the actions triggered by this scheduled search. auto - determine whether to track or not based on the tracking setting of each action, do not track scheduled searches that always trigger actions. true - force alert tracking. false - disable alert tracking for this search.
alert_comparator	One of the following strings: greater than, less than, equal to, rises by, drops by, rises by perc, drops by perc
alert_condition	A conditional search that is evaluated against the results of the saved search. Defaults to an empty string. Alerts are triggered if the specified search yields a non-empty search result list. *Note:* If you specify an alert_condition, do not set counttype, relation, or quantity.
alert_threshold	Valid values are: Integer[%] Specifies the value to compare (see alert_comparator) before triggering the alert actions. If expressed as a percentage, indicates value to use when alert_comparator is set to "rises by perc" or "drops by perc."
alert_type	What to base the alert on, overriden by alert_condition if it is specified. Valid values are: always, custom, number of events, number of hosts, number of sources.

Name	Description

allow_skew	`0 | <percentage> | <duration>`
	
	Allows the search scheduler to distribute scheduled searches randomly and more evenly over their specified search periods.
	
	CAUTION: This setting does not require adjusting in most use cases. Check with an admin before making any updates.
	
	When set to a non-zero value for searches with the following `cron_schedule` values, the search scheduler randomly skews the second, minute, and hour on which the search runs.
	
	CODE
	
	`* * * * *  Every minute.`
	`*/M * * * *  Every M minutes (M > 0).`
	`0 * * * *  Every hour.`
	`0 */H * * *  Every H hours (H > 0).`
	`0 0 * * *  Every day (at midnight).`
	
	When set to a non-zero value for a search that has any other `cron_schedule` setting, the search scheduler can randomly skew only the second on which the search runs.
	
	The amount of skew for a specific search remains constant between edits of the search.
	
	A value of `0` disallows skew. `0` is the default setting.
	
	Percentage
	
	`<int>` followed by `%` specifies the maximum amount of time to skew as a percentage of the scheduled search period.
	
	Duration
	
	`<int><unit>` specifies a maximum duration. The `<unit>` can be omitted only when the `<int>` is `0` (which disables skew).
	
	Valid duration units:
	
	• `m`
	• `min`
	• `minute`
	• `mins`
	• `minutes`
	• `h`
	• `hr`
	• `hour`
	• `hrs`
	• `hours`
	• `d`
	• `day`
	• `days`
	
	Examples
	
	CODE
	
	`100% (for an every-5-minute search) = 5 minutes maximum`
	`50% (for an every-minute search) = 30 seconds maximum`
	`5m = 5 minutes maximum`
	`1h = 1 hour maximum`

*args.**	Wildcard argument that accepts any saved search template argument, such as args.username=foobar when the search is search $username$.
auto_summarize	Indicates whether the scheduler should ensure that the data for this search is automatically summarized.
auto_summarize.command	A search template that constructs the auto summarization for this search. Caution: Advanced feature. Do not change unless you understand the architecture of auto summarization of saved searches.
auto_summarize.cron_schedule	Cron schedule that probes and generates the summaries for this saved search.
auto_summarize.dispatch.earliest_time	A time string that specifies the earliest time for summarizing this search. Can be a relative or absolute time.
auto_summarize.dispatch.latest_time	A time string that specifies the latest time for this saved search. Can be a relative or absolute time.
auto_summarize.dispatch.time_format	Time format used to specify the earliest and latest times.
auto_summarize.dispatch.ttl	Indicates the time to live (in seconds) for the artifacts of the summarization of the scheduled search. If the integer is followed by the letter 'p', the ttl is interpreted as a multiple of the scheduled search period.
auto_summarize.max_disabled_buckets	The maximum number of buckets with the suspended summarization before the summarization search is completely stopped, and the summarization of the search is suspended for auto_summarize.suspend_period.

Name	Description
auto_summarize.max_summary_ratio	The maximum ratio of summary_size/bucket_size, which specifies when to stop summarization and deem it unhelpful for a bucket. *Note:* The test is only performed if the summary size is larger than auto_summarize.max_summary_size.
auto_summarize.max_summary_size	The minimum summary size, in bytes, before testing whether the summarization is helpful.
auto_summarize.max_time	Maximum time (in seconds) that the summary search is allowed to run. *Note:* This is an approximate time. The summary search stops at clean bucket boundaries.
auto_summarize.suspend_period	Time specifier indicating when to suspend summarization of this search if the summarization is deemed unhelpful.
auto_summarize.timespan	The list of time ranges that each summarized chunk should span. This comprises the list of available granularity levels for which summaries would be available. For example a timechart over the last month whose granularity is at the day level should set this to 1d. If you need the same data summarized at the hour level for weekly charts, use: 1h,1d.
cron_schedule	The cron schedule to execute this search. For example: */5 * * * * causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: 00,20,40 * * * *, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of 03,23,43 * * * * runs the search every hour at hh:03, hh:23, hh:43. Splunk recommends that you schedule your searches so that they are staggered over time. This reduces system load. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes. Valid values: cron string
description	Description of this saved search. Defaults to empty string.
disabled	Indicates if this saved search is disabled.
*dispatch.**	* represents any custom dispatch field.
dispatch.buckets	The maximum nuber of timeline buckets.
dispatch.earliest_time	A time string that specifies the earliest time for this search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
dispatch.indexedRealtime	Indicates whether to used indexed-realtime mode when doing real-time searches.
dispatch.latest_time	A time string that specifies the latest time for the saved search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
dispatch.lookups	Indicates if lookups are enabled for this search.
dispatch.max_count	The maximum number of results before finalizing the search.
dispatch.max_time	Indicates the maximum amount of time (in seconds) before finalizing the search.
dispatch.reduce_freq	Specifies how frequently the MapReduce reduce phase runs on accumulated map values.
dispatch.rt_backfill	Indicates whether to back fill the real time window for this search. Parameter valid only if this is a real time search
dispatch.spawn_process	This parameter is deprecated and will be removed in a future release. Do not use this parameter. Indicates whether a new search process spawns when this saved search is executed.
dispatch.time_format	Time format string that defines the time format for specifying the earliest and latest time.
dispatch.ttl	Indicates the time to live (in seconds) for the artifacts of the scheduled search, if no actions are triggered. If an action is triggered, the action ttl is used. If multiple actions are triggered, the maximum ttl is applied to the artifacts. To set the action ttl, refer to `alert_actions.conf.spec`. If the integer is followed by the letter 'p', the ttl is interpreted as a multiple of the scheduled search period.
displayview	Defines the default UI view name (not label) in which to load the results. Accessibility is subject to the user having sufficient permissions.

Name	Description
durable.backfill_type	Specifies how the Splunk software backfills the lost search results of failed scheduled search jobs. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*. Valid values are `auto`, `time_interval`, and `time_whole`.
durable.lag_time	Specifies the search time delay, in seconds, that a durable search uses to catch events that are ingested or indexed late. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.max_backfill_intervals	Specifies the maximum number of cron intervals (previous scheduled search jobs) that the Splunk software can attempt to backfill for this search, when those jobs have incomplete events. Applies only to scheduled searches that have a valid setting other than `none` for *durable.track_time_type*.
durable.track_time_type	Indicates that a scheduled search is durable and specifies how the search tracks events. A value of `_time` means the durable search tracks each event by its event timestamp , based on time information included in the event. A value of `_indextime` means the durable search tracks each event by its indexed timestamp. The search is not durable if this setting is unset or is set to `none`.
is_scheduled	Indicates if this search is to be run on a schedule.
is_visible	Indicates if this saved search appears in the visible saved search list.
max_concurrent	The maximum number of concurrent instances of this search the scheduler is allowed to run.
next_scheduled_time	The time when the scheduler runs this search again.
qualifiedSearch	The exact search string that the scheduler would run.
realtime_schedule	Controls the way the scheduler computes the next execution time of a scheduled search. If this value is set to 1, the scheduler bases its determination of the next scheduled search execution time on the current time. If this value is set to 0, the scheduler bases its determination of the next scheduled search on the last search execution time. This is called continuous scheduling. If set to 0, the scheduler never skips scheduled execution periods. However, the execution of the saved search might fall behind depending on the scheduler load. Use continuous scheduling whenever you enable the summary index option. If set to 1, the scheduler might skip some execution periods to make sure that the scheduler is executing the searches running over the most recent time range. The scheduler tries to execute searches that have realtime_schedule set to 1 before it executes searches that have continuous scheduling (realtime_schedule = 0).
request.ui_dispatch_app	A field used by Splunk Web to denote the app this search should be dispatched in.
request.ui_dispatch_view	Specifies a field used by Splunk Web to denote the view this search should be displayed in.
restart_on_searchpeer_add	Indicates whether to restart a real-time search managed by the scheduler when a search peer becomes available for this saved search. *Note:* The peer can be a newly added peer or a peer down and now available.
run_on_startup	Indicates whether this search runs on startup. If it does not run on startup, it runs at the next scheduled time. Splunk recommends that you set run_on_startup to true for scheduled searches that populate lookup tables.
schedule_window	Time window (in minutes) during which the search has lower priority. The scheduler can give higher priority to more critical searches during this window. The window must be smaller than the search period. If set to `auto`, the scheduler prioritizes searches automatically.
search	Search expression to filter the response. The response matches field values against the search expression. For example: search=foo matches any object that has "foo" as a substring in a field. search=field_name%3Dfield_value restricts the match to a single field. URI-encoding is required in this example.
vsid	The viewstate id associated with the UI view listed in 'displayview'. Matches to a stanza in viewstates.conf.

Example request and response

CODE

```
curl -k -u admin:chang2me https://fool01:8092/services/saved/searches/test_durable  -d durable.track_time_type=_time -d
durable.max_backfill_intervals=100  -d durable.lag_time=30 -d durable.backfill_type=time_interval
```

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>savedsearch</title>
```

```
  <id>https://fool01:8092/services/saved/searches</id>
  <updated>2021-04-29T09:58:12-07:00</updated>
  <generator build="84cbec3d51a6" version="8.2.2105"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/saved/searches/_new" rel="create"/>
  <link href="/services/saved/searches/_reload" rel="_reload"/>
  <link href="/services/saved/searches/_acl" rel="_acl"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>test_durable</title>
    <id>https://fool01:8092/servicesNS/admin/search/saved/searches/test_durable</id>
    <updated>2021-04-29T09:58:12-07:00</updated>
    <link href="/servicesNS/admin/search/saved/searches/test_durable" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/saved/searches/test_durable" rel="list"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable" rel="edit"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable" rel="remove"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/move" rel="move"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/disable" rel="disable"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/dispatch" rel="dispatch"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/embed" rel="embed"/>
    <link href="/servicesNS/admin/search/saved/searches/test_durable/history" rel="history"/>
    <content type="text/xml">
      <s:dict>
        <!-- action settings elided -->
        <s:key name="actions"></s:key>
        <s:key name="alert.digest_mode">1</s:key>
        <s:key name="alert.expires">24h</s:key>
        <s:key name="alert.managedBy"></s:key>
        <s:key name="alert.severity">3</s:key>
        <s:key name="alert.suppress"></s:key>
        <s:key name="alert.suppress.fields"></s:key>
        <s:key name="alert.suppress.group_name"></s:key>
        <s:key name="alert.suppress.period"></s:key>
        <s:key name="alert.track">0</s:key>
        <s:key name="alert_comparator"></s:key>
        <s:key name="alert_condition"></s:key>
        <s:key name="alert_threshold"></s:key>
        <s:key name="alert_type">always</s:key>
        <s:key name="allow_skew">0</s:key>
        <s:key name="auto_summarize">0</s:key>
        <s:key name="auto_summarize.command"><![CDATA[| summarize override=partial timespan=$auto_summarize.timespan$
max_summary_size=$auto_summarize.max_summary_size$ max_summary_ratio=$auto_summarize.max_summary_ratio$
max_disabled_buckets=$auto_summarize.max_disabled_buckets$ max_time=$auto_summarize.max_time$ [ $search$ ]]]></s:key>
        <s:key name="auto_summarize.cron_schedule">*/10 * * * *</s:key>
        <s:key name="auto_summarize.dispatch.earliest_time"></s:key>
        <s:key name="auto_summarize.dispatch.latest_time"></s:key>
        <s:key name="auto_summarize.dispatch.time_format">%FT%T.%Q%:z</s:key>
        <s:key name="auto_summarize.dispatch.ttl">60</s:key>
        <s:key name="auto_summarize.max_concurrent">1</s:key>
        <s:key name="auto_summarize.max_disabled_buckets">2</s:key>
        <s:key name="auto_summarize.max_summary_ratio">0.1</s:key>
        <s:key name="auto_summarize.max_summary_size">52428800</s:key>
        <s:key name="auto_summarize.max_time">3600</s:key>
        <s:key name="auto_summarize.suspend_period">24h</s:key>
        <s:key name="auto_summarize.timespan"></s:key>
        <s:key name="auto_summarize.workload_pool"></s:key>
        <s:key name="cron_schedule">*/3 * * * *</s:key>
        <s:key name="defer_scheduled_searchable_idxc">0</s:key>
        <s:key name="description">This test job is a durable saved search</s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="dispatch.allow_partial_results">1</s:key>
        <s:key name="dispatch.auto_cancel">0</s:key>
        <s:key name="dispatch.auto_pause">0</s:key>
        <s:key name="dispatch.buckets">0</s:key>
        <s:key name="dispatch.earliest_time">-24h@h</s:key>
        <s:key name="dispatch.index_earliest"></s:key>
        <s:key name="dispatch.index_latest"></s:key>
        <s:key name="dispatch.indexedRealtime"></s:key>
        <s:key name="dispatch.indexedRealtimeMinSpan"></s:key>
        <s:key name="dispatch.indexedRealtimeOffset"></s:key>
        <s:key name="dispatch.latest_time">now</s:key>
        <s:key name="dispatch.lookups">1</s:key>
        <s:key name="dispatch.max_count">500000</s:key>
        <s:key name="dispatch.max_time">0</s:key>
        <s:key name="dispatch.reduce_freq">10</s:key>
        <s:key name="dispatch.rt_backfill">0</s:key>
        <s:key name="dispatch.rt_maximum_span"></s:key>
        <s:key name="dispatch.sample_ratio">1</s:key>
        <s:key name="dispatch.spawn_process">1</s:key>
        <s:key name="dispatch.time_format">%FT%T.%Q%:z</s:key>
        <s:key name="dispatch.ttl">2p</s:key>
        <s:key name="dispatchAs">owner</s:key>
```

```
<!-- display settings elided -->
<s:key name="displayview"></s:key>
<s:key name="durable.backfill_type">time_interval</s:key>
<s:key name="durable.lag_time">30</s:key>
<s:key name="durable.max_backfill_intervals">100</s:key>
<s:key name="durable.track_time_type">_time</s:key>
<s:key name="eai:acl">
  <s:dict>
    <s:key name="app">search</s:key>
    <s:key name="can_change_perms">1</s:key>
    <s:key name="can_list">1</s:key>
    <s:key name="can_share_app">1</s:key>
    <s:key name="can_share_global">1</s:key>
    <s:key name="can_share_user">1</s:key>
    <s:key name="can_write">1</s:key>
    <s:key name="modifiable">1</s:key>
    <s:key name="owner">admin</s:key>
    <s:key name="perms"/>
    <s:key name="removable">1</s:key>
    <s:key name="sharing">user</s:key>
  </s:dict>
</s:key>
<s:key name="eai:attributes">
  <s:dict>
    <s:key name="optionalFields">
      <s:list>
        <!-- action settings elided -->
        <s:item>actions</s:item>
        <s:item>alert.digest_mode</s:item>
        <s:item>alert.expires</s:item>
        <s:item>alert.managedBy</s:item>
        <s:item>alert.severity</s:item>
        <s:item>alert.suppress</s:item>
        <s:item>alert.suppress.fields</s:item>
        <s:item>alert.suppress.group_name</s:item>
        <s:item>alert.suppress.period</s:item>
        <s:item>alert.track</s:item>
        <s:item>alert_comparator</s:item>
        <s:item>alert_condition</s:item>
        <s:item>alert_threshold</s:item>
        <s:item>alert_type</s:item>
        <s:item>allow_skew</s:item>
        <s:item>auto_summarize</s:item>
        <s:item>auto_summarize.command</s:item>
        <s:item>auto_summarize.cron_schedule</s:item>
        <s:item>auto_summarize.dispatch.earliest_time</s:item>
        <s:item>auto_summarize.dispatch.latest_time</s:item>
        <s:item>auto_summarize.dispatch.time_format</s:item>
        <s:item>auto_summarize.dispatch.ttl</s:item>
        <s:item>auto_summarize.max_concurrent</s:item>
        <s:item>auto_summarize.max_disabled_buckets</s:item>
        <s:item>auto_summarize.max_summary_ratio</s:item>
        <s:item>auto_summarize.max_summary_size</s:item>
        <s:item>auto_summarize.max_time</s:item>
        <s:item>auto_summarize.suspend_period</s:item>
        <s:item>auto_summarize.timespan</s:item>
        <s:item>auto_summarize.workload_pool</s:item>
        <s:item>cron_schedule</s:item>
        <s:item>defer_scheduled_searchable_idxc</s:item>
        <s:item>description</s:item>
        <s:item>disabled</s:item>
        <s:item>dispatch.allow_partial_results</s:item>
        <s:item>dispatch.auto_cancel</s:item>
        <s:item>dispatch.auto_pause</s:item>
        <s:item>dispatch.buckets</s:item>
        <s:item>dispatch.earliest_time</s:item>
        <s:item>dispatch.index_earliest</s:item>
        <s:item>dispatch.index_latest</s:item>
        <s:item>dispatch.indexedRealtime</s:item>
        <s:item>dispatch.indexedRealtimeMinSpan</s:item>
        <s:item>dispatch.indexedRealtimeOffset</s:item>
        <s:item>dispatch.latest_time</s:item>
        <s:item>dispatch.lookups</s:item>
        <s:item>dispatch.max_count</s:item>
        <s:item>dispatch.max_time</s:item>
        <s:item>dispatch.reduce_freq</s:item>
        <s:item>dispatch.rt_backfill</s:item>
        <s:item>dispatch.rt_maximum_span</s:item>
        <s:item>dispatch.sample_ratio</s:item>
        <s:item>dispatch.spawn_process</s:item>
        <s:item>dispatch.time_format</s:item>
        <s:item>dispatch.ttl</s:item>
        <s:item>dispatchAs</s:item>
        <!-- display settings elided -->
        <s:item>displayview</s:item>
        <s:item>durable.backfill_type</s:item>
        <s:item>durable.lag_time</s:item>
        <s:item>durable.max_backfill_intervals</s:item>
        <s:item>durable.track_time_type</s:item>
        <s:item>estimatedResultCount</s:item>
        <s:item>federated.provider</s:item>
```

```
            <s:item>hint</s:item>
            <s:item>is_scheduled</s:item>
            <s:item>is_visible</s:item>
            <s:item>max_concurrent</s:item>
            <s:item>next_scheduled_time</s:item>
            <s:item>numFields</s:item>
            <s:item>qualifiedSearch</s:item>
            <s:item>realtime_schedule</s:item>
            <s:item>request.ui_dispatch_app</s:item>
            <s:item>request.ui_dispatch_view</s:item>
            <s:item>restart_on_searchpeer_add</s:item>
            <s:item>run_n_times</s:item>
            <s:item>run_on_startup</s:item>
            <s:item>schedule_as</s:item>
            <s:item>schedule_priority</s:item>
            <s:item>schedule_window</s:item>
            <s:item>search</s:item>
            <s:item>skip_scheduled_realtime_idxc</s:item>
            <s:item>vsid</s:item>
            <s:item>workload_pool</s:item>
          </s:list>
        </s:key>
        <s:key name="requiredFields">
          <s:list/>
        </s:key>
        <s:key name="wildcardFields">
          <s:list>
            <s:item>action\..*</s:item>
            <s:item>args\..*</s:item>
            <s:item>dispatch\..*</s:item>
            <s:item>display\.statistics\.format\..*</s:item>
            <s:item>display\.visualizations\.custom\..*</s:item>
            <s:item>durable\..*</s:item>
          </s:list>
        </s:key>
      </s:dict>
    </s:key>
    <s:key name="embed.enabled">0</s:key>
    <s:key name="federated.provider"></s:key>
    <s:key name="is_scheduled">0</s:key>
    <s:key name="is_visible">1</s:key>
    <s:key name="max_concurrent">1</s:key>
    <s:key name="next_scheduled_time"></s:key>
    <s:key name="qualifiedSearch">search search index=_internal | stats count by host</s:key>
    <s:key name="realtime_schedule">1</s:key>
    <s:key name="request.ui_dispatch_app"></s:key>
    <s:key name="request.ui_dispatch_view"></s:key>
    <s:key name="restart_on_searchpeer_add">1</s:key>
    <s:key name="run_n_times">0</s:key>
    <s:key name="run_on_startup">0</s:key>
    <s:key name="schedule_as">auto</s:key>
    <s:key name="schedule_priority">default</s:key>
    <s:key name="schedule_window">0</s:key>
    <s:key name="search">search index=_internal | stats count by host</s:key>
    <s:key name="skip_scheduled_realtime_idxc">0</s:key>
    <s:key name="vsid"></s:key>
    <s:key name="workload_pool"></s:key>
  </s:dict>
 </content>
 </entry>
</feed>
```


saved/searches/{name}/acknowledge

JSON

`https://<host>:<mPort>/services/saved/searches/{name}/acknowledge`

Acknowledge the {name} saved search alert suppression.

POST

Acknowledge the {name} saved search alert suppression and resume alerting.

Request parameters

Name	Type	Default	Description

Name	Type	Default	Description
key	String		The suppression key used in field-based suppression. For example, in host-based suppression, with data from 5 hosts, the key is the host, as each host could have different suppression expiration times.

Returned values

None

Example request and response

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/saved/searches/MyAlert/acknowledge -X POST
```

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>savedsearch</title>
  <id>https://localhost:8089/servicesNS/admin/search/saved/searches</id>
  <updated>2011-07-26T18:31:07-04:00</updated>
  <generator version="104601"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/admin/search/saved/searches/_new" rel="create"/>
  <link href="/servicesNS/admin/search/saved/searches/_reload" rel="_reload"/>
  <opensearch:totalResults>0</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
</feed>
```

saved/searches/{name}/dispatch

JSON

```
https://<host>:<mPort>/services/saved/searches/{name}/dispatch
```

Dispatch the `{name}` saved search.

POST

Dispatch the `{name}` saved search.

Request parameters

Name	Type	Default	Description
*args.**			Arg values to create a saved search is the saved search if a template search. For example, specify arg.index_name to create the following search: search index=$args.index_name$ | ...
dispatchAs	String	"owner" | "user"	Indicate the user context, quota, and access rights for the saved search. The saved search runs according to the context indicated.
*dispatch.**	String		Any dispatch.* field of the search that needs to be overridden when running the summary search.
dispatch.adhoc_search_level	String		Use one of the following search modes. CODE `[ verbose | fast | smart ]`
dispatch.now	Boolean		Dispatch the search as if the specified time for this parameter was the current time.
force_dispatch	Boolean		Indicates whether to start a new search even if another instance of this search is already running.

Name	Type	Default	Description
now	String		[Deprecated] Use *dispatch.now*.

replay_speed	Number greater than 0		Indicate a real-time search replay speed factor. For example, `1` indicates normal speed. `0.5` indicates half of normal speed, and `2` indicates twice as fast as normal.
			
			`earliest_time` and `latest_time` arguments must indicate a real-time time range to use replay options.
			
			Use *replay_speed* with *replay_et* and *replay_lt* relative times to indicate a speed and time range for the replay. For example,
			
			CODE
			
			`replay_speed = 10`
			`replay_et = -d@d`
			`replay_lt = -@d`
			
			specifies a replay at 10x speed, as if the "wall clock" time starts yesterday at midnight and ends when it reaches today at midnight.
			
			For more information about using relative time modifiers, see Search time modifiers in the *Search reference*.

replay_et	Time modifier string		Relative "wall clock" start time for the replay.
replay_lt	Time modifier string.		Relative end time for the replay clock. The replay stops when clock time reaches this time.
trigger_actions	Boolean		Indicates whether to trigger alert actions.

Returned values

None

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/saved/searches/MySavedSearch/dispatch -d trigger_actions=1
```

XML Response

XML

```
<?xml version='1.0' encoding='UTF-8'?>
<response><sid>admin__admin__search__MySavedSearch_at_1311797437_d831d980832e3e89</sid></response>
```

saved/searches/{name}/history

JSON

```
https://<host>:<mPort>/services/saved/searches/{name}/history
```

List available search jobs created from the `{name}` saved search.

GET

List available search jobs created from the `{name}` saved search.

Request parameters

Name	Description

Name	Description
savedsearch	String triplet consisting of `user:app:search_name`. The triplet constitutes a unique identifier for accessing saved search history. Passing in this parameter can help you work around saved search access limitations in search head clustered deployments. As an example, the following parameter triplet represents an `admin` user, the `search` app context, and a search named `Splunk errors last 24 hours`. CODE `savedsearch=admin:search:Splunk%20errors%20last%2024%20hours`

Returned values

Name	Description
durableTrackTime	The durable cursor timestamp for the search job, expressed in UNIX Epoch time notation (elapsed time since 1/1/1970). If `durableTrackType=_indextime`, this timestamp is associated with the indexed timestamp of the events returned by the job. If `durableTrackType=_time`, this timestamp is associated with the event timestamp of the events returned by the job.
durableTrackType	Indicates that a scheduled search is durable and specifies how the search tracks events. A value of `_time` means the durable search tracks each event by its event timestamp , based on time information included in the event. A value of `_indextime` means the durable search tracks each event by its indexed timestamp. The search is not durable if this setting is unset or is set to `none`.
earliest_time	The earliest time a search job is configured to start.
isDone	Indicates if the search has completed.
isFinalized	Indicates if the search was finalized (stopped before completion).
isRealTimeSearch	Indicates if the search is a real time search.
isSaved	Indicates if the search is saved indefinitely.
isScheduled	Indicates if the search is a scheduled search.
isZombie	Indicates if the process running the search is dead, but with the search not finished.
latest_time	The latest time a search job is configured to start.
listDefaultActionArgs	List default values of actions.*, even though some of the actions may not be specified in the saved search.
ttl	The time to live, or time before the search job expires after it completes.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://fool01:8092/services/saved/searches/summary_durable/history
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>summary_durable</title>
  <id>https://fool01:8092/services/saved/searches</id>
  <updated>2021-04-29T10:01:20-07:00</updated>
  <generator build="84cbec3d51a6" version="8.2.2105"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/saved/searches/_acl" rel="_acl"/>
  <opensearch:totalResults>2</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>scheduler__admin__search__RMD50dbc462560ef18a2_at_1619715420_1</title>
    <id>https://fool01:8092/servicesNS/nobody/search/search/jobs/scheduler__admin__search__RMD50dbc462560ef18a2_at_1619715420_1</id>
    <updated>2021-04-29T09:57:44-07:00</updated>
    <link href="/servicesNS/nobody/search/search/jobs/scheduler__admin__search__RMD50dbc462560ef18a2_at_1619715420_1" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <published>2021-04-29T09:57:17-07:00</published>
    <content type="text/xml">
      <s:dict>
        <s:key name="durableTrackTime">1619715420.000000000</s:key>
        <s:key name="durableTrackType">_time</s:key>
        <s:key name="eai:acl">
          <s:dict>
```

```
          <s:key name="app">search</s:key>
          <s:key name="can_change_perms">1</s:key>
          <s:key name="can_list">1</s:key>
          <s:key name="can_share_app">1</s:key>
          <s:key name="can_share_global">1</s:key>
          <s:key name="can_share_user">0</s:key>
          <s:key name="can_write">1</s:key>
          <s:key name="modifiable">1</s:key>
          <s:key name="owner">admin</s:key>
          <s:key name="perms">
            <s:dict>
              <s:key name="read">
                <s:list>
                  <s:item>admin</s:item>
                </s:list>
              </s:key>
              <s:key name="write">
                <s:list>
                  <s:item>admin</s:item>
                </s:list>
              </s:key>
            </s:dict>
          </s:key>
          <s:key name="removable">0</s:key>
          <s:key name="sharing">system</s:key>
        </s:dict>
      </s:key>
      <s:key name="isDone">1</s:key>
      <s:key name="isFinalized">0</s:key>
      <s:key name="isRealTimeSearch">0</s:key>
      <s:key name="isSaved">0</s:key>
      <s:key name="isScheduled">1</s:key>
      <s:key name="isZombie">0</s:key>
      <s:key name="start">1619715437</s:key>
      <s:key name="ttl">118</s:key>
    </s:dict>
  </content>
</entry>
<entry>
  <title>scheduler__admin__search__RMD50dbc462560ef18a2_at_1619715600_3</title>
  <id>https://fool01:8092/servicesNS/nobody/search/search/jobs/scheduler__admin__search__RMD50dbc462560ef18a2_at_1619715600_3</id>
  <updated>2021-04-29T10:00:14-07:00</updated>
  <link href="/servicesNS/nobody/search/search/jobs/scheduler__admin__search__RMD50dbc462560ef18a2_at_1619715600_3" rel="alternate"/>
  <author>
    <name>admin</name>
  </author>
  <published>2021-04-29T10:00:00-07:00</published>
  <content type="text/xml">
    <s:dict>
      <s:key name="durableTrackTime">1619715600.000000000</s:key>
      <s:key name="durableTrackType">_time</s:key>
      <s:key name="eai:acl">
        <s:dict>
          <s:key name="app">search</s:key>
          <s:key name="can_change_perms">1</s:key>
          <s:key name="can_list">1</s:key>
          <s:key name="can_share_app">1</s:key>
          <s:key name="can_share_global">1</s:key>
          <s:key name="can_share_user">0</s:key>
          <s:key name="can_write">1</s:key>
          <s:key name="modifiable">1</s:key>
          <s:key name="owner">admin</s:key>
          <s:key name="perms">
            <s:dict>
              <s:key name="read">
                <s:list>
                  <s:item>admin</s:item>
                </s:list>
              </s:key>
              <s:key name="write">
                <s:list>
                  <s:item>admin</s:item>
                </s:list>
              </s:key>
            </s:dict>
          </s:key>
          <s:key name="removable">0</s:key>
          <s:key name="sharing">system</s:key>
        </s:dict>
      </s:key>
      <s:key name="isDone">1</s:key>
      <s:key name="isFinalized">0</s:key>
      <s:key name="isRealTimeSearch">0</s:key>
      <s:key name="isSaved">0</s:key>
      <s:key name="isScheduled">1</s:key>
      <s:key name="isZombie">0</s:key>
      <s:key name="start">1619715600</s:key>
      <s:key name="ttl">281</s:key>
    </s:dict>
  </content>
```

```
  </entry>
</feed>
```

saved/searches/{name}/reschedule

JSON

```
https://<host>:<mPort>/services/saved/searches/{name}/reschedule
```

Set {name} scheduled saved search to start at a specific time and then run on its schedule thereafter.

POST

Define a new start time for a scheduled saved search.

Usage details

If no schedule_time argument is specified, the Splunk software runs the search as soon as possible according to its saved search definition. If you restart your Splunk platform implementation, all schedule_time values for searches are removed.

Request parameters

Name	Type	Default	Description
schedule_time	Timestamp		The next time to run the search. The timestamp can be in one of three formats: ISO8601 format (adjusted for UTC time), UNIX time format, or relative time format.

Returned values

None

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/saved/searches/Purchased%20products%2C%20last%2024%20hours/reschedule -d
schedule_time=schedule_time=2018-08-15T14:11:01-08:00
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:s="http://dev.splunk.com/ns/rest"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>savedsearch</title>
  <id>https://localhost:8089/services/saved/searches</id>
  <updated>2018-08-15T14:11:01-08:00</updated>
  <generator build="131547" version="5.0"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/saved/searches/_new" rel="create"/>
  <link href="/services/saved/searches/_reload" rel="_reload"/>
  <opensearch:totalResults>0</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
</feed>
```

saved/searches/{name}/scheduled_times

JSON

```
https://<host>:<mPort>/services/saved/searches/{name}/scheduled_times
```

Get the {name} saved search scheduled time.

GET

Access {name} saved search scheduled time.

Request parameters

Name	Type	Default	Description
earliest_time required	String		Absolute or relative earliest time
latest_time required	String		Absolute or relative latest time

Returned values

Name	Description
action.email	Indicates the state of the email action.
action.email.auth_password	The password to use when authenticating with the SMTP server. Normally this value is set when editing the email settings, however you can set a clear text password here that is encrypted on the next platform restart. Defaults to empty string.
action.email.auth_username	The username to use when authenticating with the SMTP server. If this is empty string, no authentication is attempted. Defaults to empty string. *Note:* Your SMTP server might reject unauthenticated emails.
action.email.pdfview	The name of the view to deliver if sendpdf is enabled.
action.email.subject	Specifies an email subject. Defaults to SplunkAlert-<savedsearchname>.
action.email.to	List of recipient email addresses. Required if this search is scheduled and the email alert action is enabled.
action.summary_index	The state of the summary index action.
action.summary_index._name	Specifies the name of the summary index where the results of the scheduled search are saved. Defaults to "summary."
actions	Actions triggered by this alert.
alert.digest_mode	Indicates if alert actions are applied to the entire result set or to each individual result.
alert.expires	Sets the period of time to show the alert in the dashboard. Defaults to 24h. Uses [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
alert.severity	Valid values: (1 | 2 | 3 | 4 | 5 | 6) Sets the alert severity level. Valid values are: 1 DEBUG 2 INFO 3 WARN 4 ERROR 5 SEVERE 6 FATAL
alert.suppress	Indicates whether alert suppression is enabled for this schedules search.
alert.suppress.fields	Fields to use for suppression when doing per result alerting. Required if suppression is turned on and per result alerting is enabled.
alert.suppress.period	Specifies the suppression period. Only valid if `alert.supress` is enabled. Use [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
alert.track	Specifies whether to track the actions triggered by this scheduled search. auto - determine whether to track or not based on the tracking setting of each action, do not track scheduled searches that always trigger actions. true - force alert tracking. false - disable alert tracking for this search.
alert_comparator	Valid values are: Integer[%] Specifies the value to compare (see alert_comparator) before triggering the alert actions. If expressed as a percentage, indicates value to use when alert_comparator is set to "rises by perc" or "drops by perc."
alert_condition	A conditional search that is evaluated against the results of the saved search. Defaults to an empty string. Alerts are triggered if the specified search yields a non-empty search result list. *Note:* If you specify an alert_condition, do not set counttype, relation, or quantity.

Name	Description
alert_threshold	Valid values are: Integer[%] Specifies the value to compare (see alert_comparator) before triggering the alert actions. If expressed as a percentage, indicates value to use when alert_comparator is set to "rises by perc" or "drops by perc."
alert_type	What to base the alert on, overridden by alert_condition if it is specified. Valid values are: always, custom, number of events, number of hosts, number of sources.
cron_schedule	The cron schedule to execute this search. For example: */5 * * * * causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: 00,20,40 * * * *, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of 03,23,43 * * * * runs the search every hour at hh:03, hh:23, hh:43. Splunk recommends that you schedule your searches so that they are staggered over time. This reduces system load. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes. Valid values: cron string
description	Description of the saved search.
disabled	Indicates if this saved search is disabled.
dispatch.buckets	The maximum number of timeline buckets.
dispatch.earliest_time	A time string that specifies the earliest time for this search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
dispatch.latest_time	A time string that specifies the latest time for this saved search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
dispatch.lookups	Indicates if lookups are enabled for this search.
dispatch.max_count	The maximum number of results before finalizing the search.
dispatch.max_time	Indicates the maximum amount of time (in seconds) before finalizing the search
earliest_time	For scheduled searches display all the scheduled times starting from this time.
is_scheduled	Indicates if this search is to be run on a schedule.
is_visible	Indicates if this saved search appears in the visible saved search list.
latest_time	A time string that specifies the latest time for this saved search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
listDefaultActionArgs	List default values of actions.*, even though some of the actions may not be specified in the saved search.
max_concurrent	The maximum number of concurrent instances of this search the scheduler is allowed to run.
next_scheduled_time	The time when the scheduler runs this search again.
qualifiedSearch	The exact search command for this saved search.
realtime_schedule	Controls the way the scheduler computes the next execution time of a scheduled search. If this value is set to 1, the scheduler bases its determination of the next scheduled search execution time on the current time. If this value is set to 0, the scheduler bases its determination of the next scheduled search on the last search execution time. This is called continuous scheduling. If set to 0, the scheduler never skips scheduled execution periods. However, the execution of the saved search might fall behind depending on the scheduler load. Use continuous scheduling whenever you enable the summary index option. If set to 1, the scheduler might skip some execution periods to make sure that the scheduler is executing the searches running over the most recent time range. The scheduler tries to execute searches that have realtime_schedule set to 1 before it executes searches that have continuous scheduling (realtime_schedule = 0).
request.ui_dispatch_app	A field used by Splunk Web to denote the app this search should be dispatched in.
request.ui_dispatch_view	A field used by Splunk Web to denote the app this search should be dispatched in.

Name	Description
restart_on_searchpeer_add	Indicates whether to restart a real-time search managed by the scheduler when a search peer becomes available for this saved search. *Note:* The peer can be a newly added peer or a peer down and now available.
run_on_startup	Indicates whether this search runs on startup. If it does not run on startup, it runs at the next scheduled time. Splunk recommends that you set run_on_startup to true for scheduled searches that populate lookup tables.
scheduled_times	The times when the scheduler runs the search.
search	Search expression to filter the response. The response matches field values against the search expression. For example: search=foo matches any object that has "foo" as a substring in a field. search=field_name%3Dfield_value restricts the match to a single field. URI-encoding is required in this example.
vsid	The viewstate id associated with the Splunk Web view listed in 'displayview'. Matches to a stanza in viewstates.conf.

Application usage

Specify a time range for the data returned using earliest_time and latest_time parameters.

Example request and response
XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/saved/searches/_ScheduledView__dashboard_live/scheduled_times --get -d earliest_time=-5h -d
latest_time=-3h
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>savedsearch</title>
  <id>https://localhost:8089/services/saved/searches</id>
  <updated>2011-12-02T11:12:55-08:00</updated>
  <generator version="108769"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/saved/searches/_new" rel="create"/>
  <link href="/services/saved/searches/_reload" rel="_reload"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>_ScheduledView__dashboard_live</title>
    <id>https://localhost:8089/servicesNS/admin/search/saved/searches/_ScheduledView__dashboard_live</id>
    <updated>2011-12-02T11:12:55-08:00</updated>
    <link href="/servicesNS/admin/search/saved/searches/_ScheduledView__dashboard_live" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <!-- opensearch nodes elided for brevity. -->
    <content type="text/xml">
      <s:dict>
        <s:key name="action.email">1</s:key>
        <s:key name="action.email.auth_password">$1$o2rN8S6m+0YB</s:key>
        <s:key name="action.email.auth_username">myusername</s:key>
        . . . elided . . .
        <s:key name="action.email.pdfview">dashboard_live</s:key>
        . . . elided . . .
        <s:key name="action.email.subject">Splunk Alert: $name$</s:key>
        <s:key name="action.email.to">myusername@example.com</s:key>
        . . . elided . . .
         <s:key name="action.summary_index">0</s:key>
        <s:key name="action.summary_index._name">summary</s:key>
        . . . elided . . .
        <s:key name="actions">email</s:key>
        <s:key name="alert.digest_mode">1</s:key>
        <s:key name="alert.expires">24h</s:key>
        <s:key name="alert.severity">3</s:key>
        <s:key name="alert.suppress"></s:key>
        <s:key name="alert.suppress.fields"></s:key>
        <s:key name="alert.suppress.period"></s:key>
        <s:key name="alert.track">auto</s:key>
        <s:key name="alert_comparator"></s:key>
        <s:key name="alert_condition"></s:key>
        <s:key name="alert_threshold"></s:key>
```

```
        <s:key name="alert_type">always</s:key>
        <s:key name="cron_schedule">*/30 * * * *</s:key>
        <s:key name="description">scheduled search for view name=dashboard_live</s:key>
        <s:key name="disabled">0</s:key>
        <s:key name="dispatch.buckets">0</s:key>
        <s:key name="dispatch.earliest_time">1</s:key>
        <s:key name="dispatch.latest_time">2</s:key>
        <s:key name="dispatch.lookups">1</s:key>
        <s:key name="dispatch.max_count">500000</s:key>
        <s:key name="dispatch.max_time">0</s:key>
        . . . elided . . .
        <!-- eai:acl elided -->
        <s:key name="is_scheduled">1</s:key>
        <s:key name="is_visible">0</s:key>
        <s:key name="max_concurrent">1</s:key>
        <s:key name="next_scheduled_time">2011-12-02 11:30:00 PST</s:key>
        <s:key name="qualifiedSearch"> noop</s:key>
        <s:key name="realtime_schedule">1</s:key>
        <s:key name="request.ui_dispatch_app"></s:key>
        <s:key name="request.ui_dispatch_view"></s:key>
        <s:key name="restart_on_searchpeer_add">1</s:key>
        <s:key name="run_on_startup">0</s:key>
        <s:key name="scheduled_times"><s:list><s:item>1322836200</s:item><s:item>1322838000</s:item><s:item>1322839800</s:item>
<s:item>1322841600</s:item></s:list></s:key>
        <s:key name="search">| noop</s:key>
        <s:key name="vsid"></s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

saved/searches/{name}/suppress

JSON

```
https://<host>:<mPort>/services/saved/searches/{name}/suppress
```

Get the {name} saved search alert suppression state.

GET

Get the {name} saved search alert suppression state.

Request parameters

Name	Type	Default	Description
expiration	String		Indicates the time the suppression period expires.
key			

Returned values

Name	Description
earliest_time	For scheduled searches display all the scheduled times starting from this time.
expiration	Sets the period of time to show the alert in the dashboard. Defaults to 24h. Uses [number][time-unit] to specify a time. For example: 60 = 60 seconds, 1m = 1 minute, 1h = 60 minutes = 1 hour.
latest_time	A time string that specifies the latest time for this saved search. Can be a relative or absolute time. If this value is an absolute time, use the dispatch.time_format to format the value.
listDefaultActionArgs	List default values of actions.*, even though some of the actions may not be specified in the saved search.
suppressed	Indicates if alert suppression is enabled for this search.
suppressionKey	A combination of all the values of the suppression fields (or the combinations MD5), if fields were specified.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/saved/searches/MySavedSearch/suppress
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>savedsearch</title>
  <id>https://localhost:8089/servicesNS/admin/search/saved/searches</id>
  <updated>2011-07-26T18:22:51-04:00</updated>
  <generator version="104601"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/admin/search/saved/searches/_new" rel="create"/>
  <link href="/servicesNS/admin/search/saved/searches/_reload" rel="_reload"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>MySavedSearch</title>
    <id>https://localhost:8089/servicesNS/admin/search/saved/searches/MySavedSearch</id>
    <updated>2011-07-26T18:22:51-04:00</updated>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch" rel="list"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch" rel="edit"/>
    <link href="/servicesNS/admin/search/saved/searches/MySavedSearch" rel="remove"/>
    <content type="text/xml">
      <s:dict>
        <!-- eai:acl elided -->
        <s:key name="expiration">13811</s:key>
        <s:key name="suppressed">1</s:key>
        <s:key name="suppressionKey">admin;search;MySavedSearch;;</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

scheduled/views

CODE

```
https://<host>:<mPort>/services/scheduled/views
```

Access views scheduled for PDF delivery. Scheduled views are dummy noop scheduled saved searches that email a PDF of a dashboard.

GET

List all scheduled view objects.

Request parameters

Pagination and filtering parameters can be used with this method.

Returned values

Name	Description
action.email	Indicates the state of the email action.
action.email.pdfview	Name of the view to send as a PDF.
action.email.sendpdf	Indicates whether to create and send the results as a PDF.
action.email.sendresults	Indicates whether the search results are included in the email. The results can be attached or inline.
action.email.to	List of recipient email addresses. Required if the email alert action is enabled.
action.email.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows <Integer>, int is the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p].

Name	Description
cron_schedule	The cron schedule to use for delivering the view. Scheduled views are dummy/noop scheduled saved searches that email a pdf version of a view For example: */5 * * * * causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: 00,20,40 * * * *, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of 03,23,43 * * * * runs the search every hour at hh:03, hh:23, hh:43. Splunk recommends that you schedule your searches so that they are staggered over time. This reduces system load. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes.
description	Description of this scheduled view object.
disabled	Indicates if the scheduled view is disabled.
is_scheduled	Indicates if PDF delivery of this view is scheduled.
next_scheduled_time	The next time when the view is delivered.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/scheduled/views
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>scheduledviews</title>
  <id>https://localhost:8089/servicesNS/admin/search/admin/scheduledviews</id>
  <updated>2011-07-27T16:27:55-04:00</updated>
  <generator version="104601"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/admin/search/admin/scheduledviews/_reload" rel="_reload"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>_ScheduledView__MyView</title>
    <id>https://localhost:8089/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView</id>
    <updated>2011-07-27T16:27:55-04:00</updated>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView" rel="list"/>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView" rel="edit"/>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView" rel="remove"/>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView/move" rel="move"/>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView/disable" rel="disable"/>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView/dispatch" rel="dispatch"/>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView/history" rel="history"/>
    <link href="/servicesNS/admin/search/admin/scheduledviews/_ScheduledView__MyView/notify" rel="notify"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="action.email">1</s:key>
        <s:key name="action.email.pdfview">MyView</s:key>
        <s:key name="action.email.sendpdf">1</s:key>
        <s:key name="action.email.sendresults"></s:key>
        <s:key name="action.email.to">email@example.com</s:key>
        <s:key name="action.email.ttl">10</s:key>
        <s:key name="cron_schedule">* * * * *</s:key>
        <s:key name="description">scheduled search for view name=MyView</s:key>
        <s:key name="disabled">0</s:key>
        <!-- eai:acl elided -->
        <s:key name="is_scheduled">1</s:key>
        <s:key name="next_scheduled_time">2011-07-27 16:28:00 EDT</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

scheduled/views/{name}

JSON

```
https://<host>:<mPort>/services/scheduled/views/{name}
```

Manage the {name} scheduled view.

DELETE

Delete a scheduled view.

Request parameters

None

Returned values

None

Example request and response

XML Request

CODE

```
curl -k -u admin:pass --request DELETE https://localhost:8089/servicesNS/admin/search/scheduled/views/MyView
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>scheduledviews</title>
  <id>https://localhost:8089/servicesNS/admin/search/admin/scheduledviews</id>
  <updated>2011-07-27T16:16:02-04:00</updated>
  <generator version="104601"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/admin/search/admin/scheduledviews/_reload" rel="_reload"/>
  <opensearch:totalResults>0</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
</feed>
```

GET

Access a scheduled view.

Request parameters

None

Returned values

Name	Description
action.email	Indicates the sate of the email action.
action.email.auth_password	The password to use when authenticating with the SMTP server. Normally this value is set when editing the email settings, however you can set a clear text password here and it is encrypted on the next restart. Defaults to empty string.
action.email.auth_username	The username to use when authenticating with the SMTP server. If this is empty string, no authentication is attempted. Defaults to empty string. *Note:* Your SMTP server might reject unauthenticated emails.
action.email.bcc	"BCC email address to use if action.email is enabled.
action.email.cc	CC email address to use if action.email is enabled.
action.email.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.

Name	Description
action.email.format	Specify the format of text in the email. This value also applies to any attachments.< Valid values: (plain | html | raw | csv)
action.email.from	Email address from which the email action originates. Defaults to splunk@$LOCALHOST or whatever value is set in alert_actions.conf.
action.email.hostname	Sets the hostname used in the web link (url) sent in email actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) When this value is a simple hostname, the protocol and port which are configured within splunk are used to construct the base of the url. When this value begins with 'http://', it is used verbatim. NOTE: This means the correct port must be specified if it is not the default port for http or https. This is useful in cases when the Splunk server is not aware of how to construct a url that can be externally referenced, such as SSO environments, other proxies, or when the server hostname is not generally resolvable. Defaults to current hostname provided by the operating system, or if that fails "localhost". When set to empty, default behavior is used.
action.email.inline	Indicates whether the search results are contained in the body of the email. Results can be either inline or attached to an email. See action.email.sendresults.
action.email.mailserver	Set the address of the MTA server to be used to send the emails. Defaults to <LOCALHOST> (or whatever is set in alert_actions.conf).
action.email.maxresults	Sets the global maximum number of search results to send when email.action is enabled.
action.email.maxtime	Specifies the maximum amount of time the execution of an email action takes before the action is aborted.
action.email.pdfview	The name of the view to deliver if sendpdf is enabled.
action.email.preprocess_results	Search string to preprocess results before emailing them. Defaults to empty string (no preprocessing). Usually the preprocessing consists of filtering out unwanted internal fields.
action.email.reportPaperOrientation	Specifies the paper orientation: portrait or landscape.
action.email.reportPaperSize	Specifies the paper size for PDFs. Defaults to letter. Valid values: (letter | legal | ledger | a2 | a3 | a4 | a5)
action.email.sendpdf	Indicates whether to create and send the results as a PDF.
action.email.sendresults	Indicates whether to attach the search results in the email. Results can be either attached or inline. See action.email.inline.
action.email.subject	Specifies the email subject. Defaults to SplunkAlert-<savedsearchname>.
action.email.to	List of recipient email addresses. Required if this search is scheduled and the email alert action is enabled.
action.email.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.email.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows <Integer>, int is the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p].
action.email.use_ssl	Indicates whether to use SSL when communicating with the SMTP server
action.email.use_tls	Indicates whether to use TLS (transport layer security) when communicating with the SMTP server (starttls).

Name	Description
cron_schedule	The cron schedule to execute this search. For example: */5 * * * * causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: 00,20,40 * * * *, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of 03,23,43 * * * * runs the search every hour at hh:03, hh:23, hh:43. Splunk recommends that you schedule your searches so that they are staggered over time. This reduces system load. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes. Valid values: cron string
description	Description of this saved search for this view.
disabled	Indicates if the saved search for this view is disabled.
is_scheduled	Indicates if this search is to be run on a schedule.
next_scheduled_time	The next time when the view is delivered.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/scheduled/views/MyView
```

XML Response

JSON

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:s="http://dev.splunk.com/ns/rest"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>scheduledviews</title>
  <id>https://localhost:8089/servicesNS/admin/search/scheduled/views</id>
  <updated>2011-07-27T17:12:11-04:00</updated>
  <generator version="104601"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/admin/search/scheduled/views/_reload" rel="_reload"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>_ScheduledView__MyView</title>
    <id>https://localhost:8089/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView</id>
    <updated>2011-07-27T17:12:11-04:00</updated>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView" rel="list"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView" rel="edit"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView" rel="remove"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/move" rel="move"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/disable" rel="disable"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/dispatch" rel="dispatch"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/history" rel="history"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/notify" rel="notify"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="action.email">1</s:key>
        <s:key name="action.email.auth_password"></s:key>
        <s:key name="action.email.auth_username"></s:key>
        <s:key name="action.email.bcc"></s:key>
        <s:key name="action.email.cc"></s:key>
        <s:key name="action.email.command">
          <![CDATA[$action.email.preprocess_results{default=""}$ |
                   sendemail "server=$action.email.mailserver{default=localhost}$" "use_ssl=$action.email.use_ssl{default=false}$"
                   "use_tls=$action.email.use_tls{default=false}$" "to=$action.email.to$" "cc=$action.email.cc$"
                   "bcc=$action.email.bcc$" "from=$action.email.from{default=splunk@localhost}$"
                   "subject=$action.email.subject{recurse=yes}$" "format=$action.email.format{default=csv}$"
                   "sssummary=Saved Search [$name$]: $counttype$($results.count$)" "sslink=$results.url$"
                   "ssquery=$search$" "ssname=$name$" "inline=$action.email.inline{default=False}$"
                   "sendresults=$action.email.sendresults{default=False}$" "sendpdf=$action.email.sendpdf{default=False}$"
                   "pdfview=$action.email.pdfview$" "searchid=$search_id$" "graceful=$graceful{default=True}$"
                   maxinputs="$action.email.maxresults{default=10000}$" maxtime="$action.email.maxtime{default=5m}$"]]>
        </s:key>
        <s:key name="action.email.format">html</s:key>
        <s:key name="action.email.from">splunk</s:key>
        <s:key name="action.email.hostname"></s:key>
```

```
        <s:key name="action.email.inline">0</s:key>
        <s:key name="action.email.mailserver">localhost</s:key>
        <s:key name="action.email.maxresults">10000</s:key>
        <s:key name="action.email.maxtime">5m</s:key>
        <s:key name="action.email.pdfview">MyView</s:key>
        <s:key name="action.email.preprocess_results"></s:key>
        <s:key name="action.email.reportPaperOrientation">portrait</s:key>
        <s:key name="action.email.reportPaperSize">letter</s:key>
        <s:key name="action.email.reportServerEnabled">0</s:key>
        <s:key name="action.email.reportServerURL"></s:key>
        <s:key name="action.email.sendpdf">1</s:key>
        <s:key name="action.email.sendresults">0</s:key>
        <s:key name="action.email.subject">Splunk Alert: $name$</s:key>
        <s:key name="action.email.to">info@example.com</s:key>
        <s:key name="action.email.track_alert">1</s:key>
        <s:key name="action.email.ttl">10</s:key>
        <s:key name="action.email.use_ssl">0</s:key>
        <s:key name="action.email.use_tls">0</s:key>
        <s:key name="cron_schedule">* * * * *</s:key>
        <s:key name="description">scheduled search for view name=MyView</s:key>
        <s:key name="disabled">0</s:key>
        <!-- eai:acl elided -->
        <s:key name="eai:attributes">
          <s:dict>
            <s:key name="optionalFields">
              <s:list>
                <s:item>description</s:item>
                <s:item>disabled</s:item>
                <s:item>next_scheduled_time</s:item>
              </s:list>
            </s:key>
            <s:key name="requiredFields">
              <s:list>
                <s:item>action.email.to</s:item>
                <s:item>cron_schedule</s:item>
                <s:item>is_scheduled</s:item>
              </s:list>
            </s:key>
            <s:key name="wildcardFields">
              <s:list><s:item>action\.email.*</s:item></s:list>
            </s:key>
          </s:dict>
        </s:key>
        <s:key name="is_scheduled">1</s:key>
        <s:key name="next_scheduled_time">2011-07-27 17:13:00 EDT</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

POST

Update a scheduled view.

Request parameters

Name	Type	Default	Description
action.email.to required	String		Comma or semicolon separated list of email addresses to send the view to
*action.email**	String		Wildcard argument that accepts any email action.
cron_schedule required	String		The cron schedule to use for delivering the view. Scheduled views are dummy/noop scheduled saved searches that email a pdf version of a view. For example: */5 * * * * causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: 00,20,40 * * * *, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of 03,23,43 * * * * runs the search every hour at hh:03, hh:23, hh:43. Splunk recommends that you schedule your searches so that they are staggered over time. This reduces system load. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes.

Name	Type	Default	Description
description	String		User readable description of this scheduled view object
disabled	Boolean	0	Whether this object is enabled or disabled
is_scheduled required	Boolean		Whether this pdf delivery should be scheduled
next_scheduled_time	String		The next time when the view is delivered. Ignored on edit, here only for backwards compatability.

Returned values

Name	Description
action.email	Indicates the status of the email action.
action.email.auth_password	The password to use when authenticating with the SMTP server. Normally this value is set when editing the email settings, however you can set a clear text password here that is encrypted on the next restart. Defaults to empty string.
action.email.auth_username	The username to use when authenticating with the SMTP server. If this is empty string, no authentication is attempted. Defaults to empty string. *Note:* Your SMTP server might reject unauthenticated emails.
action.email.bcc	BCC email address to use if action.email is enabled.
action.email.cc	CC email address to use if action.email is enabled.
action.email.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.email.format	Specify the format of text in the email. This value also applies to any attachments.< Valid values: (plain | html | raw | csv)
action.email.from	Email address from which the email action originates
action.email.hostname	Sets the hostname used in the web link (url) sent in email actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) When this value is a simple hostname, the protocol and port which are configured within splunk are used to construct the base of the url. When this value begins with 'http://', it is used verbatim. NOTE: This means the correct port must be specified if it is not the default port for http or https. This is useful in cases when the Splunk server is not aware of how to construct an externally referencable url, such as SSO environments, other proxies, or when the server hostname is not generally resolvable. Defaults to current hostname provided by the operating system, or if that fails "localhost". When set to empty, default behavior is used.
action.email.inline	Indicates whether the search results are contained in the body of the email. Results can be either inline or attached to an email. See action.email.sendresults.
action.email.mailserver	Set the address of the MTA server to be used to send the emails. Defaults to <LOCALHOST> (or whatever is set in alert_actions.conf).
action.email.maxresults	Sets the maximum number of search results sent using alerts.
action.email.maxtime	Specifies the maximum amount of time the execution of an email action takes before the action is aborted.
action.email.pdfview	The name of the view to deliver if sendpdf is enabled.
action.email.preprocess_results	Search string to preprocess results before emailing them. Defaults to empty string (no preprocessing). Usually the preprocessing consists of filtering out unwanted internal fields.
action.email.reportPaperOrientation	Specifies the paper orientation: portrait or landscape.

Name	Description
action.email.reportPaperSize	Specifies the paper size for PDFs. Defaults to letter. Valid values: (letter | legal | ledger | a2 | a3 | a4 | a5)
action.email.sendpdf	Indicates whether to create and send the results as a PDF.
action.email.sendresults	Indicates whether to attach the search results in the email. Results can be either attached or inline. See action.email.inline.
action.email.subject	Specifies an email subject. Defaults to SplunkAlert-<savedsearchname>.
action.email.to	List of recipient email addresses. Required if this search is scheduled and the email alert action is enabled.
action.email.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.email.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows <Integer>, int is the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p].
action.email.use_ssl	Indicates whether to use SSL when communicating with the SMTP server.
action.email.use_tls	Indicates whether to use TLS (transport layer security) when communicating with the SMTP server (starttls).
cron_schedule	The cron schedule to execute this search. For example: */5 * * * * causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: 00,20,40 * * * *, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of 03,23,43 * * * * runs the search every hour at hh:03, hh:23, hh:43. Splunk recommends that you schedule your searches so that they are staggered over time. This reduces system load. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes. Valid values: cron string
description	Description of the saved search for this view.
disabled	Indicates if the saved search for this view is disabled.
is_scheduled	Indicates if this search is to be run on a schedule.
next_scheduled_time	The next time when the view is delivered.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/scheduled/views/MyVew -d action.email.to="info@example.com" -d cron_schedule="0 * *
* *" -d is_scheduled=1 -d description="New description"
```

XML Response

JSON

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:s="http://dev.splunk.com/ns/rest"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>scheduledviews</title>
  <id>https://localhost:8089/servicesNS/admin/search/scheduled/views</id>
  <updated>2011-07-27T17:59:32-04:00</updated>
  <generator version="104601"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/admin/search/scheduled/views/_reload" rel="_reload"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>_ScheduledView__MyView</title>
    <id>https://localhost:8089/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView</id>
    <updated>2011-07-27T17:59:32-04:00</updated>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView" rel="alternate"/>
    <author>
      <name>admin</name>
```

```
    </author>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView" rel="list"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/_reload" rel="_reload"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView" rel="edit"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView" rel="remove"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/move" rel="move"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/disable" rel="disable"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/dispatch" rel="dispatch"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/history" rel="history"/>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__MyView/notify" rel="notify"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="action.email">1</s:key>
        <s:key name="action.email.auth_password"></s:key>
        <s:key name="action.email.auth_username"></s:key>
        <s:key name="action.email.bcc"></s:key>
        <s:key name="action.email.cc"></s:key>
        <s:key name="action.email.command">
          <![CDATA[$action.email.preprocess_results{default=""}$ |
                   sendemail "server=$action.email.mailserver{default=localhost}$" "use_ssl=$action.email.use_ssl{default=false}$"
                   "use_tls=$action.email.use_tls{default=false}$" "to=$action.email.to$" "cc=$action.email.cc$"
                   "bcc=$action.email.bcc$" "from=$action.email.from{default=splunk@localhost}$"
                   "subject=$action.email.subject{recurse=yes}$" "format=$action.email.format{default=csv}$"
                   "sssummary=Saved Search [$name$]: $counttype$($results.count$)" "sslink=$results.url$"
                   "ssquery=$search$" "ssname=$name$" "inline=$action.email.inline{default=False}$"
                   "sendresults=$action.email.sendresults{default=False}$" "sendpdf=$action.email.sendpdf{default=False}$"
                   "pdfview=$action.email.pdfview$" "searchid=$search_id$" "graceful=$graceful{default=True}$"
                   maxinputs="$action.email.maxresults{default=10000}$" maxtime="$action.email.maxtime{default=5m}$"]]>
        </s:key>
        <s:key name="action.email.format">html</s:key>
        <s:key name="action.email.from">splunk</s:key>
        <s:key name="action.email.hostname"></s:key>
        <s:key name="action.email.inline">0</s:key>
        <s:key name="action.email.mailserver">localhost</s:key>
        <s:key name="action.email.maxresults">10000</s:key>
        <s:key name="action.email.maxtime">5m</s:key>
        <s:key name="action.email.pdfview">MyView</s:key>
        <s:key name="action.email.preprocess_results"></s:key>
        <s:key name="action.email.reportPaperOrientation">portrait</s:key>
        <s:key name="action.email.reportPaperSize">letter</s:key>
        <s:key name="action.email.reportServerEnabled">0</s:key>
        <s:key name="action.email.reportServerURL"></s:key>
        <s:key name="action.email.sendpdf">1</s:key>
        <s:key name="action.email.sendresults">0</s:key>
        <s:key name="action.email.subject">Splunk Alert: $name$</s:key>
        <s:key name="action.email.to">info@example.com</s:key>
        <s:key name="action.email.track_alert">1</s:key>
        <s:key name="action.email.ttl">10</s:key>
        <s:key name="action.email.use_ssl">0</s:key>
        <s:key name="action.email.use_tls">0</s:key>
        <s:key name="cron_schedule">0 * * * *</s:key>
        <s:key name="description">New Description</s:key>
        <s:key name="disabled">0</s:key>
        <!-- eai:acl elided -->
        <s:key name="is_scheduled">1</s:key>
        <s:key name="next_scheduled_time">2011-07-27 18:00:00 EDT</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

scheduled/views/{name}/dispatch

JSON

`https://<host>:<mPort>/services/scheduled/views/{name}/dispatch`

Dispatch the scheduled search associated with the `{name}` scheduled view.

POST

Dispatch the scheduled search associated with the `{name}` scheduled view.

Request parameters

Name	Type	Default	Description
*args.**	String		Wildcard argument that accepts any saved search template argument, such as arg.username=foobar when the search is search $username$.
*dispatch.**	String		Wildcard argument that accepts any dispatch related argument.

Name	Type	Default	Description
dispatch.now	Boolean		Dispatch the search as if the specified time for this parameter was the current time.
force_dispatch	Boolean		Indicates whether to start a new search even if another instance of this search is already running.
now	String		[Deprecated] Use *dispatch.now*.
trigger_actions	Boolean		Indicates whether to trigger alert actions

Returned values

None

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/scheduled/views/MyView/dispatch -d trigger_actions=1
```

XML Response

XML

```
<?xml version='1.0' encoding='UTF-8'?>
<response><sid>admin__admin__search_X1NjaGVkdWxlZFZpZXdfX015Vmlldw_at_1311805021_c24ff1ea77ad714b</sid></response>
```

scheduled/views/{name}/history

JSON

```
https://<host>:<mPort>/services/scheduled/views/{name}/history
```

List search jobs used to render the {name} scheduled view.

GET

List search jobs used to render the {name} scheduled view.

Request parameters
None

Returned values

None

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/scheduled/views/MyVew/history
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:s="http://dev.splunk.com/ns/rest"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>_ScheduledView__MyView</title>
  <id>https://localhost:8089/servicesNS/admin/search/scheduled/views</id>
  <updated>2011-07-27T16:25:22-04:00</updated>
  <generator version="104601"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/servicesNS/admin/search/scheduled/views/_reload" rel="_reload"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>scheduler__admin__search_X1NjaGVkdWxlZFZpZXdfX015Vmlldw_at_1311798300_842d7ca298ab521a</title>
```

```
<id>https://localhost:8089/servicesNS/nobody/search/search/jobs/scheduler__admin__search_X1NjaGVkdWxlZFZpZXdfX015Vmlldw_at_1311798300_842d7ca298ab521a</
id>
    <updated>2011-07-27T16:25:15-04:00</updated>
    <link href="/servicesNS/nobody/search/search/jobs/scheduler__admin__search_X1NjaGVkdWxlZFZpZXdfX015Vmlldw_at_1311798300_842d7ca298ab521a"
rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <published>2011-07-27T16:25:15-04:00</published>
    <link href="/servicesNS/nobody/search/search/jobs/scheduler__admin__search_X1NjaGVkdWxlZFZpZXdfX015Vmlldw_at_1311798300_842d7ca298ab521a"
rel="list"/>
    <link href="/servicesNS/nobody/search/search/jobs/scheduler__admin__search_X1NjaGVkdWxlZFZpZXdfX015Vmlldw_at_1311798300_842d7ca298ab521a/_reload"
rel="_reload"/>
    <link href="/servicesNS/nobody/search/search/jobs/scheduler__admin__search_X1NjaGVkdWxlZFZpZXdfX015Vmlldw_at_1311798300_842d7ca298ab521a"
rel="edit"/>
    <link href="/servicesNS/nobody/search/search/jobs/scheduler__admin__search_X1NjaGVkdWxlZFZpZXdfX015Vmlldw_at_1311798300_842d7ca298ab521a"
rel="remove"/>
    <content type="text/xml">
      <s:dict>
        <!-- eai:acl elided -->
      </s:dict>
    </content>
  </entry>
</feed>
```

scheduled/views/{name}/reschedule

JSON

```
https://<host>:<mPort>/services/scheduled/views/{name}/reschedule
```

Schedule the {name} view PDF delivery.

POST

Schedule the {name} view PDF delivery.

Request parameters

Name	Type	Default	Description
schedule_time	String		Absolute or relative schedule time.

Returned values

None

Application usage

If schedule_time is not specified, then it is assumed that the delivery should occur as soon as possible.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/scheduled/views/_ScheduledView__dashboard2/reschedule -d schedule_time=2013-02-15T14:11:01Z
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>scheduledviews</title>
  <id>https://localhost:8089/services/scheduled/views</id>
  <updated>2012-10-02T08:48:18-07:00</updated>
  <generator build="138753" version="5.0"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/scheduled/views/_reload" rel="_reload"/>
  <opensearch:totalResults>0</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
</feed>
```

scheduled/views/{name}/scheduled_times

JSON

```
https://<host>:<mPort>/services/scheduled/views/{name}/scheduled_times
```

Get scheduled view times.

GET

Get scheduled view times.

Request parameters

Name	Type	Default	Description
earliest_time	String		Absolute or relative earliest time
latest_time	String		Absolute or relative latest time

Returned values

Name	Description
action.email	Indicates the state of the email action.
action.email.auth_password	The password to use when authenticating with the SMTP server. Normally this value is set when editing the email settings, however you can set a clear text password here that is encrypted on the next restart. Defaults to empty string.
action.email.auth_username	The username to use when authenticating with the SMTP server. If this is empty string, no authentication is attempted. Defaults to empty string. *Note:* Your SMTP server might reject unauthenticated emails.
action.email.bcc	BCC email address to use if action.email is enabled.
action.email.cc	CC email address to use if action.email is enabled.
action.email.command	The search command (or pipeline) which is responsible for executing the action. Generally the command is a template search pipeline which is realized with values from the saved search. To reference saved search field values wrap them in $, for example to reference the savedsearch name use $name$, to reference the search use $search$.
action.email.format	Specify the format of text in the email. This value also applies to any attachments.< Valid values: (plain | html | raw | csv)
action.email.from	Email address from which the email action originates.
action.email.hostname	Sets the hostname used in the web link (url) sent in email actions. This value accepts two forms: hostname (for example, splunkserver, splunkserver.example.com) protocol://hostname:port (for example, http://splunkserver:8000, https://splunkserver.example.com:443) When this value is a simple hostname, the protocol and port which are configured within splunk are used to construct the base of the url. When this value begins with 'http://', it is used verbatim. NOTE: This means the correct port must be specified if it is not the default port for http or https. This is useful in cases when the Splunk server is not aware of how to construct a url that can be externally referenced, such as SSO environments, other proxies, or when the server hostname is not generally resolvable. Defaults to current hostname provided by the operating system, or if that fails "localhost". When set to empty, default behavior is used.
action.email.inline	Indicates whether the search results are contained in the body of the email. Results can be either inline or attached to an email. See action.email.sendresults.
action.email.mailserver	Set the address of the MTA server to be used to send the emails. Defaults to <LOCALHOST> (or whatever is set in alert_actions.conf).
action.email.maxresults	Sets the maximum number of search results sent using alerts.
action.email.maxtime	Specifies the maximum amount of time the execution of an email action takes before the action is aborted.

Name	Description
action.email.pdfview	The name of the view to deliver if sendpdf is enabled.
action.email.preprocess_results	Search string to preprocess results before emailing them. Defaults to empty string (no preprocessing). Usually the preprocessing consists of filtering out unwanted internal fields.
action.email.reportPaperOrientation	Specifies the paper orientation: portrait or landscape.
action.email.reportPaperSize	Specifies the paper size for PDFs. Defaults to letter. Valid values: (letter | legal | ledger | a2 | a3 | a4 | a5)
action.email.reportServerEnabled	Not supported.
action.email.reportServerURL	Not supported.
action.email.sendpdf	Indicates whether to create and send the results as a PDF.
action.email.sendresults	Indicates whether to attach the search results in the email. Results can be either attached or inline. See action.email.inline.
action.email.subject	Specifies an email subject. Defaults to SplunkAlert-<savedsearchname>.
action.email.to	List of recipient email addresses. Required if this search is scheduled and the email alert action is enabled.
action.email.track_alert	Indicates whether the execution of this action signifies a trackable alert.
action.email.ttl	Specifies the minimum time-to-live in seconds of the search artifacts if this action is triggered. If p follows <Integer>, int is the number of scheduled periods. Defaults to 86400 (24 hours). If no actions are triggered, the artifacts have their ttl determined by dispatch.ttl in savedsearches.conf. Valid values are Integer[p].
action.email.use_ssl	Indicates whether to use SSL when communicating with the SMTP server.
action.email.use_tls	Indicates whether to use TLS (transport layer security) when communicating with the SMTP server (starttls).
action.email.width_sort_columns	Indicates whether columns should be sorted from least wide to most wide, left to right. Only valid if format=text.
cron_schedule	The cron schedule to execute this search. For example: */5 * * * * causes the search to execute every 5 minutes. cron lets you use standard cron notation to define your scheduled search interval. In particular, cron can accept this type of notation: 00,20,40 * * * *, which runs the search every hour at hh:00, hh:20, hh:40. Along the same lines, a cron of 03,23,43 * * * * runs the search every hour at hh:03, hh:23, hh:43. Splunk recommends that you schedule your searches so that they are staggered over time. This reduces system load. Running all of them every 20 minutes (*/20) means they would all launch at hh:00 (20, 40) and might slow your system every 20 minutes. Valid values: cron string
description	Description of the saved search for this view.
disabled	Indicates if the saved search for this view is disabled. Disabled saved searches are not visible in Splunk Web.
is_scheduled	Indicates if this search is to be run on a schedule.
next_scheduled_time	The next time when the view is delivered.

Application usage

Specify a time range for the data returned using earliest_time and latest_time parameters.

Example request and response

XML Request

CODE

```
curl -k -u admin:admin https://localhost:8089/services/scheduled/views/_ScheduledView__dashboard_live/scheduled_times --get -d earliest_time=-5h -d
latest_time=-3h
```

XML Response

JSON


```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>scheduledviews</title>
  <id>https://wma-mbp15:8089/services/scheduled/views</id>
  <updated>2011-12-01T14:40:18-08:00</updated>
  <generator version="112383"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/scheduled/views/_reload" rel="_reload"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>_ScheduledView__dashboard_live</title>
    <id>https://wma-mbp15:8089/servicesNS/admin/search/scheduled/views/_ScheduledView__dashboard_live</id>
    <updated>2011-12-01T14:40:18-08:00</updated>
    <link href="/servicesNS/admin/search/scheduled/views/_ScheduledView__dashboard_live" rel="alternate"/>
    <author>
      <name>admin</name>
    </author>
    <!-- opensearch nodes elided for brevity. -->
    <content type="text/xml">
      <s:dict>
        <s:key name="action.email">1</s:key>
        <s:key name="action.email.auth_password"></s:key>
        <s:key name="action.email.auth_username"></s:key>
        <s:key name="action.email.bcc"></s:key>
        <s:key name="action.email.cc"></s:key>
        <s:key name="action.email.command"><![CDATA[$action.email.preprocess_results{default=""}$ | sendemail
"server=$action.email.mailserver{default=localhost}$" "use_ssl=$action.email.use_ssl{default=false}$" "use_tls=$action.email.use_tls{default=false}$"
"to=$action.email.to$" "cc=$action.email.cc$" "bcc=$action.email.bcc$" "from=$action.email.from{default=splunk@localhost}$"
"subject=$action.email.subject{recurse=yes}$" "format=$action.email.format{default=csv}$" "sssummary=Saved Search [$name$]:
$counttype$($results.count$)" "sslink=$results.url$" "ssquery=$search$" "ssname=$name$" "inline=$action.email.inline{default=False}$"
"sendresults=$action.email.sendresults{default=False}$" "sendpdf=$action.email.sendpdf{default=False}$" "pdfview=$action.email.pdfview$"
"searchid=$search_id$" "width_sort_columns=$action.email.width_sort_columns$" "graceful=$graceful{default=True}$"
maxinputs="$action.email.maxresults{default=10000}$" maxtime="$action.email.maxtime{default=5m}$"]]></s:key>
        <s:key name="action.email.format">html</s:key>
        <s:key name="action.email.from">splunk</s:key>
        <s:key name="action.email.hostname"></s:key>
        <s:key name="action.email.inline">0</s:key>
        <s:key name="action.email.mailserver">localhost</s:key>
        <s:key name="action.email.maxresults">10000</s:key>
        <s:key name="action.email.maxtime">5m</s:key>
        <s:key name="action.email.pdfview">dashboard_live</s:key>
        <s:key name="action.email.preprocess_results"></s:key>
        <s:key name="action.email.reportPaperOrientation">portrait</s:key>
        <s:key name="action.email.reportPaperSize">letter</s:key>
        <s:key name="action.email.reportServerEnabled">1</s:key>
        <s:key name="action.email.reportServerURL"> </s:key>
        <s:key name="action.email.sendpdf">1</s:key>
        <s:key name="action.email.sendresults">0</s:key>
        <s:key name="action.email.subject">Splunk Alert: $name$</s:key>
        <s:key name="action.email.to">wma@splunk.com</s:key>
        <s:key name="action.email.track_alert">1</s:key>
        <s:key name="action.email.ttl">10</s:key>
        <s:key name="action.email.use_ssl">0</s:key>
        <s:key name="action.email.use_tls">0</s:key>
        <s:key name="action.email.width_sort_columns">1</s:key>
        <s:key name="cron_schedule">/5 * * * *</s:key>
        <s:key name="description">scheduled search for view name=dashboard_live</s:key>
        <s:key name="disabled">0</s:key>
        <!-- eai:acl elided -->
        <s:key name="is_scheduled">1</s:key>
        <s:key name="next_scheduled_time">2011-12-01 15:00:00 PST</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```


search/concurrency-settings

CODE

```
https://<host>:<mPort>/services/search/concurrency-settings
```

GET

List search concurrency settings.

Request parameters

None

Returned values

Name	Type	Description
max_searches_perc	Number	The maximum number of searches the scheduler can run as a percentage of the maximum number of concurrent searches. Default: 50%.
auto_summary_perc	Number	The maximum number of concurrent searches to be allocated for auto summarization, as a percentage of the concurrent searches that the scheduler can run. Default: 50.
max_searches_per_cpu	Number	The maximum number of concurrent historical searches allowed per cpu. Default: 1.
base_max_searches	Number	A baseline constant to add to the max number of searches (computed as multiplier of the CPUs.) Default is 6.
max_rt_search_multiplier	Number	A number by which the maximum number of historical searches is multiplied to determine the maximum number of concurrent real-time searches. Note: The maximum number of real-time searches is computed as max_rt_searches = max_rt_search_multiplier x max_hist_searches

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/concurrency-settings
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>search-concurrency-settings-handler</title>
  <id>https://localhost:8089/services/search/concurrency-settings</id>
  <updated>2019-04-21T14:46:39-07:00</updated>
  <generator build="efdccca30d13" version="7.3.0"/>
  <author>
    <name>Splunk</name>
  </author>
  <opensearch:totalResults>2</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>scheduler</title>
    <id>https://localhost:8089/services/search/concurrency-settings/scheduler</id>
    <updated>1969-12-31T16:00:00-08:00</updated>
    <link href="/services/search/concurrency-settings/scheduler" rel="alternate"/>
    <author>
      <name>system</name>
    </author>
    <link href="/services/search/concurrency-settings/scheduler" rel="list"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="auto_summary_perc">50</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app"></s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">0</s:key>
            <s:key name="owner">system</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list/>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">system</s:key>
          </s:dict>
        </s:key>
        <s:key name="max_searches_perc">50</s:key>
      </s:dict>
    </content>
  </entry>
```

```
  <entry>
    <title>search</title>
    <id>https://localhost:8089/services/search/concurrency-settings/search</id>
    <updated>1969-12-31T16:00:00-08:00</updated>
    <link href="/services/search/concurrency-settings/search" rel="alternate"/>
    <author>
      <name>system</name>
    </author>
    <link href="/services/search/concurrency-settings/search" rel="list"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="base_max_searches">10</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app"></s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">0</s:key>
            <s:key name="owner">system</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list/>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">system</s:key>
          </s:dict>
        </s:key>
        <s:key name="max_rt_search_multiplier">1</s:key>
        <s:key name="max_searches_per_cpu">1</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

search/concurrency-settings/scheduler

CODE

```
https://<host>:<mPort>/services/search/concurrency-settings/scheduler
```

Edit settings that determine concurrent scheduled search limits.

Authentication and Authorization
The `edit_search_concurrency_scheduled` capability is required for this endpoint.

POST

Edit settings that determine concurrent scheduled search limits.

Request parameters

Name	Type	Description
max_searches_perc	Number	The maximum number of searches the scheduler can run as a percentage of the maximum number of concurrent searches. Default: 50.
auto_summary_perc	Number	The maximum number of concurrent searches to be allocated for auto summarization, as a percentage of the concurrent searches that the scheduler can run. Default: 50.

Returned values
None

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/concurrency-settings/scheduler -d max_searches_perc=40
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>search-concurrency-settings-handler</title>
  <id>https://localhost:8089/services/search/concurrency-settings</id>
  <updated>2019-04-21T17:17:30-07:00</updated>
  <generator build="efdccca30d13" version="7.3.0"/>
  <author>
    <name>Splunk</name>
  </author>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>scheduler</title>
    <id>https://localhost:8089/services/search/concurrency-settings/scheduler</id>
    <updated>1969-12-31T16:00:00-08:00</updated>
    <link href="/services/search/concurrency-settings/scheduler" rel="alternate"/>
    <author>
      <name>system</name>
    </author>
    <link href="/services/search/concurrency-settings/scheduler" rel="list"/>
    <link href="/services/search/concurrency-settings/scheduler" rel="edit"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="auto_summary_perc">50</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app"></s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">0</s:key>
            <s:key name="owner">system</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list>
                    <s:item>admin</s:item>
                    <s:item>splunk-system-role</s:item>
                  </s:list>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">system</s:key>
          </s:dict>
        </s:key>
        <s:key name="max_searches_perc">40</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

search/concurrency-settings/search

CODE

```
https://<host>:<mPort>/services/search/concurrency-settings/search
```

Edit settings that determine the maximum number of concurrent scheduled searches.

Authentication and Authorization

The `edit_search_concurrency_all` capability is required for this endpoint.

POST

Edit settings that determine the maximum number of concurrent scheduled searches.

Request parameters

Name	Type	Description
max_searches_per_cpu	Number	The maximum number of concurrent historical searches allowed per cpu. Default: 1.
base_max_searches	Number	A baseline constant to add to the max number of searches (computed as multiplier of the CPUs.) Default is 6.

Name	Type	Description
max_rt_search_multiplier	Number	A number by which the maximum number of historical searches is multiplied to determine the maximum number of concurrent real-time searches. Note: The maximum number of real-time searches is computed as max_rt_searches = max_rt_search_multiplier x max_hist_searches

Returned values

None

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/concurrency-settings/search -d base_max_searches=5 -d max_searches_per_cpu=4
```

XML Response

CODE

```
feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>search-concurrency-settings-handler</title>
  <id>https://localhost:8089/services/search/concurrency-settings</id>
  <updated>2019-04-21T17:31:19-07:00</updated>
  <generator build="efdccca30d13" version="7.3.0"/>
  <author>
    <name>Splunk</name>
  </author>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>search</title>
    <id>https://localhost:8089/services/search/concurrency-settings/search</id>
    <updated>1969-12-31T16:00:00-08:00</updated>
    <link href="/services/search/concurrency-settings/search" rel="alternate"/>
    <author>
      <name>system</name>
    </author>
    <link href="/services/search/concurrency-settings/search" rel="list"/>
    <link href="/services/search/concurrency-settings/search" rel="edit"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="base_max_searches">5</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app"></s:key>
            <s:key name="can_list">1</s:key>
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">0</s:key>
            <s:key name="owner">system</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>*</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list>
                    <s:item>admin</s:item>
                    <s:item>splunk-system-role</s:item>
                  </s:list>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">system</s:key>
          </s:dict>
        </s:key>
        <s:key name="max_rt_search_multiplier">1</s:key>
        <s:key name="max_searches_per_cpu">4</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

search/jobs

CODE

```
https://<host>:<mPort>/services/search/jobs
```

List search jobs.

For more information about this and other search endpoints, see Creating searches using the REST API in the *REST API Tutorial*.

GET

Get details of all current searches.

Request parameters

Pagination and filtering parameters can be used with this method.

Returned values

Name	Description
cursorTime	The earliest time from which no events are later scanned. Can be used to indicate progress. See description for `doneProgress`.
custom	Custom job property. (See the search/jobs POST request for an example of how to create a custom property.) *Note:* Filtering for custom search jobs fails in a search head cluster environment. Remove the ?search=custom filter to see all search jobs including custom jobs.
delegate	For saved searches, specifies jobs that were started by the user. Defaults to scheduler.
diskUsage	The total amount of disk space used, in bytes.
dispatchState	The state of the search. Can be any of QUEUED, PARSING, RUNNING, FINALIZING, PAUSE, INTERNAL_CANCEL, USER_CANCEL, BAD_INPUT_CANCEL, QUIT, FINALIZING, FAILED, DONE.
doneProgress	A number between 0 and 1.0 that indicates the approximate progress of the search. doneProgress = (latestTime – cursorTime) / (latestTime – earliestTime)
dropCount	For real-time searches only, the number of possible events that were dropped due to the rt_queue_size (default to 100000).
earliestTime	A time string that sets the earliest (inclusive), respectively, time bounds for the search. Can be used to indicate progress. See description for `doneProgress`.
eventAvailableCount	The number of events that are available for export.
eventCount	The number of events returned by the search.
eventFieldCount	The number of fields found in the search results.
eventIsStreaming	Indicates if the events of this search are being streamed.
eventIsTruncated	Indicates if events of the search are not stored, making them unavailable from the events endpoint for the search.
eventPreviewableCount	Number of in-memory events that are not yet committed to disk. Returned if `timeline_events_preview` is enabled in `limits.conf`.
eventSearch	Subset of the entire search that is before any transforming commands. The timeline and events endpoint represents the result of this part of the search.

eventSorting	Indicates if the events of this search are sorted, and in which order.
	
	asc = ascending;
	
	desc = descending;
	
	none = not sorted

isDone	Indicates if the search has completed.
isEventPreviewEnabled	Indicates if the `timeline_events_preview` setting is enabled in `limits.conf`.
isFailed	Indicates if there was a fatal error executing the search. For example, invalid search string syntax.
isFinalized	Indicates if the search was finalized (stopped before completion).
isPaused	Indicates if the search is paused.
isPreviewEnabled	Indicates if previews are enabled.
isRealTimeSearch	Indicates if the search is a real time search.
isRemoteTimeline	Indicates if the remote timeline feature is enabled.

Name	Description
isSaved	Indicates that the search job is saved, storing search artifacts on disk for 7 days from the last time that the job was viewed or touched. Add or edit the `default_save_ttl` value in `limits.conf` to override the default value of 7 days.
isSavedSearch	Indicates if this is a saved search run using the scheduler.
isZombie	Indicates if the process running the search is dead, but with the search not finished.
keywords	All positive keywords used by this search. A positive keyword is a keyword that is not in a NOT clause.
label	Custom name created for this search.
latestTime	A time string that sets the latest (exclusive), respectively, time bounds for the search. Can be used to indicate progress. See description for `doneProgress`.
messages	Errors and debug messages.
numPreviews	Number of previews generated so far for this search job.
performance	A representation of the execution costs.
priority	An integer between 0-10 that indicates the search priority. The priority is mapped to the OS process priority. The higher the number the higher the priority. The priority can be changed using action parameter for POST search/jobs/{search_id}/control. For example, for the action parameter, specify `priority=5`. *Note:* In *nix systems, non-privileged users can only reduce the priority of a process.
remoteSearch	The search string that is sent to every search peer.
reportSearch	If reporting commands are used, the reporting search.
request	GET arguments that the search sends to splunkd.
resultCount	The total number of results returned by the search. In other words, this is the subset of scanned events (represented by the scanCount) that actually matches the search terms.
resultIsStreaming	Indicates if the final results of the search are available using streaming (for example, no transforming operations).
resultPreviewCount	The number of result rows in the latest preview results.
runDuration	Time in seconds that the search took to complete.
scanCount	The number of events that are scanned or read off disk.
searchEarliestTime	Specifies the earliest time for a search, as specified in the search command rather than the earliestTime parameter. It does not snap to the indexed data time bounds for all-time searches (something that earliestTime/latestTime does).
searchLatestTime	Specifies the latest time for a search, as specified in the search command rather than the latestTime parameter. It does not snap to the indexed data time bounds for all-time searches (something that earliestTime/latestTime does).
searchProviders	A list of all the search peers that were contacted.
sid	The search ID number.
statusBuckets	Maximum number of timeline buckets.
ttl	The time to live, or time before the search job expires after it completes.

Application usage

The user ID is implied by the authentication to the call.

Information returned for each entry includes the search job properties, such as eventCount (number of events returned), runDuration (time the search took to complete), and others. The parameters to POST /search/jobs provides details on search job properties when creating a search. Search job properties are also described in Search job properties in the Knowledge Manager Manual.

You can specify optional arguments based on the search job properties to filter the entries returned. For example, specify search=eventCount>100 as an argument to the GET operation to return searches with event counts greater than 100.

The dispatchState property is of particular interest to determine the state of a search, and can contain the following values:

CODE

```
QUEUED
   PARSING
   RUNNING
   FINALIZING
   DONE
```

```
   PAUSE
   INTERNAL_CANCEL
   USER_CANCEL
   BAD_INPUT_CANCEL
   QUIT
   FAILED
```

This operation also returns performance information for the search.

For more information refer to "View search job properties with the Search Job Inspector" in the Knowledge Manager Manual.

For more information on searches, see the Search Reference.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/jobs --get -d search="eventCount>100"
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom"
      xmlns:s="http://dev.splunk.com/ns/rest"
      xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>jobs</title>
  <id>https://localhost:8089/services/search/jobs</id>
  <updated>2011-06-21T10:12:22-07:00</updated>
  <generator version="100492"/>
  <author>
    <name>Splunk</name>
  </author>
  <opensearch:totalResults>8</opensearch:totalResults>
  <opensearch:itemsPerPage>0</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <entry>
    <title>search  index=_internal (source=*/metrics.log* OR source=*\\metrics.log*) group=per_sourcetype_thruput
        | chart sum(kb) by series | sort -sum(kb) | head 5</title>
    <id>https://localhost:8089/services/search/jobs/scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4</id>
    <updated>2011-06-21T10:10:31.000-07:00</updated>
    <link href="/services/search/jobs/scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4" rel="alternate"/>
    <published>2011-06-21T10:10:23.000-07:00</published>
    <link href="/services/search/jobs/scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4/search.log" rel="log"/>
    <link href="/services/search/jobs/scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4/events" rel="events"/>
    <link href="/services/search/jobs/scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4/results" rel="results"/>
    <link href="/services/search/jobs/scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4/results_preview"
rel="results_preview"/>
    <link href="/services/search/jobs/scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4/timeline" rel="timeline"/>
    <link href="/services/search/jobs/scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4/summary" rel="summary"/>
    <link href="/services/search/jobs/scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4/control" rel="control"/>
    <author>
      <name>splunk-system-user</name>
    </author>
    <content type="text/xml">
      <s:dict>
        <s:key name="cursorTime">1969-12-31T16:00:00.000-08:00</s:key>
        <s:key name="delegate">scheduler</s:key>
        <s:key name="diskUsage">73728</s:key>
        <s:key name="dispatchState">DONE</s:key>
        <s:key name="doneProgress">1.00000</s:key>
        <s:key name="dropCount">0</s:key>
        <s:key name="earliestTime">2011-06-20T10:10:00.000-07:00</s:key>
        <s:key name="eventAvailableCount">0</s:key>
        <s:key name="eventCount">1363</s:key>
        <s:key name="eventFieldCount">0</s:key>
        <s:key name="eventIsStreaming">1</s:key>
        <s:key name="eventIsTruncated">1</s:key>
        <s:key name="eventSearch">search index=_internal (source=*/metrics.log* OR source=*\\metrics.log*) group=per_sourcetype_thruput </s:key>
        <s:key name="eventSorting">none</s:key>
        <s:key name="isDone">1</s:key>
        <s:key name="isFailed">0</s:key>
        <s:key name="isFinalized">0</s:key>
        <s:key name="isPaused">0</s:key>
        <s:key name="isPreviewEnabled">0</s:key>
        <s:key name="isRealTimeSearch">0</s:key>
        <s:key name="isRemoteTimeline">0</s:key>
        <s:key name="isSaved">0</s:key>
        <s:key name="isSavedSearch">1</s:key>
        <s:key name="isZombie">0</s:key>
        <s:key name="keywords">group::per_sourcetype_thruput index::_internal source::*/metrics.log* source::*\metrics.log*</s:key>
        <s:key name="label">Top five sourcetypes</s:key>
        <s:key name="latestTime">2011-06-21T10:10:00.000-07:00</s:key>
        <s:key name="numPreviews">0</s:key>
        <s:key name="priority">5</s:key>
        <s:key name="remoteSearch">litsearch index=_internal ( source=*/metrics.log* OR source=*\\metrics.log* )
                group=per_sourcetype_thruput | addinfo  type=count label=prereport_events
                | fields  keepcolorder=t "kb" "prestats_reserved_*" "psrsvd_*" "series"
```

```
       | convert  num("kb")  | prestats  sum(kb) AS "sum(kb)" by series</s:key>
<s:key name="reportSearch">chart  sum(kb) by series  | sort  -sum(kb)  | head  5</s:key>
<s:key name="resultCount">4</s:key>
<s:key name="resultIsStreaming">0</s:key>
<s:key name="resultPreviewCount">4</s:key>
<s:key name="runDuration">0.259000</s:key>
<s:key name="scanCount">1363</s:key>
<s:key name="searchEarliestTime">1308589800.000000000</s:key>
<s:key name="searchLatestTime">1308676200.000000000</s:key>
<s:key name="sid">scheduler__nobody__search_VG9wIGZpdmUgc291cmNldHlwZXM_at_1308676200_22702c154383bbe4</s:key>
<s:key name="statusBuckets">0</s:key>
<s:key name="ttl">489</s:key>
<s:key name="performance">
  <s:dict>
    <s:key name="command.addinfo">
      <s:dict>
        <s:key name="duration_secs">0.005</s:key>
        <s:key name="invocations">5</s:key>
        <s:key name="input_count">1363</s:key>
        <s:key name="output_count">1363</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.chart">
      <s:dict>
        <s:key name="duration_secs">0.003</s:key>
        <s:key name="invocations">1</s:key>
        <s:key name="input_count">100000</s:key>
        <s:key name="output_count">4</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.convert">
      <s:dict>
        <s:key name="duration_secs">0.006</s:key>
        <s:key name="invocations">5</s:key>
        <s:key name="input_count">1363</s:key>
        <s:key name="output_count">1363</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.fields">
      <s:dict>
        <s:key name="duration_secs">0.005</s:key>
        <s:key name="invocations">5</s:key>
        <s:key name="input_count">1363</s:key>
        <s:key name="output_count">1363</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.head">
      <s:dict>
        <s:key name="duration_secs">0.001</s:key>
        <s:key name="invocations">1</s:key>
        <s:key name="input_count">4</s:key>
        <s:key name="output_count">4</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.presort">
      <s:dict>
        <s:key name="duration_secs">0.001</s:key>
        <s:key name="invocations">1</s:key>
        <s:key name="input_count">4</s:key>
        <s:key name="output_count">4</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.prestats">
      <s:dict>
        <s:key name="duration_secs">0.014</s:key>
        <s:key name="invocations">5</s:key>
        <s:key name="input_count">1363</s:key>
        <s:key name="output_count">12</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.search">
      <s:dict>
        <s:key name="duration_secs">0.058</s:key>
        <s:key name="invocations">5</s:key>
        <s:key name="input_count">0</s:key>
        <s:key name="output_count">1363</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.search.fieldalias">
      <s:dict>
        <s:key name="duration_secs">0.003</s:key>
        <s:key name="invocations">3</s:key>
        <s:key name="input_count">1363</s:key>
        <s:key name="output_count">1363</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.search.filter">
      <s:dict>
        <s:key name="duration_secs">0.004</s:key>
        <s:key name="invocations">3</s:key>
      </s:dict>
```

```
</s:key>
<s:key name="command.search.index">
  <s:dict>
    <s:key name="duration_secs">0.010</s:key>
    <s:key name="invocations">5</s:key>
  </s:dict>
</s:key>
<s:key name="command.search.kv">
  <s:dict>
    <s:key name="duration_secs">0.011</s:key>
    <s:key name="invocations">3</s:key>
  </s:dict>
</s:key>
<s:key name="command.search.lookups">
  <s:dict>
    <s:key name="duration_secs">0.003</s:key>
    <s:key name="invocations">3</s:key>
    <s:key name="input_count">1363</s:key>
    <s:key name="output_count">1363</s:key>
  </s:dict>
</s:key>
<s:key name="command.search.rawdata">
  <s:dict>
    <s:key name="duration_secs">0.034</s:key>
    <s:key name="invocations">3</s:key>
  </s:dict>
</s:key>
<s:key name="command.search.tags">
  <s:dict>
    <s:key name="duration_secs">0.005</s:key>
    <s:key name="invocations">5</s:key>
    <s:key name="input_count">1363</s:key>
    <s:key name="output_count">1363</s:key>
  </s:dict>
</s:key>
<s:key name="command.search.typer">
  <s:dict>
    <s:key name="duration_secs">0.005</s:key>
    <s:key name="invocations">5</s:key>
    <s:key name="input_count">1363</s:key>
    <s:key name="output_count">1363</s:key>
  </s:dict>
</s:key>
<s:key name="command.sort">
  <s:dict>
    <s:key name="duration_secs">0.001</s:key>
    <s:key name="invocations">1</s:key>
    <s:key name="input_count">4</s:key>
    <s:key name="output_count">4</s:key>
  </s:dict>
</s:key>
<s:key name="dispatch.createProviderQueue">
  <s:dict>
    <s:key name="duration_secs">0.067</s:key>
    <s:key name="invocations">1</s:key>
  </s:dict>
</s:key>
<s:key name="dispatch.evaluate">
  <s:dict>
    <s:key name="duration_secs">0.038</s:key>
    <s:key name="invocations">1</s:key>
  </s:dict>
</s:key>
<s:key name="dispatch.evaluate.chart">
  <s:dict>
    <s:key name="duration_secs">0.001</s:key>
    <s:key name="invocations">1</s:key>
  </s:dict>
</s:key>
<s:key name="dispatch.evaluate.head">
  <s:dict>
    <s:key name="duration_secs">0.001</s:key>
    <s:key name="invocations">1</s:key>
  </s:dict>
</s:key>
<s:key name="dispatch.evaluate.search">
  <s:dict>
    <s:key name="duration_secs">0.037</s:key>
    <s:key name="invocations">1</s:key>
  </s:dict>
</s:key>
<s:key name="dispatch.evaluate.sort">
  <s:dict>
    <s:key name="duration_secs">0.001</s:key>
    <s:key name="invocations">1</s:key>
  </s:dict>
</s:key>
<s:key name="dispatch.fetch">
  <s:dict>
    <s:key name="duration_secs">0.126</s:key>
    <s:key name="invocations">6</s:key>
```

```
            </s:dict>
          </s:key>
          <s:key name="dispatch.stream.local">
            <s:dict>
              <s:key name="duration_secs">0.070</s:key>
              <s:key name="invocations">5</s:key>
            </s:dict>
          </s:key>
        </s:dict>
      </s:key>
      <s:key name="messages">
        <s:dict/>
      </s:key>
      <s:key name="request">
        <s:dict>
          <s:key name="ui_dispatch_app"></s:key>
          <s:key name="ui_dispatch_view"></s:key>
        </s:dict>
      </s:key>
      <s:key name="eai:acl">
        <s:dict>
          <s:key name="perms">
            <s:dict>
              <s:key name="read">
                <s:list>
                  <s:item>admin</s:item>
                </s:list>
              </s:key>
              <s:key name="write">
                <s:list>
                  <s:item>admin</s:item>
                </s:list>
              </s:key>
            </s:dict>
          </s:key>
          <s:key name="owner">nobody</s:key>
          <s:key name="modifiable">true</s:key>
          <s:key name="sharing">global</s:key>
          <s:key name="app">search</s:key>
          <s:key name="can_write">true</s:key>
        </s:dict>
      </s:key>
      <s:key name="searchProviders">
        <s:list>
          <s:item>mbp15.splunk.com</s:item>
        </s:list>
      </s:key>
    </s:dict>
  </content>
 </entry>
 . . . elided . . .
</feed>
```

POST

Start a new search and return the search ID (<sid>)

Request parameters

Name	Type	Default	Description
adhoc_search_level	String		Use one of the following search modes. CODE `[ verbose | fast | smart ]` If `adhoc_search_level` is not specified, the default mode is `fast`.
allow_partial_results	Boolean	true	Indicates whether the search job can proceed to provide partial results if a search peer fails. When set to `false`, the search job fails if a search peer providing results for the search job fails.
auto_cancel	Number	0	If specified, the job automatically cancels after this many seconds of inactivity. (0 means never auto-cancel)
auto_finalize_ec	Number	0	Auto-finalize the search after at least this many events are processed. Specify `0` to indicate no limit.

Name	Type	Default	Description
auto_pause	Number	0	If specified, the search job pauses after this many seconds of inactivity. (0 means never auto-pause.) To restart a paused search job, specify unpause as an action to POST search/jobs/{search_id}/control. auto_pause only goes into effect once. Unpausing after auto_pause does not put auto_pause into effect again.
custom	String		Specify a custom parameter (see example).
earliest_time	String		Specify a time string. Sets the earliest (inclusive), respectively, time bounds for the search. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Refer to Time modifiers for search for information and examples of specifying a time string. Compare to `index_earliest` parameter. Also see comment for the `search_mode` parameter.
enable_lookups	Boolean	true	Indicates whether lookups should be applied to events. Specifying true (the default) may slow searches significantly depending on the nature of the lookups.
exec_mode	Enum	normal	Valid values: (blocking | oneshot | normal) If set to normal, runs an asynchronous search. If set to blocking, returns the sid when the job is complete. If set to oneshot, returns results in the same call. In this case, you can specify the format for the output (for example, json output) using the output_mode parameter as described in GET search/jobs/export. Default format for output is xml. Does not return the search ID.
force_bundle_replication	Boolean	false	Specifies whether this search should cause (and wait depending on the value of sync_bundle_replication) for bundle synchronization with all search peers.
id	String		Optional string to specify the search ID (`<sid>`). If unspecified, a random ID is generated.
index_earliest	String		Specify a time string. Sets the earliest (inclusive), respectively, time bounds for the search, based on the index time bounds. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Compare to `earliest_time` parameter. Also see comment for the `search_mode` parameter. Refer to Time modifiers for search for information and examples of specifying a time string.

Name	Type	Default	Description
index_latest	String		Specify a time string. Sets the latest (exclusive), respectively, time bounds for the search, based on the index time bounds. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Refer to Time modifiers for search for information and examples of specifying a time string. Compare to `latest_time` parameter. Also see comment for the `search_mode` parameter.
indexedRealtime	Boolean		Indicate whether or not to used indexed-realtime mode for real-time searches.
indexedRealtimeOffset	Number		Set disk sync delay for indexed real-time search (seconds).
latest_time	String		Specify a time string. Sets the latest (exclusive), respectively, time bounds for the search. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Refer to Time modifiers for search for information and examples of specifying a time string. Compare to `index_latest` parameter. Also see comment for the `search_mode` parameter.
max_count	Number	10000	The number of events that can be accessible in any given status bucket. Also, in transforming mode, the maximum number of results to store. Specifically, in all calls, `codeoffset+count max_count`.
max_time	Number	0	The number of seconds to run this search before finalizing. Specify `0` to never finalize.
namespace	String		The application namespace in which to restrict searches. The namespace corresponds to the identifier recognized in the `/services/apps/local` endpoint.
now	String	current system time	Specify a time string to set the absolute time used for any relative time specifier in the search. Defaults to the current system time. You can specify a relative time modifier for this parameter. For example, specify `+2d` to specify the current time plus two days. If you specify a relative time modifier both in this parameter and in the search string, the search string modifier takes precedence. Refer to Time modifiers for search for details on specifying relative time modifiers.
reduce_freq	Number	0	Determines how frequently to run the MapReduce reduce phase on accumulated map values.
reload_macros	Boolean	true	Specifies whether to reload macro definitions from `macros.conf`. Default is true.
remote_server_list	String	empty list	Comma-separated list of (possibly wildcarded) servers from which raw events should be pulled. This same server list is to be used in subsearches.

Name	Type	Default	Description

replay_speed	Number greater than 0		Indicate a real-time search replay speed factor. For example, `1` indicates normal speed. `0.5` indicates half of normal speed, and `2` indicates twice as fast as normal.
			
			`earliest_time` and `latest_time` arguments must indicate a real-time time range to use replay options.
			
			Use *replay_speed* with *replay_et* and *replay_lt* relative times to indicate a speed and time range for the replay. For example,
			
			CODE
			
			`replay_speed = 10`
			`replay_et = -d@d`
			`replay_lt = -@d`
			
			specifies a replay at 10x speed, as if the "wall clock" time starts yesterday at midnight and ends when it reaches today at midnight.
			
			For more information about using relative time modifiers, see Search time modifiers in the *Search reference*.

replay_et	Time modifier string		Relative "wall clock" start time for the replay.
replay_lt	Time modifier string.		Relative end time for the replay clock. The replay stops when clock time reaches this time.
required_field_list	String	empty list	[Deprecated] Use *rf*. A comma-separated list of required fields that, even if not referenced or used directly by the search, is still included by the events and summary endpoints. Splunk Web uses these fields to prepopulate panels in the Search view.
reuse_max_seconds_ago	Number		Specifies the number of seconds ago to check when an identical search is started and return the job's search ID instead of starting a new job.
rf	String		Adds a required field to the search. There can be multiple `rf` POST arguments to the search. These fields, even if not referenced or used directly by the search, are still included by the events and summary endpoints. Splunk Web uses these fields to prepopulate panels in the Search view. Consider using this form of passing the required fields to the search instead of the deprecated *required_field_list*. If both *rf* and *required_field_list* are provided, the union of the two lists is used.
rt_blocking	Boolean	false	For a real-time search, indicates if the indexer blocks if the queue for this search is full.
rt_indexfilter	Boolean	true	For a real-time search, indicates if the indexer prefilters events.
rt_maxblocksecs	Number	60	For a real-time search with rt_blocking set to true, the maximum time to block. Specify `0` to indicate no limit.
rt_queue_size	Number	10000 events	For a real-time search, the queue size (in events) that the indexer should use for this search.

search
required
	String		The search language string to execute, taking results from the local and remote servers.
			
			Examples:
			
			`"search *"`
			
			`"search * | outputcsv"`

Name	Type	Default	Description
search_listener	String		[Disabled] Registers a search state listener with the search. Use the format: search_state;results_condition;http_method;uri; For example: search_listener=onResults;true;POST;/servicesNS/admin/search/saved/search/foobar/notify;
search_mode	Enum	normal	Valid values: (normal | realtime) If set to `realtime`, search runs over live data. A real-time search may also be indicated by earliest_time and latest_time variables starting with 'rt' even if the search_mode is set to normal or is unset. For a real-time search, if both earliest_time and latest_time are both exactly 'rt', the search represents all appropriate live data received since the start of the search. Additionally, if earliest_time and/or latest_time are 'rt' followed by a relative time specifiers then a sliding window is used where the time bounds of the window are determined by the relative time specifiers and are continuously updated based on the wall-clock time.
spawn_process	Boolean	true	This parameter is deprecated and will be removed in a future release. Do not use this parameter. Specifies whether the search should run in a separate spawned process. Default is true. Searches against indexes *must* run in a separate process.
status_buckets	Number	0	The most status buckets to generate. `0` indicates to not generate timeline information.
sync_bundle_replication	Boolean		Specifies whether this search should wait for bundle replication to complete.
time_format	String	%FT%T.%Q%:z	Used to convert a formatted time string from {start,end}_time into UTC seconds. The default value is the ISO-8601 format.
timeout	Number	86400	The number of seconds to keep this search after processing has stopped.
workload_pool	String		Specifies the new workload pool where the existing running search should be placed.

Returned values

Name	Description
sid	Search ID

Application usage

Refer to Creating searches using the REST API for information on using this endpoint and other search endpoints.

The search parameter is a search language string that specifies the search. Often you create a search specifying just the search parameter. Use the other parameters to customize a search to specific needs.

Use the returned (<sid>) in the following endpoints to view and manage the search:

JSON

```
search/jobs/{search_id}: View the status of this search job.
```

JSON

search/jobs/{search_id}/control: Execute job control commands, such as pause, cancel, preview, and others.

JSON

search/jobs/{search_id}/events: View a set of untransformed events for the search.

JSON

search/jobs/{search_id}/results: View results of the search.

JSON

search/jobs/{search_id}/results_preview: Preview results of a search that has not completed

JSON

search/jobs/{search_id}/search.log: View the log file generated by the search.

JSON

search/jobs/{search_id}/summary: View field summary information

JSON

search/jobs/{search_id}/timeline: View event distribution over time.

You can also use the custom attribute to create custom job properties (see example).

For more information on searches, see the Splunk Search Reference.

Example request and response

Request

- Basic example:

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/search/jobs --data-urlencode search="search index=_internal source=*/metrics.log" -
d id=mysearch_02151949 -d max_count=50000 -d status_buckets=300
```

- Create custom property example:

CODE

```
curl -u admin:changeme -k https://localhost:8089/services/search/jobs
    -d search="search *"
    -d custom.foobar="myCustomPropA"
    -d custom.foobaz="myCustomPropB"
```

Use the search/jobs GET request to view the custom properties.

- Create indexed real-time search with five second disk sync delay example:

CODE

```
curl -k -u admin:changed https://localhost:8089/services/search/jobs
    -d search="search index=_* *"
    -d search_mode="realtime"
    -d indexedRealtime="1"
    -d indexedRealtimeOffset="300"
```

Response

CODE

```
<response><sid>mysearch_02151949</sid></response>
```

search/v2/jobs/export

CODE

```
https://<host>:<mPort>/services/search/v2/jobs/export
```

Stream search results as they become available.

The POST operation on this endpoint performs a search identical to a POST to `search/jobs`. For parameter and returned value descriptions, see search/jobs.

The GET operation is not available in the v2 iteration of this endpoint.

POST

Performs a search identical to POST search/jobs. For parameter and returned value descriptions, see the POST parameter descriptions for search/jobs.

Request parameters

Name	Type	Default	Description
search	String		See the parameters and returned values for search/jobs.
auto_cancel	Number		See the parameters and returned values for search/jobs.
auto_finalize_ec	Number		See the parameters and returned values for search/jobs.
auto_pause	Number		See the parameters and returned values for search/jobs.
earliest_time	String		See the parameters and returned values for search/jobs.
enable_lookups	Bool		See the parameters and returned values for search/jobs.
force_bundle_replication	Bool		See the parameters and returned values for search/jobs.
id	String		See the parameters and returned values for search/jobs.
index_earliest	String		Specify a time string. Sets the earliest (inclusive), respectively, time bounds for the search, based on the index time. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Refer to Time modifiers for search for information and examples of specifying a time string.
index_latest	String		Specify a time string. Sets the latest (inclusive), respectively, time bounds for the search, based on the index time. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Refer to Time modifiers for search for information and examples of specifying a time string.
latest_time	String		See the parameters and returned values for search/jobs.
max_time	Number		See the parameters and returned values for search/jobs.
namespace	String		See the parameters and returned values for search/jobs.
now	String		See the parameters and returned values for search/jobs.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
reduce_freq	Number		See the parameters and returned values for search/jobs.
reload_macros	Bool		See the parameters and returned values for search/jobs.
remote_server_list	String		See the parameters and returned values for search/jobs.
required_field_list	String		See the parameters and returned values for search/jobs.
rf	String		See the parameters and returned values for search/jobs.
rt_blocking	Bool		See the parameters and returned values for search/jobs.
rt_indexfilter	Bool		See the parameters and returned values for search/jobs.

Name	Type	Default	Description
rt_maxblocksecs	Number		See the parameters and returned values for search/jobs.
rt_queue_size	Number		See the parameters and returned values for search/jobs.
search_listener	String		See the parameters and returned values for search/jobs.
search_mode	Enum		See the parameters and returned values for search/jobs.
sync_bundle_replication	Bool		See the parameters and returned values for search/jobs.
time_format	String		See the parameters and returned values for search/jobs.
timeout	Number		See the parameters and returned values for search/jobs.

Returned values

None

Application usage

Streaming of results is based on the search string.

For non-streaming searches, previews of the final results are available if preview is enabled. If preview is not enabled, use search/jobs with exec_mode=oneshot.

If your search is too big, considering running it with the search/jobs endpoint, instead of the search/jobs/export endpoint, and using exec_mode=blocking. You'll then get back a search id, and then you can page through the results and request them from the server under your control. This is a better approach for extremely large result sets that need to be chunked.

Example

The following example runs a saved search and passes a variable to it. In this case, the variable is the host field:

CODE

```
$curl -k -u admin:password https://splunkserver:8089/services/search/v2/jobs/export -d search="savedsearch \ MySavedSearch%20host%3Dwolverine*"
```

This request creates a saved search named "MySavedSearch" which contains the following result:

CODE

```
"index=main $host$ | head 100"
```

search/jobs/export (deprecated)

CODE

```
https://<host>:<mPort>/services/search/jobs/export
```

Stream search results as they become available.

The GET and POST operations on this endpoint perform a search identical to a POST to `search/jobs`. For parameter and returned value descriptions, see search/jobs.

Note: This endpoint is deprecated as of Splunk Enterprise 9.0.1. Use the v2 instance of this endpoint instead.

GET

Performs a search identical to POST search/jobs

Request parameters

See the POST operation on search/jobs for parameter descriptions.

Name	Type	Default	Description
auto_cancel	Number		See the POST parameter descriptions for search/jobs
auto_finalize_ec	Number		See the POST parameter descriptions for search/jobs

Name	Type	Default	Description
auto_pause	Number		See the POST parameter descriptions for search/jobs
earliest_time	String		See the POST parameter descriptions for search/jobs
enable_lookups	Bool		See the POST parameter descriptions for search/jobs
force_bundle_replication	Bool		See the POST parameter descriptions for search/jobs
id	String		See the POST parameter descriptions for search/jobs
index_earliest	String		Specify a time string. Sets the earliest (inclusive), respectively, time bounds for the search, based on the index time. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Refer to Time modifiers for search for information and examples of specifying a time string.
index_latest	String		Specify a time string. Sets the latest (inclusive), respectively, time bounds for the search, based on the index time. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Refer to Time modifiers for search for information and examples of specifying a time string.
latest_time	String		See the POST parameter descriptions for search/jobs
max_time	Number		See the POST parameter descriptions for search/jobs
namespace	String		See the POST parameter descriptions for search/jobs
now	String		See the POST parameter descriptions for search/jobs
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
reduce_freq	Number		See the POST parameter descriptions for search/jobs
reload_macros	Bool		See the POST parameter descriptions for search/jobs
remote_server_list	String		See the POST parameter descriptions for search/jobs
required_field_list	String		See the POST parameter descriptions for search/jobs
rf	String		See the POST parameter descriptions for search/jobs
rt_blocking	Bool		See the POST parameter descriptions for search/jobs
rt_indexfilter	Bool		See the POST parameter descriptions for search/jobs
rt_maxblocksecs	Number		See the POST parameter descriptions for search/jobs
rt_queue_size	Number		See the POST parameter descriptions for search/jobs
search required	String		See the POST parameter descriptions for search/jobs
search_listener	String		See the POST parameter descriptions for search/jobs

Name	Type	Default	Description
search_mode	Enum		See the POST parameter descriptions for search/jobs
sync_bundle_replication	Bool		See the POST parameter descriptions for search/jobs
time_format	String		See the POST parameter descriptions for search/jobs
timeout	Number		See the POST parameter descriptions for search/jobs

Returned values

None

Application usage

Performs a search identical to POST `search/jobs`, except the search streams results as they become available. Streaming of results is based on the search string.

For non-streaming searches, previews of the final results are available if preview is enabled. If preview is not enabled, use the `search/jobs` endpoint with `exec_mode=oneshot` to retrieve results from them.

If the result set returned by a non-streaming search is significantly large, use the `search/jobs` endpoint with `exec_mode=blocking`. This approach lets you page through the results and request them from a server under your control.

Example request and response

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/search/jobs/export -d search="search index%3D_internal | head 1"
```

XML Response

CODE

```
<results preview='0'>
<meta>
<fieldOrder>
<field>_cd</field>
<field>_indextime</field>
<field>_raw</field>
<field>_serial</field>
<field>_si</field>
<field>_sourcetype</field>
<field>_subsecond</field>
<field>_time</field>
<field>host</field>
<field>index</field>
<field>linecount</field>
<field>source</field>
<field>sourcetype</field>
<field>splunk_server</field>
</fieldOrder>
</meta>
<messages>
  <msg type="DEBUG">base lispy: [ AND index::_internal ]</msg>
  <msg type="DEBUG">search context: user="admin", app="search", bs-pathname="/Applications/splunk/etc"</msg>
  <msg type="INFO">Your timerange was substituted based on your search string</msg>
</messages>

  <result offset='0'>
    <field k='_cd'>
      <value><text>50:59480</text></value>
    </field>
    <field k='_indextime'>
      <value><text>1333739623</text></value>
    </field>
    <field k='_raw'><v xml:space='preserve' trunc='0'>127.0.0.1 - admin [06/Apr/2012:12:13:42.943 -0700] "POST
/servicesNS/admin/search/search/jobs/export HTTP/1.1" 200 2063 - - - 317ms</v></field>
    <field k='_serial'>
      <value><text>0</text></value>
    </field>
    <field k='_si'>
      <value><text>mbp15.splunk.com</text></value>
      <value><text>_internal</text></value>
    </field>
    <field k='_sourcetype'>
      <value><text>splunkd_access</text></value>
    </field>
    <field k='_subsecond'>
      <value><text>.943</text></value>
    </field>
    <field k='_time'>
      <value><text>2012-04-06 12:13:42.943 PDT</text></value>
```

```
    </field>
    <field k='host'>
      <value><text>mbp15.splunk.com</text></value>
    </field>
    <field k='index'>
      <value h='1'><text>_internal</text></value>
    </field>
    <field k='linecount'>
      <value><text>1</text></value>
    </field>
    <field k='source'>
      <value><text>/Applications/splunk/var/log/splunk/splunkd_access.log</text></value>
    </field>
    <field k='sourcetype'>
      <value><text>splunkd_access</text></value>
    </field>
    <field k='splunk_server'>
      <value><text>mbp15.splunk.com</text></value>
    </field>
  </result>
</results>
```

POST

Performs a search identical to POST search/jobs. For parameter and returned value descriptions, see the POST parameter descriptions for search/jobs.

Request parameters

Name	Type	Default	Description
search	String		See the parameters and returned values for search/jobs.
auto_cancel	Number		See the parameters and returned values for search/jobs.
auto_finalize_ec	Number		See the parameters and returned values for search/jobs.
auto_pause	Number		See the parameters and returned values for search/jobs.
earliest_time	String		See the parameters and returned values for search/jobs.
enable_lookups	Bool		See the parameters and returned values for search/jobs.
force_bundle_replication	Bool		See the parameters and returned values for search/jobs.
id	String		See the parameters and returned values for search/jobs.
index_earliest	String		Specify a time string. Sets the earliest (inclusive), respectively, time bounds for the search, based on the index time. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Refer to Time modifiers for search for information and examples of specifying a time string.
index_latest	String		Specify a time string. Sets the latest (inclusive), respectively, time bounds for the search, based on the index time. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. Refer to Time modifiers for search for information and examples of specifying a time string.
latest_time	String		See the parameters and returned values for search/jobs.
max_time	Number		See the parameters and returned values for search/jobs.
namespace	String		See the parameters and returned values for search/jobs.

Name	Type	Default	Description
now	String		See the parameters and returned values for search/jobs.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
reduce_freq	Number		See the parameters and returned values for search/jobs.
reload_macros	Bool		See the parameters and returned values for search/jobs.
remote_server_list	String		See the parameters and returned values for search/jobs.
required_field_list	String		See the parameters and returned values for search/jobs.
rf	String		See the parameters and returned values for search/jobs.
rt_blocking	Bool		See the parameters and returned values for search/jobs.
rt_indexfilter	Bool		See the parameters and returned values for search/jobs.
rt_maxblocksecs	Number		See the parameters and returned values for search/jobs.
rt_queue_size	Number		See the parameters and returned values for search/jobs.
search_listener	String		See the parameters and returned values for search/jobs.
search_mode	Enum		See the parameters and returned values for search/jobs.
sync_bundle_replication	Bool		See the parameters and returned values for search/jobs.
time_format	String		See the parameters and returned values for search/jobs.
timeout	Number		See the parameters and returned values for search/jobs.

Returned values

None

Application usage

Streaming of results is based on the search string.

For non-streaming searches, previews of the final results are available if preview is enabled. If preview is not enabled, it is better to use search/jobs with exec_mode=oneshot.

If it is too big, you might instead run with the search/jobs (not search/jobs/export) endpoint (it takes POST with the same parameters), maybe using the exec_mode=blocking. You'll then get back a search id, and then you can page through the results and request them from the server under your control, which is a better approach for extremely large result sets that need to be chunked.

Example of how to pass a variable to query when using REST API:

This is an example of running a saved search and passing a variable to it. In this case, the variable is host field:

$curl -k -u admin:password https://splunkserver:8089/services/search/jobs/export -d search="savedsearch \ MySavedSearch%20host%3Dwolverine*"

(use "MySavedSearch" and input variable host=wolverine*)

I have a saved search named "MySavedSearch" the query of the search contains:

"index=main $host$ | head 100"

search/jobs/{search_id}

JSON

```
https://<host>:<mPort>/services/search/jobs/{search_id}
```

Manage the {search_id} search job.

DELETE

Delete the {search_id} search job.

Request parameters

None

Returned values

None

Application usage

{search_id} is the <sid> field returned from the GET operation for the search/jobs endpoint.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass --request DELETE https://localhost:8089/services/search/jobs/mysearch_02151949
```

XML Response

CODE

```
<response><messages><msg type='INFO'>Search job cancelled.</msg></messages></response
```

GET

Get information about the {search_id} search job.

Request parameters

None

Returned values

None

Application usage

The user ID is implied by the authentication to the call.

Information returned includes the search job properties, such as eventCount (number of events returned), runDuration (time the search took to complete), and others. The parameters to POST /search/jobs provides details on search job properties when creating a search. Search job properties are also described in View search job properties in the *Search Manual*.

The dispatchState property is of particular interest to determine the state of a search, and can contain the following values:

CODE

```
QUEUED
   PARSING
   RUNNING
   FINALIZING
   DONE
   PAUSE
   INTERNAL_CANCEL
   USER_CANCEL
   BAD_INPUT_CANCEL
   QUIT
   FAILED
```

This operation also returns performance information for the search. For more information refer to View search job properties in the *Search Manual*.

For more information on searches in Splunk, refer to the Splunk Search Reference.

POST /search/jobs returns a <sid> for a search. You can also get a search ID from the <sid> field returned from GET search/jobs.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/jobs/mysearch_02151949
```

XML Response

CODE

```
<entry
       xmlns="http://www.w3.org/2005/Atom"
       xmlns:s="http://dev.splunk.com/ns/rest"
       xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>search index</title>
  <id>https://localhost:8089/services/search/jobs/mysearch_02151949</id>
  <updated>2011-07-07T20:49:58.000-07:00</updated>
  <link href="/services/search/jobs/mysearch_02151949" rel="alternate"/>
  <published>2011-07-07T20:49:57.000-07:00</published>
  <link href="/services/search/jobs/mysearch_02151949/search.log" rel="search.log"/>
  <link href="/services/search/jobs/mysearch_02151949/events" rel="events"/>
  <link href="/services/search/jobs/mysearch_02151949/results" rel="results"/>
  <link href="/services/search/jobs/mysearch_02151949/results_preview" rel="results_preview"/>
  <link href="/services/search/jobs/mysearch_02151949/timeline" rel="timeline"/>
  <link href="/services/search/jobs/mysearch_02151949/summary" rel="summary"/>
  <link href="/services/search/jobs/mysearch_02151949/control" rel="control"/>
  <author>
    <name>admin</name>
  </author>
  <content type="text/xml">
    <s:dict>
      <s:key name="cursorTime">1969-12-31T16:00:00.000-08:00</s:key>
      <s:key name="delegate"></s:key>
      <s:key name="diskUsage">2174976</s:key>
      <s:key name="dispatchState">DONE</s:key>
      <s:key name="doneProgress">1.00000</s:key>
      <s:key name="dropCount">0</s:key>
      <s:key name="earliestTime">2011-07-07T11:18:08.000-07:00</s:key>
      <s:key name="eventAvailableCount">287</s:key>
      <s:key name="eventCount">287</s:key>
      <s:key name="eventFieldCount">6</s:key>
      <s:key name="eventIsStreaming">1</s:key>
      <s:key name="eventIsTruncated">0</s:key>
      <s:key name="eventSearch">search index</s:key>
      <s:key name="eventSorting">desc</s:key>
      <s:key name="isDone">1</s:key>
      <s:key name="isFailed">0</s:key>
      <s:key name="isFinalized">0</s:key>
      <s:key name="isPaused">0</s:key>
      <s:key name="isPreviewEnabled">0</s:key>
      <s:key name="isRealTimeSearch">0</s:key>
      <s:key name="isRemoteTimeline">0</s:key>
      <s:key name="isSaved">0</s:key>
      <s:key name="isSavedSearch">0</s:key>
      <s:key name="isZombie">0</s:key>
      <s:key name="keywords">index</s:key>
      <s:key name="label"></s:key>
      <s:key name="latestTime">1969-12-31T16:00:00.000-08:00</s:key>
      <s:key name="numPreviews">0</s:key>
      <s:key name="priority">5</s:key>
      <s:key name="remoteSearch">litsearch index | fields  keepcolorder=t "host" "index" "linecount" "source" "sourcetype" "splunk_server"</s:key>
      <s:key name="reportSearch"></s:key>
      <s:key name="resultCount">287</s:key>
      <s:key name="resultIsStreaming">1</s:key>
      <s:key name="resultPreviewCount">287</s:key>
      <s:key name="runDuration">1.004000</s:key>
      <s:key name="scanCount">287</s:key>
      <s:key name="sid">mysearch_02151949</s:key>
      <s:key name="statusBuckets">0</s:key>
      <s:key name="ttl">516</s:key>
      <s:key name="performance">
        <s:dict>
          <s:key name="command.fields">
            <s:dict>
              <s:key name="duration_secs">0.004</s:key>
              <s:key name="invocations">4</s:key>
              <s:key name="input_count">287</s:key>
              <s:key name="output_count">287</s:key>
            </s:dict>
          </s:key>
          <s:key name="command.search">
            <s:dict>
              <s:key name="duration_secs">0.089</s:key>
              <s:key name="invocations">4</s:key>
              <s:key name="input_count">0</s:key>
              <s:key name="output_count">287</s:key>
            </s:dict>
          </s:key>
          <s:key name="command.search.fieldalias">
            <s:dict>
              <s:key name="duration_secs">0.002</s:key>
              <s:key name="invocations">2</s:key>
              <s:key name="input_count">287</s:key>
              <s:key name="output_count">287</s:key>
            </s:dict>
          </s:key>
          <s:key name="command.search.index">
```

```
      <s:dict>
        <s:key name="duration_secs">0.005</s:key>
        <s:key name="invocations">4</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.search.kv">
      <s:dict>
        <s:key name="duration_secs">0.002</s:key>
        <s:key name="invocations">2</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.search.lookups">
      <s:dict>
        <s:key name="duration_secs">0.002</s:key>
        <s:key name="invocations">2</s:key>
        <s:key name="input_count">287</s:key>
        <s:key name="output_count">287</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.search.rawdata">
      <s:dict>
        <s:key name="duration_secs">0.083</s:key>
        <s:key name="invocations">2</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.search.tags">
      <s:dict>
        <s:key name="duration_secs">0.004</s:key>
        <s:key name="invocations">4</s:key>
        <s:key name="input_count">287</s:key>
        <s:key name="output_count">287</s:key>
      </s:dict>
    </s:key>
    <s:key name="command.search.typer">
      <s:dict>
        <s:key name="duration_secs">0.004</s:key>
        <s:key name="invocations">4</s:key>
        <s:key name="input_count">287</s:key>
        <s:key name="output_count">287</s:key>
      </s:dict>
    </s:key>
    <s:key name="dispatch.createProviderQueue">
      <s:dict>
        <s:key name="duration_secs">0.059</s:key>
        <s:key name="invocations">1</s:key>
      </s:dict>
    </s:key>
    <s:key name="dispatch.evaluate">
      <s:dict>
        <s:key name="duration_secs">0.037</s:key>
        <s:key name="invocations">1</s:key>
      </s:dict>
    </s:key>
    <s:key name="dispatch.evaluate.search">
      <s:dict>
        <s:key name="duration_secs">0.036</s:key>
        <s:key name="invocations">1</s:key>
      </s:dict>
    </s:key>
    <s:key name="dispatch.fetch">
      <s:dict>
        <s:key name="duration_secs">0.092</s:key>
        <s:key name="invocations">5</s:key>
      </s:dict>
    </s:key>
    <s:key name="dispatch.readEventsInResults">
      <s:dict>
        <s:key name="duration_secs">0.110</s:key>
        <s:key name="invocations">1</s:key>
      </s:dict>
    </s:key>
    <s:key name="dispatch.stream.local">
      <s:dict>
        <s:key name="duration_secs">0.089</s:key>
        <s:key name="invocations">4</s:key>
      </s:dict>
    </s:key>
    <s:key name="dispatch.timeline">
      <s:dict>
        <s:key name="duration_secs">0.359</s:key>
        <s:key name="invocations">5</s:key>
      </s:dict>
    </s:key>
  </s:dict>
</s:key>
<s:key name="messages">
  <s:dict/>
</s:key>
<s:key name="request">
  <s:dict>
    <s:key name="id">mysearch_02151949</s:key>
```

```
        <s:key name="search">search index</s:key>
      </s:dict>
    </s:key>
    <s:key name="eai:acl">
      <s:dict>
        <s:key name="perms">
          <s:dict>
            <s:key name="read">
              <s:list>
                <s:item>admin</s:item>
              </s:list>
            </s:key>
            <s:key name="write">
              <s:list>
                <s:item>admin</s:item>
              </s:list>
            </s:key>
          </s:dict>
        </s:key>
        <s:key name="owner">admin</s:key>
        <s:key name="modifiable">true</s:key>
        <s:key name="sharing">global</s:key>
        <s:key name="app">search</s:key>
        <s:key name="can_write">true</s:key>
      </s:dict>
    </s:key>
    <s:key name="searchProviders">
      <s:list>
        <s:item>mbp15.splunk.com</s:item>
      </s:list>
    </s:key>
  </s:dict>
 </content>
</entry>
```

POST

Update the `{search_id}` search job.

Request parameters

Name	Type	Default	Description
*custom.** required	String		Specify custom job properties for the specified search job.

Returned values

None

search/jobs/{search_id}/control

JSON

`https://<host>:<mPort>/services/search/jobs/{search_id}/control`

Run a job control command for the `{search_id}` search.

POST

Run a job control command for the `{search_id}` search.

Request parameters

Name	Type	Default	Description

Name	Type	Default	Description
action required	Enum		Valid values: (pause | unpause | finalize | cancel | touch | setttl | setpriority | enablepreview | disablepreview | setworkloadpool) The control action to execute. pause: Suspends the execution of the current search. unpause: Resumes the execution of the current search, if paused. finalize: Stops the search, and provides intermediate results to the /results endpoint. cancel: Stops the current search and deletes the result cache. touch: Extends the expiration time of the search to now + ttl setttl: Change the ttl of the search. Arguments: ttl=<number> setpriority: Sets the priority of the search process. Arguments: priority=<0-10> enablepreview: Enable preview generation (may slow search considerably). disablepreview: Disable preview generation. setworkloadpool: Moves a running search to a new workload pool. Arguments: workload_pool=<string>. Specifies the new workload pool. Requires edit_workload_pools capability. save: saves the search job, storing search artifacts on disk for 7 days. Add or edit the default_save_ttl value in limits.conf to override the default value of 7 days. unsave: Disables any action performed by save.

Returned values

None

Example request and response
XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/jobs/mysearch_02151949/control -d action=pause
```

XML Response

CODE

```
<response><messages><msg type='INFO'>Search job paused.</msg></messages></response>
```

search/v2/jobs/{search_id}/events

JSON

```
https://<host>:<mPort>/services/search/v2/jobs/{search_id}/events
```

Access `{search_id}` search events.

The GET operation does not include the *search* parameter in the v2 iteration of this endpoint. To use the *search* parameter, use the POST operation instead.

GET

Get `{search_id}` search events.

Request parameters

Name	Type	Default	Description
count	Number	100	The maximum number of results to return. If value is set to `0`, then all available results are returned. Default value is `100`.
earliest_time	String		A time string representing the earliest (inclusive), respectively, time bounds for the results to be returned. If not specified, the range applies to all results found.
f	String		A field to return for the event set. You can pass multiple `POST f` arguments if multiple field are required. If `field_list` and `f` are provided, the union of the lists is used.
field_list	String	*	[Deprecated] Use *f*. A comma-separated list of the fields to return for the event set.
latest_time	String		A time string representing the latest (exclusive), respectively, time bounds for the results to be returned. If not specified, the range applies to all results found.
max_lines	Number	0	The maximum lines that any single event _raw field should contain. Specify `0` to specify no limit.
offset	Number	0	The first result (inclusive) from which to begin returning data. This value is 0-indexed. Default value is 0. In 4.1+, negative offsets are allowed and are added to `count` to compute the absolute offset (for example, `offset=-1` is the last available offset. Offsets in the results are always absolute and never negative.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
output_time_format	String	`time_format`	Formats a UTC time. Defaults to what is specified in `time_format`.
segmentation	String	raw	The type of segmentation to perform on the data. This includes an option to perform k/v segmentation.
time_format	String	%m/%d/%Y:%H:%M:%S	Expression to convert a formatted time string from {start,end}_time into UTC seconds.
truncation_mode	Enum	abstract	Valid values: (abstract | truncate) Specifies how "max_lines" should be achieved.

Returned values

None

Application usage

These events are the data from the search pipeline before the first "transforming" search command. This is the primary method for a client to fetch a set of UNTRANSFORMED events for the search job.

This endpoint is only valid if the status_buckets > 0 or the search has no transforming commands.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/v2/jobs/1312313809.20/events --get -d f=arch -d f=build -d f=connectionType -d r -d count=3
```

XML Response

CODE

```
<results preview='0'>
<meta>
<fieldOrder>
<field>arch</field>
<field>build</field>
<field>connectionType</field>
<field>date_hour</field>
</fieldOrder>
</meta>
  <result offset='0'>
    <field k='arch'>
      <value><text>i686</text></value>
    </field>
    <field k='build'>
      <value><text>98164</text></value>
    </field>
    <field k='connectionType'>
      <value><text>cooked</text></value>
    </field>
    <field k='date_hour'>
      <value><text>19</text></value>
    </field>
  </result>
  <result offset='1'>
    <field k='arch'>
      <value><text>i686</text></value>
    </field>
    <field k='build'>
      <value><text>98164</text></value>
    </field>
    <field k='connectionType'>
      <value><text>cooked</text></value>
    </field>
    <field k='date_hour'>
      <value><text>19</text></value>
    </field>
  </result>
  <result offset='2'>
    <field k='arch'>
      <value><text>i686</text></value>
    </field>
    <field k='build'>
      <value><text>98164</text></value>
    </field>
    <field k='connectionType'>
      <value><text>cooked</text></value>
    </field>
    <field k='date_hour'>
      <value><text>19</text></value>
    </field>
  </result>
</results>
```

POST

Access `{search_id}` search events.

Request parameters

Name	Type	Default	Description
count	Number	100	The maximum number of results to return. If value is set to `0`, then all available results are returned. Default value is `100`.
earliest_time	String		A time string representing the earliest (inclusive), respectively, time bounds for the results to be returned. If not specified, the range applies to all results found.
f	String		A field to return for the event set. You can pass multiple `POST f` arguments if multiple field are required. If `field_list` and `f` are provided, the union of the lists is used.
field_list	String	*	[Deprecated] Use *f*. A comma-separated list of the fields to return for the event set.

Name	Type	Default	Description
latest_time	String		A time string representing the latest (exclusive), respectively, time bounds for the results to be returned. If not specified, the range applies to all results found.
max_lines	Number	0	The maximum lines that any single event _raw field should contain. Specify `0` to specify no limit.
offset	Number	0	The first result (inclusive) from which to begin returning data. This value is 0-indexed. Default value is 0. In 4.1+, negative offsets are allowed and are added to `count` to compute the absolute offset (for example, `offset=-1` is the last available offset. Offsets in the results are always absolute and never negative.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
output_time_format	String	`time_format`	Formats a UTC time. Defaults to what is specified in `time_format`.
search	String		The post processing search to apply to results. Can be any valid search language string. Only usable from POST operations.
segmentation	String	raw	The type of segmentation to perform on the data. This includes an option to perform k/v segmentation.
time_format	String	%m/%d/%Y:%H:%M:%S	Expression to convert a formatted time string from {start,end}_time into UTC seconds.
truncation_mode	Enum	abstract	Valid values: (abstract | truncate) Specifies how "max_lines" should be achieved.

Returned values

None

Application usage

These events are the data from the search pipeline before the first "transforming" search command. This is the primary method for a client to fetch a set of UNTRANSFORMED events for the search job.

This endpoint is only valid if the status_buckets > 0 or the search has no transforming commands.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/v2/jobs/1312313809.20/events --get -d f=arch -d f=build -d f=connectionType -d r -d count=3
```

XML Response

CODE

```
<results preview='0'>
<meta>
<fieldOrder>
<field>arch</field>
<field>build</field>
<field>connectionType</field>
<field>date_hour</field>
</fieldOrder>
</meta>
  <result offset='0'>
    <field k='arch'>
      <value><text>i686</text></value>
    </field>
    <field k='build'>
      <value><text>98164</text></value>
```

```
    </field>
    <field k='connectionType'>
      <value><text>cooked</text></value>
    </field>
    <field k='date_hour'>
      <value><text>19</text></value>
    </field>
  </result>
  <result offset='1'>
    <field k='arch'>
      <value><text>i686</text></value>
    </field>
    <field k='build'>
      <value><text>98164</text></value>
    </field>
    <field k='connectionType'>
      <value><text>cooked</text></value>
    </field>
    <field k='date_hour'>
      <value><text>19</text></value>
    </field>
  </result>
  <result offset='2'>
    <field k='arch'>
      <value><text>i686</text></value>
    </field>
    <field k='build'>
      <value><text>98164</text></value>
    </field>
    <field k='connectionType'>
      <value><text>cooked</text></value>
    </field>
    <field k='date_hour'>
      <value><text>19</text></value>
    </field>
  </result>
</results>
```

search/jobs/{search_id}/events (deprecated)

JSON

```
https://<host>:<mPort>/services/search/jobs/{search_id}/events
```

Get `{search_id}` search events.

Note: This endpoint is deprecated as of Splunk Enterprise 9.0.1. Use the v2 instance of this endpoint instead.

GET

Access `{search_id}` search events.

Request parameters

Name	Type	Default	Description
count	Number	100	The maximum number of results to return. If value is set to `0`, then all available results are returned. Default value is `100`.
earliest_time	String		A time string representing the earliest (inclusive), respectively, time bounds for the results to be returned. If not specified, the range applies to all results found.
f	String		A field to return for the event set. You can pass multiple `POST f` arguments if multiple field are required. If `field_list` and `f` are provided, the union of the lists is used.
field_list	String	*	[Deprecated] Use *f*. A comma-separated list of the fields to return for the event set.
latest_time	String		A time string representing the latest (exclusive), respectively, time bounds for the results to be returned. If not specified, the range applies to all results found.

Name	Type	Default	Description
max_lines	Number	0	The maximum lines that any single event _raw field should contain. Specify `0` to specify no limit.
offset	Number	0	The first result (inclusive) from which to begin returning data. This value is 0-indexed. Default value is 0. In 4.1+, negative offsets are allowed and are added to `count` to compute the absolute offset (for example, `offset=-1` is the last available offset. Offsets in the results are always absolute and never negative.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
output_time_format	String	`time_format`	Formats a UTC time. Defaults to what is specified in `time_format`.
search	String		The post processing search to apply to results. Can be any valid search language string.
segmentation	String	raw	The type of segmentation to perform on the data. This includes an option to perform k/v segmentation.
time_format	String	%m/%d/%Y:%H:%M:%S	Expression to convert a formatted time string from {start,end}_time into UTC seconds.
truncation_mode	Enum	abstract	Valid values: (abstract | truncate) Specifies how "max_lines" should be achieved.

Returned values

None

Application usage

These events are the data from the search pipeline before the first "transforming" search command. This is the primary method for a client to fetch a set of UNTRANSFORMED events for the search job.

This endpoint is only valid if the status_buckets > 0 or the search has no transforming commands.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/jobs/1312313809.20/events --get -d f=arch -d f=build -d f=connectionType -d r -d count=3
```

XML Response

CODE

```
<results preview='0'>
<meta>
<fieldOrder>
<field>arch</field>
<field>build</field>
<field>connectionType</field>
<field>date_hour</field>
</fieldOrder>
</meta>
  <result offset='0'>
    <field k='arch'>
      <value><text>i686</text></value>
    </field>
    <field k='build'>
      <value><text>98164</text></value>
    </field>
    <field k='connectionType'>
      <value><text>cooked</text></value>
    </field>
    <field k='date_hour'>
      <value><text>19</text></value>
    </field>
```

```
  </result>
  <result offset='1'>
    <field k='arch'>
      <value><text>i686</text></value>
    </field>
    <field k='build'>
      <value><text>98164</text></value>
    </field>
    <field k='connectionType'>
      <value><text>cooked</text></value>
    </field>
    <field k='date_hour'>
      <value><text>19</text></value>
    </field>
  </result>
  <result offset='2'>
    <field k='arch'>
      <value><text>i686</text></value>
    </field>
    <field k='build'>
      <value><text>98164</text></value>
    </field>
    <field k='connectionType'>
      <value><text>cooked</text></value>
    </field>
    <field k='date_hour'>
      <value><text>19</text></value>
    </field>
  </result>
</results>
```

search/v2/jobs/{search_id}/results

JSON

```
https://<host>:<mPort>/services/search/v2/jobs/{search_id}/results
```

Access `{search_id}` search results.

The GET operation does not include the *search* parameter in the v2 iteration of this endpoint. To use the *search* parameter, use the POST operation instead.

GET

Get `{search_id}` search results.

Request parameters

Name	Type	Default	Description
add_summary_to_metadata	Boolean	false	Set the value to "true" to include field summary statistics in the response.
count	Number	100	The maximum number of results to return. If value is set to `0`, then all available results are returned.
f	String		A field to return for the event set. You can pass multiple `POST f` arguments if multiple field are required. If `field_list` and `f` are provided the union of the lists is used.
field_list	String		[Deprecated] Use *f*. Specify a comma-separated list of the fields to return for the event set.
offset	Number	0	The first result (inclusive) from which to begin returning data. This value is 0-indexed. Default value is 0. In 4.1+, negative offsets are allowed and are added to `count` to compute the absolute offset (for example, `offset=-1` is the last available offset). Offsets in the results are always absolute and never negative.

Name	Type	Default	Description
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.

Returned values

None

Application usage

This is the table that exists after all processing from the search pipeline has completed.

This is the primary method for a client to fetch a set of TRANSFORMED events. If the dispatched search does not include a transforming command, the effect is the same as get_events, however with fewer options.

Example request and response

JSON request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/v2/jobs/mysearch_02151949/results --get -d f=index -d f=source -d f=sourcetype -d count=3 -d output_mode=json
```

JSON response

JSON

```
{ "init_offset" : 0,
  "messages" : [ { "text" : "base lispy: [ AND index::_internal source::*/metrics.log ]",
        "type" : "DEBUG"
      },
      { "text" : "search context: user=\"admin\", app=\"search\", bs-pathname=\"/Applications/splunk/etc\"",
        "type" : "DEBUG"
      }
    ],
  "preview" : false,
  "results" : [ { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      }
    ]
}
```

POST

Access `{search_id}` search results.

Request parameters

Name	Type	Default	Description
add_summary_to_metadata	Boolean	false	Set the value to "true" to include field summary statistics in the response.
count	Number	100	The maximum number of results to return. If value is set to `0`, then all available results are returned.
f	String		A field to return for the event set. You can pass multiple `POST f` arguments if multiple field are required. If `field_list` and `f` are provided the union of the lists is used.
field_list	String		[Deprecated] Use *f*. Specify a comma-separated list of the fields to return for the event set.

Name	Type	Default	Description
offset	Number	0	The first result (inclusive) from which to begin returning data. This value is 0-indexed. Default value is 0. In 4.1+, negative offsets are allowed and are added to `count` to compute the absolute offset (for example, `offset=-1` is the last available offset). Offsets in the results are always absolute and never negative.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
search	String		The post processing search to apply to results. Can be any valid search language string. Only usable from POST operations.

Returned values

None

Application usage

This is the table that exists after all processing from the search pipeline has completed.

This is the primary method for a client to fetch a set of TRANSFORMED events. If the dispatched search does not include a transforming command, the effect is the same as get_events, however with fewer options.

Example request and response

JSON request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/v2/jobs/mysearch_02151949/results -d f=index -d f=source -d f=sourcetype -d count=3 -d
output_mode=json
```

JSON response

JSON

```
{ "init_offset" : 0,
  "messages" : [ { "text" : "base lispy: [ AND index::_internal source::*/metrics.log ]",
        "type" : "DEBUG"
      },
      { "text" : "search context: user=\"admin\", app=\"search\", bs-pathname=\"/Applications/splunk/etc\"",
        "type" : "DEBUG"
      }
    ],
  "preview" : false,
  "results" : [ { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      }
    ]
}
```

search/jobs/{search_id}/results (deprecated)

JSON

```
https://<host>:<mPort>/services/search/jobs/{search_id}/results
```

Get `{search_id}` search results.

Note: This endpoint is deprecated as of Splunk Enterprise 9.0.1. Use the v2 instance of this endpoint instead.

GET

Get {search_id} search results.

Request parameters

Name	Type	Default	Description
add_summary_to_metadata	Boolean	false	Set the value to "true" to include field summary statistics in the response.
count	Number	100	The maximum number of results to return. If value is set to 0, then all available results are returned.
f	String		A field to return for the event set. You can pass multiple POST f arguments if multiple field are required. If field_list and f are provided the union of the lists is used.
field_list	String		[Deprecated] Use *f*. Specify a comma-separated list of the fields to return for the event set.
offset	Number	0	The first result (inclusive) from which to begin returning data. This value is 0-indexed. Default value is 0. In 4.1+, negative offsets are allowed and are added to count to compute the absolute offset (for example, offset=-1 is the last available offset). Offsets in the results are always absolute and never negative.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
search	String		The post processing search to apply to results. Can be any valid search language string.

Returned values

None

Application usage

This is the table that exists after all processing from the search pipeline has completed.

This is the primary method for a client to fetch a set of TRANSFORMED events. If the dispatched search does not include a transforming command, the effect is the same as get_events, however with fewer options.

Example request and response

JSON request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/jobs/mysearch_02151949/results --get -d f=index -d f=source -d f=sourcetype -d count=3 -d
output_mode=json
```

JSON response

JSON

```
{ "init_offset" : 0,
  "messages" : [ { "text" : "base lispy: [ AND index::_internal source::*/metrics.log ]",
        "type" : "DEBUG"
      },
      { "text" : "search context: user=\"admin\", app=\"search\", bs-pathname=\"/Applications/splunk/etc\"",
        "type" : "DEBUG"
      }
    ],
  "preview" : false,
  "results" : [ { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
```

```
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      }
    ]
}
```

search/v2/jobs/{search_id}/results_preview

JSON

```
https://<host>:<mPort>/services/search/v2/jobs/{search_id}/results_preview
```

Preview `{search_id}` search results.

The GET operation does not include the *search* parameter in the v2 iteration of this endpoint. To use the *search* parameter, use the POST operation instead.

GET

Preview `{search_id}` search results.

Request parameters

Name	Type	Default	Description
add_summary_to_metadata	Boolean	false	Set the value to "true" to include field summary statistics in the response.
count	Number	100	The maximum number of results to return. If value is set to `0`, then all available results are returned.
f	String		A field to return for the event set. You can pass multiple `POST f` arguments if multiple field are required. If `field_list` and `f` are provided the union of the lists is used.
field_list	String		[Deprecated] Use *f*. A comma-separated list of the fields to return for the event set.
offset	Number	0	The first result (inclusive) from which to begin returning data. This value is 0-indexed. Default value is 0.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.

Returned values

None

Application usage

Returns the intermediate preview results of the search specified by {search_id}. When the job is complete, this gives the same response as /search/jobs/{search_id}/results. Preview is enabled for real-time searches and for searches where status_buckets > 0.

Example request and response

JSON request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/v2/jobs/mysearch_02151949/results_preview --get -d f=index -d f=source -d f=sourcetype -d
count=3 -d output_mode=json
```

JSON response

JSON

```
{ "init_offset" : 0,
  "messages" : [ { "text" : "base lispy: [ AND index::_internal source::*/metrics.log ]",
        "type" : "DEBUG"
      },
      { "text" : "search context: user=\"admin\", app=\"search\", bs-pathname=\"/Applications/splunk/etc\"",
        "type" : "DEBUG"
      }
    ],
  "preview" : false,
  "results" : [ { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      }
    ]
}
```


POST

Access a preview of `{search_id}` search results.

Request parameters

Name	Type	Default	Description
add_summary_to_metadata	Boolean	false	Set the value to "true" to include field summary statistics in the response.
count	Number	100	The maximum number of results to return. If value is set to `0`, then all available results are returned.
f	String		A field to return for the event set. You can pass multiple `POST f` arguments if multiple field are required. If `field_list` and `f` are provided the union of the lists is used.
field_list	String		[Deprecated] Use *f*. A comma-separated list of the fields to return for the event set.
offset	Number	0	The first result (inclusive) from which to begin returning data. This value is 0-indexed. Default value is 0.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
search	String		The post processing search to apply to results. Can be any valid search language string. Only usable from POST operations.

Returned values

None

Application usage

Returns the intermediate preview results of the search specified by {search_id}. When the job is complete, this gives the same response as /search/jobs/{search_id}/results. Preview is enabled for real-time searches and for searches where status_buckets > 0.

Example request and response

JSON request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/v2/jobs/mysearch_02151949/results_preview --get -d f=index -d f=source -d f=sourcetype -d
count=3 -d output_mode=json
```

JSON response

JSON


```
{ "init_offset" : 0,
  "messages" : [ { "text" : "base lispy: [ AND index::_internal source::*/metrics.log ]",
        "type" : "DEBUG"
      },
      { "text" : "search context: user=\"admin\", app=\"search\", bs-pathname=\"/Applications/splunk/etc\"",
        "type" : "DEBUG"
      }
    ],
  "preview" : false,
  "results" : [ { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      }
    ]
}
```


search/jobs/{search_id}/results_preview (deprecated)

JSON

```
https://<host>:<mPort>/services/search/jobs/{search_id}/results_preview
```

Preview `{search_id}` search results.

Note: This endpoint is deprecated as of Splunk Enterprise 9.0.1. Use the v2 instance of this endpoint instead.

GET

Preview `{search_id}` search results.

Request parameters

Name	Type	Default	Description
add_summary_to_metadata	Boolean	false	Set the value to "true" to include field summary statistics in the response.
count	Number	100	The maximum number of results to return. If value is set to `0`, then all available results are returned.
f	String		A field to return for the event set. You can pass multiple `POST f` arguments if multiple field are required. If `field_list` and `f` are provided the union of the lists is used.
field_list	String		[Deprecated] Use *f*. A comma-separated list of the fields to return for the event set.
offset	Number	0	The first result (inclusive) from which to begin returning data. This value is 0-indexed. Default value is 0.
output_mode	Enum	xml	Valid values: (atom | csv | json | json_cols | json_rows | raw | xml) Specifies the format for the returned output.
search	String		The post processing search to apply to results. Can be any valid search language string.

Returned values

None

Application usage

Returns the intermediate preview results of the search specified by {search_id}. When the job is complete, this gives the same response as /search/jobs/{search_id}/results. Preview is enabled for real-time searches and for searches where status_buckets > 0.

Example request and response

JSON request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/jobs/mysearch_02151949/results_preview --get -d f=index -d f=source -d f=sourcetype -d
count=3 -d output_mode=json
```

JSON response

JSON

```
{ "init_offset" : 0,
  "messages" : [ { "text" : "base lispy: [ AND index::_internal source::*/metrics.log ]",
        "type" : "DEBUG"
      },
      { "text" : "search context: user=\"admin\", app=\"search\", bs-pathname=\"/Applications/splunk/etc\"",
        "type" : "DEBUG"
      }
    ],
  "preview" : false,
  "results" : [ { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      },
      { "index" : "_internal",
        "source" : "/Applications/splunk/var/log/splunk/metrics.log",
        "sourcetype" : "splunkd"
      }
    ]
}
```

search/jobs/{search_id}/search.log

JSON

```
https://<host>:<mPort>/services/search/jobs/{search_id}/search.log
```

Get the `{search_id}` search log.

GET

Get the `{search_id}` search log.

Request parameters

Name	Type	Default	Description
attachment	Boolean	false	If true, returns search.log as an attachment. Otherwise, streams search.log.

Returned values

None

Example request and response

Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/jobs/mysearch_02151949/search.log
```

Response

CODE

```
07-07-2011 21:36:22.066 INFO  ApplicationManager - Found application directory: /Applications/splunk4.3/etc/apps/user-prefs
07-07-2011 21:36:22.066 INFO  ApplicationManager - Initialized at least 12 applications: /Applications/splunk4.3/etc/apps
07-07-2011 21:36:22.066 INFO  ApplicationManager - Found 5 application(s) that might have global exports
07-07-2011 21:36:22.073 INFO  dispatchRunner - initing LicenseMgr in search process: nonPro=0
07-07-2011 21:36:22.074 INFO  LicenseMgr - Initing LicenseMgr
07-07-2011 21:36:22.075 INFO  ServerConfig - My GUID is "1F3A34AE-75DA-4680-B184-5BF309843919".
07-07-2011 21:36:22.075 INFO  ServerConfig - My hostname is "ombroso-mbp15.local".
```

```
07-07-2011 21:36:22.076 INFO  SSLCommon - added zlib compression
07-07-2011 21:36:22.077 INFO  ServerConfig - Default output queue for file-based input: parsingQueue.
07-07-2011 21:36:22.077 INFO  LMConfig - serverName=mbp15.splunk.com guid=1F3A34AE-75DA-4680-B184-5BF309843919
07-07-2011 21:36:22.077 INFO  LMConfig - connection_timeout=30
07-07-2011 21:36:22.077 INFO  LMConfig - send_timeout=30
07-07-2011 21:36:22.077 INFO  LMConfig - receive_timeout=30
. . . elided . . .
```

search/jobs/{search_id}/summary

JSON

```
https://<host>:<mPort>/services/search/jobs/{search_id}/summary
```

Get the `getFieldsAndStats` output of the events to-date, for the `search_id` search.

GET

Get the `getFieldsAndStats` output of the events to-date, for the `search_id` search.

Request parameters

Name	Type	Default	Description
earliest_time	String		Time string representing the earliest (inclusive), respectively, time bounds for the search. The time string can be either a UTC time (with fractional seconds), a relative time specifier (to now) or a formatted time string. (Also see comment for the search_mode variable.)
f	String		A field to return for the event set. You can pass multiple `POST f` arguments if multiple field are required. If `field_list` and `f` are provided, the union of the lists is used.
field_list	String		[Deprecated] Use *f*. A comma-separated list of the fields to return for the event set.
histogram	Boolean	false	Indicates whether to add histogram data to the summary output.
latest_time	String		Time string representing the latest (exclusive), respectively, time bounds for the search.
min_freq	Number	0	For each key, the fraction of results this key must occur in to be displayed. Express the fraction as a number between 0 and 1.
output_time_format	String	`time_format`	Formats a UTC time.
search	String	Empty string	Specifies a substring that all returned events should contain either in one of their values or tags.
time_format	String	%m/%d/%Y:%H:%M:%S	Expression to convert a formatted time string from {start,end}_time into UTC seconds.
top_count	Number	10	For each key, specifies how many of the most frequent items to return.

Returned values

None

Application usage

This endpoint is only valid when status_buckets > 0. To guarantee a set of fields in the summary, when creating the search, use the required_fields_list or rf parameters.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/jobs/mytestsid/summary --get -d f=source -d f=sourcetype -d f=host -d top_count=5
```

XML Response

XML

```
<?xml version='1.0' encoding='UTF-8'?>
<summary earliest_time='1969-12-31T16:00:00.000-08:00' latest_time='1969-12-31T16:00:00.464-08:00' duration='0' c='150375'>
  <field k='host' c='150375' nc='0' dc='1' exact='1'>
    <modes>
      <value c='150375' exact='1'><text>tiny</text></value>   </modes>
  </field>
  <field k='source' c='150375' nc='0' dc='13' exact='1'>
    <modes>
      <value c='136107' exact='1'><text>/mnt/scsi/steveyz/splunksi/var/log/splunk/metrics.log</text></value>      <value c='6682' exact='1'>
<text>/mnt/scsi/steveyz/splunksi/var/log/splunk/splunkd_access.log</text></value>     <value c='4656' exact='1'>
<text>/mnt/scsi/steveyz/splunksi/var/log/splunk/scheduler.log</text></value>      <value c='1714' exact='1'>
<text>/mnt/scsi/steveyz/splunksi/var/log/splunk/web_access.log</text></value>     <value c='937' exact='1'>
<text>/mnt/scsi/steveyz/splunksi/var/log/splunk/splunkd.log</text></value>   </modes>
  </field>
  <field k='sourcetype' c='150375' nc='0' dc='10' exact='1'>
    <modes>
      <value c='137053' exact='1'><text>splunkd</text></value>      <value c='6682' exact='1'><text>splunkd_access</text></value>     <value c='4656'
exact='1'><text>scheduler</text></value>      <value c='1714' exact='1'><text>splunk_web_access</text></value>      <value c='193' exact='1'>
<text>splunk_web_service</text></value>    </modes>
  </field>
</summary>
```

search/jobs/{search_id}/timeline

JSON

```
https://<host>:<mPort>/services/search/jobs/{search_id}/timeline
```

Get event distribution over time of the untransformed events read to-date, for the `search_id` search.

GET

Get event distribution over time of the untransformed events read to-date, for the `search_id` search.

Request parameters

Name	Type	Default	Description
output_time_format	String	`time_format`	Formats a UTC time.
time_format	String	%m/%d/%Y:%H:%M:%S	Expression to convert a formatted time string from {start,end}_time into UTC seconds.

Returned values

None

The output from this endpoint provides values for the following fields:

Field	Description
c	Event count
a	Available. Not all events in a bucket are retrievable. Generally capped at 10000.
t	Time in epoch seconds
d	Bucket size (time)
f	Indicates if the search finished scanning events from the time range of this bucket.
etz	Timezone offset, in seconds, for the earliest time of this bucket. etz and ltz are different if the buckets are months or days and you have a DST change during the middle.
ltz	Timezone offset, in seconds, for the latest time of this bucket.

Application usage

This endpoint is only valid when status_buckets > 0. To guarantee a set of fields in the summary, when creating the search, use the required_fields_list or rf parameters.

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/jobs/mytestsid/timeline --get -d time_format="%c"
```

XML Response

CODE

```
<timeline c='150397' cursor='1312308000'>
<bucket c='7741' a='7741' t='1312308000.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 11:00:00 2011</bucket>
<bucket c='7894' a='7894' t='1312311600.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 12:00:00 2011</bucket>
<bucket c='7406' a='7406' t='1312315200.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 13:00:00 2011</bucket>
<bucket c='6097' a='6097' t='1312318800.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 14:00:00 2011</bucket>
<bucket c='6072' a='6072' t='1312322400.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 15:00:00 2011</bucket>
<bucket c='6002' a='6002' t='1312326000.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 16:00:00 2011</bucket>
<bucket c='6004' a='6004' t='1312329600.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 17:00:00 2011</bucket>
<bucket c='5994' a='5994' t='1312333200.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 18:00:00 2011</bucket>
<bucket c='6037' a='6037' t='1312336800.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 19:00:00 2011</bucket>
<bucket c='6021' a='6021' t='1312340400.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 20:00:00 2011</bucket>
<bucket c='6051' a='6051' t='1312344000.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 21:00:00 2011</bucket>
<bucket c='6006' a='6006' t='1312347600.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 22:00:00 2011</bucket>
<bucket c='6041' a='6041' t='1312351200.000' d='3600' f='1' etz='-25200' ltz='-25200'>Tue Aug  2 23:00:00 2011</bucket>
<bucket c='5993' a='5993' t='1312354800.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 00:00:00 2011</bucket>
<bucket c='6040' a='6040' t='1312358400.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 01:00:00 2011</bucket>
<bucket c='5993' a='5993' t='1312362000.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 02:00:00 2011</bucket>
<bucket c='6061' a='6061' t='1312365600.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 03:00:00 2011</bucket>
<bucket c='5995' a='5995' t='1312369200.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 04:00:00 2011</bucket>
<bucket c='5988' a='5988' t='1312372800.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 05:00:00 2011</bucket>
<bucket c='6042' a='6042' t='1312376400.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 06:00:00 2011</bucket>
<bucket c='5998' a='5998' t='1312380000.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 07:00:00 2011</bucket>
<bucket c='6055' a='6055' t='1312383600.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 08:00:00 2011</bucket>
<bucket c='5997' a='5997' t='1312387200.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 09:00:00 2011</bucket>
<bucket c='5994' a='5994' t='1312390800.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 10:00:00 2011</bucket>
<bucket c='875' a='875' t='1312394400.000' d='3600' f='1' etz='-25200' ltz='-25200'>Wed Aug  3 11:00:00 2011</bucket>
</timeline>
```

search/v2/parser

CODE

```
https://<host>:<mPort>/services/search/v2/parser
```

Access search language parsing.

The GET operation is not available in the v2 iteration of this endpoint.

POST

Parses Splunk search language and returns semantic map.

Request parameters

Name	Type	Default	Description
enable_lookups	Boolean	false	If `true`, reverse lookups are done to expand the search expression.
output_mode	String	xml	Specify output formatting. Select from either: xml: XML formatting json: JSON formatting
parse_only	Boolean	false	If true, disables expansion of search due evaluation of subsearches, time term expansion, lookups, tags, eventtypes, sourcetype alias.
q required	String		The search string to parse.
reload_macros	Boolean	true	If true, reload macro definitions from macros.conf.

Returned values

None

Example request and response

JSON Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/search/v2/parser -d output_mode=json -d q="search index=os sourcetype=cpu"
```

JSON Response

JSON

```
{
  "remoteSearch": "litsearch  | fields  keepcolorder=t \"host\" \"index\" \"linecount\" \"source\" \"sourcetype\" \"splunk_server\"",
  "remoteTimeOrdered": true,
  "eventsSearch": "search index=os sourcetype=cpu",
  "eventsTimeOrdered": true,
  "eventsStreaming": true,
  "reportsSearch": "",
  "commands": [
    {
      "command": "search",
      "rawargs": "",
      "pipeline": "streaming",
      "args": {
        "search": [""],
      }
      "isGenerating": true,
      "streamType": "SP_STREAM",
    },
  ]
}
```

search/parser (deprecated)

CODE

```
https://<host>:<mPort>/services/search/parser
```

Get search language parsing.

Note: This endpoint is deprecated as of Splunk Enterprise 9.0.1. Use the v2 instance of this endpoint instead.

GET

Parses Splunk search language and returns semantic map.

Request parameters

Name	Type	Default	Description
enable_lookups	Boolean	false	If `true`, reverse lookups are done to expand the search expression.
output_mode	String	xml	Specify output formatting. Select from either: xml: XML formatting json: JSON formatting
parse_only	Boolean	false	If true, disables expansion of search due evaluation of subsearches, time term expansion, lookups, tags, eventtypes, sourcetype alias.
q required	String		The search string to parse.
reload_macros	Boolean	true	If true, reload macro definitions from macros.conf.

Returned values

None

Example request and response

JSON Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/search/parser --get -d output_mode=json -d q="search index=os sourcetype=cpu"
```

JSON Response

JSON

```
{
  "remoteSearch": "litsearch  | fields  keepcolorder=t \"host\" \"index\" \"linecount\" \"source\" \"sourcetype\" \"splunk_server\"",
  "remoteTimeOrdered": true,
  "eventsSearch": "search ",
  "eventsTimeOrdered": true,
  "eventsStreaming": true,
  "reportsSearch": "",
  "commands": [
    {
      "command": "search",
      "rawargs": "",
      "pipeline": "streaming",
      "args": {
        "search": [""],
      }
      "isGenerating": true,
      "streamType": "SP_STREAM",
    },
  ]
}
```

search/scheduler

CODE

```
https://<host>:<mPort>/services/search/scheduler
```

GET

Get current search scheduler enablement status.

Request parameters

None

Returned values

Name	Type	Default	Description
saved_searches_disabled	Boolean	0 or 1	A boolean value indicating whether the search scheduler is disabled.

Example request and response

XML Request
CODE

```
curl -k -u admin:pass https://localhost:8089/services/search/scheduler
```

XML Response
CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>scheduler</title>
  <id>https://localhost:8089/services/search/scheduler</id>
  <updated>2015-06-09T13:23:38-07:00</updated>
  <generator build="6cfc0237739f" version="6.3.0"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/search/scheduler/_acl" rel="_acl"/>
  <opensearch:totalResults>1</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
  <entry>
    <title>scheduler</title>
    <id>https://localhost:8089/services/search/scheduler/scheduler</id>
    <updated>2015-06-09T13:23:38-07:00</updated>
    <link href="/services/search/scheduler/scheduler" rel="alternate"/>
    <author>
      <name>system</name>
    </author>
    <link href="/services/search/scheduler/scheduler" rel="list"/>
    <link href="/services/search/scheduler/scheduler" rel="edit"/>
    <content type="text/xml">
      <s:dict>
        <s:key name="disabled">0</s:key>
        <s:key name="eai:acl">
          <s:dict>
            <s:key name="app"></s:key>
            <s:key name="can_list">1</s:key>
```

```
            <s:key name="can_write">1</s:key>
            <s:key name="modifiable">0</s:key>
            <s:key name="owner">system</s:key>
            <s:key name="perms">
              <s:dict>
                <s:key name="read">
                  <s:list>
                    <s:item>admin</s:item>
                    <s:item>splunk-system-role</s:item>
                  </s:list>
                </s:key>
                <s:key name="write">
                  <s:list>
                    <s:item>admin</s:item>
                    <s:item>splunk-system-role</s:item>
                  </s:list>
                </s:key>
              </s:dict>
            </s:key>
            <s:key name="removable">0</s:key>
            <s:key name="sharing">system</s:key>
          </s:dict>
        </s:key>
        <s:key name="saved_searches_disabled">0</s:key>
      </s:dict>
    </content>
  </entry>
</feed>
```

search/scheduler/status

CODE

```
https://<host>:<mPort>/services/search/scheduler/status
```

Enable or disable the search scheduler.

POST

Enable or disable the search scheduler.

Request parameters

Name	Type	Default	Description
disabled	Boolean		Indicates whether to disable the search scheduler. 0 enables the search scheduler. 1 disables the search scheduler.

Returned values

None

Example request and response

XML Request

CODE

```
curl -ku admin:pass -XPOST https://localhost:8089/services/search/scheduler/status -d disabled=1
```

XML Response

CODE

```
<feed xmlns="http://www.w3.org/2005/Atom" xmlns:s="http://dev.splunk.com/ns/rest" xmlns:opensearch="http://a9.com/-/spec/opensearch/1.1/">
  <title>scheduler</title>
  <id>https://localhost:8089/services/search/scheduler</id>
  <updated>2015-06-09T13:40:21-07:00</updated>
  <generator build="6cfc0237739f" version="6.3.0"/>
  <author>
    <name>Splunk</name>
  </author>
  <link href="/services/search/scheduler/_acl" rel="_acl"/>
  <opensearch:totalResults>0</opensearch:totalResults>
  <opensearch:itemsPerPage>30</opensearch:itemsPerPage>
  <opensearch:startIndex>0</opensearch:startIndex>
  <s:messages/>
</feed>
```

search/timeparser

CODE

```
https://<host>:<mPort>/services/search/timeparser
```

Get time argument parsing.

GET

Get a lookup table of time arguments to absolute timestamps.

Request parameters

Name	Type	Default	Description
now	String		The time to use as current time for relative time identifiers. Can itself either be a relative time (from the real "now" time) or an absolute time in the format specified by `time_format`.
output_time_format	String	%FT%T.%Q%:z	Used to format a UTC time. Defaults to the value of `time_format`.
time required	String		The time argument to parse. Acceptable inputs are either a relative time identifier or an absolute time. Multiple time arguments can be passed by specifying multiple time parameters.
time_format	String	%FT%T.%Q%:z	The format (`strftime`) of the absolute time format passed in time. This field is not used if a relative time identifier is provided. For absolute times, the default value is the ISO-8601 format.

Returned values

None

Example request and response

XML Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/search/timeparser --get -d time=-12h -d time=-24h
```

XML Response

CODE

```
<response>
  <dict>
    <key name="-12h">2011-07-06T21:54:23.000-07:00</key>
    <key name="-24h">2011-07-06T09:54:23.000-07:00</key>
  </dict>
</response>
```

search/typeahead

CODE

```
https://<host>:<mPort>/services/search/typeahead
```

Get search string auto-complete suggestions.

GET

Get a list of words or descriptions for possible auto-complete terms.

Request parameters

Name	Type	Default	Description

Name	Type	Default	Description
count required	Number		The number of items to return for this term.
max_servers	Number	2	Specifies the maximum number of indexer search peers that are used in addition to the search head for the purpose of providing typeahead functionality. When properly set, `max_servers` minimizes the workload impact of running typeahead search jobs in an indexer clustering deployment. If your target indexes are evenly distributed among search servers, use the default setting or a similarly low number. For load balancing, the choice of search peers for typeahead searches is random. A setting of `0` means "no limit": All available search peers are used for `typeahead` search jobs.
output_mode	String	csv	Specify output formatting. Select from: csv: CSV formatting xml: XML formatting json: JSON formatting
prefix required	String		The term for which to return typeahead results.

Returned values

None

Example request and response

JSON Request

CODE

```
curl -k -u admin:pass https://localhost:8089/servicesNS/admin/search/search/typeahead --get -d count=3 -d prefix=source -d output_mode=json
max_servers=1
```

JSON Response

JSON

```
{ "results" : [ { "content" : "source=\"sampledata.zip:./apache1.splunk.com/access_combined.log\"",
        "count" : 9199,
        "operator" : false
      },
      { "content" : "source=\"sampledata.zip:./apache2.splunk.com/access_combined.log\"",
        "count" : 27705,
        "operator" : false
      },
      { "content" : "source=\"sampledata.zip:./apache3.splunk.com/access_combined.log\"",
        "count" : 27888,
        "operator" : false
      }
    ]
}
```

Endpoints for SPL2-based applications

This documentation is designed for Splunk application developers and Splunk administrators who are creating or managing SPL2-based applications. For more information see:

- Create SPL2-based apps in the *Splunk Developer Guide* on dev.splunk.com.
- Splunk Enterprise: Install SPL2-based apps in the *Splunk Enterprise Admin Manual*.
- Splunk Cloud Platform: Install SPL2-based apps in the *Splunk Cloud Platform Admin Manual*.

search/spl2-module-dispatch

CODE

```
https://<host>:<mport>/services/search/spl2-module-dispatch
```

Dispatch a module containing one or more SPL2 statements. For more information about what constitutes an SPL2 statement, see Modules and SPL2 statements in the *SPL2 Search Manual*.

POST

Start a new search or searches and return a search ID (SID) for each named search statement.

Request parameters

Name	Type	Default	Description
module	String		Required. Contains the entire module definition including imports, within quotation marks. Example: `import _internal from ../../../../indexes;$query_name = FROM _internal`
namespace	String		The application namespace in which to restrict searches. Leave blank with only quotation marks. Example: " "
queryParameters	String		Required. Contains a list of searches by name. Each search requires its own queryName and associated metadata, and returns a separate SID.
queryName	String		Required. The name of each search in the query, followed by a stanza containing its associated metadata. You must separately specify each search in the module, or your request will not return results for that search.
earliest	String	-24h@h	A time string that specifies the earliest time to retrieve events. Can be a relative or absolute time. For absolute time, specify either UNIX time or UTC in seconds in the ISO-8601 (`%FT%T.%Q`) format. To learn about time strings in SPL2, see Time modifiers in the *SPL2 Search Manual*. Example: `2019-01-25T13:15:30Z`.
latest	String	now	A time string that specifies the latest time to retrieve events. Can be a relative or absolute time. For absolute time, specify either UNIX time or UTC in seconds in the ISO-8601 (`%FT%T.%Q`) format. To learn about time strings in SPL2, see Time modifiers in the *SPL2 Search Manual*. Example: `2019-01-25T13:15:30Z`.
timezone	String	Current system timezone	Specifies the timezone for the earliest and latest parameters, if those parameters are in relative time. If those parameters are in absolute time, then this parameter is ignored. Specify time zone for timestamps. To see all supported time zone formats, see Time zones.
relativeTimeAnchor	String	The time the search job is created	Specifies the anchor time for the earliest and latest parameters, if those parameters are in relative time. Example: If earliest is set to `-d@d`, the unit is day. If the relativeTimeAnchor is set to `2020-10-05T13:15:30Z`, then resolvedEarliest becomes `2020-10-05T00:00:00Z`, which is the day. Hours, minutes, and seconds are set to zero.
collectEventSummary	Boolean	False	Specifies whether a search can collect event summary information during the run time.
collectFieldSummary	Boolean	False	Specifies whether a search can collect fields summary information during the run time.
collectTimeBuckets	Boolean	False	Specifies whether a search can collect timeline buckets summary information during the run time.

Name	Type	Default	Description
adhocSearchLevel	String	fast	Specify the mode in which the search should run. Accepts `fast`, `smart`, or `verbose`.

Returned values

Name	Description
sid	Search ID.
name	Name of the search statement.

Example request

PYTHON

```
curl -k -u <admin>:<changeme> --location 'https://<host>:8089/services/search/spl2-module-dispatch' \
--data '{
  "module": " $search1 = from _audit | stats count()",
  "namespace": "",
  "queryParameters": {
   "search1": {
            "earliest": "-1h@h",
            "latest": "now",
            "timezone": "Etc/UTC",
            "collectFieldSummary": true
    }
   "search2": {
            "earliest": "-1h@h",
            "timezone": "Etc/UTC",
            "collectEventSummary": true
    }
  }
}'
```

Example response

JSON

```
[
    {
        "sid": "1682980180.52",
        "name": "search1"
    }
{
        "sid": "1058392067.22",
        "name": "search2"
    }
]
```

services/spl2/modules

CODE

```
https://<host>:<mport>/services/spl2/modules
```

Access a list of SPL2 modules.

POST

Create a module within the app context.

Request parameters

Name	Type	Default	Description
module	String		Required. The name of the module.
namespace	String		Required. The namespace of the module.
definition	String		Required. The definition of the module. Example: `"$a = | FROM index:terminallookup4704 GROUP BY indexed:source SELECT count();"`

Returned values None.

Example request

JSON

```
curl -k --request POST -u admin:pass 'https://localhost:8089/services/spl2/modules' \
--data-raw '{
    "name": "bar",
    "namespace": "foo",
    "definition": "$a = | FROM index:terminallookup4704 GROUP BY indexed:source      SELECT count();"
}'
```

Example response

See HTTP Status Codes for a list of possible responses.

services/spl2/modules/{resourceName}

JSON

```
https://<host>:<mport>/services/spl2/modules/{resourceName}
```

Access a specific SPL2 module.

GET

Retrieves information about a specific module.

Request parameters None.

Example request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/spl2/modules/foo.bar
```

Example response

JSON

```
{
 "namespace": "apps.sample_app_spl2",
 "name": "_default",
 "definition": "$a = | FROM _internal | limit 10 ;export $a;",
 "createdAt": "2023-08-03T00:17:31Z",
 "createdBy": "admin",
 "updatedAt": "2023-08-03T00:17:31Z",
 "updatedBy": "admin"
}
```

PUT

Create or update a specific module within the app context.

Request parameters

Name	Type	Default	Description
namespace	String		Required. The namespace of the module.
definition	String		Required. The definition of the module. Example: `"$a = | FROM index:terminallookup4704 GROUP BY indexed:source SELECT count();"`

Example request

JSON

```
curl -k --request POST -u admin:pass 'https://localhost:8089/services/spl2/modules/foo.bar' \
--data-raw '{
    "name": "bar",
    "namespace": "foo",
    "definition": "$a = | FROM index:terminallookup4704 GROUP BY indexed:source      SELECT count();"
}'
```

Example response See HTTP Status Codes for a list of possible responses. In addition to one of the listed responses, this endpoint might also return the following additional status code:

HTTP status code	Description

HTTP status code	Description
415	Unsupported media type. The type must be `application/json`.

DELETE

Delete a specific module within the app context.

Request parameters None.

Example request

CODE

```
curl -k -u admin:pass -X "DELETE" https://localhost:8089/services/spl2/modules/search.module.testmodule
```

Example response

JSON

```
{
    "code": "not_found",
    "message": "Module does not exist/already deleted"
}
```

See HTTP Status Codes for a list of possible responses.

services/spl2/permissions

CODE

```
https://<host>:<mport>/services/spl2/permissions
```

Access a list of role-based permissions for a module. Requires the edit_spl2_permissions capability.

POST

Update permissions for a module.

Request parameters

Name	Type	Default	Description
resourceType	String		Required. Must be either "modules" or "views".
resourceName	String	All objects	Required. Name of a specific module or view.
permissions	JSON array		Required. Array containing permissions for each type of supported operation.

Returned values

See HTTP Status Codes for a list of possible responses.

Example request

JSON

```
curl -k -u admin:pass https://localhost:8089/services/spl2/permissions \
--data '{
  "resourceType": "modules",
  "resourceName": "module1",
  "permissions": [
    {
      "operation": "read",
      "roles": [
        "admin",
        "user",
        "editor"
      ]
    },
    {
      "operation": "write",
      "roles": [
        "editor"
      ]
    }
  ]
}'
```

Example response

JSON

```
{
   "code":201
}
```

services/spl2/permissions/role/{rolename}

JSON

```
https://<host>:<mport>/services/spl2/permissions/role/{rolename}
```

Access a list of all permissions for a given role. Requires the edit_spl2_permissions capability.

GET

Get all permissions for a given role.

Request parameters

None.

Example request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/spl2/permissions/role/editor
```

Example response

JSON

```
[{
  "resourceType": "",
  "resourceName": "",
  "permissions": [
    {
      "operation": "read",
      "roles": [
        "admin",
        "user",
        "editor"
      ]
    },
    {
      "operation": "write",
      "roles": [
        "editor"
      ]
    }
  ]
}]
```

services/spl2/permissions/user/{username}

JSON

```
https://<host>:<mport>/services/spl2/permissions/user/{username}
```

Access a list of all permissions for a given user. Requires the edit_spl2_permissions capability.

GET

Get all permissions for a given user.

Request parameters

None.

Example request

CODE

```
curl -k -u admin:pass https://localhost:8089/services/spl2/permissions/user/user1
```

Example response

JSON

```
{
  "resourceType": "",
  "resourceName": "",
  "permissions": [
    {
      "operation": "read",
      "roles": [
        "admin",
        "user",
        "editor"
      ]
    },
    {
      "operation": "write",
      "roles": [
        "editor"
      ]
    }
  ]
}
```