ATADASE	CODING	I ABL	-				IAIIU	AN/ Wus
Path	Waypoint	Fly	Magnetic	Turn	Altitude	IAS	VPA/TCH	Navigation
Terminator	ID	over	Course(°)	Direction	(m)	(kt)		Specification
TF	YN512				<u>3600</u>			RNAV1
TF	YN510							RNAV1
TF	YN508							RNAV1
TF	YN505				2400	MAX205		RNAV1
			RWY13	STAR OMKAK	-8YA			
IF	OMKAK				<u>3600</u>			RNAV1
TF	YN506				2700			RNAV1
TF	YN505				2400	MAX205		RNAV1
			RWY13	STAR OMKAK	-8ZA			
IF	OMKAK				<u>3600</u>			RNAV1
TF	YN512							RNAV1
TF	YN510							RNAV1
TF	YN508							RNAV1
TF	YN505				2400	MAX205		RNAV1
			RWY13	STAR TODAM	-8YA	-1		
IF	TODAM							RNAV1
TF	YN521				<u>3600</u>			RNAV1
TF	YN520							RNAV1
TF	YN504				2100	MAX205		RNAV1
			RWY13	STAR TODAM	-8ZA		l	
IF	TODAM							RNAV1
TF	YN521				<u>3600</u>			RNAV1
TF	YN520							RNAV1
TF	YN511							RNAV1
TF	YN507				2700			RNAV1
TF	YN504				2100	MAX205		RNAV1
			L RWY31	STAR VAGBI-			<u> </u>	
IF	VAGBI							RNAV1
TF	SUGDO							RNAV1
TF	YN714				<u>3600</u>			RNAV1
TF	YN715				2700			RNAV1
TF	YN705				2100	MAX205		RNAV1
			RWY31	STAR ANPIG-		200		1
IF	ANPIG				3600			RNAV1
TF	YN711				2700			RNAV1
TF	YN708							RNAV1
TF	YN707							RNAV1
TF	YN706							RNAV1
TF	YN704				2100	MAX205		RNAV1
Changes: New cho					2100	IVIAAZUJ		IVIVAVI